



US009963011B2

(12) **United States Patent**
Wittliff, III et al.

(10) **Patent No.:** **US 9,963,011 B2**

(45) **Date of Patent:** **May 8, 2018**

(54) **PARKED VEHICLE INTERIOR LIFEFORM RECOGNITION**

(71) Applicants: **Bosch Automotive Service Solutions Inc.**, Warren, MI (US); **Robert Bosch GmbH**, Stuttgart (DE)

(72) Inventors: **William W. Wittliff, III**, Gobles, MI (US); **Jeremy L. Hargis**, Farmington, MI (US)

(73) Assignees: **Bosch Automotive Service Solutions Inc.**, Warren, MI (US); **Robert Bosch GmbH**, Stuttgart (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

(21) Appl. No.: **15/390,071**

(22) Filed: **Dec. 23, 2016**

(65) **Prior Publication Data**

US 2017/0190233 A1 Jul. 6, 2017

Related U.S. Application Data

(60) Provisional application No. 62/273,607, filed on Dec. 31, 2015.

(51) **Int. Cl.**
B60H 1/00 (2006.01)
H04W 4/12 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC **B60H 1/00742** (2013.01); **B60H 1/00778** (2013.01); **B60N 2/002** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B60H 1/00742; B60H 1/00778; B60N 2/002; G08B 21/22; G08B 21/24; H04W 4/12
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,120,527 B2 10/2006 Prieto et al.
8,996,237 B2 3/2015 Bertosa et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201819680 U * 5/2011
CN 101434221 B * 5/2012

(Continued)

OTHER PUBLICATIONS

Jung, Heejung "Modeling CO2 Concentrations in Vehicle Cabin", SAE International, Paper No. 2013-01-1497, Published Apr. 8, 2013.


Primary Examiner — Tuan C To

(74) *Attorney, Agent, or Firm* — Maginot Moore & Beck LLP

(57) **ABSTRACT**



A dongle that may be plugged into an On-Board Diagnostic (OBD) port of a vehicle and provide notification if a human or animal is left within a parked car. The dongle accesses a first sensor from the vehicle's communication system and a second sensor from within the dongle. If data from the first and second sensors exceeds predetermined threshold values programmed into the dongle's memory, then the dongle sends out a response signal. The response signal may be sent to an owner's cellular phone or to a 911 dispatch center. Additional sensors within the vehicle, or placed within the dongle, may also be used to verify the presence of a human or animal left within the parked vehicle.

20 Claims, 3 Drawing Sheets



US 9,963,011 B2

(51)	Int. Cl. <i>B60N 2/00</i> <i>G08B 21/22</i> <i>G08B 21/24</i>	(2006.01) (2006.01) (2006.01)	2015/0187146 A1* 7/2015 Chen G07C 5/008 701/31.5 2015/0274180 A1* 10/2015 Prakah-Asante B60W 40/09 701/36 2016/0086390 A1* 3/2016 Berkobin G07C 5/008 701/1
(52)	U.S. Cl. CPC	<i>G08B 21/22</i> (2013.01); <i>G08B 21/24</i> (2013.01); <i>H04W 4/12</i> (2013.01)	2016/0104328 A1* 4/2016 Chen G07O 5/0858 701/31.5 2016/0171802 A1* 6/2016 Fountain G07C 5/0866 701/31.4 2016/0177846 A1* 6/2016 Wittliff F02D 41/266 701/36 2016/0297324 A1* 10/2016 Taylor B60N 2/002
(56)	References Cited		
	U.S. PATENT DOCUMENTS		
	9,840,166 B2* 12/2017 Taylor	B60N 2/002	
	2014/0067231 A1* 3/2014 Mosher	F02D 28/00 701/102	
	2014/0297097 A1* 10/2014 Hurwitz	G07C 5/008 701/31.4	
	2015/0102900 A1* 4/2015 Ramchandani	G08C 17/02 340/5.25	
			FOREIGN PATENT DOCUMENTS
			KR 20090049492 A * 5/2009
			KR 20120056107 A * 6/2012
			* cited by examiner






FIG. 3




FIG. 4

1

PARKED VEHICLE INTERIOR LIFEFORM RECOGNITION

TECHNICAL FIELD

This disclosure relates to systems that identify a lifeform inside a vehicle interior, and more specifically a human or animal inside a parked vehicle.

BACKGROUND

On-board diagnostics (OBD) is an automotive industry term referring to a vehicle's self-diagnostic and reporting capability. OBD systems give the vehicle owner or repair technician access to the status of the various vehicle subsystems. The amount of diagnostic information available via OBD has varied widely since its introduction in the early 1980s versions of on-board vehicle computers. More recent OBD implementations use a standardized digital communications port to provide real-time data in addition to a standardized series of diagnostic trouble codes (DTCs), which allow one to rapidly identify and remedy malfunctions within the vehicle.

OBD-II is a current standard that specifies the type of diagnostic connector and its pinout, the electrical signaling protocols available, and the messaging format. It also provides a candidate list of vehicle parameters to monitor along with how to encode the data for each. There is also a pin in the connector that provides power from the vehicle battery for scan tools which are connected to the OBD-II port, which eliminates the need to connect a scan tool to a power source separately.

Modern vehicles are equipped with multiple systems and various sensors used in those systems. The modern automobile may have as many as 70 electronic control units (ECU) for various systems and subsystems. Typically the biggest processor is the engine control unit. Others are used for transmission, airbags, antilock braking/ABS, cruise control, electric power steering, audio systems, power windows, doors, mirror adjustment, battery and recharging systems for hybrid/electric cars, to name a few. Some of these systems are completely independent, but communications among others may exist.

A controller area network (CAN bus) is a vehicle bus standard designed to allow microcontrollers and devices from these various systems and subsystems to communicate with each other without a host computer. It is a message-based protocol, designed originally for multiplex electrical wiring within automobiles, but is also used in many other contexts. Development of the CAN bus started roughly in 1983 at Robert Bosch GmbH. The protocol was officially released in 1986 at the Society of Automotive Engineers (SAE) congress in Detroit, Mich.

An OBD port provides an access port to the OBD system which in turn is connected to the CAN bus and thus communication with the varying systems, subsystems, and sensors (and access to some sensor data) within a vehicle is possible.

Humans and animals may be left inside a vehicle when the vehicle is parked. This has been an issue with parked vehicles practically since the inception of the first vehicles, but even more so as vehicles started to have enclosed cabins. In 1910, Cadillac became the first company in North America to offer a passenger car with a fully enclosed cabin. Vehicles are not currently, nor have ever been, equipped with systems to identify if a human or animal is left inside a parked vehicle. Even if solutions have been developed or

2

proposed to identify humans and animals which may be left inside a parked vehicle, there is also no known solution for the already existing vehicles on the road today. The following disclosure solves this long felt need.

SUMMARY

One aspect of this disclosure is directed to a dongle for identifying if a human or animal is inside a parked car. The dongle is configured to couple with an On-Board Diagnostic (OBD) system of a parked vehicle to send a response signal if at least two matching conditions are met. The vehicle in this aspect has a first sensor in communication with the OBD system providing first sensor data to the OBD system. The dongle has a housing with a connector disposed along an edge of the housing which is configured to couple with an OBD port of the OBD system.

The dongle has a Central Processing Unit (CPU) disposed within the housing which is electrically connected to the connector. The OBD port provides power for the dongle. The CPU is programmed to couple with and access data from the OBD system when the dongle is plugged into the OBD port. The dongle also has a second sensor. The second sensor is at least partially disposed within the housing, is in communication with the CPU, and provides second sensor data to the CPU. The CPU is programmed to, upon receiving first sensor data exceeding a first sensor data threshold value and second sensor data exceeding a second sensor data threshold value, and the vehicle being in a parked state, send a response signal.

In one embodiment, the second sensor may be a carbon dioxide sensor. The second sensor data then would be carbon dioxide levels within an interior of the vehicle. The second sensor data threshold could then be set at 2500 parts per million of carbon dioxide or above.

The first sensor may be a temperature sensor. The temperature sensor may be either an interior cabin temperature sensor or an exterior temperature (ambient) sensor. The first sensor data may be a temperature level within an interior of the vehicle. The first sensor data threshold could be set at 90 degrees Fahrenheit or above.

The first sensor may also be an accelerometer, or a set of accelerometers or the like. In this embodiment, the first sensor data threshold value could be set at any level of transverse movement of the parked vehicle.

Alternatively, the first sensor may be a seat weight sensor. The first sensor data threshold value could then be set at any fluctuations in weight on a seat inside the parked vehicle.

The first sensor may be an interior cabin motion sensor. In this example, the first sensor data threshold could be set at any noted motion within the cabin.

The first sensor may also be a photo sensor having a view of an interior vehicle cabin. In this scenario, the first sensor data threshold could be any identification of a human or animal within the parked vehicle.

The dongle may also have a third sensor at least partially disposed within its housing. The third sensor may also be in communication with the CPU providing third sensor data to the CPU. In this embodiment, the CPU is programmed to withhold the response signal until the third sensor data exceeds a third sensor data threshold value providing, if available, yet another indication of a human or animal inside a parked car. The third sensor may be a noise sensor, and in such a case, the third sensor data threshold could be set at a fluctuating frequency and sound pressure level that is above 85 hertz and 80 decibels, respectively.

Alternatively, the vehicle may have a third sensor in communication with the OBD system providing third sensor data to the OBD system. In this alternative, the CPU may be programmed to withhold the response signal until receiving third sensor data which exceeds a third sensor data threshold value providing, if available, yet another indication of a human or animal inside a parked car.

The dongle may also have a transmitter disposed within the housing and electrically connected to the CPU. In the case where the dongle has a transmitter, the CPU may send the response signal to the transmitter to send a notification to a mobile electronic device. The mobile electronic device may be a cellular phone, although other mobile electronic devices are envisioned, and the response signal may result in a text notification being sent to a pre-programmed cellular number. Alternatively, the CPU may use a transmitter to send the response signal as an emergency call to a 911 dispatch center.

The dongle CPU may simply send the response signal into the OBD system to activate an air-conditioning system in the parked vehicle. Or the CPU may send the response signal into the OBD system to crack open a window of the parked vehicle. It is also envisioned that any combination of the above may also be possible.

Another aspect of this disclosure is directed to a lifeform recognition system for an interior of a parked automobile. In this aspect, the automobile has an on-board vehicle computer and at least one vehicle-based sensor providing first sensor data to the on-board vehicle computer. This system also has a dongle disposable within the interior of the parked automobile.

The dongle has a central processing unit (CPU) configured to communicate with the on-board vehicle computer of the parked automobile and access the vehicle-based sensor data. The dongle itself has at least one dongle-based sensor configured to provide second sensor data to the CPU. The CPU of the dongle is programmed to, upon receiving vehicle-based and dongle-based sensor data above a first and second sensor data threshold, respectively, send a response signal to a mobile electronic device located outside of the interior of the parked vehicle.

In this aspect, the at least one vehicle-based and dongle-based sensors are selected from a group consisting of a carbon dioxide sensor, a temperature sensor, an accelerometer, a weight sensor, a motion sensor, a photo sensor, and a noise sensor. As well, the system may have the vehicle-based and dongle-based sensor data received by the CPU to trigger a response signal be from two different kinds of sensors. The response signal may be a text message sent to an owner of the parked automobile.

The above aspects of this disclosure and other aspects will be explained in greater detail below with reference to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a partial diagrammatic view of a forward interior section of a vehicle.

FIG. 2 is a diagrammatic illustration of a dongle showing casing an embodiment.

FIG. 3 is a diagrammatic illustration of a dongle communicating with other systems.

FIG. 4 is a flowchart illustrating an example of dongle program logic.

DETAILED DESCRIPTION

The illustrated embodiments are disclosed with reference to the drawings. However, it is to be understood that the

disclosed embodiments are intended to be merely examples that may be embodied in various and alternative forms. The figures are not necessarily to scale and some features may be exaggerated or minimized to show details of particular components. The specific structural and functional details disclosed are not to be interpreted as limiting, but as a representative basis for teaching one skilled in the art how to practice the disclosed concepts.

FIG. 1 shows a partial diagrammatic view of a vehicle 10. Vehicle 10 is an automobile 10, although other vehicles are envisioned. The view is of the interior 12 of vehicle 10. Vehicle 10 has an On-Board Diagnostic (OBD) system 14. The OBD system 14 has an OBD port 16 which provides for diagnostic equipment to access the OBD system 14. The OBD port 16 shown here resembles that of an OBD-II port although other communication ports may be used. The OBD system is connected to various systems and subsystems 18a, 18b, 18c and their respective sensors 20a, 20b, 20c, 20d, 20e, 20f by a vehicle communication system 22. Sensors 20a, 20b, 20c, 20d, 20e, 20f may also be referred to as vehicle sensors 20a, 20b, 20c, 20d, 20e, 20f. The vehicle communication system 22 may be a controller area network (CAN bus).

Sensor 20a may be a first sensor 20a. First sensor 20a is in communication with the OBD system 14. First sensor 20a provides first sensor data to the OBD system 14. First sensor 20a may be an interior cabin temperature sensor 20a, or equivalent thereof. The first sensor data may be that of a temperature level within the interior 12 of the vehicle 10 while the vehicle is parked. The interior cabin sensor 20a may be part of a system 18a. System 18a may be a climate control system 30 within the vehicle.

Alternately, sensor 20b may be a first sensor 20b. First sensor 20b is in communication with the OBD system 14. First sensor 20b provides first sensor data to the OBD system 14. First sensor 20b may be an exterior cabin (ambient) temperature sensor 20b (or a system with ability to access the data, such as from a local cellular network publishing such data). The exterior cabin sensor 20b may be used to approximate internal cabin temperature. Internal cabin temperature may be approximated using the ambient temperature after the vehicle 10 has been keyed off and parked for a period of time. The exterior cabin sensor 20b may be part of a system 18a. System 18a may be an infotainment system 32 within the vehicle.

Alternatively, sensor 20c may be a first sensor 20c. First sensor 20c is in communication with the OBD system 14. First sensor 20c provides first sensor data to the OBD system 14. First sensor 20c may be an accelerometer 20c, set of accelerometers 20c, or equivalents thereof. The first sensor data may be that of movement of the vehicle 10, specifically transverse or lateral movement of the vehicle 10 while parked. The accelerometer 20c may be part of a system 18b. System 18b may be a stability control system 34 (see FIG. 3) within the vehicle 10. Accelerometer 20c may be a roll sensor 20c, and the lateral accelerations noted may be that of roll fluctuations caused by movement inside the vehicle and the suspension of the vehicle 10 reacting to the movement.

Alternatively, sensor 20d may be a first sensor 20d. First sensor 20d is in communication with the OBD system 14. First sensor 20d provides first sensor data to the OBD system 14. First sensor 20d may be a seat weight sensor 20d, or equivalent thereof. The first sensor data may be that of weight on a seat, specifically fluctuations in weight that may occur from a human or animal within the vehicle moving from seat to seat while the vehicle 10 is parked. The seat

5

weight sensor **20d** may be part of a system **18b**. System **18b** may be an airbag system **36** within the vehicle **10**.

Alternatively, sensor **20e** may be a first sensor **20e**. First sensor **20e** is in communication with the OBD system **14**. First sensor **20e** provides first sensor data to the OBD system **14**. First sensor **20e** may be an interior cabin motion sensor **20e**. The first sensor data may be that of motion within the vehicle **10**, specifically movement that may occur after the vehicle has been parked and possibly after a period of time. The interior cabin motion sensor **20e** may be part of a system **18c**. System **18c** may be a vehicle security system **38** within the vehicle **10**.

Alternatively, sensor **20f** may be a first sensor **20f**. First sensor **20f** is in communication with the OBD system **14**. First sensor **20f** provides first sensor data to the OBD system **14**. First sensor **20f** may be a photo sensor **20f** having a view of an interior vehicle cabin. The first sensor data may be that of motion within the vehicle **10**, or identification of a human or animal within the vehicle **10**. The photo sensor **20f** may utilize comparative technology of a first picture of the interior **12** with no occupant to that of a second picture of the interior **12** with that of an occupant. This comparison may also be iterative to identify motion of an occupant as opposed to a stationary object within the interior. The photo sensor **20f** may also be used in combination with facial character recognition software to identify a human or animal within the interior **12** of the vehicle **10**. The photo sensor **20f** may be part of a system **18c**.

A second vehicle sensor **30**, third vehicle sensor **32**, fourth vehicle sensor **34**, fifth vehicle sensor **36**, or sixth vehicle sensor **38** may also be located on the vehicle **10** and in communication with the OBD system **14**. The sensors **30**, **32**, **34**, **36**, **38** may be any combination of the above examples of a first sensor **20a**, **20b**, **20c**, **20d**, **20e**, **20f**.

Additional data may be available on the vehicle communication system **22** such as ignition status, such as the position of an ignition switch **40**. Or transmission status, such as the position of a gear selector lever **42**, or its equivalent. The vehicle communication system **22** may also contain data on whether an engine (or electric motor) is running (on), whether the vehicle heating or cooling system is on or available to be turned on, if the vehicle is moving, stopped, or parked, for how long the vehicle has been moving, stopped, or parked, and possibly, if global positioning system is available, the location of the vehicle **10**.

FIG. 2 shows an example of dongle **50**. Dongle **50** is configured to couple with an On-Board Diagnostic (OBD) system **14** (see FIG. 1) of vehicle **10**. Dongle **50** has a housing **52**. Dongle **50** has an edge **54** and a connector **56** disposed along the edge **54** of the housing **52**. Connector **56** is configured to couple with the OBD port **16** (see FIG. 1).

Dongle **50** has a Central Processing Unit (CPU) **60** disposed within the housing **52**. The CPU **60** is electrically connected to the connector **56**. The CPU **60** is programmed to couple with and access data from the OBD system **14** (see FIG. 1). The dongle **50** may also have a memory **62** disposed within the housing **52**. The CPU **60** is electrically connected to the memory **62**. Memory **62** may store first sensor data.

A second sensor **64** is at least partially disposed within the housing **52**. The second sensor **64** may also be referred to as a dongle sensor **64** or a first dongle sensor **64**. The second sensor **64** is in communication with the CPU **60**. The second sensor **64** provides second sensor data to the CPU **60**.

The second sensor **64** may be a carbon dioxide sensor **64**. The second sensor data provided by the carbon dioxide sensor may be carbon dioxide levels within an interior **12** of the vehicle **10** (see FIG. 1). Alternatively, the second sensor

6

64 may be a noise sensor **64**. The second sensor data provided by the noise sensor **64** may be sound frequency and sound pressure level (or intensity).

A second dongle sensor **66**, third dongle sensor **68**, fourth dongle sensor **70**, fifth dongle sensor **72**, sixth dongle sensor **74**, or seventh dongle sensor **76** may also be located within or on the dongle **50** and in communication with the CPU **60**. The additional dongle sensors **66**, **68**, **70**, **72**, **74**, **76** may be any combination of the above two examples of a second sensor **64** or any first sensor **20a**, **20b**, **20c**, **20d**, **20e**, **20f**.

The dongle **50** may also be equipped with a transmitter **78**. The transmitter **78** is at least partially disposed within the housing **52** and is electrically connected to the CPU **60**. Transmitter **78** may be a transceiver **78**, and thus also be capable of receiving signals as well as sending them. Transmitter **78** may be configured to send radio frequency signals, infrared frequency signals, cellular phone signals, signals interceptable by satellite communication systems, signals compatible with Bluetooth® devices, signals compatible with Wi-Fi® devices, or other known form of wireless communication signals. The transmitter **78** may be used to send a response signal (upon instruction from the CPU **60**) as a notification to another location. The CPU **60** may instruct the transmitter **78** to send a response signal based on receiving first and second signal data each being above a threshold value.

The memory **62** may store first sensor data threshold values and second sensor data threshold values. The first sensor data threshold for use with an interior cabin temperature sensor **20a** (see FIG. 1) could be set at 90 degrees Fahrenheit and above. The first sensor data threshold for use with an interior cabin temperature sensor **20a** (see FIG. 1) may also be set at 40 degrees Fahrenheit and below. The first sensor data threshold value for use with an exterior cabin temperature sensor **20b** (see FIG. 1) may be set at 80 degrees Fahrenheit and above along with an indication of the vehicle cooling system being off (vehicle key-off) for 30 minutes or longer. The first sensor data threshold value for use with an exterior cabin temperature sensor **20b** (see FIG. 1) may be set at 32 degrees Fahrenheit and below along with an indication of the vehicle heating system being off (vehicle key-off) for 30 minutes or longer.

The first sensor data threshold value for use with an accelerometer **20c** (see FIG. 1) could be set at any notable transverse/lateral movement of the parked vehicle (roll of the vehicle). The first sensor data threshold value for a seat weight sensor **20d** (see FIG. 1) could be set at any fluctuations in weight on a seat inside the parked vehicle, or changes in weight from one seat to another indicating a human or animal moving from seat to seat within the interior.

The first sensor data threshold used with an interior cabin motion sensor **20e** (see FIG. 1) could be any motion within the cabin of the vehicle. The first sensor data threshold used in conjunction with a photo sensor **20f** (see FIG. 1) could be any identification of a human or animal within the parked vehicle.

The second sensor data threshold used in conjunction with a carbon dioxide sensor **64** could be set at 2500 parts per million of carbon dioxide. The second sensor data threshold used with a noise sensor **64** could be set at is a fluctuating frequency above 85 hertz and sound pressure level of 80 decibels or greater.

FIG. 3 shows a dongle **50** communicating with the vehicle **10** via communication line **90a** communicating with other systems via communication lines **90b**, **90c**, **90d**, **90e**. The dongle **50** has a CPU **60** programmed to, upon receiving data

from a second sensor **64** and from a first sensor **20a**, **20b**, **20c**, **20d**, **20e**, **20f**; each respectively exceeding a second sensor data threshold value and a first sensor data threshold value, as saved in the memory **62**, and the vehicle being noted to be in a parked state, send a response signal **92** via one or more of the communication lines **90a**, **90b**, **90c**, **90d**, **90e**.

In one example where the interior cabin temperature sensor **20a** provides data exceeding the upper interior temperature threshold value, the response signal **92** is sent to the vehicle communication system **22** via communication line **90a** to activate an air-conditioning system **30** in the parked vehicle **10**. This response signal **92** may also include the automatic starting of a prime mover **93** (such as an engine or electric motor) In this example, the response signal **92** may be sent by the transmitter **92** wirelessly or sent back through the connection the dongle has at the OBD port **16** (see FIG. **1**). The response signal **92** may also be sent to the vehicle communication system **22** via communication line **90a** to automatically lower a power window **94** of the parked vehicle **10**. Conversely, where the interior cabin temperature sensor **20a** provides data lower than the lower interior temperature threshold value, the response signal **92** is sent to the vehicle communication system **22** via communication line **90a** to activate a heating system **30** in the parked vehicle **10**.

In yet another example, the response signal **92** is sent to a pre-programmed cellular number via communication lines **90c** or **90d**. The transmitter **92** wirelessly communicates with satellite communication systems **94** via communication line **90c** and wirelessly communicates with cellular towers **96** via communication lines **90d**. The response signal **92** in these two example may be in the form of a text notification being sent to a pre-programmed cellular number.

In yet even another example, the response signal **92** is sent to a mobile device **98** directly via communication line **90e**. Communication line **90e** may be such that the transmitter **78** sends a signal **92** that is compatible with Bluetooth® or Wi-Fi® enabled devices. Mobile device **98** may be a cellular phone **98**.

In a further example the response signal **92** may be sent directly to a 911 dispatch center **99** as an emergency notification. In this example, as with any of the rest, a GPS locator may also be sent along with the response signal **92**. The GPS locator may be a further sensor within the dongle **50** or from a system in the vehicle **10**.

The CPU **60** of the dongle **50** may also be programmed to withhold the response signal **92** until a third sensor provides data exceeding a third sensor data threshold value. Thusly, the system may use a single vehicle sensor in combination with a single dongle sensor, or the system may utilize additional vehicle and dongle sensors to verify occupancy of a human or animal with the vehicle. In the scenario of utilizing a third (or any number of additional sensors that may be available), the CPU **60** of the dongle would verify if the sensor provides data above a predetermined threshold value (as saved in the memory **62** and provided as examples above) and thusly sends a response signal **92** to notify someone of a human or animal being left inside a parked vehicle **10**.

The CPU **60** may also verify how many sensors are available in the vehicle **10**, or as outfitted in the dongle **50** itself, and add additional verifications based on the programming logic saved in the memory **62** of the dongle **50**. The programming logic may include information such as whether the engine is running or how long the vehicle has been in park.

FIG. **4** shows an example of dongle program logic. At step **100**, the program logic is started. At decision diamond **102**, the program logic may verify if the vehicle is parked. This may occur once a vehicle is keyed off (turned off), once a vehicle is placed in park (such as a transmission or transmission selector level or switch being physically placed in park), or the vehicle simply not moving for a period of time. If the vehicle is not parked, then the logic flow returns to start **100**. If the vehicle is parked, the logic flow may continue.

At step **104**, the dongle may query the vehicle communication system to gather the interior cabin temperature. If the temperature is lower than a threshold temperature value, then the logic flow may return to start. If the temperature is above the threshold temperature value, then the logic flow may progress. At step **106**, the dongle may provide whether the carbon dioxide level in the interior cabin is above a threshold CO2 value. If there is no noted CO2 in the cabin, then the logic flow would return to start **100**. If there is CO2 above the threshold value, then the logic flow would continue. Steps **104** and **106** could occur in any order.

At step **108**, the dongle may query as to whether there is yet another sensor that could be used to aid in the positive identification of a human or animal left inside the parked vehicle. If there is not a third sensor, and the previous two threshold values have been exceeded, then the dongle would send a response signal at decision block **110**. The response signal may be that of a text to an owner's cellular phone.

If there are additional sensors, the dongle may proceed to decision block **112** to determine which sensor is, or how many sensors are, available. Upon determining the additional sensor, the logic flow at step **114** determines if the data from the additional sensor is above or below a threshold value for the additional sensor. If it is below, the logic flow returns to start **100**. If the data is above the threshold value, then the logic flow continues on the response signal **110**. The system may also be programmed to send a first response signal via one channel, such as to an owner's cell phone only based on two sensors information. After a period of time, or if additional sensors begin exceeding threshold values, the dongle may then send the response signal to a 911 dispatch.

While exemplary embodiments are described above, it is not intended that these embodiments describe all possible forms of the disclosed apparatus and method. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the disclosure as claimed. The features of various implementing embodiments may be combined to form further embodiments of the disclosed concepts.

What is claimed is:

1. A dongle configured to couple with an On-Board Diagnostic (OBD) system of a parked vehicle, the vehicle having a first sensor in communication with the OBD system providing first sensor data to the OBD system, the dongle comprising:

- a housing;
- a connector disposed along an edge of the housing, the connector configured to couple with an OBD port of an OBD system;
- a Central Processing Unit (CPU) disposed within the housing and electrically connected to the connector, the CPU programmed to couple with and access data from the OBD system; and
- a second sensor at least partially disposed within the housing and in communication with the CPU providing second sensor data to the CPU, wherein the CPU is

programmed to, upon receiving second sensor data and first sensor data each respectively exceeding a second sensor data threshold value and a first sensor data threshold value, and the vehicle being in a parked state, send a response signal indicating the presence of a human or animal inside the parked vehicle.

2. The dongle of claim 1, wherein the second sensor is a carbon dioxide sensor and the second sensor data is carbon dioxide levels within an interior of the vehicle.

3. The dongle of claim 2, wherein the second sensor data threshold is 2500 parts per million of carbon dioxide or above.

4. The dongle of claim 1, wherein the first sensor is an interior cabin temperature sensor and the first sensor data is temperature level within an interior of the vehicle.

5. The dongle of claim 4, wherein the first sensor data threshold is 90 degrees Fahrenheit or above.

6. The dongle of claim 1, wherein the first sensor is at least one accelerometer and the first sensor data threshold value is transverse movement of the parked vehicle.

7. The dongle of claim 1, wherein the first sensor is a seat weight sensor and the first sensor data threshold value is fluctuations in weight on a seat inside the parked vehicle.

8. The dongle of claim 1, wherein the first sensor is an interior cabin motion sensor and the first sensor data threshold is motion within the cabin.

9. The dongle of claim 1, wherein the first sensor is a photo sensor having a view of an interior vehicle cabin and the first sensor data threshold is identification of a human or animal within the parked vehicle.

10. The dongle of claim 1, further comprising a third sensor at least partially disposed within the housing and in communication with the CPU providing third sensor data to the CPU, wherein the CPU is programmed to withhold the response signal until the third sensor data exceeds a third sensor data threshold value.

11. The dongle of claim 10, wherein the third sensor is a noise sensor and the third sensor data threshold is a fluctuating frequency above 85 hertz and 80 decibels.

12. The dongle of claim 1, wherein the vehicle has a third sensor in communication with the OBD system providing third sensor data to the OBD system, and the CPU is programmed to withhold the response signal until receiving third sensor data which exceeds a third sensor data threshold value.

13. The dongle of claim 1, further comprising a transmitter disposed within the housing and electrically connected to the CPU, and wherein the CPU sends the response signal to the transmitter to send a notification to a mobile electronic device.

14. The dongle of claim 13, wherein the mobile electronic device is a cellular phone and the response signal results in a text notification being sent to a pre-programmed cellular number.

15. The dongle of claim 1, further comprising a transmitter disposed within the housing and electrically connected to the CPU, and wherein the CPU sends the response signal as an emergency call to a 911 dispatch center.

16. The dongle of claim 1, wherein the response signal is sent into the OBD system to activate an air-conditioning system in the parked vehicle.

17. The dongle of claim 1, wherein the response signal is sent into the OBD system to crack open a window of the parked vehicle.

18. A lifeform recognition system for an interior of a parked automobile, the automobile having an on-board vehicle computer and at least one vehicle-based sensor providing vehicle-based sensor data to the on-board vehicle computer, the system comprising:

a dongle disposable within an interior of a parked automobile, the dongle having a central processing unit (CPU) configured to communicate with an on-board vehicle computer of the parked automobile and access the vehicle-based sensor data, the dongle having at least one dongle-based sensor configured to provide dongle-based sensor data to the CPU, and the CPU programmed to, upon receiving vehicle-based and dongle-based sensor data above a first and second sensor data threshold, respectively, send a response signal to a mobile electronic device located outside of the interior of the parked vehicle.

19. The system of claim 18, wherein the at least one vehicle-based and dongle-based sensors are selected from a group consisting of a carbon dioxide sensor, a temperature sensor, an accelerometer, a weight sensor, a motion sensor, a photo sensor, and a noise sensor, and the vehicle-based and dongle-based sensor data received by the CPU to trigger a response signal are from two different kinds of sensors.

20. The system of claim 19, where in the response signal is a text message sent to an owner of the parked automobile.

* * * * *