

1 573 099

(21) Application No. 53221/75  
 (23) Complete Specification filed 15 Dec 1976  
 (44) Complete Specification published 13 Aug 1980  
 (51) (51) INT.CL<sup>3</sup> B30B 9/06  
 B01D 25/12  
 (52) Index at Acceptance B5A 1R102 1R137 1R214F T13P  
 D2A 7B10 7C  
 (72) Inventor: Robert Graham



(54) IMPROVEMENTS IN AND RELATING TO APPARATUS FOR THE MANUFACTURE OF INSULATING PRODUCTS.

(71) We, NEWALLS INSULATION COMPANY LIMITED a company organised under the laws of Great Britain, 26 St Mary's Parsonage, Manchester M3 2NL formerly of 5 77 Fountain Street, Manchester M2 2EA, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the 10 following statement:—

The present invention relates to a filter press which may be used in the manufacture of sheet or slab form insulation products from relatively free flowing slurries, for 15 example containing calcium silicate and/or fibres. Our copending application No. 23886/79 (Serial Number 1573100) is directed to method of making such products, particularly by means of the press of this invention.

20 Such products may be made by paper and/or board making techniques, they may also be made by filter pressing in which a measured column of slurry is poured into a foraminous mould cavity and then de-watered by pressing.

25 Conventional platen presses can be used for this, but uneven pressure distribution and fluid leakage around the edges of the press platen tend to give a product of irregular thickness and density.

30 It is an object of the present invention to provide an improved filter press for manufacturing such sheet or slab form insulation products.

According to the present invention, a 35 filter press includes a plurality of movable platen portions disposed side-by-side lengthwise of the press, each portion having individual actuating means which are adjustable relative to one another and controlled by a common drive means arranged and adopted to move all 40 of said platen portions substantially simul-

taneously as a single platen together with means defining with said single platen a mould cavity, said means comprising sidewall members movable into the periphery of said single platen<sup>45</sup> and an endless filter band so disposed as to constitute a face of the mould cavity directly opposed to said single platen.

Preferably, one sidewall member is also moveable in a direction away from the filter band so as to enable advancement of the filter band to carry a product out of the mould cavity. The filter band may be arranged to discharge the product onto a conveyor belt provided with length/width trimming apparatus<sup>55</sup> for the product.

The platen portions are arranged side-by-side lengthwise of the press, each platen portion advantageously having a length substantially equal to the width of the product to be made, 60 the length of the press being its dimension in the direction of travel of the endless filter band. The individual actuating means may be screw jacks driven by a common drive shaft, to ensure that once the jacks have been adjusted<sup>65</sup> to produce a product of uniform thickness, this setting will be accurately repeated for each succeeding product. Preferably at least four jacks are provided for each platen portion.

The use of screw jacks and a common drive<sup>70</sup> shaft has the added advantage that the platen portions can be stopped at any point in their range of movement, without the need for fixed limit stops, as in a conventional platen press. It follows that all of the available pressure is applied to the product and not directly to the hardware of the press, thus allowing preselection of the finished product thickness.

Furthermore, the density of the product<sup>80</sup> can also be controlled by adjusting the position of the platen portions prior to pumping the

slurry into the mould cavity.

It should be noted that having made one sheet or slab, the platen portions can be raised to create a new mould cavity on top of the first sheet or slab. A second sheet or slab can then be made on top of the first, using the same or a different slurry. It is thus possible to form laminated products wherein each layer is of different density and/or composition to the next layer.

The problem of leakage around the platen of a conventional platen press can be minimized by making the platen a close fit within the walls of the mould cavity. The latter may be simply a rectangular frame constituting the bottom wall and the platen constituting the top wall of the cavity. The bottom wall, that is the press bed, may be a filter cloth stretched over an apertured backing plate and the filter cloth may be in the form of an endless band or it may be static, but in either case removal of the product after pressing can be effected by raising the press platen clear of the cavity side walls prior to sliding the mould cavity out of the press.

Where the mould cavity is in the form of a rectangular frame the method of the invention preferably therefore includes the additional step of opening the press at least sufficiently to enable the mould cavity to be withdrawn and/or inserted into the press, as appropriate. It should be noted in this context that the slurry is most conveniently supplied to the mould cavity through a supply aperture in the side walls of the cavity.

In order that the invention be better understood, a preferred embodiment of it will now be described by way of example with reference to the drawings accompanying the Provisional specification in which:-

Figure 1 is an end view, partially in section, through a platen press according to the invention, the section being taken in a plane normal to the direction of travel of the filter band and, Figure 2 is a side view of the press of Figure 1.

For convenience, like reference numerals will be applied to like parts in both figures.

In the figures, the press comprises a fixed bed 3, supporting pillars which extend above the bed and carry other parts of the press. Mounted on the bed 3, an apertured staging 5 supports an endless filter cloth 6 mounted for circulation around end/drive rollers 7, shown only in outline in Figure 2. Purely to illustrate the operation of the press, in Figure 1 a single platen portion has been "split" along the centre line of the press into two parts, one part 8 is shown in an "up" or open position whilst the other part 9 is in a "fill position", as will be described later. Each platen portion is connected to four screw jacks, 10, 11, and, through the body of geared drives 12, 13 for the jacks, to a fixed cross bar 14, which is carried by the pillars 4. The geared drives 12, 13 are linked by drive shafts 15 to line shafts 16 which extend lengthwide of the press (i.e. normal to the plane of figure 1 and parallel to the plane of Figure 2), right angle drive boxes 17 being provided on each side of the press. In the press shown in Figure 2 there are two platen portions along the length of the press, each being similar and driven by the line shafts 16 in exactly the same way, a common drive motor (not shown) being provided at one end of the machine to rotate both line shafts through exactly the same angular distance, as required to operate the press and as will be discussed later. It will be appreciated that the press may be lengthened by simply providing further platen portions of the same kind.

The downwardly-facing surfaces of each platen portion are covered by filter cloth (not shown) and the portions themselves are provided with apertures, so that in use fluid expressed from the mould cavity below can escape into the troughs 8A, 9A defined between the upstanding walls of the platen portions.

Still referring to Figure 1, at each side of the press, there is a sidewall constituted by a plate 18 connected by struts 19 to a hinge member 20, which is pivoted to the pillar 4. The free end of the hinge member is connected through a toggle mechanism 21 comprising two linkages 22, and 23, the latter pivotably connected to the pillar 4 and the former pivotably connected to the hinge member 20. The connection between the linkages is itself pivotably connected through a follower 24, and a lever 25 to a pneumatic cylinder 26. Both sides of the press are identical in this respect, but for convenience, the left-hand side sidewall, in Figure 1 is shown in the "closed" position whilst the right-hand sidewall is in the "open position", although in normal operation, this would not be the case and both sidewalls would be either open or closed.

Referring now to Figure 2, at each end of the press, there is a further sidewall 27, the right-hand one being shown "closed" and the left-hand one "open". The sidewalls 27 are mounted for sliding movement along guides 28 which cause them to follow a path away from the filter band and the platen portions. Pneumatic cylinders 29 operate each of the sidewalls 27 through a lever arrangement and linkage, generally indicated at 30.

The operation of the press in carrying out a preferred embodiment of the method of the invention will now be described briefly with reference to the Figures.

Initially, the filter band is stationary, all of the sidewalls 18 and 27 are in the "closed" position and the screwjacks have been operated to put the platen portions into the "fill" position of Figure 1. An aqueous slurry containing calcium silicated and/or fibre is then pumped into the mould cavity defined between the side walls, the platen portions and the filter band, using a flexible pipe 31 (Figure 1)

connected to an aperture in the left-hand side-wall 18. The slurry is pumped into the cavity until the back pressure due to the accumulation of solids in the cavity 32 is approximately equal to the pumping pressure and the rate of inflow of slurry decreases to zero, or nearly zero.	1. A filter press including a plurality of movable platen portions disposed side-by-side lengthwise of the press, each portion having individual actuating means which are adjustable relative to one another and controlled by a common drive means arranged and adapted to move all of said platen portions substantially simultaneously as a single platen together with means defining with said single platen a mould cavity, said means comprising sidewall members movable into the periphery of said single platen and an endless filter band so disposed as to constitute a face of the mould cavity directly opposed to said single platen.	60
When the back pressure and pumping pressure reach equilibrium, a condition assessed by monitoring the rate of inflow, (or the rate of fluid escape from the cavity) the supply is cut-off and the screwjacks are operated to move both the platen portions downwardly to reduce the vertical dimension of the cavity to the desired product thickness whilst at the same time de-watering the material in the cavity. After allowing time for drainage of the expressed fluid, the platen portions can be retracted to the "open" position, together with the sidewalls. The filter band can then be moved in the direction indicated by an arrow in Figure 2 to displace the product 33 clear of the press and on to further processing, e.g. trimming and oven drying. The cycle can then be repeated.	2. A filter press according to Claim 2 wherein one sidewall member is also moveable in a direction away from the filter band so as to enable advancement of the filter band through the press to carry a product out of the mould cavity.	65
Because the platen portions are individually operated each by four jacks and adjustable relative to one another the products made on a platen press of the kind just described can have greatly improved regularity, in particular as regards their thickness and overall flatness. Any tendency for the pressing operation to produce an uneven thickness and/or slight curvatures requiring smoothing treatments such as the pressure is inherently distributed evenly over the whole platen area, the frame of the press need not be as massive as would be required in a single hydraulic ram press of the conventional kind. as many platen portions as are required to make a given product length may be used. Drainage of the expressed fluid from the troughs 8A, 9A formed by the platen portions can be augmented by mounting the press with one end slightly higher than the opposite end, thereby enabling the fluid to be readily removed by gravity, although the exact amount of tilt will depend on the volume of fluid to be removed, the latter being, of course, related to the nature of the slurry as well as to the size/thickness/density of the product.	3. A filter press according to Claim 3 wherein the filter band is arranged to discharge the product onto a conveyer belt provided the length and/or width trimming apparatus for the product.	70
The rate of drainage can also be increased by pumping the expressed fluid from the troughs 8A and 8B. This is useful when a second sheet or slab is made on top of another slab, because a major part of the fluid will have to escape upwards into these troughs, the first-formed sheet of slab being relatively impermeable.	4. A filter press according to any of Claims 2 to 4 wherein the platen portions are disposed side-by-side lengthwise of the press, each portion having a length substantially equal to the width of the product to be made.	80
WHAT WE CLAIM IS:-	5. A filter press according to any preceding claim wherein the individual actuating means are screw jacks operated by a common drive shaft.	85
	6. A filter press according to Claim 5 in which the actuating means for each platen portion is at least four screw jacks.	90
	7. A filter press according to any preceding claim wherein the platen portions are at least in part permeable to fluid and the faces of the portions remote from the filter band include drainage channels for fluid expressed through said permeable parts.	95
	8. A filter press according to Claim 8 wherein said drainage channels extend lengthwise of the press and wherein said channels slope at an angle to the horizontal so that expressed fluid tends to drain from the channels to one end of the press under gravity.	100
	9. A filter press substantially as hereinbefore described with reference to and as illustrated by the drawings accompanying the provisional specification.	105
	10. Sheet or slab form insulation products made by the press of any preceding claim.	110
	B.D.P. WETTERS Chartered Patent Agents Agent for the Applicants.	115

FIG. 1



