(19) Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) EP 0 568 272 B1

(12) EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
10.07.1996 Bulletin 1996/28

(51) Int. Cl.[6]: **B41J 2/17**

(21) Application number: **93303155.1**

(22) Date of filing: **22.04.1993**

(54) Preheat roller for thermal ink-jet printer

Vorheizwalze für einen thermischen Tintenstrahldrucker

Rouleau de préchauffage pour imprimante à jet d'encre

(84) Designated Contracting States:
DE ES FR GB IT

(30) Priority: **01.05.1992 US 878186**

(43) Date of publication of application:
03.11.1993 Bulletin 1993/44

(73) Proprietor: **Hewlett-Packard Company**
Palo Alto, California 94304 (US)

(72) Inventors:
- **Medin, Todd R.**
  Escondido, CA 92027 (US)
- **Becker, Richard A.**
  San Diego, CA 92128 (US)
- **Richtsmeier, Brent W.**
  San Diego, CA 92120 (US)

(74) Representative: **Powell, Stephen David et al**
WILLIAMS, POWELL & ASSOCIATES
34 Tavistock Street
London WC2E 7PB (GB)

(56) References cited:
EP-A- 0 373 922
DE-A- 3 417 376
DE-A- 3 642 204

- **PATENT ABSTRACTS OF JAPAN vol. 15, no. 333 (M-1150)23 August 1991 & JP-A-31 26 561 (FUJITSU LTD) 29 May 1991**
- **Derwent Publications Ltd., London, GB; AN 92-364955 & US-A-5 154 014 (GROY; SPICKARD)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 568 272 B1

Printed by Rank Xerox (UK) Business Services
2.12.4/3.4

Description

The present invention relates to the field of computer ink-jet printers.

With the advent of computers came the need for devices which could produce the results of computer generated work product in a printed form. Early devices used for this purpose were simple modifications of the then current electric typewriter technology. But these devices could not produce picture graphics, nor could they produce multicolored images, nor could they print as rapidly as was desired.

Numerous advances have been made in the field. Notable among these has been the development of the impact dot matrix printer. While that type of printer is still widely used, it is neither as fast nor as durable as required in many applications. Nor can it easily produce high definition color printouts. The development of the thermal ink-jet printer has solved many of these problems. U.S. Patent No. 4,728,963, issued to S.O. Rasmussen et al., and assigned to the same assignee as is this application, describes an example of this type of printer technology.

Thermal ink-jet printers operate by employing a plurality of resistor elements to expel droplets of ink through an associated plurality of nozzles. In particular, each resistor element, which is typically a pad of resistive material about 50µm by 50µm in size, is located in a chamber filled with ink supplied from an ink reservoir comprising an ink-jet cartridge. A nozzle plate, comprising a plurality of nozzles, or openings, with each nozzle associated with a resistor element, defines a part of the chamber. Upon the energizing of a particular resistor element, a droplet of ink is expelled by droplet vaporization through the nozzle toward the print medium, whether paper, fabric, or the like. The firing of ink droplets is typically under the control of a microprocessor, the signals of which are conveyed by electrical traces to the resistor elements.

The ink cartridge containing the nozzles is moved repeatedly across the width of the medium to be printed upon. At each of a designated number of increments of this movement across the medium, each of the nozzles is caused either to eject ink or to refrain from ejecting ink according to the program output of the controlling microprocessor. Each completed movement across the medium can print a swath approximately as wide as the number of nozzles arranged in a column on the ink cartridge multiplied times the distance between nozzle centers. After each such completed movement or swath, the medium is moved forward the width of the swath, and the ink cartridge begins the next swath. By proper selection and timing of the signals, the desired print is obtained on the medium.

In order to obtain multicolored printing, a plurality of ink-jet cartridges, each having a chamber holding a different color of ink from the other cartridges, may be supported on the printhead.

Current ink-jet technology printers are not able to print high density plots on plain paper without suffering two major drawbacks: the saturated media is transformed into an unacceptably wavy or cockled sheet; and adjacent colors tend to run or bleed into one another. The ink used in thermal ink-jet printing is of liquid base. When the liquid ink is deposited on wood-based papers, it absorbs into the cellulose fibers and causes the fibers to swell. As the cellulose fibers swell, they generate localized expansions, which, in turn, causes the paper to warp uncontrollably in these regions. This phenomenon is called paper cockle. This can cause a degradation of print quality due to uncontrolled pen-to-paper spacing, and can also cause the printed output to have a low quality appearance due to the wrinkled paper.

Hardware solutions to these problems have been attempted. Heating elements have been used to dry the ink rapidly after it is printed. But this has helped only to reduce smearing that occurs after printing. Prior art heating elements have not been effective to reduce the problems of ink migration that occur during printing and in the first few fractions of a second after printing.

Other types of printer technology have been developed to produce high definition print at high speed, but these are much more expensive to construct and to operate, and thus they are priced out of the range of most applications in which thermal ink-jet printers may be utilized.

The user who is unwilling to accept the poor quality must either print at a painfully slow speed or use a specially coated medium which costs Substantially more than plain paper or plain medium. Under certain conditions, satisfactory print quality can be achieved at print resolutions on the order of 180 dots per inch. However, the problems such as ink bleeding are exacerbated by higher print. In particular, it has heretofore not been possible to achieve acceptable color printing or throughput on plain paper medium at 180 dots per inch.

Using thermal transfer printer technology, good quality high density plots can be achieved at somewhat reduced speeds. Unfortunately, due to their complexity, these printers cost roughly two to three times as much as thermal ink-jet types. Another drawback of thermal transfer is inflexibility. Ink or dye is supplied on film which is thermally transferred to the print medium. Currently, one sheet of film is used for each print regardless of the density. This makes the cost per page unnecessarily high for lower density plots. The problem is compounded when multiple colors are used.

Document DE-A-3642204 discloses various ink-jet printers with heating arrangements which heat the drive roller before printing. The contents of this document correspond generally to the preamble of claim 1.

The present invention seeks to provide a color ink-jet printer which prints color images on plain paper which are comparable in quality to color images printed on special papers.

The present invention further seeks to provide a plain paper color ink-jet printer characterised by high throughput and reliable, quiet operation.

According to the present invention, there is provided an ink-jet printer for printing into a print medium, including a printhead for printing on a print medium, said printhead comprising a plurality of ink-jet nozzles disposed above a print zone for ejecting jets of ink onto the surface of said medium in a controlled fashion, means for advancing the print medium via a medium path to said print zone during print operations, said advancing means comprising a drive roller for engaging said medium, wherein said medium path comprises a path about a portion of an external circumferential surface of said drive roller, wherein said medium is wrapped about said portion of said external surface of said roller in the course of advancement of said medium to said print zone and preheat means for preheating said print medium before said medium reaches said print zone, said preheat means comprising means for heating said roller external surface, characterised in that print heater means is provided which is independently - operable of said preheat means, and in that control means is provided which actuates said preheat means when the printer is switched on and which actuates said print heater means after actuation of said preheat means but before print operations by said printhead.

These and other features and advantages of the present invention will become more apparent from the following detailed description of an exemplary embodiment thereof, as illustrated in the accompanying drawings, in which:

FIG. 1 is a simplified schematic diagram illustrative of a color ink-jet printer embodying the present invention.

FIG. 2 illustrates the warm-up algorithm for the heated drive roller of the printer of FIG. 1.

FIG. 3 illustrates the preheat algorithm for the print heater element of the printer of FIG. 1.

FIG. 4 illustrates the fan speed algorithm for the crossflow fan of the printer of FIG. 1.

FIGS. 5A and 5B illustrate the control sequence for the printer of FIG. 1.

FIG. 6 is a partially-exploded perspective view showing various elements of the printer of FIG. 1, including the heated drive roller, print heater element and screen.

FIG. 7 is a top view of the heater screen of the printer of FIG. 1.

FIG. 8 is a side cross-sectional view of the heater screen, taken along line 8-8 of FIG. 7.

FIG. 9 is a side cross-sectional view of the print heater and reflector assembly, taken along line 9-9 of FIG. 6.

FIG. 10 is a bottom view of the heat reflector comprising the printer of Claim 1.

FIG. 11 is an exploded perspective view illustrating the gear train driving the printer rollers.

FIG. 12 is a side cross-sectional view of the heated drive roller comprising the printer.

FIG. 13 is a an end cross-sectional view of the heated driver roller.

FIG. 14 is a top view illustrating the printhead of the printer of FIG. 1.

FIGS. 15 and 16 illustrate the exhaust fan and duct of the printer of FIG. 1.

Fig. 17 is a simplified schematic block diagram of the controller comprising the printer of Fig.1.

An exemplary embodiment of a color thermal ink-jet printer 50 embodying the invention is illustrated in simplified schematic form in the Figures.

Overview of the Printer 50

The printer includes a means for driving the print medium in the x direction, and for controlling the movement of a printhead, indicated generally as element 52 in Fig. 1, in the y direction (orthogonal to the plane of Fig. 1), in order to direct ink from the ink cartridge, shown generally as elements 54, onto print media at the print region 56. In this embodiment, the printhead 52 supports four ink cartridges for black, yellow, magenta and cyan inks, respectively. This embodiment achieves receptacle color print quality on plain paper media, even using a print resolution of 300 dots per inch. The yellow, magenta and cyan print cartridges are staggered, so that the print nozzles of each cartridge subtend non-overlapping regions at the print zone of the printer.

The ink cartridges 54 each hold a supply of water-based inks, to which color dyes have been added.

The print medium in this embodiment is supplied in sheet form from a tray 58. A pick roller 60 is employed to advance the print medium from the tray 58 into engagement between drive roller 62 and idler roller 64. Exemplary types of print medium include plain paper, coated paper, glossy opaque polyester, and transparent polyester. Preferably the print medium is advanced in the manner described in U.S. Patent 4,990,011, by John A. Underwood, Anthony W. Ebersole and Todd R. Medin, and assigned to a common assignee with the present application. The entire contents of the patent is incorporated herein by this reference. Accordingly, this part of the printer 50 will not be described in further detail herein.

The printer operation is controlled by a controller 110, which receives instructions and print data from a host computer 130 in the conventional manner. The host computer may be a workstation or personal computer, for example. The user may manually instruct the controller 110 as to the type of print medium being loaded via front panel medium selection switches 132. In this exemplary embodiment there are three switches 132, one for plain paper, one for coated paper (e.g., Hewlett-Packard special paper), and another for polyester. The front panel switch selection data is overridden if the data received from the host computer includes medium type data.

Once the print medium has been advanced into the nip between the drive and idler rollers 62 and 64, it is advanced further by the rotation of the drive roller 62. A stepper drive motor 92 is coupled via a gear train to roller 62 to drive the rollers 60, 62, 100 and 103 which drive the medium through the printer media path.

The print medium is fed to a print zone 56 beneath the area traversed by the cartridges 54 and over a print screen 66 which provides a means of supporting the medium at the print position. The screen 66 further allows efficient transfer of radiant and convective energy from the print heater cavity 71 to the print medium as well as providing a safety barrier by limiting access to the inside of the reflector 70.

While the medium is being advanced, a movable drive plate 74 is lifted by a cam 76 actuated by the printhead carriage. Once the print medium reaches the print zone 56, the drive plate 74 is dropped, holding the medium against the screen 66, and allowing minimum spacing between the print nozzles of the thermal ink-jet print cartridges and the medium. This control of the medium in the print zone is important for good print quality. Successive swaths are then printed onto the print medium by the ink-jet head comprising the different print cartridges 54.

A print heater halogen quartz bulb 72 disposed longitudinally under the print zone 56 supplies a balance of thermal radiation and convective energy to the ink drops and the print medium in order to evaporate the carrier in the ink. This heater allows dense plots (300 dots per inch in this embodiment) to be printed on plain paper (medium without special coatings) and achieve satisfactory output quality in an acceptable amount of time. The reflector 70 allows radiated energy to be focused in the print zone and maximizes the thermal energy available.

The printer 50 further includes a crossflow fan 90 located to direct an air flow from in front of the print zone to the print zone, to aid in drying inks and directing carrier vapors toward the evacuation duct 80 for removal.

An evacuation duct 80 leads to an evacuation fan 82. The duct defines the path used to remove ink vapors from around the print zone 56. The evacuation fan 82 pulls air and vapor from around the print zone into the duct 80 and out an evacuation opening (FIG. 16). Evacuation of the ink vapors minimizes residue buildup on the printer mechanism.

An exit roller 100 and starwheels 102 and an output stacking roller 103 work in conjunction with the heated drive roller 62 to advance and eject the print medium. The gear train driving the gears is arranged such that the exit roller drives the medium slightly faster than the roller 62 so that the printer medium is under some tension once engaged by the exit roller. The frictional force between the print medium and the respective rollers is somewhat less than the tensile strength of the print medium so there is some slippage of the print medium on the rollers. The tension facilities good print quality keeping the print medium flat under the print zone.

The operation of the various elements of the printer 50 is controlled by controller 110. A thermistor 112 is provided adjacent the drive roller 62 to provide an indication of the temperature of the roller 62 surface. Power is applied to the preheat bulb 114 disposed within the roller 62 via a power measurement circuit 116, permitting the controller to monitor the power applied to the bulb 114. Power is also supplied to the print heater bulb 72 via a power measurement circuit 118, permitting the controller to monitor the power level supplied to the bulb 72. An infrared sensor 120 is mounted adjacent the print zone on the printhead 52, and is used to detect the edges of the print medium and whether the medium is transparent in order to select the appropriate operating conditions for the print heater. The printer supports a special transparent polyester medium, wherein a white opaque strip about 0.5 inches wide is adhered to the back of the medium along its leading edge, extending across the width of the medium. The sensor detects the presence or absence of the strip. By advancing the leading edge of the medium more than 0.5 inches past the sensor, the sharp reduction in energy reflected back to the sensor as the white strip is advanced beyond the sensor indicates that the medium is transparent. The white strip is also used by the sensor to detect the width of the transparent medium.

Overview of Printer Operation.

When the printer 50 is turned on, and power is applied to the printer, a warm-up algorithm is initiated. This algorithm turns on the preheat bulb 114 and rotates the drive roller 62 (without any medium in the drive path) so that no hot spots develop on the roller 62, to obtain a uniform roller surface temperature. The preheat temperature is monitored by the controller 110 via the thermistor 112.

Once the printer has come "on line" after being turned on (after various initialization routines and after the warmup algorithm has been performed) and after the print data is received, the print heater starts its preheat algorithm. During the preheat algorithm, the medium is loaded and advanced to the print zone. After the medium edges are sensed, the printing commences and a crossflow fan algorithm is initiated. These algorithms together work to turn on and control the print heater bulb 72, the crossflow fan 90 and the evacuation fan 82 in order to reach the correct operating conditions. Printing is achieved by firing drops of ink from the ink cartridges 54 while they are traversing the medium in a printhead sweep. The carrier in the ink is evaporated by the heat generated by the print heater bulb 72. The carrier vapor is directed by the airflow from the crossflow fan 90 toward the evacuation duct 80, where it is removed through the evacuation fan. The drive roller 62 advances the medium to the next line or sweep to be printed. In the event the print stream is interrupted, the heater 72 is turned off. When all lines have been printed, the print heater bulb 72 and the crossflow fan are turned off and the medium is ejected.

The evacuation fan 82 runs at all times the printer is on and is either printing or ready to print.

The Warmup Algorithm.

The warmup algorithm is illustrated in FIG. 2. When the printer 50 is powered up when the machine is turned on, the power to the preheat bulb 114 is rapidly ramped up to a preheat power setting, which in this embodiment is 225 watts. After some preheat time interval, which is selected in dependence on the temperature sensed by the thermistor 112 when the printer is turned on, the preheat bulb power is reduced to a maintenance power setting. This power setting fluctuates between 30 watts and 50 watts, depending on feedback from the thermistor 112. If the temperature sensed by the thermistor in this embodiment is greater than or equal to 70 degrees C, the power setting is at 30 watts. Once the temperature falls below 70 degrees C, the power setting is increased to 50 watts. The power to the preheat bulb cycles between these two power levels.

In this embodiment, the preheat time interval is selected from the following table, in dependence on the initial temperature sensed by the thermistor 112. The colder the initial temperature reading, the longer will be the preheat time interval.

TABLE I

ROLLER WARMUP TABLE	
Temperature (°C)	Preheat Time Interval (seconds)
≤ 40	120
41-45	100
46-50	80
51-55	60
56-60	40
61-65	20
≥ 66	0

The Preheat Algorithm

FIG. 3 illustrates the preheat algorithm for the heater bulb 72. Once the warmup algorithm of FIG. 2 has completed its warmup phase, and print data has been received from the host computer, the preheat sequence starts at time T_0. The power applied to the heater bulb 72 is rapidly ramped up to a preheat power level P. At time T_1, loading of the print medium from the storage tray is commenced, and is completed at time T_2, whereupon the power to the bulb 72 is turned off. The time interval between T_1 and T_0, T_{pre}, varies in dependence on the medium type, based on the setting of the front panel switches 132 or the print data from the host computer 130.

During the time interval between T_3 and T_2, the sensor 120 is operated to determine, from the reflectivity of the loaded media, whether the medium is transparent. The heater bulb 72 is turned off from T_2 to T_3; the operation of the infrared sensor 120 would be affected by the infrared energy generated by the bulb 72 if it was turned on during the sensor reading. This reading will affect the print heater power applied to the bulb 72 during the print process. In an exemplary embodiment, the time interval necessary to perform this sensing operation is about six seconds.

Once the sensing operation is completed, the controller determines the print power to be applied to the bulb 72 in dependence on the medium type. While it is desirable to have a high heater output in order to accelerate the ink drying process, too much heat can cause polyester media to wrinkle and cellulose-based media to turn yellow. Also, excess heat can overheat the print cartridges, resulting in larger drops of ink being expelled during print operations, and causing the cost per copy to increase. If the print cartridges become too hot, the cartridges will stop working. Excessive heat within the printer housing can also cause melting and deforming of plastic components and shorten the life of electronic components.

Some types of print media can withstand higher heat temperatures without adverse effects than other types. In particular, a paper medium can withstand higher heat temperature than a polyester medium; polyester tends to buckle when heated excessively.

At time T_3, the bulb power ramped up to P at time T_4, and then ramped down to P_{print} at T_5. At T_6, the print is completed, and the print media ejected from the printer into the output tray.

The power difference between P, the power applied to the bulb 72, and P_{print} is P_{pre}. The relationship between these three values is given by the relationships (1) and (2):

$$P = (P_{print})_{sub} + P_{pre}\,(1 - e^{(-2/3 \cdot t_{idle}/\tau)}) \quad (1)$$

for $0 \leq t_{idle} \leq 60$ seconds, where t_{idle} is the time interval between successive plots, and τ is a time constant equal to 15 seconds in this embodiment. τ is empirically determined by how long it takes the heater to warm up or cool down.

$$P = (P_{print})_{initial} + P_{pre} \quad (2)$$

for $t_{idle} > 60$ seconds.

The power applied to the print heater bulb 72 is dependant on the medium type, in accordance with the invention. Exemplary power values for an exemplary printer for different medium types are given in Table II.

TABLE II

MEDIUM	TYPE	PRINT MODE	P_{pre} (Watts)	RAMP DECREMENT (WATTS/SWATH)	P_{print} (Watts)		t_{pre} (sec.)
					INIT	SUBSEQ	
PAPER	PLAIN	1 PASS	105	12	135	125	23
		3 PASS	105	3	135	125	23
	COATED	3 PASS	125	3	115	105	23
POLYESTER	GLOSSY OPAQUE	4 PASS	60	1	55	55	25
	TRANSP	4 PASS	75	1	65	65	13

As indicated in Table II, different print modes are employed depending on the medium type. One pass mode operation is used for increased throughput on plain paper. Use of this mode on other papers will result in too large of dots on coated papers, and ink coalescence on polyester media. The one pass mode is one in which all dots to be fired on a given row of dots are placed on the medium in one swath of the print head, and then the print medium is advanced into position for the next swath.

The three pass mode is a print pattern wherein one third of the dots for a given row of dots swath are printed on each pass of the printhead, so three passes are needed to complete the printing for a given row. Typically, each pass prints the dots on one third of the swath area, and the medium is advanced by one third the distance to print the next pass as in the one pass mode. This mode is used to allow time for the ink to evaporate and the medium to dry, to prevent unacceptable cockle and ink bleeding.

Similarly, the four pass mode is a print pattern wherein one fourth of the dots for a given row are printed on each pass of the printhead. For a polyester medium, the four pass mode is used to prevent unacceptable coalescence of the ink on the medium.

Multiple pass thermal ink-jet printing is described, for example, in commonly assigned U.S. Patent Nos. 4,963,882 and 4,965,593.

In general it is desirable to use the minimum number of passes per full swath area to complete the printing, in order to maximize the throughput. Table II also shows that the rate at which P decreases (i.e., ramp decrement) from its peak at T_4 to P_{print} at T_5 varies, depending on the medium type. The ramp decrement rate has been empirically determined. For the plain paper medium using the one pass mode, which is typically used only for black only printing with relatively lower dot density, the heat output is higher initially, and the swath time is slower than on the other medium types, since all dots are being fired on a single pass. The higher decrement rate is employed to prevent overheating of the medium and the printer components. For the plain paper using three pass mode, which provides higher print quality, each swath or pass takes less time, and so a lower decrement rate/swath can be employed. Thus, for example, for plain paper, the bulb power is decrement by either 12 or 3 watts per swath, depending on the print mode, while for polyester, the ramp decrement rate is 1 watt/swath. For coated paper, the same decrement rate is used as for plain paper using the three pass printing mode. For polyester, the initial heater power is significantly lower, so the ramp decrement rate can be lower, in order to obtain the necessary heat to dry the ink.

FIG. 4 illustrates the crossflow fan algorithm, showing the fan speed for the different print medium positions and type. Positions P_1, P_3 and P_7 correspond to medium positions at the respective times of T_1, T_3 and T_7 of FIG. 3. Thus, at position P_1, loading of the print medium is commenced. At position P_3, the medium has been advanced to the print zone 56, and printing commences, and at this time the crossflow fan is turned on to 2000 RPM. At position Pa, when the leading edge of the medium is at midscreen, the fan RPM is increased to 2200 RPM. At position Pb, the leading edge of the medium has reached the starwheels and the speed is increased again to 2600 RPM if the medium, is plain paper; otherwise the speed remains constant at 2200 RPM until the printing has been completed at time T6, when the crossflow fan is turned off.

The crossflow fan 90 is not driven at its highest speed until the medium fully covers the screen 66, and the speed is ramped up as the medium advances across the screen. If the fan were to be operated at full speed at the beginning of the print cycle, the fan would blow air through the openings of the screen and into the reflector cavity. This would cool off the print heater and cavity, and reduce the heat energy available to evaporate the ink carrier.

The maximum fan speed is dependent on the print medium, and is determined by ink spray conditions on the media. It is desired to maximize the fan speed to keep the ink cartridges and printer enclosure from getting too hot. However, the air velocity creates ink spray outside the nominal print area, as tiny spray droplets are forced away from major ink drops. The visual threshold acceptability of ink spray is dependent on the medium type. Plain paper is least sensitive to ink spray, and therefore the highest fan speed setting is used for plain paper. A lower maximum fan speed is used for other types of medium, which use a lower heater setting and have less need for cooling anyway.

FIGS. 5A-5B illustrate an operational flow diagram for the printer 50 in accordance with the invention. At step 300, power to the printer is turned on, initiating the roller warmup algorithm (FIG. 2). Upon completion of the warmup phase of that algorithm and other initialization procedures, the printer checks for print data to be input to the printer from the host computer. Once input data is received, the printer preheat algorithm (FIG. 3) is initiated at step 306. At step 308, the print medium is loaded. This step includes actively aligning the leading edge of the medium at the drive roller and idler roller nip, rolling in the medium to the top of the drive roller, lifting the drive plate, pushing the medium onto the screen, and lowering the drive plate.

At this point, the print heater is turned off (step 310). If the medium is either glossy or transparent (based on the setting of the front panel switches or the print data from the host computer) (step 312), the sensor is used to find whether the medium is glossy or transparent. At step 314, the sensor is used to find the medium edges. The appropriate heater setting is selected for the particular type of medium loaded into the printer.

At step 318, printing commences. The heater bulb 72 is turned on, to a heating power setting dependent on the type of medium being printed. The crossflow fan is turned on, to a speed based on the position of the medium over the screen. The first swath is now printed (step 320) across the print medium. The printer now looks for more data defining the next swath to be printed, if any (step 322). If no more data has been received, an end of page check is performed (step 324). The print data from the host computer will typically include end-of-page flags or signals. The printer also includes a mechanical flag sensor (not shown) on the roller 62, disposed in the central peripheral groove thereof, which indicates when print medium is not in contact with the roller. If the end of the page being printed has not been reached, then the heater is turned off (step 326), and after a wait of 15 seconds, the crossflow fan is turned off (step 328). An idle stage (330) is maintained until new print data is received (322), at which time the heater and fan are turned on again to the same setting as when shut off (326, 328). Operation then proceeds to step 344.

If the end of the page has been reached (step 324), then the page is ejected from the printer (step 336), and the print heater and crossflow fan are turned off (step 338). The controller waits for receipt of new page data (step 340). Upon receipt of the new page data, if the idle time (tidle) exceeds 60 seconds, operation returns to B (step 306). If the idle time does not exceed 60 seconds, operation returns to C (step 308).

If more data has been received at step 322, operation proceeds to decision 344. If the heater setting is greater than the print power, the heater power is decremented (step 346). At step 348, if the medium edge is at the midpoint of the screen, the fan speed is set to the midpoint speed (step 350). The controller knows the position of the medium leading edge from the number of steps incremented by the drive motor 92 to advance the print medium. If the medium is not at the midpoint of the screen, then at step 352, if the medium edge is at the starwheels 102, the fan is set to the maximum speed for the print medium (step 354). If the medium is not at the starwheels 102, operation returns to step 320, to print another swath.

The Print Zone Screen 66.

The print zone screen 66 in this embodiment is further illustrated in FIGS. 6, 7 and 8, and performs several functions. It supports the paper at the print zone and above the heater reflector 70. The screen is strong enough to prevent users from touching the heater element 72. The screen transmits radiative and convective heat energy to the print medium, while transmitting little if any conductive heat energy, which would cause print anomalies, due to nonuniform heat transfer. The screen 66 must be designed such that the print medium does not catch a surface of the screen as it is driven through the print zone.

The screen 66 performs these functions by the placement of a network of thin primary and secondary webs, nominally .030 inches in width, which outline relatively large screen openings. Exemplary ones of the primary and secondary webs are indicated as respective elements 67A and 67B in FIG. 7; exemplary screen openings are indicated as "69" in FIG. 7. The purpose of the secondary webs is to provide additional strength to meet safety requirements.

The screen 66 is preferably made from a high strength material such as stainless steel, in this embodiment about .010 inches in thickness. The openings 69 can be formed by die cutting or etching processes. The screen is processed to remove any burs which might catch the medium. FIG. 8 shows a cross-sectional view, and illustrates the top surface 66A which joins side flanges 66B and 66C. The screen fits over the top of the reflector 70 as illustrated in FIG. 9.

Typical dimensions for the screen include a screen opening pattern width (i.e., the dimension in the direction of medium travel) of .810 inches (20.5 mm), and opening 69 width and length dimensions of .310 inches (8 mm) and .470 inches (12 mm), respectively. The print zone width (in the direction of medium travel) for the exemplary printhead 52 of this embodiment is .530 inches (13.5 mm) covering the region subtended by three stagger print cartridges, each print cartridge employing 48 print nozzles aligned in a row.

Referring again to FIG. 7, the screen grid pattern is essentially a mirror image about the center axis 66D. Viewed from the edge 66E of the screen initially traversed by the print medium, the primary webs 67A are at a first obtuse angle relative to a line perpendicular to the edge 66E, which angle in this embodiment is 135 degrees. The secondary webs 67B are at a second obtuse angle relative to a line perpendicular to edge 66E, which in this embodiment is 115 degrees. The edges of the openings 69 which are adjacent the edge 66F of the screen are at a 70 degree angle relative to a line perpendicular to the screen edge 66E. These angles are selected in order to provide a web network which has the requisite strength to prevent users from touching the bulb 72 and yet which permits the ready transfer of radiant and convective heat energy from the radiator cavity to the print medium.

The angle of the primary webs 67A is determined by several factors. The web angles must first meet the requirement that the leading edge of the medium not catch on the webs as the medium is advanced. Also, the web angles are also selected in dependence on the medium advance distance between adjacent print swaths. This distance is determined by the number of print nozzles and the print mode. In this exemplary embodiment, the printhead comprises 48 print nozzles in a row, spaced over a distance of .160 inches (4.1 mm). Including the spacing between staggered cartridges, the total width of the area subtended by the printhead in this exemplary embodiment is .530 inches (13.5 mm). For a single pass mode the medium advance distance for each successive swath is .160 inches, i.e., the width of the area subtended by the print nozzle of a single one of the staggered print cartridges. For a three pass mode, the distance is one-third the single pass distance, or .053 inches. For the four pass mode, the distance is .040 inches, i.e., one-fourth the medium advance distance for the single pass mode.

The width of the screen opening pattern is determined in the following manner for this exemplary printer embodiment. The opening pattern width can be considered to have three regions, the first a pre-heat region for preheating the advancing medium before reaching the active print zone. The second region is the active print zone, i.e., the area subtended by the print nozzles comprising the printhead. In this embodiment, this area is defined by the nozzle coverage of three staggered print cartridges. The third region is a post-print heating region, reached by the medium after being advanced through the active print zone. In this embodiment, the pre-heat region width is equal to two multi-pass medium advancement distances; this is equal to 2(.160 inches)/3, or about .105 inches. The active print zone region has a width of .530 inches, for the staggered three print cartridge embodiment, as described above. The post-print heating region has a width equal to a single pass mode increment distance, or .160 inches. The three regions aggregate approximately .8 inches in this embodiment.

The web angles are such that the vertical distance D between webs (i.e., the distance D on a perpendicular line to the screen edge 66E between webs as shown in FIG. 7) is not an integral multiple of the medium advance distance. This prevents the same point on the medium from being shielded from the heater cavity by adjacent webs in successive positions as the medium is advanced during printing. Such shielding would affect the drying rate slightly, and web patterns in the finished print copy could be seen if this shielding were not prevented. The problem is evident if one considers the use of vertical webs, i.e., webs which are parallel to the direction of advancement of the medium, which obviously would not catch the medium as it is advanced. However, the same areas of the medium, those disposed over webs, will be shielded from the print cavity as the medium is advanced, and this area will dry differently than unshielded areas, showing the vertical web pattern.

By way of example, the preferred embodiment, with a primary web angle of 135 degrees, employs a vertical spacing distance D between adjacent primary webs 67A of approximately 9 millimeters (.355 inches), wherein a three pass medium advance distance is 1.4 millimeters(.055 inches). This is about 6.4 advances, i.e., not an integral multiple.

The Print Heater.

The print heater bulb 72 and reflector are shown in FIGS. 6, 9 and 10 in further detail. The bulb 72 is a quartz halogen lamp, 13 inches in length. It is supported longitudinally at each end thereof within the reflector cavity 71 by conventional bushing elements 72C (shown in FIG. 6). In this exemplary embodiment, the lamp is a 90 volt, 200 watt

bulb. A thermal fuse 72A is provided in the power circuit cable disposed in a channel 70D disposed at the bottom of the reflector 70, to comply with UL safety requirements.

The reflector 70 further comprises an inner liner 70B which has an inner surface which is highly reflective of infrared energy. The reflector 70 is fabricated from a material, such as galvanized steel, which can withstand the heat generated by the bulb 72, and which supports a highly reflective aluminum inner liner 70B to reflect the heat energy generated by the bulb toward the screen 66 which is assembled to the top of the reflector cavity. The bottom of the liner 70B is peaked under the bulb 72 so as to reflect energy directed downwardly by the bulb toward the sides of the liner for further reflection upwardly to the screen 66. Without the peak, some of such downwardly directed energy would be directed back to the bulb, blocking this portion of the heat from the screen, heating the bulb unnecessarily and wasting a portion of the heat energy.

As shown more clearly in the reflector bottom view of FIG. 10, a plurality of holes 70C are formed in both the reflector and its inner liner. In this embodiment, the holes in the reflector have a diameter of .125 inches (3.2 mm), and the corresponding holes in the reflector inner liner have a diameter of .100 inches (2.5 mm). Such holes provide a means for air to enter the bottom of the reflector and circulate upwardly through openings in the screen 66. The holes therefor increase the convective heat transfer from the reflector cavity 71 to the screen, and to allow cool air to flow into the cavity, thereby decreasing the maximum temperature of the assembly.

The Heated Drive Roller 62.

FIGS. 12 and 13 illustrate the drive roller in further detail. The roller comprises an aluminum roller 62B, on which a rubber coating 62A is formed to increase the coefficient of friction between the roller and the print medium. The aluminum wall provides good thermal conductivity resulting in a fairly isothermal surface. The interior surface 62C of the roller wall is black anodized to absorb infrared energy generated by the halogen bulb 114, fitted inside the roller wall 62B.

The roller wall 62B is rotatable on axis 62D by a gear train driven by the motor 92. The roller is supported by housing walls 152 and 154, with the gear train shaft 156 supported by a bushing (not shown). At the opposite end of the roller, a stationary bushing 158 slips into the open end of the roller wall 62B so that the end of the roller wall 62B slides or turns about the bushing 158. A spring 160 and friction washer 162 bias the end 62E of the roller toward the gear train end.

Polysulfone mounts 164 and 166 are used to mount the bulb 114 within the roller 62; polysulfone is used to withstand the high temperatures generated by the bulb 114. The bulb 114 in this exemplary embodiment is a 10 inch long, quartz halogen lamp selected to provide rapid warmup by using infrared energy. In this exemplary embodiment, a 108 volt, 270 watt bulb is used. To provide structural rigidity to the bulb mounting, an aluminum extrusion extends below the bulb 114 between the mounts 164 and 166. The extrusion has a natural aluminum finish to reflect infrared energy. A power wire runs in the extrusion channel between the bulb ends, with a thermal fuse is series with the wire to protect against overheating.

The polysulfone mount 164 is secured within stationary bushing 158. At the other end of the roller, mount 166 slip fits over a shaft 146, so that the mount and bulb assembly can rotate with respect to the shaft 146.

It may be seen that the bulb 114 is stationary with respect the roller wall 62B as the wall rotates to drive the print medium. This facilitates the task of providing electrical power to the bulb 114, permitting the power wires to be run through the stationary bushing 158 to the controller 130.

The roller heater is used to dry the medium under high humidity conditions before reaching the print heater. High humidity conditions, e.g., 70 percent relative humidity or higher, result in cellulose based media having a high moisture content. The heated drive roller drys some of this moisture from the medium before reaching the print zone. If the medium were not dried before the print zone, uneven shrinkage of the medium can occur when the medium is heated by the print heater at the print zone. This results because the part of the medium not at the print zone is not being heated, and the uneven heating of the different portions of the medium can cause buckling of the medium. The medium to nozzle distance can vary due to this buckling, and in extreme cases the buckled medium can actually contact the print nozzles, causing smearing. Thus the roller heater prevents uneven shrinkage of cellulose-based media.

The Roller Gear Train and Drive Motor.

The roller gear train and drive motor interrelationship is illustrated in FIG. 11 in a simplified perspective view. The drive motor 92 is a stepper motor driven by a motor drive circuit comprising the controller 110. The motor shaft 93 has fitted on the end thereof a worm gear 94 which engages a helical gear 146 fitted on the drive roller shaft 156 (FIG. 12).

Also mounted on shaft 156 is a spur gear 142 which drives gears 100A and 103A through a series of idler gears 170-173. The diameters of the helical gear 146 and gear 100A are selected to turn roller 100 slightly faster than roller 62, in order to put tension on the print media when engaged by both rollers 62 and 100.

FIG. 6 is a partially exploded view of an assembly comprising the printer of FIG. 1, illustrating certain of the elements in the media drive path. The printer housing walls 152 and 154 and housing 155 provide a structure for supporting the drive roller 62, the exit roller 100, the drive plate 74 and reflector 70 as shown in FIG. 6. The preheat bulb 114 and its

supporting structural element 166 can be accessed via an opening in the housing side wall. Similarly, the reflector 70 and bulb 72 can be accessed from another opening in the housing side wall 154.

The Printhead and Carriage.

FIG. 14 illustrates a partially broken away top view of the printhead 52. The printhead 52 comprises the four thermal inkjet cartridges 54A-D. The printhead 52 is supported on parallel ways 52A and 52B for sliding movement along the ways. The printer includes a printhead drive means, including a drive belt 52C (driven by a dc motor, not shown) connected to the printhead 52 for driving the printhead along the Y direction to print swaths on the print medium supported below the cartridges 54A-D. (Other conventional motor and drive train elements for the printhead are not shown.)

The location of the sensor 120 on the printhead 53 is shown in FIG. 14. It is disposed directly above the surface of the screen 66. In this exemplary embodiment, the sensor senses infrared energy from an infrared LED which is reflected from the surface of the print medium at the print zone, and can sense the position of the medium edges. Such sensors are commercially available, such as the model EES133 marketed by Omoron Electronics, Inc., Minakuchi, Japan.

The Exhaust System.

FIGS. 15 and 16 illustrate the configuration of the exhaust duct 80 and exhaust fan 82. The duct 80 is elongated, with an intake port 80A positioned above the drive roller 62 and adjacent the print zone 56. The port 80A has a height dimension of about .17 inches in this exemplary embodiment. The exhaust fan 82 is positioned at the exhaust end 80B of the duct. A filter 83 is employed to trap solid particulate drawn from the exhaust duct by the fan 82. The fan size is chosen to exhaust air from the duct at a rate of about 10 cfm.

The Crossflow Fan.

In this embodiment, the fan 90 is an elongated cross-flow-type fan, mounted above the output side of the print zone 56 (FIG. 6). The fan 90 has a blade assembly length of 9 inches, and a blade assembly diameter of 1 inch in this embodiment. The fan extends across the swath width of the print zone, and in this embodiment provides an air velocity about 700 feet per minute at its highest RPM. The fan speed and operation is controlled by controller 110. This fan is driven by a dc motor 90A (FIG. 6). The drive signal to the motor 90A is pulse width modulated by the controller 110 to obtain the desired fan speed. A sensor 91 is coupled to the drive motor 90A and provides a motor speed signal to the controller 110. If the motor speed is less than the expected speed, indicating fan malfunction, the printer operation is shut down to avoid overheating the printer elements.

The crossflow fan 90 directs an airflow at the print zone and surrounding printer elements. The airflow creates turbulence at the print zone, which increases the ink carrier evaporation rate, and directs airflow toward the exhaust duct intake port 80A. The airflow also cools the printhead elements and other printer elements. When the print cartridge nozzles become too hot, larger ink dots are ejected than is desired. Moreover, the print nozzle laminate can become delaminated at very high temperatures.

The Controller

Fig. 17 illustrates the controller 110 in simplified schematic form. The various elements comprising the controller 110 are well known to those skilled in the art, and accordingly are not described herein in further detail.

It is understood that the above-described embodiments are merely illustrative of the possible specific embodiments which may represent principles of the present invention. Other arrangements may readily be devised in accordance with these principles by those skilled in the art without departing from the scope of the invention as defined in the claims.

Claims

1. An ink-jet printer for printing onto a print medium, including a printhead (52) for printing on a print medium, said printhead comprising a plurality of ink-jet nozzles disposed above a print zone (56) for ejecting jets of ink onto the surface of said medium in a controlled fashion, means for advancing the print medium via a medium path to said print zone during print operations, said advancing means comprising a drive roller (62) for engaging said medium, wherein said medium path comprises a path about a portion of an external circumferential surface of said drive roller, wherein said medium is wrapped about said portion of said external surface of said roller (62) in the course of advancement of said medium to said print zone and preheat means (114) for preheating said print medium before said medium reaches said print zone, said preheat means comprising means for heating said roller external surface, characterised in that print heater means (72) is provided which is independently operable of said preheat means (114), and in that control means (110) is provided which actuates said preheat means (114) when the printer is

switched on and which actuates said print heater means (72) after actuation of said preheat means but before print operations by said printhead (52).

2. An ink-jet printer according to claim 1, wherein said drive roller (62) is hollow, and said preheat means comprises an elongated bulb (114) for generating infrared energy disposed within said roller.

3. An ink-jet printer according to claim 2, wherein said elongated bulb (114) is fixed in position relative to said roller (62), and is stationary while said roller external surface is rotated.

4. An ink-jet printer according to any preceding claim, and having means (112) for monitoring the temperature of said external surface of said roller, said control means (110) controlling said preheat means (114) in dependence on said temperature monitoring means to maintain the temperature of said surface at a relatively constant temperature during print operations.

5. An ink-jet printer according to any of claims 1 to 3 and having temperature sensing means (112) for providing a temperature signal indicative of the temperature of said roller external surface, and wherein said control means (110) comprises means for causing said preheat means (114) to operate at a first relatively high power level for a predetermined time interval upon turning on the printer, and upon expiration of said time interval for enabling said preheat means (114) to cycle between second and third power levels which are relatively lower than said first power level in dependence on said temperature signal, said cycling occurring in response to said temperature signal.

6. An ink-jet printer according to any preceding claim, and having roller drive means (92) for rotating said driver roller, said roller drive means being controlled by said control means (110), and wherein said control means controls said drive means to rotate said roller without any print medium in engagement therewith during a predetermined warm up time prior to commencement of printing operations, said rotating of said roller serving to obtain a relatively uniform heating of said roller external surface.

7. An ink-jet printer according to any preceding claim, wherein said roller (62) has an internal circumferential roller surface which is coated to increase absorption of infrared energy generated by said preheat means.

8. An ink-jet printer according to any preceding claim, wherein said print heater means comprises a bulb (72) disposed below said print zone for supplying thermal energy to the ink and the print medium.

9. An ink-jet printer according to any preceding claim, wherein said print heater means (72) is actuated only after said preheat means (114) has reached a predetermined stage of its preheating process, and wherein said control means (110) comprises means for causing said print heater means (72) to initially operate at a relatively high power level (P_{pre}) and subsequently during print operations for causing said print heater means (72) to operate at a lower power level (P_{print}).

10. An ink-jet printer according to an preceding claim, and having a fan (90) for directing an air flow in the region of said print zone (56), wherein said control means (110) comprises means for causing said fan (90) to operate at a speed which is dependent upon the position of said print medium in said medium path.

Patentansprüche

1. Ein Tintenstrahldrucker zum Drucken auf einem Druckmedium, mit folgenden Merkmalen: einem Druckkopf (52) zum Drucken auf einem Druckmedium, wobei der Druckkopf eine Mehrzahl von Tintenstrahldüsen, die über einer Druckzone (56) angeordnet sind, um Tintenstrahlen in einer gesteuerten Form auf die Oberfläche des Mediums auszustoßen, aufweist, einer Einrichtung zum Weiterbewegen des Druckmediums über einen Medienweg zu der Druckzone während Druckoperationen, wobei die Weiterbewegungseinrichtung eine Antriebsrolle (62) aufweist, um das Medium in Eingriff zu nehmen, wobei der Medienweg einen Weg um einen Abschnitt einer äußeren Umfangsoberfläche der Antriebsrolle herum aufweist, wobei das Medium im Verlauf der Weiterbewegung des Mediums zu der Druckzone um den Abschnitt der äußeren Oberfläche der Rolle (62) gewickelt wird, und einer Vorheizeinrichtung (114) zum Vorheizen des Druckmediums, bevor das Medium die Druckzone erreicht, wobei die Vorheizeinrichtung eine Einrichtung zum Erwärmen der äußeren Rollenoberfläche aufweist, dadurch gekennzeichnet, daß eine Druckheizereinrichtung (72) vorgesehen ist, die unabhängig von der Vorheizeinrichtung (114) betreibbar ist, und daß eine Steuereinrichtung (110) vorgesehen ist, die die Vorheizeinrichtung (114) betätigt, wenn der Drucker eingeschaltet wird, und die die Druckheizereinrichtung (72) nach der Betätigung der Vorheizeinrichtung, jedoch vor Druckoperationen durch den Druckkopf (52) betätigt.

2. Tintenstrahldrucker gemäß Anspruch 1, bei dem die Antriebsrolle (62) hohl ist und die Vorheizeinrichtung eine längliche Röhre (114) aufweist, um Infrarotenergie zu erzeugen, die in der Rolle angeordnet ist.

3. Ein Tintenstrahldrucker gemäß Anspruch 2, bei dem die längliche Röhre (114) in einer Position relativ zu der Rolle (62) befestigt ist und stationär ist, während die äußere Oberfläche der Rolle gedreht wird.

4. Ein Tintenstrahldrucker gemäß einem beliebigen vorhergehenden Anspruch mit einer Einrichtung (112) zum Überwachen der Temperatur der äußeren Oberfläche der Rolle, wobei die Steuereinrichtung (110) die Vorheizeinrichtung (114) abhängig von der Temperaturüberwachungseinrichtung steuert, um die Temperatur der Oberfläche während Druckoperationen auf einer relativ konstanten Temperatur zu halten.

5. Ein Tintenstrahldrucker gemäß einem beliebigen der Ansprüche 1 bis 3 mit einer Temperaturerfassungseinrichtung (112) zum Liefern eines Temperatursignals, das die Temperatur der äußeren Oberfläche der Rolle anzeigt, wobei die Steuereinrichtung (110) eine Einrichtung aufweist, um zu bewirken, daß die Vorheizeinrichtung (114) auf einem ersten, relativ hohen Leistungspegel für eine vorbestimmte Zeitdauer auf das Einschalten des Druckers hin arbeitet, und um auf das Verstreichen der ersten Zeitdauer hin zu ermöglichen, daß die Vorheizeinrichtung (114) zyklisch zwischen einem zweiten und einem dritten Leistungspegel wechselt, die relativ geringer als der erste Leistungspegel sind, abhängig von dem Temperatursignal, wobei das zyklische Wechseln als Reaktion auf das Temperatursignal stattfindet.

6. Ein Tintenstrahldrucker gemäß einem beliebigen vorherigen Anspruch, der ferner eine Rollenantriebseinrichtung (92) zum Drehen der Antriebsrolle aufweist, wobei die Rollenantriebseinrichtung durch die Steuereinrichtung (110) gesteuert wird, und wobei die Steuereinrichtung die Antriebseinrichtung steuert, um die Rolle ohne irgendein Druckmedium in eine Eingriffnahme mit derselben während einer vorbestimmten Aufwärmzeit vor dem Beginn der Druckoperationen zu drehen, wobei das Drehen der Rolle dazu dient, eine relativ gleichmäßige Erwärmung der äußeren Rollenoberfläche zu erhalten.

7. Ein Tintenstrahldrucker gemäß einem beliebigen vorhergehenden Anspruch, bei dem die Rolle (62) eine innere, umfangsmäßige Rollenoberfläche aufweist, die beschichtet ist, um die Absorption der Infrarotenergie, die durch die Vorheizeinrichtung erzeugt wird, zu erhöhen.

8. Ein Tintenstrahldrucker gemäß einem beliebigen vorhergehenden Anspruch, bei dem die Druckheizereinrichtung eine Röhre (72) aufweist, die unter der Druckzone angeordnet ist, um der Tinte und dem Druckmedium thermische Energie zuzuführen.

9. Ein Tintenstrahldrucker gemäß einem beliebigen vorhergehenden Anspruch, bei dem die Druckheizereinrichtung (72) nur betätigt wird, nachdem die Vorheizeinrichtung (114) eine vorbestimmte Phase ihres Vorheiz-Verfahrens erreicht hat, und bei dem die Steuereinrichtung (110) eine Einrichtung aufweist, um zu bewirken, daß die Druckheizereinrichtung (72) anfänglich auf einem relativ hohen Leistungspegel (P_{pre}) arbeitet, und um nachfolgend während Druckoperationen zu bewirken, daß die Druckheizereinrichtung (72) auf einem niedrigeren Leistungspegel (P_{print}) arbeitet.

10. Ein Tintenstrahldrucker gemäß einem vorhergehenden Anspruch, der ferner einen Lüfter (90) aufweist, um einen Luftfluß in die Region der Druckzone (56) zu leiten, wobei die Steuereinrichtung (110) eine Einrichtung aufweist, um zu bewirken, daß der Lüfter (90) mit einer Geschwindigkeit arbeitet, die von der Position des Druckmediums in dem Medienweg abhängt.

Revendications

1. Imprimante à jet d'encre destinée à imprimer sur un milieu d'impression, possédant une tête d'impression (52) destinée à imprimer sur un milieu d'impression, ladite tête d'impression comprenant une pluralité de buses à jet d'encre disposées au-dessus d'une zone d'impression (56) pour éjecter des jets d'encre sur la surface dudit milieu d'une façon contrôlée, des moyens servant à faire avancer le milieu d'impression, en passant dans un trajet de milieu, jusqu'à ladite zone d'impression pendant les opérations d'impression, lesdits moyens d'avance comprenant un rouleau d'entraînement (62) destiné à attaquer ledit milieu, dans lequel ledit trajet du milieu comprend un trajet passant autour d'une partie d'une surface circonférentielle extérieure dudit rouleau d'entraînement, dans lequel ledit milieu est enroulé autour de ladite partie de ladite surface extérieure dudit rouleau (62) pendant le cours de l'avance dudit milieu vers ladite zone d'impression et des moyens de préchauffage (114) servant à préchauffer ledit milieu d'impression avant que ledit milieu n'atteigne ladite zone d'impression, lesdits moyens de préchauffage comprenant

des moyens pour chauffer ladite surface extérieure du rouleau, caractérisée en ce qu'il est prévu des moyens (72) formant élément chauffant d'impression qui peuvent être mis en action indépendamment desdits moyens de préchauffage (114) et en ce qu'il est prévu des moyens de commande (110) qui actionnent lesdits moyens de préchauffage (114) lorsque l'imprimante est allumée et qui actionnent lesdits moyens (72) formant élément chauffant d'impression après l'actionnement desdits moyens de préchauffage mais avant les opérations d'impression exécutées par ladite tête d'impression (52).

2. Imprimante à jet d'encre selon la revendication 1, dans laquelle ledit rouleau d'entraînement (62) est creux et lesdits moyens de préchauffage comprennent une lampe (114) de forme allongée pour dégager une énergie infrarouge et disposée à l'intérieur dudit rouleau.

3. Imprimante à jet d'encre selon la revendication 2, dans laquelle ladite lampe (114) de forme allongée est fixe en position par rapport audit rouleau (62) et elle est stationnaire pendant que la surface extérieure dudit rouleau est entraînée en rotation.

4. Imprimante à jet d'encre selon une quelconque des revendications précédentes, et possédant des moyens (112) servant à surveiller la température de ladite surface externe dudit rouleau, lesdits moyens de commande (110) commandant lesdits moyens de préchauffage (114) en fonction desdits moyens de surveillance de la température pour maintenir la température de ladite surface à un niveau de température relativement constant pendant les opérations d'impression.

5. Imprimante à jet d'encre selon une quelconque des revendications 1 à 3, possédant des moyens capteurs de température (112) servant à fournir un signal de température indicatif de la température de ladite surface extérieure du rouleau, et dans laquelle lesdits moyens de commande (110) comprennent des moyens servant à faire travailler lesdits moyens de préchauffage (114) à un premier niveau d'énergie relativement élevé pendant un intervalle de temps prédéterminé à la suite de la mise en marche de l'imprimante et, à la suite de l'expiration dudit intervalle de temps, à permettre auxdits moyens de préchauffage (114) de varier cycliquement entre des deuxième et troisième niveaux d'énergie qui sont relativement plus bas que ledit premier niveau d'énergie, en fonction dudit signal de température, ladite variation cyclique se produisant en réponse audit signal de température.

6. Imprimante à jet d'encre selon une quelconque des revendications précédentes, et ayant des moyens (92) d'entraînement du rouleau servant à faire tourner ledit rouleau d'entraînement, lesdits moyens d'entraînement du rouleau étant commandés par lesdits moyens de commande (110), et dans laquelle lesdits moyens de commande commandent lesdits moyens d'entraînement pour faire tourner ledit rouleau sans milieu d'impression en contact avec celui-ci pendant un temps de mise en température prédéterminé avant le commencement des opérations d'impression, ladite rotation dudit rouleau servant à obtenir un échauffement relativement uniforme de ladite surface extérieure du rouleau.

7. Imprimante à jet d'encre selon une quelconque des revendications précédentes, dans laquelle ledit rouleau (62) possède une surface circonférentielle intérieure de rouleau qui est revêtue de manière à augmenter l'absorption de l'énergie infrarouge engendrée par lesdits moyens de préchauffage.

8. Imprimante à jet d'encre selon une quelconque des revendications précédentes, dans laquelle lesdits moyens formant élément chauffant d'impression comprennent une lampe (72) disposée au-dessous de ladite zone d'impression pour fournir de l'énergie thermique à l'encre et au milieu d'impression.

9. Imprimante à jet d'encre selon une quelconque des revendications précédentes, dans laquelle lesdits moyens (72) formant élément chauffant d'impression ne sont actionnés qu'après que lesdits moyens de préchauffage (114) ont atteint un stade prédéterminé de leur processus de préchauffage et dans laquelle lesdits moyens de commande (110) comprennent des moyens servant à amener lesdits moyens (72) formant élément chauffant d'impression à travailler initialement à un niveau de puissance relativement élevé (P_{pre}) et, ensuite, pendant les opérations d'impression, à amener lesdits moyens (72) formant élément chauffant d'impression à travailler à un niveau d'énergie plus faible (P_{print}).

10. Imprimante à jet d'encre selon une quelconque des revendications précédentes et ayant un ventilateur (90) servant à projeter un flux d'air dans la région de ladite zone d'impression (56), dans laquelle lesdits moyens de commande (110) comprennent des moyens servant à faire travailler ledit ventilateur (90) à une vitesse qui dépend de la position dudit milieu d'impression dans ledit trajet du milieu.



MEDIA DIRECTION
POWER MEASUREMENT
CONTROLLER
INPUT TRAY
POWER MEASUREMENT
MEDIA SELECT SWITCHES
DRIVE MOTOR
HOST COMPUTER
X
90
91
52
54
56
58
60
62
64
66
70
72
74
76
80
82
92
100
102
103
110
112
114
116
118
120
130
132

FIG. 1

FIG.2




FIG.3




FIG.4





FIG. 5A


POWER ON
300
WARM-UP ROLLER ALGORITHM
302
304
DATA ?
NO
YES
B
PREHEAT PRINT HEATER
306
C
LOAD MEDIUM (ACTIVE PAPER ALIGN, ROLL IN MEDIUM TO TOP OF ROLLER, LIFT DRIVE PLATE, PUSH MEDIUM ON TO SCREEN & LOWER DRIVE PLATE)
308
TURN PRINT HEATER OFF
310
312
IS MEDIUM TYPE GLOSSY TRANSPARENT ?
YES
NO
314
USE SENSOR TO FIND WHETHER GLOSSY OR TRANSPARENT
314
SENSE EDGES
SELECT HEATER SETTING FOR MEDIUM
316
START PRINTING & TURN ON HEATER, TURN ON FAN BASED ON POSITION OF MEDIUM OVER SCREEN
318
A




A
320
PRINT SWATH
334
TURN ON FAN & HEATER TO SAME SETTING AS WHEN SHUT OFF
332
DATA ?
YES
NO
330
IDLE
322
MORE DATA ?
NO
YES
324
END OF PAGE ?
NO
YES
326
TURN OFF HEATER
328
WAIT 15 SECONDS TURN OFF FAN
344
HEATER SETTING > THAN PRINT POWER ?
YES
NO
346
DECREMENT HEATER
336
EJECT PAGE
338
TURN OFF PRINT HEATER TURN OFF CROSSFLOW
340
WAIT FOR NEW PAGE
342
tidle >60 ?
YES
NO
B
C
348
MEDIUM EDGE AT MIDPOINT OF SCREEN ?
YES
NO
352
MEDIUM EDGE AT STAR WHEELS ?
YES
NO
350
SET FAN AT MIDPOINT SPEED
354
SET FAN AT MAXIMUM SPEED FOR MEDIUM

FIG. 5B

FIG.6






FIG.7




FIG.9




FIG.8

FIG. 10




70
70D
70C
70C
70C
70C
70C

FIG. 11


92
93
94
146
142
62
100A
170
171
172
100



142
144
62D
140
156
152
13
13
146
166
62B
114
62C
166
62
62A
164
62E
162
160
158
154

FIG. 12



62
62A
114
166

FIG. 13




FIG. 14




FIG. 15





FIG. 16

FIG. 17


90
MOTOR
91
SENSOR
118
POWER MEASURE-MENT
72
PRINT HEATER LAMP
CROSS-FLOW FAN MOTOR DRIVER
LAMP DRIVE
PREHEAT BULB
114
110
D/A
A/D
D/A
A/D
120
SENSOR
A/D
MICROPROCESSOR
D/A
LAMP DRIVE
POWER MEASUREMENT
116
92
MOTOR
D/A
A/D
A/D
132
MEDIA SELECT SWITCH
130
HOST COMPUTER
THERMISTOR
112

REGISTER ENTRY FOR EP0568272

European Application No EP93303155.1 filing date 22.04.1993

Priority claimed:
01.05.1992 in United States of America - doc: 878186

Designated States DE ES FR GB IT

Title PREHEAT ROLLER FOR THERMAL INK-JET PRINTER.

Applicant/Proprietor
HEWLETT-PACKARD COMPANY, 3000 Hanover Street, Palo Alto, California 94304, United States of America [ADP No. 50014570004]

Inventors
TODD R. MEDIN, 2875 Zeise Court, Escondido, CA 92027, United States of America [ADP No. 61364212001]

RICHARD A. BECKER, 11033 Morning Creek Drive S., San Diego, CA 92128, United States of America [ADP No. 61365748001]

BRENT W. RICHTSMEIER, 5695 Regis Avenue, San Diego, CA 92120, United States of America [ADP No. 61364220001]

Classified to
B41J

Address for Service
WILLIAMS,POWELL & ASSOCIATES, 34 Tavistock Street, LONDON, WC2E 7PB, United Kingdom [ADP No. 05830310001]

EPO Representative
STEPHEN DAVID POWELL, WILLIAMS, POWELL & ASSOCIATES 34 Tavistock Street, London WC2E 7PB, United Kingdom [ADP No. 50777671001]

Publication No EP0568272 dated 03.11.1993
Publication in English

Examination requested 14.04.1994

Patent Granted with effect from 10.07.1996 (Section 25(1)) with title PREHEAT ROLLER FOR THERMAL INK-JET PRINTER

**** END OF REGISTER ENTRY ****

RENEWAL DETAILS

PUBLICATION NUMBER EP0568272

PROPRIETOR(S)

Hewlett-Packard Company, 3000 Hanover Street, Palo Alto, California 94304, United States of America

DATE FILED 22.04.1993

DATE GRANTED 10.07.1996

DATE NEXT RENEWAL DUE 22.04.1997

DATE NOT IN FORCE

DATE OF LAST RENEWAL

YEAR OF LAST RENEWAL 00

STATUS PATENT IN FORCE

**** END OF REPORT ****