

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau

(43) International Publication Date

30 November 2017 (30.11.2017)



(10) International Publication Number

WO 2017/205264 A1

(51) International Patent Classification:

C11D 3/39 (2006.01) C11D 7/14 (2006.01)

C11D 17/04 (2006.01) C11D 3/04 (2006.01)

C11D 7/04 (2006.01) C11D 3/08 (2006.01)

C11D 7/12 (2006.01) C11D 3/10 (2006.01)

(21) International Application Number:

PCT/US2017/033785

(22) International Filing Date:

22 May 2017 (22.05.2017)

Published:

— with international search report (Art. 21(3))

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16171595.8 26 May 2016 (26.05.2016) EP

(71) Applicant: THE PROCTER & GAMBLE COMPANY

[US/US]; One Procter & Gamble Plaza, Cincinnati, Ohio 45202 (US).

(72) Inventors: LANT, Neil, Joseph; Procter & Gamble Tech-

nical Centres Limited, Whitley Road, Longbenton, Newcastle upon Tyne NE12 9TS (GB). SCIALLA, Stefano; Procter & Gamble, Temselaan 100, Strombeek-Bever, 1853 Brussels (BE). FULLER, Linsey, Sarah; Procter & Gamble Technical Centres Limited, Whitley Road, Longbenton, Newcastle upon Tyne NE12 9TS (GB). KEULEERS, Robby, Renilde Francois; Procter & Gamble, Temselaan 100, Strombeek-Bever, 1853 Brussels (BE). BROOKER, Alan, Thomas; Procter & Gamble Technical Centres Limited, Whitley Road, Longbenton, Newcastle upon Tyne NE12 9TS (GB).

(74) Agent: KREBS, Jay A.; c/o The Procter & Gamble Com-

pany, Global IP Services, One Procter & Gamble Plaza, C9, Cincinnati, Ohio 45202 (US).

(81) Designated States (unless otherwise indicated, for every

kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every

kind of regional protection available): ARIPO (BW, GH,

(54) Title: WATER-SOLUBLE UNIT DOSE ARTICLE COMPRISING A POWDER COMPOSITION

(57) Abstract: A water-soluble unit dose article comprising a water-soluble film and powder composition, wherein the powder composition comprises a) an acyl hydrazone bleach catalyst; b) from 1% to 10% by weight of the composition of an alkali metal carbonate; c) from 5% to 20% by weight of the composition of an alkali metal bicarbonate; d) from 5% to 20% by weight of the composition of an alkali metal silicate; e) from 5% to 20% by weight of the composition of an alkali metal sulphate.



WO 2017/205264 A1

WATER-SOLUBLE UNIT DOSE ARTICLE COMPRISING A POWDER COMPOSITION

FIELD OF THE INVENTION

The present invention related to water-soluble unit dose articles comprising a bleach
5 catalyst and methods of their use.

BACKGROUND OF THE INVENTION

Water-soluble unit dose articles are liked by consumers as being convenient and efficient
to use. They comprise a single unit dose of a cleaning or treatment composition that can be
10 added to water to create a suitable wash liquor.

Formulation of bleaching ingredients into the cleaning or treatment composition provides
beneficial cleaning benefits. However, such water-soluble unit dose articles can suffer from
premature activation of the bleach ingredients. This can detrimental affect the stability of the
water-soluble unit dose article by causing premature rupture of the unit dose article due to
15 bleaching species damaging the water-soluble film and/or the bleach species damaging other
formulation ingredients. Overall this negatively affects the consumer wash experience.

Therefore, there remains a need in the art for a water-soluble unit dose article comprising a
bleach ingredient wherein the instances of premature bleach activation are minimized.

It was surprisingly found that a water-soluble unit dose article according to the present
20 invention overcame this technical problem. The specific combination of a unit dose article
comprising a powder composition comprising a specific bleach catalyst and
carbonate/bicarbonate/silicate/sulphate system overcame this technical problem.

SUMMARY OF THE INVENTION

25 A first aspect of the present invention is a water-soluble unit dose article comprising a
water-soluble film and powder composition, wherein the powder composition comprises

- a. an acyl hydrazone bleach catalyst;
- b. from 1% to 10% by weight of the composition of an alkali metal carbonate;
- c. from 5% to 20% by weight of the composition of an alkali metal bicarbonate;
- d. from 5% to 20% by weight of the composition of an alkali metal silicate;
- e. from 5% to 20% by weight of the composition of an alkali metal sulphate.

A second aspect of the present invention is a process of washing fabrics comprising the steps of diluting a water-soluble unit dose article according to any preceding claims in sufficient water to dilute the first composition between 300 and 800 fold to form a wash liquor and contacting fabrics to be washed with said wash liquor.

DETAILED DESCRIPTION OF THE INVENTION

Water-soluble unit dose article

The water-soluble unit dose article comprises a water-soluble film and a powder composition. The water-soluble film and powder composition are described in more detail below.

The water-soluble unit dose article comprises at least one water-soluble film shaped such that the unit-dose article comprises at least one internal compartment surrounded by the water-soluble film. The at least one compartment comprises the powder composition. The water-soluble film is sealed such that the powder composition does not leak out of the compartment during storage. However, upon addition of the water-soluble unit dose article to water, the water-soluble film dissolves and releases the contents of the internal compartment into the wash liquor.

The compartment should be understood as meaning a closed internal space within the unit dose article, which holds the powder composition. The unit dose article is manufactured such that the water-soluble film completely surrounds the powder composition and in doing so defines the compartment in which the powder composition resides. The unit dose article may comprise two films. A first film may be shaped to comprise an open compartment into which the powder composition is added. A second film is then laid over the first film in such an orientation as to close the opening of the compartment. The first and second films are then sealed together along a seal region. The film is described in more detail below.

The unit dose article may comprise more than one compartment, even at least two compartments, or even at least three compartments. The compartments may be arranged in superposed orientation, i.e. one positioned on top of the other. Alternatively, the compartments may be positioned in a side-by-side orientation, i.e. one orientated next to the other. The compartments may even be orientated in a 'tyre and rim' arrangement, i.e. a first compartment is positioned next to a second compartment, but the first compartment at least partially surrounds the second compartment, but does not completely enclose the second compartment. Alternatively one compartment may be completely enclosed within another compartment.

Wherein the unit dose article comprises at least two compartments, one of the compartments may be smaller than the other compartment. Wherein the unit dose article comprises at least three compartments, two of the compartments may be smaller than the third compartment, and preferably the smaller compartments are superposed on the larger compartment. The superposed compartments preferably are orientated side-by-side.

The first and second compartments maybe positioned side-by-side to one another, preferably wherein the first and second compartments are separated by a bridge region. The 'bridge region' is comprised of the film material and separates the two compartments from one another but allows the first compartment to stay attached to the second compartment and vice versa.

In a multi-compartment orientation, the powder composition may be comprised in at least one of the compartments. It may for example be comprised in just one compartment, or may be comprised in two compartments, or even in three compartments.

Each compartment may comprise the same or different compositions. The different compositions could all be in the same form, or they may be in different forms.

Preferably, the unit dose article comprises at least a first internal compartment and a second internal compartment and wherein the first compartment comprises the powder composition and the second compartment preferably comprises a second composition wherein preferably the second composition is a liquid.

The unit dose article may comprise at least a first internal compartment and a second internal compartment and wherein the first compartment comprises the powder composition and the second compartment preferably comprises a second composition wherein preferably the second composition is a liquid. Preferably, the first and second compartments are positioned side-by-side to one another, preferably wherein the first and second compartments are separated by a bridge region.

Powder composition

The water-soluble unit dose article comprises a powder composition. By powder we herein mean a solid composition which may be compacted or free flowing. Preferably, the powder composition comprises free flowing granules.

The powder may have an average particle size diameter of between 100 microns and 1500 microns, preferably between 100 microns and 1000 microns, more preferably between 100 microns and 750 microns. Those skilled in the art will be aware of standard techniques to measure particle size.

The powder composition comprises and an acyl hydrazone bleach catalyst. The acyl hydrazone bleach catalyst is described in more detail below.

The powder composition comprises from 1% to 10%, preferably between 2% and 6% by weight of the composition of an alkali metal carbonate. The alkali metal may be selected from sodium, potassium, magnesium or a mixture thereof, preferably sodium.

The powder composition comprises from 5% to 20%, preferably between 8% and 15% by weight of the composition of an alkali metal bicarbonate. The alkali metal may be selected from sodium, potassium, magnesium or a mixture thereof, preferably sodium.

The powder composition comprises from 5% to 20%, preferably between 8% and 12% by weight of the composition of an alkali metal silicate. The alkali metal may be selected from sodium, potassium, magnesium or a mixture thereof, preferably sodium.

The powder composition comprises from 5% to 20%, preferably between 8% and 12% by weight of the composition of an alkali metal sulphate. The alkali metal may be selected from sodium, potassium, magnesium or a mixture thereof, preferably sodium.


The powder composition may comprise a source of hydrogen peroxide, wherein the hydrogen peroxide source is preferably selected from alkali metal perborates, alkali metal percarbonates, urea perhydrates, peroxydicarboxylic acids, alkali metal persulfates, alkali metal peroxydisulfates, Caroates, diacyl peroxides, tetraacyl diperoxides or a mixture thereof. The powder composition may comprise between 5% and 30%, preferably between 6% and 25%, more preferably between 7% and 20% by weight of the powder composition of the hydrogen peroxide source.

The powder composition may comprise TAED, soap, brightener, carboxymethylcellulose, enzymes, soil release polymer, surfactant, citrate, HEDP, 8-hydroxyquinoline sulphonic acid, dihydroxyterephthalic acid derivatives or a mixture thereof.

Acyl hydrazone bleach catalyst

The powder composition comprises an acyl hydrazone bleach catalyst. Preferably, the powder composition comprises between 0.001% and 1%, preferably between 0.01% and 0.75%, more preferably between 0.1% and 0.5% by weight of the powder composition of the acyl hydrazone bleach catalyst.

Preferably, the acyl hydrazone bleach catalyst has the formula I;



wherein, R¹ is selected from the groups comprising CF₃, C₁₋₂₈ alkyl, C₂₋₂₈ alkenyl, C₂₋₂₂ alkynyl, C₃₋₁₂ cycloalkyl, C₃₋₁₂ cycloalkenyl, phenyl, naphthyl, C₇₋₉ aralkyl, C₃₋


20 heteroalkyl, C₃₋₁₂ cycloheteroalkyl or a mixture thereof;

R² and R³ are independently selected from the group comprising hydrogen, substituted C₁₋₂₈ alkyl, C₂₋₂₈ alkenyl, C₂₋₂₂ alkynyl, C₃₋₁₂ cycloalkyl, C₃₋₁₂ cycloalkenyl, C₇₋₉ aralkyl, C₃₋₂₈ heteroalkyl, C₃₋₁₂ cycloheteroalkyl, C₅₋₁₆ heteroaralkyl, phenyl, naphthyl, heteroaryl or a mixture thereof;

or R² and R³ are linked to form a substituted 5-, 6-, 7-, 8- or 9-membered ring that optionally comprises heteroatoms;

and R⁴ is selected from the groups comprising hydrogen, C₁₋₂₈ alkyl, C₂₋₂₈ alkenyl, C₂₋₂₂ alkynyl, C₃₋₁₂ cycloalkyl, C₃₋₁₂ cycloalkenyl, C₇₋₉ aralkyl, C₃₋₂₀ heteroalkyl, C₃₋₁₂ cycloheteroalkyl, C₅₋₁₆ heteroaralkyl, substituted phenyl, naphthyl, heteroaryl or a mixture thereof.

More preferably, the acyl hydrazone bleach catalyst is 4-(2-(2-((2-hydroxyphenylmethyl)methylene)-hydrazinyl)-2-oxoethyl)-4-methylchloride having the formula II;



Acyl hydrazone bleach catalysts boost the bleaching action of peroxidic bleaching agents, without unduly damaging the substrate to be cleaned, for example the fabric. The peroxidic bleaching agents are preferably H₂O₂ or substances that release H₂O₂ in water, including in particular alkali metal perborates, alkali metal percarbonates and urea perhydrates; however, they
5 may be also possibly employed combined with peroxycarboxylic acids, such as diperoxydecanedicarboxylic acid or phthalimido peroxycaproic acid, with other acids or acidic

salts, such as alkali metal persulfates or alkali metal peroxydisulfates or Caroates, or with diacyl peroxides or tetraacyl diperoxides.

Acyl hydrazones may be processed into the detergent in the form of a granulate. The granulate may be a two-layer coated granulate comprising;

- 5 a) a core pellet comprising 5 to 40% by weight based on the weight of the total granule of an acyl hydrazone of formula (I) and 1-10% by weight based on the weight of the total granule of water and/or water soluble binder which is selected from the group consisting of polyvinylalcohols, polyvinylpyrrolidones, polyacrylates, cellulose derivatives, carbohydrates, polyethyleneglycols and mixtures thereof;
- 10 b) 0.1% to 25% by weight based on the weight of the total granule of a subcoating comprising a polymer mixture of hydroxypropylmethylcellulose (HPMC) and methylcellulose (MC) in a ratio by weight of from 2:1 to 8:1;
- c) 1 to 25% by weight based on the weight of the total granule of a topcoating comprising a fatty acid selected from nonadecanoic acid, stearic acid, palmitic acid, myristic acid and
15 mixtures thereof; and
- d) other components

the sum of components (a) to (d) adding to 100%.

Preferably, the acyl hydrazone bleach catalyst is comprised within a granule, wherein preferably the granule comprises between 5% and 40% by weight of the granule of the acyl hydrazone bleach catalyst.

Water-soluble film

The unit dose article comprises a water-soluble film. Preferably, the water-soluble film comprises a polyvinylalcohol.

The film of the present invention is soluble or dispersible in water. The water-soluble film preferably has a thickness of from 20 to 150 micron, preferably 35 to 125 micron, even
20 more preferably 50 to 110 micron.

Preferred film materials are preferably polymeric materials. The film material can, for example, be obtained by casting, blow-moulding, extrusion or blown extrusion of the polymeric material, as known in the art.

Preferred polymers, copolymers or derivatives thereof suitable for use as pouch material
25 are selected from polyvinyl alcohols, polyvinyl pyrrolidone, polyalkylene oxides, acrylamide, acrylic acid, cellulose, cellulose ethers, cellulose esters, cellulose amides, polyvinyl acetates, polycarboxylic acids and salts, polyaminoacids or peptides, polyamides, polyacrylamide,

copolymers of maleic/acrylic acids, polysaccharides including starch and gelatine, natural gums such as xanthum and carragum. More preferred polymers are selected from polyacrylates and water-soluble acrylate copolymers, methylcellulose, carboxymethylcellulose sodium, dextrin, ethylcellulose, hydroxyethyl cellulose, hydroxypropyl methylcellulose, maltodextrin,

5 polymethacrylates, and most preferably selected from polyvinyl alcohols, polyvinyl alcohol copolymers and hydroxypropyl methyl cellulose (HPMC), and combinations thereof. Preferably, the level of polymer in the pouch material, for example a PVA polymer, is at least 60%. The polymer can have any weight average molecular weight, preferably from about 1000 to 1,000,000, more preferably from about 10,000 to 300,000 yet more preferably from about 20,000
10 to 150,000.

Mixtures of polymers can also be used as the film material. This can be beneficial to control the mechanical and/or dissolution properties of the compartments or unit dose article, depending on the application thereof and the required needs. Suitable mixtures include for example mixtures wherein one polymer has a higher water-solubility than another polymer,
15 and/or one polymer has a higher mechanical strength than another polymer. Also suitable are mixtures of polymers having different weight average molecular weights, for example a mixture of PVA or a copolymer thereof of a weight average molecular weight of about 10,000- 40,000, preferably around 20,000, and of PVA or copolymer thereof, with a weight average molecular weight of about 100,000 to 300,000, preferably around 150,000. Also suitable herein are
20 polymer blend compositions, for example comprising hydrolytically degradable and water-soluble polymer blends such as polylactide and polyvinyl alcohol, obtained by mixing polylactide and polyvinyl alcohol, typically comprising about 1-35% by weight polylactide and about 65% to 99% by weight polyvinyl alcohol. Preferred for use herein are polymers which are from about 60% to about 98% hydrolysed, preferably about 80% to about 90% hydrolysed, to
25 improve the dissolution characteristics of the material.

Preferred films are those supplied by Monosol under the trade references M8630, M8900, M8779, M8310.

Of the total PVA resin content in the film described herein, the PVA resin can comprise 30 to 85 wt% of the first PVA polymer, or 45 to 55 wt% of the first PVA polymer. For example,
30 the PVA resin can contain about 50 w.% of each PVA polymer, wherein the viscosity of the first PVA polymer is about 13 cP and the viscosity of the second PVA polymer is about 23 cP.

Naturally, different film material and/or films of different thickness may be employed in making the compartments of the present invention. A benefit in selecting different films is that the resulting compartments may exhibit different solubility or release characteristics.

The film material herein can also comprise one or more additive ingredients. For example, it can be beneficial to add plasticisers, for example glycerol, ethylene glycol, diethyleneglycol, propylene glycol, sorbitol and mixtures thereof. Other additives may include water and functional detergent additives, including surfactant, to be delivered to the wash water, for example organic polymeric dispersants, etc.

The film may be opaque, transparent or translucent. The film may comprise a printed area. The printed area may cover between 10 and 80% of the surface of the film; or between 10 and 80% of the surface of the film that is in contact with the internal space of the compartment; or between 10 and 80% of the surface of the film and between 10 and 80% of the surface of the compartment.

The area of print may cover an uninterrupted portion of the film or it may cover parts thereof, i.e. comprise smaller areas of print, the sum of which represents between 10 and 80% of the surface of the film or the surface of the film in contact with the internal space of the compartment or both.

The area of print may comprise inks, pigments, dyes, blueing agents or mixtures thereof. The area of print may be opaque, translucent or transparent.

The area of print may comprise a single colour or maybe comprise multiple colours, even three colours. The area of print may comprise white, black, blue, red colours, or a mixture thereof. The print may be present as a layer on the surface of the film or may at least partially penetrate into the film. The film will comprise a first side and a second side. The area of print may be present on either side of the film, or be present on both sides of the film. Alternatively, the area of print may be at least partially comprised within the film itself.

The area of print may comprise an ink, wherein the ink comprises a pigment. The ink for printing onto the film has preferably a desired dispersion grade in water. The ink may be of any color including white, red, and black. The ink may be a water-based ink comprising from 10% to 80% or from 20% to 60% or from 25% to 45% per weight of water. The ink may comprise from 20% to 90% or from 40% to 80% or from 50% to 75% per weight of solid.

The ink may have a viscosity measured at 20°C with a shear rate of 1000s⁻¹ between 1 and 600 cPs or between 50 and 350 cPs or between 100 and 300 cPs or between 150 and 250 cPs.

The measurement may be obtained with a cone- plate geometry on a TA instruments AR-550 Rheometer.

The area of print may be achieved using standard techniques, such as flexographic printing or inkjet printing. Preferably, the area of print is achieved via flexographic printing, in which a film is printed, then moulded into the shape of an open compartment. This compartment

is then filled with a detergent composition and a second film placed over the compartment and sealed to the first film. The area of print may be on either or both sides of the film.

Alternatively, an ink or pigment may be added during the manufacture of the film such that all or at least part of the film is coloured.

5 The film may comprise an aversive agent, for example a bittering agent. Suitable bittering agents include, but are not limited to, naringin, sucrose octaacetate, quinine hydrochloride, denatonium benzoate, or mixtures thereof. Any suitable level of aversive agent may be used in the film. Suitable levels include, but are not limited to, 1 to 5000ppm, or even 100 to 2500ppm, or even 250 to 2000rpm.

Process of making

Those skilled in the art will be aware of standard methods and techniques to make the powder composition.

10 Those skilled in the art will be aware of standard techniques to make the unit dose article. Standard forming processes including but not limited to thermoforming and vacuum forming techniques may be used.

Method of washing

15 One aspect of the present invention is a process of washing fabrics comprising the steps of contacting the unit dose article of the present invention with sufficient water to dilute the powder composition between 300 and 800 fold to form a wash liquor, and contacting fabrics to be washed with said wash liquor.

20 The unit dose article of the present invention can be added to a wash liquor to which laundry is already present, or to which laundry is added. It may be used in an automatic washing machine operation and added directly to the drum or to the dispenser drawer. It may be used in combination with other laundry detergent compositions such as fabric softeners or stain removers.

25 The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

30

EXAMPLES


A unit dose article comprising a water-soluble PVOH film, preferably M8630 film commercially available from Monosol and between 7g and 10g of a free-flowing powder laundry cleaning or care composition comprising;

Ingredient	Wt% by weight of the laundry cleaning or care composition
Percarbonate	25%-35%
TAED	7%-12%
4-(2-(2-((2-hydroxyphenylmethyl)methylene)-hydrazinyl)-2-oxoethyl)-4-methylchloride	0.001%-1%
Soap	2%-5%
Brightener 49	0.01%-2%
Carboxymethylcellulose	5%-12%
Sodium carbonate	2%-6%
Sodium bicarbonate	6%-14%
Sodium silicate	6%-12%
Sulphate	6%-12%
Water	1%-4%
Enzymes, colourants, perfumes and other common laundry detergent ingredients	Up to 100%

CLAIMS

What is claimed is:

1. A water-soluble unit dose article comprising a water-soluble film and powder composition, wherein the powder composition comprises
 - a. an acyl hydrazone bleach catalyst;
 - b. from 1% to 10% by weight of the composition of an alkali metal carbonate;
 - c. from 5% to 20% by weight of the composition of an alkali metal bicarbonate;
 - d. from 5% to 20% by weight of the composition of an alkali metal silicate;
 - e. from 5% to 20% by weight of the composition of an alkali metal sulphate.
2. The water-soluble unit dose article according to claim 1 wherein the acyl hydrazone bleach catalyst has the formula I;



wherein, R¹ is selected from the groups comprising CF₃, C₁₋₂₈ alkyl, C₂₋₂₈ alkenyl, C₂₋₂₂ alkynyl, C₃₋₁₂ cycloalkyl, C₃₋₁₂ cycloalkenyl, phenyl, naphthyl, C₇₋₉ aralkyl, C₃₋


20 heteroalkyl, C₃₋₁₂ cycloheteroalkyl or a mixture thereof;

R² and R³ are independently selected from the group comprising hydrogen, substituted C₁₋₂₈ alkyl, C₂₋₂₈ alkenyl, C₂₋₂₂ alkynyl, C₃₋₁₂ cycloalkyl, C₃₋₁₂ cycloalkenyl, C₇₋₉ aralkyl, C₃₋₂₈ heteroalkyl, C₃₋₁₂ cycloheteroalkyl, C₅₋₁₆ heteroaralkyl, phenyl, naphthyl, heteroaryl or a mixture thereof;

or R² and R³ are linked to form a substituted 5-, 6-, 7-, 8- or 9-membered ring that optionally comprises heteroatoms;

and R⁴ is selected from the groups comprising hydrogen, C₁₋₂₈ alkyl, C₂₋₂₈ alkenyl, C₂₋₂₂ alkynyl, C₃₋₁₂ cycloalkyl, C₃₋₁₂ cycloalkenyl, C₇₋₉ aralkyl, C₃₋₂₀ heteroalkyl, C₃₋₁₂ cycloheteroalkyl, C₅₋₁₆ heteroaralkyl, substituted phenyl, naphthyl, heteroaryl or a mixture thereof.

3. The water-soluble unit dose article according to claim 2 wherein the acyl hydrazone bleach catalyst is 4-(2-(2-((2-hydroxyphenylmethyl)methylene)-hydrazinyl)-2-oxoethyl)-4-methylchloride having the formula II;



4. The water-soluble unit dose article according to any preceding claims wherein the first composition comprises between 0.001% and 1%, preferably between 0.01% and 0.75%, more preferably between 0.1% and 0.5% by weight of the composition of the acyl hydrazone bleach catalyst.
5. The water-soluble unit dose article according to any preceding claims comprising between 2% and 6% by weight of the composition of an alkali metal carbonate.
6. The water-soluble unit dose article according to any preceding claims comprising between 8% and 15% by weight of the unit dose article of an alkali metal bicarbonate.
7. The water-soluble unit dose article according to any preceding claims comprising between 8% and 12% by weight of the unit dose article of an alkali metal silicate.
8. The water-soluble unit dose article according to any preceding claims comprising between 8% and 12% by weight of the unit dose article of an alkali metal sulphate.
9. The water-soluble unit dose article according to any preceding claims wherein the composition comprises a source of hydrogen peroxide, wherein the hydrogen peroxide source is preferably selected from alkali metal perborates, alkali metal percarbonates, urea perhydrates, peroxydicarboxylic acids, alkali metal persulfates, alkali metal peroxydisulfates, Caroates, diacyl peroxides, tetraacyl diperoxides or a mixture thereof, preferably comprising between 5% and 30%, preferably between 6% and 25%, more preferably between 7% and 20% by weight of the composition of the hydrogen peroxide source.

10. The water-soluble unit dose article according to any preceding claims wherein the composition comprises TAED, soap, brightener, carboxymethylcellulose, enzymes, soil release polymer, surfactant, citrate, HEDP, 8-hydroxyquinoline sulphonic acid, dihydroxyterephthalic acid derivatives or a mixture thereof.
11. The water-soluble unit dose article according to any preceding claims wherein the water-soluble film comprises a polyvinylalcohol.
12. The unit dose article according to any preceding claims comprising at least a first internal compartment and a second internal compartment and wherein the first compartment comprises the powder composition and the second compartment preferably comprises a second composition wherein preferably the second composition is a liquid.
13. The unit dose article according to claim 12, wherein the first and second compartments are positioned side-by-side to one another, preferably wherein the first and second compartments are separated by a bridge region.
14. A process of washing fabrics comprising the steps of diluting a water-soluble unit dose article according to any preceding claims in sufficient water to dilute the powder composition between 300 and 800 fold to form a wash liquor and contacting fabrics to be washed with said wash liquor.

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2017/033785

A. CLASSIFICATION OF SUBJECT MATTER INV. C11D3/39 C11D17/04 C11D7/04 C11D7/12 C11D7/14 C11D3/04 C11D3/08 C11D3/10 ADD. According to International Patent Classification (IPC) or to both national classification and IPC											
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) C11D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal											
C. DOCUMENTS CONSIDERED TO BE RELEVANT <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%; padding: 5px;">Category*</th> <th style="width: 70%; padding: 5px;">Citation of document, with indication, where appropriate, of the relevant passages</th> <th style="width: 20%; padding: 5px;">Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">X</td> <td style="padding: 5px;">DE 10 2014 223360 A1 (HENKEL AG & CO KGAA) 19 May 2016 (2016-05-19)</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-14</td> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">Y</td> <td style="padding: 5px;"> paragraphs [0003], [0006], [0011] - [0016], [0019], [0025] - [0030], [0033], [0036], [0047], [0048] pages 12-13, paragraph 57; claims 1-8, 10; example 1; table 1 ----- -/-- </td> <td style="text-align: center; vertical-align: top; padding: 5px;">1-10,14</td> </tr> </tbody> </table>			Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	X	DE 10 2014 223360 A1 (HENKEL AG & CO KGAA) 19 May 2016 (2016-05-19)	1-14	Y	paragraphs [0003], [0006], [0011] - [0016], [0019], [0025] - [0030], [0033], [0036], [0047], [0048] pages 12-13, paragraph 57; claims 1-8, 10; example 1; table 1 ----- -/--	1-10,14
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.									
X	DE 10 2014 223360 A1 (HENKEL AG & CO KGAA) 19 May 2016 (2016-05-19)	1-14									
Y	paragraphs [0003], [0006], [0011] - [0016], [0019], [0025] - [0030], [0033], [0036], [0047], [0048] pages 12-13, paragraph 57; claims 1-8, 10; example 1; table 1 ----- -/--	1-10,14									
☒ Further documents are listed in the continuation of Box C. ☒ See patent family annex.											
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family											
Date of the actual completion of the international search 7 July 2017	Date of mailing of the international search report 14/07/2017										
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Kanbier, Titia										

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2017/033785

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2012/080088 A1 (BASF SE; HENKEL AG & CO KGAA) 21 June 2012 (2012-06-21)	1-10,14
Y	page 1, lines 23-35 page 7, lines 1-9 page 8, line 13 - page 9, line 27 page 13, lines 20-34 page 14, lines 4-8 page 15, lines 29-37 page 16, lines 29-36 page 22, lines 4-8,34-40 page 23, lines 35-39 page 24, lines 25-36 page 26, lines 6-7 -----	1-10,14
Y	WO 2015/169851 A1 (BASF SE; HENKEL AG & CO KGAA) 12 November 2015 (2015-11-12) page 1, lines 21-39; claim 1 page 6, lines 1-8 page 9, lines 1-15 page 10, lines 5-13,35-43 page 11, lines 33-39; claims 12-13 -----	1-10,14
Y	WO 2007/087258 A2 (PROCTER & GAMBLE) 2 August 2007 (2007-08-02) pages 24,53,59; claims 1,6,11,12,14-22; examples XVA,XXIIIE,XXIVC -----	1,5, 7-10,14
Y	WO 01/16274 A1 (PROCTER & GAMBLE) 8 March 2001 (2001-03-08) page 3, lines 17-23 pages 4-5; examples 3M-3R -----	1,5-10, 14
A	WO 2011/127102 A1 (PROCTER & GAMBLE) 13 October 2011 (2011-10-13) page 1, line 22 - page 2, line 12; claims 1,13,16 page 15, lines 10-15 page 17, lines 27-32 -----	1,4,9-14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2017/033785

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 102014223360 A1	19-05-2016	DE 102014223360 A1	19-05-2016
		WO 2016078913 A1	26-05-2016
WO 2012080088 A1	21-06-2012	AU 2011344415 A1	04-07-2013
		BR 112013014591 A2	19-07-2016
		CN 103328455 A	25-09-2013
		EP 2651907 A1	23-10-2013
		EP 2805942 A1	26-11-2014
		ES 2524734 T3	11-12-2014
		ES 2576504 T3	07-07-2016
		JP 5923109 B2	24-05-2016
		JP 6081640 B2	15-02-2017
		JP 2014501230 A	20-01-2014
		JP 2016166226 A	15-09-2016
		KR 20140031853 A	13-03-2014
		PL 2805942 T3	30-09-2016
		RU 2013132311 A	20-01-2015
		US 2013261041 A1	03-10-2013
		US 2015225357 A1	13-08-2015
		US 2016136627 A1	19-05-2016
		WO 2012080088 A1	21-06-2012
WO 2015169851 A1	12-11-2015	EP 3140382 A1	15-03-2017
		KR 20170003922 A	10-01-2017
		US 2017175048 A1	22-06-2017
		WO 2015169851 A1	12-11-2015
WO 2007087258 A2	02-08-2007	AR 059153 A1	12-03-2008
		CA 2635946 A1	02-08-2007
		CN 101484565 A	15-07-2009
		EP 1979457 A2	15-10-2008
		JP 2009523904 A	25-06-2009
		US 2007173429 A1	26-07-2007
		WO 2007087258 A2	02-08-2007
WO 0116274 A1	08-03-2001	AR 027846 A1	16-04-2003
		AT 311432 T	15-12-2005
		AU 7072100 A	26-03-2001
		BR 0014151 A	07-05-2002
		CA 2382023 A1	08-03-2001
		CN 1384868 A	11-12-2002
		CZ 20020722 A3	16-10-2002
		DE 60024463 D1	05-01-2006
		DE 60024463 T2	17-08-2006
		EG 22867 A	30-09-2003
		EP 1206519 A1	22-05-2002
		ES 2252054 T3	16-05-2006
		JP 2003508585 A	04-03-2003
		MA 25602 A1	31-12-2002
		MX PA02002128 A	02-09-2002
		TR 200200471 T2	21-05-2002
		WO 0116274 A1	08-03-2001
WO 2011127102 A1	13-10-2011	AR 080838 A1	09-05-2012
		BR 112012025395 A2	28-06-2016
		CA 2795176 A1	13-10-2011
		CN 102869760 A	09-01-2013
		EP 2556140 A1	13-02-2013

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2017/033785

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		JP 5863767 B2	17-02-2016
		JP 2013523976 A	17-06-2013
		RU 2012142725 A	20-05-2014
		US 2011240510 A1	06-10-2011
		WO 2011127102 A1	13-10-2011
		ZA 201207401 B	23-12-2013
