



(11) (21) (C) **2,132,682**
(22) 1994/09/22
(43) 1995/03/25
(45) 2000/04/18

- (72) Koenhen, Dirk Marinus, NL
(72) Roesink, Hendrik Dirk Willem, NL
(72) Wenten, Gede, ID
(72) Rasmussen, Alan, DK
(72) Jonsson, Gunnar, DK
(73) X-Flow B.V., NL

(51) Int.Cl.⁵ B01D 61/14

(30) 1993/09/24 (9301653) NL

(54) **METHODE SERVANT A EXTRAIRE D'UN FLUIDE LES
ELEMENTS PRODUISANT DE LA TURBIDITE, AU MOYEN
DE LA MICROFILTRATION**

(54) **METHOD FOR THE REMOVAL OF COMPONENTS CAUSING
TURBIDITY, FROM A FLUID, BY MEANS OF
MICROFILTRATION**

(57) The invention relates to a process for the removal of components causing turbidity, from a fluid, by means of micro-filtration, whereby the fluid is beer, wine, fruit juice, bacterial suspension, blood, milk, enzyme suspension, etc. According to the invention the fluid to be treated is fed across an asymmetric membrane having a pore structure such that the pores on the feed side of the membrane are larger than the nominal pore size and the pores of nominal pore size occur in the cross section toward the permeate side, the filtered off components are back-flushed from the membrane and are subsequently carried away with the fluid. The nominal pore size is usually 0.1-5.0 μm and preferably 0.2-1.0 μm . The membrane may be tubular, flat or capillary. Back-flushing takes place intermittently with a frequency of 1 second to 10 minutes for 0.1-1 second at a counter pressure of 0.5-5 bar. The feed velocity is preferably below 2 m/s and the pressure difference over the membrane is less than 0.5 bar.



2132682

ABSTRACT

5 The invention relates to a process for the removal of components causing turbidity, from a fluid, by means of micro-filtration, whereby the fluid is beer, wine, fruit juice, bacterial suspension, blood, milk, enzyme suspension, etc.

10 According to the invention the fluid to be treated is fed across an asymmetric membrane having a pore structure such that the pores on the feed side of the membrane are larger than the nominal pore size and the pores of nominal pore size occur in the cross section toward the permeate side, the filtered off components are back-flushed from the membrane and
15 are subsequently carried away with the fluid. The nominal pore size is usually 0.1-5.0 μm and preferably 0.2-1.0 μm . The membrane may be tubular, flat or capillary. Back-flushing takes place intermittently with a frequency of 1 second to 10 minutes for 0.1-1 second at a counter pressure of 0.5-5 bar.
20 The feed velocity is preferably below 2 m/s and the pressure difference over the membrane is less than 0.5 bar.

Method for the removal of components causing turbidity, from a fluid, by means of microfiltration

The present invention relates to a method for the removal of components that cause turbidity, from a fluid, by means of microfiltration.

The application of microfiltration whereby by
5 maintaining a flow along the membrane wall, it is attempted to prevent accumulation of dirt, is a known technique. This technique is generally called crossflow microfiltration.

In practice this technique is applied in, for instance, ultrafiltration and microfiltration.

10 Effective velocities to prevent the build-up of a fouling layer often begin at 2 m/s while as a rule velocities from 4-6 m/s are used.

Dependent on the membrane configuration this is the range where turbulence in the flow occurs.

15 It should be noted that the technique of back-flushing membranes was introduced by Klein and Schneider for self-supporting capillary membranes (Desalination 41 (1982 263-275) whereby microfiltration membranes were applied with a pore size of above 0.01 μm . For further prior art reference is made
20 to "Microfiltration mit Membranen" by S. Ripperger (ISBN 3-527-28457-5, 1992).

In the above-mentioned known techniques the back-flush is performed once every few minutes, giving a loss of production because part of the permeate is pushed back to the
25 concentrate side of the membrane. A special technique is used by Memtec, who back-flush the membrane with gas (AU-B-34.400/-84). The fastest back-flush intervals are recorded in DK-A-476/90 (APV Pasilac).

Here back-flush frequencies are recorded of 1-10
30 back-flushes per minute at a back-flush duration of 1-5 seconds. One thing and another results in the fact, that due to these relative long back-flushing times the installation is not in use for filtration for 10-20% of the time.

A disadvantage of the known membrane is that it suffers a productivity drop due to the formation of a so-called
35 secondary membrane, consisting of a packing of particles to be

filtered off, which partly plug the pores and as layer shows only a limited "own" permeability.

The object of the invention is to provide a method with practically no productivity drop because the thickness of the layer of particles to be filtered off is limited and the secondary membrane is disturbed.

To this end, the present invention provides a process for the removal of components causing turbidity, from a fluid, by means of cross-flow microfiltration, **characterized** in that the fluid is fed across an asymmetric membrane having a pore structure such that the pores on the feed side of the membrane are larger than the nominal pore size and the pores of nominal pore size occur in the cross section toward the permeate side, the filtered off components are back-flushed from the membrane and are subsequently carried away with the fluid.

The method according to the invention is especially suitable for the removal of components causing turbidity from beer, wine, fruit juice, bacterial suspension, blood, milk, enzyme suspension, etc.

As fruit juice are considered: cherry juice, apple juice, etc.

The present invention has been shown to be especially suitable for the treatment of beer, yielding a particularly clear beer, which beer in addition remains stable during a long storage time.

The asymmetric membrane used is preferably a membrane having a nominal pore size of 0.1-5.0 μm .

A membrane having a nominal pore size of 0.2-1.0 μm has proved to be especially suitable. Membranes which according to the invention meet the requirements very well are tubular, flat or capillary.

In the method according to the invention membranes are used that reject certain components, while in many cases it is of great importance that some other components will permeate through the membrane. This is especially important, for instance, for the clarification of beer. As already known, in the production of beer yeast is used, making the beer turbid

which is the reason why after the process the yeast must be removed from the beer. Apart from yeast the beer also contains precipitated proteins, which are also components responsible for poor beer quality. On the other hand beer also contains
5 components that must not be removed during filtration, which components are high molecular weight components attributing to the beer's taste, colour, foam stability, etc. Of course, the same also goes for wine and other fruit juices.

It is especially very important that the high molecular weight colloidal components permeate through during filtration of the fluid.
10

Surprisingly it was found, that the use of hydrophilic membranes of the type described in the US patents RE 34296 and 5,076,925 give excellent results. Naturally, the invention
15 is not limited to the above-mentioned membranes.

It has been shown that when using the method according to the invention particularly good results are obtained when the asymmetric membrane is intermittently back-flushed with a frequency of 1 second to 10 minutes for 0.1-1 second at
20 a counter pressure of 0.5-5 bar.

Intermittent back-flushing of the membrane can, for instance be realized by means of an electronic three-way valve, entirely controlled by computer. The back-flush medium used here is compressed air. Apart from compressed air other
25 suitable back-flush mediums may be used.

Good results are obtained when the fluid to be treated is brought in with a flow velocity below 2 m/s.

Surprisingly it was found, that the method according to the invention can be applied successfully if the pressure
30 difference over the membrane is less than 0.5 bar.

The invention will now be further elucidated by means of the following, non-limitative examples.

In Example I and II standard technology asymmetric ceramic membranes are used, whereby there is no back-flushing
35 in Example I. In Example II back-flushing does take place.

Examples III to IX relate to beer filtration using an asymmetric membrane according to the invention, while Examples X and XI relate to cherry juice filtration, also using an asymmetric membrane according to the invention.

EXAMPLE I

Unfiltered Carlsberg pilsner beer was subjected to filtration using an asymmetric ceramic membrane, whereby no back-flushing was carried out.

5 This ceramic membrane has a nominal pore size of 1.0 μm . The beer was supplied with a crossflow velocity of 0.5 m/s. The pressure difference over the membrane was 0.15 bar. Within 2 hours the flux of the membrane appeared to decline from 150 to 3 l/m²/h. This rapid flux decline renders such a
10 filtration system without back-flush unsuitable for beer filtration.

EXAMPLE II

Again unfiltered Carlsberg pilsner beer was filtered
15 using an asymmetric ceramic membrane, whereby back-flushing did take place.

The nominal pore size, crossflow velocity and pressure difference over the membrane are the same as in Example I. Back-flushing was carried out with an interval of 3
20 seconds, whereby each back-flush lasted 0.05 seconds. By using the same membrane as in Example I, but with back-flushing, the flux was shown to decline in 2 hours from 150 to 70 l/m²/h. This demonstrates clearly the favourable effect of back-flushing on the flux.

25

EXAMPLE III

Unfiltered Carlsberg pilsner beer was filtered using an asymmetric (X-Flow) membrane, however, without back-flushing.

30 The nominal pore size of the used asymmetric membrane was 0.66 μm , while the beer was supplied with a velocity of 0.5 m/s.

The pressure difference over the membrane was 1.0 bar. After 6 hours the flux was shown to have declined from
35 180 to 18 l/m²/h. 75% of proteins of high molecular weight were seen to have permeated.

EXAMPLE IV

Unfiltered Carlsberg pilsner beer was filtered using
40 an asymmetric (X-Flow) membrane.

The nominal pore size of the membrane was $0.66 \mu\text{m}$, while the beer was supplied with a velocity of 0.5 m/s .

The pressure difference over the membrane was 0.05 bar .

5 Back-flushing was carried out at an interval of 1 minute, while each back-flush lasted 5 seconds.

After 3 hours the flux was shown to have declined from 120 to $108 \text{ l/m}^2/\text{h}$.

10 EXAMPLE V

Unfiltered Carlsberg pilsner beer was filtered using an asymmetric (X-Flow) membrane, with back-flushing.

The pore size was $0.66 \mu\text{m}$, while the beer was supplied with a velocity of 0.5 m/s .

15 The pressure difference over the membrane was 0.05 bar .

Back-flushing was carried out every 3 seconds, while each back-flush lasted 0.05 seconds. Surprisingly it was shown that the flux remained constant for 3 days, at $230 \text{ l/m}^2/\text{h}$.

20 100% of the proteins of high molecular weight had permeated.

EXAMPLE VI

400 liters beer containing yeast rests (unfiltered Carlsberg pilsner) were filtered. It took 124 minutes to obtain 300 liters permeate. The membrane surface measured 1 m^2 and the transmembrane pressure, the feed pressure was 0.04 to 0.08 bar , productivity was maintained around $150 \text{ l/m}^2/\text{h}$. The crossflow velocity was 0.5 m/s .

30 Every 5 seconds a back-flush pulse was given with a pressure of about 1.5 bar lasting less than 0.1 second. The temperature of the beer was 0°C . The nominal pore size of the membrane was $0.6 \mu\text{m}$.

The data show that high velocity back-flushing has a tremendously good effect on the constancy of the membrane productivity. In standardized figures this is $1875 \text{ l/m}^2/\text{h}/\text{bar}$.

EXAMPLE VII

The membrane of Example VI was applied with a nominal pore size of $0.6 \mu\text{m}$.

In a similar experiment using a crossflow velocity of 2.3 m/s and a pressure of 2 bar an average flux of 80 l/m²/h was achieved without back-flushing, but under otherwise the same conditions. Standardized this means a productivity of 40.

5

EXAMPLE VIII

In this Example the same membrane was used as in Examples VI and VII.

In the same situation as above a flux was obtained of 30 l/m²/h/bar.

EXAMPLE IX

In this Example the same membrane was used as in Example VI and VII.

By back-flushing in the conventional manner every 5 minutes for 5 seconds a flux was obtained of 80 l/m²/h/bar.

EXAMPLE X

This Example relates to the filtration of cherry juice using an asymmetric (X-Flow) membrane without back-flushing.

The nominal pore size of the membrane was 0.51 μm, while the cheery juice was supplied with a velocity of 0.5 m/s.

The pressure difference over the membrane was 0.5. After 2 hours the flux was shown to decline from 120 to 5 l/m²/h.

EXAMPLE XI

Cherry juice was filtered by means of an asymmetric (X-Flow) membrane as in Example X, but with back-flushing.

The nominal pore size of the membrane was 0.51 μm, while the cherry juice was supplied with a velocity of 0.5 m/s.

The pressure difference over the membrane was 0.5. Back-flushing took place every 3 seconds, every time flushing for 0.05 seconds.

After 2 hours the flux was shown to have declined from 120 to 80 l/m²/h.

40

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A process for the removal of components causing turbidity, from a fluid, by means of cross-flow microfiltration, **characterized** in that the fluid is fed across an asymmetric membrane having a pore structure such that the pores on the feed side of the membrane are larger than the nominal pore size and the pores of nominal pore size occur in the cross section toward the permeate side, the filtered off components are back-flushed from the membrane and are subsequently carried away with the fluid.

2. A process according to claim 1, **characterized** in that the fluid is selected from the group including beer, wine, fruit juice, bacterial suspension, blood, milk and enzyme suspension.

3. A process according to claim 1 or 2, **characterized** in that the fluid is beer.

4. A process according to claims 1-3, **characterized** in that the asymmetric membrane used is a microporous membrane having a nominal pore size of 0.1-5.0 μm .

5. A process according to claim 4, **characterized** in that the nominal pore size is 0.2-1.0 μm .

6. A process according to claims 1-5, **characterized** in that the membrane is tubular, flat or capillary.

7. A process according to claims 1-6, **characterized** in that back-flushing of the membrane takes place intermittently with a frequency of 1 second to 10 minutes for 0.1-1 second at a counter pressure of 0.5-5 bar.

8. A process according to claim 7, **characterized** in that the feed velocity is below 2 m/s.

9. A process according to claims 1-8, **characterized** in that the pressure difference over the membrane is less than 0.5 bar.