

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number
WO 2004/013400 A1

(51) International Patent Classification⁷: **D06C 15/02**, 3/00

(21) International Application Number:
PCT/US2003/023884

(22) International Filing Date: 31 July 2003 (31.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0217909.1 1 August 2002 (01.08.2002) GB

(71) Applicant: **E. I. DU PONT DE NEMOURS AND COMPANY** [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor: **WOODS, Malcolm**; 19 Justicia Way, Up Hatherley, Cheltenham GL51 3YH (GB).

(74) Agent: **HAMBY, Jane, O.**; E. I. Du Pont De Nemours and Company, Legal Patent Records Center, 4417 Lancaster Pike, Wilmington, DE 19805 (US).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CHINTZED STRETCH FABRICS

(57) Abstract: The invention provides stretch fabrics and articles from the fabrics comprising at least a region consisting of a single thickness of the fabric. The fabric comprises synthetic bicomponent polymer filaments, wherein the fabric has been calendered on at least one surface thereof to obtain a chintzed appearance. The fabric has an air permeability of less than 6 cubic centimeters per second per square centimeter, (cm³/cm²/sec), at 10 millimeters water gauge pressure.



TITLE OF INVENTION

CHINTZED STRETCH FABRICS

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a process for improving the stretch performance of fabrics, and to garments and other articles comprising improved fabrics produced by this process.

Description of the Related Art

In apparel applications, stretch fabrics of woven construction are known. However, none of these known fabrics is suited for outwear applications such as in light-weight fabric shells or in fabrics where low air permeability is desired. A particularly well-suited yarn for making woven stretch fabrics is *T-400™ Next Generation Fiber* from E. I. du Pont de Nemours and Company of Wilmington, Delaware (hereinafter referred to as "DuPont"). This yarn, T-400™, is a self-crimping bicomponent polyester which brings elastification to fabrics without the use of spandex core filaments in the yarn.

SUMMARY OF THE INVENTION

The present inventors have found, surprisingly, that a fabric comprising a portion of synthetic polymer bicomponent filaments, especially T-400™ fiber, retains a high level of stretch and recovery while retaining a low level of air permeability achieved by calendering ("chintzing"). Calendering is a known technique for improving the wind resistance of certain fabrics through decreased air permeability, and for reducing the leakage of fibers through a fabric from a fibrous insulation layer. However, calendering has not hitherto been applied for the improvement of these properties when used in combination with stretch fabrics and especially fabrics from fibers which self-crimp due to their bicomponent structure.

It is an object of the present invention to provide fabrics comprising a portion of self-crimping bicomponent filament yarns wherein such fabrics have a chintzed appearance obtained by calendering. At the same time, a fabric stretch and recovery property is imparted through the function of self-crimping bicomponent filament yarns which is

not sacrificed as a result of calendering.

It is a further object of the present invention to provide fabrics exhibiting high stretch and low air permeability, or wind resistance, simultaneously.

In a first aspect, the present invention provides a fabric comprising at least a region consisting of a single thickness of a fabric, wherein the fabric comprises synthetic polymer bicomponent filaments, the fabric having been chintzed on at least one surface thereof. The chintzed fabric is further characterized by an air permeability, determined as hereinafter described, of less than 6 cubic centimeters per second per square centimeter, ($\text{cm}^3/\text{cm}^2/\text{sec}$), at 10 millimeters water gauge pressure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferably, the fabric consists substantially of a single thickness of the fabric, for example a single thickness article or garment. In certain embodiments, the fabric is chintzed on only one side, and this side may be the side of the garment that is worn next to the body. The term "single thickness" refers to a single woven textile filaments. Preferably, the fabric has a weight in the range of 20 to 400 grams/ m^2 , more preferably 50 to 200 grams/ m^2 . Preferably, the fabric has an air permeability, determined as hereinafter described, of less than 6 cubic centimeters per second per square centimeter, ($\text{cm}^3/\text{cm}^2/\text{sec}$), at 10 millimeters water gauge pressure. More preferably, the fabric air permeability is less than 2 $\text{cm}^3/\text{cm}^2/\text{sec}$.

The fabric comprises synthetic filaments, and preferably it consists of synthetic-bicomponent filaments. The fibers of the invention are termed "bicomponent" fibers and are comprised of at least two polymers adhered to each other along the length of the fiber, each polymer being of the same generic class, e.g., polyamide polyester. Bicomponent fibers within the scope of the invention are melt spun from molten polymers of the same generic class and may be prepared using pre-coalescence or post-coalescence spinneret plates of the type known in the art. Preferably, the synthetic bicomponent filament component polymers are thermoplastic; more preferably, the synthetic bicomponent filaments are melt spun, and most preferably the component polymers are selected from the group consisting of polyesters and polyamides. The preferred polyester component polymers include polyethylene terephthalate (PET), polytrimethylene terephthalate (PTT) and polytetraethylene terephthalate.

Preferred polyamide component polymers are nylon 6, nylon 66, nylon 46, nylon 7, nylon 10, nylon 11, nylon 1610, nylon 612, nylon 12 and mixtures and copolyamides thereof. Especially preferred copolyamides include nylon 66 with up to 40 mole per cent of a polyadipamide wherein the aliphatic diamine component is selected from the group of DYTEK A® and DYTPK EP®. Both of these diamines are available from DuPont. The more preferred polyester bicomponent filaments comprise a portion of PET polymer and a portion of PTT polymer, both portions of polymers are in a side-by-side relationship as viewed in the cross section of the individual filament. An especially advantageous filament yarn meeting this description of the more preferred polyester bicomponent is *T-400™ Next Generation Fiber* from DuPont. The more preferred polyamide bicomponent filaments comprise a portion of nylon 66 polymer or copolyamide having a first relative viscosity and a portion of nylon 66 polymer or copolyamide having a second relative viscosity, wherein both portions of polymer or copolyamide are in a side-by-side relationship as viewed in the cross section of the individual filament.

Preferably, the synthetic filaments comprise a UV absorbent material, and more preferably they comprise titanium dioxide particles. Preferred TiO₂ particles are of a size to function also as a delusterant (preferably 0.3 to 1 micrometer) and preferably they are present at a weight concentration of from 0.1 to 4 wt.%, more preferably from 0.5 to 3 wt.%. Alternatively or additionally, the polymers may include other additives, for example ultraviolet light absorption, such as: CYASORB® UV-3346, -1164, -3638, -5411; and TINUVIN® 234 in amounts of about 0.1 to 0.3 percent by weight.

The fabric in the garments according to the invention is calendered on at least one side. Calendering (chintzing) of fabrics is performed by applying heat and pressure to at least one surface of the fabric. Calendered surfaces are readily identified by the characteristic plastic deformation of the surface. The calendering temperature is preferably maintained in a range from 140°C to 195°C. The calendering temperature is more preferably maintained at 150°C. The calendering pressure is preferably 50 tonnes/sq. inch (6.5×10^6 N/m²) (+/- 10%) and the calendering is preferably performed at a speed in a range from 4 to 24 meters per minute, and preferably in the range of 8 to 14 meters per minute.

Calendering is preferably carried out using a two roll nip. A first roll of the nip is typically a hard, smooth heated surface such as

heated stainless steel. A second roll is typically unheated and often covered with nylon/wool or optionally paper covered. Calendering equipment of this type is available from Kusters Textile Machinery Corporation, of Spartanburg, South Carolina.

As will be illustrated in more detail by the examples below, the present inventors have found a reduction in the air permeability of the fabrics of the invention as a direct result of calendering achieved without a sacrifice in the stretch and recovery of the fabric. It is surprising that the stretch properties of these fabrics and the chintz finish obtained through calendering are strongly expressed and independently achievable in the final fabric. This observation of fabric property independence after calendering is heretofore unknown and contrary to what the skilled person would predict concerning the maintaining of fabric stretch after a calendering process.

Specific embodiments and procedures of the present invention will now be described further, by way of example, as follows.

Measurement of Fabric Stretch

Fabric stretch and recovery for a stretch woven fabric is determined using an INSTRON universal electromechanical test and data acquisition system (available from: Instron Corp, 100 Royall Street, Canton, Massachusetts, 02021 USA) to perform a constant rate of extension tensile test.

Two fabric properties are measured using the INSTRON: available fabric stretch and the fabric growth. The available fabric stretch is the amount of elongation caused by a specific load between 0 and 30 Newtons and expressed as a percentage change in length of the original fabric specimen as it is stretched at a rate of 300 mm per minute. The fabric growth is the unrecovered length of a fabric specimen which has been held at 80% of available fabric stretch for 30 minutes then allowed to relax for 60 minutes. Where 80% of available fabric stretch is greater than 35% of the fabric elongation, this test is limited to 35% elongation. The fabric growth is then expressed as a percentage of the original length.

The elongation or maximum stretch of stretch woven fabrics in the stretch direction is determined using a 3 cycle test procedure. The maximum elongation measured is the ratio of the maximum extension of

the test specimen to the initial sample length found in the third test cycle at load of 30 Newtons. This third cycle value corresponds to hand elongation of the fabric specimen. This test is performed using the INSTRON tensile tester specifically equipped for the three cycle test.

Measurement of Fabric Air Permeability

Air permeability of the fabric was measured using a Shirley Air Permeability Tester, model M021, available from:

Shirley Developments Ltd.

PO Sox 6,

856 Wilmslow Road

Manchester M20 BSA England

This instrument, and the associated method of operation provided by the manufacturer, were designed to meet British Standard BS.5636:1978. This differs from the later standard BS EN ISO 9237:1995 essentially only in the units used for expressing airflow (cubic centimeters per second, instead of cubic decimeters per minute), air pressure (millimeters water gauge, instead of Pascals) and the final calculated permeability (cubic centimeters of air per second per square centimeter of fabric area, instead of millimeters per second).

The principle of the test method is to measure the flow of air drawn through a given area of fabric under a specific pressure difference. On this particular instrument, the circular sample area has an area of 5.07 square centimeters. Final results are calculated for an area of one square centimeter. Measurements were made at a pressure of 10 mm water gauge, and the final permeability results quoted are for this specific differential pressure. A feature of the instrument is that it has a "guard ring device" around the sample area, as mentioned as an option in BS EN ISO 9237 :1995, to prevent air leakage through the edges of the sample; this feature was used during the measurements.

The instrument is calibrated once per year, as recommended in BS EN ISO 9237 1995, and is checked against capillary resistance standards each time before use.

Briefly, the method is as follows.

Fabric was conditioned adjacent to the instrument for a period exceeding 16 hours, at the standard laboratory conditions of 20°C, +/- 2°C, and a relative humidity of 65%, +/- 5%. The fabric was laid across

the sample holder, flat without creasing, but also without stretching, and then clamped in place. The differential pressure across the fabric was adjusted to 10 mm water gauge. The differential pressure through the guard ring was also adjusted to 10 mm water gauge. This affects the fabric pressure slightly, so that continuing fine adjustments were made until both pressure gauges indicated 10 mm of water. The air flow through the fabric was then read from the flow meter, in cubic centimeters per second. This constitutes one measurement. A total of 10 separate measurements were made, each one on a different part of the fabric. Finally, the recorded air flows were divided by 5.07 (to reduce them to flow per square centimeter), and the mean value and standard deviation were calculated.

Final permeability was expressed in units of cubic centimeters of air per square centimeter of fabric area per second, ($\text{cm}^3/\text{cm}^2/\text{sec}$) at a differential pressure of 10 mm water gauge.

EXAMPLE OF THE INVENTION

Fabrics were woven on a Sulzer Ruti 5100 air-jet loom, with a standard nylon 66 warp of 44 decitex and 34 filaments (known as T6342 yarn, available from DuPont); this yarn was fully dull containing 1.55 weight % TiO_2 . The weft yarn was an 83 decitex (34 filaments) T-400™ (DP002) elastic polyester yarn from DuPont. Fabric construction was 55 warp threads per centimeter and 49 weft threads per centimeter in the loom. The fabrics were scoured and calendered to a woven intensity of 58/cm x 51/cm. The calendering process was carried out using a two roll nip from Kusters Textile Machinery Corporation. The first roll of the nip was heated stainless steel and the second roll was unheated and covered with nylon/wool. The calendering temperature was 150°C. The calendering pressure was about 50 tonnes/sq.inch ($6.5 \times 10^6 \text{ N/m}^2$) (+/- 10%), and the calendering was performed at a speed of 12 meters per minute.

The measured stretch available and stretch growth along with the air permeability values are reported in the following Table. This fabric had a chintz finish and a low air permeability, yet retained a high stretch (ca. 20%) and recovery property entirely suitable for use in stretch fabric applications.

TABLE

Permeability to air determined a hereinbefore described	1.04 cm ³ /m ² /sec (Standard deviation, 0.19) @ 10 mm water differential pressure
Available fabric stretch	20.19%
Fabric stretch growth (percent unrecovered stretch)	2.9%

The example is for the purpose of illustration only. Many other embodiments falling within the scope of the accompanying claims will be apparent to the skilled person.

CLAIMS

What is claimed is:

1. A fabric comprising synthetic bicomponent filaments, wherein the fabric has been calendered on at least one surface thereof and the fabric has an air permeability, determined as hereinbefore described, of less than 6 cubic centimeters per second per square centimeter. ($\text{cm}^3/\text{cm}^2/\text{sec}$), measured at a static pressure of 10 millimeters of water.
2. A fabric according to Claim 1, wherein the fabric has a weight of less than 400 grams/ m^2 , preferably 20 to 200 grams/ m^2 .
3. A fabric according to Claim 1, wherein the synthetic bicomponent filaments are selected from the group consisting of polyester filaments, polyamide filaments and mixtures thereof.
4. A fabric according to Claim 1, wherein the synthetic bicomponent filaments comprise polymers selected from the group consisting of polyethylene terephthalate, polytrimethylene terephthalate and polytetraethylene terephthalate.
5. A fabric according to Claim 1, wherein the synthetic bicomponent filaments comprise polymers selected from the group consisting of nylon 6, nylon 66, nylon 46, nylon 7, nylon 10, nylon 11, nylon 610, nylon 612, nylon 12 and mixtures and copolyamides thereof.
6. A fabric according to Claim 1, wherein at least a portion of the synthetic filaments comprises a UV absorbent additive.
7. A fabric according to Claim 6, wherein the UV absorbent additive comprises titanium dioxide particles at a weight concentration of from 0.1 to 4 wt. %, preferably from 1 to 3 wt. %.
8. A fabric according to Claim 1, wherein the fabric comprises at least a region consisting of a single thickness.

9. An article comprising a fabric according to Claim 1.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 03/23884

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 D06C15/02 D06C3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 D06C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 445 903 A (KOBAYASHI SHIGENOBU ET AL) 1 May 1984 (1984-05-01)	1-5, 8, 9
Y	examples	6, 7
Y	GB 2 371 567 A (DU PONT) 31 July 2002 (2002-07-31)	6, 7
A	column 3, lines 13-2; claims	1-5, 7, 8
A	US 5 581 856 A (KRUMMHEUER WOLF ET AL) 10 December 1996 (1996-12-10) column 4, lines 22, 23	1-9
	----- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

3 November 2003

Date of mailing of the international search report

17/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Barathe, R

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 03/23884

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>DATABASE WPI Section Ch, Week 198205 Derwent Publications Ltd., London, GB; Class A23, AN 1982-08874E XP002260046 & JP 56 165069 A (TORAY IND INC) 18 December 1981 (1981-12-18) abstract</p>	1-9
A	<p>-& JP 56 165069 A (TORAY IND INC) 18 December 1981 (1981-12-18) -----</p>	1-9
A	<p>PATENT ABSTRACTS OF JAPAN vol. 2000, no. 18, 5 June 2001 (2001-06-05) & JP 3 000868 A (TONGYANG NYLON CO LTD), 7 January 1991 (1991-01-07) abstract</p>	1-9
A	<p>-& JP 03 000868 A (TONGYANG NYLON CO LTD) 7 January 1991 (1991-01-07) the whole document -----</p>	1-9
A	<p>PATENT ABSTRACTS OF JAPAN vol. 0177, no. 08 (C-1147), 24 December 1993 (1993-12-24) & JP 5 239764 A (KANEBO LTD), 17 September 1993 (1993-09-17) abstract</p>	1-9
A	<p>-& JP 05 239764 A (KANEBO LTD) 17 September 1993 (1993-09-17) the whole document -----</p>	1-9
A	<p>US 5 356 680 A (KRUMMHEUER WOLF R ET AL) 18 October 1994 (1994-10-18) the whole document -----</p>	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 03/23884

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4445903	A	01-05-1984	JP 59150169 A	28-08-1984
			JP 1057186 B	04-12-1989
			JP 1581497 C	11-10-1990
			JP 58186663 A	31-10-1983
			JP 59030956 A	18-02-1984
			JP 1536417 C	21-12-1989
			JP 59030966 A	18-02-1984
			JP 63028154 B	07-06-1988
			CA 1213724 A1	11-11-1986
			DE 3365569 D1	02-10-1986
			EP 0092938 A1	02-11-1983
GB 2371567	A	31-07-2002	EP 1354086 A1	22-10-2003
			WO 02059407 A1	01-08-2002
US 5581856	A	10-12-1996	DE 4000740 A1	18-07-1991
			DE 4039811 A1	17-06-1992
			CA 2034067 A1	13-07-1991
			DE 59001559 D1	01-07-1993
			EP 0436950 A2	17-07-1991
			ES 2041112 T3	01-11-1993
			HK 102196 A	21-06-1996
			JP 2556624 B2	20-11-1996
			JP 4281062 A	06-10-1992
			KR 9512684 B1	20-10-1995
JP 56165069	A	18-12-1981	JP 1515956 C	24-08-1989
			JP 63061423 B	29-11-1988
JP 3000868	A	07-01-1991	NONE	
JP 5239764	A	17-09-1993	JP 2673628 B2	05-11-1997
US 5356680	A	18-10-1994	AU 656393 B2	02-02-1995
			AU 2031492 A	21-01-1993
			CA 2073957 A1	17-01-1993
			DE 59209644 D1	15-04-1999
			EP 0523546 A1	20-01-1993
			ES 2130144 T3	01-07-1999
			JP 2558040 B2	27-11-1996
			JP 5195419 A	03-08-1993
			KR 128256 B1	06-04-1998