



US011959393B2

(12) **United States Patent**
Ray et al.

(10) **Patent No.:** **US 11,959,393 B2**
(45) **Date of Patent:** **Apr. 16, 2024**

(54) **TURBINE ENGINE WITH REDUCED CROSS FLOW AIRFOILS**

(58) **Field of Classification Search**
CPC F01D 5/141
See application file for complete search history.

(71) Applicants: **GE Avio S.r.l.**, Rivalta di Torino (IT);
General Electric Company,
Schenectady, NY (US)

(56) **References Cited**

(72) Inventors: **Saurya Ranjan Ray**, Karnataka (IN);
Francesco Bertini, Rivalto di Torino
(IT); **Lyle Douglas Dailey**, Maineville,
OH (US); **Jeffrey D. Clements**, Mason,
OH (US); **Jaikumar Loganathan**,
Karnataka (IN); **Simone Rosa Taddei**,
Collegno (IT)

U.S. PATENT DOCUMENTS

3,039,736 A	6/1962	Pon
3,193,185 A	7/1965	Erwin et al.
4,012,165 A	3/1977	Kraig
4,023,350 A	5/1977	Hovan et al.
4,420,288 A	12/1983	Bischoff
4,512,718 A	4/1985	Stargardter
5,275,531 A	1/1994	Roberts
6,478,545 B2	11/2002	Crall et al.
		(Continued)

(73) Assignees: **General Electric Company**,
Schenectady, NY (US); **GE Avivo S.r.l.**,
Rivalta di Torino (IT)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

DE	1046246 B	12/1958
DE	102009018924 A1	11/2010
		(Continued)

(21) Appl. No.: **17/523,505**

Primary Examiner — Michael L Sehn

(22) Filed: **Nov. 10, 2021**

(74) *Attorney, Agent, or Firm* — McGarry Bair PC

(65) **Prior Publication Data**

US 2022/0243596 A1 Aug. 4, 2022

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Feb. 2, 2021 (IT) 102021000002240

An airfoil assembly for a turbine engine comprising an outer band, an inner band radially spaced inwardly from the outer band to define an annular region, and multiple airfoils circumferentially spaced within the annular region. Each corresponding airfoil of the multiple airfoils can project from a surface at a root and can further include an outer wall defining a pressure side and a suction side. A projection can extend upwardly from the surface on the pressure side and a valley can extend into the surface on the suction side to define a contour in the surface.


(51) **Int. Cl.**

F01D 5/14 (2006.01)

(52) **U.S. Cl.**

CPC **F01D 5/141** (2013.01); **F05D 2240/301**
(2013.01); **F05D 2240/305** (2013.01); **F05D**
2240/306 (2013.01); **F05D 2250/181**
(2013.01); **F05D 2250/711** (2013.01); **F05D**
2250/712 (2013.01)

20 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,508,626 B1 1/2003 Sakurai et al.
 7,665,964 B2 2/2010 Taylor et al.
 8,206,115 B2* 6/2012 Gupta F01D 9/04
 416/193 A
 8,257,032 B2 9/2012 Beeck et al.
 8,303,258 B2 11/2012 Aubin
 8,366,399 B2 2/2013 Allen-Bradley et al.
 8,721,291 B2* 5/2014 Lee F01D 5/141
 416/193 A
 8,920,127 B2 12/2014 McCaffrey
 9,359,900 B2* 6/2016 Chengappa F01D 5/145
 9,598,967 B2 3/2017 Xu
 9,739,154 B2 8/2017 Derclaye et al.
 9,745,850 B2 8/2017 Guendogdu et al.
 9,874,221 B2* 1/2018 DiPietro, Jr. F04D 29/324
 9,938,984 B2* 4/2018 DiPietro, Jr. F01D 5/143
 10,267,170 B2 4/2019 Clark et al.
 10,385,871 B2 8/2019 Lurie et al.
 10,458,247 B2 10/2019 Charbonnier et al.
 10,746,131 B2 8/2020 Ramm et al.
 11,125,089 B2 9/2021 Bertini et al.
 2007/0154314 A1 7/2007 Jarrah et al.
 2010/0080708 A1 4/2010 Gupta et al.
 2012/0051894 A1 3/2012 Clements et al.

2013/0051996 A1* 2/2013 Hoeger F01D 9/06
 415/185
 2014/0328675 A1 11/2014 Derclaye et al.
 2014/0348660 A1 11/2014 Guendogdu et al.
 2015/0107265 A1 4/2015 Smith et al.
 2016/0186772 A1 6/2016 DiPietro, Jr. et al.
 2016/0186773 A1 6/2016 DiPietro, Jr. et al.
 2017/0089203 A1 3/2017 Lohaus
 2017/0114796 A1 4/2017 DiPietro, Jr. et al.
 2017/0226880 A1 8/2017 Winn et al.
 2018/0347582 A1 12/2018 Malmborg
 2019/0024673 A1 1/2019 Anderson
 2019/0178094 A1 6/2019 Schutte
 2019/0186271 A1 6/2019 Xu et al.
 2020/0036271 A1 1/2020 Kies

FOREIGN PATENT DOCUMENTS

EP 0978632 A1 2/2000
 EP 1035302 B1 2/2006
 EP 2746534 A1 6/2014
 EP 2806102 A1 11/2014
 EP 3163028 A1 5/2017
 FR 2938871 A1 5/2010
 GB 840543 A 7/1960
 JP H09324605 A 12/1997
 WO 2015142200 A1 9/2015

* cited by examiner




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A

FIG. 7B

FIG. 7C




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 12

TURBINE ENGINE WITH REDUCED CROSS FLOW AIRFOILS

CROSS REFERENCE TO RELATED APPLICATIONS

This application takes priority to Italian Patent Application Serial No. 102021000002240, filed Feb. 2, 2021, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The disclosure generally relates to an airfoil for an engine, and more specifically to airfoils configured to reduce cross flow.

BACKGROUND

Turbine engines, and particularly gas or combustion turbine engines, are rotary engines that extract energy from a flow of combusted gases passing through the engine onto a multitude of rotating turbine blades.

A turbine engine includes but is not limited to, in serial flow arrangement, a forward fan assembly, an aft fan assembly, a compressor for compressing air flowing through the engine, a combustor for mixing fuel with the compressed air such that the mixture can be ignited, and a turbine. The compressor, combustor and turbine are sometimes collectively referred to as the core engine.

Turbine engines include several components that utilize airfoils. By way of a non-limiting example, the airfoils can be located in the engine turbines, compressors, or fans. Stationary airfoils are often referred to as vanes and rotating airfoils are often referred to as blades.

BRIEF DESCRIPTION

In one aspect, the disclosure relates to airfoil assembly for a turbine engine comprising an outer band, an inner band radially spaced inwardly from the outer band to define an annular region therebetween, and having an upstream edge and a downstream edge, with a surface extending therebetween, and multiple airfoils circumferentially spaced in the annular region wherein each corresponding airfoil of the multiple airfoils includes an outer wall defining a pressure side and a suction side extending between a leading edge and a trailing edge to define a chord-wise direction and extending between a root and a tip to define a span-wise direction, with the root abutting the surface, and a projection extending upwardly from the surface on the pressure side and a valley extending into the surface on the suction side to define a contour to the surface, and the projection having an apex located from the leading edge between -10% and 10% of a normalized axial chord line for the corresponding airfoil.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a schematic cross-sectional diagram for a turbine engine.

FIG. 2 is a perspective view of an airfoil assembly of turbine engine of FIG. 1 having circumferentially spaced airfoils, each with a pressure side and a suction side, extending upwardly from an endwall having a projection on the suction side, a valley formed in the endwall on the

pressure side, a fence extending along the pressure side, and a splitter located between the airfoils and extending from the endwall.

FIG. 3 is a side view of the pressure side of an airfoil of the airfoil assembly of FIG. 2 illustrating the location and height of the projection and fence relative to the surface.

FIG. 4 is a side view of the suction side of an airfoil of the airfoil assembly of FIG. 2 illustrating the location of the valley on the suction side relative to the surface.

FIG. 5 is a side view of the pressure side of an airfoil of the airfoil assembly of FIG. 2 illustrating the location of the of splitter relative to the surface.

FIG. 6 is a radial view of the airfoil assembly of FIG. 2.

FIG. 7A is a top-down view of the airfoil assembly of FIG. 2 illustrating the airfoils alone without the projection, valley, fence and splitter of the crossflow retarding aerodynamic structures and the accompanying pressure regions, and airflow.

FIG. 7B is a top-down view of the airfoil assembly of FIG. 2 including the fence, and the splitter of the crossflow retarding aerodynamic structures and the accompanying pressure regions, and airflow.

FIG. 7C is a top-down view of the airfoil assembly of FIG. 2 with the projection, valley, fence and splitter, of the crossflow retarding aerodynamic structures and the accompanying pressure regions, and airflow.

FIG. 8A is a topographical map of an example airfoil without the projection, valley, fence, and splitter of the crossflow retarding aerodynamic structures of FIG. 2.

FIG. 8B is a topographical map of an airfoil of the nozzle assembly with the projection, valley, fence and splitter of the crossflow retarding aerodynamic structures of FIG. 2.

FIG. 9 is an enlarged view of an exemplary airfoil assembly of the turbine engine of FIG. 1 according to an aspect of the disclosure herein.

FIG. 10 is an enlarged view of a root portion of the exemplary airfoil assembly of FIG. 9, further including a tunnel and trench according to another aspect of the disclosure herein.

FIG. 11 is an isometric side view of the tunnel and trench of FIG. 10.

FIG. 12 is FIG. 3 again illustrating a method of containing and guiding a flow.

DETAILED DESCRIPTION OF THE INVENTION

Aspects of this description are broadly directed to an airfoil for a turbine engine, where the airfoil can include multiple crossflow retarding aerodynamic structures such as end wall contouring (EWC) which can include a projection and a valley, a fence, and a splitter. Collectively, they can provide the airfoil with increased aerodynamic efficiency and significantly reduce secondary loss and exit swirl variation when compared to airfoils without the crossflow retarding aerodynamic structures.

As used herein, the term “upstream” refers to a direction that is opposite the fluid flow direction, and the term “downstream” refers to a direction that is in the same direction as the fluid flow. The term “fore” or “forward” means in front of something and “aft” or “rearward” means behind something. For example, when used in terms of fluid flow, fore/forward can mean upstream and aft/rearward can mean downstream.

Additionally, as used herein, the terms “radial” or “radially” refer to a direction away from a common center. For example, in the overall context of a turbine engine, radial

refers to a direction along a ray extending between a center longitudinal axis of the engine and an outer engine circumference. Furthermore, as used herein, the term “set” or a “set” of elements can be any number of elements, including only one.

All directional references (e.g., radial, axial, proximal, distal, upper, lower, upward, downward, left, right, lateral, front, back, top, bottom, above, below, vertical, horizontal, clockwise, counterclockwise, upstream, downstream, forward, aft, etc.) are only used for identification purposes to aid the reader’s understanding of the present disclosure, and do not create limitations, particularly as to the position, orientation, or use of aspects of the disclosure described herein. Connection references (e.g., attached, coupled, secured, fastened, connected, and joined) are to be construed broadly and can include intermediate members between a collection of elements and relative movement between elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and in fixed relation to one another. The exemplary drawings are for purposes of illustration only and the dimensions, positions, order and relative sizes reflected in the drawings attached hereto can vary.

FIG. 1 is a schematic cross-sectional diagram of a turbine engine 10 for an aircraft. The turbine engine 10 has a centerline or longitudinal axis 12 extending forward 14 to aft 16. The turbine engine 10 includes, in downstream serial flow relationship, a fan section 18 including a fan 20, a compressor section 22 including a booster or low-pressure (LP) compressor 24 and a high-pressure (HP) compressor 26, a combustion section 28 including a combustor 30, a turbine section 32 including a HP turbine 34, and a LP turbine 36, and an exhaust section 38.

The fan section 18 includes a fan casing 40 surrounding the fan 20. The fan 20 includes a plurality of fan blades 42 disposed radially about the longitudinal axis 12. The HP compressor 26, the combustor 30, and the HP turbine 34 form an engine core 44, which generates combustion gases. The engine core 44 is surrounded by core casing 46, which can be coupled with the fan casing 40.

A HP shaft or spool 48 disposed coaxially about the longitudinal axis 12 of the turbine engine 10 drivingly connects the HP turbine 34 to the HP compressor 26. A LP shaft or spool 50, which is disposed coaxially about the longitudinal axis 12 of the turbine engine 10 within the larger diameter annular HP spool 48, drivingly connects the LP turbine 36 to the LP compressor 24 and fan 20. The spools 48, 50 are rotatable about the engine centerline and couple to a plurality of rotatable elements, which can collectively define an inner rotor/stator 53. While illustrated as a rotor, it is contemplated that the inner rotor/stator 53 can be a stator.

The LP compressor 24 and the HP compressor 26 respectively include a plurality of compressor stages 52, 54, in which a set of compressor blades 56, 58 rotate relative to a corresponding set of static compressor vanes 60, 62 (also called a nozzle assembly) to compress or pressurize the stream of fluid passing through the stage. In a single compressor stage 52, 54, multiple compressor blades 56, 58 can be provided in a ring and can extend radially outwardly relative to the longitudinal axis 12, from a blade platform to a blade tip, while the corresponding static compressor vanes 60, 62 are positioned downstream of and adjacent to the rotating compressor blades 56, 58. It is noted that the number of blades, vanes, and compressor stages shown in FIG. 1 were selected for illustrative purposes only, and that other numbers are possible.

The compressor blades 56, 58 for a stage of the compressor can be mounted to a disk 61, which is mounted to the corresponding one of the HP and LP spools 48, 50, with each stage having its own disk 61. The static vanes 60, 62 for a stage of the compressor can be mounted to the core casing 46 in a circumferential arrangement.

The HP turbine 34 and the LP turbine 36 respectively include a plurality of turbine stages 64, 66, in which a set of turbine blades 68, 70 are rotated relative to a corresponding set of static turbine vanes 72, 74 (also called a nozzle assembly) to extract energy from the stream of fluid passing through the stage. In a single turbine stage 64, 66, multiple turbine blades 68, 70 can be provided in a ring and can extend radially outwardly relative to the longitudinal axis 12, from a blade platform to a blade tip, while the corresponding static turbine vanes 72, 74 are positioned upstream of and adjacent to the rotating blades 68, 70. It is noted that the number of blades, vanes, and turbine stages shown in FIG. 1 were selected for illustrative purposes only, and that other numbers are possible.

The blades 68, 70 for a stage of the turbine can be mounted to a disk 71, which is mounted to the corresponding one of the HP and LP spools 48, 50, with each stage having a dedicated disk 71. The static turbine vanes 72, 74 for a stage of the compressor can be mounted to the core casing 46 in a circumferential arrangement.

Complementary to the rotor portion, the stationary portions of the turbine engine 10, such as the static compressor and turbine vanes 60, 62, 72, 74 among the compressor and turbine section 22, 32 are also referred to individually or collectively as an outer rotor/stator 63. As illustrated, the outer rotor/stator 63 can refer to the combination of non-rotating elements throughout the turbine engine 10. Alternatively, the outer rotor/stator 63 that circumscribes at least a portion of the inner rotor/stator 53, can be designed to rotate.

In operation, the airflow exiting the fan section 18 is split such that a portion of the airflow is channeled into the LP compressor 24, which then supplies pressurized airflow 76 to the HP compressor 26, which further pressurizes the air. The pressurized airflow 76 from the HP compressor 26 is mixed with fuel in the combustor 30 and ignited, thereby generating combustion gases. Some work is extracted from these gases by the HP turbine 34, which drives the HP compressor 26. The combustion gases are discharged into the LP turbine 36, which extracts additional work to drive the LP compressor 24, and the exhaust gas is ultimately discharged from the turbine engine 10 via the exhaust section 38. The driving of the LP turbine 36 drives the LP spool 50 to rotate the fan 20 and the LP compressor 24.

A portion of the pressurized airflow 76 can be drawn from the compressor section 22 as bleed air 77. The bleed air 77 can be drawn from the pressurized airflow 76 and provided to engine components requiring cooling. The temperature of pressurized airflow 76 entering the combustor 30 is significantly increased. As such, cooling provided by the bleed air 77 is necessary for operating of such engine components in the heightened temperature environments.

A remaining portion of the airflow 78 bypasses the LP compressor 24 and the engine core 44 and exits the turbine engine 10 through a stationary vane row, and more particularly an outlet guide vane assembly 80, comprising a plurality of airfoil guide vanes 82, at the fan exhaust side 84. More specifically, a circumferential row of radially extending airfoil guide vanes 82 are utilized adjacent the fan section 18 to exert some directional control of the airflow 78.

Some of the air supplied by the fan 20 can bypass the engine core 44 and be used for cooling of portions, especially hot portions, of the turbine engine 10, or used to cool or power other aspects of the aircraft. In the context of a turbine engine, the hot portions of the engine are normally downstream of the combustor 30, especially the turbine section 32, with the HP turbine 34 being the hottest portion as it is directly downstream of the combustion section 28. Other sources of cooling fluid can be, but are not limited to, fluid discharged from the LP compressor 24 or the HP compressor 26.

FIG. 2 is a perspective view of an airfoil assembly 100 of the turbine engine 10 of FIG. 1 that includes multiple, spaced airfoils, specifically, a first airfoil 102 and a second airfoil 103 extending from an endwall defined by a platform or a surface 140. A variety of aerodynamic structures are provided to retard crossflow between the first and second airfoils 102, 103. The crossflow retarding aerodynamic structures include: a projection 142 and a valley 146 in the surface 140, and a splitter 120 located between the first and second airfoils 102, 103 and extending upwardly from the surface. The projection 142 and valley 146 help define a contour to the surface 140 and can be referred to as endwall contouring (EWC) of the airfoil assembly 100.

Each of the first and second airfoils 102, 103 has a leading edge 104, a trailing edge 106, a tip 108, a root 110 and an exterior wall 112. An axial direction extending generally from the leading edge 104 to the trailing edge can be called a chord-wise direction. Similar, a radial direction extending generally from the root to the tip can be referred to as a span-wise direction.

Each of the airfoils can be coupled to an inner band 96 which can be formed by a number of different components of the engine. For example, regardless of whether the airfoil is a stationary vane or a rotating blade, the inner band 96 can be what is referred to as the inner band of either rotor 53 or rotor/stator 63. Although not illustrated, an outer band can be provided radially displaced from the inner band 96 such that the inner band 96 is radially displaced inwardly from the outer band. In such a case, the outer band can form or otherwise be coupled to at least a portion of the rotor/stator 63, while the inner band 96 can be coupled to or otherwise form at least a portion of the rotor/stator 53. Alternatively, the inner band 96 can be defined as a first band and the outer band can be defined as a second band radially displaced from the first band. The first band can form or otherwise be coupled to at least a portion of the either rotor 53 or the rotor/stator 63, while the second band can form or otherwise be coupled to at least a portion of the radially opposite rotor 53 or the rotor/stator 63 to where the first band is located. As a non-limiting example, the first band could form or be coupled to at least a portion of the rotor/stator 63, while the second band could form or be coupled to at least a portion of the rotor/stator 53. In either case, the space between the inner band 96 and the outer band can define an annular region where the airfoils 102, 103 are spaced within. The inner band 96 can be defined by an upstream edge and a downstream edge with respect to the engine centerline 12. The surface 140 can extend between the upstream edge and the downstream edge.

The inner band 96 and the outer band can be formed by multiple circumferential segments, with each segment having a single airfoil and mounted to a disk by a dovetail. The inner band 96 or the outer band can be a continuous, unbroken surface. Alternatively, there can be holes, channels, ducts, cracks, troughs, or any other known feature placed throughout the inner band 96 or outer band. These

various exemplarity features of the platform can be used for various reasons to improve overall engine efficiency. These features can be used as dust escape, cooling holes, or aerodynamic efficiency boosters.

The splitter 120 can be positioned between the first and second airfoils 102, 103 of the airfoil assembly 100 such that one side 121 of the splitter 120 can face a pressure side 114 of the first airfoil 102, while the other side 123 of the splitter 120 can face a suction side 116 of the second airfoil 103. The location of the splitter 120 can be shifted more toward one airfoil than another and moved in the chord-wise direction to obtain the desired aerodynamic effect in helping to retard cross flow. The splitter 120 can extend from the surface 140 as illustrated to a radially outer portion of the splitter to define a through-channel 176 between the one side 121 of the splitter and the exterior wall 112 of the corresponding first or second airfoil 102, 203.

A set of fences 130 can be formed as part of the exterior walls 112 of the first or second airfoils 102, 103. The set of fences 130 can be one or multiple undulations along the exterior wall 112 and positioned near the root 110 of the corresponding airfoil (e.g., the first airfoil 102 or the second airfoil 103). The set of fences 130 can be formed to extend around an entirety of the exterior wall 112 on the pressure side 114 of the airfoils 102, 103, as illustrated. Alternatively, the set of fences 130 can start and terminate at various locations along any portion of the exterior wall 112 as discussed herein. The set of fences 130 can be positioned near the root 110 of the first or second airfoils 102, 103. The set of fences 130 can be further defined to be formed integrally with the exterior wall 112. As such, the set of fences 130 can form a bump from the exterior wall 112. At the points where the set of fences 130 start or terminate, the set of fences 130 can taper toward or from the exterior wall 112 such that that the termination or starting points of the set of fences 130 are integral with the exterior wall 112.

The surface 140 can be formed as part of the inner band 96. The EWC can include various features such as, for example, the projection 142, and the valley 146. The projection 142 can be formed on the pressure side 114 of the airfoil, while the valley 146 can be formed on the suction side 116 of the first or second airfoils 102, 103 between the exterior wall 112 and the splitter 120.

FIG. 3 is a side view of the pressure side 114 of the first airfoil 102 of the airfoil assembly 100 of FIG. 2, illustrating the shape and location of the projection 142, its impact on the contour of the surface 140 of the inner band 96, and the relationship of the set of fences 130 with the projection 142. Although illustrated as the first airfoil 102, it will be appreciated that what is described herein can be attributed to the second airfoil 103 or any other airfoil in the airfoil assembly 100.

The projection 142 of the surface 140 can project from a surface baseline 98 defined to be a constant radial distance from the longitudinal axis 12 of the turbine engine 10. The surface baseline 98 can be further defined as a projection of the surface 140 that does not follow the contour formed through the EWC.

A portion of the surface 140 can diverge from the surface baseline 98 near the leading edge 104 of the first airfoil 102 toward the tip 108 to an apex 144, and then converge back to the surface baseline 98 to define the projection 142. The apex 144 of the projection 142 can extend from the surface baseline 98 at a height 150. The height 150 can be between 0.5% and 2.5% of a span of the first airfoil 102. As used herein, the span can be defined as the distance from the root

110 to the tip 108 of the first airfoil 102, with 100% of the span being the tip 108 and 0% being the root 110.

It is contemplated that the set of fences 130 can include a lower fence 134 and an upper fence 132 which can follow the contour of the surface 140 such that the radial height from the surface 140 and the upper and lower fences 132, 134, respectively, remains constant at all locations long the exterior wall 112 where the upper and lower fences 132, 134 are present. As such, each fence 130 can be located a predetermined height above a local contour of the surface 140. As used herein, the local contour can be defined as the radial height of the surface 140 at a specific axial position along the first airfoil 102. Although illustrated as the upper and lower fences 132, 134, it will be appreciated that the set of fences 130 can include any number of one or more fences. Each fence 130 can be radially positioned from the surface baseline 98 at differing radial heights. The predetermined height of each fence 130 can be a constant height measured from the surface 140. Alternatively, the predetermined height of each fence 130 can increase or decrease linearly or non-linearly from the leading edge 104 to the trailing edge 106 of the first airfoil 102.

Specifically, the predetermined height of the set of fences 130 can be between 0% and 20% of the span of the first airfoil 102 as measured from the root 110. The set of fences 130 can include multiple fences, each being spaced from an adjacent fence in the span-wise direction. For example, the upper fence 132 and the lower fence 134 can each be further defined as adjacent fences of the set of fences 130 spaced apart from one another in the span-wise direction.

The set of fences 130 can include a thickness 151. The thickness 151 of the set of fences 130 can be defined as the radial distance the set of fences 130 extend along the span-wise direction of the corresponding airfoil. Specifically, the thickness 151 can be between 2% and 10% of the axial chord 154. The axial chord 154 can be defined as can be defined as the normal distance between the leading edge 104 and the trailing edge 106 of the corresponding airfoil (e.g., the first airfoil 102) in the axial direction.

The set of fences 130 can extend around at least a portion of the exterior wall 112 on the pressure side 114 of the first airfoil 102. As illustrated, the set of fences 130 can terminate along a portion of the exterior wall 112. Specifically, the set of fences 130 can terminate between 60% to 90% of the axial chord 154 on the pressure side 114 of the first airfoil 102. It will be further appreciated that at least a portion of the set of fences 130 can extend beyond the leading edge 104 of the first airfoil 102. Alternatively, the set of fences 130 can start begin at a portion of the first airfoil 102 located downstream the leading edge. As such, the set of fences 130 can include an upstream portion or otherwise be defined to start between -20% and 30% of the axial chord 154. As used herein, 0% of the axial chord 154 can be the leading edge 104 of the first airfoil 102 and 100% of the normalized axial chord 154 can be the trailing edge 106.

The set of fences 130 can be further defined to form a portion of the exterior wall 112. It is further contemplated that the set of fences 130 can smoothly taper into or out of the exterior wall 112 at the start or termination, respectively, of the set of fences 130. As such, each fence 130 can project outward from the exterior wall 112 of the first airfoil 102 a distance at the leading edge 104. The distance the set of fences 130 projects can reduce from the leading edge 104 toward the trailing edge 106. The distance the set of fences 130 project can vary linearly or non-linearly from the leading edge 104 to the trailing edge 106. It will be appreciated that the distance the set of fences 130 extend from the

exterior wall 112 can further be defined as a width of the set of fences 130. The width of the set of fences 130 can be non-constant about the exterior wall 112.

FIG. 4 is a side view of the suction side 116 of one of first airfoil 102 of the airfoil assembly 100 of FIG. 2, illustrating a portion of the set of fences 130, and the contour of the valley 146 on the suction side 116 of the first airfoil 102. Although illustrated as the first airfoil 102, it will be appreciated that what is described herein can be attributed to the second airfoil 103 or any other airfoil in the airfoil assembly 100.

The valley 146 can be defined as a portion of the surface 140 of the inner band 96 which diverges from the surface baseline 98 away from the tip 108 of the first airfoil 102 to a minimum 148. The minimum can extend into the surface 140 a depth 152 to define a maximum depth of the valley 146. The depth 152 can be between 0.15% and 1.5% of the span of the first airfoil 102. It is further contemplated that the valley 146 can be defined by a ratio of 3 between the maximum height of the projection 142 and the minimum or maximum depth of the valley 146.

As illustrated, the valley 146 can extend along at least a rear portion of the first airfoil 102 along the suction side 116. It will be appreciated that the valley 146, however, can extend along any portion of the first airfoil 102 along the suction side 116. For example, the valley 146 can extend from the leading edge 104 to the trailing edge 106 of the first airfoil 102. Alternatively, the valley 146 can extend beyond one or more of the leading edge 104 or the trailing edge 106. The valley 146 can further be defined by an upstream edge and a downstream edge, with the upstream edge located at or in front of (e.g., upstream stream of) the leading edge 104 of the corresponding airfoil 102, 103.

The valley 146 can further include a width. The width of the valley 146 can be defined as the total distance the valley extends along in the circumferential direction from the suction side 116 of the first airfoil 102. For example, the width of the valley 146 can have a circumferential width maximum width of 20% of the pitch from the first airfoil 102 to the second airfoil 103 (e.g., the valley 146 can extend along the surface 140 in the circumferential direction a maximum of 20% of the circumferential space between the first airfoil 102 and the second airfoil 103). As used herein, the pitch can be defined as the circumferential distance between the leading edges 104 of the first and second airfoils 102, 103. The pitch can be measured from the pressure side 114 of the first airfoil 102 to the suction side 116 of the second airfoil 103.

As illustrated, the set of fences 130, specifically the upper fence 132 and the lower fence 134, can terminate axially prior to the valley 146. As such, the set of fences 130 extend horizontally across the first airfoil 102 and do have a variance in the radial height from the surface 140 along the suction side 116. It is contemplated, however, that the at least a portion of the set of fences 130 can extend axially over a portion of the valley 146. As such, a portion of the set of fences 130 can follow the contour of the valley 146 and maintain a constant radial height from the surface 140. It is contemplated, that a portion of the set of fences 130 can extend radially inward from the surface baseline 98.

FIG. 5 illustrates the splitter 120 of the airfoil assembly 100 of FIG. 2 without the EWC of the surface 140, or the fence 130. The splitter 120 can include a leading edge 122, a trailing edge 124, and an inclined edge 126. The inclined edge 126 can be defined as the edge of the splitter radially farthest from the surface 140. Although illustrated as the first airfoil 102, it will be appreciated that what is described

herein can be attributed to the second airfoil 103 or any other airfoil in the airfoil assembly 100.

The splitter 120 can be defined by a maximum radial height of the trailing edge 124. The maximum radial height of the trailing edge 124 of the splitter 120 can be 15% of the span of the first airfoil 102. The splitter 120 can be further defined by the inclined edge 126. The inclined edge 126 can be defined as a sloped edge which increases in height from the leading edge 122 to the trailing edge 124 of the splitter 120. The inclined edge 122 can extend linearly from the leading edge 122 to the trailing edge 124. Alternatively, the inclined edge 122 can extend non-linearly from the leading edge 122 to the trailing edge 124.

The leading edge 122 of the splitter 120 can be positioned a distance 168 from the leading edge 104 of the first airfoil 102. The distance 168 can be defined to be along the axial chord 154 described herein. The distance 168 can be between -0.1% and 0.2% of the axial chord 154.

FIG. 6 is a radial view of the airfoil assembly 100 of FIG. 2 illustrating the axial, and circumferential placements of the splitter 120 and the EWC of the surface 140. As illustrated herein, the first and second airfoil 102, 103 are shown by a first and second mean camber lines 172, 174 respectively. It will be appreciated that the first and second mean camber lines 172, 174, and hence the first and second airfoils 102, 103, can take any form to include the leading edge 104, and a trailing edge 106.

As FIG. 6 illustrates the location of the projection 142, splitter 120, and the valley 146 relative to the first and second airfoils 102, 103, it will be helpful to define certain dimensional references. One of these references is the pitch 160, which is the circumferential distance between adjacent airfoils (e.g., the first and second airfoils 102, 103). Another dimensional reference is the axial chord 154, which is the projection of the airfoil chord onto the rotational axis of the engine. The airfoil chord is a line extending between the leading edge and the trailing edge. With these references, dimensions and/or locations for the projection 142, valley 146, and splitter 120 will be discussed herein.

The apex 144 of the projection 142 can be a distance 156 between -10% and 10% of the axial chord 154 from the leading edge 104 and the trailing edge 106 of the second airfoil 103. The apex 144 of the projection 142 can be a distance 162 of between 0% and 10% of the pitch 160 where 0% is the leading edge 104 of the second airfoil 103.

The minimum 148 of the valley 146 can be a distance 158 between 40% and 70% of the axial chord 154 from the leading edge 104 and the trailing edge of the second airfoil 103. The minimum 148 of the valley 146 can be a distance 164 between 0% and 20% of the distance from the leading edge 104 of the second airfoil 103 and the leading edge 122 of the splitter 120, where 0% is the leading edge 104 of the second airfoil 103.

The leading edge 122 of the splitter 120 can be a distance 166 between 30% and 70% of the pitch 160 from the leading edge 104 of the second airfoil 103. The splitter 120 can include an axial chord from the leading edge 122 to the trailing edge 124. The axial chord of the splitter 120 can be projected as a normalized axial chord 170 which can be defined as the normal distance between the leading edge 122 and the trailing edge 124 of the splitter 120 in the axial direction. The normalized axial chord 170 can have a length between 30% and 70% of the normalized axial chord 154 first or second airfoils 102, 103.

FIGS. 7A-7C illustrate the impact of the crossflow retarding aerodynamic structures on a cross flow. As used herein,

the cross flow can be defined a transfer or crossing over of a fluid flow from one airfoil to another adjacent airfoil or structure.

As a first non-limiting example, FIG. 7A illustrates a top-down view of the airfoil assembly 100 including the first airfoil 102 defined by the first mean camber line 172 and the second airfoil 103 defined by the second mean camber line 174 of FIG. 2 without the crossflow retarding aerodynamic structures and illustrating a fluid flow 710 as it flows around the airfoil assembly 100.

As shown, the fluid flow 710 can impinge the leading edge 104 of the first and second airfoils 102, 103. The fluid flow 710 is drawn from the pressure side 114 of the second airfoil 103, toward the suction side 116 of the first airfoil 102 due to a pressure differential created between a high-pressure region 704 on the pressure side and a low-pressure region 702 on the suction side 116. Such a pressure differential results in a pressure gradient that encourages fluid flow crossing over from the high-pressure to the low-pressure.

The cross flow of the fluid flow 710 from the pressure side 114 of the second mean camber line 174 to the suction side 116 of the first airfoil 102, induces the low-pressure region to extend into the pressure side 114 of the second airfoil 103, which increases a boundary layer growth between the exterior wall 112 and the pressure side 114, which in turn decreases the overall efficiency of the airfoil assembly 100.

As a second non-limiting example, FIG. 7B illustrates a top-down view of the airfoil assembly 100 similar to FIG. 7A, except that the splitter 120 and the set of fences 130 are included. Illustrated are the resulting high- and low-pressure regions 704, 702, and the corresponding fluid flow 710 created around the airfoil assembly 100.

The addition of the splitter 120 and the set of fences 130 retards the fluid flow 710 from transferring over to the suction side 116 of the first airfoil 102. This, in turn, restricts a first low-pressure region 706 from transferring from the pressure side 114 of the second airfoil 103 to join with the low-pressure region 702 of the suction side 116 of the first airfoil 102. As a result, the high-pressure region 704 is increased and the low-pressure region is decreased in comparison with that of FIG. 7A. The high-pressure region 704 is further constrained between the pressure side 114 of the second airfoil and the splitter 120. This, in turn, retards the boundary layer growth between the exterior wall 112 and the pressure side 114, which in turn increases the overall efficiency of the airfoil assembly 100 when compared to that of FIG. 7A.

As a third non-limiting example, FIG. 7c illustrates a top down view of the airfoil assembly 100 of similar to FIG. 7A, except that, the splitter 120, the set of fences 130, and the EWC of the surface 140 are added. Illustrated are the resulting high- and low-pressure regions 704, 702, and the corresponding fluid flow 710 created around the airfoil assembly 100.

The addition of the EWC on top of the splitter 120, and the set of fences 130 retards the fluid flow 710 from transferring over to the suction side 116 of the first airfoil 102. This, in turn, reduces the pressure gradient by restricting the first low-pressure region 706 from transferring to join with the low-pressure region 702 of the suction side 116 of the first airfoil 102. The first low-pressure region 706 is significantly smaller than the first low-pressure region of FIG. 7B. As a result, the size of the high-pressure region 704 is further increased while still being constrained to between the pressure side 114 of the second airfoil and the splitter 120. This, in turn, further retards the boundary layer growth

between the exterior wall **112** and the pressure side **114**, which in turn increases the overall efficiency of the airfoil assembly **100** when compared to the airfoil assembly **100** of FIGS. 7A-7B.

FIG. 8A illustrates a topographical map of the first airfoil **102** of the airfoil assembly **100** of FIG. 2 without the splitter **120**, or the set of fences **130**. For this example, the first airfoil **102**, defined by the first mean camber line **172** is shown, however, it will be appreciated that this can be applied to the second airfoil **103** or any other airfoil. FIG. 8A further illustrates the EWC of the surface **140** that would be needed to replicate the improvements described in FIG. 7C without the use of the splitter **120**, or the set of fences **130**.

The first airfoil **102** can be entirely surrounded by a baseline region **802** that can be defined to be the same height as the surface baseline **98** described herein. The surface **140** can then steadily increase in rising regions **804**, **806**, **808** until it reaches a projection region **844**. The projection region **844** can be defined as a region in which the apex **144** is present. Conversely on the suction side **116** of the first airfoil **102** the surface **140** can steadily decrease in reduction regions **810**, **812** until it reaches a minimum region **848**. The minimum region **848** can be defined as a region in which the minimum **148** is present.

FIG. 8B illustrates a topographical map of the first airfoil **102** of the airfoil assembly **100** of FIG. 2 including the splitter **120**, and the set of fences **130**. For this example, the first airfoil **102**, defined by the first mean camber line **172** is shown, however, it will be appreciated that this can be applied to the second airfoil **103** or any other airfoil.

With the implementation of the splitter **120**, and the set of fences **130**, the total depth or height needed to reach the minimum region **848** or the projection region **844**, respectively, can be greatly reduced. As illustrated, one rising region **804** can be used to reach the projection region **844**, while there can be no reduction regions to reach the minimum region **848**. With the implementation of the splitter **120** and the fence **130**, the amplitude of the minimum **148**, or the apex **144** can be reduced by up to 75% when compared to that of FIG. 8A.

The EWC of the surface **140** can be allow for an improved efficiency of the turbine engine **10**. The apex **144** being closer to the leading edge **104** of the first airfoil **102**, and the reduction of the overall height of the apex **144** can be less disruptive to the fluid flow **710** around the first airfoil **102**. This, in turn can increase the overall efficiency of subsequent stages downstream the airfoil assembly **100** and therefore increase the overall efficiency of the turbine engine **10**. Similarly, the reduction in the depth of the minimum **148**, and hence a shallower valley **146** can further limit the disruption of the fluid flow **710** and ultimately increase the efficiency of the turbine engine **10**.

The airfoil assembly **100** including the splitter **120**, the set of fences **130**, and EWC of the surface **140** can further be a significant improvement upon the airfoil assembly **100** without the crossflow retarding aerodynamic structures as described herein, by greatly reducing an exit swirl variation, and secondary losses and therefore, increasing the overall efficiency of the turbine engine **10**. The exit swirl variation can be defined as the difference in the angle of the fluid flow exiting the first or second airfoil **102**, **103** at the trailing edge **106** along the entire span of the first or second airfoil **102**, **103** with a reference value at of the angle of the fluid flow exiting at 50% along the span of the first or second airfoil **102**, **103**. With implementation of the crossflow retarding aerodynamic structures, the exit swirl variation can be decreased by 19% to 26%.

It will be appreciated that ranges used herein can include the values between the minimum and maximum along with the minimum and maximum themselves. For example, a range of 60% to 100% can include 60% and 100% and all of the numbers between.

FIG. 9 is a perspective view of an exemplary airfoil assembly **200** of the turbine engine **10** of FIG. 1. The exemplary airfoil assembly **200** is similar to the airfoil assembly **100**; therefore, like parts will be identified with like numerals in the **200** series, with it being understood that the description of the like parts of the airfoil assembly **100** applies to the airfoil assembly **200** unless otherwise noted.

The airfoil assembly **200** can include a set of spaced airfoils, specifically a first airfoil **202** and a second airfoil **203**. The first airfoil **202** and the second airfoil **203** can each include a leading edge **204**, a trailing edge **206**, a tip **208**, a root **210** and be bound by an exterior wall **212**.

A variety of aerodynamic structures such as a set of fences **230** including, at least, an upper fence **232** and a lower fence **234**, and a splitter **220** can be provided both on the exterior wall **212** and the surface **240** or platform to retard crossflow between the first airfoil **202** and the second airfoil **203**.

As illustrated, the lower fence **234** can follow the contour of a surface **240** or platform of an inner band **196** such that the radial height (H) between the surface **240** and the lower fence **234** remains constant at all locations long the exterior wall **212** where the lower fence **234** is present. The upper fence **232**, or any other subsequent fence, can follow the contour of the lower fence **234**. Further, the set of fences **230** can project outward from the exterior wall **212** of the corresponding first or second airfoil **202**, **203** a width (W) at the leading edge **204**. The width (W) the set of fences **230** projects can reduce from the leading edge **204** toward the trailing edge **206**.

The splitter **220** can be positioned between the spaced first airfoil **202** and the second airfoil **203** such that one side **221** of the splitter **220** faces the pressure side **214** of one of the first or second airfoils **202**, **203**, while the other side **223** of the splitter **220** faces the suction side **216** of the other one of the first and second airfoils **202**, **203**. The splitter **220** can curve toward the suction side **216** of the other one of the airfoils **202**, **203** to define a concave shape such that the one side **223** facing the pressure side **214** defines a convex shape. The location of the splitter **220** can be shifted more toward one airfoil than another and moved in the chord-wise direction to obtain the desired aerodynamic effect in helping to retard cross flow. The splitter **220** can extend from the surface **240** or from an aperture **225** formed within the surface **240** as illustrated to a top or an edge **226** spaced from the exterior wall **212** to define a through-channel **276**. The aperture **225** can be fluidly coupled to a cooling source and the concave shape of the side **221** can provide a channel along which a cooling fluid can flow.

Turning to FIG. 10, additional aerodynamic structures **278**, **280** are illustrated. The aerodynamic structure **278** extending from the splitter **220** toward the pressure side **214** is referred to herein as a bridge **278**. The bridge **278** can extend from any portion of the splitter **220**, by way of non-limiting example the edge **226** specifically a top of the splitter **220**. The bridge **278** can connect the splitter **220** to the first airfoil **202**, by way of non-limiting example to one fence of the set of fences **230**. Although illustrated as the first airfoil **202**, it will be appreciated that what is described herein can be attributed to the second airfoil **203** or any other airfoil in the airfoil assembly **200**. The bridge **278** can be formed in any shape and provide a closure for the through-

channel 276 of FIG. 9 to define a tunnel 282 extending between an inlet 284 and an outlet 286.

Yet another aerodynamic structure 280 referred to herein as a trench 280 is defined by a cavity 288 formed within the surface 240. As illustrated the cavity 288 can terminate at an end wall 290 of the surface 240 to define a trench inlet 292. The trench 280 can extend from the trench inlet 292 toward a trench outlet 294 proximate the pressure side 214 and located at or within the tunnel 282. The cavity 288 can define a decreasing depth (D) from the trench inlet 292 to the trench outlet 294 such that the trench 280 is flush with the surface 240 at or within the tunnel 282 at the trench outlet 294.

FIG. 11 illustrates a side view along line XI in FIG. 10 looking at the splitter 220. The splitter 220 can extend between a leading edge 222 or a fore edge and a trailing edge 224 or an aft edge with the top edge 226 defining an inclined edge 226 connecting the leading edge 222 to the trailing edge 224. The inclined edge 226 can increase or decrease as illustrated along a length (L) of the splitter 220. The inlet 284 can define a larger cross-sectional area than the outlet 286 such that a guided flow 296 accelerates when flowing from the inlet 284 to the outlet 286. The trench outlet 294 can be located just within the inlet 284 of the tunnel 282 as illustrated in dashed line. It is further contemplated that the trench outlet 294 is located at the inlet 284 of the tunnel 282 or prior to and/or outside of the tunnel 282. A dashed arrow 298 indicates a location range for the trench 280. As is indicated, the trench 280 can be located closer to the first airfoil 202 or further from the first airfoil 202 depending on a desired trench inlet 292 and trench outlet 294 location. In some cases the trench 280 can be located outside the tunnel 282 such that the trench outlet 294 exhausts the guided flow along the surface 240.

FIG. 12 illustrates a method of containing and guiding a flow through the trench 280 and tunnel 282 described herein. A fluid flow defined as a main fluid flow 310 can impinge the leading edge 204 of the airfoils 202, 203. The main fluid flow 310 can then be drawn from the pressure side 214 of the airfoil illustrated, toward (illustrated by dashed line 312) the suction side 216 of the other airfoil due to the pressure differential created between a high-pressure region 304 on the pressure side 214 and a low-pressure region 306 on the suction side 216 of the other airfoil (illustrated by the first airfoil 202 and the second airfoil 203 in FIG. 9). Such a pressure differential results a pressure gradient that encourages fluid flow crossing over from the high-pressure to the low-pressure. This crossing over flow is referred to as a cross flow 312. It should be understood that the high-pressure region 304 and low-pressure region 306 are in relation to each other, i.e. the high-pressure region 304 has a higher pressure than the low-pressure region 306.

As is illustrated, the set of fences 230 and the splitter 220 together can retard the main fluid flow 310 from flowing along the cross flow 312. As a result, the flow moving from high-pressure region 304 towards the low-pressure region 306 is reduced.

The additional aerodynamic structures 278, 280 only serve to enhance these benefits. The tunnel 282 formed by the bridge 278 serves to decrease mixing losses caused by any secondary flow 308, by way of non-limiting example flow coming from a seal, shaft, or disk below. The trench 280 serves to guide the secondary flow 308 to define the guided flow 312 which when passed through the tunnel 282 can become an accelerated flow 314.

The combination of the aerodynamic structures, the set of fences 230, the splitter 220, the bridge 278 and the trench 280 together contain and guide the secondary flow 308. The

splitter 220 and bridge 278 together form the tunnel 282 which contains the secondary flow 308 and helps to reduce impact caused by any interaction of the main fluid flow 310 with the end wall 290 and injection of the secondary flow 308 from inter-stage seals or rotor tip clearance cavities. The trench 280 provides a guided path for the secondary flow 308 to enable orientation and driving of the secondary flow 308 in the most appropriate direction for minimization of impact on the main fluid flow 310. While each aerodynamic structure provides benefits as described herein, a combination of all of the aerodynamic structures provides the highest levels of improvement and benefits for containing and guiding flows within the engine

To the extent not already described, the different features and structures of the various aspects can be used in combination, or in substitution with each other as desired. That one feature is not illustrated in all of the examples is not meant to be construed that it cannot be so illustrated, but is done for brevity of description. Thus, the various features of the different aspects can be mixed and matched as desired to form new aspects, whether or not the new aspects are expressly described. All combinations or permutations of features described herein are covered by this disclosure.

This written description uses examples to describe aspects of the disclosure described herein, including the best mode, and also to enable any person skilled in the art to practice aspects of the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of aspects of the disclosure is defined by the claims, and can include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Further aspects of the invention are provided by the subject matter of the following clauses:

An airfoil assembly for a turbine engine comprising an outer band, an inner band radially spaced inwardly from the outer band to define an annular region therebetween, and having an upstream edge and a downstream edge, with a surface extending therebetween, and multiple airfoils circumferentially spaced in the annular region wherein each corresponding airfoil of the multiple airfoils includes an outer wall defining a pressure side and a suction side extending between a leading edge and a trailing edge to define a chord-wise direction and extending between a root and a tip to define a span-wise direction, with the root abutting the surface, and a projection extending upwardly from the surface on the pressure side and a valley extending into the surface on the suction side to define a contour to the surface, and the projection having an apex located from the leading edge between -10% and 10% of a normalized axial chord line for the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the projection has a height between 0.5% and 2.5% of a span from the root to the tip of the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the valley has a maximum depth between 0.15% and 1.5% of the span of the corresponding airfoil.

The airfoil assembly any preceding clause wherein the maximum depth of the valley is located along the suction side less than 70% of axial chord along a mean camber line of the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the valley has an upstream edge located at or in front of the leading edge of the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the valley has a maximum circumferential width maximum of 20% of a pitch length from the suction side of the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the valley has a maximum depth of 1.5% of the span of the corresponding airfoil.

The airfoil assembly of any preceding clause, further comprising a splitter extending upwardly from the surface and located between the pressure side and suction side of a pair of adjacent airfoils of the multiple airfoils.

The airfoil assembly of any preceding clause wherein the valley is located between the splitter and the suction side of the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the valley is located closer to the splitter than the suction side of the corresponding airfoil.

The airfoil assembly of any preceding clause, further comprising at least one fence extending laterally from the pressure side of the corresponding airfoil.

The airfoil assembly of any preceding clause wherein the at least one fence comprises a set of fences having at least an upper fence and a lower fence, the upper fence being radially spaced from the lower fence.

The airfoil assembly of any preceding clause wherein the fence follows a local contour of the surface.

The airfoil assembly of any preceding clause wherein the at least one fence is located a predetermined height above the local contour.

The airfoil assembly of any preceding clause wherein the predetermined height is a fixed height.

The airfoil assembly of any preceding clause wherein the predetermined height linearly increases in a direction from the leading edge to the trailing edge.

The airfoil assembly of any preceding clause wherein the at least one fence wraps around the leading edge.

The airfoil assembly of any preceding clause wherein a distance the at least one fence projects from the pressure side reduces from the leading edge to the trailing edge.

The airfoil assembly of any preceding clause, further comprising a splitter extending upwardly from the surface and located between the pressure side and suction side of the corresponding airfoil, with a maximum depth of the valley located closer to the suction side of the corresponding airfoil than the splitter

The airfoil assembly of any preceding clause wherein the projection has a maximum height between 0.5% and 2.5% of a span from the root to the tip the corresponding airfoil, the valley extends along the suction side from the leading edge to the trailing edge and has a maximum depth of 1.5% of the span, and a maximum width of 20% of a pitch length from the suction side, a ratio of the height to the maximum depth is 3, and the fence wraps around the leading edge, terminates before the trailing edge, and projects a distance from the pressure side, with the distance diminishing from the leading edge toward the trailing edge.

What is claimed is:

1. An airfoil assembly for a turbine engine, the airfoil assembly rotatable about a rotational axis and comprising: an outer band;

an inner band radially spaced inwardly from the outer band to define an annular region therebetween, the inner band having an upstream edge, a downstream edge and a surface extending therebetween, with at

least a portion of the surface extending circumferentially along a surface baseline defined by a constant radial distance from the rotational axis;

a pair of circumferentially adjacent airfoils, with each airfoil of the pair of circumferentially adjacent airfoils having an outer wall extending between a leading edge and a trailing edge and between a root and a tip in a span-wise direction a total length between the root and the tip, the outer wall defining a pressure side and a suction side and the root provided along the surface at the surface baseline;

a projection extending radially outward from a portion of the surface at the surface baseline and being provided on the pressure side of the outer wall of a corresponding airfoil of the pair of circumferentially adjacent airfoils; and

a valley separate and spaced from the projection, the valley provided along the surface and extending radially inward from the surface baseline to a maximum depth;

wherein the surface extends along a total surface area, with the surface being at the surface baseline a greater amount of the total surface area than the valley and the projection.

2. The airfoil assembly of claim 1, wherein the projection has a height between 0.5% and 2.5% of a span from the root to the tip of the corresponding airfoil.

3. The airfoil assembly of claim 1, wherein the valley has an upstream edge located at or in front of the leading edge of the airfoil.

4. The airfoil assembly of claim 3, wherein the valley has a maximum circumferential width of 20% of a pitch length from the suction side of the airfoil.

5. The airfoil assembly of claim 1, further comprising at least one fence extending laterally from the pressure side of the corresponding airfoil.

6. The airfoil assembly of claim 5 wherein the at least one fence comprises a set of fences having at least an upper fence and a lower fence, the upper fence being radially spaced from the lower fence.

7. The airfoil assembly of claim 5 wherein the at least one fence follows a local contour of the surface.

8. The airfoil assembly of claim 7 wherein the at least one fence is located a predetermined height above the local contour.

9. The airfoil assembly of claim 8 wherein the predetermined height is a fixed height.

10. The airfoil assembly of claim 8, wherein the predetermined height linearly increases in a direction from the leading edge to the trailing edge.

11. The airfoil assembly of claim 7, further comprising a splitter extending upwardly from the surface and located circumferentially between the pair of circumferentially adjacent airfoils, with a maximum depth of the valley located closer to the suction side of the airfoil than the splitter.

12. The airfoil assembly of claim 5 wherein the at least one fence wraps around the leading edge.

13. The airfoil assembly of claim 5 wherein a distance the at least one fence projects from the pressure side reduces from the leading edge to the trailing edge.

14. An airfoil assembly for a turbine engine, the airfoil assembly rotatable about a rotational axis and comprising: a platform having an upstream edge and a downstream edge, with a platform surface extending therebetween, with at least a portion of the platform surface extending along a platform surface baseline defined by a constant radial height from the rotational axis;

17

- a pair of circumferentially adjacent airfoils, with each airfoil of the pair of circumferentially adjacent airfoils having an outer wall extending between a leading edge and a trailing edge and between a root and a tip in a span-wise direction a total length between the root and the tip, the outer wall defining a pressure side and a suction side and the root provided along the platform surface at the platform surface baseline;
- a projection provided along a portion of the platform surface and against the outer wall of a corresponding airfoil of the pair of circumferentially adjacent airfoils, the projection extending radially outward from the platform surface baseline;
- a splitter provided along a portion of the platform circumferentially between the pair of circumferentially adjacent airfoils, the splitter extending radially outward from the platform surface baseline; and
- a valley provided along the platform surface and extending radially inward from the platform surface baseline to a maximum depth, the valley being located entirely between the splitter and the suction side of the corresponding airfoil.

15. The airfoil assembly of claim 14, wherein the valley is located closer to the splitter than the suction side of the corresponding airfoil that the projection is provided along.

16. The airfoil assembly of claim 14, further comprising a fence provided along the outer wall of the corresponding airfoil, with the fence wrapping around the leading edge of the corresponding airfoil.

17. An airfoil assembly for a turbine engine, the airfoil assembly being rotatable about a rotational axis, the airfoil assembly comprising:

18

- a platform having a surface terminating at an end wall provided along an axially forward portion of the surface;
- a pair of circumferentially adjacent airfoils spaced a circumferential distance from one another, with each airfoil of the pair of circumferentially adjacent airfoils having an outer wall extending between a leading edge and a trailing edge to define a chord-wise direction and between a root and a tip in a span-wise direction, the outer wall defining a pressure side and a suction side;
- a splitter circumferentially spaced from the airfoil to define a channel therebetween, with respect to the rotational axis; and
- a trench at least partially formed within the channel and including a trench inlet provided along the end wall, the trench inlet extending circumferentially a distance that is less than the circumferential distance between the pair of circumferentially adjacent airfoils.

18. The airfoil assembly of claim 17, further comprising a bridge extending from the splitter and to the outer wall of the airfoil.

19. The airfoil assembly of claim 18, wherein the splitter extends between a splitter root at the surface and a splitter tip, with the bridge extending from the splitter tip.

20. The airfoil assembly of claim 17, wherein:
 at least a portion of the surface extending circumferentially along a surface baseline defined by a constant radial distance from the rotational axis; and
 the trench extends between the trench inlet and a trench outlet, the trench including a ramped surface defining decreasing depth, with respect to the surface baseline, extending from the trench inlet and towards the trench outlet.

* * * * *