

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2013235173 B2**

(54) Title
Internal combustion engine using a water-based mixture as fuel and method for operating the same

(51) International Patent Classification(s)
F02D 19/08 (2006.01)

(21) Application No: **2013235173** (22) Date of Filing: **2013.03.20**

(87) WIPO No: **WO13/142575**

(30) Priority Data

(31) Number	(32) Date	(33) Country
13/847,555	2013.03.20	US
61/613,550	2012.03.21	US

(43) Publication Date: **2013.09.26**

(44) Accepted Journal Date: **2017.03.16**

(71) Applicant(s)
Maymaan Research, LLC

(72) Inventor(s)
Shmueli, Yehuda;Shmueli, Eitan;Shmueli, Doron

(74) Agent / Attorney
Shelston IP Pty Ltd., Level 21, 60 Margaret Street, Sydney, NSW, 2000, AU

(56) Related Art
WO 2008/077204 A2
WO 2005/071230 A2
US 7370626 B2
US 3738576 A
US 5156114 A
US 2009/0229541 A1
US 2012/0037098 A1



(43) International Publication Date
26 September 2013 (26.09.2013)


- (51) International Patent Classification:
F02D 19/08 (2006.01)
- (21) International Application Number:
PCT/US2013/033100
- (22) International Filing Date:
20 March 2013 (20.03.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/613,550 21 March 2012 (21.03.2012) US
13/847,555 20 March 2013 (20.03.2013) US
- (71) Applicant: MAYMAAN RESEARCH, LLC [US/US];
3700 N. 29th Ave.; #202, Hollywood, Florida 33020 (US).
- (72) Inventors: SHMUELI, Yehuda; 5905 S.W. 58th Court,
Davie, Florida 33314 (US). SHMUELI, Eitan; 5905 S.W.
58th Court, Davie, Florida 33314 (US). SHMUELI,
Doron; 5905 S.W. 58th Court, Davie, Florida 33314 (US).
- (74) Agents: TARLETON, E., Russell et al.; Seed Intellectual
Property Law Group PLLC, Suite 5400, 701 Fifth Avenue,
Seattle, WA 98104-7092 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: INTERNAL COMBUSTION ENGINE USING A WATER-BASED MIXTURE AS FUEL AND METHOD FOR OPERATING THE SAME



(57) Abstract: An internal combustion engine includes a cylinder with a combustion chamber and a piston selectively changing the volume of the combustion chamber. The combustion chamber receives a mixture of air, hydrogen and a liquid fuel consisting essentially of water and a flammable, preferably non-fossil, substance. The contents of the combustion chamber are ignited generating power.

WO 2013/142575 A1

— *with amended claims (Art. 19(1))*

INTERNAL COMBUSTION ENGINE USING A WATER-BASED MIXTURE AS FUEL AND METHOD FOR OPERATING THE SAME

BACKGROUND OF THE INVENTION

Field of Invention

[0001] This invention pertains to a method and apparatus for operating an internal combustion engine using a fuel consisting of water and a water-soluble flammable substance that is injected into a mixture of hydrogen and air.

Description of the Prior Art

[0002] Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common general knowledge in the field.

[0003] The use of fossil fuels to run engines that used, for example, in cars and other vehicles, as well as many other engines used for a variety of purposes, is based on a very old concept based on the internal combustion engines developed in the nineteenth century. Despite intense research and development for alternate fuels for the last 50 years, fossil fuel derived from petroleum or natural gas, is still essentially the primary source of energy almost all the internal combustion engines presently in use all over the world.

[0004] As a result, the world supply of fossil fuels have been severely depleted creating a shortage, and the price of oil has been climbing for the past 40 years. In addition such fuels are very polluting and some suggest that it has either been the primary cause or has contributed substantially to global warming. All these factors led to many efforts to find and harness renewable energy sources other than traditional fossil fuels. Several alternative fuels have been introduced in the past few years to reduce the impact of petroleum depletion, including hybrid cars, electric cars, bio diesel, hydrogen based cars, etc. However, none of these solutions were effective. One reason for this lack of success is that they require a completely new infrastructure for the production of the engines, as well as the production and distribution of the fuel. Moreover, the most solutions proposed so far were incompatible with the existing engines and, therefore. The cost of replacing all the existing fossil burning engines may be so high that it may render any solution based on alternate fuels unacceptable, at least, in a short term basis.

[0005] Water as a source of fuel has been suggested by many in the past and many experiments have been conducted testing such systems. The basis of such experiments is the fact that water can be separated into hydrogen and oxygen and the resulting stoichiometric mixture can be fed into an internal combustion engine to generate power. However past experiments yielded unsatisfactory results. The main obstacle for their success is based on the fact that the energy required to separate the water into its components is much greater than the energy produced by the engine. In addition the amount of H₂ mixture needed to run a typical automotive engine is too large to make such a system practical.

[0006] Systems are presently available on market that can be used as accessories or add-ons to internal combustion engines using fossil fuels, however independent tests have shown that, in fact, these systems have very little, if any, effect on the overall efficiency of the engine.

[0007] A system developed by the present inventors is described in two co-pending applications includes means of generating from water and supplying a small amount of hydrogen/oxygen gas mixture into a standard internal combustion engine. (See U.S. Patent Application Publications 2010/0122902 and 2011/0203977). More specifically, these co-pending applications describe an efficient process and apparatus for generating a two-to-one mixture of hydrogen and oxygen, commonly referred to as brown gas or HHO. The mixture helps increase the efficiency of the conventional internal combustion engine by burning the fossil fuel more efficiently. While this latter system is much more efficient than previously described systems; its efficiency is still limited by the amount of hydrogen and oxygen produced on board a vehicle. Moreover, the internal combustion engine described is still burning a fossil fuel.

SUMMARY OF THE INVENTION

[0008] According to a first aspect of the invention, there is provided an internal combustion engine for use with only non-fossil fuel, the engine comprising: at least one cylinder having a combustion chamber; a hydrogen source configured to provide hydrogen, and an oxygen source configured to provide oxygen, at least one of the hydrogen source and the oxygen source in fluid communication with the combustion chamber to provide at least one of hydrogen and oxygen to the combustion chamber; a fuel source configured to provide only a non-fossil fuel of water and a water-soluble, non-fossil flammable substance; a fuel injector configured to selectively inject the fuel from the fuel source to the combustion

chamber; at least one piston in the at least one cylinder and structured to move within the at least one cylinder and compress the hydrogen, oxygen, and fuel together in the combustion chamber with a compression ratio in the range of 10/1 to 40/1; and an ignition device configured to ignite the compressed hydrogen, oxygen, and fuel in the combustion chamber to generate power.

[0009] According to a second aspect of the invention, there is provided a method of generating power using a non-fossil fueled internal combustion engine, the method comprising: introducing hydrogen and oxygen into a combustion chamber of the internal combustion engine; introducing a non-fossil fuel consisting essentially of water and a water-soluble, non-fossil flammable substance into the combustion chamber; compressing the hydrogen, oxygen, and the fuel with a piston in the combustion chamber with a compression ratio in the range of 10/1 and 40/1; and igniting the compressed hydrogen, oxygen, and fuel in the combustion chamber to create power.

[0010] According to a third aspect of the invention, there is provided a vehicle, comprising: an internal combustion engine for use with only non-fossil fuel, the engine comprising: at least one cylinder having a combustion chamber; a hydrogen source configured to provide hydrogen, and an oxygen source configured to provide oxygen, at least one of the hydrogen source and the oxygen source in fluid communication with the combustion chamber to provide at least one of hydrogen and oxygen to the combustion chamber; a fuel source configured to provide a fuel of water and a water-soluble, non-fossil flammable substance; a fuel injector configured to selectively deliver the fuel from the fuel source to the combustion chamber; at least one piston in the at least one cylinder and structured to move within the at least one cylinder and compress the hydrogen, oxygen, and fuel together in the combustion chamber with a compression ratio in the range of 10/1 to 40/1; and an ignition device configured to ignite the compressed hydrogen, oxygen, and fuel in the combustion chamber to generate power.

[0011] A vehicle, comprising an internal combustion engine for use with only non-fossil fuel, the engine comprising: at least one cylinder having a combustion chamber; a hydrogen source configured to provide hydrogen, and an oxygen source configured to provide oxygen, at least one of the hydrogen source and the oxygen source in fluid communication with the at least one cylinder to provide at least one of hydrogen and oxygen to the combustion cylinder; a fuel source configured to provide a non-fossil fuel consisting essentially of water and a water-soluble, non-fossil flammable substance; a fuel injector configured to selectively deliver the fuel from the fuel source to the combustion chamber; at least one piston in the at least

one cylinder and structured to move within the at least one cylinder and compress the hydrogen, oxygen, and fuel together in the combustion chamber with a compression ratio in the range of 10/1 to 40/1; and an ignition device configured to ignite the compressed hydrogen, oxygen, and fuel in the combustion chamber to generate power.

[0012] Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise”, “comprising”, and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to”.

[0013] Briefly, an internal combustion engine includes a cylinder with a combustion chamber having a variable volume as defined by a reciprocating piston in a generally conventional manner. Hydrogen and air are initially fed into the combustion chamber. Then, a fuel in form of fine droplets of liquid are injected into the compressed combustion chamber. The resulting liquid/gas mixture is then compressed to a very high pressure, which causes the temperature to rise, and an ignition device causes combustion. The combustion results in hot and pressurized gases that cause the piston to move and generate power. Advantageously, the fuel consists essentially of water and a flammable substance. The flammable material is an alcohol, acetone, aldehyde or other flammable, preferably non-fossil substance that is soluble in water. (The term non-fossil is used to refer to a fuel that is not derived substantially from fossil-base, non renewable materials, such oil or natural gas, but from a renewable source.) Preferably the fuel contains approximately 10-40% flammable material by volume.

[0014] The system and method described herein can be adapted to any engine such as rotary and jet engines and are not limited to a piston based as long as the engine can be used to implement the basic principle of the invention,. This basic principle includes (1) mixing hydrogen and air with a solution of water and a flammable, water soluble fuel (2) compressing the mixture to a high pressure to create high heat and a very explosive mixture in a combustion chamber, and (3)igniting the explosive mixture to cause the sudden expansion of such gases and the formation of steam thereby generating mechanical power.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Fig. 1 shows a first embodiment of the invention in which H₂, air and an aqueous solution forming a fuel is introduced directly into the combustion chamber of the engine with the H₂ and the air being introduced through a common intake.

[0016] Figs. 2A and 2B show sectional and side views of some elements of an internal combustion engine constructed in accordance with this invention.

[0017] Fig. 3 shows a second embodiment in which the ingredients are first mixed in a mixing chamber before exploding.

[0018] Fig. 4 shows a third embodiment of the invention in which air is introduced through the intake manifold and H₂ are introduced by way of injection directly to the compression chamber.

DETAILED DESCRIPTION OF THE INVENTION

[0019] Fig. 1 shows an engine 100 constructed in accordance with this invention. The engine includes a cylinder 10, with a reciprocating piston 12 driving a shaft (not shown) through a linkage 14. For example, an experimental engine 100 was constructed by the inventors, by modifying a generic, off the shelf 400 cc Diesel engine. The engine 100 further includes a conventional air intake manifold 26 with an air intake 28 and a butterfly-type adjustment valve 30, an intake valve 64, an exhaust valve 66, an exhaust manifold 70 and a fuel injector 48.

[0020] In a conventional four cycle Diesel engine, air is sucked in through manifold 26 into the combustion chamber 50 of the cylinder 10 while the piston 12 moves down. The intake valve 64 then closes, the piston 12 moves up and a Diesel fuel is injected by the injector 48 into the chamber 50. The piston 12 compresses the mixture of air and fuel and combustion occurs. The piston 12 then moves down to drive the shaft and moves up again, and the exhaust valve 66 opens exhausting the remaining gases through the exhaust manifold 70.

[0021] The modified engine 100 further includes a hydrogen source 20. In one embodiment, source 20 is implemented as a reactor that generates a stoichiometric H₂/O₂ gas mixture (herein referred to as brown gas) from water using electrolysis process. An example of such process is described in more detail in U.S. Patent Application Publications 2010/0122902 and 2011/0203977. The brown gas is fed through a tube 22 and a valve 24 into intake manifold 26. It should be understood that the amount of brown gas introduced into the intake manifold as compared to the amount of air (that inherently also includes oxygen) is so small that the oxygen from the brown gas is negligible and can be ignored. In effect, the brown gas generator is used as a source of hydrogen. Obviously, other types of hydrogen generator can be used as alternatives to the brown gas generator as well.

[0022] The intake manifold 26 also receives ambient air through the air intake 28 and, as will be discussed in more detail below, the amount of air flowing into the chamber 26 is controlled by the valve 30.

[0023] The engine 100 further includes a fuel tank 40 holding a fuel 42. The fuel 42 is provided through a tube 44 by pump 46 to the fuel injector 48.

[0024] The fuel in the fuel tank consists essentially of water and a flammable substance soluble in water. More specifically, it is believed that the flammable substance should be 30% soluble in water by volume. The flammable substance may include, alcohol, acetone, aldehyde and other similar, preferably non-fossil substances or mixtures thereof. In a preferred embodiment, the flammable substance is an alcohol selected from iso-propyl alcohol, iso butanol, propyl alcohol, butyl alcohol, ethyl alcohol, methyl alcohol or a mixture of such alcohols.

[0025] Alternatively, the flammable substance is one of formaldehyde, acetaldehyde, butyraldehyde, benzaldehyde, cinnamaldehyde, tolualdehyde, furfural, retinaldehyde, glyoxal, malondaldehyde, succindialdehyde, glutaraldehyde, phtalaaldehyde or mixtures thereof.

[0026] The concentration of the flammable material can be in the range of 5-40%, and preferably 10-35%. The inventors have found that, in particular a mixture of about 70% water to 30% isopropyl alcohol is particularly advantageous in that it provides a favorable cost vs. performance characteristics.

[0027] The fuel 42 from the fuel tank 40 is provided to the fuel injector 48 by pump 43 at a pressure in the range of 200-3,000 psi. In one embodiment, the fuel is injected at a pressure of about 2000 PSI. Systems have been proposed in the past in which water has been separated via electrolysis into H₂ O₂ mixture and then was fed in to the engine intake system. The main fuel used in such known engines was a fossil fuel. In the present engine 100, the fuel 42 is essentially an aqueous mixture of a flammable material, preferably with no fossil components.

[0028] The engine 100 also includes a high-energy ignition system 60 providing electrical current to an ignition device 62 (such as a standard spark plug) extending into the chamber 50 as shown. The system 60 and spark plug 62 are conventional components used for internal combustion engines using gasoline as fuel.

[0029] A timing controller 54 (typically including a microprocessor-not shown) receives input timing signals and a load signal indicative of the load on the engine 100. The input timing signals are typically derived from the position of the crankshaft (not shown). The load signal is indicative of the load on the engine 100 are derived using conventional techniques. In response, the timing controller generates output timing signals that control the operation of ignition device 62, fuel injector 48, valve 24 and air intake valve 30, valves 64 and 66 open and close it controlled by a traditional camshaft (not shown).

[0030] Importantly, the engine 100 operates at a very high compression ratio. Typically, a conventional combustion engine operates at a compression ratio of around 15/1 to 18/1 , except for some very special engines, such as the engines used car racing. The present invention can be constructed to operate in the range of 10/1 -40/1 , and preferably in the range of 25/1 -35/1 . An optimal compression ratio is about 30/1 . This high compression ratio can be achieved by shaping the head of the top of the piston to reduce the volume of the combustion chamber. For example, as shown in Figs. 2A and 2B, the top surface of the piston 12 can be shaped with an indentation 70. This indentation has a predetermined size and shape selected to provide the required compression ratio and to generate turbulence in fuel plume 52. For this purpose, the indentation 70 is placed so that as the piston 12 is moves upward toward the top of the cylinder and the plume of fuel 52 is released by the fuel injector 48, the plume 52 using the shape of the surface of the indentation causing it to swirl.

[0031] In one embodiment of the invention, a single plume 52 is released by the fuel injector 48 in every intake cycle. In an alternate embodiment, 1 -5 plumes are released, depending on several variables, such as the type of fuel being used, the load on the engine, ambient temperature, etc. If more than the one plume is released, the first plume is released much earlier than the combustion point, to enrich the vapor mixture in the chamber 50, and the other plumes are released just prior to combustion, as well during combustion.

[0032] The engine 100 operates in a manner similar to a standard four-cycle internal combustion engine but with some important differences. During the intake cycle, as the piston 12 moves downward, the valves 30, 24 and 64 open to allow air and brown gas to enter into and mix in chamber 50. As explained above, the ratio of brown gas to the volume of the cylinder is very small by volume (about 1/2-2%), that the amount of O₂ in the brown gas as compared to the amount of O₂ in the air is negligible and, and therefore only the hydrogen (H₂) is of any real importance. Next, during the compression cycle, valve 64 closes, and the piston 12 moves upward compressing the gases in chamber 50. At a predetermined point, e.g., typically at around 20 degrees btdc (before top dead center), a plume 52 of fine droplets

2013235173 17 Feb 2017

of fuel is injected into the chamber 50 by fuel injector 48 and it mixes with the air/H₂ mixture. The piston 12 keeps moving upward compressing further to a very high pressure and temperature which create a very explosive content inside the combustion chamber 50. The mixture in chamber 50 is ignited (typically at top dead center) by spark plug 62 or other ignition device causing combustion that converts the mixture within the chamber 50 into very hot and highly pressurized gases including steam. These gases force the piston 12 to move down in the conventional manner. The next upward movement (exhaust cycle) of the piston 12 causes the remains of the combustion to be exhausted through manifold 70. These remains consist mostly of water vapor.

[0033] Surprisingly, at substantially no load, it was found that engine 100 can run at 2500 RPM indefinitely, even when the air intake adjustment valve 30 is closed, and therefore almost no air (and, very little oxygen) is provided to the engine. Apparently, during the compression and/or explosion stages least some of the water from the fuel disassociates into H₂ and O₂ and provides the oxygen necessary for the combustion. The remainder of the water is apparently turning into steam.

[0034] As the load on the engine increases, the valve 30 should be opened; otherwise the engine is slowing down and can stops running. The amount of air being introduced through valve 30 is dependent on the load on the engine and, since apparently the air is not needed for the combustion, it is believed that, as the load increases, in order to maintain RPM and produce power against the load, a higher torque is needed, the air is needed as a working gas that create a higher combustion pressure which intern create a higher torque when is pushing the piston down.

[0035] The operating parameters of the engine 100 as described are as follows:

Compression ratio 30/1;

Fuel 70% water 30% iso-propyl alcohol at ambient temperature;

H₂ 2-10 l/min at standard atmospheric pressure and ambient temperature;

Air 0-50 l/min at ambient pressure and temperature;

Fuel pressure 200-3000 PSI.

[0036] If multiple injections are used, the first injection or pilot consists of 5-30 % of the total fuel and the remainder is then rationed during the combustion cycle.

[0037] While presently the exact phenomenon occurring in the cylinder portion 50 during explosion is not fully understood, it is believed that some if not all of the water from the fuel mixture also disassociates in the cylinder into H₂ and O₂ and provides more fuel for conversion which is triggered by the H₂/O₂ that is fed in to the chamber, It was found that the process worked well when a volume of 2 ml. of the H₂/O₂ gas mixture was provided to the engine for every revolution. Since the engine is a 400 ml (or 400 cc) engine,. The amount of H₂/O₂ provided for each revolution is about 1/2-2% of H₂ by volume.

[0038] As discussed above, the fuel is preferably a solution of water and a flammable liquid substance. In addition an additive can be added, such as a non corrosive material that increase the conductivity of the water at high pressure during combustion thereby helping the separation of the water to H₂/O₂.

[0039] The techniques shown can be easily applied multiple cylinder, in addition to a regular piston or a rotary engine, the invention can be developed turbine and jet engine as well.

[0040] For example a conversion of a Diesel based engine is fairly simple, only the head is needed to be modified in order to introduce the ignition device, a high power ignition system, the shape of the piston and the combustion chamber to allow a suitable compression ratio, and a fairly small H₂/O₂ reactor (or other H₂ source) need to be added, making this solution an inexpensive and simple to introduce to the market place.

[0041] Since water is practically available in any fuel station, no main infrastructure needed to be created. The flammable substance can be automatically mixed with clean water and fed in to the fuel tank of the vehicle.

[0042] Fig. 3 shows another embodiment. In this embodiment, engine 200 is very similar to engine 100. The difference is that a novel mixing chamber 210 is provided at the top of the cylinder 10 in communication with the cylinder portion 50 where the combustion takes place. The H₂ O₂ mixture is fed by a second injector 220 into this mixing chamber 210 (rather than into the chamber 50).

[0043] Thus, the mixing chamber 210 receives both the fuel mixture 42 and the H₂/O₂ mixture. These materials mix with each other and are sucked into the portion 50 when required through a channel 230.

[0044] Fig. 4 shows another embodiment 300. In this embodiment, the water fuel mixture and the H₂/O₂ mixture are both fed directly into the combustion chamber.

[0045] In other words, the H₂/O₂ mixture can be fed to the engine in three different ways: into the manifold, into a mixing chamber, or into the combustion chamber itself.

[0046] The present invention has several advantages. First, it makes use of commonly available renewable substances as fuel, instead of relying on nonrenewable fossil substances. It is believed that the invention is much more efficient and similar engines using on fossil-based fuels and can generate more power. Third, during the experiments performed on the engine, the exhaust from the engine was very clean, minimal pollution being observed, and even in a non ventilated area there was no visible smoke, nor did the inventor found any difficulty breathing.

[0047] Numerous modifications may be made to this invention without departing from its scope as defined in the appended claims.

CLAIMS:

1. An internal combustion engine for use with only non-fossil fuel, the engine comprising:
 - at least one cylinder having a combustion chamber;
 - a hydrogen source configured to provide hydrogen, and an oxygen source configured to provide oxygen, at least one of the hydrogen source and the oxygen source in fluid communication with the combustion chamber to provide at least one of hydrogen and oxygen to the combustion chamber;
 - a fuel source configured to provide only a non-fossil fuel of water and a water-soluble, non-fossil flammable substance;
 - a fuel injector configured to selectively inject the fuel from the fuel source to the combustion chamber;
 - at least one piston in the at least one cylinder and structured to move within the at least one cylinder and compress the hydrogen, oxygen, and fuel together in the combustion chamber with a compression ratio in the range of 10/1 to 40/1; and
 - an ignition device configured to ignite the compressed hydrogen, oxygen, and fuel in the combustion chamber to generate power.
2. The engine of claim 1 wherein the fuel is injected into the combustion chamber at a pressure in the range of 200-3000 PSI.
3. The engine of claim 1 wherein the non-fossil fuel includes 5-40% of the non-fossil flammable substance.
4. The engine of claim 1 wherein the non-fossil flammable substance is 30% alcohol.
5. The engine of claim 1 wherein the hydrogen source is configured to be in selective fluid communication with the combustion chamber via an injector and the oxygen source is configured to be in selective fluid communication with the combustion chamber via an intake manifold.
6. The engine of claim 1 wherein the non-fossil flammable substance includes iso-propyl alcohol.
7. The engine of claim 1 wherein the compressed hydrogen, oxygen, and fuel includes about ½ to 10% hydrogen by volume.

8. A method of generating power using a non-fossil fueled internal combustion engine, the method comprising:
 - introducing hydrogen and oxygen into a combustion chamber of the internal combustion engine;
 - introducing a non-fossil fuel consisting essentially of water and a water-soluble, non-fossil flammable substance into the combustion chamber;
 - compressing the hydrogen, oxygen, and the fuel with a piston in the combustion chamber with a compression ratio in the range of 10/1 and 40/1; and
 - igniting the compressed hydrogen, oxygen, and fuel in the combustion chamber to create power.
9. The method of claim 8 wherein the step of introducing a non-fossil fuel comprises injecting the fuel into the combustion chamber at a pressure in the range of 200-3000 PSI.
10. The method of claim 8 comprising mixing the hydrogen, oxygen, and fuel in a mixing chamber prior to the introducing.
11. The method of claim 8 wherein the fuel includes 10-35% of the non-fossil flammable substance.
12. The method of claim 8 wherein the non-fossil flammable substance is an iso-propyl alcohol.
13. The method of claim 8 wherein the non-fossil flammable substance is alcohol and constitutes 30% of the fuel.
14. The method of claim 8 wherein the compressed hydrogen, oxygen, and fuel includes about ½% to 10% hydrogen by volume.
15. The method of claim 8 wherein the alcohol comprises isopropyl alcohol, and wherein the step of introducing the non-fossil fuel comprises injecting the fuel into the combustion chamber at ambient temperature, and further wherein the step of introducing the hydrogen comprises injecting the hydrogen into the combustion chamber at ambient temperature.
16. The method of claim 15 wherein the compressed hydrogen, oxygen, and fuel includes about ½% to 10% hydrogen by volume.

17. The method of claim 16 comprising mixing the hydrogen, oxygen, and fuel in a mixing chamber prior to the injection of the hydrogen and the fuel into the combustion chamber at ambient temperature.
18. A vehicle, comprising:
 - an internal combustion engine for use with only non-fossil fuel, the engine comprising:
 - at least one cylinder having a combustion chamber;
 - a hydrogen source configured to provide hydrogen, and an oxygen source configured to provide oxygen, at least one of the hydrogen source and the oxygen source in fluid communication with the combustion chamber to provide at least one of hydrogen and oxygen to the combustion chamber;
 - a fuel source configured to provide a fuel of water and a water-soluble, non-fossil flammable substance;
 - a fuel injector configured to selectively deliver the fuel from the fuel source to the combustion chamber;
 - at least one piston in the at least one cylinder and structured to move within the at least one cylinder and compress the hydrogen, oxygen, and fuel together in the combustion chamber with a compression ratio in the range of 10/1 to 40/1; and
 - an ignition device configured to ignite the compressed hydrogen, oxygen, and fuel in the combustion chamber to generate power.
19. The vehicle of claim 18 wherein the fuel is injected into the combustion chamber at a pressure in the range of 200-3000 PSI.
20. The vehicle of claim 19 wherein the non-fossil fuel includes 5-40% of the non-fossil flammable substance.
21. The vehicle of claim 20 wherein the fuel includes 10-35% of the non-fossil flammable substance.
22. The vehicle of claim 19 wherein the hydrogen source is configured to be in selective fluid communication with the combustion chamber via an injector and the oxygen source is configured to be in selective fluid communication with the combustion chamber via the intake manifold.

2013235173 17 Feb 2017

23. The vehicle of claim 22 wherein the alcohol is isopropyl alcohol and constitutes 30% of the fuel and water constitutes 70% of the fuel.
24. The vehicle of claim 23 wherein the compressed hydrogen, oxygen, and fuel includes about ½% to 10% hydrogen by volume.
25. A vehicle, comprising
an internal combustion engine for use with only non-fossil fuel, the engine comprising:
 - at least one cylinder having a combustion chamber;
 - a hydrogen source configured to provide hydrogen, and an oxygen source configured to provide oxygen, at least one of the hydrogen source and the oxygen source in fluid communication with the at least one cylinder to provide at least one of hydrogen and oxygen to the combustion cylinder;
 - a fuel source configured to provide a non-fossil fuel consisting essentially of water and a water-soluble, non-fossil flammable substance;
 - a fuel injector configured to selectively deliver the fuel from the fuel source to the combustion chamber;
 - at least one piston in the at least one cylinder and structured to move within the at least one cylinder and compress the hydrogen, oxygen, and fuel together in the combustion chamber with a compression ratio in the range of 10/1 to 40/1; and
 - an ignition device configured to ignite the compressed hydrogen, oxygen, and fuel in the combustion chamber to generate power.
26. The vehicle of claim 25 wherein the non-fossil fuel includes 5-40% of the non-fossil flammable substance.
27. The vehicle of claim 25 wherein the fuel includes 10-35% of the non-fossil flammable substance.
28. The vehicle of claim 25 wherein the non-fossil flammable substance is 30% alcohol.
29. The vehicle of claim 25 wherein the hydrogen source is configured to be in selective fluid communication with the combustion chamber via an injector and the oxygen source is configured to be in selective fluid communication with the combustion chamber via an intake manifold.

30. The vehicle of claim 25 wherein the non-fossil flammable substance is iso-propyl alcohol and constitutes 30% of the fuel and water constitutes 70% of the fuel.

31. The vehicle of claim 25 wherein the compressed hydrogen, oxygen, and fuel includes about ½% to 10% hydrogen by volume.

32. The vehicle of claim 25 further comprising a mixing chamber in fluid communication with the combustion chamber and configured to receive and mix the hydrogen, oxygen, and fuel.

33. The vehicle of claim 25 wherein said piston, cylinder and head are arranged to generate a compression ratio of 30/1.




FIG.1




FIG.2A





FIG.2B






FIG.4