

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 200066329 B2
(10) Patent No. 777861

(54) Title
Production of maleic anhydride

(51) 6 International Patent Classification(s)
C07D 307/34

(21) Application No: 200066329 (22) Application Date: 2000.08.11

(87) WIPO No: WO01/14359

(30) Priority Data

(31) Number (32) Date (33) Country
09/377589 1999.08.19 US

(43) Publication Date : 2001.03.19

(43) Publication Journal Date : 2001.05.24

(44) Accepted Journal Date : 2004.11.04

(71) Applicant(s)
Scientific Design Company, Inc.

(72) Inventor(s)
Bharat M. Doshi

(74) Agent/Attorney
Griffith Hack, GPO Box 1285K, MELBOURNE VIC 3001

(56) Related Art
US 4231943
EP 0507617
GB 1516430

AU 200066329

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 March 2001 (01.03.2001)

PCT

(10) International Publication Number
WO 01/14359 A1

(51) International Patent Classification?: C07D 307/34 (74) Agent: LONG, William, C.; 90 Maple Avenue, Morris-
town, NJ 07960 (US).

(21) International Application Number: PCT/US00/21962

(81) Designated States (national): AU, BR, CA, CN, ID, JP,
KR, MX, SG.

(22) International Filing Date: 11 August 2000 (11.08.2000)

(25) Filing Language: English

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).

(26) Publication Language: English

Published:
With international search report.

(30) Priority Data:
09/377,589 19 August 1999 (19.08.1999) US

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(71) Applicant: SCIENTIFIC DESIGN COMPANY, INC.
[US/US]; 49 Industrial Avenue, Little Ferry, NJ 07643-
1901 (US).

(72) Inventor: DOSHI, Bharat, M.; 27 Sturbridge Drive, Pis-
cataway, NJ 08854 (US).



WO 01/14359 A1

(54) Title: PRODUCTION OF MALEIC ANHYDRIDE

(57) Abstract: n-butane and molecular oxygen are reacted in a first reactor to form maleic anhydride, the produced maleic anhydride is scrubbed to separate maleic anhydride values, n-butane is added to the scrubber gases and these are reacted in a second reactor to form additional maleic anhydride.

PRODUCTION OF MALEIC ANHYDRIDEBackground of the Invention1. Field of the Invention

5 The present invention relates to an improved process for the oxidation of n-butane to maleic anhydride. The specific improvement of the present invention resides in the use of a series of reactors to accomplish the n-butane oxidation with removal of product maleic anhydride from the effluent of a
10 reactor prior to forwarding the remaining gases together with supplemental n-butane to the next in the series of oxidation reactors. Air or oxygen enriched air can be used to accomplish the oxidation.

Description of the Prior Art

15 The production of maleic anhydride by the oxidation of n-butane is, of course, by now a well known and commercially practiced process. Primarily the maleic anhydride is produced by introducing n-butane in admixture with air into contact with an oxidation catalyst such as a VPO catalyst under conditions
20 such that the n-butane is oxidized to maleic anhydride. In conventional practices, the effluent from this reactor may be cooled to partially condense the product maleic anhydride from the effluent gases. The gaseous product, with or without partial maleic anhydride removal, is scrubbed using a solvent,
25 usually water, to recover all of product maleic anhydride. The remaining gases, containing unconverted n-butane, are commonly incinerated in an effluent gas incinerator prior to venting to atmosphere.

30 There are references which relate to the use of more than one reactor in series in order to produce maleic anhydride. Specifically, U.S. Patent 5,360,916 provides a two stage process for maleic anhydride production wherein n-butane is oxidized in a first reaction zone and the effluent from this zone is passed together with supplemental n-butane to a second reactor in series in order to complete production of the maleic anhydride.
35 A feature of the process described in this patent is that there

is at most only a partial removal of maleic anhydride by condensation from the effluent from the first of the reactors prior to introduction into the second and last in the series of reactors.

5 A literature article by Bissot et al. entitled "Oxidation of Butane to Maleic Anhydride" appearing in IEC vol. 2 No. 1 March 1963, pages 57-60 discloses a process for maleic anhydride production wherein n-butane is oxidized in a series of fluidized bed reactors using a
10 cobalt or nickel molybdate catalyst, the effluent from the first of the reactors passing to the second reactor after intermediate removal of product maleic anhydride. There is no teaching in this literature reference of the addition of supplemental n-butane to the effluent of the first of
15 the reactors prior to continuing the reaction in a second reactor after maleic anhydride removal.

BRIEF DESCRIPTION OF THE INVENTION

According to the present invention there is provided
20 a process for the production of maleic anhydride from n-butane which comprises reacting a mixture of molecular oxygen containing gas and 0.5-3 vol % n-butane in a first reactor at conditions effective for the formation of maleic anhydride, scrubbing the reaction gas mixture from
25 the first reactor to recover the maleic anhydride values from the remaining reaction gas mixture components, separating the scrubber liquid containing said maleic anhydride values, adding n-butane to said remaining reaction gas mixture components and reacting the resulting
30 gas mixture in a second reactor at conditions effective for the formation of maleic anhydride.

In accordance with the present invention, n-butane is oxidized using a VPO catalyst in a first reactor, preferably a fixed bed reactor, in order to produce maleic
35 anhydride. This reaction is carried out in accordance with known procedures. The effluent from this first reactor is cooled and either optionally treated for partial

condensation of product maleic anhydride by cooling and/or directly scrubbed with liquid, preferably water, to separate all of the remaining maleic anhydride formed in the first reactor. The gases from the scrubber which 5 comprise unreacted n-butane and unreacted oxygen, are passed together with supplemental added n-butane to a second reactor, preferably a similar fixed bed reactor, wherein the reaction is continued converting n-butane to additional product maleic anhydride. The effluent from the 10 second reactor is then treated in accordance with conventional procedures to recover the product maleic anhydride values. Where more than two reactors are employed, the scrubber gases are further treated as above described; that is oxidized to maleic anhydride after 15 addition of supplemental n-butane.

333

555

- 2a -

Brief Description of the Drawings

The accompanying Figure illustrates in schematic form a suitable practice of the present invention.

Detailed Description

5 In accordance with the present invention, n-butane together with a molecular oxygen containing gas such as air or oxygen enriched air is introduced into a first reaction zone and therein the n-butane is oxidized by conventional procedures using a VPO catalyst to produce maleic anhydride. The gaseous effluent from this first reactor is then passed to a first scrubbing zone, optionally after part of the maleic anhydride is removed by partial condensation, wherein product maleic anhydride formed in the first reactor is scrubbed from these effluent gases and comprises a product of the process; some of the water of reaction is also removed in the scrubbing zone. The gases from the scrubber comprised of some unreacted n-butane, unreacted oxygen, carbon monoxide, carbon dioxide, nitrogen and the like are then passed to a second reactor and therein further reacted to form additional maleic anhydride.

10 Prior to introduction of this gas stream into the second reactor, supplemental n-butane is added to the feed in order to obtain a n-butane enriched feed stream to the second reactor. In the second reactor the gas mixture is oxidized using a VPO catalyst to produce additional maleic anhydride. Effluent from the second reactor after removal of all product maleic anhydride in the second scrubber can, if economical, be passed to a still further series reactor together with supplemental n-butane or the gases from the second reactor may be incinerated prior to discharge to the atmosphere.

15 A striking advantage of the present invention is the fact that operating costs including raw material costs and power costs are substantially reduced. Maleic anhydride production as a function of the capital needed for construction of a new maleic anhydride installation can be significantly reduced in accordance with the present invention. Thus, economies are

effected in the compressor, scrubber, and other elements of equipment and lower operating costs are incurred in the production of the desired maleic anhydride. A main advantage in capital cost saving comes from a reduction in the size of the 5 vent gas incinerator.

The accompanying drawing illustrates a preferred practice of the present invention.

Referring to the drawing, reactor 1 is a conventional multi tube fixed bed reactor packed with VPO catalyst suitable for the 10 oxidation of n-butane to maleic anhydride in accordance with known procedures. A gas mixture comprised of n-butane and molecular oxygen (illustratively introduced as air) passes via line 2 to reactor 1 and is distributed to the various reactor tubes located therein. These tubes are surrounded by a 15 circulating heat removal medium such as molten salt in accordance with known procedures. In passing through reactor 1 n-butane is reacted with the molecular oxygen under conditions effective to produce maleic anhydride.

The reaction mixture exits reactor 1 via line 3 and passes 20 to scrubber 4. Scrubbing water is introduced into scrubber 4 by means of line 5 and in the scrubber maleic anhydride is effectively scrubbed from the mixture of reaction gases from reactor 1. An aqueous stream containing the scrubbed maleic 25 anhydride, now in the form of maleic acid, exits scrubber 4 via line 6 and passes to refining wherein maleic anhydride is recovered by known procedures.

As an important feature of the present invention, the 30 scrubbed gases from scrubber 4 exit via line 7 and pass to a second reactor, reactor 8, which can be similar to reactor 1 and indeed preferably contains the same VPO catalyst which is contained in reactor 1. As a critical feature of the present invention, supplemental n-butane is added to the exit gases from scrubber 4 via line 9, and this combination of gases is introduced as feed into reactor 8 and therein reacted under 35 conditions effective for the oxidation of n-butane to maleic

anhydride in accordance with known procedures.

Reaction gases from reactor 8 exit via line 10 and pass to scrubber 11 wherein these gases are contacted with scrubbing water which is introduced via line 12. Additional product maleic anhydride values are recovered in the aqueous stream removed from scrubber 11 via line 13. This stream may be combined with the stream from line 6 and together passed to a refining section wherein by conventional procedures maleic anhydride product is recovered.

Gases from scrubber 11 exit via line 14, these gases comprising a small amount of unreacted n-butane, which can be incinerated, together with unreacted oxygen in minor amount, nitrogen, and various carbon oxides together with various amounts of water. These gases are disposed of in accordance with known procedures.

An important advantage of practice of the present invention when compared to conventional single reactor procedures is that, for the two reactors in series, for the same maleic anhydride production the air feed rate and the vent gas load are cut almost in half. Overall n-butane consumption is substantially reduced, by as much as 10%, the power required in the air compressor is reduced by as much as 20% and the operating costs of a vent gas incinerator associated with the process is reduced by almost half. In addition, the capital cost of this vent gas incinerator is reduced substantially.

N-butane consumption is reduced largely because the n-butane contained in the gases exiting the first reactor rather than being flared or incinerated is fed to the second reactor. The advantages of this procedure are partially offset by a somewhat lower selectivity in the second stage reactor due to a less favorable inlet gas composition but on balance the advantages achieved through practice of the present invention result in up to 10% reduction in n-butane consumption for the same maleic anhydride production.

The same or different catalysts of the VPO type can be used

in the several reactors; preferably the same catalyst is employed in each reactor. An especially useful catalyst is that described in U.S. Patent 5,885,919 although practice of the invention is not restricted to the use of any particular catalyst.

The oxidation of the n-butane to maleic anhydride in each reactor is accomplished by contacting n-butane in low concentrations in oxygen with the described catalyst. Air is entirely satisfactory as a source of oxygen for the first reactor but synthetic mixtures of oxygen and diluent gases, such as nitrogen also may be employed. Air enriched with oxygen may be employed.

The gaseous feed stream to the first reactor normally will contain air and about 0.5 to about 3.0 mole percent n-butane. About 1.0 to about 2.5 mole percent of n-butane are satisfactory for optimum yield of product for the process of this invention. Although higher concentrations may be employed, explosion hazards may be encountered except in fluidized bed reactors where concentrations of up to about 4 or 5 mole percent can be used without explosive hazard. Lower concentrations of n-butane, less than about one percent, of course, will reduce the total productivity obtained at equivalent flow rates and thus are not normally economically employed.

The flow rate of the gaseous stream through the first reactor may be varied within rather wide limits but a preferred range of operations is at the rate of about 10 to 300 grams of n-butane per liter of catalyst per hour and more preferably about 50 to about 250 grams of n-butane per liter of catalyst per hour. Residence times of the gas stream will normally be less than about 4 seconds, more preferably less than about one second, and down to a rate where less efficient operations are obtained.

The temperature of reaction in the first reactor may be varied within some limits, but normally the reaction should be conducted at temperatures within a rather critical range. The

oxidation reaction is exothermic and once reaction is underway, the main purpose of the salt bath or other media is to conduct heat away from the walls of the reactor and control the reaction. Better operations are normally obtained when the reaction temperature employed is no greater than about 100°C above the salt bath temperature. The temperature in the reactor tubes, of course, will also depend to some extent upon the size of the tubes and the n-butane concentration. Under usual operating conditions in a preferred procedure, the temperature in the center of the reactor, measured by thermocouple, is about 365° to about 550°C. The range of temperature preferably employed in the reactor, measured as above, should be from about 380°C to about 515°C and the best results are ordinarily obtained at temperatures from about 380°C to about 475°C. Described another way, in terms of salt bath reactors with carbon steel reactor tubes about 1.0" in diameter, the salt bath temperature will usually be controlled between about 350°C to about 550°C. Under normal conditions, the temperature in the reactor ordinarily should not be allowed to go above about 475°C for extended lengths of time because of decreased yields and possible deactivation of the catalyst.

The reaction may be conducted at atmospheric, super atmospheric or below atmospheric pressure. The exit pressure will be at least slightly higher than the ambient pressure to insure a positive flow from the reaction. The pressure of the gases must be sufficiently high to overcome the pressure drop through the reactor.

In accordance with the invention, the gaseous effluent exiting the first reactor is scrubbed with water optionally after separation of some maleic hydride by cooling and condensation in order to separate essentially all product maleic anhydride values leaving a gas mixture containing substantial unreacted n-butane and molecular oxygen values. Generally this gas mixture comprises by volume about 0.1 to 1.0 vol %, the n-butane, preferably 0.2 to 0.6 vol %, the remainder being oxygen,

nitrogen, carbon oxides, and the like. Typically the gas mixture comprises about 0.4 vol % n-butane.

5 N-butane is added to the gas mixture in amount generally sufficient to provide a combined gas mixture comprised by volume of 0.5 to 3.0 vol % n-butane and usually about 10 to 15 vol % molecular oxygen depending upon oxygen consumption in the first reactor. This mixture forms the feed to the second of the series of reactors.

10 The second reactor is similar to the first reactor, preferably containing the same VPO catalyst. Reaction conditions are much the same in the second reactor as in the first, and the reaction gas mixture exiting the second reactor is scrubbed with water to recover the additional maleic anhydride values, optionally after first cooling and condensing 15 some maleic anhydride values. N-butane in the scrubber gases can be incinerated in a vent gas incinerator and vented to atmosphere or otherwise treated.

20 A variety of reactors will be found to be useful and multiple tube heat exchanger type reactors are quite satisfactory for each reactor. The tubes of such reactors may vary in diameter from about 1/4" to about 3", and the length may be varied from about 3 to 18' or longer. The oxidation reaction is an exothermic reaction and, therefore, relatively close 25 control of the reaction temperature should be maintained. It is desirable to have the surface of the reactors at a relatively constant temperature and some medium to conduct heat from the reactors is necessary to aid temperature control. Such media may be Woods metal, molten sulfur, mercury, molten lead, and the like, but it has been found that eutectic salt baths are 30 completely satisfactory. One such salt bath is a sodium nitrate-sodium nitrite-potassium nitrite eutectic constant temperature mixture. An additional method of temperature control is to use a metal block reactor whereby the metal surrounding the tube acts as a temperature regulating body. As 35 will be recognized by one skilled in the art, the heat exchange

medium may be kept at the proper temperature by heat exchangers and the like. The reactor or reaction tubes may be iron, stainless steel, carbon steel or nickel and have excellent long life under the conditions for the reactions described herein. 5 Normally, the reactors contain a preheat zone of an inert material such as 1/4' Alundum pellets, inert ceramic balls, nickel balls or chips and the like, present at about 1/5 to 1/20 the volume of the active catalyst present.

Example 1

10 A two series reactor system, as illustrated in the attached Figure, is provided for the oxidation of n-butane to maleic anhydride.

15 With reference to the Figure, n-butane together with air is fed via line 2 to reactor 1 and therein reacted to form maleic anhydride. Reactor 1 is a conventional multi tube reactor packed with VPO catalyst such as that described in Example 1 of U.S. Patent 5,885,919 and provided with a coolant to remove reaction heat.

20 The feed enters reactor 1 and therein reacts to form maleic anhydride, the hot spot in the tubes is maintained at about 420-460°C, the gas feed is fed at 40-50 psia.

25 The reaction mixture exits reactor 1 via line 3 and is cooled in stages to about 60°C (not shown). The cooled mixture is introduced into scrubber 4 and therein contacted with scrubbing water which is introduced via line 5. The aqueous stream containing the scrubbed maleic anhydride values is removed via line 6 and sent to conventional maleic anhydride recovery.

30 The reaction gas mixture from which maleic anhydride has been scrubbed is removed from scrubber 4 via line 7. Supplemental n-butane is added via line 9 and the resulting admixture is fed to reactor 8.

35 Reactor 8, like reactor 1, is a conventional multi tube reactor packed with the same VPO catalyst used in reactor 1. Hot spot temperature in reactor 8 is 420-460°C and inlet

pressure is about 30-40 psia.

5 The reaction gas mixture is removed from reactor 8 via line 10, cooled (not shown), and passed to scrubber 11 wherein maleic anhydride values are scrubbed with water which is introduced via line 12.

The scrubber liquid containing maleic anhydride formed in reactor 8 is removed from scrubber 11 via line 13 and sent to conventional maleic anhydride recovery.

10 Reaction gases are removed from scrubber 11 via line 14 and sent to a vent gas incinerator prior to venting to the atmosphere.

The following Table 1 gives the amounts and compositions of the various process streams. Table 2 gives the various conversions and selectivities.

Table 1

Stream No.	2		3		7	
Component	Mols/hr	Mol %	Mols/hr	Mol %	Mols/hr	Mol %
n-butane	56.23	1.9200	10.12	0.3389	10.12	0.3618
n-butane	2.34	0.0800		0.0000		0.0000
MAN			32.56	1.0933		
CO			36.58	1.2247	36.58	1.3074
CO ₂			26.13	0.8748	26.13	0.9239
O ₂	586.80	20.0263	388.43	13.0045	388.43	13.8829
N ₂	2213.41	75.5717	2213.53	74.1078	2213.53	79.1136
H ₂ O	70.29	2.4000	279.45	9.3560	123.12	4.4604
Total	2928.89	100	2980.90	100	2797.91	100

Table 1 continued

Stream No.	9		10		14	
Component	Mols/hr	Mol %	Mols/hr	Mol %	Mols/hr	Mol %
n-butane	45.68	96.0000	11.01	0.3795	11.01	0.3975
n-butane	1.90	4.0000				
MAN			31.08	1.0715		
CO			71.89	2.4784	71.89	2.5975
CO ₂			51.35	1.7703	51.35	1.8541
O ₂			199.80	6.8880	199.80	7.2104
N ₂			2214.02	78.3266	2214.02	79.9387
H ₂ O			321.56	11.0856	221.57	8.0000
Total	47.59	100	2900.71	100	2769.64	100

Table 2

Basis Production of 63.74 mols/hr MPA (equivalent to 6250 kg/hr of Product MAN)			
	REACTOR 1	REACTOR 2	OVERALL for the Plant
Total n-butane Mol %	2.00	2.00	3.57
n-butane Purity %	96.00	96.70	96.00
Conc. n-butane	1.92	1.93	3.42
Conc. n-butane	0.08	0.06	0.14
Conv. n-butane	82.00	80.00	89.05
Conv. n-butane	100.00	100.00	100.00
Overall Conv %	82.72	80.86	89.49
Selectivity %	70.81	69.62	69.89
Rx Yield, wt. %	98.00	94.00	105.54

Example 2

This example illustrates practice of the invention using oxygen enriched air as the molecular oxygen containing gas in the first reactor in the two series reactor system as shown in the accompanying Figure.

With reference to the Figure, n-butane together with air enriched with oxygen to an oxygen concentration of 28 vol % (dry basis) is fed via line 2 to reactor 1 and therein reacted to form maleic anhydride. Reactor 1 is a conventional multi tube reactor packed with VPO catalyst such as that described in Example 1 of U.S. Patent 5,885,919 and provided with a coolant to remove reaction heat.

5 The feed enters reactor 1 and therein reacts to form maleic anhydride, the hot spot in the tubes is maintained at about 420-460°C, the gas feed is fed at 40-50 psia.

10 The reaction mixture exits reactor 1 via line 3 and is cooled in stages to about 60°C (not shown). The cooled mixture is introduced into scrubber 4 and therein contacted with scrubbing water which is introduced via line 5. The aqueous 15 stream containing the scrubbed maleic anhydride values is removed via line 6 and sent to conventional maleic anhydride recovery.

10 The reaction gas mixture from which maleic anhydride has been scrubbed is removed from scrubber 4 via line 7. Supplemental n-butane is added via line 9 and the resulting admixture is fed to reactor 8.

20 Reactor 8, like reactor 1, is a conventional multi tube reactor packed with the same VPO catalyst used in reactor 1. Hot spot temperature in reactor 8 is 420-460°C and inlet 25 pressure is about 30-40 psia.

25 The reaction gas mixture is removed from reactor 8 via line 10, cooled (not shown), and passed to scrubber 11 wherein maleic anhydride values are scrubbed with water which is introduced via line 12.

30 The scrubber liquid containing maleic anhydride formed in reactor 8 is removed from scrubber 11 via line 13 and sent to conventional maleic anhydride recovery.

35 Reaction gases are removed from scrubber 11 via line 14 and sent to a vent gas incinerator prior to venting to the atmosphere.

The following Table 3 gives the amount and compositions of the various process streams. Table 4 gives the various conversions and selectivities.

Table 3

Stream No.	2	3	7			
Component	Mols/hr	Mol %	Mols/hr	Mol %	Mols/hr	Mol %
n-butane	54.331	1.9200	9.78	0.3391	9.78	0.3621
iso-butane	2.264	0.0800		0.0000		0.0000
MAN			32.82	1.1380		
CO			33.08	1.1470	33.08	1.2247
CO ₂			23.63	0.8193	23.63	0.8748
O ₂	757.460	26.7681	567.79	19.6878	567.79	21.0216
N ₂	1947.747	68.8319	1947.85	67.5409	1947.85	72.1164
H ₂ O	67.913	2.4000	269.01	9.3279	118.85	4.4004
Total	2829.715	100	2863.95	100	2700.98	100

Table 3 continued

Stream No.	9		10		14	
Component	Mols/hr	Mol %	Mols/hr	Mol %	Mols/hr	Mol %
n-butane	44.46	96.0000	9.56	0.3413	9.56	0.3583
iso-butane	1.85	4.0000				
MAN			30.92	1.1034		
CO			68.17	2.4330	68.17	2.5538
CO ₂			48.69	1.7379	48.69	1.8241
O ₂			381.22	13.6054	381.22	14.2805
N ₂			1948.29	69.5333	1948.29	72.9634
H ₂ O			315.10	11.2456	213.56	8.0000
Total	46.34	100	2801.95	100	2669.50	100

Table 4

Basis Production of 63.74 mol/s/hr MAN (equivalent to 6250 kg/hr of Product MAN)			
	REACTOR 1	REACTOR 2	OVERALL FOR THE PLANT
Total n-butane Mol. #	2.00	2.00	3.56
N-butane Purity %	96.00	96.70	96.00
Conc. n-butane	1.32	1.93	3.42
Conc. iso-butane	0.08	0.06	0.14
Conv. n-butane	82.00	82.00	90.15
Conv. iso-butane	100.00	100.00	100.00
Overall Conv. %	82.72	82.59	90.54
Selectivity %	72.98	69.37	70.88
Rx Yield, wt. %	101.00	96.00	108.30

A comparison of Examples 1 and 2 demonstrates the improved yields which are achieved through practice of the invention wherein oxygen enriched air is fed to the first reactor.

In the claims of this application and in the description of the invention, except where the context requires otherwise due to express language or necessary implication, the words "comprise" or variations such as 5 "comprises" or "comprising" are used in an inclusive sense, i.e. to specify the presence of the stated features but not to preclude the presence or addition of further features in various embodiments of the invention.

888

1000

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A process for the production of maleic anhydride from n-butane which comprises reacting a mixture of molecular oxygen containing gas and 0.5-3 vol % n-butane in a first reactor at conditions effective for the formation of maleic anhydride, scrubbing the reaction gas mixture from the first reactor to recover the maleic anhydride values from the remaining reaction gas mixture components,
5 separating the scrubber liquid containing said maleic anhydride values, adding n-butane to said remaining reaction gas mixture components and reacting the resulting gas mixture in a second reactor at conditions effective for the formation of maleic anhydride.
10
- 15 2. The process of claim 1 wherein the reaction gas mixture from the first reactor is scrubbed with water.
3. The process of claim 1 or claim 2 wherein the feed to
20 the second reactor comprises 0.5-3 vol % n-butane.
4. The process of any one of claims 1 to 3 wherein air enriched with oxygen is the molecular oxygen containing gas in the first reactor.
25
5. The process of any one of claims 1 to 4 wherein both n-butane and molecular oxygen are added to said remaining reaction gas mixture components.
30
- 35 6. The process of any one of claims 1 to 5 wherein the gas mixture from the second reactor, after separation of maleic anhydride, is further reacted in a subsequent reactor after addition of n-butane and optionally molecular oxygen.

7. A process for the production of maleic anhydride, substantially as hereinbefore described with reference to the accompanying example and/or drawing.

5

Dated this 9th day of September 2004

SCIENTIFIC DESIGN COMPANY, INC.

By their Patent Attorneys

GRIFFITH HACK

10 Fellows Institute of Patent and
Trade Mark Attorneys of Australia

33

55

- 19 -

