



(19) **United States**

(12) **Patent Application Publication**
Li

(10) **Pub. No.: US 2004/0257653 A1**

(43) **Pub. Date: Dec. 23, 2004**

(54) **POLARIZATION RECOVERY SYSTEM FOR PROJECTION DISPLAYS**

(52) **U.S. Cl. 359/483; 359/485**

(75) **Inventor: Kenneth K. Li, Arcadia, CA (US)**

(57) **ABSTRACT**

Correspondence Address:
ROTHWELL, FIGG, ERNST & MANBECK,
P.C.
1425 K STREET, N.W.
SUITE 800
WASHINGTON, DC 20005 (US)

A waveguide polarization recovery system both polarizes the input light energy for use with an LCD imager and converts the polarity of unusable light energy to add to the illumination of the LCD imager. The compact polarization recovery waveguide system generally includes: (1) an input waveguide that provides non-polarized light energy into the system; (2) an output waveguide that receives polarized light energy from the system; (3) a polarized beam splitter that received the light energy from the input waveguide and transmits lights energy of a first polarization type and reflects light energy of a second polarization type, and (4) a wave plate that modifies the polarization of either the transmitted or reflected light energy. The polarization recovery system also generally includes one or more mirrors that are positioned as need to direct the transmitted and the reflected light energy to the output waveguide. The input and output waveguides may be shaped as needed by the projection system. For example, either one or both of the input and output waveguides may be tapered as needed to produce a desired image. In the waveguide polarization recovery system, the input and output waveguides are configured to have either an either a substantially parallel or a substantially perpendicular orientation. In another embodiment, the waveguide polarization recovery system further includes has one or more "gaps" of optically clear material positioned between the optical components to encourage the occurrence of total internal reflection that minimizes the loss of the optical energy by the system.

(73) **Assignee: Cogent Light Technologies, Inc., Santa Clarita, CA (US)**

(21) **Appl. No.: 10/850,469**

(22) **Filed: May 21, 2004**


Related U.S. Application Data

(63) Continuation of application No. 10/347,522, filed on Jan. 21, 2003, which is a continuation of application No. 09/814,970, filed on Mar. 23, 2001, now Pat. No. 6,587,269.

(60) Provisional application No. 60/227,312, filed on Aug. 24, 2000. Provisional application No. 60/246,583, filed on Nov. 8, 2000.

Publication Classification

(51) **Int. Cl.⁷ G02B 27/28**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

POLARIZATION RECOVERY SYSTEM FOR PROJECTION DISPLAYS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of application Ser. No. 09/814,970, filed Mar. 23, 2001, which claims benefit of U.S. Provisional Application No. 60/227,312, filed Aug. 24, 2000 and 60/246,583, filed Nov. 8, 2000.

FIELD OF INVENTION

[0002] The present invention relates an improved system and methodology for substantially increasing the light output of a polarized optical projection system through the recovery of optical energy of an unused polarization.

BACKGROUND OF INVENTION

[0003] A liquid crystal display (hereafter "LCD") is a known device used to control the transmission of polarized light energy. The LCD may be either clear or opaque, depending on the current applied to the LCD. Because of this functionality, projection systems commonly use an array containing numerous LCDs to form an image source. In particular, the projection system inputs high intensity, polarized light energy to the LCD array (also called an imager), which selectively transmits some of the inputted light energy to form a projection of a desired image. Because a single LCD is relatively small, numerous LCDs can be packed together into the array, thereby forming an imager that can produce a high resolution image.

[0004] As suggested above, a projection system must first polarize the light input to the LCD. However, light energy from a light source, such as a bulb, may have either p-polarization or s-polarization. Since this light input to the LCD imager must be in one orientation (i.e., either p-polarization or s-polarization), the LCD projector generally uses only half of the light energy from the light source. However, it is desirable in projection systems to maximize the brightness and intensity of the light output. In response, various methodologies have been developed to capture the light energy of unusable polarization, to convert the polarization of this captured light energy, and then to redirect the converted light energy toward the LCD imager. These known polarization recovery methodologies involve creating an expanded beam of light in which the unused portion of the light (of undesired polarity) is sent through a half-wave plate to change the polarization and then recombined with the original polarized beam. Unfortunately, the implementation of these known methodologies requires complex, bulky systems, which usually include 2-dimensional lense arrays and an array of polarization beam splitters. Furthermore, the known methodologies lose much of the light energy and, therefore, compromise the projector's goal of producing a high intensity output. As a result, there exists a current need for a simple, low cost, and compact polarization recovery system that operates with high efficiency.

SUMMARY OF THE INVENTION

[0005] In response to these needs, the present invention uses a waveguide system to perform the polarization recovery function in an LCD projection system. In particular, the present invention's waveguide polarization recovery system

both polarizes the input light energy for use with an LCD imager and converts the polarity of unusable light energy to add to the illumination of the LCD imager. The compact polarization recovery waveguide system generally includes the following optical components that are integrated into a single unit: (1) an input waveguide that inputs non-polarized light energy into the system; (2) an output waveguide that removes polarized light energy from the system; (3) a polarized beam splitter that receives the light energy from the input waveguide and transmits light energy of a first polarization type and reflects light energy of a second polarization type, and (4) a wave plate that modifies the polarization of either the transmitted or reflected light energy. The polarization recovery system also generally includes one or more mirrors that are positioned as needed to direct the transmitted and/or reflected light energy to the output waveguide. The input and output waveguides may be shaped as needed by the projection system. For example, either one or both of the input and output waveguides may be tapered as needed to produce a desired image.

[0006] In the waveguide polarization recovery system, the input and output waveguides are configured to have either a substantially parallel or a substantially perpendicular orientation. In configurations in which the input and output waveguides are substantially parallel, the output waveguide directly receives light energy transmitted by the beam splitter. In this way, light energy enters and exits the polarization recovery system in substantially the same direction. Alternatively, the input and the output waveguides may be positioned substantially perpendicular to each other such that the light energy exits the polarization recovery system at a right angle from the direction it enters. In configurations having input and output waveguides of perpendicular orientation, a mirror receives the light energy transmitted by the polarized beam splitter and redirects this energy by 90° toward the output waveguide.

[0007] The polarization recovery waveguide system of the present invention combines the above-enumerated list of optical components into a single, compact unit. In one embodiment, the waveguide polarization recovery system further includes one or more "gaps" of optically clear material positioned between the optical components to encourage the occurrence of total internal reflection that minimizes the loss of the optical energy by the system.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] These and other advantages of the present invention will be described in detail with reference to the following drawings in which like reference numbers refer to like elements:

[0009] FIGS. 1-4 and 6-10 are schematic diagrams that illustrate various embodiments of the waveguide polarization recovery system of the present invention; and

[0010] FIG. 5 is a schematic diagram that illustrates a compact projection device that uses one embodiment of the polarization recovery system of the present invention.

DETAILED DESCRIPTIONS OF THE PREFERRED EMBODIMENTS

[0011] As illustrated in FIGS. 1-4 and 6-10, the present invention is a compact waveguide polarization recovery

system **10** having an input waveguide **20**, a polarizing beam splitter (“PBS”) **30**, a wave plate **40**, which can be a half-wave plate, or a quarter-wave plate depending on the configuration, and an output waveguide **50**. The waveguide polarization recovery system **10** generally further includes mirrors **60** as needed to direct the light stream between the input and output waveguides, **20** and **50**. The following discussion first summarizes several possible configurations for the waveguide polarization recovery system **10** and then describes the individual elements in greater detail.

[0012] FIGS. 1, 3, and 6 illustrate one configuration of the waveguide polarization recovery system **10** in which the output light energy is substantially parallel with the input light energy. In this embodiment, the input waveguide **20** introduces unpolarized input light at incidence to the PBS **30**. The illustrated PBS **30** transmits p-polarized light, and so the p-polarized portion of the input light energy continues through in the same direction as the initial input while the s-polarized light is reflected in a perpendicular direction to the initial direction of input. The half-wave plate **40** is positioned to receive the reflected s-polarized light and convert it to p-polarized. Subsequently, mirror **60** redirects the converted energy from the half-wave plate **40** back to the initial direction of input. Both the transmitted light energy from the PBS **30** and the converted light energy from the half-wave plate **40** are recombined in the output waveguide and mixed. As a result, the output light energy has a uniform intensity profile and is polarized. It should be appreciated that an output of the opposite polarization may be produced through the use of a PBS **30** that only transmits s-polarized light.

[0013] FIGS. 2, 4, and 7-8 illustrate another embodiment of the waveguide polarization recovery system **10** that has an alternative configuration in which the output light energy is perpendicular to the original input light energy. As in the embodiment of FIG. 1, the input waveguide **20** introduces unpolarized input light at incidence to the PBS **30**. Furthermore, the PBS **30** performs the same function of transmitting the p-polarized light, and so the p-polarized portion of the input light energy continues through in the same direction as the initial input while the s-polarized light is reflected in a perpendicular direction to the initial direction of input. However, in the configuration of FIG. 2, one mirror **60** redirects the transmitted p-polarized portion of the input light energy by 90° toward the output waveguide **50**. Furthermore, the reflected s-polarized light from the PBS **30** propagates once through a quarter-wave plate **40'**, and a second mirror **60** then returns the reflected light energy to the quarter-wave plate **40'** for another pass. The second pass is also in the direction of the output waveguide **50**. Because the reflected s-polarized light passes twice through the quarter-wave plate **40'**, s-polarized light is shifted by a half-wave to become p-polarized twice with the mirror as shown. Again, both p-polarized outputs will be mixed in the output waveguide, producing a uniform intensity output. The embodiment of FIG. 2 requires only two optical sections: A first section formed through the combination of the input waveguide **20**, the PBS **30**, the quarter-wave plate **40'** and a mirror **60**; and a second section formed through the combination of the output waveguide **50** and a second mirror **60**. Therefore, the system has a simple design and a relatively low cost. Positioning the output light energy perpendicular to the original input light energy also has the

advantage of allowing a more compact projection system, as described in greater detail below.

[0014] In contrast to the above-described configuration in which the wave plate **40** modifies the light energy reflected by the PBS **30**, other configurations for the waveguide polarization recovery system **10** position the wave plate to modify the light energy transmitted by the PBS **30**. For example, FIGS. 9 and 10 illustrate configurations in which the half-wave plate **40** is positioned to receive light energy transmitted by the PBS **30**. In the configuration of FIG. 9, the half-wave plate **40** is optically positioned between a mirror **60** and the output waveguide **50**. The half-wave plate **40** receives transmitted light energy that has first been redirected by a mirror **60**. Similarly, in FIG. 10, the half-wave plate **40** is placed between the PBS **30** and mirror **60**. In this way, the transmitted light energy from the PBS **30** is first repolarized before being redirected toward the output waveguide **50**. The configurations of FIGS. 9-10 are advantageous because the input light energy only passes through the polarization layer of the PBS **30** once, thus reducing the loss of optical energy in the system **10**. In contrast, the above-described configuration of the FIGS. 2, 4, and 7-8 requires some of the input light energy to pass through the PBS **30** twice.

[0015] Elements of the Waveguide Polarization Recovery System

[0016] The various configurations of the waveguide polarization recovery system **10** use the same elements, which are now described in greater detail.

[0017] The input waveguide **20** is typically an integrator that collects the light from a light source, such as an arc lamp, and mixes the light through multiple reflections to produce a more uniform intensity profile into the waveguide polarization recovery system **10**. Likewise, the output waveguide **50** is typically an integrator that collects the light from the waveguide polarization recovery system **10** and mixes the light through multiple reflections to produce a more uniform intensity profile for illumination of the imager. The input waveguide **20** and the output waveguide **50** may be, for example, single core optic fibers, fused bundles of optic fibers, fiber bundles, solid or hollow square or rectangular light pipes, or homogenizers, which can be tapered or un-tapered. In optical projection systems, the input waveguide **20** and the output waveguide **50** are typically rectangular in cross-section to correspond with the shape of the imager and the final projected image. The input waveguide **20** and the output waveguide **50** wave can be made from glass, quartz, or plastic depending on the power-handling requirement.

[0018] Either one or both of the input waveguide **20** and the output waveguide **50** can have an increasing or decreasing taper as needed for the projection system. For example, FIG. 3-4 and 6-10 illustrate embodiments of the waveguide polarization recovery system **10** in which the input waveguide **20** is a tapered rod with the input cross-section matched to the area of the light source and the output cross-section related to the dimensions of a LCD imager. The final dimensions for the input waveguide **20** may vary as needed to minimize stray light loss in the optical projection system. Similarly, FIG. 8 illustrates an embodiment of the waveguide polarization recovery system **10** in which the output waveguide **50** is also tapered. Tapering of the output

waveguide **50'** is advantageous because, depending on the performance parameters of the PBS **30**, the wave plate **40**, and the output requirements for the projection system, polarization recovery may not always be done at the same numerical aperture as the output aperture. The performances of the PBS **30** and the wave plate **40** are better at smaller numerical apertures, and as a result, advantageous increases in performance are achieved by transforming the input light energy into a larger area with a small numerical aperture and then transforming the light energy back into larger numerical apertures at the output of the output waveguide **50'**. Overall, the tapering of the input wave guide **20** and the output waveguide **50** can be selected to match the overall performance requirements of the projection system, and similarly, the input and output waveguides can be tapered in either direction.

[0019] The waveguide polarization recovery system **10** further includes PBS **30**. The PBS **30** is a well-known optical element that transmits light energy of one polarization while reflecting light energy of a different polarization. Typically, the PBS **30** is a rectangular prism of optically clear material, such as plastic or glass, that has a polarizing coating applied to the diagonal surface. Alternatively, the PBS **30** may be composed of a material that selectively transmit light energy depending on the polarization of the light energy. However, it should be appreciated that there exist numerous alternative designs and types of PBS, and any of these alternative PBS's may be employed in the waveguide polarization recovery system **10** of the present invention. Because the PBS **30** is a well known and commercially available item, it is not discussed further.

[0020] Another element of the waveguide polarization recovery system **10** is the wave plate **40**. The wave plate **40** is an optically transparent component that modifies the polarization of light energy that passes through the wave plate **40**. The wave plate **40** typically changes the propagating of light in one axis, thus changes the polarization. The wave plate **40** may be either a half-wave or quarter-wave as needed by the specific configuration of the waveguide polarization recovery system **10**. Overall, the wave plate **40** is a well known and commonly available item and will not be discussed further.

[0021] The waveguide polarization recovery system **10** may further include one or more mirrors **60** as needed to direct the light energy through the waveguide polarization recovery system **10**. While mirrors are commonly known to be metal-coated glass surfaces or polished metal, the mirrors **60** should not be limited to this common definition for the purpose of this invention. Instead, mirrors **60** should be considered any optical component capable of reflecting or redirecting light energy. For example, mirrors **60** may be prisms that use the angle of incidence to capture and redirect light energy. For example, FIGS. **9** and **10** illustrate a waveguide polarization recovery system **10** that has a prism to redirect light energy transmitted by the PBS **30** toward the output waveguide **50**. For systems with small numerical apertures, total internal reflection at the prism can be used, and as a result, the coating is not necessary.

[0022] In another preferred embodiment of the present invention, illustrated in FIGS. **6-10**, the waveguide polarization recovery system **10** further includes one or more optically clear areas, or "gaps," **70** between the other optical

elements. The gaps **70** may be pockets of air left between the optical components. The gap **70** can also be filled with low index epoxy or other transparent material such that the total internal reflection still occurs, but the assembly of the components will be simplified. For example, FIG. **6** illustrates a configuration having gap **70** between the input waveguide **20** and the PBS **30**. This gap **70** ensures that light energy reflected by the diagonal PBS **30** is turned by 90° toward the quarter-wave plate **40'** because total internal reflection from the interface between the PBS **30** and the gap **70** prevents the light energy from returning instead to the input waveguide **20** and exiting as a loss. The waveguide polarization recovery system **10** in FIG. **6** also has other gaps **70** to promote total internal reflection between the different optical elements. Similarly, FIG. **7** illustrates a waveguide polarization recovery system **10** in which gaps **70** have been added to a polarization recovery system with a tapered input waveguide **20** and perpendicularly configured output waveguide **50** illustrated in FIG. **4**. Again these gaps **70** increase the efficiency by encouraging total internal reflection between the optical components. As illustrated in FIGS. **6-7**, the gaps **70**, while increasing the efficiency of the system, cause the waveguide polarization recovery system **10** to become more complex with an increased number of discrete parts.

[0023] In the above-described configurations of FIG. **9-10**, the gaps **70** further serve the purpose of improving the performance of the prism **60'** that serves as a mirror to direct the light energy toward the output waveguide **50**. In particular, the gap **70** is needed between the PBS **30** and the prism **60'** such that the light reflected from the hypotenuse of the prism **60'**, back toward the PBS **30**, hits this interface of the gap **70** and is internally reflected toward the output waveguide **50**. In this way, efficiency of the system is improved by minimizing loss.

[0024] The performance advantages of the gaps **70** may be further increased through the use of anti-reflection coating on both surfaces such that the transmitted light suffers minimal loss.

[0025] FIG. **5** illustrates a projector **100** that employs the waveguide polarization recovery system **10**. The projector **100** consists of a light collecting system **110**, which in this illustrated example has two paraboloid reflectors and a retro-reflector that increase the output by reflecting the light from a light source **120** back into itself. The arc of the light source **120** is placed at a focus of the first paraboloid reflector and the proximal end of the input waveguide **20** is at the focus of the second paraboloid reflector. It should be appreciated that this light collection system **110** is provided merely for illustration, and many other light collection systems are known and may be used. Likewise, the light source **120** may be an arc lamp, such as xenon, metal-halide lamp, HID, or mercury lamps, or a filament lamp, such as a halogen lamp, provided that the system is modified to accommodate the non-opaque filaments of the lamp.

[0026] Within the illustrated projector **100**, the input waveguide **20** is a tapered light pipe that is designed to match the light input collected from the light collecting system **110** to the optical needs of an LCD imager **150**. As described above in FIG. **4**, the light output of the input waveguide **20** is polarized by the PBS **30** and the other polarization is recovered by the quarter-wave plate **40'**. The

output waveguide **50** then directs the polarized optical energy toward the LCD imager **150**. In this case, the light output in the output waveguide **50** is then incident into a second PBS **130** whose orientation is matched to the polarization of the incident light to minimize the loss. A color wheel **140**, or other type of color selection system, and the reflective LCD imager **150** create the projected image by the projection lenses **160** in a traditional manner. As shown in **FIG. 5**, the number of optical elements is minimal and, as the result, the cost for the projector is relatively low.

[0027] It should be appreciated that the waveguide polarization recovery system **10** may be used in other types of projection systems. For example, the projector may also use two or three imagers **150** to define the projected image. The imager **150** may also be a reflective display using liquid crystal on silicon (“LCOS”) technology, or any other type of systems that requires polarized light. Similarly, the color wheel **140** can also be replaced by electrically switchable color system without moving parts or other known color projection systems.

[0028] While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth, and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the following claims.

1-54. (Cancelled)

55. A light guide comprising at least first and second light guide sections and at least one light coupling element between the light guide sections, the light guide sections each having an entrance aperture, an exit aperture and a guide wall defining a light guiding direction, the light coupling element being composed of an optically transparent material having an entrance face with a TIR surface, and an exit face with a TIR surface, the entrance face adjacent to the exit aperture of the first light guide section and extending in the light guiding direction of the second light guide section, and exit face adjacent to the entrance aperture of light guide section and extending in the light guiding direction of the first light guide section.

56. The light guide of claim 55 in which the light coupling element is wedge-shaped and has an internally reflecting face extending between the entrance face and the exit face.

57. The light guide of claim 56 in which the cross sections of the light guide sections have the cross sectional shape of an even-numbered polygon.

58. The light guide of claim 55 in which at least the first light guide section is a solid element of an optically transparent material, and the entrance face of light coupling element adjacent to the exit aperture of the solid light guide section is spaced a distance apart from the exit aperture of light guide section, to form a space between the entrance face of light coupling element and the exit aperture of the solid light guide section.

59. The light guide of claim 58 in which the second light guide section is a solid element of an optically transparent material, and the exit face of light coupling element adjacent to the entrance aperture of the solid light guide section is spaced a distance apart from the entrance aperture of light guide section, to form a space between the exit face of light coupling element and the entrance aperture of the solid light guide section.

60. The light guide of claim 58 in which the space is filled with air.

61. The light guide of claim 58 in which the space is filled with an optically transparent material having an index of refraction less than that of the material of the light coupling element.

62. The light guide of claim 58 in which the distance *d* between the entrance face of light coupling element and the exit aperture of the solid light guide section is substantially the same across the width of the space.

63. The light guide of claim 55 in which at least the first light guide section is a hollow conduit having a guide wall with an interior reflective surface.

64. The light guide of claim 63 in which the second light guide section is a hollow conduit having a guide wall with an interior reflective surface.

65. The light guide of claim 55 in which the entrance and exit faces of light coupling element form a right angle.

66. The light guide of claim 64 in which the guide walls form an obtuse angle.

67. The light guide of claim 56 in which the reflective surface is a polarizing surface, reflecting a first polarization direction and transmitting a second one.

* * * * *