



(12) **United States Patent**
Germain et al.

(10) **Patent No.:** **US 10,806,510 B2**
(45) **Date of Patent:** **Oct. 20, 2020**

(54) **MEDICAL SYSTEMS AND METHODS**

(71) Applicant: **MINERVA SURGICAL, INC.**, Santa Clara, CA (US)

(72) Inventors: **Aaron Germain**, Campbell, CA (US); **Michael D. Walker**, San Francisco, CA (US); **Benedek Orczy-Timko**, Budapest (HU)

(73) Assignee: **MINERVA SURGICAL, INC.**, Santa Clara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 816 days.

(21) Appl. No.: **15/292,711**

(22) Filed: **Oct. 13, 2016**

(65) **Prior Publication Data**

US 2017/0027637 A1 Feb. 2, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/053,434, filed on Oct. 14, 2013, now Pat. No. 9,498,244.
(Continued)

(51) **Int. Cl.**
A61B 18/14 (2006.01)
A61B 17/32 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 18/1485** (2013.01); **A61B 10/0275** (2013.01); **A61B 17/32002** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **A61B 18/1485**; **A61B 10/0275**; **A61B 17/32002**; **A61B 17/3205**; **A61B 18/18**
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,650,462 A 3/1987 DeSatnick et al.
4,678,459 A 7/1987 Onik et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0153190 A1 8/1985
EP 2100567 A1 9/2009
(Continued)

OTHER PUBLICATIONS

“AAGL Practice Report: Practice Guidelines for the Management of Hysteroscopic Distending Media: Replaces Hysteroscopic Fluid Monitoring Guidelines. J Am Assoc Gynecol Laparosc. 2000;7:167-168,” Journal of Minimally Invasive Gynecology, vol. 20(2):137-148, Mar./Apr. 2013.

(Continued)


Primary Examiner — Phillip A Gray

(74) *Attorney, Agent, or Firm* — Seager, Tufte & Wickhem, LLP

(57) **ABSTRACT**

Tissue is resected and extracted from an interior location in a patient's body using a probe or tool which both effects resection and causes vaporization of a liquid or other fluid to propel the resected tissue through an extraction lumen of the resecting device. Resection is achieved using an electrosurgical electrode assembly including a first electrode on a resecting member and a second electrode within a resection probe or tool. Over a first resecting portion, radio frequency current helps resect the tissue and over a second or over transition region, the RF current initiates vaporization of the fluid or other liquid to propel the tissue from the resection device. In one embodiment, an extending element extends from a housing and into a channel in a resecting member as the resecting member moves toward a distal position.

20 Claims, 20 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO 2011060189 A1 5/2011
WO WO02010096139 A3 12/2011

OTHER PUBLICATIONS

Liu et al., "Clinical application of hysteroscopic electroresection in 775 cases," J First Mil Med Univ, vol. 24(4):467-469, Apr. 2004.
Phillips et al., "The Effect of Dilute Vasopressin Solution on Blood Loss During Operative Hysteroscopy," J Am Assoc Gynecol Laparosc, 3(4, Supplement):S38, Aug. 1996.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A










FIG. 9B








FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14




FIG. 15




FIG. 16A




FIG. 16B




FIG. 17




FIG. 18




FIG. 19

MEDICAL SYSTEMS AND METHODS**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 14/053,434, filed Oct. 14, 2013, which application claims the benefit of U.S. Provisional Application No. 61/716,049, filed Oct. 19, 2012, the full disclosures of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to tissue resection devices and methods, for example, for use in resecting and extracting uterine fibroid tissue, polyps and other abnormal uterine tissue.

BACKGROUND OF THE INVENTION

Uterine fibroids are non-cancerous tumors that develop in the wall of uterus. Such fibroids occur in a large percentage of the female population with some studies indicating up to 40 percent of all women have fibroids. Uterine fibroids can grow over time to be several centimeters in diameter and symptoms can include menorrhagia, reproductive dysfunction, pelvic pressure and pain.

One current treatment of fibroids is hysteroscopic resection or myomectomy which involves transcervical access to the uterus with a hysteroscope together with insertion of a resecting instrument through a working channel in the hysteroscope. The resecting instrument may be a mechanical tissue cutter or an electro-surgical resection device such as an RF loop. Mechanical cutting devices are disclosed in U.S. Pat. Nos. 7,226,459; 6,032,673 and 5,730,752 and U.S. Published Patent Appl. 2009/0270898. An electro-surgical resecting device is disclosed in U.S. Pat. No. 5,906,615.

In a myomectomy or hysteroscopic resection, the initial step of the procedure includes distention of the uterine cavity to create a working space for assisting viewing through the hysteroscope. In a relaxed state, the uterine cavity collapses with the uterine walls in contact with one another. A fluid management system is used to distend the uterus to provide a working space by means of a fluid being introduced through a passageway in the hysteroscope under sufficient pressure to expand or distend the uterine cavity. The fluids used to distend the uterus are typically liquid aqueous solutions such as a saline solution or a sugar-based aqueous solution.

While hysteroscopic resection can be effective in removing uterine fibroids, many commercially available instruments are too large in diameter and thus require anesthesia in an operating room environment. Conventional resectoscopes require cervical dilation to about 9 mm. What is needed is a system that can effectively resect and remove fibroid tissue through a small diameter hysteroscope.

SUMMARY OF THE INVENTION

The present invention provides methods for resecting and removing target tissue from a patient's body, such as fibroids from a uterus. The tissue is resected, captured in a probe, catheter, or other tissue-removal device, and expelled from the resecting device by vaporizing a liquid adjacent to the captured tissue in order to propel the tissue from the device, typically through an extraction or other lumen present in a body or shaft of the device. Exemplary embodiments of the

tissue resecting device comprise an RF electrode, wherein the electrode can be advanced past a tissue-receiving window on the device in order to sever a tissue strip and capture the strip within an interior volume or receptacle on the device. The liquid or other expandable fluid is also present in the device, and energy is applied to the fluid in order to cause rapid expansion, e.g., vaporization, in order to propel the resected tissue strip through the extraction lumen. In this way, the dimensions of the extraction lumen can be reduced, particularly in the distal regions of the device where size is of critical importance.

In another aspect of the invention, a tubular resecting device has an inner resecting sleeve that reciprocates in a passageway in an outer sleeve or housing to resect tissue in a window of the outer sleeve. Within a distal portion of the stroke of the inner resecting sleeve, a projecting element extends into a tissue extraction channel in the inner sleeve. In a variation, the cross-section of the projecting element functions in a scissor-like manner to push the tissue against an electrode edge of the inner sleeve to resect the tissue. The projecting element can have an axial length of at least 2 mm. The projecting element also can have a tapered region for insuring that the inner sleeve when moving distally is guided over the projecting element even if there is flex in the distal portion of the outer sleeve in the region of the tissue-receiving window.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a plan view of an assembly including a hysteroscope and a tissue resecting device corresponding to the invention that is inserted through the working channel of the hysteroscope.

FIG. 2 is a schematic perspective view of a fluid management system used for distending the uterus and for assisting in electro-surgical tissue resection and extraction.

FIG. 3 is a cross-sectional view of the shaft of the hysteroscope of FIG. 1 showing various channels therein.

FIG. 4 is a schematic side view of the working end of the electro-surgical tissue resecting device of FIG. 1 showing an outer sleeve, a reciprocating inner sleeve and an electrode arrangement.

FIG. 5 is a schematic perspective view of the working end of the inner sleeve of FIG. 4 showing its electrode edge.

FIG. 6A is a schematic cut-away view of a portion of outer sleeve, inner RF resecting sleeve and a tissue-receiving window of the outer sleeve.

FIG. 6B is a schematic view of a distal end portion another embodiment of inner RF resecting sleeve.

FIG. 7A is a cross sectional view of the inner RF resecting sleeve of FIG. 6B taken along line 7A-7A of FIG. 6B.

FIG. 7B is another cross sectional view of the inner RF resecting sleeve of FIG. 6B taken along line 7B-7B of FIG. 6B.

FIG. 8 is a schematic view of a distal end portion of another embodiment of inner RF resecting sleeve.

FIG. 9A is a cross sectional view of the RF resecting sleeve of FIG. 8 taken along line 9A-9A of FIG. 8.

FIG. 9B is a cross sectional view of the RF resecting sleeve of FIG. 8 taken along line 9B-9B of FIG. 8.

FIG. 10A is a perspective view of the working end of the tissue resecting device of FIG. 1 with the reciprocating RF resecting sleeve in a non-extended position.

FIG. 10B is a perspective view of the tissue resecting device of FIG. 1 with the reciprocating RF resecting sleeve in a partially extended position.

FIG. 10C is a perspective view of the tissue resecting device of FIG. 1 with the reciprocating RF resecting sleeve in a fully extended position across the tissue-receiving window.

FIG. 11A is a sectional view of the working end of the tissue resecting device of FIG. 10A with the reciprocating RF resecting sleeve in a non-extended position.

FIG. 11B is a sectional view of the working end of FIG. 10B with the reciprocating RF resecting sleeve in a partially extended position.

FIG. 11C is a sectional view of the working end of FIG. 10C with the reciprocating RF resecting sleeve in a fully extended position.

FIG. 12A is an enlarged sectional view of the working end of tissue resecting device of FIG. 11B with the reciprocating RF resecting sleeve in a partially extended position showing the RF field in a first RF mode and plasma resection of tissue.

FIG. 12B is an enlarged sectional view of the working end of FIG. 11C with the reciprocating RF resecting sleeve almost fully extended and showing the RF fields switching to a second RF mode from a first RF mode shown in FIG. 12A.

FIG. 12C is an enlarged sectional view of the working end of FIG. 11C with the reciprocating RF resecting sleeve again almost fully extended and showing the explosive vaporization of a captured liquid volume to expel resected tissue in the proximal direction.

FIG. 13 is an enlarged perspective view of a portion of the working end of FIG. 12C showing an interior chamber and a fluted projecting element.

FIG. 14 is a sectional view of the working end of FIG. 12C showing an interior chamber and a variation of a projecting element.

FIG. 15 is a sectional view of the working end of FIG. 12C showing an interior chamber and a variation of a projecting element configured to explosively vaporize the captured liquid volume.

FIG. 16A is sectional view of a working end of a resection probe similar to that of FIGS. 11A-12C showing a variation of a projecting element and resecting sleeve.

FIG. 16B is another view of the working end of FIG. 16A with the resecting sleeve moving distally over a tapered portion of the projecting element.

FIG. 17 is a schematic view of a system for fibroid removal including a fluid management system.

FIG. 18 is a schematic view of the fluid management system of FIG. 17 with an enlarged view of the working end of a tissue resecting probe as generally described in FIGS. 1-12C in a position to resect and remove a fibroid.

FIG. 19 is a cut-away schematic view of a filter module of the fluid management system of FIGS. 17-18.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates an assembly that comprises an endoscope 50 used for hysteroscopy together with a tissue resecting and extracting device 100 extending through a working channel 102 of the endoscope. The endoscope or hysteroscope 50 has a handle 104 coupled to an elongated shaft 105 having a diameter of 3 mm to 7 mm. The working channel 102 therein may be round, D-shaped or any other suitable shape. The endoscope shaft 105 is further configured with an optics channel 106 and one or more fluid inflow/outflow channels 108a, 108b (FIG. 3) that communicate with connectors 110a, 110b configured for coupling to

a fluid inflow source 120, or optionally a negative pressure source 125 (FIGS. 1-2). The fluid inflow source 120 is a component of a fluid management system 126 as is known in the art (FIG. 2) which comprises a fluid container 128 and pump mechanism 130 which pumps fluid through the hysteroscope 50 into the uterine cavity. As can be seen in FIG. 2, the fluid management system 126 further includes the negative pressure source 125 coupled to the tissue resecting device 100. The handle 104 of the endoscope includes the angled extension portion 132 with optics to which a video-scopic camera 135 can be operatively coupled. A light source 136 is coupled to light coupling 138 on the handle of the hysteroscope 50. The working channel 102 of the hysteroscope is configured for insertion and manipulation of the tissue resecting and extracting device 100, for example to treat and remove fibroid tissue. In one embodiment, the hysteroscope shaft 105 has an axial length of 21 cm, and can comprise a 0° scope, or 15° to 30° scope.

Still referring to FIG. 1, the tissue resecting device 100 has a highly elongated shaft assembly 140 configured to extend through the working channel 102 in the hysteroscope. A handle 142 of the tissue resecting device 100 is adapted for manipulating the electrosurgical working end 145 of the device. In use, the handle 142 can be manipulated both rotationally and axially, for example, to orient the working end 145 to resect targeted fibroid tissue. The tissue resecting device 100 has subsystems coupled to its handle 142 to enable electrosurgical resection of targeted tissue. A radiofrequency generator or RF source 150 and controller 155 are coupled to at least one RF electrode carried by the working end 145 as will be described in detail below. In one embodiment shown in FIG. 1, an electrical cable 156 and negative pressure source 125 are operatively coupled to a connector 158 in handle 142. The electrical cable couples the RF source 150 to the electrosurgical working end 145. The negative pressure source 125 communicates with a tissue-extraction channel 160 in the shaft assembly 140 of the tissue resecting device 100 (FIG. 4).

FIG. 1 further illustrates a seal housing 162 that carries a flexible seal 164 within the hysteroscope handle 104 for sealing the shaft 140 of the tissue resecting device 100 in the working channel 102 to prevent distending fluid from escaping from a uterine cavity.

In one embodiment as shown in FIG. 1, the handle 142 of tissue resecting device 100 includes a motor drive 165 for reciprocating or otherwise moving a resecting component of the electrosurgical working end 145 as will be described below. The handle 142 optionally includes one or more actuator buttons 166 for actuating the device. In another embodiment, a footswitch can be used to operate the device. In one embodiment, the system includes a switch or control mechanism to provide a plurality of reciprocation speeds, for example 1 Hz, 2 Hz, 3 Hz, 4 Hz and up to 8 Hz. Further, the system can include a mechanism for moving and locking the reciprocating resecting sleeve in a non-extended position and in an extended position. Further, the system can include a mechanism for actuating a single reciprocating stroke.

Referring to FIGS. 1 and 4, an electrosurgical tissue resecting device has an elongate shaft assembly 140 extending about longitudinal axis 168 comprising an exterior or first outer sleeve 170 with passageway or lumen 172 therein that accommodates a second or inner sleeve 175 that can reciprocate (and optionally rotate or oscillate) in lumen 172 to resect tissue as is known in that art. In one embodiment, the tissue-receiving window 176 in the outer sleeve 170 has an axial length ranging between 10 mm and 30 mm and extends in a radial angle about outer sleeve 170 from about

5

45° to 210° relative to axis **168** of the sleeve. The outer and inner sleeves **170** and **175** can comprise a thin-wall stainless steel material and function as opposing polarity electrodes as will be described in detail below. FIGS. **6A-8** illustrate insulative layers carried by the outer and inner sleeves **170** and **175** to limit, control and/or prevent unwanted electrical current flows between certain portions of the sleeve. In one embodiment, a stainless steel outer sleeve **170** has an O.D. of 0.143" with an I.D. of 0.133" and with an inner insulative layer (described below) the sleeve has a nominal I.D. of 0.125". In this embodiment, the stainless steel inner sleeve **175** has an O.D. of 0.120" with an I.D. of 0.112". The inner sleeve **175** with an outer insulative layer has a nominal O.D. of about 0.123" to 0.124" to reciprocate in lumen **172**. In other embodiments, outer and/or inner sleeves can be fabricated of metal, plastic, ceramic of a combination thereof. The cross-section of the sleeves can be round, oval or any other suitable shape.

As can be seen in FIG. **4**, the distal end **177** of inner sleeve **175** comprises a first polarity electrode with distal electrode edge **180** about which plasma can be generated. The electrode edge **180** also can be described as an active electrode during tissue resection since the electrode edge **180** then has a substantially smaller surface area than the opposing polarity or return electrode. In one embodiment in FIG. **4**, the exposed surfaces of outer sleeve **170** comprises the second polarity electrode **185**, which thus can be described as the return electrode since during use such an electrode surface has a substantially larger surface area compared to the functionally exposed surface area of the active electrode edge **180**.

In one aspect of the invention, the inner sleeve or resecting sleeve **175** has an interior tissue extraction lumen **160** with first and second interior diameters that are adapted to electro-surgically resect tissue volumes rapidly—and thereafter consistently extract the resected tissue strips through the highly elongated lumen **160** without clogging. Now referring to FIGS. **5** and **6A**, it can be seen that the inner sleeve **175** has a first diameter portion **190A** (with diameter **A**) that extends from the handle **142** (FIG. **1**) to a distal region **192** of the sleeve **175** wherein the tissue extraction lumen transitions to a smaller second diameter lumen **190B** with a reduced diameter indicated at **B** which is defined by the electrode sleeve element **195** that provides the resection electrode edge **180**. The axial length **C** of the reduced cross-section lumen **190B** can range from about 2 mm to 20 mm. In one embodiment, the first diameter **A** is 0.112" and the second reduced diameter **B** is 0.100". As shown in FIG. **5**, the inner sleeve **175** can be an electrically conductive stainless steel and the reduced diameter electrode portion also can comprise a stainless steel electrode sleeve element **195** that is welded in place by weld **196** (FIG. **6A**). In another alternative embodiment, the electrode and reduced diameter electrode sleeve element **195** comprises a tungsten tube that can be press fit into the distal end **198** of inner sleeve **175**. FIGS. **5** and **6A** further illustrate the interfacing insulation layers **202** and **204** carried by the first and second sleeves **170**, **175**, respectively. In FIG. **6A**, the outer sleeve **170** is lined with a thin-wall insulative material **200**, such as PFA, or another material described below. Similarly, the inner sleeve **175** has an exterior insulative layer **202**. These coating materials can be lubricious as well as electrically insulative to reduce friction during reciprocation of the inner sleeve **175**.

The insulative layers **200** and **202** described above can comprise a lubricious, hydrophobic or hydrophilic polymeric material. For example, the material can comprise a

6

bio-compatible material such as PFA, TEFLON®, polytetrafluoroethylene (PTFE), FEP (Fluorinated ethylenepropylene), polyethylene, polyamide, ECTFE (Ethylenechlorotrifluoro-ethylene), ETFE, PVDF, polyvinyl chloride or silicone.

Now turning to FIG. **6B**, another variation of inner sleeve **175** is illustrated in a schematic view together with a tissue volume being resected with the plasma electrode edge **180**. In this embodiment, as in other embodiments in this disclosure, the RF source operates at selected operational parameters to create plasma around the edge **180** of electrode sleeve **195** as is known in the art. Thus, the plasma generated at electrode edge **180** can ablate a path **P** in the tissue **220** and is suited for resecting fibroid tissue and other abnormal uterine tissue. In FIG. **6B**, the distal portion of the resecting sleeve **175** includes a ceramic collar **222** which is proximate to the distal edge **180** of the electrode sleeve **195**. The ceramic collar **222** functions to confine plasma formation about the distal electrode edge **180** and functions further to prevent plasma from contacting and damaging the polymer insulative layer **202** on the resecting sleeve **175** during operation. In one aspect of the invention, the path **P** ablated in the tissue **220** with the plasma at electrode edge **180** provides a path **P** having an ablated width indicated at **W**, wherein such path width **W** is substantially wide due to tissue vaporization. This vaporization of tissue in path **P** to provide the resection is substantially different than the effect of resecting similar tissue with a sharp blade edge, as in various prior art devices. A sharp blade edge can divide tissue (without cauterization) but applies mechanical force to the tissue and may prevent a large cross section slug of tissue from being resected. In contrast, the plasma at the electrode edge **180** can vaporize a path **P** in tissue without applying any substantial force on the tissue to thus resect larger cross sections or strips of tissue. Further, the plasma resecting effect reduces the cross section of tissue strip **225** received in the reduced cross-section region **190B** of the tissue extraction lumen **160**. FIG. **6B** depicts a tissue strip **225** entering the reduced cross-section region **190B**, wherein the tissue strip has a smaller cross-section than the lumen due to the vaporization of tissue. Further, the cross section of tissue strip **225** as it enters the larger cross-section lumen **190A** results in even greater free space **197** around the tissue strip **225**. Thus, the resection of tissue with the plasma electrode edge **180**, together with the lumen transition from the smaller cross-section (**190B**) to the larger cross-section (**190A**) of the tissue-extraction lumen **160** can significantly reduce or eliminate the potential for successive resected tissue strips **225** clogging the lumen. Prior art resection devices with such a small diameter tissue-extraction lumen typically have problems with tissue clogging.

In another aspect of the invention, the negative pressure source **125** coupled to the proximal end of tissue-extraction lumen **160** (see FIGS. **1** and **4**) also assists in aspirating and moving tissue strips **225** in the proximal direction to a collection reservoir (not shown) outside the handle **142** of the resecting device.

FIGS. **7A-7B** illustrate the change in lumen diameter of resecting sleeve **175** of FIG. **6B**. FIG. **8** illustrates the distal end of a variation of resecting sleeve **175'** which is configured with an electrode resecting element **195'** that is partially tubular in contrast to the previously described tubular electrode element **195** (FIGS. **5** and **6A**). FIGS. **9A-9B** again illustrate the change in cross-section of the tissue-extraction lumen between reduced cross-section region **190B'** and the increased cross-section region **190A'** of the resecting sleeve **175'** of FIG. **8**. Thus, the functionality remains the same

whether the resecting electrode element 195' is tubular or partly tubular. In FIG. 8A, the ceramic collar 222' is shown, in one variation, as extending only partially around sleeve 175' to cooperate with the radial angle of resecting electrode element 195'. Further, the variation of FIG. 8 illustrates that the ceramic collar 222' has a larger outside diameter than insulative layer 202. Thus, friction may be reduced since the short axial length of the ceramic collar 222' interfaces and slides against the interfacing insulative layer 200 about the inner surface of lumen 172 of outer sleeve 170.

In general, one aspect of the invention comprises a tissue resecting and extracting device (FIGS. 10A-11C) that includes first and second concentric sleeves having an axis and wherein the second (inner) sleeve 175 has an axially-extending tissue-extraction lumen therein, and wherein the second sleeve 175 is moveable between axially non-extended and extended positions relative to a tissue-receiving window 176 in first sleeve 170 to resect tissue, and wherein the tissue extraction lumen 160 has first and second cross-sections. The second sleeve 175 has a distal end configured as a plasma electrode edge 180 to resect tissue disposed in tissue-receiving window 176 of the first sleeve 170. Further, the distal end of the second sleeve, and more particularly, the electrode edge 180 is configured for plasma ablation of a substantially wide path in the tissue. In general, the tissue resecting device is configured with a tissue extraction lumen 160 having a distal end portion with a reduced cross-section that is smaller than a cross-section of medial and proximal portions of the lumen 160.

In one aspect of the invention, referring to FIGS. 7A-7B and 9A-9B, the tissue-extraction lumen 160 has a reduced cross-sectional area in lumen region 190B proximate the plasma resecting tip or electrode edge 180 wherein said reduced cross section is less than 95%, 90%, 85% or 80% than the cross sectional area of medial and proximal portions 190A of the tissue-extraction lumen, and wherein the axial length of the tissue-extraction lumen is at least 10 cm, 20 cm, 30 cm or 40 cm. In one embodiment of tissue resecting device 100 for hysteroscopic fibroid resection and extraction (FIG. 1), the shaft assembly 140 of the tissue resecting device is 35 cm in length.

FIGS. 10A-10C illustrate the working end 145 of the tissue resecting device 100 with the reciprocating resecting sleeve or inner sleeve 175 in three different axial positions relative to the tissue receiving window 176 in outer sleeve 170. In FIG. 10A, the resecting sleeve 175 is shown in a retracted or non-extended position in which the sleeve 175 is at its proximal limit of motion and is prepared to advance distally to an extended position to thereby electrosurgically resect tissue positioned in and/or suctioned into window 176. FIG. 10B shows the resecting sleeve 175 moved and advanced distally to a partially advanced or medial position relative to tissue resection window 176. FIG. 10C illustrates the resecting sleeve 175 fully advanced and extended to the distal limit of its motion wherein the plasma resecting electrode 180 has extended past the distal end 226 of tissue-receiving window 176 at which moment the tissue strip 225 is resected from tissue volume 220 and captured in reduced cross-sectional lumen region 190B.

Now referring to FIGS. 10A-10C and FIGS. 11A-11C, another aspect of the invention comprises tissue displacement mechanisms provided by multiple elements and processes to displace and move tissue strips 225 in the proximal direction in lumen 160 of resecting sleeve 175 to thus ensure that tissue does not clog the lumen of the inner sleeve 175. As can be seen in FIG. 10A and the enlarged views of FIGS. 11A-11C, one tissue displacement mechanism comprises a

projecting element 230 that extends proximally from distal tip 232 which is fixedly attached to outer sleeve 170. The projecting element 230 extends proximally along central axis 168 in a distal chamber 240 defined by outer sleeve 170 and distal tip 232. In one embodiment depicted in FIG. 11A, the shaft-like projecting element 230, in a first functional aspect, comprises a mechanical pusher that functions to push a captured tissue strip 225 proximally from the small cross-section lumen 190B of resecting sleeve 175 as the sleeve 175 moves to its fully advanced or extended position. In a second functional aspect, the chamber 240 in the distal end of sleeve 170 is configured to capture a volume of saline distending fluid 244 from the working space, and wherein the existing RF electrodes of the working end 145 are further configured to explosively vaporize the captured fluid 244 to generate proximally-directed forces on tissue strips 225 resected and disposed in lumen 160 of the resecting sleeve 175. Both of these two functional elements and processes (tissue displacement mechanisms) can apply substantial mechanical force to captured tissue strips 225. For example, the explosive vaporization of liquid in chamber 240 can function to move tissue strips 225 in the proximal direction in the tissue-extraction lumen 160. It has been found that using the combination of multiple functional elements and processes can virtually eliminate the potential for tissue clogging the tissue extraction lumen 160.

More in particular, FIGS. 12A-12C illustrate sequentially the functional aspects of the tissue displacement mechanisms and the explosive vaporization of fluid captured in chamber 240. In FIG. 12A, the reciprocating resecting sleeve 175 is shown in a medial position advancing distally wherein plasma at the electrode edge 180 is resecting a tissue strip 225 that is disposed within lumen 160 of the resecting sleeve 175. In FIG. 12A-12C, it can be seen that the system operates in first and second electrosurgical modes corresponding to the reciprocation and axial range of motion of resecting sleeve 175 relative to the tissue-receiving window 176. As used herein, the term "electrosurgical mode" refers to which electrode of the two opposing polarity electrodes functions as an "active electrode" and which electrode functions as a "return electrode". The terms "active electrode" and "return electrode" are used in accordance with convention in the art—wherein an active electrode has a smaller surface area than the return electrode which thus focuses RF energy density about such an active electrode. In the working end 145 of FIGS. 10A-11C, the resecting electrode element 195 and its electrode edge 180 must comprise the active electrode to focus energy about the electrode to generate the plasma for tissue resection. Such a high-intensity, energetic plasma at the electrode edge 180 is needed throughout stroke X indicated in FIGS. 12A-12B to resect tissue. The first mode occurs over an axial length of travel of inner sleeve 175 as it crosses the tissue receiving window 176, at which time the entire exterior surface of outer sleeve 170 comprises the return electrode indicated at 185. The electrical fields EF of the first RF mode are indicated schematically generally in FIG. 12A.

FIG. 12B illustrates the moment in time at which the distal advancement or extension of inner resecting sleeve 175 entirely crosses the tissue-receiving window 176. At this time, the electrode sleeve 195 and its electrode edge 180 are confined within the mostly insulated-wall chamber 240 defined by the outer sleeve 170 and distal tip 232. At this moment, the system is configured to switch to the second RF mode in which the electric fields EF switch from those described previously in the first RF mode. As can be seen in FIG. 12B, in this second mode, the limited interior surface

area **250** of distal tip **232** that interfaces chamber **240** functions as an active electrode and the distal end portion of resecting sleeve **175** exposed to chamber **240** acts as a return electrode. In this mode, very high energy densities occur about surface **250** and such a contained electric field EF can explosively and instantly vaporize the fluid **244** captured in chamber **240**. The expansion of water vapor can be dramatic and can thus apply tremendous mechanical forces and fluid pressure on the tissue strip **225** to move the tissue strip in the proximal direction in the tissue extraction lumen **160**. FIG. **12C** illustrates such explosive or expansive vaporization of the distention fluid **244** captured in chamber **240** and further shows the tissue strip **225** being expelled in the proximal direction in the lumen **160** of inner resecting sleeve **175**. In another variation, FIG. **14** further shows the relative surface areas of the active and return electrodes at the extended range of motion of the resecting sleeve **175**, again illustrating that the surface area of the non-insulated distal end surface **250** is small compared to surface **255** of electrode sleeve which comprises the return electrode.

Still referring to FIGS. **12A-12C**, it has been found that a single power setting on the RF source **150** and controller **155** can be configured both (i) to create plasma at the electrode edge **180** of electrode sleeve **195** to resect tissue in the first mode, and (ii) to explosively vaporize the captured distention fluid **244** in the second mode. Further, it has been found that the system can function with RF mode-switching automatically at suitable reciprocation rates ranging from 0.5 cycles per second to 8 or 10 cycles per second. It has been found that the tissue resecting device described above can resect and extract tissue at the rate of from 4 grams/min to 20 grams/min without any potential for tissue strips **225** clogging the tissue-extraction lumen **160**, depending on the diameter of the device. In one embodiment, a negative pressure source **125** can be coupled to the tissue-extraction lumen **160** to apply additional tissue-extracting forces to tissue strips **225** in the system.

Of particular interest, the fluid-capture chamber **240** defined by sleeve **170** and distal tip **232** can be designed to have a selected volume, exposed electrode surface area, length and geometry to optimize the expelling forces applied to resected tissue strips **225**. In one embodiment, the diameter of the chamber is 3.175 mm and the length is 5.0 mm which taking into account the projecting element **230**, provides a captured fluid volume of approximately 0.040 mL. In other variations, the captured fluid volume can range from 0.004 to 0.080 mL.

In one example, a chamber **240** with a captured liquid volume of 0.040 mL together with 100% conversion efficiency in an instantaneous vaporization would require 103 Joules to heat the liquid from room temperature to water vapor. In operation, since a Joule is a W*s, and the system reciprocates at 3 Hz, the power required would be on the order of 311 W for full, instantaneous conversion of the captured liquid to water vapor. A corresponding theoretical expansion of 1700x would occur in the phase transition, which would result in up to 25,000 psi instantaneously (14.7 psi*1700), although due to losses in efficiency and non-instantaneous expansion, the actual pressures would be less. In any event, the pressures are substantial and can apply expelling forces sufficient to expel the captured tissue strips **225** along the length of the extraction channel **160** in the probe.

Referring to FIG. **12A**, the interior chamber **240** can have an axial length from about 0.5 mm to 10 mm to capture a liquid volume ranging from about 0.004 mL 0.01 mL. It can be understood in FIG. **12A**, that the interior wall of chamber

240 has an insulator layer **200** which thus limits the electrode surface area **250** exposed to chamber **240**. In one embodiment, the distal tip **232** is stainless steel and is welded to outer sleeve **170**. The post element **248** is welded to tip **232** or machined as a feature thereof. The projecting element **230** in this embodiment is a non-conductive ceramic.

FIG. **13** shows the cross-section of the ceramic projecting element **230** which is fluted, which in one embodiment has three flute elements **260** in three corresponding axial grooves **262** in its surface. Any number of flutes, channels or the like is possible, for example from 2 to about 20. The purpose of this design is to provide a significant cross-sectional area at the proximal end of the projecting element **230** to push the tissue strip **225**, while at the same time the three grooves **262** permit the proximally-directed jetting of water vapor to impact the tissue exposed to the grooves **262**. In one embodiment, the axial length D of the projecting element **230** is configured to push tissue entirely out of the reduced cross-sectional region **190B** of the electrode sleeve element **195**. In another embodiment, the volume of the chamber **240** is configured to capture liquid that when explosively vaporized provides a gas (water vapor) volume sufficient to expand into and occupy at least the volume defined by a 10% of the total length of extraction channel **160** in the device, at least 20% of the extraction channel **160**, at least 40% of the extraction channel **160**, at least 60% of the extraction channel **160**, at least 80% of the extraction channel **160** or at least 100% of the extraction channel **160**.

As can be understood from FIGS. **12A** to **12C**, the distention fluid **244** in the working space replenishes the captured fluid in chamber **240** as the resecting sleeve **175** moves in the proximal direction or towards its non-extended position. Thus, when the resecting sleeve **175** again moves in the distal direction to resect tissue, the interior chamber **240** is filled with fluid **244** which is then again contained and is then available for explosive vaporization as described above when the resecting sleeve **175** closes the tissue-receiving window **176**. In another embodiment, a one-way valve can be provided in the distal tip **232** to draw fluid directly into interior chamber **240** without the need for fluid to migrate through window **176**.

FIG. **15** illustrates another variation in which the active electrode surface area **250'** in the second mode comprises a projecting element **230** with conductive regions and non-conductive regions **261** which can have the effect of distributing the focused RF energy delivery over a plurality of discrete regions each in contact with the captured fluid **244**. This configuration can more efficiently vaporize the captured fluid volume in chamber **240**. In one embodiment, the conductive regions **250'** can comprise metal discs or washers on post **248**. In other variation (not shown) the conductive regions **250'** can comprise holes, ports or pores in a ceramic material **261** fixed over an electrically conductive post **248**.

In another embodiment, the RF source **150** and controller **155** can be programmed to modulate energy delivery parameters during stroke X and stroke Y in FIGS. **12A-12C** to provide the optimal energy (i) for plasma resection with electrode edge **180**, and (ii) for explosively vaporizing the captured fluid in chamber **240**.

FIGS. **16A-16B** are sectional views of a working end **600** of a tissue resecting probe that is similar to previous embodiments. In FIGS. **16A** and **16B**, the inner resecting member or sleeve **610** is shown in a distal portion of its stroke after resecting a tissue strip **225** captured in the window **612** in the outer sleeve **615** or housing as generally depicted in the tissue resecting sequence of FIGS. **12A-12B**.

FIGS. 16A-16B illustrate another aspect of the invention wherein the inner resecting sleeve 610 moves in a passage-way 620 in the outer sleeve 615 and in the distal portion of its stroke, a projecting or extending element 630 extends into the tissue extraction channel 632 in the inner sleeve 610. In one variation, the cross-section of the extending element 630 is configured to extend into the distal reduced cross-section portion 635 of the tissue extraction channel 632 and function in a scissor-like manner to push the tissue against the electrode edge 640 of the inner sleeve 610 as depicted in FIG. 16A. The extending element 630 can have an axial length of at least 2 mm. In a variation, the extending element 630 has a length ranging from 4 mm to 10 mm. The extending element 630 can have a length that equals at least 50% of the axial length of the distal reduced cross-section region 635 of the extraction channel 632.

In one variation, a method of resecting tissue comprises positioning a working end of a tissue resecting probe against tissue and moving a resecting sleeve or member 610 carried by the probe wherein the moveable resecting member 610 interfaces with an extending element 630 carried by the probe that extends into a channel 632 in the resecting sleeve to thereby resect tissue that is captured between the resecting member 610 and the extending element 630. In such a variation, the step of resecting tissue is accomplished by plasma formed at the distal electrode edge 640 of the resecting member 610, with electrical fields EF (FIG. 16A) as described above.

In one variation, still referring to FIGS. 16A-16B, the extending element 630 has a tapered region 644 that tapers in the proximal direction. In use, the tapered region helps insure that the distally moving inner sleeve 610 is guided over the projecting element 630 even if there is some flex in the distal portion of the outer sleeve 615 in the region of window 612. It can be understood that distal movement of the inner sleeve 610 will engage the tapered region 644 of element 630 if the outer sleeve is flexed in any direction and thereafter further distal movement of the inner sleeve 610 over the projecting element 630 will center the outer sleeve 615 relative to the inner sleeve 610.

In general, a method of resecting and extracting tissue comprises positioning a window of a tubular resecting device against tissue, and reciprocating a resecting sleeve in forward and backward strokes across the window wherein a projecting member separate from the resecting sleeve projects into a bore in the resecting sleeve during a portion of its forward stroke to prevent flexing of the sleeve proximate the window.

In one embodiment shown in FIGS. 16A-16B, the extending element 630 has a recessed region 648 therein for receiving a fluid volume. As can be seen in FIG. 16B, the extending element 630 is a dielectric material (e.g., a ceramic) with a central bore 660 for mounting the element 630 over the post element 652 of metal endcap 655. The proximal surface 658 of post element 652 functions as an electrode when vaporizing captured fluid as described previously and shown in FIG. 16B. The electrical fields EFⁿ are shown in FIG. 16B which result in the explosive vaporization of the contained liquid. It can be seen in FIG. 16B that metal endcap 655 is fixed with annular weld 656 to outer sleeve 615 (electrode) so that endcap 655 and its post element 652 also function as an electrode. FIG. 16B further illustrates that the working end has insulative layers on all surfaces of the distal annular space 660 that receives the inner resecting sleeve 610 to focus RF current paths in the central bore 650 of the projecting element 630. More in

particular, the outer sleeve 615 is lined with an insulative layer 662 and the endcap 655 has an annular inner insulator 664 bonded thereto.

FIGS. 17-19 illustrate a fluid management system 500 that can be used when treating tissue in a body cavity, space or potential space 502 (FIG. 18). The fluid management system 500 is depicted schematically in a hysteroscopic fibroid treatment system 510 that is adapted for resection and extraction of fibroids or other abnormal intra-uterine tissue using a hysteroscope 512 and tissue resection probe 515 that can be similar to those described above. FIG. 17 depicts the probe 515 with handle 516 and extension member 518 with working end 520 (FIG. 18) that can be introduced through working channel 522 extending through the body 523 and shaft 524 of the hysteroscope 512. FIG. 17 further shows a motor 525 in handle 516 of the probe that is coupled to a controller 545 and power supply by power cable 526. FIG. 18 illustrates the working end 520 of the resecting probe in a uterine cavity proximate a targeted fibroid 530.

Referring to FIGS. 17-18, in general, the fluid management system 500 comprises a fluid source or reservoir 535 of a distention fluid 244, a controller and pump system to provide fluid inflows and outflows adapted to maintain distension of a body space and a filter system 540 for filtering distention fluid 244 that is removed from the body cavity and thereafter returned to the fluid source 535. The use of a recovered and filtered fluid 244 and the replenishment of the fluid source 535 is advantageous because (i) the closed-loop fluid management system can effectively measure fluid deficit to thereby monitor intravasation and insure patient safety, (ii) the system can be set up and operated in a very time-efficient manner, and (iii) the system can be compact and less expensive to thereby assist in enabling office-based procedures.

The fluid management system 500 (FIG. 17) includes a computer control system that is integrated with the RF control system in an integrated controller 545. The controller 545 is adapted to control first and second peristaltic pumps 546A and 546B for providing inflows and outflows of a distention fluid 244, such as saline solution, from source 535 for the purpose of distending the body cavity and controlling the intra-cavity pressure during a tissue resecting and extracting procedure as depicted in FIG. 18. In one embodiment shown in FIGS. 17-19, the controller 545 controls peristaltic pump 546A to provide positive pressure at the outflow side 548 of the pump (FIG. 17) to provide inflows of distention fluid 244 through first flow line 550 which is in communication with fitting 561 and fluid flow channel 108a in hysteroscope 515. The flow channel 108a is described above in a previous embodiment and is illustrated in FIG. 3 above. The controller 545 further controls the second peristaltic pump 546B to provide negative pressure at the inflow side 552 of the pump (FIG. 18) to the second line 555 to assist in providing outflows of distention fluid 244 from the body cavity 502. As described above, the explosive vaporization of fluid in the working end 525 of probe 515 functions to expel tissue strips 225 proximally in the extraction channel 160 of resecting sleeve 175, which can operate in conjunction with negative pressures in line 555 provided by pump 546B. In operation, the second peristaltic pump 546B also operates to provide positive pressure on the outflow side 556 of pump 546B in the second flow line portion 555' to pump outflows of distention fluid 244 through the filter system 540 and back to the fluid source 535.

In one system embodiment, the controller 545 operates to control pressure in cavity 502 by pressure signals from a

disposable pressure sensor **560** that is coupled to a fitting **562** in hysteroscope **512** which communicates with a flow channel **108b** (see FIG. 17) that extends through the hysteroscope. The pressure sensor **560** is operatively coupled to controller **545** by cable **564**. In one embodiment, the flow channel **108b** has a diameter of at least 1.0 mm to allow highly accurate sensing of actual intra-cavity pressure. In prior art commercially-available fluid management systems, the intra-cavity pressure is typically estimated by various calculations using known flow rates through a pump or remote pressure sensors in the fluid inflow line that can measure back pressures. Such prior art fluid management systems are stand-alone systems and are adapted for use with a wide variety of hysteroscopes and endoscopes, most of which do not have a dedicated flow channel for communicating with a pressure sensor. For this reason, prior art fluid management systems rely on algorithms and calculations to estimate intra-cavity pressure.

The fluid channel or sensor channel **108b** used by the pressure sensor **560** is independent of flow channel **108a** used for distention fluid inflows into the body cavity. In the absence of fluid flows in the sensor channel **108b**, the fluid in the channel **108b** then forms a static column of incompressible fluid that changes in pressure as the pressure in the body cavity changes. With a sensor channel cross-section of 1 mm or more, the pressure within the pressure channel column and the pressure in the body cavity are equivalent. Thus, the pressure sensor **560** is capable of a direct measurement of pressure within the body cavity.

FIG. 18 schematically illustrates the fluid management system **500** in operation. The uterine cavity **502** is a potential space and needs to be distended to allow for hysteroscopic viewing. A selected pressure can be set in the controller **545**, for example via a touch screen **565**, which the physician knows from experience is suited for distending the cavity **502** and/or for performing a procedure. In one embodiment, the selected pressure can be any pressure between 0 and 150 mm Hg. In one system embodiment, the first pump **546A** can operate as a variable speed pump that is actuated to provide a flow rate of up to 850 ml/min through first line **550**. In this embodiment, the second pump **546B** can operate at a fixed speed to move fluid in the second line **555**. In use, the controller **545** can operate the pumps **546A** and **546B** at selected matching or non-matching speeds to increase, decrease or maintain the volume of distention fluid **244** in the uterine cavity **502**. Thus, by independent control of the pumping rates of the first and second peristaltic pumps **546A** and **546B**, a selected set pressure in the body cavity can be achieved and maintained in response to signals of actual intra-cavity pressure provided by sensor **560**.

In one system embodiment, as shown in FIGS. 18-19, the fluid management system **500** includes a filter module or system **540** that can include a first filter or tissue-capturing filter **570** that is adapted to catch tissue strips **225** that have been resected and extracted from the body cavity **502**. A second filter or molecular filter **575**, typically a hollow fiber filter, is provided beyond the first filter **570**, wherein the molecular filter **575** is adapted to remove blood and other body materials from the distention fluid **244**. In particular, the molecular filter **575** is capable of removing red blood cells, hemoglobin, particulate matter, proteins, bacteria, viruses and the like from the distention fluid **244** so that endoscopic viewing of the body cavity is not obscured or clouded by any such blood components or other contaminants. As can be understood from FIGS. 16-18, the second peristaltic pump **546B** at its outflow side **556** provides a positive pressure relative to fluid flows into the filter module

540 to move the distention fluid **244** and body media through the first and second filters, **570** and **575**, and in a circulatory flow back to the fluid source **535**.

Referring to FIG. 19, in an embodiment, the first filter **570** comprises a container portion or vial **576** with a removable cap **577**. The inflow of distention fluid **244** and body media flows through line portion **555** and through fitting **578** into a mesh sac or perforate structure **580** disposed in the interior chamber **582** of the vial **576**. The pore size of the perforate structure **580** can range from about 200 microns to 10 microns. The lumen diameter of hollow fibers **585** in the second filter **575** can be from about 400 microns to 20 microns. In general, the pore size of perforate structure **580** in the first filter **570** is less than the diameter of the lumens of hollow fibers **585** in the second filter **575**. In one embodiment, the pore size of the perforate structure **580** is 100 microns, and the lumen size of the hollow fibers **585** in the molecular filter **575** is 200 microns. In one embodiment, the molecular filter **575** is a Nephros DSU filter available from Nephros, Inc., 41 Grand Ave., River Edge, N.J. 07661. In one variation, the filter **575** is configured with hollow fibers having a nominal molecular weight limit (NMWL) of less than 50 kDa, 30 kDa or 20 kDa.

Referring to FIG. 19, it can be seen that the filter module **540** includes detachable connections between the various fluid flow lines to allow for rapid coupling and de-coupling of the filters and flow lines. More in particular, flow line **555** extending from the tissue resecting probe **515** has a connector portion **592** that connects to inlet fitting **578** in the first filter **570**. Flow line portion **555'** that is intermediate the filters **570** and **575** has connector portion **596a** that connects to outlet fitting **596b** in first filter **570**. The outflow end of flow line **555'** has connector **598a** that connects to inlet fitting **598b** of the second filter **575**. The portion **590** of the second flow line **555** that is intermediate the second filter **575** and fluid source **535** has connector portion **602a** that connects to outlet fitting **602b** in the second filter **575**. In one embodiment, at least one check valve **605** is provided in the flow path intermediate the filters **570**, **575** which for example can be in line **555'**, connectors **596a**, **598a** or fittings **596b**, **598b**. In FIG. 19, a check valve **605** is integrated with the inlet end **608** of the second filter **575**. In use, the operation of the system will result in substantial fluid pressures in the interior of the second filter, and the check valve **605** allows for de-coupling the first filter without escape of pressure and release of fluid media into the environment, for example, when the tissue resection procedure is completed and the physician or nurse wishes to transport the vial **576** and tissue strips **225** therein to a different site for biopsy purposes.

In one aspect, a fluid management system comprising a first fluid line **550** configured to carry distention fluid **224** or influent from a fluid source **535** to a body space, a second fluid line **555**, **555'** and **560** configured to carry fluid from the body space to a first filter **570** and then to a second filter **575** and then back to the fluid source **535**, a pump operatively coupled to the second fluid line to move the fluid and at least one check valve **605** in the second fluid line intermediate the first and second filters **570** and **575**.

In one embodiment, the controller **545** of the fluid management system **500** is configured for calculation of a fluid deficit that is measured as a difference between a fluid volume delivered to the body space **502** and a fluid volume recovered from the body space during a medical procedure such as fibroid removal (see FIGS. 17-18). A method of fluid management in a hysteroscopic procedure comprises providing a distention fluid source **535** (FIG. 18) having a

predetermined volume, introducing fluid (e.g., saline) from the source 535 through a first flow path or line 550 into the uterine cavity and through a second flow line 555 out of the cavity into a filter module 540 and through a further portion 590 of the second flow line back to the fluid source 535 wherein the interior volume of the first and second flow lines and the filter module when subtracted from the predetermined volume of the source 535 equals 2.5 liters or less to thereby insure that saline intravasation is less than 2.5 liters. In this variation, the predetermined volume of the source 535 can be 3.0 liters, as in a standard 3 liter saline bag, and the interior system volume can be at least 0.5 liters. In one variation, the fluid management system 500 can include a sensor system for determining the volume of fluid remaining in the source 535, and the sensor can provide a signal to the controller 545 which in turn can provide a visual or aural signal relating to remaining fluid volume in fluid source 535. In one variation, the fluid source 535 can be a bag that hangs from a member including a load cell 625 (FIGS. 17, 19) which is configured to send load signals to the controller 545. The controller can have a screen 565 which continuously displays a fluid parameter such as calculated fluid deficit or fluid remaining in the source 535. In other variations, the sensor adapted for sensing the weight or volume of fluid in the fluid source can be a float or level sensor in a fluid container, an impedance or capacitance sensor coupled to the fluid source container, an optical sensor operatively coupled to the fluid container or any other suitable type of weight or volume sensing mechanism. Any such sensor system can send signals to the controller for providing fluid deficit calculations or fluid intravasation warnings.

While certain embodiments of the present invention have been described above in detail, it will be understood that this description is merely for purposes of illustration and the above description of the invention is not exhaustive. Specific features of the invention are shown in some drawings and not in others, and this is for convenience only and any feature may be combined with another in accordance with the invention. A number of variations and alternatives will be apparent to one having ordinary skills in the art. Such alternatives and variations are intended to be included within the scope of the claims. Particular features that are presented in dependent claims can be combined and fall within the scope of the invention. The invention also encompasses embodiments as if dependent claims were alternatively written in a multiple dependent claim format with reference to other independent claims.

What is claimed is:

1. A medical fluid management system, comprising:
 - a first fluid line carrying a distention fluid from a fluid source to a body space;
 - a second fluid line carrying the distention fluid from the body space through a filter system back to the fluid source; and
 - a controller controlling operation of an inflow pump for delivering the distention fluid from the fluid source through the first fluid line to the body space and an outflow pump for moving the distention fluid through the second fluid line back to the fluid source;
 wherein the fluid source hangs from a member, the member including a load cell sending load signals to the controller relating to a fluid deficit of the distention fluid from the fluid source.
2. The medical fluid management system of claim 1, wherein the controller is configured to calculate the fluid deficit as a difference between a fluid volume of the disten-

tion fluid delivered to the body space from the fluid source and a fluid volume of the distention fluid returned to the fluid source during a medical procedure.

3. The medical fluid management system of claim 2, wherein the controller is configured to display the calculated fluid deficit.

4. The medical fluid management system of claim 2, wherein the controller is configured to display an amount of distention fluid remaining in the fluid source during the medical procedure.

5. The medical fluid management system of claim 1, wherein a sum of an interior fluid volume of the first fluid line, the second fluid line, and the filter system is at least 0.5 liters.

6. The medical fluid management system of claim 5, wherein the fluid source has an initial volume of 3 liters of distention fluid.

7. The medical fluid management system of claim 1, wherein the filter system includes a tissue capturing filter and a molecular filter.

8. The medical fluid management system of claim 7, wherein the tissue capturing filter is configured to catch resected tissue.

9. The medical fluid management system of claim 8, wherein the molecular filter is configured to filter out red blood cells.

10. The medical fluid management system of claim 7, further comprising a check valve positioned in the second fluid line between the tissue capturing filter and the molecular filter.

11. The medical fluid management system of claim 10, wherein the check valve is integrated with an inlet of the molecular filter.

12. A medical fluid management system, comprising:
- a fluid source having an initial volume of a distention fluid;
 - a first fluid line carrying the distention fluid from the fluid source to a body space;
 - a second fluid line carrying the distention fluid from the body space through a filter system back to the fluid source;
 - a controller controlling operation of an inflow pump for delivering the distention fluid from the fluid source through the first fluid line to the body space and an outflow pump for moving the distention fluid through the second fluid line back to the fluid source; and
 - an impedance or capacitance sensor coupled to the fluid source.

13. The system of claim 12, wherein the sensor is configured to send a signal to the controller relating to a fluid deficit of the distention fluid from the fluid source.

14. The system of claim 12, wherein the controller is configured to calculate a fluid deficit equal to a difference between a fluid volume of the distention fluid delivered to the body space from the fluid source and a fluid volume of the distention fluid returned to the fluid source during a medical procedure.

15. The system of claim 14, wherein the controller is configured to display the calculated fluid deficit.

16. The system of claim 14, wherein the controller is configured to display an amount of the distention fluid remaining in the fluid source during the medical procedure.

17. The system of claim 12, wherein a sum of an interior fluid volume of the first fluid line, the second fluid line, and the filter system is at least 0.5 liters.

18. The system of claim 17, wherein the fluid source has an initial volume of 3 liters of distention fluid.

17

18

19. The system of claim 12, wherein the filter system includes a tissue capturing filter and a molecular filter.

20. The system of claim 19, further comprising a check valve fluidly coupled between the tissue capturing filter and the molecular filter.

5

* * * * *