



(51) International Patent Classification:

B01D 35/30 (2006.01) *B01D 46/00* (2006.01)
B01D 45/08 (2006.01) *B01D 46/52* (2006.01)

(21) International Application Number:

PCT/US2015/066579

(22) International Filing Date:

18 December 2015 (18.12.2015)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/094,314 19 December 2014 (19.12.2014) US

(71) Applicant: **CUMMINS FILTRATION IP, INC.**
[US/US]; 500 Jackson Street, Columbus, Indiana 47201
(US).

(72) Inventors: **BANNISTER, Robert A.**; 2133 Blue Heron
Court, Stoughton, Wisconsin 53589 (US). **DETRA, Kelly
A.**; 5590 Alpine Rd., Brooklyn, Wisconsin 53521 (US).

ROLTGEN, Joel; 616 Shagbark Ln, DeForest, Wisconsin
53532 (US). **HOLZMANN, Mark V.**; 200 N. Lynn Street,
Stoughton, Wisconsin 53589 (US).

(74) Agents: **BROWN, Marshall J.** et al.; Foley & Lardner
LLP, 3000 K St. NW., Washington, District of Columbia
20007 (US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,

[Continued on next page]

(54) Title: PRE-CLEANING AIR FILTER




FIG. 1B

(57) Abstract: A filter element including a filter media, an end cap, and a baffle. The filter media is configured to be secured within a housing. The housing includes an inlet configured to accept a fluid for filtering and the filter media including a circumferential outer surface. The end cap is positioned at and coupled to one end of the filter media. The baffle is positioned relative to the filter media at a position such that, when the filter element is correctly installed within the housing, the baffle is proximate the inlet of the housing. The baffle extends around only a portion of the circumferential outer surface of the filter media in a radial direction.



GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,

SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

PRE-CLEANING AIR FILTER

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

[0001] This application claims priority to and the benefit of U.S. Provisional Patent Application No. 62/094,314, filed December 19, 2014, the entire disclosure of which is incorporated herein by reference.

FIELD

[0002] The present application relates to filters configured to filter fluid such as air.

BACKGROUND

[0003] Air filters, such as pre-cleaning air filters, may direct the unfiltered air in order to obtain the optimal air filtration. Accordingly, the air filters may include a baffle ring that extends around the entire perimeter of the air filter. Alternatively, the air cleaner housing, which may hold the filter, may include an integrated baffle ring that wraps around the air filter. The baffle ring of current air filters completely covers the lower portion of the filter. In both such arrangements, however, a large portion of the filter is covered by the baffle ring. Therefore, the amount of easily accessed open filter media to the air flow is reduced, which increases the system restriction.

SUMMARY

[0004] Various embodiments provide for a filter element that includes a filter media, an end cap, and a baffle. The filter media is configured to be secured within a housing. The housing includes an inlet configured to accept a fluid for filtering and the filter media including a circumferential outer surface. The end cap is positioned at and coupled to one end of the filter media. The baffle is positioned relative to the filter media at a position such that, when the filter element is correctly installed within the housing, the baffle is proximate the inlet of the housing. The baffle extends around only a portion of the circumferential outer surface of the filter media in a radial direction.

[0005] These and other features (including, but not limited to, retaining features and/or viewing features), together with the organization and manner of operation thereof, will become apparent from the following detailed description when taken in conjunction with the accompanying drawings, wherein like elements have like numerals throughout the several drawings described below.

BRIEF DESCRIPTION OF THE FIGURES

[0006] FIG. 1A is a top view of an air filter according to one embodiment.

[0007] FIG. 1B is a cross-sectional, front view of the air filter of FIG. 1A.

[0008] FIG. 2 is a front, perspective view of a housing that may be disposed within the air filter of FIG. 1A.

[0009] FIGS. 3A-3B are back perspective and front perspective views, respectively, of filter media that may be disposed within the air filter of FIG. 1A.

[0010] FIG. 4A is a top, partially see-through view of an air filter according to another embodiment.

[0011] FIGS. 4B-4C are front perspective views of filter media with and without an end cap, respectively, that may be disposed in the air filter of FIG. 4A.

[0012] FIG. 5A is a cross-sectional, perspective view of an air filter according to yet another embodiment.

[0013] FIGS. 5B-5C are front-perspective and close-up perspective views of a housing that may be disposed in the air filter of FIG. 5A.

[0014] FIG. 6 is a cross-sectional, side view of an air filter according to still another embodiment.

[0015] FIG. 7A is a perspective view of an air filter according to yet another embodiment.

[0016] FIG. 7B is a partial side view of the air filter of FIG. 7A.

[0017] FIG. 7C is a cross-sectional view of the filter of FIG. 7A.

[0018] FIG. 7D is an enlarged, partial cross-sectional view of the filter of FIG. 7A.

[0019] FIG. 8A is a perspective view of an air filter according to another embodiment.

[0020] FIG. 8B is a partial side view of the air filter of FIG. 8A.

[0021] FIG. 8C is a cross-sectional view of the filter of FIG. 8A.

[0022] FIG. 8D is an enlarged, partial cross-sectional view of the filter of FIG. 8A.

[0023] FIG. 9 is an enlarged, partial cross-sectional view of an air filter according to still another embodiment.

[0024] FIG. 10 is an enlarged, partial cross-sectional view of an air filter according to another embodiment.

[0025] FIG. 11A is a perspective view of an air filter according to yet another embodiment.

[0026] FIG. 11B is a perspective, cut-away view of the air filter of FIG. 11A.

[0027] FIG. 11C is a side view of the filter assembly of FIG. 11A.

[0028] FIG. 11D is a top view of the filter assembly of FIG. 11A.

[0029] FIG. 12A is a perspective view of a filter element that can be disposed in the air filter of FIG. 11A.

[0030] FIG. 12B is a partial side view of the filter element of FIG. 12A.

[0031] FIG. 12C is a cross-sectional view of the filter element of FIG. 12A.

[0032] FIG. 12D is an enlarged, partial cross-sectional view of the filter element of FIG. 12A.

[0033] FIG. 13 is an enlarged, partial cross-sectional view of an air filter according to another embodiment.

[0034] FIG. 14 is a graph showing experimental results of the system life as function of the percentage of the inlet covered by a baffle.

[0035] FIG. 15A is a perspective view of a filter element according to another embodiment.

[0036] FIG. 15B is a partial side view of the filter element of FIG. 15A.

[0037] FIG. 15C is a bottom view of the filter element of FIG. 15A.

[0038] FIG. 15D is a cross-sectional view along line A-A of FIG. 15C.

[0039] FIG. 16A is a perspective view of a filter element according to yet another embodiment.

[0040] FIG. 16B is a partial side view of the filter element of FIG. 16A.

[0041] FIG. 16C is a cross-sectional view of the filter element of FIG. 16A.

[0042] FIG. 17A is a perspective view of a filter element according to yet another embodiment.

[0043] FIG. 17B is a partial side view of the filter element of FIG. 17A.

[0044] FIG. 17C is a cross-sectional view of the filter element of FIG. 17A.

[0045] FIG. 18A is a perspective view of a filter element according to still another embodiment.

[0046] FIG. 18B is a partial side view of the filter element of FIG. 18A.

[0047] FIG. 18C is a cross-sectional view of the filter element of FIG. 18A.

[0048] FIG. 19A is a perspective view of a filter element according to yet another embodiment.

[0049] FIG. 19B is a partial side view of the filter element of FIG. 19A.

[0050] FIG. 19C is a cross-sectional view of the filter element of FIG. 19A.

[0051] FIG. 20A is a perspective view of a filter element according to yet another embodiment.

[0052] FIG. 20B is a partial side view of the filter element of FIG. 20A.

[0053] FIG. 20C is a cross-sectional view of the filter element of FIG. 20A.

[0054] FIG. 21A is a perspective view of a filter element according to still another embodiment.

[0055] FIG. 21B is a partial side view of the filter element of FIG. 21A.

[0056] FIG. 21C is a cross-sectional view of the filter element of FIG. 21A.

[0057] FIG. 22A is a perspective view of a filter element according to yet another embodiment.

[0058] FIG. 22B is a partial side view of the filter element of FIG. 22A.

[0059] FIG. 22C is a cross-sectional view of the filter element of FIG. 22A.

DETAILED DESCRIPTION OF VARIOUS EMBODIMENTS

[0060] Referring to the figures generally, the various embodiments disclosed herein relate to an air filter with a localized baffle. More specifically, mechanisms described herein may reduce the restriction of air flow through the filter and may improve the pre-cleaning performance of the housing of the filter which can increase the useful life of the filter assembly.

Air Filter

[0061] Referring now to FIGS. 1A-1B, there is shown an air filter 20 according to one embodiment. The air filter 20 may be, for example, a pre-cleaning air filter and/or a tangential air cleaner. Although an air filter is referred to at various locations herein, it is understood that the air filter 20 may not be limited to air, but may be used with other fluids, such as liquids.

[0062] The air filter system or assembly 20 of FIGS. 1A-1B includes a housing 30 and a filter element 26. The filter element 26 includes a filter media 40, an end cap 42, and a baffle 50. The housing 30 (as shown in FIG. 2) is used to house, protect, receive and/or secure the filter media 40. The filter media 40 (as shown in FIGS. 3A-3B) is used to filter the fluid (e.g., air or liquid) that flows through the air filter 20 and may include pleats. Accordingly, the filter media 40 is positioned and secured within the housing 30, as shown in FIGS. 1A-1B.

Housing

[0063] As shown in FIGS. 1A-1B, the housing 30 includes an inlet 32 and an outlet 34, which may be integrated into the walls of the housing 30 according to one embodiment. The inlet 32 and the outlet 34 are configured to accept a fluid to be filtered and release the filtered fluid. For example, the air may flow into the air filter 20 and within the housing 30 through the inlet 32, into the filter media 40 to be filtered, and out of the housing 30 (and the air filter 20) through the outlet 34.

Filter Assembly

[0064] The filter assembly 26 includes a filter media 40, an end cap 42, and a baffle 50. The filter media 40 may be in a variety of different shapes, according to the desired configuration. For example, the filter media 40 may be cylindrical or may have a D-shaped cross-section (e.g., circular around a first portion of the circumference and flat or straight along a second portion of the circumference as shown, for example, in FIGS. 15A-15D). For example, the filter media disclosed in Patent Application No. PCT/US2015/029443, the entire disclosure of which is incorporated by reference herein in its entirety, can be used within the filter assembly 26.

[0065] The filter media cap, a filter seal ring, a bottom ring, or end cap 42 (as shown, for example, in FIG. 1B and 3A-3B) to help seal the filter media 40 and the housing 30 together. The end cap 42 is positioned at and coupled to one end of the filter media 40.

[0066] The end cap 42 may have a rigid outer section or portion 41 and a soft or pliable inner section or portion 45 (e.g., a soft seal). The rigid portion 41 may provide a secure attachment to the filter media 40. The pliable portion 45 may be used to completely seal portions of the filter media 40 and secure to other components, such as the housing 30.

[0067] Various embodiments depict different configurations of the rigid portion 41 and the pliable portion 45 of the end cap 42 and the attachment of the end cap 42 to the filter media 40. For example, as shown in FIGS. 7C-7D, the rigid portion 41 extends into the inside region of the filter media 40 such that the rigid portion 41 covers a portion of the inner circumference of the filter media 40. The rigid portion 41 also extends around the outside of the filter media 40 and accordingly covers or surrounds a portion of the outer circumference of the filter media 40. The rigid portion 41 also completely covers the end of the filter media 40. The rigid portion 41 includes an extension that extends from the end of the filter media 40. The pliable portion 45 covers an inner circumference of the extension of the rigid portion 41 to provide an area for the filter assembly 20 to seal to other components.

[0068] According to another embodiment as shown in FIG. 8C-8D and 12C-12D, the rigid portion 41 extends around the outside of the filter media 40 and accordingly covers or surrounds a portion of the outer circumference and a first portion of the end of the filter media 40. The rigid portion 41 also includes an extension that extends from the end of the filter media 40. The pliable portion 45 covers an inner circumference of the extension of the rigid portion 41. Neither the rigid portion 41 nor the pliable portion 45 covers the entire end of the filter media 40. Furthermore, neither the rigid portion 41 nor the pliable portion 45 extend into the inside region of the filter media 40 and accordingly do not cover any portion of the inner circumference of the filter media 40. Accordingly, a second portion of the end of the filter media 40 is exposed. In order to form the end cap 42 of FIG. 8D, the rigid portion 41 may be placed into a mold to form the shape of and attach with the pliable portion 45.

[0069] According to yet another embodiment as shown in FIGS. 9 and 13, the rigid portion 41 extends around the outside of the filter media 40 and accordingly covers or surrounds a portion of the outer circumference of the filter media 40 and includes an extension that extends from the end of the filter media 40. The pliable portion 45 extends into the inside region of the filter media 40 and accordingly a portion of the pliable portion 45 is positioned along an inner circumference of the extension of the rigid portion 41 and covers a portion of the inner circumference of the filter media 40. The pliable portion 45 also covers or surrounds the entire

end of the filter media 40. Accordingly, the end of the filter media 40 is not exposed and is completely covered by the pliable portion 45.

[0070] As shown in FIGS. 8D, 9, 12D, and 13, the pliable portion 45 may further include an extension that extends from the end of the filter media 40 alongside the extension of the rigid portion 41. In order to attach the rigid portion 41 and the pliable portion 45 together, the rigid portion 41 may include a protrusion that protrudes upwardly into and is covered or surrounded by the extension of the pliable portion 45.

[0071] According to still another embodiment as shown in FIG. 10, the pliable portion 45 covers or surrounds a portion of the outer circumference and a portion of the end of the filter media 40. The pliable portion 45 includes an extension that extends from the end of the filter media 40. The rigid portion 41 substantially covers or surrounds any exposed portions of the pliable portion 45 that are along the sides (e.g., on the sides of the pliable portion 45 or on the end of the pliable portion 45 that is not connected to the filter media 40). Accordingly, the rigid portion 41 extends along the portion of the outer circumference of the filter media 40, along the inner and outer circumference of the extension of the pliable portion 45, and along the end of the extension of the pliable portion 45. Neither the rigid portion 41 nor the pliable portion 45 cover the entire end of the filter media 40 and do not cover any portion of the inner circumference of the filter media 40. Accordingly, a portion of the filter media 40 is exposed.

[0072] As shown in FIG. 10, an overmolded wiper seal 44 is included and positioned along the entire inner circumference of the rigid portion 41 to help seal the filter media 40 to various components and prevent leakage. The seal 44 extends radially around a center axis of the filter media 40, thereby reducing the inner diameter of the opening leading to the filter media 40. The seal 44 may be constructed out of various materials, including but not limited to overmolded rubber.

[0073] The rigid portion 41 and the pliable portion 45 may be constructed out of a variety of materials, including but not limited to urethane or polyurethane.

[0074] According to one embodiment as shown in FIGS. 3A-3B and 4B-4C, the filter media 40 of the filter element 26 includes a circumferential outer wrap or outer surface 48 that

extends around the perimeter of the filter media 40 such that the filter media 40 is under the outer surface 48. The circumferential outer surface 48 is located by at least the inlet 32 of the housing 30 and is in the line of the incoming air flow. The outer surface 48 may be the outside surface of the actual filter media such that the actual filter media is directly exposed within the housing 30. Alternatively, the outer surface 48 may include a separate covering or wrap that extends around the outside surface of the actual filter media such that the actual filter media is covered within the housing 30.

Baffle

[0075] According to one embodiment and as further shown in the figures, a local baffle section or baffle 50 is positioned relative to the filter media 40 proximate the inlet 32 of the housing 30. In one embodiment, the baffle 50 may be integrated with or otherwise coupled to the filter media 40 itself. Alternatively, the baffle 50 may be integrated with or otherwise coupled to the end cap 42. In any of these particular implementations, however, when the filter element 26 is correctly installed and aligned within the housing 30, the incoming air flow 22 enters through the inlet 32, directly contacts the baffle 50, and is thereby initially directed into a particular direction (e.g., a pre-cleaning direction) with respect to the filter media 40 before entering and being filtered by the filter media 40. The baffle 50 may be positioned proximate the end cap 42.

[0076] The local baffle 50 improves the overall system performance of the air filter 20, while maintaining, or even reducing, the package size of the air filter 20. According to one embodiment, the baffle 50 may improve pre-cleaning functionality and performance of the air filter 20. As shown in FIG. 1B, for example, as the air first enters the air filter 20, the air first hits the baffle 50, which directs the air flow 22 to the inner surface of the outer wall of the air filter 20 (e.g., a sidewall 39 of the housing 30), thus causing the air flow 22 to flow around the filter media 40 and creating a centrifugal force before the air goes through the filter media 40. This centrifugal force helps to pre-clean the air before going through the filter media 40 and allows for larger particulate separation. The baffle 50 may also be used for water separation by preventing water entering into the air filter 20 from going directly into the filter media 40.

[0077] The baffle 50 may extend around a section of the perimeter (rather than the entire perimeter) of the circumferential outer surface 48 of the filter media 40 and may protrude from the end cap 42 along the length of the filter media 40. For example, the baffle 50 extends around only a portion of the circumferential outer surface 48 in the radial direction 28, as shown in FIGS. 3A-3B, such that the baffle 50 does not wrap around the entire circumferential outer surface 48. Accordingly, the baffle 50 extends in the radial direction 28 around the circumferential outer surface 48 less than 360 degrees around the filter media 40, which may be a variety of shapes, for example being cylindrical in shape or having a “race track” or a D-shaped cross-section as shown, for example, in FIGS. 15A-15D. The length of the baffle along the axial direction (e.g., along the x-axis, as shown in FIG. 3B) on the filter media 40 may vary according to the desired configuration. By integrating or positioning the baffle 50 into or onto a local region of the filter media 40, rather than using a baffle ring that wraps around the entire perimeter of the filter media 40, the flow restriction of the air filter 20 is reduced by increasing the amount of filter media 40 available for filtering. More specifically, since the size of the baffle 50 is reduced and the air flow 22 is only blocked by the smaller and local baffle 50, the amount of filter media 40 that is open, uncovered, and available for filtering air is maximized. Accordingly, only the area of the filter media 40 that is in the line of flow at the inlet 32 is blocked by the baffle 50. The baffle 50 may be curved about the perimeter of the filter media 40. For example, the baffle 50 may match the curvature of the filter media 40.

[0078] As shown in FIGS. 1A-1B, the baffle 50 is located in a local region to the inlet 32 on the filter media 40. Accordingly, when the filter element 26 is installed correctly within the housing 30, the baffle 50 is positioned directly across from, located near, and proximate to the inlet 32 of the housing 30. For example, the baffle 50 may be positioned on the same side and end of the filter element 26 as the inlet 32. Furthermore, the baffle 50 may be on an opposite side of the filter element 26 as a Dust Ejection Valve (DEV) port and an air filter outlet of the housing 30 (where the DEV port and the air filter outlet are near or next to each other). Although the baffle 50 is shown in a local region to the inlet 32, it is anticipated that the baffle 50 may be located near and correspond to the air filter outlet according to an alternative embodiment. Further, although the baffle 50 is shown to be attached to the filter media 40, it is

also anticipated that the baffle 50 may be attached to the housing 30 and still located in a local region around the inlet 32, according to another embodiment.

[0079] The baffle 50 may be made out of variety of materials, including but not limited to plastic and metal (e.g., stamped sheet metal).

[0080] According to one embodiment and as shown in FIGS. 3A-3B, the baffle 50 is a part of and integral with the circumferential outer surface 48 (e.g., the out wrap) of the filter media 40.

[0081] According to other embodiments as shown in FIGS. 8A-8D, the baffle 50 is an integral component with the end cap 42 (i.e., the baffle 50 and the end cap 42 are formed as a single component). Providing the baffle 50 and the end cap 42 as an integral component allows for easier keying alignment and assembly due to the baffle 50 that forms a rigid outer section.

[0082] According to other embodiments and as shown in FIGS. 4A-4C and 7A-7D, the baffle 50 is added onto the outer surface 48 of the filter media 40 as a separate or add-on component. Further, the baffle 50 may be a separate component from the end cap 42 and the filter element 26, instead being attachable to the end cap 42 and/or the filter element 26.

[0083] According to another embodiment as shown in FIGS. 21A-21C and 22A-22C, the baffle 50 is an integral component with the end cap 42. Accordingly, the baffle 50 and the end cap 42 (which may include the keying feature 46) are formed (through, for example, pouring or molding) together at the same time. The baffle 50 and the end cap 42 are formed out of the same material, such as urethane or polyurethane, and are formed or potted at the same time together. The baffle 50 that is integral with the end cap 42 may optionally not include a vane (as shown in FIGS. 21A-21C) or may optionally include the integrated vane 62 (as described further herein and as shown in FIGS. 22A-22C). Accordingly, the end cap 42, the baffle 50, and the vane 62 may be made from the same material and formed or molded at the same time.

[0084] To reduce the size of the baffle 50, the baffle 50 may correspond to and may be approximately the shape and size of the inlet 32. The length of the baffle 50 may be adjusted to a variety of different lengths in order to specifically fine tune the system performance of the air filter 20 according to the desired application of the air filter 20.

[0085] As shown in FIGS. 4A-4C and according to an alternative embodiment, the baffle 50 may be a variety of different sizes to change or fine-tune the length and coverage of the baffle 50 according to the desired configuration or specific application. The baffle 50 may include one baffle with a specific size or multiple baffles to create the desired size, as described further herein. The various size baffles may include, but are not limited to, a small size baffle 51, a medium size baffle 52, and/or a large size baffle 53. However, it is anticipated that a variety of other baffle sizes may be provided. Accordingly, the baffle 50 is usable with any size housing 30, inlet 32, and filter media 40 and may cover all of the perimeter of the filter media 40 or only a small portion of the perimeter.

[0086] According to one embodiment, one of the baffle sections 54 (e.g., the small size baffle 51, the medium size baffle 52, or the large size baffle 53) may be attached to the filter element 26. The baffle with the desired baffle size may be initially inserted or attached to the filter element 26 or the existing baffle may be replaced by a baffle with the desired baffle size such that one baffle 50 is attached to the filter element 26. Accordingly, the various baffle sections 54 may be attachable along a section of the outer perimeter of the sidewall 39 of the filter media 40 as well as detachable from and reattachable to the sidewall 39. This process may be completed during manufacturing or post-manufacturing.

[0087] According to another embodiment, multiple baffle sections 54 may be placed next to each other or overlap each other along a portion or section of the outer perimeter of the filter media 40 to change the size of the baffle 50. The baffle sections 54 may be the same size baffle or may be different baffle sizes (such as the small size baffle 51, the medium size baffle 52, and/or the large size baffle 53). By adding or removing the various baffle sections 54, the coverage of the baffle 50 along the filter media 40 is changed.

[0088] According to one embodiment, baffle 50 may be an add-on element to allow the filter element 26 to be fine-tuned according to the user's preferences and/or to allow the baffle 50 to be attached to existing filters in standard filter manufacturing. Accordingly, various portions of the filter element 26 and/or the baffle 50 may include attachment mechanisms to help attach the baffle 50 to the filter media 40 and/or the end cap 42. The baffle 50 may be attached to the filter media 40 and/or the end cap 42 with a variety of different attachment mechanisms,

including but not limited to, a snap-fit relationship, a press-fit relationship, adhesives, or a tongue and groove relationship. The end cap 42 may attach to or over the baffle 50 to secure the baffle 50 to the filter media 40.

[0089] As shown in FIGS. 4A and 4C, the baffle 50 includes openings to allow a portion of the end cap 42 to fit within, thus creating a mechanical lock between the baffle 50 and the end cap 42. For example, as the end cap 42 is being formed, the end cap material (e.g., urethane) may flow through the openings on the baffle 50 to create the mechanical lock.

Baffle Vane

[0090] According to another embodiment as shown in FIGS. 11A-12D, the baffle 50 includes an extension or vane 62 to further direct the air entering in through the inlet 32 of the housing 30. As shown in FIGS. 12A-12B, the baffle vane 62 extends substantially perpendicularly to the outer surface 48 of the filter media 40 and to a radial covering area 64 of the baffle 50. The radial covering area 64 is configured to extend alongside and cover a portion of the outer surface 48 of the filter media 40 and is positioned directly across from or proximate the inlet 32 of the housing 30 after installation. Accordingly, the baffle vane 62 extends along a portion of the outer perimeter of the filter media 40 next to the radial covering area 64. The vane 62 and the baffle 50 may be integral components as shown, for example, in FIGS. 22A-22C and formed together at the same time.

[0091] The vane 62 is positioned at the top of the baffle 50 such that the vane 62 and the connection of the baffle 50 to the end cap 42 are on opposite sides of the radial covering area 64. The height of the vane 62 (e.g., the distance that the vane 62 extends substantially perpendicularly from the radial covering area 64 of the baffle 50) is such that the vane 62 nears or abuts the inner surface of the sidewall 39 of the housing 30 when the filter media 40 (with the baffle 50) is positioned within the housing 30. One embodiment of an extension to a vane is shown in U.S. Patent No. 8,828,114, the entire disclosure of which is incorporated by reference herein in its entirety.

[0092] The housing 30 may also include a housing vane 72. As shown in FIG. 11A, the housing vane 72 extends into the housing 30 from the sidewall 39 of the housing 30 such that the housing vane 72 is substantially perpendicular to the sidewall 39 of the housing 30.

[0093] As shown in FIGS. 11A-11D, the vane 62 of the baffle 50 is positioned within the housing 30 such that the baffle vane 62 is a continuation or extension of the vane 72 of the housing 30. For example, the baffle vane 62 is in line with the end of the housing vane 72 and continues along the direction of extension of the housing vane 72. Accordingly, the vane 62 of the baffle 50 may increase the pre-cleaner separator length by further extending the effective length of the vane 72 along the length of the filter media 40, which further improves the pre-cleaner performance of the air filter 20.

Keying Features

[0094] According to one embodiment and as shown in FIGS. 2, 3A-3B, and 5A-5C, since the baffle 50 may not encompass the perimeter of the filter media 40, the air filter 20 includes keying features 36 and 46 to properly align the baffle 50 and the inlet 32 of the housing 30 and thus provide optimal performance. For example, the keying features 36 and 46 allow the filter media 40 to fit only in a particular orientation and location within the housing 30. The keying features 36 and 46 are located on or towards an open end (e.g., the outlet 34, as shown in FIG. 5C) of the housing 30. More specifically, the housing 30 includes a housing keying feature 36 (as shown in FIG. 2) and the end cap 42 of the filter media 40 includes a media keying feature 46 (as shown in FIGS. 3A-3B). The media keying feature 46 and the corresponding housing keying feature 36 have complementary geometries such that the keying features 36 and 46 can engage with each other and fit together and maintain the relative positioning, alignment, and/or orientation of the housing 30 and the filter media 40. Accordingly, when the filter element 26 is correctly installed within the housing 30, the filter element 26 is fully engaged and interlocked with the housing 30.

[0095] The keying features 36 and 46 may possess a variety of different shapes and configurations, depending on the desired locking interaction between the keying feature 36 and 46. As shown in FIGS. 2, 3A-3B, and 5A-5C, the keying features 36 and 46 may include a

ridge, a recessed region, or a flat surface along a portion of the perimeter of the housing 30 and the filter cap 42 such that a portion of the perimeters is flat and another portion is curved. The keying feature 36 is located on the inside perimeter of the housing 30 and the keying feature 46 is located on the outer perimeter of the end cap 42. Accordingly, when the end cap 42 is positioned within the housing 30, the flat portions of the keying features 36 and 46 (and the curved portions of the keying features 36 and 46) fit or interlock together to prevent relative movement or rotation between components, as shown in FIG. 5A.

[0096] As shown in FIGS. 5B-5C and according to one embodiment, the housing keying feature 36 includes a protrusion 38, or other similar features, for additional support and for an additional keying feature. Accordingly, the filter media 40 may have complementary geometry to the keying feature 36 of the housing 30 to ensure that the correct filter is being used and/or to secure the filter media 40 to the housing 30. The protrusion 38 may be particularly beneficial when different sized baffles 50 may be used with the same size filter media 40 for fine-tuning. Additionally, the protrusion 38 may aid in the manufacturing of the filter housing 30. For example, the protrusion 38 may help the housing keying feature 36 eject from a mold. The protrusion 38 may be located in a variety of different locations within the housing 30, such as on either side of the wall of the housing keying feature 36.

[0097] As shown in FIGS. 3A-3B and 4B, the media keying feature 46 is located on the end cap 42. Alternatively or additionally, the media keying feature 46 may be located directly on the filter media 40.

[0098] Alternatively or additionally as shown in FIG. 4C, the baffle 50 includes a baffle keying feature 56. The baffle keying feature 56 may have complementary geometry to the keying features 36 and/or 46 to maintain relative orientations of each component. For example, the baffle keying feature 56 may interlock or align with the media keying feature 46 to ensure that the baffle 50 is properly oriented relative to, installed on, or attached to the filter media 40, regardless of the relative positioning of the housing 30. The baffle keying feature 56 of the baffle 50 may extend beyond a filtering portion of the filter media 40 and along the keying feature 46 of the filter media 40 to lock the relative positions of the baffle 50 and the filter media 40.

[0099] It is understood that the air filter 20 can include only two keying features 36, 46, and/or 56 or three of the keying features 36, 46, and 56 that are complementary to each other in order to ensure the correct configuration. Furthermore, it is understood that the housing 30, the filter media 40, and/or the baffle 50 may each have two keying features to that correspond separately to the respective keying features of the other two components within the air filter 20. For example, the filter media 40 may have two keying features 46 that correspond to either the housing keying feature 36 or the baffle keying feature 56 for proper alignment.

[0100] It is also understood that media keying feature 46 and the housing keying feature 36 can be used within an air filter 20, regardless as to whether the air filter 20 includes a baffle or what type of baffle is used. According to one embodiment as shown in FIGS. 16A-16C, the filter element 26 may include a full baffle ring 80 that extends around the entire circumference of the filter media 40 (e.g., the baffle ring 80 extends 360° around the filter media 40 in, for example, a full ring, and is attachable to the filter media 40). According to another embodiment as shown in FIGS. 17A-17C, the filter element 26 does not include any baffle (e.g., there is no baffle on the filter media 40). According to yet another embodiment as shown, for example, in FIGS. 15A-15D, the filter element 26 includes the baffle 50, as described further herein.

[0101] According to another embodiment as shown in FIG. 6, the inner diameter 43 of the end cap 42 is maximized and increased compared to previous air filters, which reduces the amount of material needed to make the air filter 20 and further improves the performance of the air filter 20. Increasing the diameter 43 of the end cap 42 increases the size (e.g., diameter) of the outlet 34 of the air filter 20 and thus further reduces the restriction across the air filter 20. According to yet another embodiment, the radius transition of the housing 30 may be increased from the flat end of the air filter 20 to the outlet 34 in order to help further reduce the restriction within the air filter 20.

[0102] According to one embodiment, the filter assembly 20 includes the filter housing 30 with the housing keying feature 36 that extends within an inner region of the filter housing 30. As described previously, the housing keying feature 36 is configured to engage with a

complementary media keying feature 46. The filter assembly 20 also includes the filter media 40 that is configured to be received within the inner region of the housing 30.

[0103] The filter assembly 20 also includes the end cap 42 with a first end and a second end. The first end of the end cap 42 is positioned at and coupled to one end of the filter media 40 and has a first outer circumference. According to one embodiment as shown in FIGS. 18A-20C, the second end of the end cap 42 comprises a stepped-in or recessed ring 96. Accordingly, the second end of the end cap 42 has a second outer circumference that is smaller than the first outer circumference of the end cap 42 such that the end cap 42 is stepped inward along the entire perimeter of the end cap 42 along the second end (relative to the first end). The second outer circumference of the end cap 42 is also smaller than the inner circumference of the housing 30 (measured in the region that includes the housing keying feature 36) such that the second outer circumference of the end cap 42 is stepped inboard of and fits inside of the housing keying feature 36 along the entire perimeter of the end cap 42. Accordingly, when the filter media 40 is installed within the housing 30, the second end of the end cap 42 bypasses and does not engage with the housing keying feature 36, and the end cap 42 does not need a feature (e.g., a keying feature) that is exactly complementary to the housing keying feature 36. According to one embodiment, the end cap 42 may rotate within and relative to the housing 30 when the filter media 40 and the end cap 42 are installed within the housing 30. The recessed ring 96 may be used with the baffle 50 (as shown in FIGS. 18A-18C), with no baffle (as shown in FIGS. 19A-19C), or with the full baffle ring 80 (as shown in FIGS. 20A-20C).

[0104] The filter assembly 26 may include a baffle (as described further herein) or may not include a baffle. According to particular embodiments as shown in FIGS. 16A-16C and 20A-20C, for example, the filter assembly 20 includes the full baffle ring 80 that extends around the entire circumference of the filter media 40 (e.g., the baffle ring 80 extends 360° around the filter media 40 in, for example, a full ring, and is attachable to the filter media 40). According to other embodiments as shown in FIGS. 17A-17C and 19A-19C, the filter assembly 20 does not include any baffle (e.g., there is no baffle on the filter media 40). According to yet another embodiment, the filter element 26 includes the baffle 50, which may be a partial baffle as shown in FIGS. 15A-15D and 18A-18C, as described further herein.

[0105] It is anticipated that the various components, configurations, and features of the different embodiments of the air filter 20 may be combined according to the desired use and configuration.

Experimental Data

[0106] FIG. 14 is a graph providing experimental data and depicting the percentage of improvement of the system life of different air filters (compared to the baseline, when 0% of the inlet is covered by a baffle) as a function of the percentage that the inlet was covered by a baffle. The experiment was conducted at a single flow rate. The system life of each different percentages of the inlet covered was compared to the baseline system life (i.e., the system life with 0% of the inlet covered).

[0107] As shown, when 20% of the inlet is covered by the baffle, the system life of the filter is approximately 107.8%. When 60% of the inlet is covered by the baffle, the system life of the filter is approximately 108.9%. When 100% of the inlet is covered by the baffle, the system life of the filter is approximately 107.9%. These percentages of the system life are all system life percentages when compared to baseline testing (e.g., when 0% of the inlet is covered by a baffle).

[0108] As utilized herein, the terms “approximately,” “about,” “substantially” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and are considered to be within the scope of the disclosure.

[0109] The terms “coupled,” “connected,” and the like as used herein mean the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed

as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another.

[0110] References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below,” etc.) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

[0111] It is important to note that the construction and arrangement of the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter described herein. For example, elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or positions may be altered or varied. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes and omissions may also be made in the design, operating conditions and arrangement of the various exemplary embodiments without departing from the scope of the present invention.

WHAT IS CLAIMED IS:

1. A filter element, comprising:
a filter media configured to be secured within a housing, the housing including an inlet configured to accept a fluid for filtering, the filter media including a circumferential outer surface;
an end cap positioned at and coupled to one end of the filter media; and
a baffle positioned relative the filter media at a position such that, when the filter element is correctly installed within the housing, the baffle is proximate the inlet of the housing, the baffle extending around only a portion of the circumferential outer surface of the filter media in a radial direction.
2. The filter element of claim 1, wherein the baffle is positioned proximate the end cap.
3. The filter element of claim 1, wherein the baffle includes at least two baffle sections configured to be attached along and detached from a section of the outer perimeter of the filter media.
4. The filter element of claim 1, further comprising a media keying feature located on the end cap, the media keying feature having complementary geometry with and configured to engage a corresponding housing keying feature located on the housing.
5. The filter element of claim 4, wherein the media keying feature is a flat portion of the outer perimeter of the end cap.
6. The filter element of claim 1, further comprising a media keying feature located on the end cap, wherein the baffle includes a baffle keying feature that has complementary geometry with and is configured to engage with the media keying feature.
7. The filter element of claim 1, wherein the baffle is specifically positioned on the filter media such that, when the filter element is correctly installed within the housing, the fluid for filtering directly contacts the baffle before entering the filter media.

8. The filter element of claim 1, wherein the baffle and the end cap are separate components attachable with each other.

9. The filter element of claim 1, wherein the baffle and the end cap are integral components.

10. The filter element of claim 1, wherein the baffle and the circumferential outer surface of the filter media are integral components.

11. The filter element of claim 1, wherein the baffle includes a baffle vane that extends perpendicularly to a radial covering area of the baffle, wherein the radial covering area covers the portion of the circumferential outer surface of the filter media.

12. The filter element of claim 11, wherein the baffle vane is alignable with a housing vane of the housing such that the baffle vane extends along the direction of extension of the housing vane.

13. The filter element of claim 1, wherein the end cap includes a rigid portion and a pliable portion.

14. The filter element of claim 13, wherein at least one of the rigid portion and/or the pliable portion completely covers the one end of the filter media.

15. The filter element of claim 13, wherein at least one of the rigid portion and/or the pliable portion partially cover a first portion of the one end of the filter media such that a second portion of the one end of the filter media is exposed.

16. The filter element of claim 13, further comprising a seal that extends along an inner perimeter of the end cap.

17. A filter assembly, comprising:
a filter housing including an inlet configured to accept a fluid for filtering;
a filter media configured to be secured within the housing, the filter media including a circumferential outer surface;

an end cap positioned at and coupled to one end of the filter media; and
a baffle positioned relative the filter media at a position such that, when the filter element is correctly installed within the housing, the baffle is proximate the inlet of the housing, the baffle extending around only a portion of the circumferential outer surface of the filter media in a radial direction.

18. The filter assembly of claim 17, wherein the baffle is positioned proximate the end cap.

19. The filter assembly of claim 17, wherein the baffle includes at least two baffle sections configured to be attached along and detached from a section of an outer perimeter of the filter media.

20. The filter assembly of claim 17, further comprising a media keying feature located on the end cap and a housing keying feature located on the housing, the media keying feature and the housing keying feature having complementary geometry and configured to engage with each other.

21. The filter assembly of claim 20, wherein the media keying feature is a flat portion of an outer perimeter of the end cap.

22. The filter assembly of claim 20, wherein the baffle includes a baffle keying feature that has complementary geometry with and is configured to engage the media keying feature.

23. The filter assembly of claim 17, wherein the baffle is specifically positioned on the filter media such that, when the filter element is correctly installed within the housing, the fluid for filtering directly contacts the baffle before entering the filter media.

24. The filter assembly of claim 17, wherein the baffle includes a baffle vane that extends perpendicularly to a radial covering area of the baffle, and wherein the radial covering area covers the portion of the outer surface of the filter media.

25. The filter assembly of claim 24, wherein the housing includes a housing vane, and wherein the baffle vane is configured to align with the housing vane such that the baffle vane extends along the direction of extension of the housing vane.

26. A filter element, comprising:
a filter media configured to be secured within a housing, the housing including an inlet configured to accept a fluid for filtering;
an end cap positioned at and coupled to one end of the filter media; and
a media keying feature located on the end cap, the media keying feature having a complementary geometry with and configured to engage a corresponding housing keying feature located on the housing, such that, when the filter element is correctly installed within the housing, the filter element is fully engaged and interlocked with housing.

27. The filter element of claim 26, further comprising a baffle extending around an entire circumference of the filter media.

28. The filter element of claim 26, wherein the filter element does not include any baffle.

29. A filter assembly, comprising:
a filter housing having a housing keying feature extending within an inner region of the housing and configured to engage with a complementary media keying feature, the housing having an inner circumference that includes the housing keying feature;
a filter media configured to be received within the inner region of the housing;
and
an end cap with a first end and a second end, the first end of the end cap positioned at and coupled to one end of the filter media and having a first outer circumference, the second end of the end cap having a second outer circumference that is smaller than the first outer circumference of the end cap and smaller than the inner circumference of the housing such that, when the filter media is installed within the housing, the second end of the end cap bypasses and does not engage with the housing keying feature.

30. The filter assembly of claim 29, further comprising a baffle extending around an entire circumference of the filter media.

31. The filter assembly of claim 29, wherein the filter assembly does not include any baffle.

32. The filter assembly of claim 29, further comprising a baffle positioned along a circumferential outer surface of the filter media, wherein the baffle extends around only a portion of the circumferential outer surface of the filter media in a radial direction.




FIG. 1A





FIG. 1B

2/24



3/24




FIG. 4C




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C

5/24





FIG. 6

6/24



7/24




FIG. 7C







FIG. 7D



9/24



85

10/24




FIG. 9




FIG. 10

11/24




FIG. 11B




FIG. 11A

12/24




FIG. 11D






FIG. 11C





15/24




FIG. 13




FIG. 14




FIG. 15D




FIG. 15C




FIG. 15A









FIG. 15B

















INTERNATIONAL SEARCH REPORT

International application No.

PCT/US15/66579

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - B01D 35/30, 45/08, 46/00, 46/52 (2016.01)

CPC - B01D 46/0005, 46/0021, 46/0046

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8): B01D 35/30, 45/08, 46/00, 46/52; B23P 15/22 (2016.01)

CPC: B01D 46/0005, 46/0021, 46/0046

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PatSeer (US, EP, WO, JP, DE, GB, CN, FR, KR, ES, AU, IN, CA, Other Countries (INPADOC), RU, AT, CH, TH, BR, PH), EBSCO, PatentsGoogle, Google Scholar, sciencedirect.com: baffles, end cap, impingement, filter media, filter element, housing, radial, circumferential, outer, rigid, pliable, baffle vane, housing vane, alignable, completely covers one end, seal, attachable, detachable**

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US 8,784,523 B2 (COULONVAUX, P et al.) 22 July 2014; figures 9-10; column 2, lines 40-60; column 5, lines 10-30	26-27 --- 4-6, 20-22, 28-32
Y	WO 2002/20132 A2 (DONALDSON COMPANY, INC) 14 March 2002; page 28, lines 25-34; page 29, lines 1-5, 15-34; page 30, lines 1-5; page 32, lines 19-24; page 34, lines 5-34; page 35, lines 1-5; figures 22-23, 25-26, 29	1-25, 28
Y	US 2013/0043176 A1 (DONALDSON COMPANY, INC) 21 February 2013; figures 1-2; paragraphs [0003]-[0004], [0020]-[0021]	9-10
Y	US 7,833,305 B1 (STUDER, RM) 16 November 2010; figure 5; column 6, lines 55-67; column 7, lines 1-15	1-25, 32
Y	US 2010/0122952 A1 (SOUTH, KC et al.) 20 May 2010; figures 1, 4, 9; paragraphs [0016]-[0023], [0027]	8, 29-32
Y	US 7,998,251 B2 (PONDELICK, MA et al.) 16 August 2011; figures 1, 9-10; column 3, lines 1-10; column 4, lines 5-15; column 7, lines 50-65	12, 25
Y	US 8,828,114 B2 (DHIMAN, R et al.) 9 September 2014; figure 4; column 2, lines 54-65; column 4, lines 20-51	5, 21, 31
A	US 2004/0093859 A1 (SCHMEICHEL, SD et al.) 20 May 2004; entire document	1-32



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

3 February 2016 (03.02.2016)

Date of mailing of the international search report

26 FEB 2016

Name and mailing address of the ISA/

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450
Facsimile No. 571-273-8300

Authorized officer

Shane Thomas

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US15/66579

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4,020,783 A (ANDERSON, ED et al.) 3 May 1977; entire document	1-32