



US007025254B1

(12) **United States Patent**
Brickett et al.

(10) **Patent No.:** **US 7,025,254 B1**
(45) **Date of Patent:** **Apr. 11, 2006**

(54) **NON-VISUALLY IDENTIFIABLE FISHING GEAR**

(75) Inventors: **Benjamin P. Brickett**, Eliot, ME (US);
Scott Moffat, Kittery, ME (US)

(73) Assignee: **Blue Water Concepts, Inc.**, Eliot, ME (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 66 days.

(21) Appl. No.: **10/978,974**

(22) Filed: **Nov. 1, 2004**

Related U.S. Application Data

(60) Provisional application No. 60/517,183, filed on Nov. 5, 2003.

(51) **Int. Cl.**
G06F 17/00 (2006.01)

(52) **U.S. Cl.** **235/375**; 235/439; 235/487

(58) **Field of Classification Search** 441/136,
441/1, 6, 11, 89, 133; 43/4, 7, 100; 114/326,
114/328; 340/539.1, 693.5, 572.1; 235/375,
235/385, 492, 493, 380, 382, 435, 449, 451,
235/487

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

440,582 A * 11/1890 Bahlsen 24/114.5
2,177,364 A * 10/1939 Fotsch 403/185
2,686,963 A * 8/1954 Freyssinet 264/249
3,475,795 A * 11/1969 Youngblood 24/122.6
3,600,765 A * 8/1971 Rovinsky et al. 24/122.6
3,676,899 A * 7/1972 Ehlert 403/247
3,722,014 A * 3/1973 Hill et al. 441/2

3,996,417 A * 12/1976 Annas 174/90
4,177,542 A * 12/1979 Denney 24/115 R
4,262,379 A * 4/1981 Jankiewicz 441/2
4,734,961 A * 4/1988 Guthmann 24/122.6
4,980,989 A * 1/1991 Davis 43/100
5,390,581 A * 2/1995 Hiltz et al. 89/1.812
5,398,441 A * 3/1995 Melanson 43/100
5,415,490 A * 5/1995 Flory 403/267
5,906,170 A * 5/1999 Robertson 114/254
5,962,834 A * 10/1999 Markman 235/385
6,510,988 B1 * 1/2003 Kraus 235/382
6,598,800 B1 * 7/2003 Schmit et al. 235/462.44
6,676,061 B1 * 1/2004 Cain 242/401
6,747,561 B1 * 6/2004 Reeves 340/573.1
6,754,083 B1 * 6/2004 Lin 361/737
6,825,751 B1 * 11/2004 Kita et al. 340/5.61
2003/0169207 A1 * 9/2003 Beigel 343/718
2003/0179584 A1 * 9/2003 Pond et al. 362/487
2004/0100386 A1 * 5/2004 Tendler 340/573.3

FOREIGN PATENT DOCUMENTS

GB 2398454 * 8/2004
WO WO 8905460 * 6/1989
WO WO 20040320641 * 4/2005

* cited by examiner

Primary Examiner—Karl D. Frech


Assistant Examiner—Daniel Walsh

(74) *Attorney, Agent, or Firm*—Hayes Soloway PC

(57) **ABSTRACT**

A non-visual identification apparatus includes aquatic gear. At least one water-resistant device is joined with the aquatic gear. The water-resistant device stores information. A reader is provided that is capable of non-visually reading the information stored by the device. The water-resistant device may be joined mechanically and/or adhesively with the aquatic gear. The reader may be capable of wirelessly reading the information stored by the device.

16 Claims, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5

**FIG. 6**

1

NON-VISUALLY IDENTIFIABLE FISHING GEAR

CROSS-REFERENCES

This application claims priority to co-pending U.S. Provisional Application entitled, "non-Visually Identifiable Fishing Gear," having Ser. No. 60/517,183, filed Nov. 5, 2003, which is incorporated herein by reference.

FIELD OF THE INVENTION

The present invention is in the field of identification devices. Specifically, the present invention is in the field of non-visual identification means for equipment in a water environment.

BACKGROUND OF THE INVENTION

A substantial portion of the fishing industry involves fixed gear fishing. Fixed gear fishing involves the use of fishing equipment being left unattended in the water for a period of time and then collected, presumably once fish have been caught. One typical example of fixed gear is a lobster trap, which is often left at the bottom of the sea for anywhere from a day to a week and then reeled in and the traps are emptied.

Fixed gear fishing is regulated. Some regulations are in place to avoid decimation of the marine wildlife targeted by the fixed fishing gear. For instance, some regulations are placed on lobster fishing to avoid decimating the current lobster population. Other regulations are in place to avoid unintended harm to other marine wildlife. For instance, some regulations are placed on lobster fishing to avoid harm to the endangered right whales, which annually suffer casualties after becoming entangled in lobster fishing lines. Enforcement of these regulations requires being able to identify the owner of fixed gear while the fixed gear is unattended.

Current methods of marking fixed gear to identify the owner of fixed gear are visual in nature. One common method of marking gear is painting the buoys that support the fixed gear a different color for each fisherman. This method is effective for small numbers of fisherman, but can be confusing differentiating between large numbers of fisherman, particularly when the water discolors the buoys. Another known method of making fixed gear visually identifiable has been to tie colored threads to the ropes at various intervals. This system can handle larger volumes of fishermen but using multiple threads (e.g., one blue, one green, and one red identifies one fisherman, while two blue and a yellow identify another fisherman). This system again suffers the effect of the threads becoming discolored by the water. The threads may also break off during use of the rope and require regulators to get very close to the rope to make identification.

Thus, a heretofore unaddressed need exists in the industry to address the aforementioned deficiencies and inadequacies.

SUMMARY OF THE INVENTION

Embodiments of the present invention provide a system and method for non-visually identifying equipment in a water environment.

Briefly described, in architecture, one embodiment of the system, among others, can be implemented as follows. A non-visual identification apparatus includes aquatic gear. At

2

least one water-resistant device is joined with the aquatic gear. The water-resistant device stores information. A reader is provided that is capable of non-visually reading the information stored by the device.

5 The present invention can also be viewed as providing methods for non-visually identifying equipment in a water environment. In this regard, one embodiment of such a method, among others, can be broadly summarized by the following steps: storing information on at least one water-resistant device; inserting the water-resistant device in aquatic gear; and non-visually reading the information stored on the device. The present invention can also be viewed as providing a system for non-visually identifying equipment in a water environment. In this regard, one embodiment of such a system, among others, can be broadly summarized by the following: means for storing information; means for making the means for storing information water-resistant; means for joining the means for storing information with the aquatic gear; and means for reading information off of the means for storing information.

Other systems, methods, and advantages of the present invention will be or become apparent to one with skill in the art upon examination of the following drawings and detailed description. It is intended that all such additional systems, methods, features, and advantages be included within this description, be within the scope of the present invention, and be protected by the accompanying claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Many aspects of the invention can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present invention. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

FIG. 1 is a cross-sectional view of a first exemplary embodiment of the present invention.

FIG. 2 is a cross-sectional view of a second exemplary embodiment of the present invention.

FIG. 3 is a cross-sectional view of a portion of a third exemplary embodiment of the present invention.

FIG. 4 is a flow diagram of a method of using the first exemplary embodiment of the present invention.

FIG. 5 is a flow diagram of a method of using the third exemplary embodiment of the present invention.

FIG. 6 is a perspective drawing illustrating one of the steps of the method of using the third exemplary invention, in accordance with FIG. 5.

DETAILED DESCRIPTION

55 FIG. 1 contains a cross-sectional view of a first exemplary embodiment of the present invention. A non-visual identification apparatus 10 utilizes a cooperative identification system, in which the identifying agency and the object to be identified cooperate in the identification process according to a prearranged scheme. Specifically, the non-visual identification apparatus 10 is designed to be used with aquatic gear 12. At least one water-resistant device 14 is joined with the aquatic gear 12. The water-resistant device 14 stores information. A reader 16 is provided that is capable of non-visually reading, by induced electromagnetic or other energy carrier wave, the information stored by one or more the water-resistant devices 14.

The aquatic gear **12** can be any item that can be expected to be submersed in, operated on, or subjected to an aqueous environment. Aquatic gear **12**, includes, but is not limited to, lobster traps, buoys, fishing rope, other fishing gear, nautical vessels, and scuba equipment.

The water-resistant device **14** and reader **16** are capable of communication with each other. Communication may be achieved wirelessly or with a disconnectable wired connection. One applicable system for the water-resistant device **14** and reader **16** is an RFID (Radio Frequency Identification) system. A second exemplary embodiment of the present invention is shown in FIG. 2. In the RFID system shown, the water-resistant device **114** and reader **116** include an antenna **118**, a transceiver **120** (with decoder), and a transponder tag **122** programmed with information.

The antenna **118** emits radio signals to activate the tag **122** and read and write data to it. The antenna **118** is the conduit between the tag **122** and the transceiver **120**, which controls data acquisition and communication for the system **110**. The antenna **118** can be packaged with the transceiver **120** with decoder to become the reader **116**, which can be configured either as a handheld or a fixed-mount device. The reader **116** can be configured to emit radio waves in ranges of anywhere from one inch to 100 feet or more, depending upon its power output and the radio frequency used. These radio waves, called an activation signal, create an electromagnetic zone for the tags **122**. When a transponder tag **122** passes through the electromagnetic zone, it detects the activation signal. The reader **116** decodes the data encoded in the tag **122** and the data is collected for processing.

Transponder tags **122** are categorized as either active or passive. Active transponder tags **122** are powered by an internal battery and are typically read/write, i.e., tag data can be rewritten and/or modified. Memory size for an active transponder tag **122** varies according to application requirements; some transponder tags **122** currently operate with up to 1 MB of memory. The battery-supplied power of an active transponder tag **122** generally gives it a longer read range. The trade off is greater size, greater cost, and a limited operational life (which may yield up to 10 years with current technology, depending upon operating temperatures and battery type).

Passive transponder tags **122** operate without a separate external power source and obtain operating power generated from the reader **116**. Passive transponder tags **122** are consequently much lighter than active transponder tags **122**, less expensive, and offer a virtually unlimited operational lifetime. The trade off is that they have shorter read ranges than active transponder tags **122** and require a higher-powered reader **116**. Read-only tags **122** are typically passive and are programmed with a unique set of data (usually 32 to 128 bits) that cannot be modified.

In this second exemplary embodiment, the water-resistant device **114** can be an active or passive Transponder tag **122** having a hermetic seal **124**. Hermetically sealing the tag **122** allows the integrated circuit within the tag **122** to be submersed in water for significant periods of time without water damage. However, the tag **122** and/or hermetic seal **124** may still be subject to physical damage if put in a location subject to significant strain, including crushing or bending damage.

Frequency ranges also distinguish RFID systems. Low-frequency (30 KHz to 500 KHz) systems have short reading ranges and lower system costs. High-frequency (850 MHz to 950 MHz and 2.4 GHz to 2.5 GHz) systems, offering long read ranges (greater than 90 feet) and high reading speeds. The high-frequency systems would allow reading of submersed tags **122** from the surface of a body of water if the

tags **122** are submersed at a depth that is less than the range of the high frequency system.

Tags **122** can be read through the water, a hermetic seal **124**, and many other materials in which the transponder tags **122** may be mounted, including the exterior of some aquatic gear **112**. Transponder tags **122** can also be read in challenging circumstances at remarkable speeds, in most cases responding in less than 100 milliseconds. The read/write capability of an active RFID system is also a significant advantage in interactive applications such as work-in-process or maintenance tracking.

Other systems are contemplated by the present invention, including other types of wireless and optical technology.

As the water-resistant devices **114**, which include transponder tags **122** and hermetic seals **124**, are vulnerable to crushing and bending damage, the water-resistant devices **114** may be housed in a protective base **126**. The protective base **126** may be constructed to both house the water-resistant devices **114** and mount within the aquatic gear **112**.

An adhesive **128** may be used to join the water-resistant device **114** to the aquatic gear **112**. If a base **126** is used, the adhesive **128** may be used to join the base **126** to the aquatic gear **112**. The adhesive **128** must be effective in water. Epoxies function particularly well as the adhesive **128**. Instead, or in addition, the water-resistant device **114** and/or base **126** may be joined mechanically to the aquatic gear **112**. The base **126** may have hooks that latch to a rope, may be threadably attached to a buoy or lobster trap, or may be attached to aquatic gear **112** using other mechanical mechanisms known to those having ordinary skill in the art.

FIG. 3 shows a portion of a third exemplary embodiment, specifically containing a cross-section of one design for the base **226**. The base **226**, as shown, may be used to make the water-resistant device **214** more easily received by the aquatic gear **212**, shown as a three-strand rope. The base **226** can have a triangular cross-section, which is a shape designed to be received within an interstice of a standard three-strand rope. Each side **230** of the triangular cross-section may be linear or it may be arcuate. An arcuate side **230** may be better shaped to fit within the interstice of the rope. An epoxy or other adhesive **228** may be used as a redundant method of retaining the base **214** within the aquatic gear **212**.

Another feature of the invention embodied within the third exemplary embodiment is an adhesive **228** filling a gap between the base **226** and the water resistant device **214**. One of the reasons for using a base **226** is to protect the water resistant device **214** and, in particular, the hermetic seal from breaking. The base **226**, having a greater structural strength than the hermetic seal of the water resistant device **214**, provides some protection from bending or crushing damage. However, the base **226** may still be bent a degree or two by significant force put on the rope in which the base **226** may be embedded. Even that minute bending can damage the hermetic seal in the water resistant device **214**. Therefore, to avoid having the bending endured by the base **226** translated to the water resistant device **214**, a gap may be provided between the water resistant device **214** and the base **226** sufficient to avoid translation of the bending force. To allow the base **226** to retain the water resistant device **214** with a gap there between, an adhesive **228** or similar substance unlikely to translate the bending force may be inserted between the base **226** and the water resistant device **214**.

The flow chart of FIG. 4 shows the architecture, functionality, and operation of a possible implementation of the non-visual identification apparatus **10**. In this regard, each

5

block represents a module, segment, or step, which comprises one or more executable instructions for implementing the specified function. It should also be noted that in some alternative implementations, the functions noted in the blocks might occur out of the order noted in FIG. 4. For example, two blocks shown in succession in FIG. 4 may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved, as will be further clarified herein.

The present invention includes a method 300 of using a non-visual identification apparatus 10 in an aquatic environment in accordance with the first exemplary embodiment. The method 300 includes storing information on at least one water-resistant device 14 (block 302). The method 300 also includes inserting the water-resistant device 14 in aquatic gear 12 (block 304). The method 300 also includes non-visually reading the information stored on the water-resistant device 14 (block 306).

The step of non-visually reading the information stored on the water-resistant device 14 (block 306) may further involve wirelessly reading the information stored on the water-resistant device 14. The step of inserting the water-resistant device 14 in aquatic gear 12 may further involve prefabricating the water-resistant device 14 in aquatic gear 12. The method 300 may also involve joining the water-resistant device 14 to the rope with an epoxy or other adhesive 28. The method 300 may also involve submerging the water-resistant device 14 in water. The method 300 may also include marking a location of the water-resistant device 14 in the aquatic gear 12 with a visual marker, such as a colored thread or other visual methods known to those having ordinary skill in the art.

As applied to the third exemplary embodiment, the step of inserting the water-resistant device 214 in aquatic gear 212 may further involve inserting the water-resistant device 212 in a length of rope, one type of aquatic gear 212. One method 400 for inserting the water-resistant device 214 in aquatic gear 212 is shown in FIG. 5 and partially illustrated in FIG. 6. The method 400 involves putting the water-resistant device 214 at the end of an insertion rod 232 (block 402). The method 400 also involves caging the rope exposing the interstice of part of the rope (block 404). The method 400 also involves inserting the water-resistant device 214 in the caged rope using the insertion rod 232 (block 406). The method 400 also involves creating tension in the rope to close the caged portion of the rope (block 408). The method 400 also involves pulling the insertion rod 232 from the rope, leaving the water-resistant device 214 within the rope (block 410). The method 400 may be practiced with the water-resistant device 214 held within the base 226. The method 400 may also involve sealing the water-resistant device 214 to the rope with an epoxy or other adhesive 228 (block 412).

It should be emphasized that the above-described embodiments of the present invention are merely possible examples of implementations, merely set forth for a clear understanding of the principles of the invention. Many variations and modifications, such as varying the shape of the base 226 and/or using various wireless technologies, may be made to the above-described embodiments of the invention without departing substantially from the spirit and principles of the invention. All such modifications and variations are intended to be included herein within the scope of this disclosure and the present invention and protected by the following claims.

6

What is claimed is:

1. An apparatus comprising:
 - a three-strand rope;
 - a base attachable to a water-resistant housing, wherein the base is within an interstice of the three-strand rope;
 - at least one electronic device within the water-resistant housing wherein the electronic device further comprises a microchip;
 - the base comprises a triangular cross-section shaped to be received within the interstice of the three-strand rope; and
 - information stored by the electronic device.
2. The enclosure of claim 1, further comprising a reader that nonvisually reads the information stored by the electronic device.
3. The reader of claim 2, further comprising a reader that utilizes electromagnetic waves to read the information stored by the electronic device.
4. The enclosure of claim 1, further comprising an adhesive joining the base to the rope.
5. The enclosure of claim 1, further comprising a latching arrangement joining the base to the rope.
6. An enclosure for an aqueous environment, the enclosure comprising:
 - a base;
 - a gap, accommodating a microchip, within the base; and
 - the base having a polygonal cross-section, the polygonal cross-section held within an interstice of a rope having a plurality of strands.
7. The enclosure of claim 6, wherein the base has at least one mechanical mechanisms to inhibit a movement of the base against the plurality of strands.
8. The enclosure of claim 6, wherein the base is held by a porous structure.
9. The enclosure of claim 6, further comprising:
 - the rope;
 - the base within the rope;
 - the microchip within the base; and
 - information stored by the microchip.
10. The enclosure of claim 6, further comprising an adhesive joining the electronic device to the rope.
11. The enclosure of claim 6, wherein the rope comprises three strands and the polygonal cross-section comprises a triangular cross-section shaped to be received within an interstice of the three-strand rope.
12. The enclosure of claim 6, further comprising an epoxy joining the base to the rope.
13. A method of inserting a base in a rope, the method comprising the steps of:
 - caging a rope having a plurality of strands;
 - inserting the base in an interstice of the rope wherein the base has a polygonal cross-section, the polygonal cross-section held within the interstice of the rope;
 - compacting the rope to hold the base; and
 - putting an electronic device storing information in the base.
14. The method of claim 13, further comprising the step of putting an electronic device in the base.
15. The method of claim 13, further comprising joining the base to the rope with an epoxy.
16. The method of claim 13, further comprising submerging the rope with the base therein in water.

* * * * *