



(86) Date de dépôt PCT/PCT Filing Date: 2011/12/23
(87) Date publication PCT/PCT Publication Date: 2012/09/27
(85) Entrée phase nationale/National Entry: 2013/07/23
(86) N° demande PCT/PCT Application No.: US 2011/002004
(87) N° publication PCT/PCT Publication No.: 2012/128738
(30) Priorité/Priority: 2010/12/23 (US61/457,084)

(51) Cl.Int./Int.Cl. *H04W 4/12* (2009.01)
(71) Demandeur/Applicant:
TELECOMMUNICATION SYSTEMS, INC., US
(72) Inventeurs/Inventors:
CASTO, PAUL, US;
TUTTLE, LEWIS, US;
GAO, DONGHONG, US
(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : MAPPAGE D'ADRESSES ALPHANUMERIQUES POUR DES RESEAUX DE MESSAGES COURTS NON
HOMOGENES

(54) Title: ALPHANUMERIC ADDRESS MAPPING FOR NON-HOMOGENEOUS SHORT MESSAGE NETWORKS




FIG. 1

(57) Abrégé/Abstract:

Text messages with alphanumeric addresses are delivered to mobiles and external short message entities (ESMEs) which do not support alphanumeric addressing, providing meaningful fallback handling. Additionally, the invention enables delivery of SMPP



(57) **Abrégé(suite)/Abstract(continued):**

messages from ESME or SMPP networks which can only originate numeric addresses, yet provide for mapping to alphanumeric addresses for delivery to the mobile. A two-way mapping is provided between alphanumeric addresses and S-S short-codes to enable delivery of text messages with alphanumeric addressing in networks which contain mobiles and/or ESME's that lack support of alphanumeric addressing.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(10) International Publication Number
WO 2012/128738 A1(43) International Publication Date
27 September 2012 (27.09.2012)(51) International Patent Classification:
G06F 15/16 (2006.01)

(21) International Application Number:

PCT/US2011/002004

(22) International Filing Date:

23 December 2011 (23.12.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/457,084 23 December 2010 (23.12.2010) US

(71) Applicant (for all designated States except US): **TELE-COMMUNICATION SYSTEMS, INC.** [US/US]; 275 West Street, Suite 400, Annapolis, MD 21401 (US).(72) Inventors: **CASTO, Paul**; 12605 Kembridge Drive, Bowie, MD 20715 (US). **TUTTLE, Lewis**; 327 ColumbiaLane, Stevensville, MD 21666 (US). **GAO, Donghong**; 6466 Galway Drive, Clarksville, MD 21029 (US).(74) Agent: **BOLLMAN, William, H.**; Manelli Selter PLLC, 2000 M Street, NW, 7th Floor, Washington, DC 20036 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

[Continued on next page]

(54) Title: ALPHANUMERIC ADDRESS MAPPING FOR NON-HOMOGENEOUS SHORT MESSAGE NETWORKS

(57) Abstract: Text messages with alphanumeric addresses are delivered to mobiles and external short message entities (ESMEs) which do not support alphanumeric addressing, providing meaningful fallback handling. Additionally, the invention enables delivery of SMPP messages from ESME or SMPP networks which can only originate numeric addresses, yet provide for mapping to alphanumeric addresses for delivery to the mobile. A two-way mapping is provided between alphanumeric addresses and S-S short-codes to enable delivery of text messages with alphanumeric addressing in networks which contain mobiles and/or ESME's that lack support of alphanumeric addressing.




FIG. 1

WO 2012/128738 A1

WO 2012/128738 A1

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report (Art. 21(3))*

ALPHANUMERIC ADDRESS MAPPING FOR NON-HOMOGENEOUS SHORT MESSAGE NETWORKS

This application claims priority from U.S. Provisional No. 61/457,084, entitled "ALPHANUMERIC ADDRESS MAPPING FOR NON-HOMOGENEOUS SHORT MESSAGE NETWORKS" to Paul CASTO, Lewis TUTTLE, and Donghong GAO, filed December 23, 2010, the entirety of which is expressly incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to telecommunications. More particularly, it relates to wireless based technologies.

2. Background of the Related Art

When a short message service center (SMSC) operates in a long term evolution (LTE)/CDMA (or GSM/CDMA, or UMTS/CDMA) dual mode network, the vast majority of GSM, UMTS and LTE mobiles support alphanumeric addressing where as many or most CDMA mobiles may not. This impacts the display of the originator of the message to the end-user of the mobile phone (or conversely the terminator, when the user is replying). Many corporations would like messages that they send to an end-user to appear with some form of corporate branding. E.g. ABXCorp would rather have the end user see a message from ABXCorp, rather than see that they have a message from 12345, and then have to figure out what those numbers represent.

A similar issue is also found in supporting external short message entities (ESMEs) from two different vendors. Some ESMEs support alphanumeric addressing while others do not.

Currently, if the mobile or ESME does not allow for message delivery with alphanumeric addresses encoded, the message to the mobile or the ESME may be discarded.

Alternatively, for messages destined to a Mobile, a generic numerical address may be substituted for the alphanumeric address, but a substituted generic numerical address is not meaningful to the Mobile end-user.

Many GSM/UMTS/LTE handsets support alphanumeric addresses.

5 Some CDMA handsets may support alphanumeric (IA5) addresses. SMPP standard supports alphanumeric addresses, but many ESMEs/SMPP gateways have not fully implanted that portion of the standard. Thus, while end-points (some handsets and some ESMEs) may support alphanumeric addressing, the support for end-to-end alphanumeric addressing is not always complete.

10 ESMEs that are aware that a particular end-user handset has the alphanumeric capability could attempt delivery using that format, but that would require the ESME to maintain information about every phone number that it is sending to. Moreover, an ESME maintaining information about every phone number that it is sending to would be very susceptible to the user changing
15 handset models.

Messages that are deleted due to protocol errors (e.g. handset cannot decode an address with alphanumeric characters) result in non-delivery to the subscriber. Messages that have had generic 'alphanumeric to generic' translation rules applied arrive at the handset without allowing the handset device
20 to obtain the identity of the originator, thus also preventing the user device from responding.

SUMMARY OF THE INVENTION

In accordance with the principles of the present invention, a method
25 of handling alphanumeric address mapping for a non-homogeneous short message network comprises receiving a message including an alphanumeric origination address, from an external short message entity (ESME), destined for a terminating mobile device. Mapping the alphanumeric origination address identifying the originating sender's address to a digit string identifying the
30 originating sender's address prior to the first attempt to deliver the message to

the terminating mobile device. The message is then routed to a terminating mobile device including numeric destination addressing.

A method of handling alphanumeric address mapping for a non-homogeneous short message network in accordance with another embodiment of the invention comprises receiving a message including an alphanumeric origination address identifying an originating sender from an external short message entity (ESME). The message is routed to a terminating mobile device including alphanumeric origination addressing. A failed delivery message relating to failure of the message is received. The alphanumeric origination address identifying the originating sender is mapped to a digit string that provides an alternative identification of the originating sender. The message is routed to the terminating mobile device including numeric destination addressing. This provides support for the use cases where the originating ESMEs (and intervening infrastructure) provides the capability to originate messages from alphanumeric addresses, but the receiving devices include a range of network types (LTE/CDMA/UMTS/GSM) and handset types, some of which do support receiving these messages, others of which can not.

Yet another embodiment of the invention discloses a method of handling alphanumeric address mapping for a non-homogeneous short message network. A message is received including a numeric origination address identifying the originating sender from an external short message entity (ESME). The numeric origination address identifying the the originating sender is mapped to an alphanumeric string identifying the an alphanumeric address for the originating sender, prior to a first attempt to deliver the message to the terminating mobile device. The message is routed to a terminating mobile device including alphanumeric originating address. This provides support for the use cases where the originating ESMEs (or intervening infrastructure) lacks the capability to originate messages addressed from an alphanumeric address, yet some, or all of the handsets (and supporting infrastructure) has the capability to receive such messages. A further fallback to the first embodiment is also possible in this case.

Still another embodiment discloses a method of handling alphanumeric address mapping for a non-homogeneous short message network. A message is received including an alphanumeric destination address identifying a terminating external short message entity (ESME), from a mobile device. It is determined through configuration that the terminating external short message entity (ESME) requires numeric addressing. The alphanumeric destination address is converted to a digit address. The message addressed with the digit address is routed to the external short message entity (ESME). This provides support for the use cases where the originating handsets (and intervening infrastructure) provide the capability to originate messages addressed to an alphanumeric ESME address (including the case of 'reply to' alphanumeric addresses), but the ESME (or intervening infrastructure) lacks the capability to receive such messages.

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the present invention become apparent to those skilled in the art from the following description with reference to the drawings:

Fig. 1 shows call flow from an alphanumeric addressing external short message entity (ESME) to a numeric addressing mobile device, for non-homogeneous short message networks, in accordance with the principles of the present invention.

Fig. 2 shows another exemplary call flow from an alphanumeric addressing external short message entity (ESME) to a numeric addressing mobile device, for non-homogeneous short message networks, in accordance with the principles of the present invention.

Fig. 3 shows call flow from a numeric addressing external short message entity (ESME) to an alphanumeric addressing mobile device, for non-homogeneous short message networks, in accordance with the principles of the present invention.

Fig. 4 shows call flow from an alphanumeric addressing mobile device to a numeric addressing external short message entity (ESME), for non-homogeneous short message networks, in accordance with the principles of the present invention.

5

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

The present invention delivers text messages with alphanumeric addresses to mobile devices and external short message entities (ESMEs) which do not support alphanumeric addressing, and provides meaningful fallback
10 handling.

Additionally, the invention enables delivery of Short Message Peer to Peer (SMPP) messages from ESMEs or SMPP networks which can only originate numeric addresses, yet provide for mapping to alphanumeric addresses for delivery to a destination wireless mobile device.

15

The present invention adapts technology which is available within various telecommunication standards, but under-used due to the challenges of interoperability in heterogeneous networks. The inventive solution provides a two-way mapping between alphanumeric addresses and short message system (SMS) short-codes to enable delivery of text messages with alphanumeric
20 addressing in networks which contain mobiles and/or ESME's that lack support of alphanumeric addressing.

25

In accordance with the invention, an ESME can send a text message using an alphanumeric origination address, without the need to know which handsets support the capability, and which do not, or whether handsets are on CDMA, or GSM, or UMTS, or long term evolution (LTE) networks, or can continue to send using a numeric origination address. The Short Message Servicing Center (SMSC) provides conversions to alphanumeric addresses on behalf of the ESME and mobile device.

30

This supports mapping of source and originating addresses both from and to numeric addresses, and mapping of numeric source addresses to alphanumeric for ESME_> Mobile Terminated call flows.

The configuration of the mapping is preferably accomplished such that the number is a meaningful representation of the alphanumeric address. For example, if ABXCorp's short-code address is "12345", messages with an originating address of "ABXCorp" will fall back to "12345". In this manner,
5 response messages addressed to either "ABXCorp" or "12345" are routed to the same destination ESME.

As an extension, or alternate to, the static mapping approach, ESMEs may also include a custom Tag Length Value (TLV) component of an SMPP message to provide an alternate origination address. This allows ESMEs
10 to provide address information in a dynamic fashion, without need for provisioning of a translation table at the SMSC, and still overcomes cases where the infrastructure between the ESME and the SMSC does not support use of alphanumeric addresses directly.

Messages which fail to be delivered due to protocol errors, system
15 or interface configuration, preferably trigger the SMSC 120 to convert the alphanumeric origination address to a meaningful numeric origination address.

In addition to per-message support, entire air-interfaces may be configured to convert alphanumeric addresses back to numeric.

For ESMEs connected to a specific port, the connection may be
20 configured to convert addresses to numbers when alphanumeric addresses are not supported. ESMEs can also be configured by system-type to identify those which cannot support alphanumeric addressing. Or by alphanumeric name (e.g., messages to "ABXCorp" always get converted to "12345").

The present invention provides focus on four primary call flows
25 shown in Figs. 1 through 4.

Fig. 1 shows call flow from an alphanumeric addressing external short message entity (ESME) to a numeric addressing mobile device, for non-homogeneous short message networks, in accordance with the principles of the present invention.

30 In particular, as shown in the call flow of Fig. 1, a message originates from an external short message entity (ESME) with an alphanumeric

originating address, and terminates to a mobile device where the ESME does not support alphanumeric addressing. These may be addressed in two ways, shown in Fig. 1 and Fig.2.

With respect to Fig. 1, the air interface (such as CDMA) may be configured not to support alphanumeric addressing. This causes the message's alphanumeric origination address to be mapped to a digit string, prior to the first attempt. The second technique (shown in Fig. 2) permits the message to fail delivery based on a failure response (such as protocol error), at which time, the SMSC then maps the alphanumeric origination address to a number and retries delivery of the message.

As shown in Fig. 1, an exemplary call flow is described between an originating mobile device **110** (e.g., a CDMA/GSM/UMTS/LTE mobile), a short message service center (SMSC) **120**, a prepaid server **130**, and a receiving external short message entity (ESME) **140**.

The ESME **140** sends a Submit_SM message **310** including alphanumeric originating address to the SMSC **120**.

As depicted in module **320**, the prepaid server **130** is configured for numeric addressing only.

In step **340**, an alphanumeric originating address is mapped to a unique numeric value. The SMSC **120** sends a Debit request message **350** with numeric originating address to the prepaid server **130**.

The prepaid server **130** sends a Debit Response message **360** back to the SMSC **120**, which sends a Submit_SM Response message **330** to the ESME **140**.

In step **370** the CDMA or GSM network, or per-subscriber, is configured to convert alphanumeric addresses prior to delivery.

The alphanumeric originating address is mapped to a unique numeric value in step **372**.

The SMSC **120** sends a Delivery Attempt message with numeric originating address **374** to the CDMA or GSM or IMS or LTE mobile device **110**, which sends back a Delivery Attempt message **376** with results.

In step **378**, the **SMSC 120** configures the billing/call detail records for a numeric address.

In step **380**, the alphanumeric originating address is mapped to a unique numeric value.

5 In step **382**, the billing/call detailed record is written with a numeric origination address.

Fig. 2 shows another exemplary call flow from an alphanumeric addressing external short message entity (ESME) to a numeric addressing mobile device, for non-homogeneous short message networks, in accordance
10 with the principles of the present invention.

In particular, as shown in Fig. 2, the **ESME 140** sends a **Submit_SM** message **410** including alphanumeric originating address to the **SMSC 120**.

As depicted in module **420**, the prepaid server **130** is configured for
15 numeric addressing only.

In step **440**, an alphanumeric originating address is mapped to a unique numeric value. The **SMSC 120** sends a Debit request message **450** with numeric originating address to the prepaid server **130**.

The prepaid server **130** sends a Debit Response message **460**
20 back to the **SMSC 120**, which sends a **Submit_SM** Response message **430** to the **ESME 140**.

The **SMSC 120** sends a Delivery Attempt with alphanumeric originating address to the mobile device **110** (e.g., a CDMA, GSM, IMS or LTE mobile device).

25 In response, a Delivery Attempt Failure message **480** with protocol error is sent from the mobile device **110** back to the **SMSC 120**.

In step **482**, it is determined that the message containing an alphanumeric address failed with a protocol error.

In step **484** the alphanumeric originating address is mapped to a
30 unique numeric value.

A Delivery Attempt message **486** with numeric originating address is sent to the mobile device **110**, which sends back a Delivery Attempt Success message **488**.

5 In step **490**, billing/call detail records are configured for numeric address.

In step **492**, the alphanumeric originating address is mapped to a unique numeric value.

In step **494**, the billing/call detailed record is written with a numeric origination address.

10 Fig. 3 shows call flow from a numeric addressing external short message entity (ESME) to an alphanumeric addressing mobile device, for non-homogeneous short message networks, in accordance with the principles of the present invention.

In particular, in the call flow of Fig. 3, a message originates from an ESME terminating to a mobile device where the ESME sends a numeric address (but would prefer an alphanumeric address be used where possible). This call flow encompasses messages originating from an ESME with numeric originating addresses, and terminating to a mobile which may support alphanumeric addressing (based on per-interface or per subscriber rules). This causes the message's numeric origination address to be mapped to an alphanumeric string, prior to the first attempt. Should an attempt fail, due to protocol error, the fallback mapping occurs as with respect to the call flow of Figs. 1 and 2.

15 As shown in Fig. 3, the ESME **140** sends a Submit_SM message **510** including a numeric originating address to the SMSC **120**.

25 The SMSC **120** sends a Debit Request message **520** with numeric originating address to the prepaid server **130**, which sends a Debit Response message **540** back to the SMSC **120**.

The SMSC **120** sends a Submit_SM Response message **530** to the ESME **140**.

30 In step **550**, the LTE, CDMA, UMTS, or GSM network, or per-subscriber, is configured to convert alphanumeric addresses prior to delivery.

In step **560** the numeric originating address is mapped to a unique alphanumeric value.

The SMSC **120** sends a Delivery Attempt with alphanumeric originating address message **570** to the mobile device **110** (e.g., a CDMA, GSM, UMTS or LTE mobile device).

In response, a Delivery Attempt results message **580** is sent from the mobile device **110** back to the SMSC **120**.

In step **582**, it is determined that the delivery attempt failed with a protocol error.

In step **584** the alphanumeric originating address is mapped back to the original numeric value.

A Delivery Attempt message **586** with numeric originating address is sent to the mobile device **110**, which sends back a Delivery Attempt results message **588**.

In step **590**, the billing/call detail records are written with a numeric origination address.

Fig. 4 shows call flow from an alphanumeric addressing mobile device to a numeric addressing external short message entity (ESME), for non-homogeneous short message networks, in accordance with the principles of the present invention.

In particular, in the call flow of Fig. 4, a message originates from a mobile device with an alphanumeric destination address, and terminates to an ESME that does not support alphanumeric addressing. In this case, based on ESME configuration provisioning, the SMSC converts the alphanumeric destination address to a digit address and sends the text message to the ESME. Since ESMEs are relatively static, the requirement to convert is normally accomplished through configuration. While the invention encompasses a possible attempt followed by a retry, this is inefficient for the mobile originated (MO) to ESME case.

As shown in Fig. 4, the short message service center **120** receives a Submit_SM type message **210** from the originating mobile device **110**, including an alphanumeric destination address.

A prepaid/usage control module **150** in the SMSC **120** receives the
5 Submit_SM message **210**, and the prepaid/usage control module **150** is configured for numeric address only.

In step **160**, the alphanumeric destination address is mapped to a unique numeric value **160** within an appropriate module at the SMSC **120**.

In message **215**, a Debit request with numeric destination address
10 is sent from the SMSC **120** to a prepaid module **130**. The prepaid module **130** returns a Debit Response to the SMSC **120**, and a Submit_SM Response is passed from the SMSC **120** to the originating mobile device **110**.

In step **170**, the SMSC **120** determines that the ESME **140** is configured to accept numeric values only, so there is a need to convert
15 alphanumeric addresses to numeric value.

In step **180** an alphanumeric destination address is mapped to a unique numeric value.

In message **240** a Submit_SM with numeric destination address is sent from the SMSC **120** to the external short message entity (ESME) **140**.

20 In message **250** the ESME **140** sends a Submit_SM with response back to the SMSC **120**.

In step **190** the billing/call detail records configured for numeric address.

In step **200** the alphanumeric destination address is mapped to a
25 unique numeric value.

In step **210** the billing/call detailed record written with numeric destination address.

There are numerous extensions envisioned within the scope of the principles of the present invention. For instance:

Tracking and retaining the handsets capabilities for a period of time. In this way, if an alphanumeric fails, subsequent messages are automatically converted, prior to the first attempt.

Configuring per-subscriber exceptions to the per-air-interface rules.

- 5 This accommodates gradual adoption of handsets - particularly in the CDMA environment which supports IA5 encoding.

The present invention provides an SMSC module that provides a bridge between systems which have the capability to support addressing between wireless devices that may or may not be capable of dealing with alphanumeric addresses.

The present invention permits ESMEs to support a branded source to clearly identify the originator, e.g., a message from "ABXCorp" or a message from "12345" -- Many vendors much prefer to put their brand name in front of a customer, rather than a short code.

- 15 The present invention has particular applicability to wireless carrier markets, e.g., to carriers having mixed LTE/CDMA or GSM/CDMA or UMTS/CDMA networks. The invention may be implemented in an SMSC that supports dual networks (e.g., CDMA network + LTE or GSM) where handsets receive text messages from ESMEs that show an originating alphanumeric address.

While prepaid debit is shown with respect to the embodiments of the present invention, the invention applies equally to post-paid embodiments.

- While the invention has been described with reference to the exemplary embodiments thereof, those skilled in the art will be able to make various modifications to the described embodiments of the invention without departing from the true spirit and scope of the invention.

CLAIMS

What is claimed is:

1. A method of handling alphanumeric address mapping for a non-homogeneous short message network, comprising:

5 receiving a message including an alphanumeric origination address identifying unique origination source, from an external short message entity (ESME) destined for a terminating mobile device;

mapping, prior to a first attempt to deliver said message to said terminating mobile device, said alphanumeric origination address identifying said
10 unique origination source to a digit string identifying said terminating mobile device; and

routing said message to a terminating mobile device including numeric addressing.

15 2. The method of handling alphanumeric address mapping for a non-homogeneous short message network according to claim 1, further comprising:

configuring an air interface to said terminating mobile device not to support alphanumeric addressing, causing said message's alphanumeric
20 origination address to be mapped to said digit string prior to said first attempt to deliver said message to said terminating device.

3. The method of handling alphanumeric address mapping for a non-homogeneous short message network according to claim 1, whereby:

25 said ESME can send a message using an alphanumeric origination address, without a need to know which mobile devices support such capability, and which do not, or whether mobile devices are on CDMA, or GSM, or UMTS, or long term evolution (LTE) networks, or must continue to send using a numeric origination address.

30

4. The method of handling alphanumeric address mapping for a non-homogeneous short message network according to claim 3, further comprising:

5 configuring an air interface to said terminating mobile device not to support alphanumeric addressing, causing said message's alphanumeric origination address to be mapped to said digit string prior to said first attempt to deliver said message to said terminating device.

10 5. A method of handling alphanumeric address mapping for a non-homogeneous short message network, comprising:

receiving a message including an alphanumeric origination address identifying unique origination source, from an external short message entity (ESME) destined for a terminating mobile device; routing said message to a terminating mobile device including alphanumeric origination addressing;

15 receiving a failed delivery message relating to failure of said message;

mapping said alphanumeric origination address identifying said unique origination source to a digit string identifying said unique originating source; and

20 routing said message to said terminating mobile device including numeric addressing.

25 6. The method of handling alphanumeric address mapping for a non-homogeneous short message network according to claim 5, whereby:

said ESME can send a message using an alphanumeric origination address, without a need to know which mobile devices support such capability, and which do not, or whether mobile devices are on CDMA, or GSM, or UMTS, or long term evolution (LTE) networks, or must continue to send using a numeric origination address.

30

7. A method of handling alphanumeric address mapping for a non-homogeneous short message network, comprising:

receiving a message including a numeric numeric origination address identifying unique origination source, from an external short message entity (ESME) destined for a terminating mobile device; mapping, prior to a first attempt to deliver said message to said terminating mobile device, said numeric destination address identifying said unique origination source to an alphanumeric string identifying said unique origination source; and

routing said message to a terminating mobile device including numeric addressing.

8. The method of handling alphanumeric address mapping for a non-homogeneous short message network according to claim 7, whereby:

said ESME can send a message using an alphanumeric origination address, without a need to know which mobile devices support such capability, and which do not, or whether mobile devices are on CDMA, or GSM, or UMTS, or long term evolution (LTE) networks, or must continue to send using a numeric origination address.

9. A method of handling alphanumeric address mapping for a non-homogeneous short message network, comprising:

receiving a message including an alphanumeric destination address identifying a terminating external short message entity (ESME), from a mobile device;

determining through configuration that said terminating external short message entity (ESME) requires numeric addressing;

converting the alphanumeric destination address to a digit address; and

routing said message addressed with said digit address to said external short message entity (ESME).


10. The method of handling alphanumeric address mapping for a non-homogeneous short message network according to claim 9, wherein:

a Short Message Servicing Center (SMSC) provides conversions to alphanumeric addresses on behalf of said terminating external short message
5 entity (ESME).

10

1/8

FIG. 1



CONTINUED ON SHEET 2/8

2/8

FIG. 1

CONTINUED FROM SHEET 1/8





FIG. 2


3/8



CONTINUED ON SHEET 4/8


4/8

FIG. 2



5/8

FIG. 3




CONTINUED ON SHEET 6/8

6/8

FIG. 3


CONTINUED FROM SHEET 5/8



ESME Numeric to Mobile Alphanumeric

7/8


FIG. 4




CONTINUED ON SHEET 8/8

8/8

FIG. 4





ESME Alphanumeric to Mobile Numeric

FIG. 1