



US007720475B2

(12) **United States Patent**
McKenna et al.

(10) **Patent No.:** **US 7,720,475 B2**
(45) **Date of Patent:** ***May 18, 2010**

(54) **COMMUNIQUE SYSTEM WITH ACTIVE FEEDBACK FOR CELLULAR COMMUNICATION NETWORKS**

5,553,315 A 9/1996 Sobti et al.
5,613,191 A 3/1997 Hylton et al.

(Continued)

(75) Inventors: **Daniel B. McKenna**, Steamboat Springs, CO (US); **James M. Graziano**, Platteville, CO (US)

FOREIGN PATENT DOCUMENTS

DE 4338023 5/1995
DE 29918265 3/2000
EP 0837609 4/1998
EP 0998075 5/2000
EP 1037434 9/2000

(73) Assignee: **QUALCOMM Incorporated**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 671 days.

(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

"Multicast for Mobility Protocol (MMP) for Emerging Internet Networks", by A. Mihailovic, Published Sep. 2000, pp. 327-333, In the Eleventh IEEE International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC 2000) London UK.
Dong-Hood, Nam et al., "Adaptive Multimedia Stream Presentation in Mobile Computing Environment", TENCON 99, Proceeding of the IEEE Region 10 Conference, Cheju Island, South Korea, Sep. 15-17, 1999, pp. 966-969, IEEE, Piscataway, NJ.

(21) Appl. No.: **11/230,754**

(22) Filed: **Sep. 19, 2005**

(Continued)

(65) **Prior Publication Data**

US 2006/0099981 A1 May 11, 2006

Related U.S. Application Data

(63) Continuation of application No. 09/731,674, filed on Dec. 6, 2000, now Pat. No. 7,024,200, which is a continuation-in-part of application No. 09/638,744, filed on Aug. 14, 2000, now Pat. No. 6,594,498.

Primary Examiner—Danh C Le
(74) *Attorney, Agent, or Firm*—Sandip (Micky) S. Minhas; Mary A. Fales

(51) **Int. Cl.**

H04Q 7/20 (2006.01)

(52) **U.S. Cl.** **455/435.1; 455/445; 455/450; 455/414.1; 370/328; 709/227**

(57) **ABSTRACT**

An apparatus and method for providing a communiqué constituting program content concurrently delivered to a plurality of subscribers is described. Subscriber confirmation for each of a plurality of subscribers is stored. The subscribers whose wireless devices are active in a cell are identified. Data that identifies a plurality of subscribers is automatically generated. One or more cell are selected to provide communiqué to subscribers who are members of at least one community of subscribers and who are served by other cells of the cellular communication network. Data constituting said communiqué from a selected program source is routed, concurrently, to authorized wireless subscriber devices.


(58) **Field of Classification Search** **455/414.1, 455/418, 445, 450, 435.1; 370/328; 709/227**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,499,386 A 3/1996 Karlsson

16 Claims, 12 Drawing Sheets



U.S. PATENT DOCUMENTS

5,844,522	A	12/1998	Sheffer et al.	
5,852,775	A	12/1998	Hidary	
5,862,345	A	1/1999	Osawa et al.	
5,882,345	A	3/1999	Yoon	
5,911,120	A	6/1999	Jarett et al.	
5,983,005	A	11/1999	Butterworth et al.	
6,026,289	A	2/2000	Zellner et al.	
6,038,452	A	3/2000	Strawczynski et al.	
6,047,189	A	4/2000	Yun et al.	
6,070,070	A	5/2000	Ladue	
6,081,536	A	6/2000	Gorsuch et al.	
6,097,949	A	8/2000	Jung et al.	
6,104,922	A	8/2000	Baumann	
6,148,198	A	11/2000	Anderson et al.	
6,161,016	A	12/2000	Yarwood	
6,169,894	B1	1/2001	McCormick et al.	
6,175,743	B1	1/2001	Alperovich et al.	
6,219,346	B1	4/2001	Maxemchuk	
6,256,509	B1*	7/2001	Tanaka et al.	455/515
6,314,094	B1*	11/2001	Boys	370/352
6,337,715	B1	1/2002	Inagaki et al.	
6,338,140	B1	1/2002	Owens et al.	
6,351,647	B1	2/2002	Gustafsson	
6,360,076	B1	3/2002	Segura et al.	
6,385,455	B1	5/2002	St. Clair et al.	
6,389,288	B1	5/2002	Kuwahara et al.	
6,397,076	B1	5/2002	Brown et al.	
6,400,942	B1	6/2002	Hansson et al.	
6,408,179	B1	6/2002	Stosz et al.	
6,415,330	B1	7/2002	Okanoue	
6,430,185	B1	8/2002	Kerns et al.	
6,442,258	B1	8/2002	Mashinsky	
6,490,432	B1*	12/2002	Wegener et al.	455/3.05
6,493,331	B1	12/2002	Walton et al.	
6,510,327	B1	1/2003	Jung et al.	
6,600,917	B1*	7/2003	Maupin	455/414.1
6,605,120	B1	8/2003	Fields et al.	
6,611,684	B1	8/2003	Franks	
6,612,932	B2	9/2003	Stern	
6,622,016	B1	9/2003	Sladek et al.	
6,625,442	B1	9/2003	Kojima	
6,631,122	B1	10/2003	Arunachalam et al.	
6,647,257	B2	11/2003	Owensby	
6,650,902	B1	11/2003	Richton	
6,694,641	B1	2/2004	Gill	
6,825,442	B2	11/2004	Schroth	
6,898,423	B2*	5/2005	Motegi et al.	455/414.2
6,907,020	B2	6/2005	Periyalwar et al.	
6,934,527	B1	8/2005	Hamada	
6,968,179	B1*	11/2005	De Vries	455/414.1
6,977,912	B1	12/2005	Porter et al.	
7,003,115	B1*	2/2006	Suzuki et al.	380/270
7,024,464	B1*	4/2006	Lusher et al.	709/219
7,049,971	B2	5/2006	Guillory	
2001/0055379	A1	12/2001	Mamiya et al.	
2001/0056354	A1	12/2001	Feit et al.	
2002/0027894	A1	3/2002	Arrakoski et al.	
2002/0059218	A1	5/2002	August et al.	
2002/0087401	A1	7/2002	Leapman et al.	

FOREIGN PATENT DOCUMENTS

EP	1058465	12/2000
EP	1081606	3/2001
FR	2816143	5/2002
GB	2327571	1/1999
JP	08-111891	4/1996
JP	10-190717	7/1998
JP	10-304449	11/1998
JP	11-032072	2/1999
JP	11-032073	2/1999

JP	11-136720	5/1999
JP	11-243569	9/1999
JP	11-262054	9/1999
JP	2000-004475	1/2000
JP	2000-013864	1/2000
JP	2000-101566	4/2000
JP	2000-138966	5/2000
JP	2000-175250	6/2000
JP	2000-201145	7/2000
JP	2001-510970	8/2001
JP	2002-511670	4/2002
JP	2002-520707	7/2002
WO	9428687	12/1994
WO	9615639	5/1996
WO	9631992	10/1996
WO	9810604	3/1998
WO	9832265	7/1998
WO	99004583	1/1999
WO	9907168	2/1999
WO	99052304	10/1999
WO	9959355	11/1999
WO	9966670	12/1999
WO	00/02389	1/2000
WO	0027080	5/2000
WO	0041359	7/2000
WO	0069163	11/2000
WO	0070898	11/2000
WO	0079734	12/2000

OTHER PUBLICATIONS

Gubbi, R., "Multimedia Streams and Quality of Service in the Next Generation Wireless Home Networks," Mobile Multimedia Communication, 1999. 1999 IEEE International Workshop on San Diego, CA, Nov. 15-17, 1999, Piscataway, NJ, USA, IEEE, p. 232-235.

TSGW1 #3 (99) 200 TSG-RAN Working Group 1 Radio Meeting #3, Eskilstuna, Sweden 22026, Mar. 1999.

International Search Report PCT/US2001/025331, International Search Authority-European Patent Office, Jun. 25, 2002.

International Search Report PCT/US2001/025329, International Search Authority-European Patent Office, Mar. 7, 2002.

International Search Report PCT/US2001/025328, International Search Authority-European Patent Office, Jun. 25, 2002.

International Search Report PCT/US2001/025323, International Search Authority-European Patent Office, Jun. 21, 2002.

International Search Report PCT/US2001/049674, International Search Authority-European Patent Office, Oct. 22, 2002.

International Search Report PCT/US2001/025375, International Search Authority-European Patent Office, Jul. 10, 2002.

International Search Report PCT/US2001/049685, International Search Authority-European Patent Office, Oct. 2, 2002.

International Search Report PCT/US2001/049700, International Search Authority-European Patent Office, Jun. 18, 2003.

International Search Report PCT/US2001/025325, International Search Authority-European Patent Office, Jun. 21, 2002.

International Preliminary Examination Report - PCT/US01/025331, IPEA - European Patent Office, Dec. 10, 2002.

International Preliminary Examination Report - PCT/US01/025329, IPEA - European Patent Office, Nov. 29, 2002.

International Preliminary Examination Report - PCT/US01/025328, IPEA - European Patent Office, Nov. 29, 2002.

International Preliminary Examination Report - PCT/US01/025323, IPEA - European Patent Office, Dec. 5, 2002.

International Preliminary Examination Report - PCT/US01/049674, IPEA - US, Dec. 12, 2003.


International Preliminary Examination Report - PCT/US01/025375, IPEA - European Patent Office, Oct. 25, 2002.

International Preliminary Examination Report - PCT/US01/049685, IPEA - US, Nov. 3, 2003.

International Preliminary Examination Report - PCT/US01/049700, IPEA - US, Nov. 16, 2004.

International Preliminary Examination Report - PCT/US01/025325, IPEA - European Patent Office, Nov. 22, 2002.

* cited by examiner



TO FIG. 1B





FIG. 2
PRIOR ART






FIG. 3




FIG. 4




FIG. 5





FIG. 6

FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13

COMMUNIQUE	TIME	NARROWCAST REGION
A	6AM-10AM DAILY	910
B	6AM-10AM DAILY	922
C	6AM-11PM AS REQUIRED	909
.	.	.
.	.	.
.	.	.
M	3PM-7PM	923
N	6PM-11PM	909
.	.	.
.	.	.

FIG. 14

FIG. 15

**COMMUNIQUE SYSTEM WITH ACTIVE
FEEDBACK FOR CELLULAR
COMMUNICATION NETWORKS**

CROSS REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 09/731,674 filed on Dec. 6, 2000 now U.S. Pat. No. 7,024,200 which is a continuation-in-part of U.S. patent application Ser. No. 09/638,744, titled "Communiqué System for Cellular Communication Networks" and filed on 14 Aug. 2000 now U.S. Pat. No. 6,594,498.

FIELD OF THE INVENTION

This invention relates to cellular communication networks and to a communiqué system that makes use of the bandwidth capacity in existing point-to-point cellular communication networks to provide subscribers with access to a plurality of broadcast and narrowcast based services.

PROBLEM

It is a problem in cellular communication networks that the network topology is exclusively point to point in nature. This paradigm represents the historical view of cellular communications as a wireless equivalent of traditional wire-line telephone communication networks, which serve to interconnect a calling party with a called party. An additional problem in cellular communication networks is that the need to concurrently serve many voice subscribers with the limited bandwidth available in cellular communication networks has prevented the provision of wide bandwidth communication services, such as data, to these subscribers.

The third generation (3G) wireless communication systems, as specified by the ITU/IMT-2000 requirements for cellular communications, represent a step toward solving the above-noted problems. The third generation wireless communication systems support the provision of advanced packet data services. In 3G/IMT-2000 systems, dynamic Internet Protocol address assignment is required in addition to static Internet Protocol (IP) address assignment. With static IP address assignment, the wireless subscriber station's static IP address is fixed and assigned by the home wireless network. When the wireless subscriber station is away from its home wireless network (roaming), a special data communications link (Wireless IP tunnel) needs to be established between the visited wireless network and the home wireless network. In this case, IP packets destined to the wireless subscriber station's IP address of the home wireless network are routed to the home wireless network according to standard IP routing. A Wireless IP tunnel is used in the home wireless network to redirect the IP packets that are destined to the wireless subscriber stations static IP address to the visited wireless network where the roaming wireless subscriber station is located and being served. When a wireless subscriber station moves from one wireless network coverage area to another, Wireless IP mobility binding updates are performed between the wireless subscriber station and its Home Agent (HA) in the home wireless network. Since both the wireless station's IP address and its Home Agent IP address are static or fixed, a shared secret between the wireless subscriber station and the Home Agent can be preprogrammed into the wireless station and its Home Agent so that the Home Agent can authenticate Wireless IP registrations requested by the wireless subscriber station and perform mobility binding updates in a secure manner.

However, even with advances in bandwidth utilization and the provision of packet data services, the cellular communication networks still operate on a point to point paradigm, with the networks being unable to concurrently communicate data to a plurality of subscribers, which is the fundamental concept of broadcast communications, especially in the case of a dynamically changing audience for the broadcasts.

SOLUTION

The above described problems are solved and a technical advance achieved by the communiqué system for cellular communication networks that operates with existing cellular communication networks to provide communiqué communication services to subscribers. The Communiqué can be unidirectional (broadcast) or bidirectional (interactive) in nature and the extent of the Communiqué can be network-wide broadcast or narrowcast, where one or more cells and/or cell sectors are grouped to cover a predetermined geographic area or demographic population or subscriber interest group to transmit information to subscribers who populate the target audience for the narrowcast transmissions. The communiqué system uses active feedback to dynamically adjust the communiqué coverage area and/or communiqué content, using one or more parameters including but not limited to: the number of subscribers in the communiqué coverage area and components thereof, the demographics of the subscribers, the flow of subscribers into & out of existing communiqué coverage area, the usage of communiqué services: free vs subscription vs toll, and the like.

The content of these transmissions can be multi-media in nature and comprising a combination of various forms of media: audio, video, graphics, text, data and the like. The subscriber terminal devices used to communicate with the communiqué system for cellular communication networks are typically full function communication devices that include: WAP enabled cellular telephones, personal digital assistants, Palm Pilots, personal computers, and the like or special communiqué only communication devices that are specific to communiqué reception; or MP3 audio players (essentially a radio receiver or communiqué radio); or an MPEG4 video receiver (communiqué TV); or other such specialized communication device. The subscriber terminal devices can either be mobile wireless communication devices in the traditional mobile subscriber paradigm, or the fixed wireless communication devices in the more recent wireless product offerings. Furthermore, these communiqué communication services can be free services, subscription based services, or toll based services, while the data propagation can be based on push, pull and combinations of push/pull information distribution modes.

BRIEF DESCRIPTION OF THE DRAWING

FIGS. 1A & 1B illustrate in block diagram form the overall architecture of a typical cellular communication network that is equipped with the present communiqué system for cellular communication networks;

FIG. 2 illustrates in flow diagram form the operation of a typical cellular communication system in implementing an idle handoff mode of operation;

FIG. 3 illustrates in block diagram form a typical configuration of the base to end subscriber forward CDMA channel used in cellular communication networks;

FIG. 4 illustrates in block diagram form a typical assignment of cells in a cellular communication network for a unidirectional transmission without subscriber registration

mode of operation of the present communique system for cellular communication networks;

FIG. 5 illustrates in block diagram form a typical configuration of the base to end subscriber forward CDMA channel used in cellular communication networks;

FIG. 6 illustrates in block diagram form a typical assignment of cells in a cellular communication network as an example of the operation of the present communique system for cellular communication networks;

FIG. 7 illustrates in block diagram form a typical assignment of cells in a cellular communication network for a non-interactive bidirectional transmission with subscriber registration mode of operation of the present communique system for cellular communication networks;

FIG. 8 illustrates in block diagram form a typical signaling protocol for a Traffic channel for use in the present communique system for cellular communication networks;

FIGS. 9 & 10 illustrate typical dynamic coverage areas for various types of communique transmissions;

FIG. 11 illustrates in flow diagram form the operation of the Spatial-Temporal Content Manager;

FIG. 12 illustrates a typical program coverage pattern;

FIG. 13 illustrates a typical program stream for a plurality of communication channels;

FIG. 14 illustrates in tabular form a typical definition of a plurality of narrowcasts applicable to the program streams of FIG. 13 as applied to the typical dynamic coverage areas of FIGS. 9 & 10; and

FIG. 15 illustrates in flow diagram form one mode of using subscriber information as active feedback in the operation of the present communique system for cellular communication networks.

DETAILED DESCRIPTION

Existing cellular communication networks are designed with a network topology that is exclusively point to point in nature. This paradigm represents the historical view of cellular communications as a wireless equivalent of traditional wire-line telephone communication networks, which serve to interconnect a calling party with a called party. The need to concurrently serve many voice subscribers with the limited bandwidth available in cellular communication networks has also prevented the provision of wide bandwidth communication services to these subscribers. These existing systems are largely static in their operation, with each cell providing point to point communications to a population of subscribers who reside in or roam into the predefined service area of the cell. There is an absence of a capability to provide a communication service to a subscriber population that comprises a dynamically changing coverage area that spans multiple cells. The dynamic convergence of a plurality of subscribers to constitute a target audience for Communiques is a paradigm that is not addressed by existing cellular communication systems, nor is there any functionality suggested in existing cellular communication systems to deal with providing information relevant to this target audience in a real time manner.

Cellular Communication Network Philosophy

Cellular communication networks as shown in block diagram form in FIGS. 1A & 1B, provide the service of connecting wireless telecommunication customers, each having a wireless subscriber device, to both land-based customers who are served by the common Carrier Public Switched Telephone Network (PSTN) 108 as well as other wireless telecommunication customers. In such a network, all incoming and outgoing

calls are routed through Mobile Telephone Switching Offices (MTSO) 106, each of which is connected to a plurality of cell sites (also termed Base Station Subsystems 131-151) which communicate with wireless subscriber devices 101, 101' located in the area covered by the cell sites. The wireless subscriber devices 101, 101' are served by the cell sites, each of which is located in one cell area of a larger service region. Each cell site in the service region is connected by a group of communication links to the Mobile Telephone Switching Office 106. Each cell site contains a group of radio transmitters and receivers (Base Station Transceiver 132, 142, 143, 152) with each transmitter-receiver pair being connected to one communication link. Each transmitter-receiver pair operates on a pair of radio frequencies to create a communication channel: one frequency to transmit radio signals to the wireless subscriber device and the other frequency to receive radio signals from the wireless subscriber device. The first stage of a cellular communication connection is set up when a transmitter-receiver pair in a cell site 131, operating on a predetermined pair of radio frequencies, is turned on and a wireless subscriber device 101, located in the cell site 131, is tuned to the same pair of radio frequencies to thereby activate a communication channel between the wireless subscriber device 101 and the cell site 131. The second stage of the communication connection is between the communication link connected to this transmitter-receiver pair and the common carrier Public Switched Telephone Network 108. This second stage of the communication connection is set up in the Mobile Telephone Switching Office 106, which is connected to the common carrier Public Switched Telephone Network 108 by incoming and outgoing trunks. The Mobile Telephone Switching Office 106 contains a switching network 106N to switch wireless subscriber voice and/or data signals from the communication link to an incoming or outgoing trunk. The Mobile Telephone Switching Office 106 and associated software typically manages the base station controllers 132, 142, 152 and the Base Station Transceiver Transmit/Receive electronics which serve to implement the wireless radio frequency link to the wireless subscriber devices 101. The Mobile Telephone Switching Office 106, in conjunction with the Home Location Register (HLR) 161 and the Visitor Location Register (VLR) 162, manages subscriber registration, subscriber authentication, and the provision of wireless services such as voice mail, call forwarding, roaming validation and so on. The Mobile Telephone Switching Office Controller 106C also controls the actions of the associated base station controllers 132, 142, 152 by generating and interpreting the control messages that are exchanged with the associated base station controllers 132, 142, 152 over data links that interconnect these subsystems. The base station controllers 132, 142, 152 at each cell site 131-151, in response to control messages from the Mobile Telephone Switching Office 106, control the transmitter-receiver pairs at the cell site 131. The control processes at each cell site also control the tuning of the wireless subscriber devices to the selected radio frequencies. In the case of CDMA, the system also selects the PN code word to enhance isolation of the communications with the wireless subscriber devices.

Each cell in the cellular communication network comprises a predetermined volume of space radially arranged around the cell site transmitting antenna with the region of space roughly approximating a cylindrical volume having predetermined height. Since all of the wireless subscriber devices are installed in ground-based units (such as motor vehicles or handheld units) in traditional cellular communication systems, the antenna radiation pattern of the cell site is aligned to be proximate to the ground and the polarization of

the signals produced by the cell site antenna is vertical in nature. In order to prevent the radio signals in one cell site from interfering with radio signals in an adjacent cell site, the transmitter frequencies for adjacent cell sites are selected to be different so that there is sufficient frequency separation between adjacent transmitter frequencies to avoid overlapping transmissions among adjacent cell sites. In order to reuse the same frequencies, the cellular telecommunication industry has developed a small but finite number of transmitter frequencies and a cell site allocation pattern that ensures that two adjacent cell sites do not operate on the same frequency. When a ground-based wireless subscriber device initiates a call connection, control signals from the local cell site transmitter cause the frequency agile transponder in the ground-based wireless subscriber device to operate at the frequency of operation designated for that particular cell site. As the ground-based wireless subscriber device moves from one cell site to another, the call connection is handed off to the successive cell sites and the frequency agile transponder in the ground-based wireless subscriber device adjusts its frequency of operation to correspond to the frequency of operation of the transmitter located in the cell site in which the ground-based wireless subscriber device is presently operational.

There are numerous technologies that can be used to implement the cellular communication network and these include both digital and analog paradigms, with the digital apparatus representing the more recent of the two technologies. Furthermore, the frequency spectrum is allocated for different cellular communication systems, with the personal communication system (PCS) systems being located in the 1.9 GHz region of the spectrum while traditional cellular systems are located in the 800 MHz region of the spectrum. The access methods used in cellular communication systems include Code Division Multiple Access (CDMA) that uses orthogonal codes to implement communication channels, Time Division Multiple Access (TDMA) which uses time division multiplexing of a frequency to implement communication channels and Frequency Division Multiple Access (FDMA) which uses separate frequencies to implement communication channels, as well as combinations of these technologies. These concepts are well known in the field of cellular communications and various ones of these can be used to implement the ubiquitous wireless subscriber device of the present invention. These technologies are not limitations to the system which is described herein, since a novel system concept is disclosed, not a specific technologically limited implementation of an existing system concept.

The traditional CDMA cellular network architecture is designed to carry a wireless call between a wireless subscriber device and a base station, by simultaneously using multiple base stations or antennas to mitigate the effects of signal fading of various types, including, but not limited to: Raleigh, rician and log-normal. If one cell or one antenna in the CDMA cellular network has a poor signal for a given time frame, another cell or antenna in the CDMA cellular network which had an acceptable signal carries the call. This call management process is called soft or softer hand-off, depending on whether the call is carried between two cells or two antennas at a given cell, respectively.

Cellular Communication Network Architecture

FIG. 1 is the block diagram of the architecture of the present communique system for cellular communication networks **100** and one example of an existing commercial cellular communication network in which it is implemented. In the description of the present communique system for cellular

communication networks, the major entities of the cellular communication network providing communique services to the wireless subscriber device **101** are the Base Station Subsystems **131-151** that are associated with the Mobile Telephone Switching Office **106**. In a typical cellular communications network, there are numerous Mobile Telephone Switching Offices **106**, but for the sake of simplicity only a single Mobile Telephone Switching Office is shown.

The typical implementation of an existing Mobile Telephone Switching Office **106** comprises a Mobile Telephone Switching Office Controller **106C** which executes call processing associated with the Mobile Telephone Switching Office **106**. A switching network **106N** provides the telephone connectivity between Base Station Subsystems **131-151**. Base Station Subsystems **131-151** communicate with wireless subscriber device **101** using Radio Frequency (RF) channels **111** and **112**, respectively. RF channels **111** and **112** convey both command messages as well as digital data, which may represent voice signals being articulated at the wireless subscriber device **101** and the far-end party. With a CDMA system, the wireless subscriber device **101** communicates with at least one Base Station Subsystem **131**. In FIG. 1, the wireless subscriber device **101** is simultaneously communicating with two Base Station Subsystems **131**, **141**, thus constituting a soft handoff. However, a soft handoff is not limited to a maximum of two base stations. Standard EIA/TIA IS-95-B supports a soft handoff with as many as six base stations. When in a soft handoff, the base stations serving a given call must act in concert so that commands issued over RF channels **111** and **112** are consistent with each other. In order to accomplish this consistency, one of the serving base station subsystems may operate as the primary base station subsystem with respect to the other serving base station subsystems. Of course, a wireless subscriber device **101** may communicate with only a single base station subsystem if determined as sufficient by the cellular communication network.

Cellular communication networks provide a plurality of concurrently active communications in the same service area, with the number of concurrently active communication connections exceeding the number of available radio channels. This is accomplished by reusing the channels via the provision of multiple Base Station Subsystems **131-151** in the service area that is served by a single Mobile Telephone Switching Office **106**. The overall service area of a Mobile Telephone Switching Office **106** is divided into a plurality of "cells", each of which includes a Base Station Subsystem **131** and associated radio transmission tower **102**. The radius of the cell is basically the distance from the base station radio transmission tower **102** to the furthest locus at which good reception between the wireless subscriber device **101** and the radio transmission tower **102** can be effected. The entire service area of a Mobile Telephone Switching Office **106** is therefore covered by a plurality of adjacent cells. There is an industry standard cell pattern in which sets of channels are reused. Within a particular cell, the surrounding cells are grouped in a circle around the first cell and the channels used in these surrounding cells differ from the channels used in the particular cell and from each of the other surrounding cells. Thus, the signals emanating from the radio transmission tower in the particular cell do not interfere with the signals emanating from the radio transmission towers located in each of the surrounding cells because they are at different radio frequencies and have different orthogonal coding. However, in the case of soft handoff, the frequencies must be the same for all cells involved in the soft or softer handoff process. In addition, the next closest cell using the transmission fre-

quency of the particular cell is far enough away from this cell that there is a significant disparity in signal power and therefore sufficient signal rejection at the receivers to ensure that there is no signal interference. The shape of the cell is determined by the surrounding terrain and is typically not circular, but skewed by irregularities in the terrain, the effect of buildings and vegetation and other signal attenuators present in the cell area. Thus, the cell pattern is simply conceptual in nature and does not reflect the actual physical extent on the various cells, since the implemented cells are not hexagonal in configuration and do not have precisely delimited boundary edges.

The control channels that are available in this system are used to setup the communication connections between the subscriber stations **101** and the Base Station Subsystem **131**. When a call is initiated, the control channel is used to communicate between the wireless subscriber device **101** involved in the call and the local serving Base Station Subsystem **131**. The control messages locate and identify the wireless subscriber device **101**, determine the dialed number, and identify an available voice/data communication channel consisting of a pair of radio frequencies and orthogonal coding which is selected by the Base Station Subsystem **131** for the communication connection. The radio unit in the wireless subscriber device **101** re-tunes the transmitter-receiver equipment contained therein to use these designated radio frequencies and orthogonal coding. Once the communication connection is established, the control messages are typically transmitted to adjust transmitter power and/or to change the transmission channel when required to handoff this wireless subscriber device **101** to an adjacent cell, when the subscriber moves from the present cell to one of the adjoining cells. The transmitter power of the wireless subscriber device **101** is regulated since the magnitude of the signal received at the Base Station Subsystem **131** is a function of the subscriber station transmitter power and the distance from the Base Station Subsystem **131**. Therefore, by scaling the transmitter power to correspond to the distance from the Base Station Subsystem **131**, the received signal magnitude can be maintained within a predetermined range of values to ensure accurate signal reception without interfering with other transmissions in the cell.

The voice communications between wireless subscriber device **101** and other subscriber stations, such as land line based subscriber station **109**, is effected by routing the communications received from the wireless subscriber device **101** via switching network **106N** and trunks to the Public Switched Telephone Network (PSTN) **108** where the communications are routed to a Local Exchange Carrier **125** that serves land line based subscriber station **109**. There are numerous Mobile Telephone Switching Offices **106** that are connected to the Public Switched Telephone Network (PSTN) **108** to thereby enable subscribers at both land line based subscriber stations and wireless subscriber devices to communicate between selected stations thereof. This architecture represents the present architecture of the wireless and wireline communication networks. The present communication system for cellular communication networks **100** is shown connected to the Public Switched Telephone Network **108**, the Mobile Telephone Switching Offices **106**, as well as a data communication network such as the Internet **107**, although these examples of interconnections are subject to an implementation selected by the purveyor of communicate services and some of these connections can be eliminated as unnecessary for some implementations as described below.

Format of the Forward CDMA Channel

FIG. 3 illustrates in block diagram form a typical configuration of the Base Station Subsystem **131** to wireless subscriber device **101** forward CDMA channel used in cellular

communication networks. The typical Base Station Subsystem **131** to wireless subscriber device **101** forward CDMA channel comprises a predefined bandwidth centered about a selected carrier frequency. The bandwidth of the selected channel as well as the selected carrier frequency is a function of the technical implementation of the Base Station Subsystem **131** of the cellular communication network and is not discussed further herein. The channel is typically divided into a plurality of segments: Pilot **301**, Synchronization (Synch) **302**, Paging **303**, Traffic **304**. The Paging **303** and Traffic **304** segments are further divided into a plurality of channels Ch1-Ch7 and Ch1-Ch55, respectively. Each traffic channel represents a communication space for a selected wireless subscriber device **101**. The plurality of paging channels Ch1-Ch7 are available for the base station subsystem **131** to page a selected wireless subscriber device **101** in well known fashion. In order to segregate these channels, each channel is assigned a selected one of the 64 Walsh codes, from W=0 to W=63. For example, the Pilot channel is assigned a Walsh code of W=0, while the Synch channel is assigned a Walsh code of W=32. The Paging channels Ch1-Ch7 are assigned Walsh codes of W=1-W=7, respectively. The remaining Walsh codes are assigned to the traffic channels CH1-CH55 as shown in FIG. 3. Each Traffic channel consists of data traffic **311** as well as in band signaling **312** transmitted from the base station subsystem **131** to the wireless subscriber device **101**.

Idle Handoff of Wireless Subscriber Devices

FIG. 2 illustrates in flow diagram form the operation of a typical cellular communication system in implementing an idle handoff mode of operation. An idle handoff occurs when a wireless subscriber device **101** has moved from the coverage area of one Base Station Subsystem **131** into the coverage area of another Base Station Subsystem **141** during the Wireless Station Idle State. As shown in FIG. 2, at step **201**, the wireless subscriber device **101** scans for pilot signals for the base stations that serve the coverage area in which the wireless subscriber device **101** is operational. If the wireless subscriber device **101** detects a Pilot channel signal from another base station subsystem **141**, that is sufficiently stronger than that of the present Base Station Subsystem **131**, the wireless subscriber device **101** determines that an idle handoff should occur. Pilot channels are identified by their offsets relative to the zero offset pilot PN sequence and typically are the Walsh Code **0** for each channel. Pilot offsets are grouped by the wireless subscriber device **101** at step **202** into sets describing their status with regard to pilot searching. The following sets of pilot offsets are defined for a wireless subscriber device **101** in the Wireless Station Idle State. Each pilot offset is a member of only one set.

Active Set: The pilot offset of the Forward CDMA Channel whose Paging channel is being monitored.

Neighbor Set: The offsets of the Pilot channels that are likely candidates for idle handoff. The members of the Neighbor Set are specified in the Neighbor List Message, Extended Neighbor List Message, and the General Neighbor List Message.

Remaining Set: The set of all possible pilot offsets. In the process of FIG. 2, the wireless subscriber device **101** at step **203** selects the 3 strongest pilot signals for use in establishing/maintaining the cellular communication connection. In this process, the RAKE receiver in the wireless subscriber device **101** at step **207** continuously looks for the strongest pilot signals to ensure the continuation of the cellular communication connection. The wireless subscriber device **101** at step **204** decodes the pilot signals and locks on to the synch channel of selected forward CDMA channels having the strongest pilot signals.

At step 205, the wireless subscriber device 101 transmits on the Access channel of the end subscriber to base station reverse CDMA channels, corresponding to of the selected forward CDMA channels having the strongest pilot signals, using a random access procedure. Many parameters of the random access procedure are supplied by the Base Station Subsystem 131 in the Access Parameters Message. The entire process of sending one message and receiving (or failing to receive) an acknowledgment for that message is called an access attempt. One access attempt consists of one or more access sub-attempts. Each transmission in the access sub-attempt is called an access probe. Each access probe consists of an Access channel preamble and an Access channel message capsule.

When the wireless subscriber device 101 stops transmitting access probes of an access attempt to one pilot and begins transmitting access probes of an access attempt to another pilot, it is said to perform an access probe handoff. The portion of an access attempt which begins when the wireless subscriber device 101 begins transmitting access probes to one pilot, and ends when the wireless subscriber device 101 either performs an access probe handoff or receives an acknowledgment for that message is called an access sub-attempt. When the access probe handoff is successful, at step 205 the wireless subscriber device 101 switches to idle Traffic channels, one per selected forward CDMA channel and demodulates the signals received therein and at step 206 outputs the demodulated multi-media output to the subscriber interface of the wireless subscriber device 101 for use by the subscriber.

As described herein, the overhead required in point to point cellular communications to manage hand-offs between cells within the cellular communication network is considerable and continuous, since many of the wireless subscriber devices served by the cellular communication network are mobile in nature. In the present communicate system for cellular communication networks, the need for this overhead in processing call hand-offs is reduced since the wireless subscriber device is not provided with a unique communication link, but shares this link with many other wireless subscriber devices. There are a number of communicate implementations that can be overlaid on this standard handoff process.

Within an access sub-attempt, access probes are grouped into access probe sequences. The Access channel used for each access probe sequence is chosen pseudo randomly from among all the Access channels associated with the present Paging channel. If there is only one Access channel associated with the present paging channel, all access probes within an access probe sequence are transmitted on the same Access channel. If there is more than one access channel associated with the present Paging Channel, all access probes within an access probe sequence may be transmitted on the different Access channels associated with the present Paging channel. Each access probe sequence consists of up to $1 + \text{NUM_STEPS}$ access probes. The first access probe of each access probe sequence is transmitted at a specified power level relative to the nominal open loop power level. Each subsequent access probe is transmitted at a power level that is adjusted by the PWR_STEPS plus the mean input power change plus the interference correction change from the previous access probe.

The timing of access probes and access probe sequences is expressed in terms of Access channel slots. The transmission of an access probe begins at the start of an Access channel slot. There are two types of messages sent on the Access channel: a response message (one that is a response to a base station message) or a request message (one that is sent

autonomously by the wireless subscriber device). Different procedures are used for sending a response message and for sending a request message. The timing of the start of each access probe sequence is determined pseudo randomly. Timing between access probes of an access probe sequence is also generated pseudo randomly. After transmitting each access probe, the wireless subscriber device waits a specified period, $\text{TA} = (2 + \text{ACC_TMO}_s)H$ 80 ms, from the end of the slot to receive an acknowledgment from the base station. If an acknowledgment is received, the access attempt ends. If no acknowledgment is received and the wireless subscriber device transmits all access probes within an access probe sequence on the same Access channel associated with the current Paging channel, the next access probe is transmitted after an additional back off delay, RT, from 0 to $1 + \text{PROBE_BKOFF}_s$ slots. If no acknowledgment is received and the wireless subscriber device pseudo randomly selects an Access channel from among all Access channels associated with the current Paging channel, the next access probe is transmitted after an additional back off delay, RT, from 0 to PROBE_BKOFF_s slots. The wireless subscriber device 101 shall not begin a new access attempt until the previous access attempt has ended.

Access Handoff

The wireless subscriber device 101 is permitted to perform an access handoff to use the Paging channel with the best pilot strength and an associated Access channel. The wireless subscriber device 101 is permitted to perform an access handoff when waiting for a response from the Base Station Subsystem 131 or before sending a response to the Base Station Subsystem 131. An access handoff is permitted after an access attempt while the wireless subscriber device 101 is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate. When the wireless subscriber device 101 declares a loss of the Paging channel, the wireless subscriber device 101 shall perform an access handoff while waiting for a response from the Base Station Subsystem 131 in the System Access State if the wireless subscriber device 101 is not performing an access attempt and all of the following conditions hold:

The new base station is in the list ACCESS_HO_LIST, ACCESS_HOs is equal to $>1=$, and

The wireless subscriber device is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate.

When the wireless subscriber device 101 declares a loss of the Paging channel, the wireless subscriber device 101 shall perform an access handoff after receiving a message and before responding to that message while in the System Access State if the wireless subscriber device 101 is not performing an access attempt and all of the following conditions hold:

The new base station is in the list ACCESS_HO_LIST, ACCESS_HOs is equal to $>1=$, ACCESS_HO_MSG_RSPs is equal to $>1=$, and

The wireless subscriber device is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate.

When the wireless subscriber device 101 declares an insufficiency of the Paging channel, the wireless subscriber device 101 may perform an access handoff while waiting for a response from the Base Station Subsystem 131 in the System Access State if the wireless subscriber device 101 is not performing an access attempt and all of the following conditions hold:

The new base station is in the list ACCESS_HO_LIST, ACCESS_HOs is equal to $>1=$, and

The wireless subscriber device is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate.

When the wireless subscriber device **101** declares an insufficiency of the Paging channel, the wireless subscriber device **101** may perform an access handoff after receiving a message and before responding to that message while in the System Access State if the wireless subscriber device **101** is not performing an access attempt and all of the following conditions hold:

The new base station is in the list ACCESS_HO_LIST, ACCESS_HOs is equal to $>1=$, ACCESS_HO_MSG_RSPs is equal to $>1=$, and

The wireless subscriber device is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate.

Before the wireless subscriber device **101** transmits an access probe to the new Base Station Subsystem **141**, the wireless subscriber device **101** shall update the parameters based on the System Parameters Message, the Access Parameters Message and the Extended System Parameters Message on the associated new Paging channel and process the parameters from the messages. The wireless subscriber device **101** shall update the parameters based on the Neighbor List Message, Extended Neighbor List Message or the General Neighbor List Message on the associated new Paging channel and process the parameters from the message. If the wireless subscriber device **101** receives a Global Service Redirection Message which directs the wireless subscriber device **101** away from the new Base Station Subsystem **141**, the wireless subscriber device **101** shall not access the new Base Station Subsystem **141**. The wireless subscriber device **101** shall process these messages only once after each access handoff. If ACCESS_PROBE_HO_s is equal to $>0=$ and ACCESS_HO_s is equal to $>1=$, the wireless station may monitor other Paging Channels which are in ACCESS_HO_LIST for T_{42m} seconds after the wireless subscriber device **101** declares a loss of the original Paging channel during an access attempt.

Access Probe Handoff

The wireless subscriber device **101** is permitted to perform an access probe handoff when the wireless subscriber device **101** is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate. The wireless subscriber device **101** may perform an access probe handoff during an access attempt to a pilot in ACCESS_HO_LIST when the message being sent is the Origination Message or the Page Response Message if all of the following conditions hold:

ACCESS_PROBE_HOs is equal to $>1=$,

The wireless subscriber device is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate, and

The wireless subscriber device has performed fewer than $(MAX_NUM_PROBE_HOs + 1)$ access probe hand-offs during the current access attempt.

The wireless subscriber device **101** may also perform an access probe handoff during an access attempt to a pilot in ACCESS_HO_LIST when the message being sent is a message other than the Origination Message or the Page Response Message if all of the preceding conditions hold and ACC_PROBE_HO_OTHER_MSGs is equal to $>1=$. The wireless subscriber device **101** may also perform an access probe handoff during an access attempt to a pilot not in ACCESS_HO_LIST when the message being sent is the Origination Message or the Page Response Message if all of the following conditions hold:

ACC_HO_LIST_UPDs is equal to $>1=$,

ACCESS_PROBE_HOs is equal to $>1=$,

The new pilot is stronger than any pilot in ACCESS_HO_LIST,

The new pilot has the corresponding ACCESS_HO_ALLOWED field in the NGHBR_REC equal to $>1=$,

Inclusion of the new pilot in ACCESS_HO_LIST does not cause the Access channel message to exceed the maximum capsule size,

Inclusion of the new pilot in ACCESS_HO_LIST does not cause the number of members to exceed N_{13m} ,

The wireless subscriber device is in the Page Response Substrate or the Wireless Station Origination Attempt Substrate, and

The wireless subscriber device has performed fewer than $(MAX_NUM_PROBE_HOs + 1)$ access probe handoffs during the current access attempt.

The wireless subscriber device **101** may also perform an access probe handoff during an access attempt to a pilot in ACCESS_HO_LIST when the message being sent is a message other than the Origination Message or the Page Response Message if all of the preceding conditions hold and ACC_PROBE_HO_OTHER_MSGs is equal to $>1=$. If the above conditions are met, the wireless subscriber device **101** may perform an access probe handoff when the wireless subscriber device **101** declares a loss of the Paging channel; the wireless subscriber device **101** may also perform an access probe handoff after the TA timer expires and the wireless subscriber device **101** declares an insufficiency of the Paging channel.

Before the wireless subscriber device **101** transmits an access probe to the new base station **104**, the wireless subscriber device **101** shall update the parameters based on the System Parameters Message, the Access Parameters Message and the Extended System Parameters Message on the associated new Paging channel and process the parameters from the message. The wireless subscriber device **101** shall update the parameters based on the Neighbor List Message, Extended Neighbor List Message, or the General Neighbor List Message on the associated new Paging channel and process the parameters from the message. If the wireless subscriber device **101** receives a Global Service Redirection Message which directs the wireless subscriber device **101** away from the new Base Station Subsystem **141**, the wireless subscriber device **101** shall not access the New Base Station Subsystem **141**. The wireless subscriber device **101** shall process these messages only once per access sub-attempt during an access attempt.

If the wireless subscriber device **101** performs an access probe handoff, the wireless subscriber device **101** shall restart the access attempt probe sequence number on the new pilot, starting with the first probe of the first probe sequence of the access sub-attempt. The wireless subscriber device **101** shall not reset its access probe handoff count until the access attempt ends. The wireless subscriber device **101** shall abort the access attempt if the length of the message to be sent exceeds MAX_CAP_SIZE of the new base station. The wireless subscriber device **101** may monitor other Paging channels which are in ACCESS_HO_LIST for T_{42m} seconds.

Philosophy of the Communique System

The terms "cell site" and "cell" are sometimes loosely used in the literature, and the term "cell site" generally denotes the locus, such as Base Station Subsystem **131**, at which the radio frequency transmitter and receiver apparatus (Base Station Transceiver **133**, **143**, **144**, **153**) is located, while the term "cell" generally denotes the region of space which is served by a particular radio frequency transmitter-receiver pair which is installed in Base Station Transceiver **133** at Base Station Subsystem **131**, and includes sectors of a particular cell where the cell comprises a plurality of sectors. The par-

particular technology used to implement the communications between wireless subscriber devices and the radio frequency transmitter-receiver pairs as well as the nature of the data transferred there between, be it voice, video, telemetry, computer data, and the like, are not limitations to the communicate system for cellular communication networks **100** which is described herein, since a novel system concept is disclosed, not a specific technologically limited implementation of an existing system concept. Therefore, the term “cellular” as it is used herein denotes a communication system which operates on the basis of dividing space into a plurality of volumetric sections or cells, and managing communications between wireless subscriber devices located in the cells and the associated radio frequency transmitter-receiver pairs located at the cell site for each of these cells. In addition, the term “telecommunications cell” is used in the general sense and includes a traditional cell generated by a cell site as well as a sector of a cell, as well as a cell elevation sector, regardless of size and shape. The wireless subscriber device, as noted above, can be any of a number of full function communication devices that include: WAP enabled cellular telephones, personal digital assistants, Palm Pilots, personal computers, and the like or special communicate only communication devices that are specific to communicate reception; or MP3 audio players (essentially a radio receiver or communicate radio); or an MPEG4 video receiver (communicate TV); or other such specialized communication device. The subscriber terminal devices can either be mobile wireless communication devices in the traditional mobile subscriber paradigm, or the fixed wireless communication devices in the more recent wireless product offerings.

The communicate system for cellular communication networks operates with existing cellular communication networks, as described above, to provide other than strictly point to point communication services, which are collectively termed “communicate services” herein, to subscribers. The Communicate can be unidirectional (broadcast) or bidirectional (interactive) in nature and the extent of the Communicate can be network-wide or narrowcast, where one or more cells and/or cell sectors are grouped to cover a predetermined geographic area or demographic population or subscriber interest group to transmit information to subscribers who populate the target audience for the narrowcast transmissions. For instance, the coverage region can be implemented in the radio frequency domain by using frequency assignments, code assignments or dynamically shaped antenna patterns. Pattern shaping is done now to manage capacity constraint issues (e.g. a cell size would be shaped/shrunk at busy hour with adjacent cells helping to carry a particular region’s traffic). The communicate system for cellular communication networks can use pattern shaping to create a narrowcast region for instance.

The communicate system for cellular communication networks creates broadcast and/or narrowcast regions in a “virtual” manner. With this concept, the RF configuration is separable, in that it can be static in its architecture or it could be configured as described above in a dynamic manner. The “virtual” architecture is achieved in the content domain—a very powerful and flexible concept. By selectively enabling and disabling specific content on a cell-by-cell basis, a shaped broadcast or narrowcast can be realized from the end-subscriber’s perspective even though the RF configuration may have remained static or unchanged. This is a powerful narrowcast tool since it is relatively simple to dynamically change the specific content being transmitted at a given cell. The combinatorial effect is spatial and temporal in its extent even though the RF architecture may have been unchanged.

The methods available to achieve this effect are similar to the zip code advertising systems used in cable TV transmissions wherein regional servers select, parse and reassemble content for a particular geographic region. The content management can also be done on a centralized basis.

The basic functionality of the communicate system for cellular communication networks **100** comprises an information distribution management functionality that concurrently propagates information to a plurality of wireless subscriber devices, using push, pull and combinations of push/pull data propagation modes. The need for information dissemination is identified: in response to external events, in response to predetermined temporal/spatial stimuli; as a function of subscriber inquiries/requests; and the like. The communicate system for cellular communication networks **100**, in response to an identified information dissemination event, identifies a plurality of cells in the cellular communication network as well as available communication channels in each of these cells to carry the information that is to be transmitted to a plurality of wireless subscriber devices extant in the locales served by the selected cells. The communication channels can be dedicated to communicate services or can be selected from the pool of available communication channels. The subscribers access the Communicates by selecting the communication channel on their wireless subscriber device that carries the Communicate. The subscriber can be alerted to the presence of the Communicate in many ways or can activate their wireless subscriber device to retrieve the Communicate absent any alert being transmitted to the wireless subscriber device. The Communicate retrieved by the subscriber is not subscriber-unique, in that the Communicate is transmitted to many subscribers, with a plurality of subscribers concurrently accessing the Communicate being a typical mode of operation. In addition, the bandwidth required for communicate services can be variable, with unused channels of the existing cellular communication network being allocated on an as needed basis to communicate services. Furthermore, the routine point to point cellular communication traffic can be load balanced with the communicate services, with routine cellular traffic being preferentially served by cells that have unused capacity to thereby free up channels in other cells for communicate services. In addition, the communicate system for cellular communication networks **100** identifies the appropriate source of information available from a program source which is to be used to constitute the communicate service. The information can be a predetermined continuous feed, or can be comprised of a plurality of segments which can be interspersed with advertisements, other information segments and the like.

Communicate Services in Cellular Communication Networks

As can be seen from the above description, the wireless subscriber device **101** listens for the strongest pilot signal in one of the available communication channels and uses this pilot signal to derive a time/frequency reference. The wireless subscriber device **101** then demodulates the synch signal for this communication channel to precisely align the clock of the wireless subscriber device **101** with that contained in the Base Station Subsystem **131**. For a broadcast mode of operation, the wireless subscriber device **101** must be given information that identifies which PN codes are broadcast/narrowcast signals for this communication channel. This can be accomplished by transmitting directory information to the wireless subscriber device **101** in the pilot or synch signals or by using a predefined PN code for selected broadcast signals.

Since the cellular communication network continuously transmits the Communicate signals from various cell sites,

there is no statistical reduction of self interference. Therefore, proper selection of frequencies for transmission and PN codes are necessary to reduce interference. Each PN code space can contain either a single transmission or can be used in a multiplex mode where multiple signals are transmitted. In the latter mode, time slotted baseband data is streamed on a single CDMA waveform by the creation of multiple subchannels in each frame of the transmission. In this manner, lower data rate signals can share a single transmission.

The Mobile Telephone Switching Office **106**, in conjunction with the VLR and HLR, helps to manage the registration process which includes subscriber authorization. The Visitor Location Register **161** and the Home Location Register **162** are essentially sophisticated databases that are hooked to the Mobile Telephone Switching Office **106**. The VLR and HLR are sometimes the same device with logical functional partitions although VLRs can stand alone and be distributed in their deployment while HLRs are typically more centralized. The Communicate Location Register (CLR) **163**, is the apparatus in the communicate system for cellular communication networks **100** where all of the systems information for subscribers' authorization and service plans reside, as well as (optionally) the subscriber profiles for the subscribers where these profiles include information concerning the subscriber's Communicate service preferences above the information contained in the subscriber's service plans. This has substantial merit in terms of practical implementation since it can be a wholly separate device that connects to the Mobile Telephone Switching Office **106** or as an integral part of the communicate system for cellular communication networks **100**. The Communicate Location Register **163** is attached to the Mobile Telephone Switching Office **106** in a manner similar to the HLR/VLR.

In order to describe the various services that are available from the communicate system for cellular communication networks **100**, the terms used to describe the processes operational in the recognition of a subscriber and provision of service to a subscriber must be defined. "Acquisition" is the process where the wireless subscriber device scans for pilots, locks onto synch channels and has all system based knowledge necessary to know where and how to receive Communicates. "Registration" is the process that entails the interchange of information between the wireless subscriber device and the cellular communication network wherein the cellular communication network becomes aware of and knows which subscribers are receiving Communicates and where they are receiving them. "Authorization" is the process where the communicate system for cellular communication networks **100** grants end-subscriber access to broadcast or narrowcast content to one or many subscribers in a general or specific location. Thus, a "free" communicate service has the ACQUISITION process but does not have REGISTRATION or AUTHORIZATION processes. "Subscription" communicate services have all three processes. "Pre-pay" communicate services have a modified ACQUISITION process but do not include REGISTRATION or AUTHORIZATION processes. Therefore, the term "autonomous" can be used to describe the "free" broadcast architecture, since the cellular communication network does not know who is listening or where they are listening. This is the equivalent of today's broadcast radio and TV with the exception that the content can be specialized into "free" narrowcasts that have a limited spatial extent which can be dynamically managed. The wireless subscriber device used for such a communicate service can be a one-way receive only (ultra-low cost) wireless subscriber device. For a communicate service that includes free broadcasts and subscription services, the wireless subscriber device is not content interactive, meaning communicate services such as request-reply are not available. The wireless subscriber device is two-way in terms of its communication capability

with the network for registration and authorization purposes. A Pre-pay Subscription communicate service is conceptually similar to the digital TV recorders that have a one-time-only pre-pay subscription fee. This concept uses a modified forward paging channel to provide initialization information for traffic channels and then uses in-band signaling on the forward traffic channel to convey systems information.

Unidirectional Transmission Without Subscriber Registration

There are numerous possible architectures that can be used to transmit information to the wireless subscriber devices with the architecture selected having an impact on the types of transmissions.

FIG. 4 illustrates in block diagram form a typical assignment of cells in a cellular communication network for a unidirectional transmission without subscriber registration mode of operation of the present communicate system for cellular communication networks **100**, where a plurality of cells are transmitting communicate signals, with each cell using the same frequency and optionally the same Walsh (PN) code for a selected Communicate. There is a K=3 cell repeat pattern, although alternatively, the cells can be subdivided into three sectors for the same effect. In this manner, the wireless subscriber device **101** does not have to search for the desired Communicate, since the location is uniform throughout the cellular communication network. The wireless subscriber device **101** is always in soft handoff mode and in the example of FIG. 4, the PN code varies by cell according to the K=3 repeat pattern, so the wireless subscriber device **101** maintains a soft handoff mode with the three PN codes, regardless of the location of the wireless subscriber device **101** in the cellular communication network. Existing wireless subscriber devices are equipped with three receivers in the rake receiver system which enables operation in this mode.

Alternatively, adjacent cells (or cell sectors) can transmit the Communicate signals on different frequencies, but this requires additional complexity in the wireless subscriber device, since the handoff must occur with both frequency and PN code making it a hard handoff. In addition, the lack of uniformity in the transmission frequency requires the wireless subscriber device to receive information from the base station to identify the location of the desired Communicate in order to enable the wireless subscriber device to lock on to the appropriate combination of frequency and PN code for each cell. One way of avoiding the complexity is illustrated in FIG. 6 where there is a grouping of K=3 for the cells and the Walsh code assignment is static, using a specific Walsh code for each of the K=3 cells, such as Traffic channel **8** (Walsh code W=8) for the cell K=1 and Traffic channel Ch9 (Walsh code W=9) for the cell K=2 and Traffic channel Ch10 (Walsh code W=10) for cell K=3. Therefore, the subscriber does not need additional information from the cellular communication network to receive the broadcast information, since the wireless subscriber device **101** has 3 RAKE receivers, which can each be locked on to one of the three Walsh codes W=8-W=10 used in the K=3 repeat scenario. The wireless subscriber device **101** can always be in a soft handoff mode to ensure that continual reception of the transmission takes place as the wireless subscriber device **101** receives signals from the three predetermined Traffic channels.

Non-interactive Bidirectional Transmission With Subscriber Registration

FIG. 7 illustrates in block diagram form a typical assignment of cells in a cellular communication network for a non-interactive bidirectional transmission with subscriber registration mode of operation of the present communicate system for cellular communication networks **100**, where a plurality of cells are transmitting Communicate signals, with each cell using any frequency and any Walsh (PN) code for a

selected Communique. This mode of operation enables the cellular communication system to select any repeat pattern of cells, any assignment of Walsh codes for a transmission to thereby enable communique services. The wireless subscriber device **101** communicates with the Base Station Subsystem **131** for channel assignment spoofed registration purposes to receive free communique services, but does not enter an interactive mode once registration is accomplished. Thus, the wireless subscriber device **101** does not require a unique MIN for this free communique services mode of operation, since billing or authorization are not required.

However, for subscription services, as shown in FIG. 7, at step **701**, the wireless subscriber device **101** scans for pilot signals from the Base Station Subsystems that serve the coverage area in which the wireless subscriber device **101** is operational. If the wireless subscriber device **101** detects a Pilot Channel signal from another Base Station Subsystem **141**, that is sufficiently stronger than that of the present Base Station Subsystem **131**, the wireless subscriber device **101** determines that an idle handoff should occur. Pilot Channels are identified by their offsets relative to the zero offset pilot PN sequence and typically are the Walsh Code **0** for each channel. Pilot offsets are grouped by the wireless subscriber device **101** at step **702** into sets describing their status with regard to pilot searching. The wireless subscriber device **101** at step **703** selects the 3 strongest pilot signals for use in establishing/maintaining the cellular communication connection. In this process, the RAKE receiver in the wireless subscriber device **101** at step **710** continuously looks for the strongest pilot signals to ensure the continuation of the cellular communication connection. The wireless subscriber device **101** at step **704** decodes the pilot signals and locks on to the synch channel of the 3 selected forward CDMA channels having the strongest pilot signals.

At step **705**, the wireless subscriber device **101** registers with the Base Station Subsystem **131** using their unique ESN and SSD, but a common MIN that is used for communique purposes to spoof the base station subsystem **131** into recognizing the wireless subscriber device **101** without requiring a unique identity for the wireless subscriber device **101**. In addition, the fraud prevention system (software) in the Mobile Telephone Switching Office **106** is disabled for Communiques since the fraud system rejects multiple simultaneous MINs at different geographic locations. This feature is designed to prevent cloning fraud (more of an artifact for analog versus digital) although multi-MIN fraud detection is used in digital systems as well. The Base Station Subsystem **131** verifies the authorization of this wireless subscriber device **101** to receive the requested service, identifies the inbound call to the wireless subscriber device **101** (shared by potentially many wireless subscriber devices) at step **706** via the Paging channel used by the wireless subscriber device **101** to request this service and, in response to control signals received by the wireless subscriber device **101** from the Base Station Subsystem **131**, the wireless subscriber device **101** at step **707** changes to the identified traffic channel that carries the selected Communique. The wireless subscriber device **101** at step **709** remains in a soft handoff mode to ensure uninterrupted reception of the Communique and also at step **708** outputs the received multi-media data to the subscriber.

In this scenario, the issue of "push/pull" transmissions was not mentioned. The subscriber at wireless subscriber device **101** can receive "push" data transmissions from a source which are directed to all subscribers of this service by the base station flood paging the MIN associated with this Communique. Thus, the wireless subscriber device **101** would potentially have multiple MINs, with one for point to point tradi-

tional cellular communications and one for each of the communique services to which the subscriber enrolls. Thus, when the wireless subscriber device **101** is active in the service area, the flood page of one of the subscriber's MINs on the paging channel alerts the subscriber of the presence of a Communique transmission. The subscriber can activate wireless subscriber device **101** to receive this transmission or can reject the transmission by operating appropriate buttons on the wireless subscriber device **101**. The reverse path on this communique channel is disabled, since there are many subscribers simultaneously registering for the Communique.

The Mobile Telephone Switching Office **106**, Base Station Controller (BSC) **132**, **142**, **152** and Base Station Transceiver (BST) **133**, **143**, **144**, **153** need appropriate software and control revisions to not alarm or error when no reverse path transmission on the traffic channel is received from the communique device (mobile or fixed). For the provision of subscription or toll services via the non-interactive bidirectional transmission with subscriber registration mode of operation of the present communique system for cellular communication networks **100**, a plurality of cells transmit Communique signals, with each cell using any frequency and any Walsh (PN) code for a selected Communique. This mode of operation enables the cellular communication system to select any repeat pattern of cells, any assignment of Walsh codes for a transmission to thereby enable not only free communique services but also subscription services. The wireless subscriber device **101** communicates with the base station **102** for registration purposes, but does not enter an interactive mode once registration is accomplished. Thus, the wireless subscriber device **101** does not require a unique MIN for this mode of operation, since the subscription billing and authorization can be implemented using the ESN and/or SSD of the wireless subscriber device **101**.

The difference with this process compared to that of FIG. 7 is that the registration process of step **705** consists of the wireless subscriber device **101** transmitting the spoofing MIN as well as the SSD and/or ESN to the Base Station Subsystem **131** in a brief data exchange on the reverse CDMA paging channel to log the subscriber in to the selected subscription or toll services. The forward page to the wireless subscriber device **101** can include the Traffic channel identification of the subscribed services and the wireless subscriber device **101** responds on the reverse CDMA channel with the subscriber registration information. Much of the communications to effect soft handoff and registration can be carried in-band on the reverse CDMA channel.

Content Delivery

The content of the Communiques can vary widely and include but are not limited to: free information, subscription based information, toll based information, and the like, as noted above. The content can be locally generated or remotely generated, with the propagation of the information to the various cell sites being implemented in a number of ways. FIGS. **1A** & **1B** illustrate in block diagram form the overall architecture of a typical content delivery network for the present communique system for cellular communication networks **100**. In particular, there is a Program Manager **113** that functions to receive the program source information from multiple sources and migrate information to selected cell sites for transmission to the subscribers served by these cell sites. The Spatial-Temporal Content Manager **114** defines the geographic area or demographic population or subscriber interest group that are the metrics used to transmit information to subscribers who populate the target audience for narrowcast transmissions. The Spatial-Temporal Content Manager **114**

also can include the selection of frequencies and PN codes that are used by each cell site to transmit the Communiques to subscribers. The basic content delivery network is independent of the existing radio frequency cellular communication network, but is cooperatively operative with the cellular communication network. Thus, it is expected that part of the functionality described herein for the content delivery network can be part of or integrated with the cellular communication network, as a matter of expediency. The degree to which the content delivery network is incorporated into the cellular communication network or even into the communicate system for cellular communication networks **100** varies and does not diminish the applicability of the concepts embodied in the communicate system for cellular communication networks **100**.

As shown in block diagram form in FIGS. **1A** & **1B**, the sources of data for the communicate system for cellular communication networks **100** can be varied, and a few typical content sources are shown here to illustrate the concepts of the communicate system for cellular communication networks **100**. In particular, the communicate system for cellular communication networks **100** is connected to a plurality of content sources. The sources can be a remotely located program source for providing for example network news, such as a national network station **122** which is connected via a satellite uplink **123** and satellite **124** to a satellite downlink **126** and forwarded to satellite interface **117** that is part of the communicate system for cellular communication networks **100** or can use the Public Switched Telephone Network and trunk interface **116B**. Alternatively, the program source can be a local program source **120** for local news and information, that is connected via a data communication medium, such as the Internet **107**, to an Internet server interface **115** of the communicate system for cellular communication networks **100**. In addition, a program source, such as local program source **121** is connected via the Public Switched Telephone Network **108** to a trunk interface **116A** of the communicate system for cellular communication networks **100**. In addition, a local terminal device **127** can be connected via interface **110** to the communicate system for cellular communication networks **100** for inputting information. The various program sources provide information of various types, including but not limited to: news, advertisements, traffic, weather, travel information, and the like.

The communicate system for cellular communication networks **100** also includes a local mass storage memory **119** for storing control instructions for use by processor **118** as well as program material received from the various program sources identified above. The communicate system for cellular communication networks **100** is controlled by a processor complex which includes Spatial-Temporal Content Manager **114** to manage the definition of the cells to which a particular Communique is transmitted. Furthermore, communicate system for cellular communication networks **100** includes Program Manager **113** to integrate information received from the various program sources into Communiques that are transmitted over selected Traffic channels of the forward CDMA channel within one or more cells as identified by the Spatial-Temporal Content Manager **114**. The Communiques generated by the Program Manager **113** are transmitted to the various Base Station Subsystems **131-151** identified by the Spatial-Temporal Content Manager **114** either directly or via the associated Mobile Telephone Switching Office **106**. The Program Manager **113** functions to assemble program streams as described below and transmits the program streams containing the Communiques via a selected communication medium, such as the Public Switched Telephone

Network **108**, using network interface **116A**, or some other communication medium, such as an IP network.

Content Domain Narrowcast

An alternative to the use of centralized, predetermined Communiques that are formatted at the communicate system for cellular communication networks **100** and transmitted via the Base Station Subsystems **132, 142, 152** to the wireless subscriber devices, the delivery of information can be effected by using the content domain as a distribution format. The content domain enables the communicate system for cellular communication networks **100** to achieve a dynamic, changeable broadcast/narrowcast without modifying or reconfiguring the RF network domain. In particular, a broadband program stream containing all information for all cells can be created by the Spatial-Temporal Content Manager **114**. This information, such as that described below with respect to FIG. **8**, is delivered to the Mobile Telephone Switching Office **106** for distribution to all relevant Base Station Subsystems **132, 142, 152**. The Base Station Subsystems **132, 142, 152** can either parse the information contained in the frame into a plurality of Communiques for transmission in their cells, such as the plurality of cells included in coverage areas A-C shown on FIG. **12**. Alternatively, the information can be passed directly to the wireless subscriber devices for parsing therein. However, it is expected that the bandwidth limitations in the communication link from the Base Station Subsystems **132, 142, 152** to the wireless subscriber devices render the former parsing scheme preferable to parsing at the wireless subscriber device. Yet another alternative is the hierarchical parsing of the information, where the Base Station Subsystems **132, 142, 152** parse the received information frame into a plurality of subframes of similar format and reduced content for transmission to the wireless subscriber devices for further parsing of the subframes into the individual Communiques. The process utilizes the available bandwidth to provide the wireless subscriber devices with the information necessary to produce a number of Communiques, thereby eliminating the need for the Base Station Subsystems **132, 142, 152** to communicate with the wireless subscriber devices to switch channels to access other Communiques. This distributed switching and hierarchical information delivery architecture thereby reduces the Paging channel traffic for the Base Station Subsystems **132, 142, 152**.

The Spatial-Temporal Content Manager **114** controls the actual information that is transmitted from each cell site by sending program stream parsing control signals to routers contained in the Base Station Controllers **132, 142, 152** at each cell site which then, on a distributed basis, re-assemble the broadband program stream containing all information for all cells into a data stream that is only relevant for that particular cell. By grouping cells as shown on FIG. **12** into "content similar blocks" or more specifically coverage areas A-C, the Spatial-Temporal Content Manager **114** has commanded the routers at the cell sites to parse the broadband program stream identically for the grouped cells (as predefined by the systems programming or a content programming operator), the effect of a narrowcast can be achieved without modifying the RF network architecture. From the subscriber's perspective, the subscriber is only receiving narrowcast information when in the grouped cells' transmission range. And, as the subscriber moves from one region to another, the broadcast/narrowcast Communique received may be different depending on the spatial programming of the

Spatial-Temporal Content Manager **114**. Also, overtime, a given narrowcast region may change in its physical shape or disappear altogether.

The operation of this Spatial-Temporal Content Manager **114** is illustrated in flow diagram form in FIG. **11** where at step **1101** each cell in the cellular communication network the is served by the communicate system for cellular communication networks **100** is assigned a unique address, using a selected protocol, such as TCP/IP. At step **1102**, the cells are grouped into collections comprising coverage areas. The program in the form of Communicates are selected at step **1103** and assigned to destinations, using the cell addresses assigned at step **1101**. At step **1104**, the Communicate schedule is defined in terms of time of transmission, duration of transmission, duration of narrowcast region, temporal and/or spatial characteristics of narrowcast region, and the like. Finally, at step **1105**, the identified Communicates are transmitted to the selected cells using the assigned cell addresses. The transmission can occur on a real time basis where the Communicates are provided to the cells at the time they are to be broadcast, or the Communicates can be distributed in advance of transmission and stored for future transmission. The process of FIG. **11** then returns to either step **1101** where address information is updated as needed or step **1102** where the cell groupings are modified and the process cycles through the above-noted steps as required.

One disadvantage of this particular distributed re-assembly approach is with a CDMA architecture designed to operate in soft or softer handoff (this limitation is not present in an analog or TDMA architecture since they do not operate in soft handoff). Since the data streams must be identical for the wireless subscriber device to operate in soft handoff, as a subscriber transitions form the boundary of one narrowcast region to another, the number of cell sites available to be in soft handoff is varying and could be zero. One method for solving this limited shortcoming is to broadcast the broadband content stream from all sites all the time and put the router function within the wireless subscriber device itself. Commands on how to re-assemble the content is based on an subscriber's physical location and the signaling is done on an in-band basis (i.e. the data parsing commands are contained within the traffic channel in a TDM fashion). This reduces the effective available bandwidth for a narrowcast since much of the broadband content is not for a given subscriber and is Athrown away by a given subscriber. It also places higher computing power at the wireless subscriber device in order to parse the data. Again, if soft handoff isn't required for reliable CDMA operation, the aforementioned limitation isn't a concern and parsing can be done at the cell site. And, in either parsing scheme, distributed at the cell site or distributed at the wireless subscriber device, if the content is overlaid on an analog or TDMA network, the soft handoff limitation is not an issue.

Management of Spatial-Temporal Control of Distributed Content

Conceptually, the programming of the broadcast/narrowcast regions for management by the Program Manager **113** is done initially by content operators (people) who pre-program the system for content distribution. As a general principle, the content can be classified into groups such as:

Diurnal Narrowcasts	(e.g. AM/PM traffic reports along highways)
Special Narrowcasts	(e.g. football game, art-in-the-park)
Campuses	(e.g. schools, work complexes)
General	(e.g. news weather sports)
Other	

Much of the programming is repetitive and only needs to done once i.e. a diurnal narrowcast. One-time only events can be programmed in advance, and say for a football game, can retain all of the programming features such as it's spatial coverage extent, and only need to be recalled and given a new narrowcast execution time window. From a subscriber interface perspective, imagine a GUI that displays all of the cells available for a broadcast/narrowcast wherein an operator can select given cells to form a narrowcast region. This region is then saved as a narrowcast group. Next, the operator goes to another GUI screen that contains all available broadcast information and selects which content files are appropriate for the narrowcast group just previously designed. Last, the operator defines the time window for the narrowcast. By repeating this process and building a database of spatial, temporal and content information, all requisite knowledge is programmed into the system for a 24 hour 7 day operation in the Spatial-Temporal Content Manager.

The database, at a minimum, has the following fields:

Start Time
 Stop Time
 Narrowcast Cell Grouping
 Broadcast Cell Grouping
 Narrowcast Content Stream
 Broadcast Content Stream
 Other

Communicate Content Selection via Subscriber Profiles

FIG. **15** illustrates in flow diagram form one mode of using subscriber information as active feedback in the operation of the present communicate system for cellular communication networks. The communicate system for cellular communication networks **100** can dynamically and automatically manage both the content of the narrowcasts and the scope of coverage of the narrowcasts by use of subscriber information.

This is accomplished where the communicate system for cellular communication networks **100** at step **1501** automatically accesses the subscriber's authorization and service plans, as well as (optionally) the subscriber profiles for the subscribers, which for simplicity are termed "subscriber information" herein, for each subscriber in a given cell, which subscriber profile describes the subscriber's interest level, and/or subscription to various types of programs. This subscriber information, as noted above, can be stored, for example, as part of the subscriber-specific record in the Communicate Location Register **163**.

The Spatial-Temporal Content Manager **114** of the communicate system for cellular communication networks **100** retrieves from its memory and/or retrieves from another source, such as the program source, one or more pieces of information about each program at step **1502**. These pieces of information are termed "attributes" which can be data in any form and format, which can also be decomposed into a numeric measure, which numeric measure is associated with a content parameter. This means that any set of attributes can be replaced by a set of numeric measures, and hence any profile can be represented as a vector of numbers denoting the values of these numeric measures for each content parameter. In this manner, the program is numerically quantified based upon a number of predetermined parameters or program characteristics. Relevance feedback can also be used herein as part of the subscriber information, since it determines the subscriber's interest in certain programs: namely, the programs that the subscriber has actually had the opportunity to evaluate (whether actively or passively). For programs of a type that the subscriber has not yet seen, a content filtering system must estimate the likelihood of a subscriber's interest in the

program. This estimation task is the heart of the filtering problem, and the reason that the similarity measurement is important.

The evaluation of the likelihood of interest in a particular program for a specific subscriber can automatically be computed by the Spatial-Temporal Content Manager **114** on a dynamic basis. The communique system for cellular communication networks **100** uses the Spatial-Temporal Content Manager **114** to evaluate a given set of available programs against the subscriber information for the subscribers who are active within each cell site coverage area to identify whether any of the presently available programs are of interest to these subscribers so that the subscribers can be advised of relevant programs, which are automatically selected by the communique system for cellular communication networks for transmission to selected cells. Each subscriber is advised of the availability of the program transmitted in their cell that closely matches the subscriber's interests as described by the subscriber's information in the Communique Location Register **163**. Subscriber's information are automatically updated on a continuing basis to reflect each subscriber's changing interests.

The use of this information to dynamically alter the content of Communiques and the communique coverage area can be effected in several modes. The typical mode is where programs are available from the program sources and the communique system for cellular communication networks **100** must determine the appropriate community of subscribers, if any, for each or at least a plurality of these programs. This is a "push" mode of program delivery, where the programs are migrated to the determined communities of subscribers. An alternative mode of delivery of programs is the "pull" mode, where the subscribers request access to programs and the communique system for cellular communication networks **100** creates communique coverage areas to deliver the requested programs to the subscribers. The former case is used as an example herein, since it is the typical mode of program delivery. The subscriber information and program attributes are compared by the Spatial-Temporal Content Manager **114** at step **1503** for each cell in order to identify appropriate programs for the Communiques that are transmitted in each cell coverage area. Thus, subscriber clustering can be used on the basis of subscribers active in each cell, which clustering data is correlated with the program available for narrowcast in the cell. This results at step **1504** in the identification of groups of subscribers in each cell who have an interest in a program available for transmission in that cell. This interested group of subscribers can also be factored at step **1505** by thresholding data, such as: number of said identified subscribers entering into and moving out of a cell of the cellular communication network, number of subscribers active in a cell of the cellular communication network, services requested by identified subscribers active in a cell of the cellular communication network, density of subscribers active in the cellular communication network. These factors can be used to modify the program selection based on subscriber population and activity so that bandwidth is not expended to serve a minimal number of subscribers in any particular cell. The result of these computations is that the Spatial-Temporal Content Manager **114** at step **1506** defines data indicative of at least one community of subscribers, with each of the communities of subscribers comprising a plurality of subscribers who are active in at least one cell of the cellular communication network and who have an interest in an identified program. This community data therefore is used at step **1507** to activate the program distribution as described herein to create a narrowcast coverage area which transmits a

selected program via at least one cell to an identified population of subscribers who are active in the identified cells.

Format of the Forward CDMA Channel for Communique Architectures

FIG. 5 illustrates in block diagram form a typical configuration of the Base Station Subsystem **131** to wireless subscriber device **101** forward CDMA channel used for Communique transmissions in cellular communication networks. As noted above, the typical Base Station Subsystem **131** to wireless subscriber device **101** forward CDMA channel comprises a predefined bandwidth centered about a selected carrier frequency. The bandwidth of the selected channel as well as the selected carrier frequency is a function of the technical implementation of the base station of the cellular network and is not discussed further herein. The communication space for Communique transmissions is typically divided into a plurality of segments: Pilot **501**, Synchronization (Synch) **502**, Traffic **503**. The Traffic **503** segment is further divided into a plurality of channels Ch1-Ch62. Each traffic channel represents a communication space for a selected wireless subscriber device **101**. The plurality of traffic channels CH1-CH62 as shown in FIG. 5 are assigned the remaining Walsh codes. Each Traffic channel consists of data traffic as well as in band signaling transmitted from the Base Station Subsystem **131** to the wireless subscriber device **101**, as noted above.

Typical Content Transmission Format

FIG. 8 illustrates in block diagram form a typical signaling protocol for use in the present communique system for cellular communication networks **100**. A frame **800** can be used to transmit both content as well as control information and a broadcast guide. The frame **800** is shown in one typical form, although the particulars of the frame **800** can vary as a function of the use of this element. In particular as noted above, a broadband program stream containing all information for all cells can be created by the Spatial-Temporal Content Manager **114**. This information is delivered to the Mobile Telephone Switching Office **106** via a communication medium, such as the Public Switched Telephone Network **108**, for distribution to all relevant Base Station Subsystems **132**, **142**, **152**. The Base Station Subsystems **132**, **142**, **152** can either parse the information contained in the frame into a plurality of Communiques for transmission in their cells, such as the plurality of cells included in coverage areas A-C shown on FIG. 12. Alternatively, the information can be passed directly to the wireless subscriber devices for parsing therein. Yet another alternative is the hierarchical parsing of the information, where the Base Station Subsystems **132**, **142**, **152** parse the received information frame into a plurality of subframes of similar format and reduced content for transmission to the wireless subscriber devices for further parsing of the subframes into the individual Communiques.

The frame **800** has a plurality of constituent parts, including a Header **801**, Administration **802**, Data **803** and Trailer **804**. The Header **801** and Trailer **804** are used to identify the beginning and end of the Frame **800** and can include error check bits to ensure proper transmission of the data. The Administration **802** is used to convey various control information to the Base Station Subsystem and to the wireless subscriber device. The Administration **802** can include a Radio Frequency Configuration segment **811** which defines the Traffic channel on which the frame is to be broadcast. The remaining segments of the Administration **802** consist of a "Program Guide" **812** which includes a schedule segment **821** to define the time at which the frame is to be transmitted and the information parsing data, content definition segment

822 the defines the content of the data section **803** of the frame **800** (and optionally the information parsing data), Authorization segment **823** which defines the type of service associated with the content of the data section **803** of the frame **800**. Advertisements **824** can also be included in the Program Guide **812**, along with optional special services **825**, such as traffic reports **841**, public service announcements **842** and the like **843**. Other segments **826** can optionally be included. In the content segment **822**, the content definitions describe the information that is available, and a plurality of such elements are shown to illustrate this concept, including but not limited to: music **831**, **832**, sports **833** and other programs **834**.

It is evident that this example of a format is simply an illustration and it is expected that numerous variations can be implemented that fall within the scope of the concept taught herein. In particular, in the case of hierarchical parsing, the frame that is transmitted to the wireless subscriber device would be a reduced content version of frame **800**, since the content would be reduced to match the bandwidth capabilities of the communication link from the Base Station Subsystems **132**, **142**, **152** to the wireless subscriber devices.

Examples of Narrowcast Dynamic Coverage Areas

FIGS. **9-10** illustrate typical dynamic coverage areas for various types of Communique transmissions. As an example of the capabilities of the communique system for cellular communication networks **100**, FIGS. **9** and **10** illustrate a typical operating environment for this system under dynamically changing conditions. For example, there can be an entertainment complex or sports stadium **912** located proximate two major arterial roads, such as North-South oriented highway **910** and East-West oriented highway **911**. There are typically a plurality of cells that provide cellular communication services in the area encompassed by the elements shown in FIG. **9**. For example, cells **901-904** provide cellular communication services for subscribers who are traveling on North-South oriented highway **910** while cells **905-908** provide cellular communication services for subscribers who are traveling on East-West oriented highway **911**. A cell **909** provides cellular communication services for subscribers who are located at or around entertainment complex **912** and when the entertainment complex **912** is not in use, the cellular communication traffic in cell **909** is minimal. The other cells also are subject to varying traffic and, for example, during a morning rush hour traffic the cells **901-904** can be collected into a narrowcast coverage area **921** while the cells **905-908** can be collected into a narrowcast coverage area **922**. Thus, subscribers traveling on North-South oriented highway **910** can receive traffic status information via narrowcast coverage area **921** and subscribers traveling on East-West oriented highway **911** can receive traffic status information via narrowcast coverage area **922**. Later in the day, when people are leaving the entertainment complex **912** and entering both the North-South oriented highway **910** and East-West oriented highway **911**, then the communique system for cellular communication networks **100** can reconfigure the narrowcast coverage areas to encompass cells **903**, **907-909** into a narrowcast coverage area **923** to provide traffic status information relating to the outflow of traffic from the entertainment complex **912**. As the traffic propagates outward from the entertainment complex **912**, the communique system for cellular communication networks **100** can reconfigure the narrowcast coverage areas to also encompass cells **902**, **904**, **906**. The communique system for cellular communication networks **100** can dynamically adapt the extent of narrowcast coverage area **923** in response to the dispersion of the traffic and, for

example, once the entertainment complex **912** is emptied, cell **909** can be dropped from the extent of narrowcast coverage area **923**.

The dynamic adaptation of the narrowcast coverage areas and the selection of information transmitted to subscribers located in these narrowcast coverage areas is accomplished by the communique system for cellular communication networks **100**, operating in cooperation with the Mobile Telephone Switching Office **106**. The Program Manager **113** and the Spatial-Temporal Communique Manager **114** operate to determine: the presence of subscribers in a particular cell, the presence of external events, the movement of the subscribers from cell to cell, the available programs that are to be transmitted to the subscribers, and then process this information to create the Communiques and the narrowcast coverage areas. This is accomplished in part by the communication between the communique system for cellular communication networks **100**, operating in cooperation with the Mobile Telephone Switching Office **106** in which the above-noted information is exchanged. In addition, the communique system for cellular communication networks **100** maintains data in memory **119** that defines the call coverage area of the cells so that the external events can be mapped to locales and their associated serving cells.

Program Stream Management

FIG. **13** illustrates a typical stream for a plurality of communication channels and FIG. **14** illustrates in tabular form a typical definition of a plurality of narrowcasts applicable to the program streams of FIG. **13** as applied to the typical dynamic coverage areas of FIGS. **9** & **10**. Communiques are formed by the Program Manager, **113**, and the Spatial Temporal Communique Manager **114**, and delivered to the cellular system via the Public Switched Telephone Network **108**, which is comprised of a grouping of various architectures (circuit, packet switched (e.g. TCP/IP), ATM, frame relay, satellite and so on) to convey the information from the Communique System **100**, to the Mobile Telephone Switching Office **106**, to Base Station Subsystem **131**, **141**, **151** and ultimately to Base Station Transceiver **133**, **143**, **144**, **153** for transmission as a broadcast/narrowcast Communique to the various wireless subscriber devices. The communiques can be labeled in any manner appropriate for composite system operation, and for this example, the communiques are given alpha designators (A, B, C and so on). A given Communique may have spatial relevance and could be delivery targeted by the Spatial Temporal Communique Manager **114**, to a specific region as described in FIGS. **9** & **10**.

As shown in FIG. **13**, the example Communique A comprises programming from sources:

National Source **122**, content residing at key media nodes (in a centralized manner);

Regional Source **120**, content residing at a plurality of media nodes attached to the Internet (in a centralized/decentralized manner);

Local Source **121**, content residing at a plurality of media nodes connected via the Local Exchange Carrier (in a decentralized manner);

Local Source **127**, content residing at end-subscriber nodes (in a decentralized manner).

The content from Regional Source **120** is diverse in its substance and embodies the plethora of media available on the Internet (data, stock quotes, music, video, email, special interest, sports, news and so on). The content from National Source **122** comprises more general information that is applicable to many communiques such as news, weather and sports. The content from Local Source **127** is information

gathered and conveyed by the end-subscriber in an active or passive mode. An example of Active information is identifying that a particular lane on a particular highway is blocked. Passive information may be reporting of outside air temperature.

To generate Communique A as shown in FIG. 13, the Program Manager 113, collects and collates all available content from sources 120, 122 and 127 from the universe of All Content Sources and forms/creates/parses 120, 122 and 127 to the desired, predetermined information stream thereby creating Communique A. In this example, it is desired to deliver Communique A to narrowcast region 910. This is the responsibility of the Spatial Temporal Communique Manager 114.

Communique A contains the following content in this example:

From Regional Source 120:

stock quotes (free to the end-subscriber)
music (channelized) (free/subscription to the end-subscriber)

composite traffic flow map (subscription to the end-subscriber)

other

From National Source 122:

news (free to the end subscriber)
weather (free to the end subscriber)
sports (free to the end subscriber)

other

From Local Source 127:

end-subscriber traffic data (free to the network)
end-subscriber temperature data (free to the network)
other

Each individual content stream can also contain advertising (typical for a free service). Typical subscription services would not contain advertising.

The Spatial Temporal Content Manager (STCM) 114, receives all Communiques from the Program Manager 113, and assigns the communiques for a given period of time to given cells to form narrowcast regions in the time domain. As described in FIG. 14, Communique A, which is the data payload for 803 delivered to narrowcast region 910, is but one of many Communique \times Narrowcast \times Time pairings that occurs in the Spatial Temporal Communique Manager 114. In addition to

Communique A, FIG. 14 describes:

Communique B is a diurnal narrowcast covering region 922.

Communique C is a special event narrowcast in region 909 for entertainment complex 912. In this example, Communiques A & B are repeated daily. Observe that cells 903, 906, 902, 907 are transmitting both Communiques A & B. For these overlapping narrowcast regions, data payload 803 contains both Communiques A & B.

At a time different than given for FIG. 9, FIG. 10 describes new narrowcast regions formed by the Spatial Temporal Communique Manager 114. These narrowcast regions are served with information contained in communiques S & N which is the payload 803 for narrowcast regions 923 and 909, respectively.

The Spatial Temporal Communique Manager 114, through repetitive programming, ensures that all cells, whether stand-alone or grouped into a narrowcast region, have content available 24 hours per day 7 days per week.

The programming described herein is deterministic meaning the content contained within a Communique, where a Communique is transmitted and how long a communique is transmitted is pre-programmed by the network operator.

Another embodiment concerns dynamic active feedback from end-subscribers within a given narrowcast region to Ainform—the Spatial Temporal Communique Manager 114, whether or not they are within the narrowcast region, as described above. For instance, let=s say that the Spatial Temporal Communique Manager 114, learns that all end-subscribers have left the entertainment complex located in region 909 delivering Communique C because the baseball game ended earlier than scheduled. The Spatial Temporal Communique Manager 114, can be embodied with a form of artificial intelligence to not only change the narrowcast region earlier than scheduled but also change the content, or Communique within the new region. An example would be to expand the Communique region along highway arterials leaving the stadium, change the Communique content and insert advertising for restaurants for hungry ball game spectators.

SUMMARY

The communique system for cellular communication networks operates with existing cellular communication services to provide communique communication services to subscribers. The Communique can be unidirectional (broadcast) or bidirectional (interactive) in nature and the extent of the Communique can be network-wide or narrowcast, where one or more cells and/or cell sectors are grouped to cover a predetermined geographic area or demographic population or subscriber interest group to transmit information to subscribers who populate the target audience for the narrowcast transmissions.

What is claimed:

1. A machine readable medium for use in a wireless communication system comprising:
 - instructions for storing subscriber information for each of a plurality of subscribers;
 - instructions for identifying subscribers, whose wireless subscriber device is active in a cell of said cellular communication network, for at least one of said cells;
 - instructions for automatically generating data that identifies a plurality of subscribers, who comprise at least one community of subscribers, as a function of said stored subscriber information for said identified subscribers;
 - instructions for selecting at least one of said plurality of cells to provide a communique communication service to subscribers who are members of said at least one community of subscribers; and
 - instructions for routing information constituting said communique communication service from a selected program source to cell sites associated with said selected at least one of said plurality of cells for transmission via a one of said plurality of wireless communication channels to wireless subscriber devices of ones of said identified subscribers who are present in said selected at least one of said plurality of cells.
2. The medium of claim 1 wherein instructions for storing further comprises:
 - instructions for communique location register means for storing at least one of: a subscriber's authorization, a subscriber's service plan, and a subscriber profile.
3. The medium of claim 1 wherein said instructions for automatically generating further comprises:
 - instructions for correlating said identified subscribers with program data indicative of said communique communication service from a selected program source to create data indicative of subscribers interested in said communique communication service in each of said cells.

29

4. The medium of operating of claim 3 wherein instructions for selecting further comprises:

instructions for managing spatial temporal content of said
 5
 10
 15
 20
 25
 30
 35
 40
 45
 50
 55
 60
 65
 70
 75
 80
 85
 90
 95
 100
 105
 110
 115
 120
 125
 130
 135
 140
 145
 150
 155
 160
 165
 170
 175
 180
 185
 190
 195
 200
 205
 210
 215
 220
 225
 230
 235
 240
 245
 250
 255
 260
 265
 270
 275
 280
 285
 290
 295
 300
 305
 310
 315
 320
 325
 330
 335
 340
 345
 350
 355
 360
 365
 370
 375
 380
 385
 390
 395
 400
 405
 410
 415
 420
 425
 430
 435
 440
 445
 450
 455
 460
 465
 470
 475
 480
 485
 490
 495
 500
 505
 510
 515
 520
 525
 530
 535
 540
 545
 550
 555
 560
 565
 570
 575
 580
 585
 590
 595
 600
 605
 610
 615
 620
 625
 630
 635
 640
 645
 650
 655
 660
 665
 670
 675
 680
 685
 690
 695
 700
 705
 710
 715
 720
 725
 730
 735
 740
 745
 750
 755
 760
 765
 770
 775
 780
 785
 790
 795
 800
 805
 810
 815
 820
 825
 830
 835
 840
 845
 850
 855
 860
 865
 870
 875
 880
 885
 890
 895
 900
 905
 910
 915
 920
 925
 930
 935
 940
 945
 950
 955
 960
 965
 970
 975
 980
 985
 990
 995

5. The medium of claim 1 wherein said instruction for selecting comprises:

instructions for dynamically revising selection of at least
 one of said plurality of cells to provide a communicate
 communication service to subscribers who are members
 of said at least one community of subscribers.

6. The medium of claim 1 wherein said instruction for selecting comprises:

instructions for identifying, in response to occurrence of an
 event, a temporal and spatial extent of said communicate
 communication service; and

instructions for translating said identified temporal and
 spatial extent into said set of said cells.

7. The medium of claim 1 further comprising the step of:
 instructions for enabling each of said plurality of wireless
 subscriber devices of ones of said identified subscribers
 who are present in said selected at least one of said
 plurality of cells to receive said information via said one
 of said plurality of wireless communication channels.

8. The medium of claim 7 wherein said instruction for enabling further comprises:

instructions for identifying each of said plurality of wire-
 less subscriber devices via a communicate address
 assigned to said plurality of wireless subscriber devices
 to enable the cell sites to recognize each of said plurality
 of wireless subscriber devices without requiring a
 unique identity for each of said plurality of wireless
 subscriber devices.

9. The medium of claim 8 wherein said step of identifying further comprises:

instructions for assigning a common MIN as said commu-
 nique address assigned to said plurality of wireless sub-
 scriber devices to enable the cell sites to recognize each
 of said plurality of wireless subscriber devices without
 requiring a unique identity for each of said plurality of
 wireless subscriber devices.

30

10. The medium claim 7 wherein said instructions for enabling further comprises:

instructions for registering at least one of said plurality of
 wireless subscriber devices to uniquely identify said at
 least one wireless subscriber device; and

instructions for authorizing said at least one wireless sub-
 scriber device to receive a subscriber selected commu-
 nique.

11. The medium of claim 1 wherein said instructions for routing operates in at least one information distribution mode selected from the class of information distribution modes including: push, pull, and combinations of push/pull information distribution modes.

12. The medium of claim 1 wherein said instructions for selecting comprises:

instructions for creating temporal and spatial extent of
 narrowcast in the content domain.

13. The medium of claim 12 wherein said instructions for creating temporal and spatial extent further comprises:

instructions for defining program segments for a plurality
 of communicates that are excerpted from a program
 stream in at least one of said plurality of cell sites.

14. The medium of claim 13 further comprising:

instructions for transmitting a program stream to said plu-
 rality of wireless subscriber devices served by said
 selected at least one of said plurality of cell sites; and
 instructions for transmitting program stream parsing control
 signals to said plurality of wireless subscriber
 devices served by said selected at least one of said plu-
 rality of cell sites to define at least one communicate that
 is excerpted from said program stream.

15. The medium of claim 14 further comprising:

instructions for transmitting a program stream to a plurality
 of cell sites; and
 instructions for transmitting program stream parsing control
 signals to said at least one of said plurality of cell
 sites to define at least one communicate that is excerpted
 from a program stream in said at least one of said plu-
 rality of cell sites.

16. The medium of claim 15 further comprising:

instructions for generating, in said plurality of cell sites, a
 plurality of communicates from said received program
 stream and said program stream parsing control signals;
 and
 instructions for transmitting said plurality of communi-
 ques to said plurality of wireless subscriber devices
 served by said selected at least one of said plurality of
 cell sites.

* * * * *