



US011815860B2

(12) **United States Patent**
Pandya et al.

(10) **Patent No.:** **US 11,815,860 B2**

(45) **Date of Patent:** ***Nov. 14, 2023**

(54) **SWITCH MODULE FOR ELECTRONIC CROWN ASSEMBLY**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Sameer Pandya**, Sunnyvale, CA (US);
Antonio Herrera, Woodside, CA (US);
Colin M Ely, Sunnyvale, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/989,057**

(22) Filed: **Nov. 17, 2022**

(65) **Prior Publication Data**

US 2023/0077241 A1 Mar. 9, 2023

Related U.S. Application Data

(63) Continuation of application No. 16/890,880, filed on Jun. 2, 2020, now Pat. No. 11,550,268.

(51) **Int. Cl.**
G04C 11/00 (2006.01)
G04C 3/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G04C 3/002** (2013.01); **A61B 5/332** (2021.01); **A61B 5/681** (2013.01); **G04G 21/025** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G04C 3/002; A61B 5/332; A61B 5/681; A61B 5/282; A61B 5/02438;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,237,860 A 4/1941 Bolle
2,288,215 A 6/1942 Taubert et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CH 1888928 1/1937
CN 1302740 9/2001
(Continued)

OTHER PUBLICATIONS

Author Unknown, "Desirable Android Wear smartwatch from LG," Gulf News, Dubai, 3 pages, Jan. 30, 2015.

(Continued)


Primary Examiner — Thuy N Pardo

(74) *Attorney, Agent, or Firm* — Brownstein Hyatt Farber Schreck, LLP

(57) **ABSTRACT**

A switch module for an electronic device detects translational inputs and defines at least portion of a conductive path from an input surface of the electronic device to a processing unit of the electronic device. The switch module may be a component of a crown assembly for detecting rotational inputs, translational inputs, touch inputs and/or biological signals such as electrocardiogram (ECG) signals. The switch module may include a conductive dome and a friction guard that is positioned between the conductive dome and the actuation member of the crown assembly. The conductive dome and/or the friction guard may define at least a portion of the conductive path from the input surface to the processing unit.

20 Claims, 19 Drawing Sheets



(51)	Int. Cl.		4,922,070 A	5/1990	Dorkinski
	H05K 5/00	(2006.01)	4,931,794 A	6/1990	Haag
	H05K 5/02	(2006.01)	4,952,799 A	8/1990	Loewen
	H01H 19/14	(2006.01)	4,980,685 A	12/1990	Souloumiac et al.
	A61B 5/00	(2006.01)	4,987,299 A	1/1991	Kobayashi et al.
	G04G 21/02	(2010.01)	5,034,602 A	7/1991	Garcia et al.
	G04G 21/08	(2010.01)	5,177,355 A	1/1993	Branan
	H01H 19/08	(2006.01)	5,214,278 A	5/1993	Banda
	A61B 5/332	(2021.01)	5,258,592 A	11/1993	Nishikawa et al.
(52)	U.S. Cl.		5,288,993 A	2/1994	Bidiville et al.
	CPC	G04G 21/08 (2013.01); H01H 19/08	5,347,123 A	9/1994	Jackson et al.
		(2013.01); H01H 19/14 (2013.01); H05K	5,383,166 A	1/1995	Gallay
		5/0017 (2013.01); H05K 5/0217 (2013.01)	5,471,054 A	11/1995	Watanabe
(58)	Field of Classification Search		5,477,508 A	12/1995	Will
	CPC	A61B 5/0245; G04G 21/025; G04G 21/08;	5,509,174 A	4/1996	Worrell
		H01H 19/08; H01H 19/14; H01H 25/06;	5,559,761 A	9/1996	Frenkel et al.
		H01H 2231/028; H05K 5/0017; H05K	5,572,314 A	11/1996	Hyman et al.
		5/0217; G06F 1/1671; G06F 1/169; G06F	5,583,560 A	12/1996	Florin et al.
		3/0312; G06F 3/0383; G06F 1/163	5,631,881 A	5/1997	Pessey et al.
	USPC	345/8, 9, 169; 368/10, 46, 61	5,726,645 A	3/1998	Kamon et al.
		See application file for complete search history.	5,738,104 A	4/1998	Lo
(56)	References Cited		5,748,111 A	5/1998	Bates
	U.S. PATENT DOCUMENTS		5,825,353 A	10/1998	Will
	2,497,935 A	2/1950 Feurer	5,841,050 A	11/1998	Clift et al.
	2,771,734 A	11/1956 Morf	5,847,335 A	12/1998	Sugahara et al.
	2,788,236 A	4/1957 Kafowi	5,867,082 A	2/1999	Van Zeeland
	2,797,592 A	7/1957 Marrapese	5,943,233 A	8/1999	Ebina
	3,040,514 A	6/1962 Dinstman	5,953,001 A	9/1999	Challener et al.
	3,056,030 A	9/1962 Kelchner	5,960,366 A	9/1999	Duwaer et al.
	3,130,539 A	4/1964 Davis	5,963,332 A	10/1999	Feldman et al.
	3,355,873 A	12/1967 Morf	5,999,168 A	12/1999	Rosenberg et al.
	3,362,154 A	1/1968 Perret	6,069,567 A	5/2000	Zawilski
	3,410,247 A	11/1968 Dronberger	6,128,006 A	10/2000	Rosenberg et al.
	3,495,398 A	2/1970 Widmer et al.	6,134,189 A	10/2000	Carrard
	3,577,876 A	5/1971 Spadini	6,154,201 A	11/2000	Levin et al.
	3,621,649 A	11/1971 Vulcan et al.	6,175,679 B1	1/2001	Veligdan et al.
	3,662,618 A	5/1972 Kröll et al.	6,203,190 B1	3/2001	Stotz
	3,733,803 A	5/1973 Hiraga	6,241,684 B1	6/2001	Amano
	3,937,002 A	2/1976 Haften	6,246,050 B1	6/2001	Tullis et al.
	4,007,347 A	2/1977 Haber	6,252,825 B1	6/2001	Perotto
	4,031,341 A	6/1977 Wuthrich et al.	6,304,247 B1	10/2001	Black
	4,037,068 A	7/1977 Gaynor	6,355,891 B1	3/2002	Ikunami
	4,051,665 A	10/1977 Arn	6,361,502 B1	3/2002	Puolakanaho et al.
	4,077,200 A	3/1978 Schneider	6,377,239 B1	4/2002	Isikawa
	4,133,404 A	1/1979 Griffin	6,392,640 B1	5/2002	Will
	4,170,104 A	10/1979 Yamagata	6,396,006 B1	5/2002	Yokoji et al.
	4,258,096 A	3/1981 LaMarche	6,422,740 B1	7/2002	Leuenberger
	4,274,152 A	6/1981 Ikegami	6,477,117 B1	11/2002	Narayanaswami et al.
	4,287,400 A	9/1981 Kitik	6,502,982 B1	1/2003	Bach et al.
	4,289,400 A	9/1981 Kubola et al.	6,525,278 B2	2/2003	Villain et al.
	4,311,026 A	1/1982 Ochoa	6,556,222 B1	4/2003	Narayanaswami
	4,311,990 A	1/1982 Burke	6,575,618 B1	6/2003	Inoue et al.
	4,324,956 A	4/1982 Sakakino et al.	6,587,400 B1	7/2003	Line
	4,345,119 A	8/1982 Latasiewicz	6,636,197 B1	10/2003	Goldenberg et al.
	4,364,674 A	12/1982 Tesch	6,646,635 B2	11/2003	Pogatz et al.
	4,379,642 A	4/1983 Meyrat	6,661,438 B1	11/2003	Shiraishi et al.
	4,395,134 A	7/1983 Luce	6,672,758 B2	1/2004	Ehram et al.
	4,396,298 A	8/1983 Ripley	6,794,992 B1	9/2004	Rogers
	4,417,824 A	11/1983 Paterson et al.	6,809,275 B1	10/2004	Cheng et al.
	4,448,199 A	5/1984 Schmid	6,834,430 B2	12/2004	Worrell
	4,520,306 A	5/1985 Kirby	6,846,998 B2	1/2005	Hasumi et al.
	4,581,509 A	4/1986 Sanford et al.	6,882,596 B2	4/2005	Guanter
	4,600,316 A	7/1986 Besson	6,888,076 B2	5/2005	Hetherington
	4,617,461 A	10/1986 Subbarao et al.	6,896,403 B1	5/2005	Gau
	4,634,861 A	1/1987 Ching et al.	6,909,378 B1	6/2005	Lambrechts et al.
	4,641,026 A	2/1987 Garcia, Jr.	6,914,551 B2	7/2005	Vidal
	4,670,737 A	6/1987 Rilling	6,950,695 B2	9/2005	Chen
	4,766,642 A	8/1988 Gaffney et al.	6,961,099 B2	11/2005	Takano et al.
	4,783,772 A	11/1988 Umemoto et al.	6,963,039 B1	11/2005	Weng et al.
	4,884,073 A	11/1989 Souloumiac	6,967,903 B2	11/2005	Guanter
	4,914,831 A	4/1990 Kanezashi et al.	6,977,868 B2	12/2005	Brewer et al.
			6,982,930 B1	1/2006	Hung
			6,985,107 B2	1/2006	Anson
			6,987,568 B2	1/2006	Dana
			6,998,553 B2	2/2006	Hisamune et al.
			7,009,915 B2	3/2006	Brewer et al.
			7,016,263 B2	3/2006	Gueissaz et al.
			7,021,442 B2	4/2006	Borgerson
			7,031,228 B2	4/2006	Born et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,034,237	B2	4/2006	Ferri et al.	8,441,450	B2	5/2013	Degner et al.
7,081,905	B1	7/2006	Raghunath et al.	8,446,713	B2	5/2013	Lai
7,102,626	B2	9/2006	Denny, III	8,456,430	B2	6/2013	Oliver et al.
7,111,365	B1	9/2006	Howie, Jr.	8,477,118	B2	7/2013	Lan et al.
7,113,450	B2	9/2006	Plancon et al.	8,493,190	B2	7/2013	Periquet et al.
7,119,289	B2	10/2006	Lacroix	8,508,511	B2	8/2013	Tanaka et al.
7,135,673	B2	11/2006	Saint Clair	8,525,777	B2	9/2013	Stavelly et al.
7,167,083	B2	1/2007	Giles	8,562,489	B2	10/2013	Burton et al.
7,187,359	B2	3/2007	Numata	8,568,313	B2	10/2013	Sadhu
7,244,927	B2	7/2007	Huynh	8,576,044	B2	11/2013	Chapman
7,255,473	B2	8/2007	Hiranuma et al.	8,593,598	B2	11/2013	Chen et al.
7,265,336	B2	9/2007	Hataguchi et al.	8,607,662	B2	12/2013	Huang
7,274,303	B2	9/2007	Dresti et al.	8,614,881	B2	12/2013	Yoo
7,285,738	B2	10/2007	Lavigne et al.	8,666,682	B2	3/2014	LaVigne et al.
7,286,063	B2	10/2007	Gauthey	8,677,285	B2	3/2014	Tsern et al.
7,292,741	B2	11/2007	Ishiyama et al.	8,704,787	B2	4/2014	Yamamoto
7,358,481	B2	4/2008	Yeoh et al.	8,711,093	B2	4/2014	Ong et al.
7,369,308	B2	5/2008	Tsuruta et al.	8,717,151	B2	5/2014	Forutanpour et al.
7,371,745	B2	5/2008	Ebright et al.	8,724,087	B2	5/2014	Van De Kerkhof et al.
7,385,874	B2	6/2008	Vuilleumier	8,730,167	B2	5/2014	Ming et al.
7,404,667	B2	7/2008	Born et al.	8,743,088	B2	6/2014	Watanabe
7,465,917	B2	12/2008	Chin et al.	8,783,944	B2	7/2014	Doi
7,468,036	B1	12/2008	Rulkov et al.	8,797,153	B2	8/2014	Vanhelle et al.
7,474,592	B2	1/2009	Lyon	8,804,993	B2	8/2014	Shukla et al.
7,506,269	B2	3/2009	Lang et al.	8,810,514	B2	8/2014	Zhao et al.
7,520,664	B2	4/2009	Wai	8,816,962	B2	8/2014	Obermeyer et al.
7,528,824	B2	5/2009	Kong	8,824,245	B2	9/2014	Lau et al.
7,545,367	B2	6/2009	Sunda et al.	8,847,741	B2	9/2014	Birnbaum et al.
7,591,582	B2	9/2009	Hiranuma et al.	8,851,372	B2	10/2014	Zhou
7,593,755	B2	9/2009	Colando et al.	8,859,971	B2	10/2014	Weber
7,605,846	B2	10/2009	Watanabe	8,860,674	B2	10/2014	Lee et al.
7,634,263	B2	12/2009	Louch et al.	8,863,219	B2	10/2014	Brown et al.
7,646,677	B2	1/2010	Nakamura	D717,679	S	11/2014	Anderssen
7,655,874	B2	2/2010	Akieda	8,878,657	B2	11/2014	Periquet et al.
7,682,070	B2	3/2010	Burton	8,885,856	B2	11/2014	Sacha
7,708,457	B2	5/2010	Girardin	8,895,911	B2	11/2014	Takahashi
7,710,456	B2	5/2010	Koshiba et al.	8,905,631	B2	12/2014	Sakurazawa et al.
7,732,724	B2	6/2010	Otani et al.	8,908,477	B2	12/2014	Peters
7,761,246	B2	7/2010	Matsui	8,920,022	B2	12/2014	Ishida et al.
7,763,819	B2	7/2010	Ieda et al.	8,922,399	B2	12/2014	Bajaj et al.
7,772,507	B2	8/2010	Orr	8,928,452	B2	1/2015	Kim et al.
7,778,115	B2	8/2010	Ruchonnet	8,948,832	B2	2/2015	Hong et al.
7,781,726	B2	8/2010	Matsui et al.	8,954,135	B2	2/2015	Yuen et al.
RE41,637	E	9/2010	O'Hara et al.	8,975,543	B2	3/2015	Hakemeyer
7,791,587	B2	9/2010	Kosugi	8,994,827	B2	3/2015	Mistry et al.
7,791,588	B2	9/2010	Tierling et al.	9,001,625	B2	4/2015	Essery et al.
7,791,597	B2	9/2010	Silverstein et al.	9,024,733	B2	5/2015	Wouters
7,822,469	B2	10/2010	Lo	9,028,134	B2	5/2015	Koshoji et al.
7,856,255	B2	12/2010	Tsuchiya et al.	9,030,446	B2	5/2015	Mistry et al.
7,858,583	B2	12/2010	Schmidt et al.	9,034,666	B2	5/2015	Vaganov et al.
7,865,324	B2	1/2011	Lindberg	9,039,614	B2	5/2015	Yuen et al.
7,894,957	B2	2/2011	Carlson	9,041,663	B2	5/2015	Westerman
7,946,758	B2	5/2011	Mooring	9,042,971	B2	5/2015	Brumback et al.
8,063,892	B2	11/2011	Shahoian et al.	9,049,998	B2	6/2015	Brumback et al.
8,138,488	B2	3/2012	Grot	9,052,696	B2	6/2015	Breuillot et al.
8,143,981	B2	3/2012	Washizu et al.	9,086,717	B2	7/2015	Meerovitsch
8,167,126	B2	5/2012	Stiehl	9,086,738	B2	7/2015	Leung et al.
8,169,402	B2	5/2012	Shahoian et al.	9,091,309	B2	7/2015	Battlogg
8,188,989	B2	5/2012	Levin et al.	9,100,493	B1	8/2015	Zhou
8,195,313	B1	6/2012	Fadell et al.	9,101,184	B2	8/2015	Wilson
8,229,535	B2	7/2012	Mensing et al.	9,105,413	B2	8/2015	Hiranuma et al.
8,248,815	B2	8/2012	Yang et al.	9,123,483	B2	9/2015	Ferri et al.
8,263,886	B2	9/2012	Lin et al.	9,134,807	B2	9/2015	Shaw et al.
8,263,889	B2	9/2012	Takahashi et al.	9,141,087	B2	9/2015	Brown et al.
8,275,327	B2	9/2012	Yi et al.	9,176,577	B2	11/2015	Jangaard et al.
8,294,670	B2	10/2012	Griffin et al.	9,176,598	B2	11/2015	Sweetser et al.
8,312,495	B2	11/2012	Vanderhoff	9,202,372	B2	12/2015	Reams et al.
8,318,340	B2	11/2012	Stimits	9,213,409	B2	12/2015	Redelshheimer et al.
8,368,677	B2	2/2013	Yamamoto	9,223,296	B2	12/2015	Yang et al.
8,371,745	B2	2/2013	Manni	9,241,635	B2	1/2016	Yuen et al.
8,373,661	B2	2/2013	Lan et al.	9,244,438	B2	1/2016	Hoover et al.
8,405,618	B2	3/2013	Colgate	9,256,209	B2	2/2016	Yang et al.
8,410,971	B2	4/2013	Friedlander	9,277,156	B2	3/2016	Bennett et al.
8,432,368	B2	4/2013	Momeyer et al.	9,350,850	B2	5/2016	Pope et al.
8,439,559	B2	5/2013	Luk et al.	9,367,146	B2	6/2016	Piot
				9,386,932	B2	7/2016	Chatterjee et al.
				9,426,275	B2	8/2016	Eim et al.
				9,430,042	B2	8/2016	Levin
				9,437,357	B2	9/2016	Furuki et al.

(56)		References Cited					
		U.S. PATENT DOCUMENTS					
9,449,770	B2	9/2016	Sanford et al.	10,474,194	B1	11/2019	Elli et al.
9,501,044	B2	11/2016	Jackson et al.	10,503,258	B2	12/2019	Holenarsipur et al.
9,520,100	B2	12/2016	Houjou et al.	10,509,486	B2	12/2019	Bushnell et al.
9,532,723	B2	1/2017	Kim	10,524,671	B2	1/2020	Lamego
9,542,016	B2	1/2017	Armstrong-Muntner	10,534,320	B2	1/2020	Ferri et al.
9,545,541	B2	1/2017	Aragones et al.	10,534,900	B2	1/2020	Cheong et al.
9,552,023	B2	1/2017	Joo et al.	10,551,798	B1	2/2020	Bushnell et al.
9,599,964	B2	3/2017	Gracia	10,572,053	B2	2/2020	Ely et al.
9,600,071	B2	3/2017	Rothkopf	10,579,090	B2	3/2020	Jackson et al.
9,606,721	B2	3/2017	Park et al.	10,599,101	B2	3/2020	Rothkopf et al.
9,607,505	B2	3/2017	Rothkopf et al.	10,610,157	B2	4/2020	Pandya et al.
9,620,312	B2	4/2017	Ely et al.	10,613,685	B2	4/2020	Shedletsy
9,627,163	B2	4/2017	Ely	10,627,783	B2	4/2020	Rothkopf et al.
9,632,318	B2	4/2017	Goto et al.	10,655,988	B2	5/2020	Boonsom et al.
9,632,537	B2	4/2017	Memering	10,664,074	B2	5/2020	Moussette et al.
9,638,587	B2	5/2017	Marquas et al.	10,732,571	B2	8/2020	Ely et al.
9,651,922	B2	5/2017	Hysek et al.	10,765,019	B2	9/2020	Werner
9,659,482	B2	5/2017	Yang et al.	10,845,764	B2	11/2020	Ely et al.
9,680,831	B2	6/2017	Jooste et al.	10,852,700	B2	12/2020	Abramov
9,709,956	B1	7/2017	Ely et al.	10,852,855	B2	12/2020	Niu
9,753,436	B2	9/2017	Ely et al.	10,871,385	B2	12/2020	Kok
D800,172	S	10/2017	Akana	10,884,549	B2	1/2021	Shedletsy et al.
9,800,717	B2	10/2017	Ma et al.	10,936,071	B2	3/2021	Pandya et al.
9,836,025	B2	12/2017	Ely et al.	10,942,491	B2	3/2021	Rothkopf
9,873,711	B2	1/2018	Hoover et al.	10,948,880	B2	3/2021	Ely et al.
9,874,945	B2	1/2018	Fukumoto	10,955,937	B2	3/2021	Bushnell et al.
9,886,006	B2	2/2018	Ely et al.	10,962,930	B2	3/2021	Ely et al.
9,891,590	B2	2/2018	Shim et al.	10,962,935	B1	3/2021	Ely et al.
9,891,651	B2	2/2018	Jackson et al.	10,987,054	B2	4/2021	Pandya et al.
9,891,667	B2	2/2018	Jung et al.	11,000,193	B2	5/2021	Tal et al.
9,898,032	B2	2/2018	Hafez et al.	11,002,572	B2	5/2021	Boonsom et al.
9,913,591	B2	3/2018	Lapetina et al.	11,029,831	B2	6/2021	Block et al.
9,921,548	B2	3/2018	Mitani	11,036,318	B2	6/2021	Bokma et al.
9,927,902	B2	3/2018	Burr et al.	11,148,292	B2	10/2021	Bryner et al.
9,939,923	B2	4/2018	Sharma	11,181,863	B2	11/2021	Ely et al.
9,946,297	B2	4/2018	Nazzaro et al.	11,194,298	B2	12/2021	Roach et al.
9,952,558	B2	4/2018	Ely	11,194,299	B1*	12/2021	Taylor G06F 3/016
9,952,682	B2	4/2018	Zhang et al.	11,221,590	B2	1/2022	Rothkopf et al.
9,971,305	B2	5/2018	Ely et al.	11,347,189	B1*	5/2022	Herrera H04N 23/51
9,971,405	B2	5/2018	Holenarsipur et al.	11,347,351	B2	6/2022	Shedletsy et al.
9,971,407	B2	5/2018	Holenarsipur et al.	11,360,440	B2	6/2022	Perkins et al.
9,979,426	B2	5/2018	Na et al.	11,385,599	B2	7/2022	Ely et al.
10,001,817	B2	6/2018	Zambetti et al.	11,474,483	B2	10/2022	Rothkopf
10,012,550	B2	7/2018	Yang	11,567,457	B2	1/2023	Rothkopf et al.
10,018,966	B2	7/2018	Ely et al.	2002/0101457	A1	8/2002	Lang
10,019,097	B2	7/2018	Ely et al.	2003/0174590	A1	9/2003	Arikawa et al.
10,037,006	B2	7/2018	Ely	2004/0047244	A1	3/2004	Lino et al.
10,037,081	B2	7/2018	Grant	2004/0082414	A1	4/2004	Knox
10,048,802	B2	8/2018	Shedletsy	2004/0130971	A1	7/2004	Ecoffet et al.
10,057,470	B2	8/2018	Kim et al.	2004/0264301	A1	12/2004	Howard et al.
10,061,399	B2	8/2018	Bushnell et al.	2005/0075558	A1	4/2005	Vecerina et al.
10,066,970	B2	9/2018	Gowreesunker et al.	2005/0088417	A1	4/2005	Mulligan
10,092,203	B2	10/2018	Mirov	2006/0250377	A1	11/2006	Zadesky et al.
10,108,016	B2	10/2018	Bosveld	2007/0013775	A1	1/2007	Shin
10,114,342	B2	10/2018	Kim et al.	2007/0050054	A1	3/2007	Sambandam Guruparan et al.
10,145,711	B2	12/2018	Boonsom et al.	2007/0182708	A1	8/2007	Poupyrev et al.
10,175,652	B2	1/2019	Ely et al.	2007/0211042	A1	9/2007	Kim et al.
10,190,891	B1	1/2019	Rothkopf et al.	2007/0222756	A1	9/2007	Wu et al.
10,203,662	B1	2/2019	Lin et al.	2007/0229671	A1	10/2007	Takeshita et al.
10,209,148	B2	2/2019	Lyon et al.	2007/0247421	A1	10/2007	Orsley et al.
10,216,147	B2	2/2019	Ely et al.	2008/0130914	A1	6/2008	Cho
10,222,755	B2	3/2019	Coakley et al.	2009/0051649	A1	2/2009	Rondel
10,222,756	B2	3/2019	Ely et al.	2009/0073119	A1	3/2009	Le et al.
10,222,909	B2	3/2019	Shedletsy et al.	2009/0122656	A1	5/2009	Bonnet et al.
10,234,828	B2	3/2019	Ely et al.	2009/0146975	A1	6/2009	Chang
10,241,593	B2	3/2019	Chen	2009/0152452	A1	6/2009	Lee et al.
10,296,125	B2	5/2019	Ely et al.	2009/0217207	A1	8/2009	Kagermeier et al.
10,331,081	B2	6/2019	Ely et al.	2009/0285443	A1	11/2009	Camp et al.
10,331,082	B2	6/2019	Ely et al.	2009/0312051	A1	12/2009	Hansson et al.
10,332,111	B2	6/2019	Mokhasi et al.	2009/0312655	A1	12/2009	Lo
10,353,487	B2	7/2019	Chung et al.	2010/0033430	A1	2/2010	Kakutani et al.
10,379,629	B2	8/2019	Bushnell et al.	2010/0053468	A1	3/2010	Havrill
10,386,940	B2	8/2019	Kim	2010/0081375	A1	4/2010	Rosenblatt et al.
10,401,961	B2	9/2019	Cruz-Hernandez et al.	2010/0149099	A1	6/2010	Elias
10,429,959	B2	10/2019	Battlogg	2010/0190999	A1	6/2010	Burton et al.
				2011/0007468	A1	1/2011	Li et al.
				2011/0090148	A1	4/2011	Brewer et al.
				2011/0158057	A1	6/2011	Ono et al.
				2011/0242064	A1	10/2011	Davis et al.
				2011/0270358	A1	11/2011	

(56)		References Cited					
U.S. PATENT DOCUMENTS							
2012/0067711	A1	3/2012	Yang	2019/0317454	A1	10/2019	Holenarsipur et al.
2012/0068857	A1	3/2012	Rothkopf et al.	2020/0041962	A1	2/2020	Beyhs
2012/0075082	A1	3/2012	Rothkopf et al.	2020/0064779	A1	2/2020	Pandya et al.
2012/0112859	A1	5/2012	Park et al.	2020/0073339	A1*	3/2020	Roach G04G 17/08
2012/0113044	A1	5/2012	Strazisar et al.	2020/0159172	A1	5/2020	Bushnell et al.
2012/0206248	A1	8/2012	Biggs	2020/0310609	A1	10/2020	Ham
2012/0272784	A1	11/2012	Bailey et al.	2021/0055696	A1	2/2021	Ely
2013/0037396	A1	2/2013	Yu	2021/0181682	A1	6/2021	Ely et al.
2013/0087443	A1	4/2013	Kikuchi	2021/0181691	A1	6/2021	Rothkopf et al.
2013/0191220	A1	7/2013	Dent et al.	2021/0181692	A1	6/2021	Rothkopf et al.
2013/0235704	A1	9/2013	Grinberg	2021/0181865	A1	6/2021	Bushnell et al.
2013/0261405	A1	10/2013	Lee et al.	2021/0255590	A1	8/2021	Ely et al.
2013/0335196	A1	12/2013	Zhang et al.	2021/0303081	A1*	9/2021	Kuboyama G04C 3/001
2014/0009397	A1	1/2014	Gillespie	2021/0353226	A1*	11/2021	Hiemstra A61B 5/7435
2014/0045547	A1	2/2014	Singamsetty et al.	2021/0373501	A1	12/2021	Pandya et al.
2014/0071098	A1	3/2014	You	2021/0405594	A1*	12/2021	Holenarsipur G04G 21/08
2014/0073486	A1	3/2014	Ahmed et al.	2022/0043397	A1*	2/2022	Ely G04G 21/025
2014/0132516	A1	5/2014	Tsai et al.	2022/0075328	A1	3/2022	Taylor
2014/0197936	A1	7/2014	Biggs et al.	2022/0299944	A1	9/2022	Ely et al.
2014/0340318	A1	11/2014	Stringer et al.	2022/0326660	A1	10/2022	Perkins et al.
2014/0347289	A1	11/2014	Suh et al.	2023/0012897	A1	1/2023	Bushnell et al.
2014/0368442	A1	12/2014	Vahtola	2023/0013283	A1	1/2023	Herrera et al.
2014/0375579	A1	12/2014	Fujiwara	2023/0028554	A1	1/2023	Rothkopf et al.
2015/0049059	A1	2/2015	Zadesky et al.	2023/0097827	A1	3/2023	Rothkopf et al.
2015/0098309	A1	4/2015	Adams et al.	2023/0101015	A1	3/2023	Ely et al.
2015/0124415	A1	5/2015	Goyal et al.	2023/0161299	A1	5/2023	Beyhs
2015/0186609	A1	7/2015	Utter, II				
2015/0221460	A1	8/2015	Teplitxky et al.				
2015/0293592	A1	10/2015	Cheong	CN	1445627	10/2003	
2015/0320346	A1	11/2015	Chen	CN	1504843	6/2004	
2015/0338642	A1	11/2015	Sanford	CN	1601408	3/2005	
2015/0366098	A1	12/2015	Lapetina et al.	CN	1624427	6/2005	
2016/0018846	A1	1/2016	Zenoff	CN	1792295	6/2006	
2016/0054813	A1	2/2016	Shediwy et al.	CN	1825224	8/2006	
2016/0062623	A1	3/2016	Howard et al.	CN	101035148	9/2007	
2016/0069713	A1	3/2016	Ruh et al.	CN	101201587	6/2008	
2016/0147432	A1	5/2016	Shi et al.	CN	201081979	7/2008	
2016/0170598	A1	6/2016	Zambetti et al.	CN	101404928	4/2009	
2016/0170608	A1	6/2016	Zambetti et al.	CN	201262741	6/2009	
2016/0170624	A1	6/2016	Zambetti et al.	CN	101750958	6/2010	
2016/0241688	A1	8/2016	Vossoughi	CN	201638168	11/2010	
2016/0253487	A1	9/2016	Sarkar et al.	CN	101923314	12/2010	
2016/0306446	A1	10/2016	Chung et al.	CN	102067070	5/2011	
2016/0320583	A1	11/2016	Hall, Jr.	CN	102216959	10/2011	
2016/0327911	A1	11/2016	Eim et al.	CN	202008579	10/2011	
2016/0338642	A1	11/2016	Parara et al.	CN	102590925	7/2012	
2016/0378069	A1	12/2016	Rothkopf et al.	CN	102741772	10/2012	
2016/0378070	A1	12/2016	Rothkopf et al.	CN	102890443	1/2013	
2017/0027461	A1	2/2017	Shin et al.	CN	202710937	1/2013	
2017/0031449	A1	2/2017	Karsten et al.	CN	103177891	6/2013	
2017/0061863	A1	3/2017	Eguchi	CN	103191557	7/2013	
2017/0069443	A1	3/2017	Wang et al.	CN	103253067	8/2013	
2017/0069444	A1	3/2017	Wang et al.	CN	103645804	3/2014	
2017/0069447	A1	3/2017	Wang et al.	CN	203564224	4/2014	
2017/0216519	A1	8/2017	Vouillamoz	CN	103852090	6/2014	
2017/0216668	A1	8/2017	Burton et al.	CN	203630524	6/2014	
2017/0238138	A1	8/2017	Aminzade	CN	103919536	7/2014	
2017/0251561	A1	8/2017	Fleck et al.	CN	103956006	7/2014	
2017/0269715	A1	9/2017	Kim et al.	CN	203693601	7/2014	
2017/0285404	A1	10/2017	Kubota et al.	CN	203705837	7/2014	
2017/0301314	A1	10/2017	Kim et al.	CN	203732900	7/2014	
2017/0307414	A1	10/2017	Ferri et al.	CN	103995456	8/2014	
2017/0331869	A1	11/2017	Bendahan et al.	CN	104020660	9/2014	
2017/0357465	A1	12/2017	Dzeryn et al.	CN	203941395	11/2014	
2018/0059624	A1	3/2018	James	CN	104777987	4/2015	
2018/0196517	A1	7/2018	Tan et al.	CN	104685794	6/2015	
2018/0225701	A1	8/2018	Han	CN	204479929	7/2015	
2018/0235491	A1	8/2018	Bayley et al.	CN	204496177	7/2015	
2018/0337551	A1	11/2018	Park	CN	104880937	9/2015	
2019/0025940	A1	1/2019	Shim et al.	CN	104898406	9/2015	
2019/0056700	A1	2/2019	Matsuno	CN	204650147	9/2015	
2019/0072911	A1	3/2019	Ely et al.	CN	105022947	11/2015	
2019/0072912	A1	3/2019	Pandya et al.	CN	105096979	11/2015	
2019/0088583	A1	3/2019	Ashikaga et al.	CN	105339871	2/2016	
2019/0278232	A1	9/2019	Ely et al.	CN	105547146	5/2016	
				CN	105556433	5/2016	
				CN	105683876	6/2016	
				FOREIGN PATENT DOCUMENTS			

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	105760067	7/2016	JP	2007101380	4/2007
CN	105955519	9/2016	JP	2007149620	6/2007
CN	205645648	10/2016	JP	2007248176	9/2007
CN	205721636	11/2016	JP	2007311153	11/2007
CN	205750744	11/2016	JP	2008053980	3/2008
CN	106236051	12/2016	JP	2008122124	5/2008
CN	106557218	4/2017	JP	2008122377	5/2008
CN	206147524	5/2017	JP	2008170436	7/2008
CN	206209589	5/2017	JP	2008235226	10/2008
CN	107111342	8/2017	JP	2009009382	1/2009
CN	107122088	9/2017	JP	2009070657	4/2009
CN	107966895	4/2018	JP	2009519737	5/2009
CN	209560397	10/2019	JP	2009540399	11/2009
CN	209625187	11/2019	JP	2010032545	2/2010
CN	114220694	3/2022	JP	2010515153	5/2010
CN	106125968	11/2022	JP	2010165001	7/2010
DE	3706194	9/1988	JP	2010186572	8/2010
DE	102008023651	11/2009	JP	2010243344	10/2010
DE	102016215087	3/2017	JP	2010244797	10/2010
EP	0165548	12/1985	JP	2011021929	2/2011
EP	0556155	8/1993	JP	2011165468	8/2011
EP	1345095	9/2003	JP	2011221659	11/2011
EP	1519452	3/2005	JP	2012053801	3/2012
EP	1669724	6/2006	JP	2013057516	3/2013
EP	1832969	9/2007	JP	2013079961	5/2013
EP	2375295	10/2011	JP	2013524189	6/2013
EP	2579186	4/2013	JP	3190075	4/2014
EP	2720129	4/2014	JP	5477393	4/2014
EP	2884239	6/2015	JP	2014512556	5/2014
FR	2030093	10/1970	JP	2014112222	6/2014
FR	2801402	5/2001	JP	2014174031	9/2014
GB	2433211	6/2007	JP	2017219448	12/2017
JP	S52151058	12/1977	JP	2018510451	4/2018
JP	S52164551	12/1977	KR	20010030477	4/2001
JP	S53093067	8/1978	KR	200278568	3/2002
JP	S54087779	6/1979	KR	20070011685	1/2007
JP	S5708582	1/1982	KR	20070014247	2/2007
JP	S5734457	2/1982	KR	100754674	9/2007
JP	S60103936	6/1985	KR	20080028935	4/2008
JP	S60103937	6/1985	KR	20080045397	5/2008
JP	H02285214	11/1990	KR	2020100007563	7/2010
JP	H04093719	3/1992	KR	20110011393	2/2011
JP	H04157319	5/1992	KR	20110012784	2/2011
JP	H05203465	8/1993	KR	20110103761	9/2011
JP	H05312595	11/1993	KR	20110113368	10/2011
JP	H06050927	12/1994	KR	20130036038	4/2013
JP	H06331761	12/1994	KR	20130131873	12/2013
JP	H06347293	12/1994	KR	20140051391	4/2014
JP	H07116141	5/1995	KR	20140064689	5/2014
JP	H0914941	1/1997	KR	20140104388	8/2014
JP	H10161811	6/1998	KR	20160017070	2/2016
JP	H11121210	4/1999	KR	20160048967	5/2016
JP	H11191508	7/1999	KR	20170106395	9/2017
JP	2000258559	9/2000	NL	1040225	11/2014
JP	2000316824	11/2000	RO	129033	11/2013
JP	2000337892	12/2000	TW	200633681	10/2006
JP	2001084934	3/2001	WO	WO2001/022038	3/2001
JP	2001167651	6/2001	WO	WO2001/069567	9/2001
JP	2001202178	7/2001	WO	WO2003/032538	4/2003
JP	2001215288	8/2001	WO	WO2010/058376	5/2010
JP	2001524206	11/2001	WO	WO2012/083380	6/2012
JP	2002071480	3/2002	WO	WO2012/094805	7/2012
JP	2002165768	6/2002	WO	WO2014/018118	1/2014
JP	2003050668	2/2003	WO	WO2014/200766	12/2014
JP	2003151410	5/2003	WO	WO2015/147756	10/2015
JP	2003331693	11/2003	WO	WO2016080669	5/2016
JP	2004184396	7/2004	WO	WO2016/104922	6/2016
JP	2004028979	11/2004	WO	WO2016/155761	10/2016
JP	2005017011	1/2005	WO	WO2016196171	12/2016
JP	2005063200	3/2005	WO	WO2016208835	12/2016
JP	2005099023	4/2005	WO	WO2017/013278	1/2017
JP	2005108630	4/2005	WO	WO2020173085	9/2020
JP	2006101505	4/2006			
JP	2006164275	6/2006			
JP	3852854	12/2006			

OTHER PUBLICATIONS

Author Unknown, "Fossil Q ups smartwatch game with handsome design and build," Business Mirror, Makati City, Philippines, 3 pages, Dec. 20, 2016.

(56)

References Cited

OTHER PUBLICATIONS

Author Unknown, "How Vesag Helps Kids Women and Visitors," <http://www.sooperarticles.com/health-fitness-articles/children-health-articles/how-vesag-helps-kids-women-visitors-218542.html>, 2 pages, at least as early as May 20, 2015.

Author Unknown, "mHealth," <http://mhealth.vesag.com/?m=201012>, 7 pages, Dec. 23, 2010.

Author Unknown, "mHealth Summit 2010," <http://www.virtualpressoffice.com/eventsSubmenu.do?page=exhibitorPage&showId=1551&companyId=5394>, 5 pages, Nov. 18, 2010.

Author Unknown, "MyKronoz ZeTime: World's Most Funded Hybrid Smartwatch Raised over \$3M on Kickstarter, Running until Apr. 27," Business Wire, New York, New York, 3 pages, Apr. 21, 2017.

Author Unknown, "RedEye mini Plug-in Universal Remote Adapter for iPhone, iPod touch and iPad," Amazon.com, 4 pages, date unknown.

Author Unknown, "Re iPhone Universal Remote Control—Infrared Remote Control Accessory for iPhone and iPod touch," <http://www.amazon.com/iPhone-Universal-Remote-Control-Accessory/dp/tech-data/B0038Z4...>, 2 pages, at least as early as Jul. 15, 2010.

Author Unknown, "Vesag Wrist Watch for Dementia Care from VYZIN," <http://vyasa-kaaranam-ketkadey.blogspot.com/2011/03/vesag-wrist-watch-for-dementia-care.html>, 2 pages, Mar. 31, 2011.

Author Unknown, "Vyzin Electronics Private Limited launches Vesag Watch," <http://www.virtualpressoffice.com/showJointPage.do?page=jp&showId=1544>, 5 pages, Jan. 6, 2011.

Author Unknown, "Vyzin Unveiled Personal Emergency Response System (PERS) with Remote Health Monitoring That Can Be Used for Entire Family," <http://www.24-7pressrelease.com/press-release/vyzin-unveiled-personal-emergency-response-system-pers-with-remote-health-monitoring-that-can-be-used-for-entire-family-219317.php>, 2 pages, Jun. 17, 2011.

Author Unknown, "DeskThorityNet, Optical Switch Keyboards," <http://deskthority.net/keyboards-f2/optical-switch-keyboards-t1474.html>, 22 pages, Jul. 11, 2015.

Epstein et al., "Economical, High-Performance Optical Encoders," Hewlett-Packard Journal, pp. 99-106, Oct. 1988. [text only version]. GreyB, "Google Watch: Convert your arm into a keyboard," <http://www.whatafuture.com/2014/02/28/google-smartwatch/#sthash.Yk35cDXK.dpbs>, 3 pages, Feb. 28, 2014.

IBM, "Additional Functionality Added to Cell Phone via "Learning" Function Button," www.ip.com, 2 pages, Feb. 21, 2007.

Kim, Joseph, "2010 mHealth Summit Emerges as Major One-Stop U.S. Venue for Mobile Health," <http://www.medicineandtechnology.com/2010/08/2010-mhealth-summit-emerges-as-major.html>, 3 pages, Aug. 26, 2010.

Krishnan et al., "A Miniature Surface Mount Reflective Optical Shaft Encoder," Hewlett-Packard Journal, Article 8, pp. 1-6, Dec. 1996.

Narayanaswami et al., "Challenges and considerations for the design and production of a purpose-optimized body-worn wrist-watch computer," Defense, Security, and Cockpit Displays, 2004.

M.T. Raghunath et al., User Interfaces for Applications on a Wrist Watch, Personal and Ubiquitous Computing, vol. 6, No. 1, 2002, Springer.

Rick, "How VESAG Helps Health Conscious Citizens," <http://sensetekgroup.com/2010/11/29/wireless-health-monitoring-system/>, 2 pages, Nov. 29, 2010.

Sadhu, Rajendra, "How VESAG Helps People Who Want to 'Be There?'," <http://ezinearticles.com/?How-Vesag-Helps-People-Who-Want-to-Be-There?&id=5423873>, 1 page, Nov. 22, 2010.

Sherr, Sol, "Input Devices," p. 55, Mar. 1988.

Tran et al., "Universal Programmable Remote Control/Telephone," www.ip.com, 2 pages, May 1, 1992.

U.S. Appl. No. 17/377,482, filed Jul. 16, 2021, pending.

U.S. Appl. No. 17/840,222, filed Jun. 14, 2022, pending.

U.S. Appl. No. 17/899,498, filed Aug. 31, 2022, pending.

U.S. Appl. No. 17/951,020, filed Sep. 22, 2022, pending.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 7

SWITCH MODULE FOR ELECTRONIC CROWN ASSEMBLY

CROSS-REFERENCE TO RELATED APPLICATION(S)

This application is a continuation patent application of U.S. patent application Ser. No. 16/890,880, filed Jun. 2, 2020, and titled "Switch Module for Electronic Crown Assembly", the contents of which are incorporated herein by reference in its entirety.

FIELD

Embodiments generally relate to a switch module for an electronic device. More particularly, embodiments described herein relate to a switch module routing an external signal and a switch signal for an electronic device.

BACKGROUND

Electronic devices frequently use physical input devices to facilitate user interaction. For example, buttons, keys, dials, and the like can be physically manipulated by users to control operations of the device. Physical input devices may use various types of sensing mechanisms to translate the physical manipulation to signals usable by the electronic device. For example, buttons and keys may use collapsible dome switches to detect presses, while dials and other rotating input devices may use encoders or resolvers to detect rotational movements.

SUMMARY

Embodiments of the systems, devices, methods, and apparatuses described in the present disclosure are directed to a switch module for an electronic device.

One embodiment may take the form of an electronic watch that includes an enclosure, a processing unit, a display, and a crown assembly. The enclosure may define an interior volume and an opening into the interior volume. The processing unit may be positioned within the interior volume. The display may be operably coupled to the processing unit and configured to provide a graphical output. The crown assembly may be positioned at least partially within the interior volume, and may include an actuation member extending through the opening and defining a input surface for sensing an input signal along an exterior of the electronic watch. The crown assembly may further include a rotation sensor positioned within the interior volume and configured to detect a rotational input at the crown assembly. The crown assembly may further include a switch module positioned within the interior volume. The switch module may include a switch housing defining a recess, a persistent electrical contact positioned in the recess and conductively coupled to the processing unit, a switch electrical contact positioned in the recess and conductively coupled to the processing unit, and a conductive dome positioned at least partially in the recess and conductively coupled to the actuation member. The conductive dome may be configured to transition from an uncollapsed configuration to a collapsed configuration in response to a translational input at the actuation member. In the uncollapsed configuration and the collapsed configuration, the conductive dome may contact the persistent electrical contact to at least partially define a conductive path between the input surface and the processing unit. In the collapsed configuration, the conductive dome may contact

the switch electrical contact to register the translational input. The graphical output may be responsive to the input signal, the rotational input, and the translational input.

Another embodiment may take the form of a switch module for a crown assembly for an electronic watch. The switch module may include a switch housing that includes a base defining a recess and a bracket for coupling the switch module to a device enclosure. The switch module may further include a conductive dome positioned at least partially in the recess and defining a first portion of a conductive path between an actuation member and a processing unit. The conductive dome may be configured to transition from an uncollapsed configuration to a collapsed configuration in response to a translational input at the actuation member. The switch module may further include a friction guard contacting the conductive dome and configured to be positioned between the conductive dome and the actuation member. The friction guard may define a second portion of the conductive path. The switch module may further include a persistent electrical contact positioned in the recess and contacting the conductive dome, the persistent electrical contact defining a third portion of the conductive path. The switch module may further include a first conductive member at least partially encapsulated within the base and defining a fourth portion of the conductive path. The switch module may further include a switch electrical contact positioned in the recess and configured to contact the conductive dome in the collapsed configuration to register the translational input. The switch module may further include a second conductive member at least partially encapsulated within the base and configured to conductively couple the switch electrical contact to the processing unit.

Another embodiment may take the form of an electronic watch that includes an enclosure, a processing unit, and a crown assembly. The enclosure may define an interior volume and an opening into the interior volume. The processing unit may be positioned within the interior volume. The crown assembly may be positioned at least partially within the interior volume, and may include an actuation member extending through the opening and defining a input surface for sensing an input signal along an exterior of the electronic watch. The crown assembly may further include a rotation sensor positioned within the interior volume and configured to detect a rotational input at the crown assembly. The crown assembly may further include a switch module positioned within the interior volume. The switch module may include a switch housing defining a recess, a conductive dome positioned in the recess and configured to collapse in response to a translational input at the crown assembly, and a friction guard at least partially defining a conductive path between the input surface and the processing unit. The friction guard may include a support member attached to the switch housing, a translating portion contacting the actuation member, and a first flexure and a second flexure extending from the support member and at least partially surrounding the translating portion, the first flexure and the second flexure configured to allow the translating portion to move relative to the switch housing.

In addition to the example aspects and embodiments described above, further aspects and embodiments will become apparent by reference to the drawings and by study of the following description.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will be readily understood by the following detailed description in conjunction with the accompa-

nying drawings, wherein like reference numerals designate like structural elements, and in which:

FIG. 1 is a functional block diagram of an electronic device;

FIGS. 2A-2C show an example of a watch that incorporates a switch module as described herein;

FIG. 3A-3F show an example switch module for an electronic device;

FIGS. 4A-4C show an example switch module for an electronic device;

FIGS. 5A-5C show an example switch module for an electronic device;

FIGS. 6A-6B show an example switch module for an electronic device; and

FIG. 7 shows a sample electrical block diagram of an electronic device that may incorporate a switch module.

The use of cross-hatching or shading in the accompanying figures is generally provided to clarify the boundaries between adjacent elements and also to facilitate legibility of the figures. Accordingly, neither the presence nor the absence of cross-hatching or shading conveys or indicates any preference or requirement for particular materials, material properties, element proportions, element dimensions, commonalities of similarly illustrated elements, or any other characteristic, attribute, or property for any element illustrated in the accompanying figures.

Additionally, it should be understood that the proportions and dimensions (either relative or absolute) of the various features and elements (and collections and groupings thereof) and the boundaries, separations, and positional relationships presented therebetween, are provided in the accompanying figures merely to facilitate an understanding of the various embodiments described herein and, accordingly, may not necessarily be presented or illustrated to scale, and are not intended to indicate any preference or requirement for an illustrated embodiment to the exclusion of embodiments described with reference thereto.

DETAILED DESCRIPTION

Reference will now be made in detail to representative embodiments illustrated in the accompanying drawings. It should be understood that the following description is not intended to limit the embodiments to one preferred embodiment. To the contrary, it is intended to cover alternatives, modifications, and equivalents as can be included within the spirit and scope of the described embodiments as defined by the appended claims.

The following disclosure relates to electronic devices, and in particular to a switch module for a crown assembly that receives rotational inputs and translational inputs, and includes an actuation member defining an input surface for receiving sensor inputs, such as touch inputs, electrocardiogram (ECG) signals, and the like. The switch module may provide at least a portion of a conductive path from the input surface of the crown assembly to a processing unit or other circuitry of the electronic device. The conductive path may be electrically isolated from one or more additional components of the crown assembly and/or the electronic device, and may allow signals from to be transmitted between the input surface and the processing unit.

The switch module may include a conductive dome and a friction guard that is positioned between the conductive dome and the actuation member of the crown assembly. The conductive dome and/or the friction guard may define at least a portion of the conductive path from the input surface to the processing unit.

The conductive dome may collapse in response to a translational input moving the actuation member from an unactuated position to an actuated position. The conductive dome and/or the friction guard may provide an outward biasing force that maintains the actuation member in the unactuated position absent an inward force on the actuation member. The outward biasing force may be a spring force exerted by the conductive dome and/or the friction guard on the actuation member. A translational input may be provided to the crown assembly in the form of an inward force that overcomes the outward biasing force and causes the actuation member to translate inward to an actuated position. When the inward force is removed or reduced, the outward biasing force may cause the actuation member to return to the unactuated position.

When the actuation member is in the unactuated position, the conductive dome is in an uncollapsed configuration. When the actuation member is in the actuated position, the conductive dome is in a collapsed configuration. In the uncollapsed configuration and/or the collapsed configuration, the conductive dome may contact a first electrical contact that is conductively coupled to the processing unit, thereby facilitating transmission of signals between the input surface and the processing unit. In the collapsed configuration, the conductive dome may contact a second electrical contact, which may close a circuit to register the translational input. In the uncollapsed configuration and/or the collapsed configuration, the conductive dome may contact a reference electrical contact that provides a bias voltage for detecting translational inputs and/or input signals at the input surface. When the conductive dome contacts the second electrical contact, it may close a circuit that includes the reference electrical contact, which, in turn, may register a translational input.

The conductive dome may define one or more conductive routes that are electrically isolated from one another. The conductive dome may include vias or other structural elements for defining the isolated conductive routes. The conductive dome may define a first conductive path between a friction guard and the first electrode for transmitting signals between the sensor and the processing unit. The conductive dome may define a second conductive path between the second electrical contact and the reference electrical contact for detecting translational inputs. The first and second conductive paths may be electrically isolated from one another to prevent signal interference.

In embodiments in which the friction guard provides at least a portion of the outward biasing force, the friction guard may include a translating portion and one or more flexures that allow the translating portion to move. The friction guard may act as a spring, with the flexures exerting a reaction force on the translating portion (and therefore on the actuation member) that is dependent on the position of the translating portion. The spring dynamics of the friction guard may be defined by the material properties, the thickness, and the length of the flexures.

The switch module may include a switch housing that at least partially surrounds one or more components of the switch module. The housing may define a recess in which the conductive dome, the friction guard, and/or one or more of the electrical contacts are positioned. The switch housing may include a bracket or other fastening component for coupling the switch module to the enclosure or one or more other components of the electronic watch. In some cases, the electrical contacts may be at least partially encapsulated within the switch housing. As used herein, "encapsulated" may refer to a component that is contacted by and partially

5

or completely surrounded by another component. For example, the electrical contacts may be encapsulated within a base of the switch housing by injection molding.

The term “attached,” as used herein, may refer to two or more elements, structures, objects, components, parts or the like that are physically affixed, fastened, and/or retained to one another. The term “coupled,” as used herein, may refer to two or more elements, structures, objects, components, parts or the like that are physically attached to one another, operate with one another, communicate with one another, are in electrical connection with one another, and/or otherwise interact with one another. Accordingly, while elements attached to one another are coupled to one another, the reverse is not required. As used herein, “operably coupled” or “electrically coupled” may refer to two or more devices that are coupled in any suitable manner for operation and/or communication, including wiredly, wirelessly, or some combination thereof. As used herein, “conductively coupled” may refer to two or more elements, structures, objects, components, parts or the like that are coupled in any suitable manner for facilitating the transmission of electrical current therebetween.

These and other embodiments are discussed with reference to FIGS. 1-7. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes only and should not be construed as limiting.

FIG. 1 is a functional block diagram of an electronic device 100. In some examples, the device 100 may be an electronic watch or electronic health monitoring device. The electronic device 100 may include a device enclosure 102 that defines an interior volume 106 of the device. The device may include a crown assembly 110, a processing unit 120, a display 122, one or more input devices 124, and one or more output devices 126 positioned at least partially within the interior volume. Each of the components of the electronic device 100 may be operably coupled to the processing unit 120, for example via connectors 128a-e.

In some cases, the electronic device 100 includes a crown assembly 110 configured to receive translational inputs, rotational inputs, touch inputs and/or biometric signals. Inputs received at the crown assembly 110 may result in changes in outputs provided by the electronic device 100, such as a graphical output of the display 122, and/or otherwise modify operations of the electronic device. In some cases, the crown assembly 110 may be positioned along a side of the enclosure 102, and may extend through an opening 104 defined in the enclosure and into the interior volume 106.

The crown assembly 110 may include an actuation member 112 that may be translated (e.g., by a user) to provide translational inputs, rotated to provide rotational inputs, and touched to provide touch inputs and/or biometric signals. The crown assembly 110 may include a switch module 116 that is used to detect translational inputs to the crown assembly. The switch module 116 may also define at least a part of a conductive path between the actuation member 112 and the processing unit 120. This may facilitate the transmission of touch inputs and/or biometric signals from the actuation member 112 to the processing unit 120.

The actuation member 112 may include a crown body 112a positioned at least partially outside the enclosure 102 and a crown shaft 112b extending through the opening 104 and positioned at least partially within the enclosure 102. As shown, the crown body 112a and the crown shaft 112b may be formed as a unitary structure, though other actuation members may have different components and/or configura-

6

tions, and may be defined by several different components that are attached together. The actuation member 112 may be formed from or include a conductive material (e.g., metal, carbon fiber, conductive polymer, conductive ceramics, or the like).

The actuation member 112 may define an input surface 114 that users can touch to provide touch inputs or biological signals to the electronic device 100. The actuation member 112 and the switch module 116 may form at least a portion of a conductive path 130 between the input surface 114 and the processing unit 120. This may facilitate the transmission of input signals from the input surface 114 to the processing unit 120. The input surface 114 may be an electrically conductive surface. The electrical conductivity of the input surface 114 may facilitate a conductive path (e.g., conductive path 130) from a user's finger in contact with the input surface to other components of the electronic device.

Additionally or alternatively, the crown assembly 110 may include one or more sensing elements for detecting touch inputs and/or biological signals. Example sensing elements include capacitive sensors, ultrasonic sensors, optical sensors, and the like. The actuation member 112 and/or the switch module 116 may define at least a portion of a conductive path between the sensing element(s) and the processing unit 120.

The input surface 114 may function as an electrode to sense input signals, which may include voltages or signals indicative of one or more touch inputs and/or biological parameters of a user in contact with the conductive surface. The enclosure 102 may define another touch-sensitive or conductive surface that is electrically coupled to the processing unit 120 and also functions as an electrode. The processing unit 120 may determine an electrocardiogram using outputs of the electrodes of the input surface 114 and the enclosure 102. In various embodiments, the crown assembly 110 is electrically isolated from the enclosure 102. This may prevent or mitigate signal interference between the electrodes, for example to allow separate measurements at each electrode.

The crown assembly 110 may include a rotation sensor 118 positioned within the interior volume 106 for detecting rotation of the actuation member 112. The rotation sensor 118 may include one or more light emitters and/or light detectors. The light emitter(s) may illuminate an encoder pattern or other rotating portion of the actuation member 112. The encoder pattern may be carried on (e.g., formed on, printed on, etc.) the crown shaft 112b or another component of the actuation member 112. The light detector(s) may receive light emitted by the light emitter(s) and reflected from the actuation member 112. The light detector(s) may be operably coupled to the processing unit 120, which may determine a direction of rotation, speed of rotation, angular position, translation, or other state(s) of the actuation member 112. In some embodiments, the rotation sensor 118 may detect rotation of the actuation member 112 by detecting rotation of the crown shaft 112b. The rotation sensor 118 may be electrically coupled to the processing unit 120 of the electronic device by a connector 128b.

As discussed above, the display 122 may be disposed at least partially within the enclosure 102. The display 122 provides a graphical output, for example associated with an operating system, user interface, and/or applications of the electronic device 100. In one embodiment, the display 122 includes one or more sensors and is configured as a touch-sensitive (e.g., single-touch, multi-touch) and/or force-sensitive display to receive inputs from a user. The display 122

is operably coupled to the processing unit **120** of the electronic device **100**, for example by a connector **128c**.

A graphical output of the display **122** may be responsive to inputs provided at the crown assembly **110**, the display **122**, and/or another input device **124**. For example, the processing unit **120** may be configured to modify the graphical output of the display **122** in response to determining an electrocardiogram, receiving rotational inputs, receiving translational inputs, or receiving touch inputs. The display **122** can be implemented with any suitable technology, including, but not limited to liquid crystal display (LCD) technology, light emitting diode (LED) technology, organic light-emitting display (OLED) technology, organic electroluminescence (OEL) technology, or another type of display technology. In some cases, the display **122** is positioned beneath and viewable through a cover sheet that forms at least a portion of the enclosure **102**.

Broadly, the input devices **124** may detect various types of input, and the output devices **126** may provide various types of output. The processing unit **120** may receive input signals from the input devices **124** in response to inputs detected by the input devices. The processing unit **120** may interpret input signals received from one or more of the input devices **124** and transmit output signals to one or more of the output devices **126**. The output signals may cause the output devices **126** to provide one or more outputs. Detected input at one or more of the input devices **124** may be used to control one or more functions of the device **100**. In some cases, one or more of the output devices **126** may be configured to provide outputs that are dependent on, or manipulated in response to, the input detected by one or more of the input devices **124**. The outputs provided by one or more of the output devices **126** may also be responsive to, or initiated by, a program or application executed by the processing unit **120** and/or an associated companion device.

In various embodiments, the input devices **124** may include any suitable components for detecting inputs. Examples of input devices **124** include audio sensors (e.g., microphones), optical or visual sensors (e.g., cameras, visible light sensors, or invisible light sensors), proximity sensors, touch sensors, force sensors, mechanical devices (e.g., crown assemblies, switches, buttons, or keys), vibration sensors, orientation sensors, motion sensors (e.g., accelerometers or velocity sensors), location sensors (e.g., global positioning system (GPS) devices), thermal sensors, communication devices (e.g., wired or wireless communication devices), resistive sensors, magnetic sensors, electroactive polymers (EAPs), strain gauges, electrodes, and so on, or some combination thereof. Each input device **124** may be configured to detect one or more particular types of input and provide a signal (e.g., an input signal) corresponding to the detected input. The signal may be provided, for example, to the processing unit **120**.

In some cases, the input devices **124** include set of one or more electrodes. An electrode may be a conductive portion of the device **100** that contacts or is configured to be in contact with a user. The electrodes may be disposed on one or more exterior surfaces of the device **100**, including a surface of the crown assembly **110**, the enclosure **102**, and the like. The processing unit **120** may monitor for voltages or signals received on at least one of the electrodes. In some embodiments, one of the electrodes may be permanently or switchably coupled to a device ground. The electrodes may be used to provide an electrocardiogram (ECG) function for the device **100**. For example, a 2-lead ECG function may be provided when a user of the device **100** contacts first and second electrodes that receive signals from the user. As

another example, a 3-lead ECG function may be provided when a user of the device **100** contacts first and second electrodes that receive signals from the user, and a third electrode that grounds the user to the device **100**. In both the 2-lead and 3-lead ECG embodiments, the user may press the first electrode against a first part of their body and press the second electrode against a second part of their body. The third electrode may be pressed against the first or second body part, depending on where it is located on the device **100**. In some cases, the enclosure **102** of the device **100** may function as an electrode. In some cases, input devices, such as buttons, crowns, and the like, may function as an electrode.

The output devices **126** may include any suitable components for providing outputs. Examples of output devices **126** include audio output devices (e.g., speakers), visual output devices (e.g., lights or displays), tactile output devices (e.g., haptic output devices), communication devices (e.g., wired or wireless communication devices), and so on, or some combination thereof. Each output device **126** may be configured to receive one or more signals (e.g., an output signal provided by the processing unit **120**) and provide an output corresponding to the signal.

The processing unit **120** may be operably coupled to the input devices **124** and the output devices **126**, for example by connectors **128d** and **128e**. The processing unit **120** may be adapted to exchange signals with the input devices **124** and the output devices **126**. For example, the processing unit **120** may receive an input signal from an input device **124** that corresponds to an input detected by the input device. The processing unit **120** may interpret the received input signal to determine whether to provide and/or change one or more outputs in response to the input signal. The processing unit **120** may then send an output signal to one or more of the output devices **126**, to provide and/or change outputs as appropriate. Example processing units are discussed below with respect to FIG. 7.

FIG. 2A shows an example of a watch **200** (e.g., an electronic watch or smart watch) that incorporates a switch module as described herein. The watch **200** may include a watch body **231** and a watch band **232**. Other devices that may incorporate a crown assembly include other wearable electronic devices, other timekeeping devices, other health monitoring or fitness devices, other portable computing devices, mobile phones (including smart phones), tablet computing devices, digital media players, or the like. The watch **200** may have similar components, structure, and/or functionality as the device **100** described with respect to FIG. 1.

The watch body **231** may include an enclosure **202**. The enclosure **202** may include a front side enclosure member that faces away from a user's skin when the watch **200** is worn by a user, and a back side enclosure member that faces toward the user's skin. Alternatively, the enclosure **202** may include a singular enclosure member, or more than two enclosure members. The one or more enclosure members may be metallic, plastic, ceramic, glass, or other types of enclosure members (or combinations of such materials).

The enclosure **202** may include a cover sheet **234** mounted to a front side of the watch body **231** (i.e., facing away from a user's skin) and may protect a display **222** mounted within the enclosure **102**. The display **222** may produce graphical output that may be viewable by a user through the cover sheet **234**. In some cases, the cover sheet **234** may be part of a display stack, which display stack may include a touch sensing or force sensing capability. The display may be configured to depict a graphical output of the

watch **200**, and a user may interact with the graphical output (e.g., using a finger, stylus, or other pointer). As one example, the user may select (or otherwise interact with) a graphic, icon, or the like presented on the display by touching or pressing (e.g., providing touch input) on the cover sheet **234** at the location of the graphic. As used herein, the term “cover sheet” may be used to refer to any transparent, semi-transparent, or translucent surface made out of glass, a crystalline material (such as sapphire or zirconia), plastic, or the like. Thus, it should be appreciated that the term “cover sheet,” as used herein, encompasses amorphous solids as well as crystalline solids. The cover sheet **234** may form a part of the enclosure **202**. In some examples, the cover sheet **234** may be a sapphire cover sheet. The cover sheet **234** may also be formed of glass, plastic, or other materials.

In some embodiments, the watch body **231** may include an additional cover sheet (not shown) that forms a part of the enclosure **202**. The additional cover sheet may have one or more electrodes thereon. For example, the watch body **231** may include an additional cover sheet mounted to a back side of the watch body **231** (i.e., facing toward a user’s skin). The one or more electrodes on the additional cover sheet may be used to determine a biological parameter, such as a heart rate, an electrocardiogram, or the like. In some cases, the electrodes are used in combination with one or more additional electrodes, such as a surface of a crown assembly or other input device.

The watch body **231** may include at least one input device or selection device, such as a crown assembly, scroll wheel, knob, dial, button, or the like, which input device may be operated by a user of the watch **200**. In some embodiments, the watch **200** includes a crown assembly **210** that includes an actuation member **212**. The enclosure **202** may define an opening through which the actuation member **212** extends. The actuation member **212** may be accessible to a user exterior to the enclosure **202**. The actuation member **212** may be user-rotatable, and may be manipulated (e.g., rotated, pressed) by a user. The actuation member **212** may be mechanically, electrically, magnetically, and/or optically coupled to components within the enclosure **202**, as one example. A user’s manipulation of the actuation member **212** may be used, in turn, to manipulate or select various elements displayed on the display, to adjust a volume of a speaker, to turn the watch **200** on or off, and so on.

The enclosure **202** may also include an opening through which a button **236** protrudes. The button **236** may be used to provide inputs to the watch **200**. In some embodiments, the actuation member **212**, scroll wheel, knob, dial, button **236**, or the like may be touch sensitive, conductive, and/or have a conductive surface, and a signal route may be provided between the conductive portion of the actuation member **212**, scroll wheel, knob, dial, button **236**, or the like and a circuit within the watch body **231**, such as a processing unit.

The enclosure **202** may include structures for attaching the watch band **232** to the watch body **231**. In some cases, the structures may include elongate recesses or openings through which ends of the watch band **232** may be inserted and attached to the watch body **231**. In other cases (not shown), the structures may include indents (e.g., dimples or depressions) in the enclosure **202**, which indents may receive ends of spring pins that are attached to or threaded through ends of a watch band to attach the watch band to the watch body. The watch band **232** may be used to secure the watch **200** to a user, another device, a retaining mechanism, and so on.

In some examples, the watch **200** may lack any or all of the cover sheet **234**, the display **222**, the crown assembly **210**, or the button **236**. For example, the watch **200** may include an audio input or output interface, a touch input interface, a force input or haptic output interface, or other input or output interface that does not require the display, crown assembly **210**, or button **236**. The watch **200** may also include the aforementioned input or output interfaces in addition to the display **222**, crown assembly **210**, or button **236**. When the watch **200** lacks the display, the front side of the watch **200** may be covered by the cover sheet **234**, or by a metallic or other type of enclosure member.

FIG. **2B** depicts a partial cross-sectional view of the example watch **200**, taken through section line A-A of FIG. **2A**. The crown assembly **210** may extend through an opening **204** in the enclosure **202**. The actuation member **212** may include a crown body **212a** positioned at least partially outside the enclosure **202** and a crown shaft **212b** extending through the opening **204** and positioned at least partially within the enclosure **202**. As shown, the crown body **212a** and the crown shaft **212b** may be formed as a unitary structure, though other actuation members may have different components and/or configurations, and may be defined by several different components that are attached together. The actuation member **212** may be formed from or include a conductive material (e.g., metal, carbon fiber, conductive polymer, conductive ceramics, or the like).

The crown assembly **210** may include a switch module **216** that is used to detect translational inputs to the crown assembly. The actuation member **212** may define an input surface **214** that users can touch to provide touch inputs or biological signals to the watch **200**. The actuation member **212** and the switch module **216** may form at least a portion of a conductive path **230** between the input surface **214** and the processing unit **220**. This may facilitate the transmission of inputs and/or signals from the input surface **214** to the processing unit **220**. The input surface **214** may be an electrically conductive surface. The electrical conductivity of the input surface **214** may facilitate a conductive path (e.g., conductive path **230**) from a user’s finger in contact with the input surface to other components of the electronic device.

The switch module **216** may include a conductive dome **240** and a friction guard **250** that is positioned between the conductive dome **240** and the actuation member **212** of the crown assembly **210**. The conductive dome **240** and/or the friction guard **250** may define at least a portion of the conductive path **230** from the input surface **214** to the processing unit **220**.

The conductive dome **240** and/or the friction guard **250** may provide an outward biasing force that maintains the actuation member in an unactuated position shown in FIG. **2B** absent an inward force on the actuation member. The outward biasing force may include a spring force exerted by the conductive dome **240** and/or the friction guard **250** on the actuation member **212**.

As noted herein, the crown assembly **210** may receive translational inputs that cause the actuation member **212** to translate inward from the unactuated position to an actuated position. FIG. **2C** depicts the actuation member **212** of the crown assembly **210** in the actuated position in response to a translational input on the actuation member **212**. A translational input may be provided to the crown assembly **210** in the form of an inward force F that overcomes the outward biasing force provided by the conductive dome **240** and/or the friction guard **250** and causes the actuation member **212** to translate inward to the actuated position shown in FIG.

2C. When the inward force *F* is removed or reduced, the outward biasing force may cause the actuation member **212** to return to the unactuated position shown in FIG. 2B.

The conductive dome **240** may collapse in response to the translational input moving the actuation member **212** from the unactuated position to the actuated position. As shown in FIG. 2B, when the actuation member **212** is in the unactuated position, the conductive dome **240** is in an uncollapsed configuration. As shown in FIG. 2C, when the actuation member **212** is in the actuated position, the conductive dome **240** is in a collapsed configuration.

At least a portion of the conductive dome **240** may be conductively coupled to a persistent electrical contact **260** that forms at least a portion of the conductive path **230** from the input surface **214** to the processing unit **220**. The persistent electrical contact **260** may be conductively coupled to the processing unit **220**, for example by a connector **228a**, to facilitate transmission of signals between the input surface **214** and the processing unit. The conductive dome **240** may be in direct contact with the persistent electrical contact **260**. The conductive dome **240** may contact the persistent electrical contact **260** while the conductive dome is in the uncollapsed configuration, the collapsed configuration, and positions therebetween so that the conductive coupling between the input surface **214** and the processing unit **220** may be maintained regardless of the position of the actuation member **212**.

As shown in FIG. 2C, in the collapsed configuration, the conductive dome **240** may contact a switch electrical contact **262**. The conductive dome **240** contacting the switch electrical contact **262** may conductively couple at least a portion of the conductive dome **240** to the switch electrical contact **262**, which may close a circuit to register a translational input. The circuit may include and/or be operably coupled to the processing unit **220**, for example via a connector **228b**.

In the uncollapsed configuration and/or the collapsed configuration, the conductive dome **240** may contact a reference electrical contact **264** that provides a bias voltage for detecting translational inputs and/or input signals at the input surface **214**. The reference electrical contact **264** may be operably coupled to the processing unit **220**, for example by a connector **228c**. The conductive dome **240** contacting the switch electrical contact **262** may close a circuit that includes the reference electrical contact **264**, which may register a translational input. The circuit may include and/or be operably coupled to the processing unit **220**, for example via connectors **228b** and **228c**.

The conductive dome **240** may be a unitary piece of conductive material that is able to collapse and return to an uncollapsed configuration thereafter. The conductive dome **240** may include multiple pieces, such as layers. In some cases, the conductive dome **240** is substantially homogeneous, meaning it has consistent materials throughout its entire volume. The conductive dome **240** may be formed of any suitable conductive material or combination of materials (e.g., metal, carbon fiber, conductive polymer, conductive ceramics, or the like).

The conductive dome **240** may define one or more conductive routes that are electrically isolated from one another. The conductive dome **240** may include vias or other structural elements for defining the isolated conductive routes. The conductive dome **240** may define a first conductive route between the friction guard **250** and the persistent electrical contact **260** that forms at least a portion of the conductive path **230**. The conductive dome **240** may define a second conductive route between the switch electrical contact **262** and the reference electrical contact **264** that

forms a part of the circuit for detecting translational inputs. The first and second conductive routes may be electrically isolated from one another to prevent signal interference. In some cases, the conductive dome **240** does not define separate conductive routes. That is to say, the conductive route between the friction guard **250** and the persistent electrical contact **260** that forms at least a portion of the conductive path **230** is not electrically isolated from the conductive route between the switch electrical contact **262** and the reference electrical contact **264** that forms a part of the circuit for detecting translational inputs.

The friction guard **250** may be positioned between the actuation member **212** and the conductive dome **240**, and may protect the conductive dome **240** or other components of the switch module **216** from damage resulting from contacting the actuation member **212**. For example, the friction guard **250** may protect the conductive dome **240** from shearing forces resulting from rotation of the actuation member **212**. As noted herein, the friction guard **250** may form part of the conductive path **230**. The friction guard **250** may be formed of any suitable conductive material or combination of materials (e.g., metal, carbon fiber, conductive polymer, conductive ceramics, or the like). In some cases, the friction guard **250** may be omitted or integrated with the conductive dome **240**.

As noted herein, the conductive dome **240** and/or the friction guard **250** may provide an outward biasing force that maintains the actuation member in an unactuated position shown in FIG. 2B. In embodiments in which the friction guard **250** provides at least a portion of the outward biasing force, the friction guard may include one or more flexures that provide the outward biasing force. As described in more detail below with respect to FIGS. 4A-5C, the friction guard **250** may maintain a gap between the friction guard and the conductive dome **240** when the actuation member **212** is in the unactuated position and/or for at least a portion of the transition to the actuated position such that the friction guard **250** provides the outward biasing force. During the transition from the unactuated position to the actuated position, the friction guard **250** may come into contact with the conductive dome **240** or otherwise cause the force exerted on the actuation member **212** to be transferred to the conductive dome **240**, thereby causing the dome to collapse.

The switch module **216** may include a switch housing **270** that at least partially surrounds one or more components of the switch module **216**. The housing **270** may define a recess **272** in which the conductive dome **240**, the friction guard **250**, and/or one or more of the electrical contacts **260**, **262**, **264** are positioned. The switch housing **270** may include a bracket or other fastening component for coupling the switch module **216** to the enclosure **202** or one or more other components of the electronic watch **200**. In some cases, the electrical contacts **260**, **262**, **264** may be encapsulated within the switch housing **270**. For example, the electrical contacts may be formed as part of a base of the switch housing **270** by injection molding.

As shown in FIG. 2B, the crown assembly **210** may include a rotation sensor **218** positioned along a side of the crown shaft **212b** or at another suitable location. The rotation sensor **218** may have similar structure or functionality as the rotation sensors discussed herein (e.g., rotation sensor **118**). The processing unit **220** may have similar structure or functionality as the processing units discussed herein (e.g., processing unit **120** of FIG. 1).

FIG. 3A shows an example switch module **316** for an electronic device. The switch module **316** may be part of a crown assembly (e.g., crown assembly **110**, **210**) for an

electronic device (e.g., electronic device 100, 200). The switch module 316 may include a housing 370 that defines an opening 375 through which an actuation member 312 may partially extend. The switch module 316 may detect movement of the actuation member 312 to detect translational inputs, and the switch module may define at least a portion of a conductive path between the actuation member 312 and a processing unit.

FIG. 3B shows an exploded view of the example switch module 316. As shown in FIG. 3B, the switch module 316 includes a conductive dome 340 and friction guard 350 that are positioned at least partially within a switch housing formed by a cover 374 and a base 376. The cover 374 may be coupled to the base 376. The base 376 may define a recess 372 in which a persistent electrical contact 360, a switch electrical contact 362, and a reference electrical contact 364 are located. The conductive dome 340 may be positioned in the recess 372. Each electrical contact 360, 362, 364 may be defined by and/or conductively coupled to a conductive member (e.g., conductive members 363, 365) that may contact a connector when the switch module 316 is installed in the electronic watch to conductively couple the respective electrodes to a processing unit or other circuitry. The switch electrical contact 362 may be positioned in a center region of the recess 372. The persistent electrical contact 360 and/or the reference electrical contact 364 may be positioned in a peripheral region of the recess 372 that surrounds the central region. The switch electrical contact 362 may contact a center portion of the conductive dome 340 when the conductive dome collapses. The persistent electrical contact 360 may contact a peripheral portion of the conductive dome 340 that surrounds the center portion.

The cover 374 and the base 376 may be formed of any suitable material or combination of materials, including metals, polymers, ceramics and the like. In some cases, the cover 374 is formed of a non-conductive material, such as a polymer, to electrically isolate the actuation member 312, the friction guard 350, and/or the conductive dome 340 from other components of the switch module 316 or the electronic device. The base 376 may include a non-conductive material, such as a polymer, surrounding conductive material, such as metal, that forms the electrical contacts 360, 362, 364, and/or the conductive members 363, 365. In some cases, the electrical contacts 360, 362, 364, and/or the conductive members 363, 365 are encapsulated within the base 376, for example by injection molding.

The switch housing 370 may include a bracket 378 for attaching the switch module 316 to the electronic watch. The bracket 378 may be formed of any suitable material or combination of materials, including metals, polymers, ceramics and the like. In some cases, the bracket 378 includes one or more metals, and the base 376 is attached to the bracket by molding the base around the bracket.

The cover 374 may define an opening 375 that the actuation member 312 may extend at least partially through. The cover 374 may extend around the actuation member 312. The cover 374 may retain the conductive dome 340 and/or the friction guard 350 within the recess 372. The friction guard 350 may be aligned with the opening such that the actuation member 312 contacts the friction guard. The friction guard 350 may include a recess 352 for receiving the actuation member 312 and preventing lateral movement of the actuation member.

FIGS. 3C and 3D are example cross-section views of the switch module 316, taken through section line B-B of FIG. 3A. FIG. 3C shows the actuation member 312 in an unactuated position and the conductive dome 340 in an uncol-

lapsed configuration. FIG. 3D shows the actuation member 312 in an actuated position and the conductive dome 340 in a collapsed configuration, for example in response to a force applied to the actuation member 312. The conductive dome 340 may provide an outward biasing force that maintains the actuation member 312 in the unactuated position absent an inward force on the actuation member.

As noted herein, the friction guard 350 and the conductive dome 340 may define at least a portion of a conductive path 330 from an input surface of the actuation member 312 to a processing unit 320 of the electronic device. The persistent electrical contact 360 may also define a portion of the conductive path 330 between the input surface of the actuation member 312 and the processing unit 320. As shown in FIGS. 3C and FIG. 3D, the conductive dome 340 contacts the persistent electrical contact 360 in the uncollapsed configuration and the collapsed configuration, such that the conductive path 330 is maintained whether the actuation member 312 is in the unactuated position or the actuated position. The persistent electrical contact 360 may be defined by and/or conductively coupled to a conductive member 361 that extends through the base 376. The conductive member 361 may be conductively coupled to the processing unit 320, for example by a connector 328a. As noted above, the persistent electrical contact 360 and/or the conductive member 361 may be encapsulated within the base 376, for example by injection molding.

As shown in FIG. 3C, when the actuation member 312 is in the unactuated position, the conductive dome 340 is in the uncollapsed configuration and the conductive dome does not contact the switch electrical contact 362. As shown in FIG. 3D, when the actuation member 312 is in the actuated position, for example in response to an inward force applied to the actuation member 312, the conductive dome 340 is in the collapsed configuration and contacts the switch electrical contact 362, which may close a circuit that includes the switch electrical contact 362 and the reference electrical contact 364 to register a translational input. The switch electrical contact 362 may be defined by and/or conductively coupled to a conductive member 363 that extends through the base 376. The conductive member 363 may be conductively coupled to the processing unit 320, for example by a connector 328b. The reference electrical contact 364 may be defined by and/or conductively coupled to a conductive member 365 that extends through the base 376. The conductive member 365 may be conductively coupled to the processing unit 320, for example by a connector 328c.

FIGS. 3E and 3F are example cross-section views of the switch module 316, taken through section line C-C of FIG. 3A. FIG. 3E shows the actuation member 312 in the unactuated position and the conductive dome 340 in the uncollapsed configuration. FIG. 3F shows the actuation member 312 in the actuated position and the conductive dome 340 in the collapsed configuration, for example in response to a force applied to the actuation member 312. As shown in FIG. 3E, when the actuation member 312 is in the unactuated position, the conductive dome 340 is in the uncollapsed configuration and the conductive dome does not contact the switch electrical contact 362. As shown in FIG. 3F, when the actuation member 312 is in the actuated position, for example in response to an inward force applied to the actuation member 312, the conductive dome 340 is in the collapsed configuration and contacts the switch electrical contact 362 to register a translational input.

FIGS. 4A-4C show an example switch module 416 for an electronic device. The switch module 416 may be part of a crown assembly (e.g., crown assembly 110, 210) for an

electronic device (e.g., electronic device 100, 200). FIG. 4A shows an exploded view of the switch module 416.

The switch module 416 may include a friction guard 450. As noted herein, the friction guard 450 may provide an outward biasing force that maintains the actuation member in an unactuated position. The friction guard 450 may include a translating portion 458 and one or more flexures 454 that allow the translating portion 458 to move relative to the switch housing. The friction guard 450 may be attached to the base 476 via a support member 456. The flexures 454 may extend from the support member 456 and at least partially surround the translating portion 458 of the friction guard 450. The translating portion 458 may be adapted to receive the actuation member 412. The actuation member 412 may contact the translating portion 458, and the translating portion may translate relative to the support member 456 and the base 476 to allow translation of the actuation member. The friction guard 450 may act as a spring, with the flexures 454 exerting a reaction force on the translating portion 458 (and therefore on the actuation member 412) that is dependent on the position of the translating portion. The spring dynamics of the friction guard 450 may be defined by the material properties, the thickness, and the length of the flexures 454. In some cases, as shown in FIG. 4A, the flexures 454 may be M-shaped flexures. This may allow the flexures to have a sufficient length to provide a desired outward biasing force while minimizing or reducing the size of the friction guard 450. Minimizing or reducing the size of the friction guard may reduce the size of the switch module 416, which may reduce a size of a device that the switch module is installed in.

As described herein, the friction guard 450 may define at least a portion of a conductive path from the actuation member 412 to a processing unit. In some cases, the flexures 454 may define a portion of the conductive path. For example, the actuation member 412 may contact the translating portion 458 of the friction guard, and a conductive path may extend from the translating portion 458, through one or both flexures 454, and through the support member 456 to a conductive member 460 extending from the support member 456. The conductive member 460 may be conductively coupled to a connector that is conductively coupled to a processing unit or another circuit of the electronic device.

The switch module 416 may include a housing 470 that includes a base 476 and a bracket 478 for attaching the switch module 416 to the electronic device. The base 476 may define a recess 472, and a conductive dome 440 may be positioned in the recess. A switch electrical contact 462 and a reference electrical contact 464 for detecting translational inputs may be positioned at least partially in the recess 472. Each electrical contact 462, 464 may be defined by and/or conductively coupled to a conductive member 463, 465 that may contact a connector when the switch module 416 is installed in the electronic watch to conductively couple the respective electrical contacts to a processing unit or other circuitry.

The housing 470 may include a flexible cover 480 attached to the base using an adhesive 484 (e.g., a pressure-sensitive adhesive or heat-sensitive adhesive). The flexible cover 480 and/or a spacer 482 may electrically isolate the friction guard 450 and the conductive dome 440 so that signals related to sensing translational inputs at the conductive dome 440 do not interfere with signals from the actuation member 412 being transmitted through the friction guard 450.

The base 476 may be formed of any suitable material or combination of materials, including metals, polymers,

ceramics and the like. The base 476 may include a non-conductive material, such as a polymer, surrounding conductive material, such as metal, that forms the electrical contacts 462, 464, and/or the conductive members 463, 465. In some cases, the electrical contacts 462, 424, and/or the conductive members 463, 465 are encapsulated within the base 476, for example by injection molding.

FIGS. 4B and 4C are example cross-section views of the switch module 416. FIG. 4B shows the actuation member 412 in an unactuated position and the friction guard 450 and the conductive dome 440 in an uncollapsed configuration. FIG. 4C shows the actuation member 412 in an actuated position and the friction guard 450 and the conductive dome 440 in a collapsed configuration, for example in response to a force applied to the actuation member 412. The friction guard 450 may provide an outward biasing force that maintains the actuation member 412 in the unactuated position shown in FIG. 4B absent an inward force on the actuation member.

The friction guard 450 may maintain a gap 490 between the friction guard and the conductive dome 440 when the actuation member 412 is in the unactuated position and/or for at least a portion of the transition to the actuated position such that the friction guard provides the outward biasing force on the actuation member 412. During the transition from the unactuated position to the actuated position, the friction guard 450 may come into contact with the spacer 482 or otherwise cause the force exerted on the actuation member 412 to be transferred to the conductive dome 440, thereby causing the dome to collapse.

As shown in FIGS. 4B and 4C, the conductive path 430 may be maintained when the actuation member 412 is in the unactuated position, the actuated position, and positions therebetween. The friction guard 450 may be conductively coupled to the processing unit, for example by a connector 428a. The conductive path 430 may be electrically isolated from the conductive dome so that signals used to detect translational inputs do not interfere with the signals from the actuation member 412.

As shown in FIG. 4B, when the actuation member 412 is in the unactuated position, the conductive dome 440 is in the uncollapsed configuration and the conductive dome does not contact the switch electrical contact 462. As shown in FIG. 4C, when the actuation member 412 is in the actuated position, for example in response to an inward force applied to the actuation member 412, the conductive dome 440 is in the collapsed configuration and contacts the switch electrical contact 462, which may close a circuit that includes the switch electrical contact 462 and the reference electrical contact 464 to register a translational input. The switch electrical contact 462 may be defined by and/or conductively coupled to a conductive member 463 that extends through the base 476. The conductive member 463 may be conductively coupled to the processing unit 420, for example by a connector 428b. The reference electrical contact 464 may be defined by and/or conductively coupled to a conductive member 465 that extends through the base 476. The conductive member 465 may be conductively coupled to the processing unit 420, for example by a connector 428c.

FIGS. 5A-5C show an example switch module 516 for an electronic device. The switch module 516 may be part of a crown assembly (e.g., crown assembly 110, 210) for an electronic device (e.g., electronic device 100, 200). FIG. 5A shows an exploded view of the switch module 516. FIG. 5B is a first example cross-section view of the switch module 516. FIG. 5C is a second example cross-section view of the switch module 516.

The switch module **516** may include a friction guard **550**. Similar to the friction guard **450** discussed with respect to FIGS. **4A-4C**, the friction guard **550** may provide an outward biasing force that maintains the actuation member **512** in an unactuated position. The friction guard **550** may act as a spring, and may include one or more flexures **554** that define the spring dynamics of the friction guard. The friction guard **550** may be attached to the base **576** via support members **555a**, **555b**. Each flexure **554** may extend from a support member **555a**, **555b** and at least partially surround a translating portion **558** of the friction guard **550**. The actuation member **512** may contact the translating portion **558**, and the translating portion may translate relative to the support members **555a**, **555b** and the base **576** to allow translation of the actuation member. The spring dynamics of the friction guard **550** may be defined by the material properties, the thickness, and the length of the flexures **554**. In some cases, as shown in FIG. **5A**, the flexures **554** may be U-shaped flexures. This may allow the flexures **554** to have a sufficient length to provide a desired outward biasing force while minimizing or reducing the size of the friction guard **550**. Minimizing or reducing the size of the friction guard **550** may reduce the size of the switch module **516**, which may reduce a size of a device that the switch module is installed in.

As shown in FIGS. **5B** and **5C**, the friction guard **550** may define at least a portion of a conductive path **530** from the actuation member **512** to a processing unit **520**. In some cases, one or more of the flexures **554** may define a portion of the conductive path. For example, the actuation member **512** may contact the translating portion **558** of the friction guard, and the conductive path **530** may extend from the translating portion **558**, through a flexure **554**, and through the support member **555a**. The support member **555a** may be conductively coupled to a persistent electrical contact **560** that is defined by and/or conductively coupled to a conductive member **561** that may be conductively coupled to the processing unit **520** or another circuit of the electronic device.

The switch module **516** may include a housing **570** that includes a base **576** and a bracket **578** for attaching the switch module **516** to the electronic device. The base **576** may define a recess **572**, and a conductive dome **540** may be positioned in the recess. A switch electrical contact **562** and reference electrical contacts **564a-d** for detecting translational inputs may be positioned at least partially in the recess **572**. In some cases, the persistent electrical contact **560** and the switch electrical contact **562** may share a common conductive member (e.g., conductive member **561**) such that they are conductively coupled to one another. As shown in FIGS. **5A** and **5B**, the switch electrical contact **562** and the persistent electrical contact **560** may be conductively coupled to the processing unit **520** via the conductive member **561** and the connector **528a**. This may reduce a number of conductive paths from the switch module **516** to the processing unit **520**. Each electrical contact **564a-d** may be defined by and/or conductively coupled to a conductive member **565** that may contact a connector when the switch module **516** is installed in the electronic watch to conductively couple the electrical contact to a processing unit or other circuitry.

In some cases, the persistent electrical contact **560** and the switch electrical contact **562** may have separate conductive members that are electrically isolated from one another. As shown in FIG. **5C**, the persistent electrical contact **560** may be defined by and/or conductively coupled to the conductive member **561**, which is conductively coupled to the process-

ing unit **520** via the connector **528a**. The switch electrical contact **562** may be defined by and/or conductively coupled to a conductive member **563**, which is conductively coupled to the processing unit **520** via a connector **528b**.

As shown in FIGS. **5A-5C**, a switch module may have a friction guard and a conductive dome that are separate components. In some embodiments, the friction guard and the conductive dome of a switch module may be formed as a single component. FIGS. **6A-6B** show an example switch module **616** for an electronic device in which a conductive dome **640** and a friction guard **650** are formed as a single component. Forming the conductive dome **640** and the friction guard **650** as a single component may reduce the size of the switch module **616**, which may reduce a size of a device that the switch module is installed in and may simplify manufacturing by reducing a number of components. The switch module **616** may be part of a crown assembly (e.g., crown assembly **110**, **210**) for an electronic device (e.g., electronic device **100**, **200**). FIG. **6A** shows an exploded view of the switch module **616**. FIG. **6B** is an example cross-section view of the switch module **616**. The switch module **616** may be similar to the switch module **516** discussed with respect to FIGS. **5A-5C**.

As shown in FIG. **6B**, the conductive dome **640** and friction guard **650** may define at least a portion of a conductive path **630** from an actuation member **612** to a processing unit **620**. The conductive dome **640** and friction guard **650** may provide an outward biasing force that maintains the actuation member **612** in an unactuated position.

The conductive dome **640** may be positioned in a recess **672** of a base **676** of the switch module **616**. The conductive dome **640** may contact persistent electrical contacts **660a-d**, one or more of which form at least a portion of the conductive path **630**. Each persistent electrical contact **660a-d** may be defined by and/or conductively coupled to a conductive member **661**, which is conductively coupled to the processing unit **620** via a connector **628a**. The conductive dome **640** may be configured to collapse in response to a translational movement of the actuation member **612**, causing the conductive dome to contact a switch electrical contact **662** to register a translational input. The switch electrical contact may be defined by and/or conductively coupled to a conductive member **663**, which is conductively coupled to the processing unit **620** via a connector **628b**.

FIG. **7** shows a sample electrical block diagram of an electronic device **700** that may incorporate a switch module. The electronic device may in some cases take the form of any of the electronic devices described with reference to FIGS. **1-6B**, or other portable or wearable electronic devices. The electronic device **700** can include a display **712** (e.g., a light-emitting display), a processing unit **702**, a power source **714**, a memory **704** or storage device, an input device **706** (e.g., a crown assembly), and an output device **710**.

The processing unit **702** can control some or all of the operations of the electronic device **700**. The processing unit **702** can communicate, either directly or indirectly, with some or all of the components of the electronic device **700**. For example, a system bus or other communication mechanism **716** can provide communication between the processing unit **702**, the power source **714**, the memory **704**, the input device(s) **706**, and the output device(s) **710**.

The processing unit **702** can be implemented as any electronic device capable of processing, receiving, or transmitting data or instructions. For example, the processing unit **702** can be a microprocessor, a central processing unit

(CPU), an application-specific integrated circuit (ASIC), a digital signal processor (DSP), or combinations of such devices. As described herein, the term “processing unit” is meant to encompass a single processor or processing unit, multiple processors, multiple processing units, or other suitably configured computing element or elements.

It should be noted that the components of the electronic device 700 can be controlled by multiple processing units. For example, select components of the electronic device 700 (e.g., an input device 706) may be controlled by a first processing unit and other components of the electronic device 700 (e.g., the display 712) may be controlled by a second processing unit, where the first and second processing units may or may not be in communication with each other. In some cases, the processing unit 702 may determine a biological parameter of a user of the electronic device, such as an ECG for the user.

The power source 714 can be implemented with any device capable of providing energy to the electronic device 700. For example, the power source 714 may be one or more batteries or rechargeable batteries. Additionally or alternatively, the power source 714 can be a power connector or power cord that connects the electronic device 700 to another power source, such as a wall outlet.

The memory 704 can store electronic data that can be used by the electronic device 700. For example, the memory 704 can store electrical data or content such as, for example, audio and video files, documents and applications, device settings and user preferences, timing signals, control signals, and data structures or databases. The memory 704 can be configured as any type of memory. By way of example only, the memory 704 can be implemented as random access memory, read-only memory, Flash memory, removable memory, other types of storage elements, or combinations of such devices.

In various embodiments, the display 712 provides a graphical output, for example associated with an operating system, user interface, and/or applications of the electronic device 700. In one embodiment, the display 712 includes one or more sensors and is configured as a touch-sensitive (e.g., single-touch, multi-touch) and/or force-sensitive display to receive inputs from a user. For example, the display 712 may be integrated with a touch sensor (e.g., a capacitive touch sensor) and/or a force sensor to provide a touch-and/or force-sensitive display. The display 712 is operably coupled to the processing unit 702 of the electronic device 700.

The display 712 can be implemented with any suitable technology, including, but not limited to liquid crystal display (LCD) technology, light emitting diode (LED) technology, organic light-emitting display (OLED) technology, organic electroluminescence (OEL) technology, or another type of display technology. In some cases, the display 712 is positioned beneath and viewable through a cover that forms at least a portion of an enclosure of the electronic device 700.

In various embodiments, the input devices 706 may include any suitable components for detecting inputs. Examples of input devices 706 include audio sensors (e.g., microphones), optical or visual sensors (e.g., cameras, visible light sensors, or invisible light sensors), proximity sensors, touch sensors, force sensors, mechanical devices (e.g., crowns, switches, buttons, or keys), vibration sensors, orientation sensors, motion sensors (e.g., accelerometers or velocity sensors), location sensors (e.g., global positioning system (GPS) devices), thermal sensors, communication devices (e.g., wired or wireless communication devices),

resistive sensors, magnetic sensors, electroactive polymers (EAPs), strain gauges, electrodes, and so on, or some combination thereof. Each input device 706 may be configured to detect one or more particular types of input and provide a signal (e.g., an input signal) corresponding to the detected input. The signal may be provided, for example, to the processing unit 702.

As discussed above, in some cases, the input device(s) 706 include a touch sensor (e.g., a capacitive touch sensor) integrated with the display 712 to provide a touch-sensitive display. Similarly, in some cases, the input device(s) 706 include a force sensor (e.g., a capacitive force sensor) integrated with the display 712 to provide a force-sensitive display.

The output devices 710 may include any suitable components for providing outputs. Examples of output devices 710 include audio output devices (e.g., speakers), visual output devices (e.g., lights or displays), tactile output devices (e.g., haptic output devices), communication devices (e.g., wired or wireless communication devices), and so on, or some combination thereof. Each output device 710 may be configured to receive one or more signals (e.g., an output signal provided by the processing unit 702) and provide an output corresponding to the signal.

In some cases, input devices 706 and output devices 710 are implemented together as a single device. For example, an input/output device or port can transmit electronic signals via a communications network, such as a wireless and/or wired network connection. Examples of wireless and wired network connections include, but are not limited to, cellular, Wi-Fi, Bluetooth, IR, and Ethernet connections.

The processing unit 702 may be operably coupled to the input devices 706 and the output devices 710. The processing unit 702 may be adapted to exchange signals with the input devices 706 and the output devices 710. For example, the processing unit 702 may receive an input signal from an input device 706 that corresponds to an input detected by the input device 706. The processing unit 702 may interpret the received input signal to determine whether to provide and/or change one or more outputs in response to the input signal. The processing unit 702 may then send an output signal to one or more of the output devices 710, to provide and/or change outputs as appropriate.

The foregoing description, for purposes of explanation, uses specific nomenclature to provide a thorough understanding of the described embodiments. However, it will be apparent to one skilled in the art that the specific details are not required in order to practice the described embodiments. Thus, the foregoing descriptions of the specific embodiments described herein are presented for purposes of illustration and description. They are not targeted to be exhaustive or to limit the embodiments to the precise forms disclosed. It will be apparent to one of ordinary skill in the art that many modifications and variations are possible in view of the above teachings.

Although the disclosure above is described in terms of various exemplary embodiments and implementations, it should be understood that the various features, aspects and functionality described in one or more of the individual embodiments are not limited in their applicability to the particular embodiment with which they are described, but instead can be applied, alone or in various combinations, to one or more of the some embodiments of the invention, whether or not such embodiments are described and whether or not such features are presented as being a part of a described embodiment. Thus, the breadth and scope of the present invention should not be limited by any of the

above-described exemplary embodiments but is instead defined by the claims herein presented.

One may appreciate that although many embodiments are disclosed above, that the operations and steps presented with respect to methods and techniques described herein are meant as exemplary and accordingly are not exhaustive. One may further appreciate that alternate step order or fewer or additional operations may be required or desired for particular embodiments.

As used herein, the phrase “at least one of” preceding a series of items, with the term “and” or “or” to separate any of the items, modifies the list as a whole, rather than each member of the list. The phrase “at least one of” does not require selection of at least one of each item listed; rather, the phrase allows a meaning that includes at a minimum one of any of the items, and/or at a minimum one of any combination of the items, and/or at a minimum one of each of the items. By way of example, the phrases “at least one of A, B, and C” or “at least one of A, B, or C” each refer to only A, only B, or only C; any combination of A, B, and C; and/or one or more of each of A, B, and C. Similarly, it may be appreciated that an order of elements presented for a conjunctive or disjunctive list provided herein should not be construed as limiting the disclosure to only that order provided.

As described above, one aspect of the present technology is determining electrocardiograms, and the like. The present disclosure contemplates that in some instances this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, twitter IDs (or other social media aliases or handles), home addresses, data or records relating to a user’s health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to provide haptic or audiovisual outputs that are tailored to the user. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user’s general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can

subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (“HIPAA”); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of determining spatial parameters, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services or anytime thereafter. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user’s privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data at a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, haptic outputs may be provided based on non-personal information data or a bare minimum amount of personal information, such as events or states at the device associated with a user, other non-personal information, or publicly available information.

What is claimed is:

1. An electronic watch comprising:
 - a display;
 - a cover over the display;
 - an enclosure coupled to the cover and at least partially enclosing the display;
 - a crown assembly comprising:
 - an actuation member extending through an opening in the enclosure and comprising a knob positioned

23

along an exterior side of the enclosure, the knob defining an input surface configured to receive a user input thereon;

a collapsible dome positioned at an end of the actuation member and configured to collapse in response to a translational input at the actuation member; and

a friction guard positioned between the end of the actuation member and the collapsible dome; and

a processing system within the enclosure and conductively coupled to the input surface of the knob via a conductive path extending through the collapsible dome, the friction guard, and the actuation member, the conductive path persisting when the collapsible dome is collapsed and when the collapsible dome is uncollapsed.

2. The electronic watch of claim 1, wherein: the crown assembly further comprises a switch housing; the collapsible dome is coupled to the switch housing; and the crown assembly further comprises a conductive member at least partially encapsulated in the switch housing, the conductive path further extending through the conductive member.

3. The electronic watch of claim 2, wherein: the conductive member is a first conductive member; the first conductive member is conductively coupled to the collapsible dome when the collapsible dome is collapsed and when the collapsible dome is uncollapsed; the crown assembly further comprises a second conductive member; the collapsible dome is conductively coupled to the second conductive member when the collapsible dome is collapsed; and the collapsible dome is conductively decoupled from the second conductive member when the collapsible dome is uncollapsed.

4. The electronic watch of claim 3, wherein the second conductive member is at least partially encapsulated in the switch housing.

5. The electronic watch of claim 1, wherein the processing system is configured to determine a biological parameter of a user based at least in part on a voltage detected at the input surface via the conductive path.

6. The electronic watch of claim 1, wherein the friction guard is configured to impart a biasing force to the actuation member to bias the actuation member towards an unactuated position.

7. The electronic watch of claim 6, wherein: the biasing force is a first biasing force; and the collapsible dome is configured to impart a second biasing force to the actuation member to bias the actuation member towards the unactuated position.

8. A wearable electronic device comprising: an enclosure at least partially defining an internal volume; an input assembly configured to receive a rotational input and a translational input and comprising: a body portion external to the enclosure and defining an input surface; and a shaft extending from the body portion through a hole defined in the enclosure;

a collapsible dome positioned in the internal volume and configured to transition from an uncollapsed state to a collapsed state in response to the translational input and configured to remain conductively coupled to the shaft when the collapsible dome is in the uncollapsed state and the collapsed state; and

24

a processing system within the internal volume and conductively coupled to the input surface via a conductive path through the collapsible dome, the shaft, and the body portion, the processing system configured to determine a biological parameter of a user based at least in part on a voltage detected at the input surface.

9. The wearable electronic device of claim 8, wherein the wearable electronic device is a watch.

10. The wearable electronic device of claim 8, wherein the wearable electronic device further comprises a friction guard defining an interposing portion positioned between the shaft and the collapsible dome.

11. The wearable electronic device of claim 10, wherein the friction guard conductively couples the shaft to the collapsible dome when the collapsible dome is in the uncollapsed state and the collapsed state.

12. The wearable electronic device of claim 10, wherein: the wearable electronic device further comprises a switch housing positioned in the internal volume; the collapsible dome is coupled to the switch housing; and the friction guard is coupled to the switch housing.

13. The wearable electronic device of claim 12, further comprising a conductive member at least partially encapsulated in the switch housing and defining at least a portion of the conductive path.

14. The wearable electronic device of claim 12, wherein: the friction guard further includes a flexure coupling the interposing portion to the switch housing; the flexure is configured to impart a biasing force on the shaft via the interposing portion; and the biasing force biases the input assembly towards an unactuated position.

15. A wearable electronic device comprising: an enclosure; an actuation member coupled to the enclosure and configured to receive a rotational input and a translational input, the actuation member comprising: a knob external to the enclosure; and a shaft coupled to the knob and extending through a hole defined in the enclosure;

a conductive dome positioned at an end of the shaft and configured to transition from an uncollapsed state to a collapsed state in response to a translational input applied to the knob; and

a friction guard positioned between the shaft and the conductive dome and conductively coupling the shaft to the conductive dome when the conductive dome is in the uncollapsed state and when the conductive dome is in the collapsed state.

16. The wearable electronic device of claim 15, further comprising a processing system at least partially within the enclosure and configured to determine a biological parameter of a user based at least in part on a voltage detected at an input surface of the knob via a conductive path extending through the knob, the shaft, the conductive dome, and the friction guard.

17. The wearable electronic device of claim 16, wherein the processing system is configured to determine the biological parameter when the conductive dome is in the collapsed state and when the conductive dome is in the uncollapsed state.

18. The wearable electronic device of claim 15, further comprising a switch housing at least partially within the enclosure and comprising: a body; and a conductive member coupled to the body and configured to conductively couple to the conductive dome when

the conductive dome is in the collapsed state and when the conductive dome is in the uncollapsed state.

19. The wearable electronic device of claim 18, wherein: the conductive member is a first conductive member; the switch housing further comprises a second conductive member coupled to the body; and the conductive dome is configured to conductively couple to the second conductive member in response to the collapse of the conductive dome. 5

20. The wearable electronic device of claim 19, wherein: the switch housing further comprises a third conductive member coupled to the body and configured to conductively couple to the conductive dome when the conductive dome is in the collapsed state and when the conductive dome is in the uncollapsed state; and a bias voltage is provided to the conductive dome via the third conductive member. 15

* * * * *