



(22) Date de dépôt/Filing Date: 2005/11/14

(41) Mise à la disp. pub./Open to Public Insp.: 2006/05/15

(45) Date de délivrance/Issue Date: 2018/09/11

(62) Demande originale/Original Application: 2 526 668

(30) Priorités/Priorities: 2004/11/15 (US60/627,866);
2005/05/10 (US11/126,006)

(51) Cl.Int./Int.Cl. *A47K 10/44* (2006.01)

(72) Inventeurs/Inventors:

CITTADINO, ANTONIO M., US;
MARONEY, DAVID R., US;
BURNS, BRENT J., US;
KISSINGER, KARL D., US;
KIRKPATRICK, ANDY L., US;
KILGORE, MICHAEL R., US;
BUDZ, GREGORY D., US


(73) Propriétaire/Owner:

GPCP IP HOLDINGS LLC, US

(74) Agent: NORTON ROSE FULBRIGHT CANADA
LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : DISTRIBUTEUR DE SERVIETTES DE TABLE A GRANDE CAPACITE

(54) Title: HIGH CAPACITY NAPKIN DISPENSER



(57) Abrégé/Abstract:

A kit with a locking faceplate for mounting on a napkin dispenser housing comprises a mounting bracket, means for securing the mounting bracket to the dispenser housing and a faceplate with an elongate aperture. Hinge means are used for pivotally mounting the faceplate to the mounting bracket such that it is movable between a closed position for dispensing a stack of napkins and an open position for reloading. Means lock the faceplate in the closed position, the locking means being operable to lock the faceplate to the mounting bracket in the closed position and including release means for unlocking the faceplate located adjacent an inner surface of the faceplate such that when the faceplate is in the closed position on a dispenser the release means is concealed in the interior of the dispenser and accessible through the dispensing aperture.

ABSTRACT

A kit with a locking faceplate for mounting on a napkin dispenser housing comprises a mounting bracket, means for securing the mounting bracket to the dispenser housing and a faceplate with an elongate aperture. Hinge means are used for pivotally mounting the faceplate to the mounting bracket such that it is movable between a closed position for dispensing a stack of napkins and an open position for reloading. Means lock the faceplate in the closed position, the locking means being operable to lock the faceplate to the mounting bracket in the closed position and including release means for unlocking the faceplate located adjacent an inner surface of the faceplate such that when the faceplate is in the closed position on a dispenser the release means is concealed in the interior of the dispenser and accessible through the dispensing aperture.

HIGH CAPACITY NAPKIN DISPENSER

5

Technical Field

The present invention relates generally to napkin dispensers and in a preferred embodiment to an in-counter, high capacity napkin dispenser with an injection-molded faceplate having a concealed latch accessible through its
10 dispensing aperture.

Background

Napkin dispensers are well known in the art. There is disclosed in United States Patent No. 4,311,252 to *Hope, Jr. et al.*, a large capacity elevator-type
15 napkin dispenser comprising an elongated supporting structure or cage composed of a series of spaced rod-like vertical supports. A stack of folded napkins is supported on a pressure plate that is mounted on a carriage adapted to slide vertically within the cage. The pressure plate is supported from the carriage by a plurality of compression springs which enable the pressure plate to float and
20 accommodate the varying thickness of the stack of folded napkins. A cover is mounted on the upper end of the cage and has an opening through which the napkins are dispensed. The pressure plate and stack of napkins are urged upwardly toward the undersurface of the cover by a biasing mechanism that includes a pair of extension springs. The springs have a varying spring rate so that
25 the force of the springs will be greatest when the pressure plate is fully loaded with napkins.

Radek discloses another vertically oriented napkin dispenser in United States Patent No. 4,094,442 wherein there is shown a napkin dispenser for
30 disposition on a restaurant table or counter and normally housing a stack of paper napkins. The dispenser is in the form of a parallelepiped with a top access opening

for loading and removing napkins. The opening is generally rectangular except for a concavely arcuate edge on one side from which napkins are normally extracted. Two opposed sides of the opening normal to the arcuate edge are provided with a pair of relatively narrow spring biased leaves resiliently extendable into the
5 container to facilitate loading, the free edges of said leaves being longitudinally gently oblique and widening toward the aforesaid arcuate edge. Each of said leaves has a longitudinal outwardly turned lip and the exposed corners of the leaves are rounded. All of said features contribute toward convenient extraction of a napkin without damage. *See also*, United States Patent No. 4,343,415, also to
10 *Radek*.

Further features of napkin and towel dispensers are seen in the following: EPO Application 0 101 287 of *Evans*; United States Patent No. 4,329,001 of *Filipowicz et al.*; United States Patent No. 2,840,268 of *Casey et al.*; United States
15 Patent No. 4,155,484 of *Pastore*; United States Patent No. 5,156,293 of *Petterson et al.*; and United States Patent No. 5,964,375 of *Carlson et al.*

Despite advances in the art, many issues with dispensers remain unresolved. For one, most napkin dispensers do not have a large capacity and
20 need to be re-filled frequently adding to labor costs and/or causing consumer inconvenience. Moreover, it is desirable to lock dispensers so that they cannot be opened by unauthorized personnel; however, keys get lost. It will be appreciated from the foregoing patents that existing dispensers are relatively expensive to fabricate and install especially when made of multiple parts including metal parts
25 requiring multiple fasteners, springs, brackets and the like.

Existing high capacity napkin dispenser are also oftentimes difficult to reload. When the cover is open, the napkins are not sufficiently retained within the dispenser such that a technician must exercise considerable skill in order to
30 refill the dispenser without assistance or damaging product.

Still yet other issues include reliably feeding the napkins to the dispensing aperture without damaging the product by way of tearing, or jamming of the dispenser as will be appreciated by one of skill in the art.

5 Summary of the Invention

 The present invention provides an improved high capacity napkin dispenser with multiple features which provide for superior operation. The inventive features include a sequestered locking mechanism which is easy to operate and which is hidden within the dispenser such that a technician with
10 knowledge of its operation can readily unlock the dispenser without the need for a key. Another aspect of the invention includes gripping surfaces adjacent the faceplate so that a stack of napkins can be retained within the dispenser while the face plate is open, yet the gripping surfaces will not interfere with feeding product to the aperture when the faceplate is closed. Preferably, the gripping surfaces are
15 bowed surfaces which facilitate feeding product to the aperture of the dispenser as illustrated in the appended drawings and described herein.

 Still yet another aspect of the present invention is an injection molded construction which dramatically reduces the cost of high capacity dispensers,
20 providing an order of magnitude reduction in cost. A high capacity dispenser of the invention may be produced for as little as 15-30 dollars as opposed to 150-250 dollars and more for conventional products of similar capacity. Such dramatic cost reductions are achieved by providing identical panels for defining the storage chamber, as well as, for example, identical plates for holding a biasing spring, as
25 well as, for example, utilizing molded-in label technology to provide for a suitable appearance. Injection-molded parts and panels with molded-in assembly features make it possible to greatly reduce assembly complexity. Still yet other features and advantages of the present invention will become apparent from the discussion which follows.

There is provided in a first aspect of the invention a large capacity napkin dispenser comprising: (a) an elongate housing defining a storage chamber with a generally rectangular cross-section for receiving a stack of napkins ; (b) a faceplate with a dispensing aperture extending between a first and a second side of the dispenser, the faceplate being hinged to the housing at the first side so as to be movable between an open position for re-loading and a closed position for dispensing, the faceplate having an outer surface and an inner surface which is inside the dispenser when the faceplate is in the closed position; (c) a movable support member mounted in the housing; (d) biasing means for urging the movable support toward the faceplate so that the stack of napkins is advanced to the aperture as it is depleted; and (e) means for locking the faceplate in the closed position, the locking means being operable to lock the faceplate to the second side of the dispenser in the closed position and includes release means located adjacent the inner surface of the faceplate such that when the faceplate is in the closed position the release means is concealed in the interior of the dispenser and accessible through the dispensing aperture. In a preferred embodiment the faceplate is hinged to a mounting bracket secured to the housing and the release means of the locking means is located adjacent one end of the dispensing aperture. Especially preferred are constructions wherein the locking means includes an injection-molded unitary latch including both an integrally formed spring and a latch member. The injection-molded unitary latch is formed from an injection-molding composition comprising nylon, polyacetal or polyester.

The faceplate preferably has a plurality of guide ridges at its inner surface and the injection-molded unitary latch has a pair of spring arms configured to engage a guide ridge. The unitary latch is provided with a beveled edge in preferred constructions to facilitate operation of the dispenser, while the faceplate is perhaps most preferably integrally formed by injection-molding and includes a plurality of guide ridges at its inner surface. The guide ridges comprise triangular guide ridges having a profile inclined toward the dispensing aperture so as to guide the napkin stack thereto. In a preferred embodiment the guide ridges extend

progressively further from the inner surface of the faceplate with increasing distance from the aperture thereby flaring away from the aperture. The guide ridges may be further characterized in that: (i) the guide ridges are generally orthogonal to an elongate axis of the dispensing aperture; and (ii) the guide ridges are generally parallel to an axis of the storage chamber when the faceplate the closed position. Suitable materials for the faceplate include an injection-molding composition comprising an acrylonitrile-butadiene-styrene resin or injection-molding compositions comprising an acrylic resin or a polycarbonate resin.

10 The housing is also preferably made by way of injection-molding, including injection-molding at least two panels having molded-in features for joining the panels to each other. These panels are made from an injection-molding composition comprising an acrylonitrile-butadiene-styrene resin or these panels are made from an injection-molding composition comprising an acrylic resin or a polycarbonate resin. A particularly cost effective method of manufacturing the dispenser is wherein the generally rectangular storage chamber has sidewalls defined by two substantially identical U-shaped channel members molded from a polymer composition as noted above. The housing is vertically oriented when the dispenser is an in-counter dispenser and is sized to accommodate at least about 1,000 single-fold napkins.

Another feature of the present invention which makes the dispenser particularly cost effective includes a construction wherein a helical spring is secured to two substantially identical plates which are molded from a polymer composition in order to provide biasing means to advance the napkins to the dispensing aperture. Preferably, the substantially identical plates include molded-in locking means for securing the helical spring. A particularly preferred construction is wherein the helical spring has at its extremities two end portions which project radially inwardly with respect to the axis of the spring and the plates each include molded-in quick lock features for securing the spring thereto without other hardware. This feature eliminates the need for additional screws, brackets

and so forth as well as greatly reduce fabrication labor required to produce the dispenser. The quick lock feature is perhaps most preferably achieved by including a radial hook with a radial locking finger extending radially outwardly with respect to the axis of the helical spring and a tangential hook with a locking
5 finger extending tangentially with respect to the coils of the helical spring. The tangential hooks have locking protuberances on surfaces thereof opposed to their respective plates in order to secure the spring and to hinder rotation of the spring with respect to the plates to which the spring is secured. Optionally included are a plurality of positioning posts for positioning the spring with respect to the plates
10 in addition to the hooks. The plates are thus adapted to operate as the movable support member to advance the napkins to the dispensing aperture.

The construction is achieved with a minimum of molds. As one of skill in the art will appreciate, molds for injection-molding are quite expensive and can
15 add many tens of thousands of dollars to the capital cost involved for each part.

In another aspect of the invention, there is provided a large capacity napkin dispenser including: (a) an elongate housing defining a storage chamber with a generally rectangular cross-section for receiving a stack of napkins; (b) a
20 faceplate with a dispensing aperture extending between a first and a second side of the dispenser, the faceplate being hinged to the housing at the first side so as to be movable between an open position for re-loading and a closed position for dispensing, the faceplate further having an outer surface and an inner surface which is inside the dispenser when the faceplate is in the closed position; (c) a
25 movable support member mounted in the housing; (d) biasing means for urging the movable support toward the faceplate so that the stack of napkins is advanced to the aperture as it is depleted; (e) means for locking the faceplate in the closed position; and (f) means for gripping the napkin stack adjacent the faceplate to control advancement of the napkin stack to the aperture. Preferably,
30 the means for gripping the stack include a pair of opposed gripping surfaces which define a progressively decreasing span in the direction of the dispensing aperture

such as wherein the gripping surfaces each have an inwardly convex bowed profile and define a progressively decreasing span. In a preferred embodiment, the means for gripping the napkin stack adjacent the faceplate are effective to retain the napkin stack within the elongate housing when the faceplate is in the open position.

Another aspect of the invention is a kit for converting existing dispensers. There is thus provided a kit with a locking faceplate for mounting on a napkin dispenser housing comprising: (a) a mounting bracket; (b) means for securing the mounting bracket to the dispenser housing; (c) a faceplate with an elongate aperture; (d) hinge means for pivotally mounting the faceplate to the mounting bracket such that it is movable between a closed position for dispensing a stack of napkins and an open position for reloading; and (e) means for locking the faceplate in the closed position, the locking means being operable to lock the faceplate to the mounting bracket in the closed position and including release means for unlocking the faceplate located adjacent an inner surface of the faceplate such that when the faceplate is in the closed position on a dispenser the release means is concealed in the interior of the dispenser and accessible through the dispensing aperture. The means for securing the mounting bracket to the dispenser includes a mounting collar adapted to be secured to the mounting bracket; ordinarily about a flange in the housing of an existing dispenser. Here again the locking means includes biasing means adapted to maintain it in a locking position and the locking means preferably includes an injection-molded unitary latch including an integrally-formed spring and a latch member as noted above.

Another aspect of the invention provides an injection-molded unitary faceplate for a napkin dispenser made from an injection-molding composition, the faceplate having a dispensing aperture as well as a plurality of guide ridges on an inner surface thereof inclined toward the aperture, the faceplate being further provided with a molded-in label film on an outer surface thereof; the label film

including an outwardly facing polymer film layer extending over substantially the entire outer surface of the faceplate. Typically, the molded-in label film comprises a polymer film layer and an ink layer. The ink layer may be formulated to mimic a metallic finish. In a preferred embodiment, the label film consists of a thermoplastic polymer film layer and an ink layer, wherein the ink layer is melt-bonded to the injection-molding composition and the outwardly facing polymer film layer is a polycarbonate film. In many cases, a heat activated adhesive will be used between the ink layer and the underlying polymer. However, if the proper outer thermoplastic polymer film layer is chosen for compatibility with the ink and the underlying polymer, it may be possible to dispense with the heat activated adhesive layer entirely.

A method of making an injection-molded faceplate for a napkin dispenser of the invention includes: (a) printing an ink composition onto a thermoplastic polymer film; (b) thermoforming the film into a shape suitable for a faceplate layer; and (c) injection-molding structural resins onto the ink layer of the thermoformed film, wherein the faceplate is provided with a dispensing aperture and the polymer film extends over substantially the entire outer surface of the faceplate.

The present invention is also directed to using the improvements noted above to dispense napkins.

Still further features and advantages of the present invention will become apparent from the discussion which follows.

Brief Description of the Drawings

The invention is described in detail below with reference to the various drawings wherein like numbers designate similar parts in the drawings:

Figure 1 is a perspective view of the dispenser of the invention mounted in-counter;

Figure 2 is an exploded perspective view of the napkin dispenser of **Figure 1**, showing its various components;

5

Figure 3 is a perspective view of the faceplate of **Figures 1** and **2** and the mounting bracket of **Figures 1** and **2**;

Figure 4 is a perspective bottom view of the unitary latch shown in **Figure 3**;

10

Figure 5 is a view of a collar that can be used to mount the bracket and faceplate of **Figure 3** on an existing dispenser;

Figure 6 is a view in section of the mounting bracket of **Figure 3** along line 6-6 showing the profile of dispensing opening **100**;

15

Figure 7 is a schematic view illustrating a stack of interfolded, single fold napkins;

20

Figure 8 is an enlarged detail showing support plate **16** of **Figure 2** with spring **18** attached thereto;

Figure 9 is a detail showing a portion of support plate **16**;

25

Figure 10 is a detail showing a label film disposed on the outer surface of face plate **14** of dispenser **10**; and

Figure 11 is a schematic view of a multilayer mold-in label film useful in connection with the invention.

30

Detailed Description of the Invention

The invention is described in detail below with reference to the drawings for purposes of illustration only. Modifications within the spirit and scope of the invention, set forth in the appended claims will be readily apparent to one of skill
5 in the art.

Referring to **Figures 1** through **10**, there is shown a high capacity napkin dispenser **10** including a housing **12**, a faceplate **14** and a movable support plate **16** provided with a biasing spring **18**. Faceplate **14** is hinged to a mounting
10 bracket **20** which, in turn, is secured to housing **12**. A hinge suitably includes a pin (not shown) as well as a hinge plate **22** to secure faceplate **14** to bracket **20** such that it pivots between a closed position (**Figure 1**) and an open position for reloading. Hinge plate **22** optionally includes ribs **23**.

15 Housing **12** and faceplate **14** thus define a storage chamber generally indicated at **13** for receiving a stack of napkins.

Housing **12** suitably includes two multi-faceted panels **24**, **26** as well as an end plate **28**. Panels **24**, **26** define opposed sidewalls **30**, **32**, **34** and **36** when
20 secured together by way of tabs **38** which fits in slots **40**. Preferably, plates **16**, **28** are injection-molded and of identical construction. This reduces fabrication costs as well as provides an opportunity to include molded-in features in the plate such as the quick lock mounting for spring **18** described herein. So also, panels **24**, **26** are of identical construction which saves considerable capital costs when
25 producing the molds. Injection-molding allows for providing multiple molded-in features which reduces the number of parts as well as the labor required to fabricate the inventive dispensers.

An optional tether **42** secures plate **28** to movable support plate **16** so that
30 when the empty dispenser is opened support plate **16** is not pushed out of the interior of the housing by spring **18**. Preferably, the ends of the spring are bent

inwardly at ends **18a**, **18b** and secured to support plates **16**, **28** provided by way of quick locking hooks **17**, **19** with fingers **17a** and **19a** over apertures **17b** and **19b** respectively configured so that a tether is not necessary. Details are best seen in **Figures 8, 9**. In particular, retention finger **17a** projects radially outward while

5 retention finger **19a** projects tangentially with respect to the coils of helical spring **18**. Retention protuberance **19c** formed on the lower surface of retention finger **19a** serves to retain the inwardly projecting free end **18a** of helical spring **18**. Guide posts **21** and **23** together with rack **17** and **19** as well as stop pin **25** define an imaginary mounting circle **29**. During assembly, inwardly projecting end **18a**

10 of helical spring **18** may be placed between stop pin **25** and retention hook **19** while diametrically opposed portion **31** of helical spring **18** is slipped under retention finger **17b** with guide posts **21** and **23** restraining lowermost coil **33** of helical spring **18**. Helical spring **18** is then locked into position by urging inwardly projecting end **18a** of helical spring **18** under retention finger **19a** and

15 past a retention protuberance **19c** thereby locking helical spring **18** in place. This arrangement (repeated with plate **28** on the other end of spring **18**) greatly expedites assembly of the dispenser. Further, plates **16** and **28** may be substantially identical eliminating extra cost for an additional mold.

20 After assembly and loading with napkins, the weight of a napkin stack compresses spring **18** which, in turn, forces the stack to the faceplate as the stack is depleted.

Faceplate **14** is provided with an elongate aperture **44** which extends

25 between sidewalls **30** and **36** and provides access to the napkin stack. At the outer surface **46** of the faceplate there is optionally provided a molded-in label film layer **48**, which extends substantially over the entire outer surface of faceplate **14**. At the inner surface **50** of faceplate **14** there is provided a plurality of triangular guide ridges **52**, **54** and so forth inclined towards aperture **44** as is seen in **Figure**

30 **3**.

It is appreciated from **Figure 3** in particular that the guide ridges extend progressively further from the inner surface of faceplate **14** with increasing distance from the dispensing aperture, thereby flaring away therefrom. The guide ridges are further characterized in that they are generally orthogonal to an elongate
5 axis **55** of the dispensing aperture. It is also appreciated from the various diagrams, that the guide ridges are generally parallel to an axis **57** of the storage chamber when the faceplate is in the closed position.

Faceplate **14** is preferably injection-molded and of unitary structure. A
10 Preferred class of materials are acrylonitrile-butadiene-styrene (ABS) molding compositions due to their unique combination of impact resistance and warp resistance.

Faceplate **14** is also provided with a unitary injection-molded locking latch
15 **56** which is provided with a molded-in spring in the form of a pair of arms **58, 60** which bear upon the guide ridges to bias latching member **62** of the latch to a locking position where it is maintained when mounted in the faceplate. When faceplate **14** is closed (**Figure 1**) lock member **62** is thus maintained in locking engagement with portion **64** of bracket **20** when the faceplate is closed so that the
20 faceplate cannot be opened. Moreover, the locking latch **56** is mounted at inner surface **50** of faceplate **14** adjacent an end **66** of aperture **44**. Latch **56** is thus concealed from view when the dispenser is closed, but readily accessible through aperture **44** to a technician aware of its placement at the end of the dispensing aperture.

25

In order to release the latch, a technician simply pulls the latch away from the locking position by pulling on a lip **68** of the latch to displace it inwardly toward the center of the aperture.

Preferably, the latch has a beveled edge **72** to facilitate closing and is made of relatively durable polymer such as nylon or polyacetal. Celcon acetal copolymer is available from Celanese Limited, Dallas, Texas.

5 Optionally, faceplate **14** and bracket **20** are provided as part of a kit with an additional collar **80** as shown in **Figure 5**. Collar **80** is sized to fit around an existing dispenser and to be secured to bracket **20** through an existing flange, for example. Holes **82, 88, 94 and 96** are provided to secure the collar to bracket **20**, while holes **84, 86, 90 and 92** can be used to secure the collar to a counter in
10 which the dispenser is mounted. A cutaway **98** in the collar can be used to accommodate features of an existing dispenser, such as a latch which is no longer used. Thus, the inventive arrangement is used to retrofit existing dispensers so that they are easier to operate.

15 In a preferred construction of the inventive dispenser, bracket **20** defines an opening **100** (**Figures 3, 6**) suitable for retaining a stack of napkins **102** so that the dispenser may be more easily loaded. To this end, opening **100** is adjacent a pair of lateral retention ledges **102, 104** which progressively project inwardly so that the napkins will be restrained within the dispenser when the cover (faceplate
20 **14**) is open. Preferably retention ledges **102, 104** have a profile configured to grip the napkins lightly but allow them to slip out without imposing such a force on them that they will not be torn or otherwise damaged as they are dispensed.

 In this regard, it is noted that a geometry with simply a rectangular
25 cantilever projecting over the opening of the storage chamber was less desirable than the bowed geometry seen in **Figure 6**.

 The relative dimensions of opening **100** and a napkin stack **106** are better understood with reference to **Figures 6 and 7**. **Figure 6** is a view in section along line **6-6** of **Figure 3** showing the profile of bracket **20**. Bracket **20** has two
30 laterally inwardly projecting retention ledges **102, 104** as shown in the **Figures**. Each of these retention ledges **102** and **104** has an arcuate profile which flares

upwardly and inwardly from its lower portions to its upper portions located adjacent dispensing opening **100**. At the lower portion, the bracket defines a lateral span **108** which is generally larger than the lateral span or width **110** of napkins to be dispensed through opening **100**. At the upper part of opening **100**

5 the span between edges **102**, and **104** as shown at **112** is generally less than the span **110** of a napkin stack **106** to be dispensed there through. Thus, if it is desired to dispense a stack of interfolded, single folded napkins **106** as shown in **Figure 7** through opening **120**, the progressively inwardly projecting retention ledges **102**, **104** will restrain the stack as well as guide it through opening **102**. As

10 will be appreciated from the diagram, portions **102**, **104** most preferably have an inwardly bowed, convex profile which projects progressively toward the center of the dispenser with height (toward the aperture) to facilitate dispensing through the opening without tearing or otherwise damaging the napkins. This geometry is also effective for hindering upward motion of the stack which is biased by spring

15 **18**. It will be further appreciated from **Figures 6** and **7** that the tails (such as tail **105**) of the napkins have their edges parallel to the contour lines of convex profiles **102**, **104** in a preferred embodiment. That is to say, the edges of the tails of the napkins are generally parallel to axis **55** of aperture **44** as may be seen in **Figure 1**.

20

In a preferred embodiment, span **110** of the napkins may be about 5 inches or so and the span at **112** may be about 4.5 inches, about 10% less than the width of the napkin stack.

25

Figure 8 is a detail showing spring **18** attached to end plate **16**, there is shown in **Figure 9** an enlarged view of hook **19** and stop pin **25** for purposes of illustration. It will be appreciated from the discussion above that plate **28** is most preferably identical to plate **16** and secured to spring **18** in an identical manner. To this end, posts such as **21**, **23** and hooks such as **17**, **19** position and secure the

30 plates to the spring. The radial hooks **17** have a finger **17a** extending generally in a radial direction with respect to axis **57** of spring **18** to secure the spring axially,

while the tangential hooks **19** have a finger **19a** extending generally in a tangential direction with respect to the coils of spring **18** to hinder rotation of the spring and secure it to the plates.

5 Plates **16, 28** are suitably injection-molded from an ABS resin composition which is used for the other components of the dispenser such as the U-shaped panels defining the storage chamber for the napkins.

 A napkin dispenser faceplate of the invention is likewise made by
10 injection-molding such that it has molded-in guide ridges inclined to the aperture in a unitary structure as illustrated. A preferred faceplate has a molded-in label film at its outer surface which gives the faceplate a brushed stainless steel appearance, for example, when a polymer layer printed with an appropriately pigmented ink is used. The inventive dispenser is most preferably provided with a
15 decorative cover film **48** of the type illustrated schematically in **Figure 10**. In **Figure 10** there is shown a film such as film **150** which is provided with an ink layer **152** as shown in the diagram. Film **150** may be a relatively thin, polycarbonate film if so desired, while ink layer **152** may be any suitable ink, preferably an ink which provides a metallic appearance to film **150**. A preferred
20 method of fabrication is to print ink **152** onto film **150** and then thermoform the film into the desired shape. The thermoformed film is then positioned in a mold. Thereafter a structural resin, such as resin **154**, is injection-molded onto the ink layer of the film while it is disposed in the mold. Thus, the surface appearance is provided by way of a thermoformed film which has been positioned in the mold
25 and provided with a structural backing to form the faceplate. The bilayer film preferably extends substantially over the entire outer surface of the faceplate.

 Alternatively, metallic foil containing label film is used. A label film is shown schematically in **Figure 11**. Film **200** includes an optional adhesive layer **202** for securing it to the mold, optionally a protective outer layer **204** of
30 transparent polymer, a facestock layer **206** and another optional melt-activated adhesive layer **208**. Other suitable films are disclosed in United States Patent No.

6,773,653 to *Miller et al.* The films are pre-cut and adhered to the mold by way of layer **202**, then the part is injection-molded from a molten injection-molding composition applied over the film. The heat-activated adhesive layer **208** of the film melt-bonds with the part to produce a durable structure which provides a very large number of decorative options by way of choosing a suitable facestock layer. Moreover, other layers may be added as desired. The faceplate of the invention can thus be made with a metallic appearance on one side and integral plastic guide ridges on the other side without the need for making multiple parts to achieve the desired effect.

10

The optional heat activated or heat-activatable layer of the label film is a layer of material which is activated by heat during the molding process to improve bonding of the label to a plastic article in the molding process. Materials for the heat-activatable adhesive layer may comprise any heat-activatable adhesive or thermoplastic film material. Such materials include but are not limited to the following film-forming materials used alone or in combination such as polyolefins, (linear or branched), metallocene catalyzed polyolefins, syndiotactic polystyrenes, syndiotactic polypropylenes, cyclic polyolefins, polyacrylates, polyethylene ethyl acrylate, polyethylene methyl acrylate, acrylonitrile butadiene styrene polymer, ethylene-vinyl alcohol copolymer, ethylene-vinyl acetate copolymers, polyamides such as nylon, polystyrenes, polyurethanes, polysulfones, polyvinylidene chlorides, polycarbonates, styrene maleic anhydride polymers, styrene acrylonitrile polymers, ionomers based on sodium or zinc salts of ethylene/methacrylic acid, cellulosics, fluoroplastics, polyacrylonitriles, and thermoplastic polyesters. More specific examples are the acrylates such as ethylene methacrylic acid, ethylene methyl acrylate, ethylene acrylic acid and ethylene ethyl acrylate. Also, included are polymers and copolymers of olefin monomers having, for example, 2 to about 12 carbon atoms, and in one embodiment 2 to about 8 carbon atoms. These include the polymers of alpha-olefins having from 2 to about 4 carbon atoms per molecule. These include polyethylene, polypropylene, poly-1-butene, etc. An example of a copolymer

30

within the above definition is a copolymer of ethylene with 1-butene having from about 1 to about 10 weight percent of the 1-butene comonomer incorporated into the copolymer molecule. The polyolefins include amorphous polyolefins. The polyethylenes that are useful in the heat seal layer include those with various densities including low, medium and high density ranges. The ethylene/methyl acrylate copolymers available from Chevron under the tradename EMAC can be used. These include EMAC 2260, which has a methyl acrylate content of 24% by weight and a melt index of 2.0 grams/10 minutes at 190°C., 2.16 Kg; and EMAC SP 2268T, which also has a methyl acrylate content of 24% by weight and a melt index of 10 grams/10 minutes at 190°C., 2.16 Kg. Polymer film materials prepared from blends of copolymers or blends of copolymers with homopolymers are also useful.

Also, the heat activatable first adhesive layer may contain antiblock additives (such as silica, diatomaceous earth, synthetic silica, glass spheres, ceramic particles, etc.) This layer also may contain an antistatic additive (such as an amine or an amide or a derivative of a fatty acid).

The heat activatable adhesive layer is designed for and activated at temperatures known to those skilled in the art. Generally the heat-activatable first adhesive layer has a lower melting point than any of the other layers of the in-mold label. While the heat activatable layer may activate at temperatures below those specified for activation, the layer is designed to activate at certain temperatures based on the substrate material under normal in-mold labeling conditions. In one embodiment, the heat activatable adhesive layer activates at temperatures between about 80°C. to about 300°C., more often the heat seal layer activates at temperatures between about 87°C. to about 250°C.


The facestock layer may include or consist of paper, foils, pigmented polymer layers and so forth as enumerated in United States Patent No. 6,773,653 noted above.


The polymer facestock and the heat activatable first adhesive layer may be formed by simultaneous extrusion from two or more extruders with a suitable coextrusion die whereby the facestock and first adhesive layer are adhered to each other in a permanently combined state to provide a unitary coextrudate. A tie layer (adhesion promoting layer) may also be coextruded with the facestock and the heat-activatable first adhesive layer to improve the adhesion of the heat-activatable layer to the facestock. Alternatively, a coating process may be used to lay down a layer of the heat-activatable material on the facestock, or the two layers can be formed separately and thereafter laminated together with or without the aid of an adhesive layer.

CLAIMS

1. A kit with a locking faceplate for mounting on a napkin dispenser housing comprising:
 - (a) a mounting bracket;
 - (b) means for securing the mounting bracket to the dispenser housing;
 - (c) a faceplate with an elongate aperture;
 - (d) hinge means for pivotally mounting the faceplate to the mounting bracket such that it is movable between a closed position for dispensing a stack of napkins and an open position for reloading; and
 - (e) means for locking the faceplate in the closed position, the locking means being operable to lock the faceplate to the mounting bracket in the closed position and including release means for unlocking the faceplate located adjacent an inner surface of the faceplate such that when the faceplate is in the closed position on a dispenser the release means is concealed in the interior of the dispenser and accessible through the dispensing aperture.
2. The kit according to claim 1, wherein the means for securing the mounting bracket to the dispenser includes a mounting collar adapted to be secured to the mounting bracket.
3. The kit according to claim 2, wherein the locking means includes biasing means adapted to maintain it in a locked position.
4. The kit according to claim 3, wherein the locking means includes an injection-molded unitary latch including an integrally-formed spring and a latch member.
5. The kit according to claim 4, wherein the injection-molded unitary latch member is formed from an injection-molding composition comprising nylon, polyacetal or polyester.


FIG. 1






3/7

FIG. 3



4/7

FIG. 4



5/7





FIG. 5**FIG. 6****FIG. 7**

FIG. 8



7/7

FIG. 9




FIG. 10




FIG. 11

