



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2845558 A1 2014/09/13

(21) **2 845 558**

(12) **DEMANDE DE BREVET CANADIEN
CANADIAN PATENT APPLICATION**

(13) **A1**

(22) **Date de dépôt/Filing Date:** 2014/03/12

(41) **Mise à la disp. pub./Open to Public Insp.:** 2014/09/13

(30) **Priorité/Priority:** 2013/03/13 (US61/780,206)

(51) **Cl.Int./Int.Cl.** *E03C 1/22* (2006.01),
A47K 1/14 (2006.01), *F16L 55/24* (2006.01)

(71) **Demandeur/Applicant:**
WCM INDUSTRIES, INC., US

(72) **Inventeur/Inventor:**
BALL, WILLIAM T., US

(74) **Agent:** RICHES, MCKENZIE & HERBERT LLP

(54) **Titre : CREPINE AMELIORANT L'ECOULEMENT**

(54) **Title: STRAINER WITH IMPROVED FLOW**

(57) **Abrégé/Abstract:**

A wastewater strainer is provided that includes a strainer body that has at least one opening that enhances fluid flow through the strainer body and the wastewater plumbing to which it is interconnected. The strainer body includes a flange for engagement to the inner portion of a bathtub and a hub that is spaced from a lower edge of the strainer body.



ABSTRACT

A wastewater strainer is provided that includes a strainer body that has at least one opening that enhances fluid flow through the strainer body and the wastewater plumbing to which it is interconnected. The strainer body includes a flange for engagement to the inner portion of a bathtub and a hub that is spaced from a lower edge of the strainer body.

STRAINER WITH IMPROVED FLOW

This application claims the benefit of U.S. Provisional Patent Application Serial No. 61/780,206, filed March 13, 2013, the entirety of which is incorporated by reference herein.

5

FIELD OF THE INVENTION

Embodiments of the present invention are generally related to wastewater strainers commonly found in bathtubs and other fluid-holding basins. Strainers are located at a low point of the bathtub and interconnect to a wastewater drain system associated with a drain port of the bathtub and provide a fluid conduit from the bathtub or basin to the wastewater drain system.

10

BACKGROUND OF THE INVENTION

Wastewater plumbing is interconnected to a bathtub, shower, or other fluid-holding basin (hereinafter “bathtub”) by way of a strainer that prevents large items from entering the wastewater plumbing system. The strainer also accommodates a drain stopper. Referring now to Fig. 3, strainers 2 generally include an externally threaded cylindrical body 6 with an outwardly extending flange 22. Strainers 2 also often include at least one arm 54 that extends from an inner surface 56 of the cylindrical body 6. The arm 54 or arms support a centrally-located hub 30. The hub 30 receives a post or carrier that operatively supports the drain stopper. Common strainers and drain stoppers are described in U.S. Patent Nos. 5,758,368 and 6,418,570, the entirety of which are incorporated by reference herein.

15

20

Wastewater plumbing often includes a generally L-shaped elbow 18 having a flange 38 extending from its upper surface for contacting a bottom surface of the bathtub. The other end, i.e., a generally “horizontal portion 50 of the elbow, is interconnected to a pipe that extends generally parallel to the outer, lower surface of the bathtub. To interconnect the wastewater elbow 18 to the bathtub, the elbow flange 38 is placed adjacent to the bottom surface of the bathtub wherein a seal 42 is often positioned therebetween. The strainer 2 is then inserted into the drain outlet and external threads 10 are interconnected to internal threads 14 of the drain elbow. As the strainer 2 is tightened

30

onto the elbow 18, the strainer flange 22 will engage the bottom, internal surface of the bathtub to secure the wastewater elbow and associated plumbing to the bathtub.

Because the strainer body 6 is often longer than the upper portion of the elbow that interfaces with the bathtub 52, a portion of the strainer body will obstruct the wastewater flow path defined by the inner surface of the horizontal portion 50 of the elbow 18. Stated differently, the strainer body 6 when interconnected to the elbow 18 will extend past the intersection of the upper portion 52 and the horizontal portion 50 of the elbow, which obstructs flow. As one of skill in the art will appreciate, the more the strainer body extends past the intersection, the greater the flow obstruction as fluid leaving the bathtub must first circumvent the strainer body sidewall before it can enter the horizontal portion of the elbow. Flow obstructions prevent water from quickly escaping the bathtub, which is not ideal in overflow situations, for example, when users rely on opening a drain stopper to quickly drain the bathtub.

Thus, it has been a long felt need in the field of plumbing to provide a wastewater strainer that enhances fluid flow from the bathtub. The following disclosure describes an improved strainer that minimizes obstructions commonly found in strainer/elbow interconnections.

SUMMARY OF THE INVENTION

It is one aspect of embodiments of the present invention to provide a wastewater strainer ("hereinafter "strainer") that enhances fluid flow from a bathtub or other fluid-holding basin. The contemplated strainer includes a strainer body and a flange extending from a top edge of the strainer body. The strainer also includes a hub supported by at least one arm. The hub receives a post or carrier that operatively receives a drain stopper that cooperates with the flange to prohibit fluid flow from the bathtub. Enhanced flow is provided by decreasing the strainer body length while maintaining the distance from the hub to the strainer flange. Extensions are provided that offset the arms from a lower edge of the strainer body, which allows the distance between the hub and strainer flange to be maintained. The distance between the hub and the strainer flange is, in some respects, important because stopper mechanisms in use require predetermined carrier length to function properly and, if the hub location is raised relative to the inner surface

of the bathtub, the stopper will not engage the strainer flange to seal the bathtub. By shortening the strainer body, at least two openings in the strainer body sidewall are provided that coincide with the fluid conduit provided by the horizontal portion of the wastewater elbow. Thus, fluid flowing through the strainer body will flow directly from
5 the strainer body to the horizontal portion of the elbow without having to circumvent the strainer body sidewall.

It is another aspect of the present invention to provide a wastewater strainer, comprising: a body having an upper edge and a lower edge; a flange extending from the upper edge; at least one extension extending from the lower edge; and an arm
10 interconnected on a first end to the extension and on a second end to a hub positioned within the body.

It is still yet another aspect of the present invention to provide a wastewater strainer used in combination with drain plumbing associated with a water receptacle, comprising: a body adapted to fit within a first portion of an elbow, the body having an
15 upper edge and a lower edge and including an opening associated with the lower edge, the opening generally coinciding with the inner diameter of a second portion of the elbow such that a fluid flow path from the body and the second portion of the elbow is generally unobstructed; and a flange extending from the upper edge of the cylindrical body.

The Summary of the Invention is neither intended nor should it be construed as
20 being representative of the full extent and scope of the present invention. Moreover, references made herein to "the present invention" or aspects thereof should be understood to mean certain embodiments of the present invention and should not necessarily be construed as limiting all embodiments to a particular description. The present invention is set forth in various levels of detail in the Summary of the Invention as well as in the
25 attached drawings and the Detailed Description of the Invention and no limitation as to the scope of the present invention is intended by either the inclusion or non-inclusion of elements, components, etc. in this Summary of the Invention. Additional aspects of the present invention will become more readily apparent from the Detail Description, particularly when taken together with the drawings.

30

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and together with the general description of the invention given above and the detailed description of the drawings
 5 given below, explain the principles of these inventions.

Fig. 1 is a front elevation view of a strainer of the prior art;

Fig. 2 is a front elevation view of a strainer of one embodiment of the present invention;

Fig. 3 is a cross-sectional view of the strainer of the prior art interconnected to an
 10 elbow of a bath wastewater plumbing system;

Fig. 4 is a cross-sectional view of the strainer of one embodiment of the present invention interconnected to an elbow of a wastewater plumbing system;

Fig. 5 is a left elevation view of the strainer of the prior art interconnected to an elbow of a wastewater plumbing system;

Fig. 6 is a left elevation view of the strainer of one embodiment of the present
 15 invention interconnected to an elbow of a wastewater plumbing system;

Fig. 7 is a side elevation view of one embodiment of the present invention that employs angled extensions; and

Fig. 8 is a side elevation of one embodiment of the present invention that employs
 20 a sidewall with a plurality of holes.

To assist in the understanding of one embodiment of the present invention the following list of components and associated numbering found in the drawings is provided herein:

<u>#</u>	<u>Component</u>
2	Strainer
6	Strainer body
10	External threads
14	Internal threads
18	Drain elbow
22	Strainer flange

<u>#</u>	<u>Component</u>
26	Upper edge
30	Hub
34	Lower edge
38	Drain flange
42	Seal
46	Conduit
50	Horizontal portion
52	Upper portion
54	Arm
56	Inner surface
58	Extension
62	Openings
66	Inner wall
70	Vertical portion
74	Hole

It should be understood that the drawings are not necessarily to scale. In certain instances, details that are not necessary for an understanding of the invention or that render other details difficult to perceive may have been omitted. It should be understood, of course, that the invention is not necessarily limited to the particular embodiments illustrated herein.

DETAILED DESCRIPTION

Figs. 2, 4, and 6 show a wastewater strainer 2 of one embodiment of the present invention that includes a strainer body 6 with external threads 10. The external threads 10 are designed to engage internal threads 14 of an elbow 18 of a wastewater plumbing system. The strainer 2 also includes a flange 22 positioned at an upper edge 26 of the strainer 2 and a hub 30 positioned adjacent its lower edge 34. The hub 30 receives a post or carrier associated with a drain stopper.

Figs. 3 and 6 show the interconnection of a prior art strainer to an elbow that is positioned adjacent to the bottom portion of a bathtub (not shown) with a seal 42 positioned between the drain flange 38 and the bottom surface of the bathtub. To secure the drain elbow 18 and associated wastewater plumbing to the bathtub, the strainer 2 is first placed in a drain port of the bathtub and threadingly engaged into the elbow 18. As the strainer 2 is tightened onto the elbow 18, the strainer flange 22 will engage an inner bottom surface of the bathtub and compress the seal 42 to sandwich the bathtub wall between the strainer flange 22 and the drain flange 38. After this connection is complete, the drain stopper assembly (not shown) is interconnected to the hub 30.

As shown in Fig. 3, water flowing through the prior art strainer 2 would necessarily have to circumvent the lower edge 34 of the strainer body 6 to enter a conduit 46 provided by a generally horizontal portion 50 of the drain elbow 18. Again, this obstruction reduces mass flow through the drain elbow 18, which is undesirable.

Figs. 2, 4, and 6 show one embodiment of the present invention that addresses the fluid flow problems previously described herein. More specifically, the strainer body 6 is shorter relative to the strainer body length of the prior art wherein the location of the hub 30 relative to the strainer flange 22 is maintained. That is, the location of the hub 30 and associated arms 54 with respect to the strainer flange 22 is maintained by extensions 58 interconnected to the lower edge 34 of the strainer body. This arrangement maintains the position of the hub 30 relative to the flange and creates openings 62 in the strainer body 6 that will allow water to flow more effectively.

Figs. 4 and 6 show the interconnection of the strainer body of one embodiment. In operation, the strainer body 2 is threaded into the drain elbow 18 as in the prior art. Here, however, after interconnection, the lower edge 34 of the strainer body 6 is positioned close to an inner wall 66 of the horizontal portion 50 of the drain elbow 18. Thus, the arms 54 and hub 30 of the strainer body 6 create the only substantial flow obstruction and fluid does not have to circumvent an extended side wall of the strainer body to enter the conduit 16. The rotational position of the strainer relative to the elbow is irrelevant as at least two openings 62 are provided that allow the water to flow directly from the strainer body 6 to the horizontal portion 50 of the drain elbow 18.

One of skill in the art will also appreciate that the arms/extensions do not have to be formed in a 90° configuration as shown. More specifically, the arms 54 may be angled relative to the hub 30 and the inner wall 66 of the strainer body 6. In addition, one of skill in the art will appreciate that although two arms 54 are provided, more or less
5 arms may be used without departing from the scope of the invention. For example, to prevent items from falling into the drain system, more arms 54 can be provided. Alternatively, a single arm cantilevered from the extension may be provided to further increase the flow through the strainer body.

Although the openings are shown as providing a strainer body 6 with a relatively
10 planar lower edge 34, one of skill in the art will appreciate that any strainer body 6 that has extensions 58 and that space the hub 30 away from the strainer flange 22 is contemplated. More specifically, the openings 62 may have an arcuate profile such that only the portion above the extensions has threads that engage the threads 14 of the drain elbow 18. In this fashion, the majority of the sidewall associated with the strainer body 6
15 would be removed. That is, any configuration that removes portions of the strainer body 6, while providing sufficient threads 10 for securely engaging with the threads 14 of the drain elbow 18 is contemplated and is within the scope of the present invention.

Further, as provided in Fig. 1, some embodiments employ extensions that directly interconnect to the hub. In these embodiments, the extensions are angled downwardly to
20 position the hub at the correct distance below the strainer flange. Some other embodiments of the present invention as shown in Fig. 8 employ sidewalls with a plurality of holes that facilitate fluid flow. Here, although a traditional sidewall is used, the plurality of holes decreases the amount of fluid that must circumvent the sidewall.

While various embodiments of the present invention have been described in
25 detail, it is apparent that modifications and alterations of those embodiments will occur to those skilled in the art. However, it is to be expressly understood that such modifications and alterations are within the scope and spirit of the present invention, as set forth in the following claims. Further, the invention(s) described herein is capable of other embodiments and of being practiced or of being carried out in various ways. In addition,
30 it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of "including,"

"comprising," or "having" and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items.

What is claimed is:

1. A wastewater strainer, comprising:
 - a body having an upper edge and a lower edge;
 - a flange extending from said upper edge;
 - at least one extension extending from said lower edge; and
 - 5 an arm interconnected on a first end to said extension and on a second end to a hub positioned below lower edge of said body.
2. The wastewater strainer of Claim 1, wherein said body is threaded.
3. The wastewater strainer of Claim 1, wherein the distance between the lower surface of said flange and said lower edge is between about 0.25-1.0 inches.
4. The wastewater strainer of Claim 1, wherein said extension are selectively removable.
5. The wastewater strainer of Claim 1, wherein said arms are selectively removable.
6. The wastewater strainer of Claim 1, wherein a bottom surface of said hub extends at least about 0.5 inches below said lower edge.

7. A wastewater strainer, comprising:
a body having an upper edge and a lower edge;
a flange extending from said upper edge;
at least one extension extending from said lower edge; and
5 a hub positioned below said lower edge of said body, said hub being interconnected to said at least one extension.
8. The wastewater strainer of Claim 7, wherein said body is threaded.
9. The wastewater strainer of Claim 7, wherein said at least one extension is angled relative to said flange.
10. The wastewater strainer of Claim 7, wherein the distance between the lower surface of said flange and said lower edge is between about 0.25-1.0 inches.
11. The wastewater strainer of Claim 7, wherein a bottom surface of said hub extends at least about 0.5 inches below said lower edge.

12. A wastewater strainer used in combination with drain plumbing associated with a water receptacle, comprising:

5 a body adapted to fit within a first portion of an elbow, said body having an upper edge and a lower edge and including an opening associated with said lower edge, said opening generally coinciding with the inner diameter of a second portion of the elbow such that a fluid flow path from said body and said second portion of the elbow is generally unobstructed; and

a flange extending from said upper edge of said cylindrical body.

13. The wastewater strainer of Claim 12, further comprising at least one arm interconnected to an interior wall of said cylindrical body, said arm also being interconnected to a hub that is adapted for receipt of a drain valve operating mechanism.

14. The wastewater strainer of Claim 12, further comprising an extension emanating from said lower edge, said extension being interconnected to an arm that extends into said body, said arm also being interconnected to a hub that is adapted for receipt of a drain valve operating mechanism.

15. The wastewater strainer of Claim 12, wherein said hub is located below said second end.

Application number / Numéro de demande: 2845558

Figures: 1, 2, 3, 4, 5, 6, 7, 8

all figures

Pages: _____

Unscannable items received with this application
(Request original documents in File Prep. Section on the 10th floor)

Documents reçu avec cette demande ne pouvant être balayés '
(Commander les documents originaux dans la section de la préparation
des dossiers au 10^{ième} étage)