

(12) **United States Patent**  
**Phillips et al.**

(10) **Patent No.:** US 12,151,623 B2  
(45) **Date of Patent:** Nov. 26, 2024

(54) **PORTABLE VIDEO AND IMAGING SYSTEM**

(71) Applicant: **Digital Ally, Inc.**, Lenexa, KS (US)

(72) Inventors: **Steve Phillips**, Olathe, KS (US); **Jason R. Troxel**, Lee's Summit, MO (US)

(73) Assignee: **Digital Ally, Inc.**, Lenexa, KS (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/136,398**

(22) Filed: **Apr. 19, 2023**

(65) **Prior Publication Data**  
US 2023/0249631 A1 Aug. 10, 2023

**Related U.S. Application Data**

(63) Continuation of application No. 17/687,913, filed on Mar. 7, 2022, now Pat. No. 11,667,251, which is a (Continued)

(51) **Int. Cl.**  
**B60R 11/04** (2006.01)  
**B60R 11/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **B60R 11/04** (2013.01); **F16M 11/10** (2013.01); **F16M 11/14** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... H04N 5/2252; H04N 5/2251; H04N 5/77; H04N 5/907; H04N 5/765; H04N 5/775; H04N 5/781; H04N 5/782; H04N 5/85;

H04N 7/142; H04N 7/14; H04N 7/183; H04N 7/185; H04N 7/188; H04N 9/7921; H04N 9/8042; H04N 9/8205;  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,012,335 A \* 4/1991 Cohodar ..... G08B 13/19632 396/419  
6,542,182 B1 \* 4/2003 Chutorash ..... B60R 1/26 348/148

(Continued)

FOREIGN PATENT DOCUMENTS

EP 3073449 A1 9/2016

OTHER PUBLICATIONS

Prospero, Oregon Scientific ATC Chameleon Review, <https://www.laptopmag.com/reviews/cameras/orgon-scientific-atc-chameleon>, Mar. 27, 2013 (Year: 2013).


(Continued)

*Primary Examiner* — Pritham D Prabhakher  
(74) *Attorney, Agent, or Firm* — Erise IP, P.A.

(57) **ABSTRACT**

A portable video and imaging system includes a camera for capturing video of an event, and a video recording device for recording the captured video of the event. The camera is housed in a first housing, the recording device is housed in a second housing, and the first and second housings are physically separate. Various embodiments provide for the system to be mounted to a user's body, an article of clothing, such as a shirt or a hat, to a vehicle, or to an ancillary component carried by the user, such as a firearm.

**20 Claims, 18 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 16/371,509, filed on Apr. 1, 2019, now Pat. No. 11,310,399, which is a continuation of application No. 15/651,599, filed on Jul. 17, 2017, now Pat. No. 10,257,396, which is a continuation of application No. 14/991,607, filed on Jan. 8, 2016, now Pat. No. 9,712,730, which is a continuation of application No. 14/575,433, filed on Dec. 18, 2014, now Pat. No. 9,237,262, which is a continuation of application No. 14/040,329, filed on Sep. 27, 2013, now Pat. No. 9,019,431.

(60) Provisional application No. 61/707,326, filed on Sep. 28, 2012, provisional application No. 61/707,348, filed on Sep. 28, 2012.

(51) **Int. Cl.**

**F16M 11/10** (2006.01)  
**F16M 11/14** (2006.01)  
**F16M 11/20** (2006.01)  
**F16M 13/04** (2006.01)  
**G03B 17/56** (2021.01)  
**G07C 5/08** (2006.01)  
**G11B 27/10** (2006.01)  
**G11B 27/11** (2006.01)  
**G11B 27/34** (2006.01)  
**H04N 5/77** (2006.01)  
**H04N 7/18** (2006.01)  
**H04N 23/50** (2023.01)  
**H04N 23/51** (2023.01)

(52) **U.S. Cl.**

CPC ..... **F16M 11/2078** (2013.01); **F16M 13/04** (2013.01); **G03B 17/561** (2013.01); **G03B 17/566** (2013.01); **G07C 5/0866** (2013.01); **G11B 27/102** (2013.01); **G11B 27/11** (2013.01); **G11B 27/34** (2013.01); **H04N 5/77** (2013.01); **H04N 7/183** (2013.01); **H04N 7/185** (2013.01); **H04N 7/188** (2013.01); **H04N 23/50** (2023.01); **H04N 23/51** (2023.01); **B60R 2011/0089** (2013.01); **G03B 2206/00** (2013.01)

(58) **Field of Classification Search**

CPC ... A61B 5/0024; A61B 5/7275; A61B 5/0402; A61B 5/0476; A61B 5/1112; A61B 5/1117; A61B 5/14542; A61B 5/681; A61B 5/7214; A61B 5/7465; A61B 7/04; G08B 21/02; G08B 13/19621; G08B 13/19669; G08B 25/007; H04M 1/15; H04M 1/05; H04M 1/0214; H04M 1/0283; H04M 1/18; F41C 33/02; F41C 33/048; F41C 33/041; F41C 33/0209;

H04R 1/028; H04R 1/083; A45C 3/001; A45F 5/02; A45F 5/021; A45F 5/04; A45F 2200/0516; G06F 1/1628; A41B 1/08; A41D 27/20; A41D 1/002; A41C 33/045; A61M 5/1417; A61M 5/14244; G02B 21/0294; G02B 21/0288; G11B 27/102; G11B 27/11; G11B 27/34; B60R 2011/0089; G03B 2206/00; G03B 17/566; G03B 17/561; F16M 11/10; F16M 11/14; F16M 11/2078

See application file for complete search history.

(56)

**References Cited**

U.S. PATENT DOCUMENTS


8,497,776	B2 *	7/2013	Stern	.....	G08B 13/2402	340/572.1
8,538,961	B2 *	9/2013	Xu	.....	G06V 20/10	707/736
8,836,784	B2 *	9/2014	Erhardt	.....	G07C 5/008	348/148
9,299,388	B2 *	3/2016	Abe	.....	G11B 27/005	
2007/0008321	A1 *	1/2007	Gallagher	.....	G06V 20/30	345/473
2010/0195976	A1 *	8/2010	Abe	.....	G11B 27/105	386/343
2012/0001743	A1 *	1/2012	Cotten	.....	G01C 23/00	701/32.7
2012/0030263	A1 *	2/2012	John	.....	G06F 16/48	707/825
2012/0081382	A1 *	4/2012	Lindahl	.....	G06T 11/00	345/581
2012/0099800	A1 *	4/2012	Llano	.....	G06F 16/58	382/224
2012/0105635	A1 *	5/2012	Erhardt	.....	G07C 5/0866	348/148
2012/0148216	A1 *	6/2012	Pavagada	.....	H04N 5/772	386/278
2012/0169500	A1 *	7/2012	Stern	.....	G08B 13/2402	340/572.1
2012/0233571	A1 *	9/2012	Wever	.....	G06F 3/048	715/835
2013/0006718	A1 *	1/2013	Nielsen	.....	G06Q 10/06312	705/7.42
2013/0128038	A1 *	5/2013	Cok	.....	H04N 1/32101	348/143
2013/0226926	A1 *	8/2013	Beaurepaire	.....	G06V 20/39	707/E17.046

OTHER PUBLICATIONS

Shapton, Dave "Digital Microphones: A new approach?" from soundonsound.com published Mar. 2004, 4 pages (Year: 2004).  
 Sharper Image User Guide, <https://cdn4.sharperimage.com/si/pdf/manuals/206463.pdf>, Jan. 2, 2012 (Year: 2012).

\* cited by examiner

*Fig. 1.*










Fig. 5.






*Fig. 6.*



*Fig. 7.*

Fig. 8.








Fig. 11.







Fig. 12.




*Fig. 13.*




*Fig. 14.*



*Fig. 15.*



*Fig. 16.*



*Fig. 17.*




Fig. 18.




Fig. 19.




Fig. 20.







Fig. 21.




*Fig. 22.*




*Fig. 23.*




*Fig. 24.*



*Fig. 25.*



*Fig. 26.*



*Fig. 27.*




Fig. 28.




Fig. 29.




Fig. 30.

## PORTABLE VIDEO AND IMAGING SYSTEM

## RELATED APPLICATIONS

This is a continuation application of U.S. patent application Ser. No. 17/687,913, filed Mar. 7, 2022; which is a continuation application of U.S. patent application Ser. No. 16/371,509, filed Apr. 1, 2019, now U.S. Pat. No. 11,310,399, issued Apr. 19, 2022; which is a continuation application of U.S. patent application Ser. No. 15/651,599, filed Jul. 17, 2017, now U.S. Pat. No. 10,257,396, issued Apr. 9, 2019; which is a continuation application U.S. patent application Ser. No. 14/991,607, filed Jan. 8, 2016, now issued as U.S. Pat. No. 9,712,730 on Jul. 18, 2017; which is a continuation application of U.S. patent application Ser. No. 14/575,433, filed Dec. 18, 2014; now U.S. Pat. No. 9,237,262, issued on Jan. 12, 2016; which is a continuation application of U.S. patent application Ser. No. 14/040,329, filed Sep. 27, 2013; now U.S. Pat. No. 9,019,431, issued Apr. 28, 2015; which claims priority to U.S. Provisional Patent Application No. 61/707,348, filed Sep. 28, 2012 and U.S. Provisional Patent Application No. 61/707,326, filed Sep. 28, 2012; the disclosures of which are hereby incorporated by reference in their entirety into the present application.

## BACKGROUND

## 1. Field

Embodiments of the invention relate to a portable system for recording videos and still images. More particularly, embodiments of the invention relate to a portable digital video recording system sized to be worn on a user's body and configured to be mounted in a plurality of locations on the user's body, including a clothing article worn by the user, on a device carried by the user, such as a firearm, or in a vehicle. In other embodiments, the portable video and imaging system may be mounted in or on a vehicle.

## 2. Related Art

Although recording devices for recording video and still images are generally known, the recording device is commonly housed in a single housing that stores a camera, a memory element, and a processing element. The single housing is not mountable to a user's body. Moreover, when the recording device is used for law enforcement where captured video is frequently used as evidence, the loss of captured video due to damage or removal of the single housing of the recording device is problematic.

## SUMMARY

Embodiments of the invention solve the above-mentioned problems by providing a computer program, method, apparatus, and system for mounting a small, portable digital video recording system to a user's body, an article of clothing, a device carried by the user, or in a vehicle.

An embodiment of the video recording system broadly comprises a camera component for capturing video of an event and a recording component comprising a processor and a memory associated with the camera component for storing the captured video. The camera component includes a camera housed within a housing having a size configured to mount on a user's body. The housing includes at least one input to instruct recording by the camera. The video recording system further includes a mounting assembly for mount-

ing the camera to the user's body. In embodiments, the mounting assembly is a button-mount assembly including a slotted plate presenting a slot for receipt of a button through the slot.

Another embodiment of the video recording system broadly comprises the camera component and recording component described above. The mounting assembly, however, is a clip, such as an alligator clip, configured for grasping a clothing article of the user. In yet another embodiment, the mounting assembly is a hook-and-loop fastener. An even further embodiment comprises a mounting assembly for mounting the camera and recording components to a vehicle and broadly comprising a cradle for holding the recording component and a mounting arm for holding the camera component, wherein the mounting arm is secured to the cradle. Other embodiments comprise mounting assemblies for securing at least one or both of the camera and recording components to a belt worn by the user, around a head of a user or hat worn by the user, and on a firearm carried by the user.

In embodiments of the invention, the camera component is in a first housing, and the recording component is in a second housing. The camera and recording components are communicatively coupled together, and the housings for the two components are physically separate housings.

This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the detailed description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Other aspects and advantages of the current invention will be apparent from the following detailed description of the embodiments and the accompanying drawing figures.

## BRIEF DESCRIPTION OF THE DRAWING FIGURES

Embodiments of the current invention are described in detail below with reference to the attached drawing figures, wherein:

FIG. 1 is an environmental view of a portable video and imaging system of embodiments of the invention and mounted on a user's body;

FIG. 2 is a front exploded view of the camera component mounted to a first mounting assembly that is a button-mount assembly;

FIG. 3 is a rear exploded view of the button-mount assembly of FIG. 2;

FIG. 4 is a rear perspective view of the button-mount assembly of FIG. 2;

FIG. 5 is an exploded view of the button-mount assembly and particularly illustrating mounting of the assembly on the user's body;

FIG. 6 is a fragment, right side elevation view of the camera component and button-mount assembly and particularly illustrating the assembly mounted to the button of the user's shirt;

FIG. 7 is a horizontal cross-sectional view taken through line 7-7 of FIG. 7 and illustrating a retention clip of the button-mount assembly;

FIG. 8 is an environmental view of a second mounting assembly of embodiments of the invention secured to the user's body;

FIG. 9 is a rear perspective view of the second mounting assembly and particularly illustrating a clip;

FIG. 10 is an exploded view of a third mounting assembly that is a hook-and-loop fastener;

FIG. 11 is a front exploded view of a fourth mounting assembly for securing the camera component and the recording component together in a vehicle and particularly illustrating the camera component mounted to the clip of the second mounting assembly;

FIG. 12 is a rear exploded view of the fourth mounting assembly of FIG. 11;

FIG. 13 is an exploded view of the clip and a mounting bracket of the fourth mounting assembly and particularly illustrating mounting of the camera component;

FIG. 14 is a fragment front perspective view of the clip mounted in the mounting bracket and particularly illustrating structure that frictionally secures the clip in place;

FIG. 15 is a front perspective view of the camera component mounted to the clip, and the clip mounted on a mounting arm of the fourth mounting assembly;

FIG. 16 is a rear perspective view of the fourth mounted assembly of FIG. 15;

FIG. 17 is a left side elevation view of the assembly of FIG. 15;

FIG. 18 is a front exploded view of a fifth mounting assembly similar to the fourth mounting assembly of FIG. 13 but particularly illustrating the camera component mounted to the button-mount assembly of FIG. 2;

FIG. 19 is a rear perspective view of the camera component mounted by the fifth mounting assembly;

FIG. 20 is a horizontal cross sectional view taken through line 20-20 of FIG. 19 and illustrating a boss secured within the button-mount assembly of FIG. 2;

FIG. 21 is an environmental view of a sixth mounting assembly for mounting the system to a user's head or hat;

FIG. 22 is a rear perspective view of a portion of the sixth mounting assembly and particularly illustrating mounting of the camera component;

FIG. 23 is a front exploded view of the camera component mounted via the sixth assembly and particularly illustrating a first angle of rotation of the camera component;

FIG. 24 is a rear exploded view of the camera component mounted via the sixth assembly of FIG. 23;

FIG. 25 is a rear perspective view of the camera component mounted by the sixth mounting assembly;

FIG. 26 is a front perspective view of a seventh mounting assembly for mounting the camera component;

FIG. 27 is a rear perspective view of the seventh mounting assembly of FIG. 26;

FIG. 28 is a front perspective view of an eighth mounting assembly for mounting the camera component;

FIG. 29 is a rear perspective view of the eighth mounting assembly of FIG. 28; and

FIG. 30 is a schematic of the camera component and recording component of embodiments of the invention.

The drawing figures do not limit the current invention to the specific embodiments disclosed and described herein. The drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the invention.

#### DETAILED DESCRIPTION

The following detailed description references the accompanying drawings that illustrate specific embodiments in which the invention can be practiced. The embodiments are intended to describe aspects of the invention in sufficient detail to enable those skilled in the art to practice the invention. Other embodiments can be utilized and changes

can be made without departing from the scope of the current invention. The following detailed description is, therefore, not to be taken in a limiting sense. The scope of the current invention is defined only by the appended claims, along with the full scope of equivalents to which such claims are entitled.

In this description, references to "one embodiment," "an embodiment," or "embodiments" mean that the feature or features being referred to are included in at least one embodiment of the technology. Separate references to "one embodiment," "an embodiment," or "embodiments" in this description do not necessarily refer to the same embodiment and are also not mutually exclusive unless so stated and/or except as will be readily apparent to those skilled in the art from the description. For example, a feature, structure, act, etc. described in one embodiment may also be included in other embodiments, but is not necessarily included. Thus, the current technology can include a variety of combinations and/or integrations of the embodiments described herein.

Features and components of embodiments of the invention may be, in some respects, similar to features and components described in U.S. application Ser. No. 14/040,006, filed Sep. 27, 2013, claiming priority to U.S. Provisional Patent Application No. 61/707,326, filed Sep. 28, 2012, and entitled "MOBILE VIDEO AND IMAGING SYSTEM" (identified above in the Related Applications section), and owned by the assignee of the present application. The referenced non-provisional application filed concurrently herewith and claiming priority to the '326 Provisional Application is incorporated by reference herein in its entirety. Additionally, the following patent and patent application, both of which are owned by the assignee of the present application, are incorporated by reference herein in their entirety: U.S. Pat. No. 8,520,069, issued Aug. 27, 2013, and entitled "VEHICLE-MOUNTED VIDEO SYSTEM WITH DISTRIBUTED PROCESSING; and U.S. patent application Ser. No. 13/967,151, filed Aug. 14, 2013, entitled "COMPUTER PROGRAM, METHOD, AND SYSTEM FOR MANAGING MULTIPLE DATA RECORDING DEVICES."

Turning to the figures, and particularly FIG. 1, an embodiment of the present invention is a digital video recording system 10 broadly comprising a camera component 12, a recording component 14, and a mounting assembly 16. The digital video recording system 10 is portable and relatively small, such that the system can be easily carried by a user on the user's body, a clothing article of the user, a device carried by the user, such as a firearm, or in a vehicle. The system 10 is unobtrusive and lightweight so as to not interfere with routine activity by the user. Moreover, the mounting assembly 16 of the system 10 for mounting on the user's body or clothing article of the user provides a secure mount that will not become dislodged, even under active movement by the user.

In embodiments of the invention, the digital video recording system 10 is advantageous for use by law enforcement personnel during an event, such as approaching a suspect or performing an arrest. Law enforcement personnel routinely encounter physically demanding activities and other rigors. The mounting assembly 16 of embodiments of the invention provides secure mounting configurations that can be used by the law enforcement personnel during these demanding activities and based on their preference of location on the personnel's body or clothing. Although embodiments of the invention are adapted for law enforcement personnel, it should be appreciated that the digital video recording system 10 can be used by any user desiring to record events

occurring in front of and around the user or a vehicle (in embodiments where the recorder is mounted in the vehicle).

In embodiments of the invention, the camera component **12** is physically separated from the recording component **14**, such that each component **12,14** is housed in its own distinct housing, as described in more detail below. The camera and recording components **12,14** are, in embodiments, communicatively coupled via cabling **18**, such as a pigtail cable having a mini-USB for interconnecting the two components. In alternative embodiments, the camera and recording components **12,14** are wirelessly communicatively coupled, and wireless signals comprising instructions or data may be transmitted via communications networks such as the Internet, Wi-Fi links, radio-frequency (“RF”) links, Bluetooth technology, infrared (IR), Near Field Communication (NFC) technology, or long and short wave radio.

The camera component **12** is configured to capture video or still images (individually or collectively, “video”) and to transmit the captured video to the recording component **14** for storage on a memory of the recording component, as further discussed below. By separating the housing for the camera component **12** from the housing for the recording component **14**, the housing for the camera component can be very small, light, and easily mounted in multiple locations. Additionally, should the camera component **12** be dislodged or removed during physical activity, such as an altercation between law enforcement personnel and a suspect, the recording component **14** that stores the captured video is not removed or damaged. For example, should the suspect remove the camera component **12** from the law enforcement personnel’s body, the recording component **14** is not also removed (or at least not easily removed). In situations where the captured video is legally important to law enforcement personnel (such as evidence to establish a particular event occurred), insuring that the captured video is not stolen or destroyed is advantageous.

The camera component **12** generally includes image and audio capture components and circuitry, such as a camera **20**, a microphone **22**, and user interface elements **24** for providing input or instructions to the camera. The camera **20** comprises an image sensor **26** and a lens **28** and is configured to operate with relatively little ambient light. The image sensor **26** is a high-sensitivity image sensor operable to capture video in HD and in low light at a minimum lux of at least 0.0687 lux. Suitable image sensors of embodiments of the invention are sold by Omnivision™, Product No. OV10630-CBGA. In embodiments of the invention, a suitable lens **28** of the camera **20** is sold by Sunex Digital Imaging Optics™, Product No. DSL235, and a suitable lens holder is also sold by Sunex, Part No. CMT233. The lens **28** has the following field of view: horizontal, 97 degrees; vertical, 70 degrees; and diagonal, 136 degrees. In embodiments of the invention, the camera **20** is operable to record in 720p video with an H.264 codec, a 1280×720 resolution, and at 30 frames per second. Moreover, encoded, captured video may be viewed on standardized video-viewing software. It should be appreciated that other image sensors and lenses could be employed in embodiments of the invention.

In alternative embodiments of the invention, the camera component **12** may also include a memory element (not shown) for temporarily storing captured video prior to transmission to the recording component **14**. In such an embodiment, storage of the captured video on the memory element of the camera component **12** is cached for short-term storage, such as if the captured video cannot be transmitted to the recording component **14**.

As noted above, the camera component **12** includes a first housing **30**. A width of the housing **30** is approximately 0.25 inch to approximately 5 inches, approximately 0.5 inch to approximately 4 inches, approximately 0.75 inch to approximately 3 inches, or approximately 1.125 inch. A height of the housing **30** is approximately 0.5 inch to approximately 5 inches, approximately 0.75 inch to approximately 4 inches, approximately 1.25 inches to approximately 3 inches, or approximately 1.5 inches. A depth of the housing (excluding the lens and lens holder that extend from a main body of the housing **30**) is approximately 0.15 inch to approximately 1 inch, approximately 0.25 inch to approximately 0.9 inch, approximately 0.35 inch to approximately 0.75 inch, or approximately 0.5 inch. Additionally, the camera component **12** weighs less than or equal to 5 ounces, less than or equal to 3 ounces, less than or equal to 1 ounce, or approximately 0.8 ounce.

The housing **30** is made of ABS or other lightweight, durable material and is covered with neoprene to be soft to the touch and water resistant. The housing **30** includes the user interface elements **24** positioned thereon, which in embodiments of the invention comprise at least a first input **32** and a second input **34**. The first input **32** is a power on/off switch that can be actuated to a power on position where the system **10** is, in various embodiments of the invention, either (1) in a standby mode, such that the system is ready to begin capturing video upon instruction by the user; (2) in a capture mode, such that the system begins continuously capturing video upon actuation of the power on/off switch; or (3) in a trigger event mode, such that the system begins capturing video upon a triggering event, as described in more detail below. The first input **32** is a slide switch that can be moved from an actuated position to a non-actuated position. When in an actuated position, the first input **32** slides to reveal a green-colored portion of the housing to indicate the actuated position to the user. The first input **32** is located on a side of the housing **30**.

The second input **34** controls active record and marking of an event. In particular, in embodiments of the invention where the first input **32** places the camera component **12** in a standby mode, the user can quickly instruct recording by depressing or otherwise actuating the second input **34**. During recording of an event, the user can also mark the captured video. “Marking” of the captured video provides an indication of a point in time, i.e., the time when the user depresses the second input **34**. The user can then quickly move to marked locations in the captured video upon viewing of the video using standardized video viewing software. Marking of the captured video allows the user to identify the point in time at which a particular event in the captured video occurs. Actuation of the second input **34** thus serves as both an instruction to begin recording and to mark the captured video to identify a time or location in the captured video corresponding to actuation of the second input **34**.

The microphone **22** is mounted in the housing **30** and is operable to capture audio of an event. The microphone **22** comprises at least one opening **36** on a front of the housing **30**. In embodiments of the invention, the housing **30** includes a third input (not shown) for stopping or otherwise muting the recording of audio (while still recording video). This third input may be desired by some law enforcement personnel located in a jurisdiction that does not allow audio recordings of an event.

In embodiments of the invention, the housing **30** does not include any LEDs or other indication that the camera component **12** is recording so that persons encountered by

the user of the system **10** do not realize they are being recorded. However, in alternative embodiments, the housing **30** may include one or more LEDs or other indicators to identify recording by the system **10**, and such indicators may or may not be viewable by persons other than the user of the system **10**.

As shown in FIGS. **1** and **2**, the cabling **18** for communicatively connecting the housing **30** to the recording component **14** extends from a rear of the housing **30**. Various lengths of cabling **18** may be provided depending on how and where the user mounts the camera component **12** and the recording component **14**.

Referring to FIG. **30**, the recording component **14** generally includes a processing element **38**, a memory element **40**, a power element **42**, and at least one communication port **44**. As noted above, the recording component is housed in a second housing **46** that is physically separate from the first housing **30** of the camera component.

The processing element **38** may include processors, microprocessors, microcontrollers, digital signal processors (DSPs), field-programmable gate arrays (FPGAs), analog and/or digital application-specific integrated circuits (ASICs), and the like, or combinations thereof. The processing element **38** may generally execute, process, or run instructions, code, software, firmware, programs, applications, apps, processes, services, daemons, or the like, or may step through states of a finite-state machine.

The memory element **40** may include data storage components such as read-only memory (ROM), programmable ROM, erasable programmable ROM, random-access memory (RAM), hard disks, floppy disks, optical disks, flash memory, thumb drives, universal serial bus (USB) drives, and the like, or combinations thereof. In embodiments, the memory element **40** is a solid state element with no moving parts. The memory element **40** may include, or may constitute, a non-transitory "computer-readable storage medium." The memory element **40** may store the instructions, code, software, firmware, programs, applications, apps, services, daemons, or the like that are executed by the processing element **40**. In particular embodiments, the memory element **40** stores the video captured by the camera component **12** and transmitted to the recording component **14**. The memory element **40** may also store settings, data, documents, sound files, photographs, movies, images, databases, and the like. The processing element **38** may be in communication with the memory element **40** through address busses, data busses, control lines, and the like.

The power element **42** is a battery or other component for providing power to the system **10**. The power element **42** is housed in the second housing **46** and is, in embodiment, rechargeable. In embodiments, the batter can be easily removed and replaced in the field, which extends the operating time and use for the system **10**.

The at least one communication port **44** generally allows the recording component **14** to communicate with the camera component **12** or a server or other computing device (not shown) through a communications network (not shown). Thus, the communication port **44** may be in communication with the processing element **38** and the memory element **40**.

The communication port **44** may be wired and may include connectors or couplers to receive metal conductor cables or connectors or optical fiber cables. In embodiments, a first communication port **44a** is a mini-USB port (also known as a micro-USB port) for receipt of the mini-USB adaptor from the cabling **18** for transmission of captured data from the camera component **12** and to the recording component **14**. In embodiments, the port **44a** is recessed

within the second housing **46** to allow for quick break-away of the cabling **18** from the recording component **14**. Such may be desirable if the user is in a situation where the camera component **12** is being removed or dislodged from the user's body or clothing, as the recording component having the stored video is not also removed with the camera component **12**. The at least one communication port **44** may also comprise a second communication port **44b** for receipt of a mini-USB for transmission of recorded video to a computing device.

In embodiments, the at least one communication port **44** may also or alternatively be wireless and may include antennas, signal or data receiving circuits, and signal or data transmitting circuits. The communication port **44** may transmit and receive radio frequency (RF) signals and/or data and may operate utilizing communication standards such as cellular 2G, 3G, or 4G, IEEE 802.11 or 802.16 standards, Bluetooth™, or combinations thereof.

The second housing **46** for the recording component **14** is generally rectangularly-shaped, although it could be other shapes. In embodiments, the second housing is sized and configured to be positioned in the user's front breast pocket or front pants pocket, as illustrated in FIG. **1**, when the camera component **12** is mounted to a front of the user's shirt. A width of the second housing **46** is approximately 1 inch to approximately 5 inches, approximately 1.5 inches to approximately 4 inches, approximately 2 inches to approximately 3 inches, or approximately 2.625 inches. A height or length of the housing **46** is approximately 1 inch to approximately 8 inches, approximately 2 inches to approximately 7 inches, approximately 3 inches to approximately 6 inches, or approximately 4 inches. A depth of the housing **46** is approximately 0.15 inch to approximately 1 inch, approximately 0.25 inch to approximately 0.9 inch, approximately 0.35 inch to approximately 0.75 inch, or approximately 0.625 inch. Additionally, the recording component **14** weighs less than or equal to 7 ounces, less than or equal to 5 ounces, less than or equal to 4 ounces, or approximately 3.1 ounces. Similar to the first housing **30**, the second housing **46** is made of ABS or other lightweight, durable material and is covered with neoprene to be soft to the touch and water resistant. The communication ports **44a,44b** are positioned on the housing **46**.

In embodiments of the invention, the digital video recording system **10** may be provided with "pre-event" recording program and method in which the system **10** records constantly in a loop of a selected duration of time, such as thirty seconds or sixty seconds. Upon a triggering event occurring, as described below, the camera component **12** transmits to the recording component **14** the captured video for the selected duration of time, e.g., the thirty-second segment of captured video occurring prior to the triggering event. Examples of a triggering event may include, for example, the user actuating the second input **34** to instruct recording by the camera component **12**, turning on a vehicle's siren and/or signal lights, an accelerometer measurement outside a pre-established norm, a position of the vehicle and/or officer as measured by a GPS, a vehicle crash event or the police vehicle attaining a threshold speed (e.g., 80 m.p.h.), etc. In embodiments, the recording component **14** may receive a signal from, for example, the vehicle indicative of a triggering event. In response to receipt of the signal, or based on a type of triggering event as evidenced by the signal, the recording component **14** may begin recording.

The digital video recording system **10** may also generate time stamps for the captured video. In such an embodiment, the system **10** includes a clock (not shown) for noting a time

when a particular item of video is captured. The recording component **14** then identifies each frame based on the time generated by the clock. Each frame of the captured video has a unique time stamp. An officer or other user reviewing the captured video will then know when a particular image or item of video obtained from the recording component **14**. In even further embodiments, the time stamp may include a date (if not already included in the time stamp), any triggering event (as described herein), etc.

Various embodiments of the digital video recording system **10** may include any one or more of the following features: required entry of a password or code prior to accessing and changing operational settings; required use of a key to unlock a lockable housing for removal of any removable memory components; incorporation of electronic watermarks into the recorded video images to prevent tampering or alteration; wireless downloading of the contents of the memory element **40** to a laptop or other computer; streaming the live video from the camera component **12** and possibly other inputs and/or outputs via a high-speed wireless data network; encoding of multiple video streams from multiple cameras simultaneously; a remote control device for allowing a user to remotely control the operation of the system **10**; and a temperature sensor and temperature indicator operable to detect and warn the user if the system **10** is at risk of malfunction or damage due to an ambient temperature that is too high or too low for proper operation, such as may easily occur in a vehicle on a very hot or very cold day. The housings **30,46** may be vented to dissipate heat and may include other passive or active features to moderate temperature, especially in relatively extreme environments. Embodiments of the invention may also include a computer program for viewing the captured video on a mobile communications device, such as via an app, at a website, or using viewing software.

In yet further alternative embodiments, the system **10** may also include an integrated GPS receiver (not shown) connected to a GPS antenna (not shown). Utilizing the information provided by these components, the system **10** may mark recorded video with real-time position data of where the captured video was taken. The system **10** may include a “dead reckoning” function that works with GPS to allow for operation in shielded locations, such as underground garages. Some embodiments may communicate directly with the GPS receiver so that GPS coordinates stored in video event metadata may be automatically updated upon the automatic or manual marking or flagging of a video event.

In addition or as an alternative to the GPS, embodiments of the invention may include an RFID or another type of location or identification feature or sensor (not shown) that informs the system **10** of the location of the camera component **12** and/or the recording component **14**. In embodiments, the RFID is mounted within the first housing **30** of the camera component to identify the user using the system **10** and potentially a location of the camera component **12**.

Turning now to FIGS. 2-29, various mounting assemblies **16** are illustrated. As discussed above, the camera component **12** and/or both the camera and recording components **12,14** are configured to be mounted to the user’s body or clothing, a device carried by the user, or a vehicle. In embodiments of the invention, the mounting assemblies **16** are interchangeable, so that the user may mount the camera component **12** and/or the recording component **14** in various positions and locations based on the desired preferences of the user. As illustrated in FIG. 1, to facilitate ease of manufacture, mounting, purchase, and use of the camera and

recording components **12,14**, the camera component **12** includes a generally square-shaped recessed seat **48** located on a rear of the first housing **30** for securing or otherwise coupling the user-preferred mounting assembly to the camera component **12**. The recessed seat is sized and configured to couple to each of the mounting assemblies **16**, as described below, so as to present a system **10** with the interchangeable mounting assemblies.

In a first mounting assembly **16a** illustrated in FIGS. 2-7, the mounting assembly is a button-mount assembly for mounting the camera component **12** to a button **50** located on the user’s shirt. The mounting assembly **16a** broadly comprises a slotted plate **52**, a mounting bracket **54** forwardly extending from the slotted plate **52**, a longitudinal track **56** formed between the slotted plate **52** and the mounting bracket **54**, a retention clip **58** held in the longitudinal track **56** and for preventing the mounting assembly **16a** from becoming dislodged from the user’s clothing, and a coupler **60** for securing the mounting assembly **16a** to the camera component **12**.

The slotted plate **52** comprises a generally rectangular-shaped, flat body **62** having a slot **64** formed therethrough. The slot **64** is formed in the body **62** of the plate **52** along a general longitudinal axis of the plate **52**. The longitudinal axis generally coincides with the height of the camera component **12** once the mounting assembly **16a** is coupled with the camera component **12**. Alternatively, the slot **64** could be formed along a transverse, diagonal, or other axis of the plate **52**. The slot **64** is open at a first, lower end **66** of the slotted plate **52** and closed at a second, general upper end **68** of the slotted plate **52**. In use, the slot **64** is placed behind the button **50** on the user’s shirt and guided downwards over yarn or other material that secures the button **50** to the user’s clothing. Once the slot **64** is positioned over the yarn retaining the button **50**, the button extends from a general front **70** of the slotted plate **52** and the yarn or other material securing the button to the user’s clothing is held within the slot **64** of the slotted plate **52**. A rear **72** of the slotted plate **52** is then adjacent the user’s shirt.

The mounting bracket **54** is integrally formed on or coupled to the front **70** of the slotted plate **52**, such that the mounting bracket **54** at least partially overlays and forwardly extends from the front **70** of the plate **52**. The bracket **54** thus presents a raised area comprising the longitudinal track **56** between the front **70** of the plate **52** and a front **74** of the bracket **54**. The track **56** extends along at least a portion of the slot **64**. When the button-mount assembly **16a** is mounted to the button **50** of the user’s clothing, the button **50** is held in the longitudinal track **56** between the front **70** of the slotted plate **52** and the mounting bracket **54**.

To insure that the button-mount assembly **16a** does not become dislodged from the user’s clothing, the assembly **16a** further includes the retention clip **58**, as illustrated in FIGS. 5-7. The retention clip **58** is mechanically secured within the longitudinal track **56**, as further described below. The clip **58** comprises a generally flat body **76** having a transverse shoulder **78** and two longitudinally-extending legs **80**. A top **82** of the shoulder **78** is provided with an inverted saddle **84** that is arcuate in shape to interfit and mate with an arcuate shape of the button **50**. The legs **80** extend downwards from a bottom **86** of the shoulder **78**, and a lower end **88** of each leg **80** is toothed **90** to facilitate grasping of the legs by the user.

To position the retention clip **58** within the longitudinal track **56**, the user slides the clip upwards, shoulder first, so that the inverted saddle **84** seats with the button. Each leg **80** is provided with an outwardly extending, chamfered tab **92**.

## 11

The longitudinal track **56** has receiving openings **94** formed at a general lower end of the track **56**. To secure the clip **58** within the track **56**, the legs **80** are transversely resilient so that they can be flexed inwards towards each other. The user places a finger at the toothed portion **90** of each leg **80** and slightly pushes inwards while sliding the retention clip **58** upwards into the track **56**. Once seated within the track **56**, the user releases the inwards pressure on the legs **80**, which returns the legs **80** to a neutral state and locates the outwardly extending tabs **92** on the legs within the receiving openings **94** on the track **56**. To remove the camera component **12** from the user's clothing, the user reverses the above process by pressing inwardly on the toothed portion **90** of the legs to remove the tabs **92** from the openings **94** in the track **56** and allow the retention clip **58** to be slid out of the track **56**. The user can then remove the slotted plate **52** from the button **50**.

The coupler **60** of the button-mount assembly **16** comprises a ledge **96** integral or coupled with the mounting bracket **54** and sized and configured to interfit with the recessed seat **48** on the rear of the housing **30**, and a screw **98** for securing the combined mounting bracket **54** and slotted plate **52** to the camera component **12**. As illustrated in FIG. 2, the ledge **96** is positioned on the front **74** of the mounting bracket **54**. The ledge **96** is generally square-shaped to match the generally square-shaped recessed seat **48** on the camera component housing **30**. As can be appreciated, the perimeter of the ledge **96** may be slightly less than an inner perimeter of the recessed seat **48** to insure the ledge **96** fits or seats within the recessed seat **48**.

As illustrated in FIG. 2, a small opening or hole **100** is formed in the front **74** of the mounting bracket **54** to receive the screw **98** therethrough. The screw **98** is received within a similarly-sized threaded opening **102** on the rear of the camera component housing **30**. The user screws the combined slotted plate **52** and mounting bracket **54** to the rear of the camera component housing **30** by placing the screw **98** through the hole **100** in the bracket **54** and threading in the opening **102**.

Referring now to FIGS. 8-9, a second mounting assembly **16b** is illustrated and comprises a clip **104** configured for grasping a clothing article of the user. In embodiments, the clip **104** is an alligator clip and comprises a first, bottom plate **106**, a second, top plate **108**, a spring **110** interposed between the plates **106,108** to provide resilient grasping tension, and a coupler **112**. Referring to FIG. 9, each plate **106,108** has an inner face **114**, an outer face **116**, a grasping end **118** that is grasped by the user when positioning the clip **104**, and an open end **120** that opens up to receive the user's clothing or other structure to which the clip **104** is being attached.

The plates **106,108** are pivotably secured together at their respective grasping ends **118**. The spring **110** is interposed between the plates **106,108** to provide a pivot point about which the plates are pivoted. The spring **110** is a flat, U-shaped spring, and opposing ends **122** of the spring **110** are secured to the inner face **114** of each plate **106,108**. In the spring's rest state, the opposing ends **122** of the spring **110** extend outwardly. Upon the user grasping each of the grasping ends **118** of the plates **106,108**, the opposing ends **122** of the spring **110** are pushed together to pivot the grasping ends **118** of each plate **106,108** towards each other and, in response, pivot the open ends **120** of each plate **106,108** away from each other.

In a plan view, each plate **106,108** has the same general shape. However, when viewing the clip **104** from the sides, it can be seen that the first, bottom plate **106** is generally flat,

## 12

except that the grasping end **118** angles slightly downwards. The second, top plate **108** is also generally flat, except that the grasping end **118** angles slightly upwards. The angle for the top plate **108** is greater than the angle for the lower plate **106**. This provides better positioning for the user to apply force at the grasping end **118** when the user is applying pressure to the top plate **108** to open the plates **106,108**. As is illustrated, the outer face **116** of each plate **106,108** at the grasping end **118** includes a plurality of depressions **124** to assist in tactile gripping of the plates during positioning of the clip **104**.

Referring to FIG. 11 (which illustrates both a second mounting assembly **16b** and the second mounting assembly **16b** working in conjunction with a fourth mounting assembly **16d**), the coupler **112** comprises a raised seat **126** and a screw **128**. The raised seat **126** is integral with or secured to the outer face **116** of the bottom plate **106**. Similar to the first mounting assembly **16a** and the ledge **96** of the mounting bracket **54**, a perimeter and a shape of the raised seat **126** is approximately the same as the perimeter and shape of the recessed seat **48** on the rear of the camera component housing **30**. The raised seat **126** of the clip **104** then interfits with the recessed seat **48** of the housing **30**. As can be appreciated, the perimeter of the raised seat **126** may be slightly less than an inner perimeter of the recessed seat **48** to insure the raised seat **126** fits or seats within the recessed seat **48**.

The screw **128** is threaded through an opening **130** in the bottom plate **106** to secure the clip **104** to the camera component **12**. The clip **104** can be mounted to the camera component **12** in a plurality of directions by rotating the orientation of the clip **104** relative to the housing **30**.

A third mounting assembly **16c** is illustrated in FIG. 10 and is a hook-and-loop mount (also known as Velcro™). The hook-and-loop mounting assembly **16c** broadly comprises a plate **132**, a mounting bracket (not shown) substantially similar to the mounting bracket **54**, a coupler **136** for coupling the plate **132** and mounting bracket to the camera component housing **30**, and adhesively-securable hook-and-loop material **138**. The plate **132** and mounting bracket are, in embodiments, integral, although the mounting bracket may be, in alternative embodiments, a separate component coupled with the plate **132**. The plate **132** is generally rectangular-shaped. The mounting bracket is integrally formed on or coupled to a front **140** of the plate **132**, such that the mounting bracket at least partially overlays and forwardly extends from the front **140** of the plate **132**.

The coupler **136** comprises a ledge (not shown but substantially similar to the ledge **96** of mounting bracket **54**) integral or coupled with the mounting bracket and sized and configured to interfit with the recessed seat **48** on the rear of the camera component housing **30**, and a screw **144** for securing the combined mounting bracket and plate **132** to the camera component **12**. Similar to ledge **96**, the ledge of mounting assembly **16c** is positioned on a front of the mounting bracket. The ledge is generally square-shaped to match the generally square-shaped recessed seat **48** on the camera component housing **30**. As can be appreciated, the perimeter of the ledge may be slightly less than an inner perimeter of the recessed seat **48** to insure the ledge fits or seats within the recessed seat **48**. To secure the mounting assembly **16c** to the camera component housing **30**, the screw **144** is threaded through an opening **146** in the mounting bracket.

The hook-and-loop material **138** comprises a first substrate **148** having a hooked material **150** on one face and adhesive (not shown) on another face, and a second substrate

152 having a loop material 154 on one face and adhesive (not shown) on another face. One of the first and second substrates 148, 152 is adhesively secured to a rear of the plate 132, and the other of the substrates 148, 152 is adhesively secured to a structure to which the system 10 is desired to be mounted. The user can then mate the hook-and-loop materials 150, 154 to secure the system 10 to the desired structure.

A small opening or hole is formed through the plate 132 and mounting bracket to receive the screw 144 therethrough. The user then screws the combined plate and mounting bracket to the rear of the camera component housing 30 by threading the screw 144 through the opening.

A fourth mounting assembly 16d is illustrated in FIGS. 11-17 and is a cradle mount for mounting both the camera component 12 and the recording component 14. The mounting assembly 16d broadly comprises a cradle 158, a mounting arm 160, a first clip mounting bracket 162, and the clip 104 of the mounting assembly 16b. The cradle 158 is sized and configured to releasably and easily mount the recording component 14. The cradle 158 includes a main body 164 with a plurality of flexible arms 166 extending therefrom to secure the recording component 14 in the cradle. The plurality of arms 166 extend from the body 164 at generally right angles to the body. An outermost end 168 of each arm 166 curves slightly inwardly to hold the recording component 14 within the cradle 158. In particular, the recording component 14 is snap-fit within the cradle 158, such that the flexible arms 166 can be moved slightly outwardly to place the recording component 14 against the cradle's body 164. The outermost end 168 of each arm 166 then wraps around the recording component 14 to snap or frictionally secure the recording component 14 within the cradle 158.

A portion 170 of the body 164 of the cradle 158 extends rearwardly, as illustrated in FIG. 11, to receive the mounting arm 160, and is provided with a plurality of openings 172. The mounting arm 160 can then be secured to the body 164 of the cradle 158 through any one of the openings 172, as discussed in more detail below, depending on a desired positioning of the mounting assembly 16d. It should be appreciated that the mounting arm 160 may also be secured to the body 164 of the cradle 158 in a plurality of angles or orientations. For example, as illustrated in FIG. 11, a longitudinal axis of the mounting arm 160 (i.e., the axis extending from the narrow to the wide ends of the arm) is generally perpendicular to a transverse axis of the cradle 158. However, the mounting arm 160 could be positioned so that its longitudinal axis is generally parallel to the transverse axis of the cradle 164 by rotating the arm approximately 90 degrees to the left or to the right from the orientation shown in FIG. 11. Thus, the mounting arm 160 can be positioned at any desired angle relative to the cradle 158 and further can be positioned at different locations on the cradle 158 by securing a screw through one of the plurality of openings 172 in the cradle 158, as further described below.

The mounting arm 160 comprises a tapered body 174 having a wide end 176 and a narrow end 178. The wide end 176 is provided with a first hole or opening 180 through the body 174 to receive a first screw (not shown) for securing the mounting arm 160 to the body 164 of the cradle 158. In particular, the first screw (not shown) is located through the first opening 180 in the wide end 176 of the mounting arm 160 and through one of the plurality of openings 172 in the body 164 of the cradle 158 to secure the mounting arm 160 to the cradle 158. The narrow end 178 is provided with the second hole or opening 182 through the body 174 to receive a second screw 186 for securing the first clip mounting

bracket 162 to the body 174 of the mounting arm 160. The narrow end 178 of the mounting arm 160 is provided with a raised, generally circular positioning mount 188 for positioning the attached camera component 12 in a plurality of orientations. The circular positioning mount 188 extends generally rearwardly from the body 174 of the mounting arm 160 (i.e., the direction opposite the front of the recording component 14 when mounted in the cradle 158) and includes a plurality of depressions 190. In particular, four depressions 190 are provided, one at each of the general north, south, east, and west locations on the circular positioning mount 188. However, it should be appreciated that more or less depressions may be provided and may also be positioned at different locations on the circular positioning mount 188. The location of each depression 190 corresponds to a preferred angle or orientation of a position of the camera component 12 as described below.

The first clip mounting bracket 162 is sized and configured to removably retain the camera component 12 and includes a front face 192 (facing towards the mounting arm 160 when the first clip mounting bracket 162 is secured to the mounting arm 160) and a rear face 194 (facing towards the rear of the camera component 12 when the camera component 12 is retained in the first clip mounting bracket 162). The front face 192 of the first clip mounting bracket 162 is provided with a plurality of detents 196 configured to be received in the plurality of depressions 190 on the circular positioning mount 188 of the mounting arm 160. In embodiments, the mounting bracket 162 includes four detents 196, one of each provided at the general north, south, east, and west locations to coincide with the location of the depressions 190 on the circular positioning mount 188. However, it should be appreciated that more or less detents 196 may be provided and may also be positioned at different locations on the first clip mounting bracket 162.

The first clip mounting bracket 162 is pivotably secured to the narrow end 178 of the mounting arm 160, as illustrated in FIGS. 11 and 12. The second screw 186 is located through the second hole or opening 182 in the narrow end 178 of the mounting arm 160 and secured to the mounting bracket 162 to couple the components together. To enable pivoting of the clip mounting bracket 162 relative to the mounting arm 160, a spring 198 surrounds the second screw 186. The spring 198 enables the clip mounting bracket 162 to be pulled by the user away from the mounting arm 160, such that the detents 196 on the bracket 162 clear the circular positioning mount 188. That is, in a secure position, the detents 196 are held in or otherwise interfit with the depressions 190, as illustrated in FIGS. 11 and 12. During pivoting of the mounting bracket 162, the bracket is pulled laterally from the mounting arm 160 so that the detents 196 slide above the circular positioning mount 188 during rotation of the bracket 162 relative to the mounting arm 160. Upon rotating the mounting bracket 162 to the desired location, the spring 198 locates the mounting bracket 162 back towards the mounting arm 160, such that the detents 196 again interfit with the depressions 190 and secure the mounting bracket 162 in position.

The rear face 192 of the first clip mounting bracket 162 is provided with a pair of walls 200 that create a track or slot 202 within which the clip 104 of the second mounting assembly 16b can be frictionally secured. As illustrated in FIG. 13, the walls 200 are positioned on the edge of the rear face 192 of the clip mounting bracket 162. A width of the track 202 created between the walls 200 is approximately the same size as (or slightly larger) than a width of the first and second plates 106, 108 of the clip 104. The width of the plates 106, 108 increases from the open end 120 to the

## 15

grasping end **118** of the clip **104**, and similarly, the width of the track **202** in the mounting bracket **162** widens from a lower to an upper end of the track. The camera component **12** can then be secured to the clip **104**, as described above, and the clip **104** can be secured within the track **202** on the clip mounting bracket **162**. To assist with securing the clip **104** in the clip mounting bracket **162**, the walls **200** of the track are each provided with a locking tab **184** at the lower end and as best illustrated in FIGS. **13** and **14**. The locking tab interfits with ridges **185** on the plates **106,108** of the clip **104**.

The fourth mounting assembly **16d** is configured to be mounted to a vehicle, such as the inside of a vehicle near a dashboard, an upper middle console, a windshield, or any other location desired by the user. To mount the mounting assembly **16d** to the vehicle, the mounting assembly further includes a coupler **204**, such as a RAM mount sold by RAM Mounts®. The coupler **204** includes a ball joint **206** operable to be secured to the mounting arm **160** and cradle **158** via a screw (not shown) threaded through the first hole **180** of the mounting arm **160**. Extending from the ball joint **206** is a ball **208** operable to be received in a socket **210** of a separate mounting installation **212**, such as the RAM mount. The separate mounting installation **212** may be a suction-cup unit that includes the socket **210** for receipt of the ball **208** of the ball joint **206**. The suction-cup unit can then be mounted to the windshield or dashboard of the vehicle. Other methods and configurations of mounting the fourth mounting assembly **16d** within the vehicle may be employed.

A fifth mounting assembly **16e** illustrated in FIGS. **18-20** is substantially similar to the fourth mounting assembly **16d**, except that instead of the first clip mounting bracket **162**, the mounting assembly **16e** includes a button mounting bracket **212** sized and configured to operate with the button-mount assembly **16a**. It should be noted that in reference to the figures, like structure is identified with the same reference numeral. The button mounting bracket **212** is operable to be secured to the mounting arm **160** of the fourth mounting assembly **16d** and removably retains the camera component **12**. The button mounting bracket **212** includes a front face **214** (facing towards the mounting arm **160** when the button mounting bracket **212** is secured to the mounting arm **160**) and a rear face **216** (facing towards the rear of the camera component **12** when the camera component **12** is retained on the button mounting bracket **212**). The front face **214** of the button mounting bracket **212** is provided with the plurality of detents **196**, substantially similar to the first clip mounting bracket **162**, that are configured to be received in the plurality of depressions **190** on the circular positioning mount **188** of the mounting arm **160**. The button mounting bracket is pivotably secured to the narrow end **178** of the mounting arm **160**, as illustrated in FIG. **18** and as described above for the fourth mounting assembly **16d**.

The rear face **216** of the button mounting bracket **212** is provided with a large boss **218** that simulates the button to which the button-mount assembly **16a** is attached. Thus, it should be understood that the button mounting bracket **212** does not mount to an actual button but rather uses the button-mount assembly **16a** to removably couple the camera component housing **30** to the mounting arm **160** via the button mounting bracket **212**. That is, when the camera component **12** has the button-mount assembly **16a** secured to it, the mounting bracket **54** of mounting assembly **16a** is slid over the boss **218**, such that the boss **218** fits within the longitudinal track **56** of the mounting bracket **54**. The

## 16

retention clip **58** can then be used to secure the mounting bracket **54** on the boss, as described above for mounting assembly **16a**.

Similar to the fourth mounting assembly **16d**, the button mounting bracket **212** of the fifth mounting assembly **16e** is sized and configured to be pivotably secured to the mounting arm **160**, and the mounting arm is in turn secured to the cradle **158**. The fifth mounting assembly **16e** thus provides for indirectly mounting the camera component **12** to the cradle **158** via the mounting arm **160** without having to remove the button-mount assembly **16a** secured to the camera component housing **30**. In embodiments, the user is provided with two mounting arms **160**, each having either the first clip mounting bracket **162** or the button mounting bracket **212** secured thereto so that the user does not have to remove the respective mounting bracket **162,212**.

A sixth mounting assembly **16f** is illustrated in FIGS. **21** and **22** and is a hat mount for mounting the video recording system **10** to the user's helmet, cap, or other type of hat **220**, directly to the user's head, or to an animal, such as a canine. The sixth mounting assembly **16f** works in conjunction with a strap **222** that surrounds the hat **220**, such as a strap that is buckled or stretchable to fit securely on the hat. The mounting assembly **16f** is sized and configured to mount the button-mount assembly **16a** described above. That is, when the camera component **12** is secured to the button-mount assembly **16a**, the button-mount assembly **16a** can be secured to the user's hat **220** via the mounting assembly **16f**, such that the camera component **12** is secured to the user's hat. The recording component **14** can also be secured to the user's hat **220** via the mounting assembly **16f**. In particular, when the recording component **14** is mounted in the cradle **158** of mounting assembly **16d** or **16e**, the cradle can be mounted to the hat via the mounting assembly **16f**, as further described below.

The mounting assembly **16f** broadly comprises a first mounting plate **224** for mounting the camera component **12** and a second mounting plate **226** for mounting the recording component **14**. The first mounting plate **224** is slightly concave about a lateral axis to fit snugly against an arcuate crown of the hat **220**. The first mounting plate **224** comprises two vertical slots **228** formed in the plate **224** for threading of the strap **222** on the hat **220** therethrough. A third lateral slot **230** is provided along a top end of the plate **224** for a further securement point, if desired. An outward face of the plate **224** includes a hinged backplate **232** for receipt of the button-mount assembly **16a**. As illustrated in FIG. **21**, the hinged backplate **232** is attached, at its general bottom end, to a general bottom center of the first mounting plate **224** via a hinge **234**. The backplate **232** is rotatable along a vertical axis relative to the first mounting plate **224**, and in embodiments, pressure actuated by the user is needed to rotate the backplate **232** (that is, the backplate **232** does not rotate easily, such that the attached camera component **12** stays in the desired position). A boss, substantially similar to the boss **218**, is located on the hinged backplate **232**. Similar to the mounting assembly **16e**, the button-mount assembly **16a** is secured to the hinged backplate **232** by locating the boss **218** in the longitudinal track of the button-mount assembly **16a**.

Referring to FIG. **21**, the second mounting plate **226** is similar to the first mounting plate **224**, except that the second mounting plate **226** does not include the hinged backplate **232** and instead includes two screw holes **236** for securing the second mounting plate **226** to the cradle **158**. In use, the second mounting plate **226** is positioned to a rear or side of the user's head.

A seventh mounting assembly **16g** is substantially similar to the sixth mounting assembly **16f** that is a hat mount, except that mounting assembly **16g** is sized and configured to mount the camera component **12** when it is attached to the clip **104** of the second mounting assembly **16b**. Referring to FIGS. **23-25**, the mounting assembly **16g** comprises the first and second mounting plates **224,226** that are substantially similar to the first and second mounting plates **224,226** of mounting assembly **16f**. The only difference is that instead of the large boss **218**, the hinged backplate **232** secured to the first mounting plate **224** includes a recessed seat **238** and a post **240**. The seventh mounting assembly **16g** further includes a second clip mounting bracket **242** that is substantially similar to the first clip mounting bracket **162**, except that a front face **246** of the second clip mounting bracket **242** is provided with an octagonal-shaped seat **248** for interfitting with the recessed seat **238** on the hinged backplate **232**. In embodiments, the user can rotate the clip **104** at 45 degree angles relative to the hinged backplate **232**. The octagonal-shaped seat **248** assists with locating the clip **104** at the desired angle. In use, the user secures the clip **104** at the desired angle by inserting a screw **244** through a receiving post **250** on the front face **246** of the second clip mounting bracket **242**. In alternative embodiments, the clip **104** may be rotatable relative to the hinged backplate **232** without having to screw in position. It should be appreciated that the octagonal-shaped seat **248** could be provided on the hinged backplate **232**, and the recessed seat **238** could be provided on the front face **246** of the second clip mounting bracket **242**.

In an eighth mounting assembly **16h** shown in FIGS. **26** and **27**, either of the button-mount assembly **16a** or the clip mounting assembly **16b** (not shown) is secured to the eighth mounting assembly **16h** to provide for angling of the camera component **12** along a vertical axis (i.e., relative to a horizontal plane). The eighth mounting assembly **16h** comprises first and second plates **252,254** secured together via a hinge **256**. The first plate **252** is secured to the rear of the camera component **12** via a screw **258**, and the second plate **254** is secured to either the mounting bracket **54** of the button-mount assembly **16a** or the clip **104** of the clip mounting assembly (not shown). An outer face of the first plate **252** (the face closest to the camera component **12**) includes a raised seat **260** sized and configured to interfit with the recessed seat **48** on the camera component housing **30**. The two plates **252,254** are secured together at their respective bottom ends via the hinge **256**. The hinge **256** allows for rotation of one plate with respect to the other plate. In embodiments, the hinge **256** is generally tight, such that it does not easily rotate but instead will only rotate upon pressure being applied by the user against the first plate **252**, which is secured to the camera component **12**, or the camera component itself.

The user can couple the button-mount assembly **16a** to the second plate **254**, as shown in FIG. **26**. The user can then mount the button-mount assembly **16a** to the user's shirt or article of clothing, as described above. The hinged plates **252,254** allow the camera component **12** to be rotated to different angles relative to the horizon. As noted above, the hinged plates **252,254** of the eighth mounting assembly **16h** could also be secured to the clip **104** of the second mounting assembly **16b**, such that the second plate **254** is secured to the clip **104** via a screw.

Referring now to FIGS. **28** and **29**, a ninth mounting assembly **16i** comprises a saddle bracket **262** for securing the camera component **12** to a barrel of a firearm (not shown). The saddle bracket **262** includes a body **264** having

a top end **266** and a bottom end **268**. A general upper half of the body **264** includes two arms **270** that are sized and configured to extend around the barrel of a firearm. The saddle bracket **262** can then be secured to the firearm by inserting two screws (not shown) through openings **272** in two tabs **274** extending from the top end **266** of the bracket **262**. The bottom end **268** of the saddle bracket **262** is provided with an octagonal-shaped raised seat **276**, similar to the seat **248**. The raised seat **276** is configured to receive the second clip mounting bracket **244** of the seventh mounting assembly **16g**, similar to how the second clip mounting bracket **244** is secured to the hinged backplate **232** of the first mounting plate **224** of mounting assembly **16g**.

Although the invention has been described with reference to the embodiments illustrated in the attached drawing figures, it is noted that equivalents may be employed and substitutions made herein without departing from the scope of the invention as recited in the claims.

Having thus described various embodiments of the invention, what is claimed as new and desired to be protected by Letters Patent includes the following:

1. A portable video and imaging system comprising:
  - a camera configured to capture video of an event;
  - an input manually or automatically actuable and in response to an actuation, generate an activation signal; and
  - at least one processor configured to:
    - receive said activation signal generated in response to the actuation of the input;
    - upon receiving said activation signal, store a mark in a video file identifying a point in time or a location in the video file indicative of the actuation of the input;
    - store the video file comprising the video of the event and the mark; and
    - upon receiving a video playback command, automatically advancing the video to the mark.
2. The portable video and imaging system of claim 1, further comprising a location sensor,
- wherein the actuation is automatically initiated, and the mark is indicative of a geographic location.
3. The portable video and imaging system of claim 2, wherein the camera is configured to be mounted in a vehicle.
4. The portable video and imaging system of claim 2, wherein the at least one processor is further configured to:
  - store metadata comprising the geographic location; and
  - associating the metadata with the video.
5. The portable video and imaging system of claim 1, wherein the actuation is manual, and the mark is indicative of an actuation time of the actuation.
6. The portable video and imaging system of claim 5, wherein the camera is configured to be mounted on a body of a user.
7. The portable video and imaging system of claim 6, wherein the input is a first input, wherein the portable video and imaging system further comprises a second input configured to activate the video, and wherein the first input and the second input are manually actuated.
8. The portable video and imaging system of claim 1, wherein the at least one processor is further configured to:
  - wirelessly transmit the video file to a remote mobile communication device, the remote mobile communication device configured for viewing the video.
9. A portable video and imaging system comprising:
  - a camera configured to capture video of an event,

19

wherein the camera is disposed in a vehicle and configured to be selectively rotatable to capture various directions;

an input manually or automatically actuatable and in response to an actuation, generate an activation signal; and

at least one processor configured to: receive said activation signal generated in response to the actuation of the input; upon receiving said activation signal, store a mark in a video file identifying a point in time or a location in the video file indicative of the actuation of the input; store the video file comprising the video of the event and the mark; and upon receiving a video playback command, automatically advancing the video to the mark.

10. The portable video and imaging system of claim 9, wherein the actuation is automatically initiated, and the mark is indicative of a geographic location.

11. The portable video and imaging system of claim 9, wherein the input is a first input, wherein the portable video and imaging system further comprises a second input configured to initiate storage of the video, and

wherein the first input and the second input are manually actuated.

12. The portable video and imaging system of claim 11, wherein the at least one processor is further configured to store the video including an amount of video data recorded before the actuation of the second input.

13. The portable video and imaging system of claim 12, wherein the at least one processor is further configured to store additional data associated with the vehicle.

14. The portable video and imaging system of claim 13, wherein the additional data comprises vehicle sensor data including speed and acceleration.

15. A portable video and imaging system comprising: a camera configured to capture video of an event,

20

wherein the camera is disposed in a vehicle or on a person and is configured to be selectively rotatable to capture various directions;

an input manually or automatically actuatable and in response to an actuation, generate an activation signal; and

at least one processor configured to: receive said activation signal generated in response to the actuation of the input;

upon receiving said activation signal, store a mark in a video file identifying a point in time or a location in the video file indicative of the actuation of the input; store the video file comprising the video of the event and the mark; and

upon receiving a video playback command, automatically advancing the video to the mark.

16. The portable video and imaging system of claim 15, further comprising:

an identification sensor associated with a user and wherein the at least one processor is further configured to:

determine an identity of the user; and determine a proximity of the user to the at least one processor.

17. The portable video and imaging system of claim 15, wherein the at least one processor is further configured to transmit the video by a cellular communication standard.

18. The portable video and imaging system of claim 15, wherein the at least one processor is further configured to store data indicative of a triggering signal that initiated the video.

19. The portable video and imaging system of claim 15, wherein the camera is configured to transmit captured video data wirelessly to a remote datastore.

20. The portable video and imaging system of claim 19, wherein the at least one processor is further configured to add metadata to the video file, wherein the metadata includes geographic location data and time data.

\* \* \* \* \*