

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 August 2009 (06.08.2009)

PCT


(10) International Publication Number
WO 2009/097554 A1

- (51) International Patent Classification:
G06Q 10/00 (2006.01)
- (21) International Application Number:
PCT/US2009/032686
- (22) International Filing Date: 30 January 2009 (30.01.2009)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/024,756 30 January 2008 (30.01.2008) US
12/362,386 29 January 2009 (29.01.2009) US
- (71) Applicant (for all designated States except US): **THE BOEING COMPANY** [US/US]; 100 North Riverside Plaza, Chicago, Illinois 60606-2016 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BEEBE, Clifford, A.** [US/US]; 2515 175th Avenue SE, Snohomish, Washington 98291 (US). **HASHIMI, Mir, H.** [US/US]; 10715 45th Avenue SE, Everett, Washington 98208 (US). **JAHNS, Stephen, E.** [US/US]; 28106 29th Avenue S, Federal Way,

- Washington 98003-3387 (US). **BOVEY, Lee, Victoria** [US/US]; 6706 163rd Place SW, Lynnwood, Washington 98037 (US). **PIGION, Richard, George** [US/US]; 4119 244th Lane SE, Issaquah, Washington 98029 (US).
- (74) Agent: **TSUDA, Diane, M.**; The Boeing Company, P.O. Box 2515, MC 110-SD54, Seal Beach, California 90740-1515 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: AIRCRAFT MAINTENANCE LAPTOP



(57) Abstract: An apparatus comprises a portable computer, and program code stored on the portable computer. The program code is capable of being executed to establish a communications link with an aircraft network data processing system in an aircraft, obtain information about the aircraft over the communications link, display the information on a display device for the portable computer, receive user input to control a data processing system on the aircraft network data processing system in the aircraft, and send a number of commands to the data processing system in response to receiving the user input. PDA or handheld wireless device for tracking or monitoring the repair works or maintenance being performed on an aircraft. Commands and instructions can be sent to the peripherals connected to the isolated network of the aircraft or airplane.

WO 2009/097554 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ,

CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

AIRCRAFT MAINTENANCE LAPTOP**RELATED PROVISIONAL APPLICATION**

5 The present invention is related to and claims the benefit of priority of provisional U.S. Patent Application Serial No. 61/024,756 entitled "Aircraft Maintenance Laptop", filed on January 30th, 2008, which is hereby incorporated by reference.

BACKGROUND INFORMATION

10

1.Field:

The present disclosure relates generally to an improved data processing system and in particular to a method and apparatus for processing data. Still more particularly, the present disclosure relates to a computer implemented method, apparatus, and computer usable program code for performing maintenance on an aircraft.

15

2.Background:

Modern aircraft are extremely complex. For example, an aircraft may have many types of electronic systems on board. A particular component within an electronic system on an aircraft may also be referred to as a line replaceable unit (LRU). Each line replaceable unit may further take on various forms. A line replaceable unit may be, for example, without limitation, a component of a flight management system, an autopilot, an in-flight entertainment system, a communications system, a navigation system, a flight controller, a flight recorder, and a collision avoidance system. An aircraft also has various complex electrical wiring, mechanical, and hydraulic systems. These types of systems may be controlled by line replaceable units.

25

Personnel, such as aircraft maintenance technicians and line maintenance mechanics may perform various maintenance activities on an aircraft. These activities may include, for example, monitoring systems, diagnosing problems, troubleshooting issues, preparing failed or damaged items, or other suitable maintenance activities.

30

Currently, maintenance personnel employ a multitude of different tools in performing maintenance on different systems within an aircraft. The number of tools and the cost of the tools may increase the cost for maintaining aircraft.

Therefore, it would be advantageous to have a method and apparatus that overcomes the problems described above.

SUMMARY

5

In one advantageous embodiment, an apparatus comprises a portable computer and program code stored on the portable computer. The program code is capable of being executed to establish a communications link with an aircraft network data processing system in an aircraft, obtain information about the aircraft over the communications link, display the information on a display device for the portable computer, receive user input to control a data processing system on the aircraft network data processing system in the aircraft, and send a number of commands to the data processing system in response to receiving the user input.

In another advantageous embodiment, an apparatus for performing maintenance operations on an aircraft comprises a health and fault information process, an aircraft system information process, an aircraft support information access process, a flight control rigging process, a circuit breaker and contactor process, and a laptop computer. The health and fault information process is capable of accessing health and fault information on the aircraft. The aircraft system information process is capable of accessing status information for the aircraft. The aircraft support information access process is capable of accessing support information for the aircraft. The flight control rigging process is capable of rigging flight control surfaces on the aircraft. The circuit breaker and contactor process is capable of obtaining and manipulating a state of circuit breakers and contactors on the aircraft. The laptop computer is capable of establishing a wireless communications link with an aircraft network data processing system located within a selected distance of the laptop computer. The health and fault information process, the aircraft support information access process, the aircraft system information process, the flight control rigging process, and the circuit breaker and contactor process execute on the laptop computer.

In yet another advantageous embodiment, a method is present for performing maintenance operations. A communications links is established with an aircraft network data processing system in an aircraft using a portable computer. Information is received at the portable computer about the aircraft from the aircraft network data processing system. A number of data processing systems in the aircraft are controlled using the portable computer to perform a maintenance operation.

In still yet another advantageous embodiment, a computer program product for performing maintenance operations comprises a computer recordable storage medium and program code stored on the computer recordable storage medium. Program code is present for establishing a communications link with an aircraft network data processing system in an aircraft using a portable computer. Program code is also present for receiving information at the portable computer about the aircraft from the aircraft network data processing system. Further, program code is present for controlling a number of data processing systems in the aircraft using the portable computer to perform a maintenance operation.

The features, functions, and advantages can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the advantageous embodiments are set forth in the appended claims. The advantageous embodiments, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an advantageous embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a diagram of an aircraft manufacturing and service method in which an advantageous embodiment may be implemented;

Figure 2 is a block diagram of an aircraft in accordance with an advantageous embodiment;

Figure 3 is a diagram of a data processing system in accordance with an advantageous embodiment;

Figure 4 is a diagram of an aircraft network data processing system in accordance with an advantageous embodiment;

Figure 5 is a functional block diagram of a laptop computer in accordance with an advantageous embodiment;

Figure 6 is a block diagram of a maintenance control display function in accordance with an advantageous embodiment;

Figure 7 is an illustration of a display of a maintenance control display function in accordance with an advantageous embodiment;

Figure 8 is an illustration of a ground test switch in accordance with an advantageous embodiment;

Figure 9 is a flowchart of a process for establishing a wireless connection between a laptop computer and an aircraft in accordance with an advantageous embodiment;

5 **Figure 10** is a flowchart of a process for performing maintenance operations in accordance with an advantageous embodiment;

Figure 11 is a flowchart of a process for performing a maintenance solution using a laptop computer in accordance with an advantageous embodiment;

10 **Figure 12** is a flowchart of a process for performing a maintenance solution in an aircraft in accordance with an advantageous embodiment; and

Figure 13 is a flowchart of a process for accessing and controlling aircraft systems in accordance with an advantageous embodiment.

DETAILED DESCRIPTION

15 Referring more particularly to the drawings, embodiments of the disclosure may be described in the context of aircraft manufacturing and service method **100** as shown in **Figure 1** and aircraft **200** as shown in **Figure 2**. Turning first to **Figure 1**, a diagram illustrating an aircraft manufacturing and service method is depicted in accordance with an advantageous embodiment.
20 During pre-production, exemplary aircraft manufacturing and service method **100** may include specification and design **102** of aircraft **200** in **Figure 2** and material procurement **104**.

During production, component and subassembly manufacturing **106** and system integration **108** of aircraft **200** in **Figure 2** takes place. Thereafter, aircraft **200** in **Figure 2** may go through certification and delivery **110** in order to be placed in service **112**. While in service
25 by a customer, aircraft **200** in **Figure 2** is scheduled for routine maintenance and service **114**, which may include modification, reconfiguration, refurbishment, and other maintenance or service.

The different advantageous embodiments may be implemented during portions of aircraft manufacturing and service method **100** when maintenance operations are required. A
30 maintenance operation is any operation, process, or procedure that is performed to maintain an aircraft. A maintenance operation may include, for example, monitoring systems, diagnosing problems or detected faults, troubleshooting problems, repairing damaged parts, replacing parts, and other suitable operations.

Each of the processes of aircraft manufacturing and service method **100** may be performed or carried out by a system integrator, a third party, and/or an operator. In these examples, the operator may be a customer. For the purposes of this description, a system integrator may include, without limitation, any number of aircraft manufacturers and major-
5 system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, leasing company, military entity, service organization, and so on.

With reference now to **Figure 2**, a block diagram of an aircraft is depicted in which an advantageous embodiment may be implemented. In this example, aircraft **200** is produced by
10 aircraft manufacturing and service method **100** in **Figure 1** and may include airframe **202** with a plurality of systems **204** and interior **206**. Examples of systems **204** include one or more of propulsion system **208**, electrical system **210**, hydraulic system **212**, environmental system **214**, and aircraft network data processing system **216**. Any number of other systems may be included. Although an aerospace example is shown, different advantageous embodiments may
15 be applied to other industries, such as the automotive industry.

Apparatus and methods embodied herein may be employed during any one or more of the stages of aircraft manufacturing and service method **100** in **Figure 1**. For example, one or more of apparatus embodiments, method embodiments, or a combination thereof may be utilized while aircraft **200** is in service **112** or during maintenance and service **114** in **Figure 1**.

The different advantageous embodiments recognize that with aircraft network data
20 processing system **216** being located on aircraft **200**, that currently maintenance mechanics or other maintenance personnel may access information about the aircraft from a limited number of locations. For example, aircraft system health and fault information is currently available from a maintenance access terminal located on the flight deck. Accessing this terminal typically
25 requires the flight crew to vacate or leave the flight deck for maintenance operations to occur. Another option that may be used is a portable maintenance access terminal, which is located in the electronics bay of the aircraft. This type of terminal is a high cost option in an aircraft.

As a result, many aircraft only include a maintenance access terminal and not a portable maintenance access terminal. The portable maintenance access terminal (PMAT) has some
30 limited ability to be removed from the electronics bay and can in turn be plugged into or physically connected to a limited number of other locations around the aircraft in order to perform maintenance. These locations are limited to the engines and the auxiliary power unit.

Industry experience has shown that the functional limitations of the portable maintenance access terminal, combined with its limited mobility, have resulted in it seldom if ever being used outside of the stowage position in the electronics bay. Also, the limited functionality of the device results in a need to visit the flight deck to perform other related maintenance actions, limiting the benefit of its portability. As a result, the different advantageous embodiments recognize that in currently available aircraft, limited access constrains and prolongs the maintenance operations performed by maintenance mechanics.

Further, these types of maintenance operations also may cause disruptions on the flight deck that inhibit or slow down other work that could otherwise be performed concurrently. The different advantageous embodiments recognize that these limitations may lead to delays for maintenance performed between flights.

Thus, the different advantageous embodiments provide a computer implemented method, apparatus, and computer usable program code for a portable data processing system to communicate with the aircraft network data processing system. The different advantageous embodiments also allow the portable data processing system to control various components within the aircraft as well as access information needed for maintenance operations.

In one advantageous embodiment, an apparatus comprises a portable computer and program code stored on the portable computer. The program code is capable of being executed by the portable computer to establish a communications link with an aircraft network data processing system in an aircraft, obtain information about the aircraft over the communications link, display the information on a display device for the portable computer, receive user input to control a data processing system on the aircraft network data processing system in the aircraft, and send a number of commands to the data processing system.

In one or more of the different advantageous embodiments, the control and access is performed through a wired and/or wireless connection in which the operator of the portable data processing system may access aircraft systems information from various locations on board or within a specified radius around the aircraft. As a result, an operator may perform maintenance operations and access necessary aircraft information without leaving the work area. In other words, the different advantageous embodiments provide an ability for an operator to read the aircraft system health and fault information from almost any location within some radius or distance from or in the aircraft.

The advantageous embodiments provide a computer implemented method, apparatus, and computer program code for performing maintenance operations on an aircraft. As described

above, the advantageous embodiments may include one or more features including an ability for a mechanic to view aircraft system health and fault information from any location where maintenance work is performed on the aircraft; an ability for the mechanic to view aircraft system information and manipulate specific aircraft systems from any location where maintenance work may be performed on the aircraft; an ability to integrate fault data with aircraft support information; ability to indicate and/or manipulate circuit breaker and contactor status on the aircraft; an ability to control rigging of the aircraft; and an ability to integrate the different features of all the above features, along with existing maintenance system functionalities into one portable computer tool.

Turning now to **Figure 3**, a diagram of a data processing system is depicted in accordance with an advantageous embodiment. Data processing system **300** is a hardware device and is an example of a data processing system that may be used in aircraft **200** in **Figure 2**. Data processing system **300** may be used to implement computers, portable computers, laptop computers, line replaceable units and other suitable devices. In this illustrative example, data processing system **300** includes communications fabric **302**, which provides communications between processor unit **304**, memory **306**, persistent storage **308**, communications unit **310**, input/output (I/O) unit **312**, and display **314**.

Processor unit **304** serves to execute instructions for software that may be loaded into memory **306**. Processor unit **304** may be a set of one or more processors or may be a multi-processor core, depending on the particular implementation. Further, processor unit **304** may be implemented using one or more heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **304** may be a symmetric multi-processor system containing multiple processors of the same type.

Memory **306** and persistent storage **308** are examples of storage devices **316**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Memory **306**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device.

Persistent storage **308** may take various forms depending on the particular implementation. For example, persistent storage **308** may contain one or more components or devices. For example, persistent storage **308** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by

persistent storage **308** also may be removable. For example, a removable hard drive may be used for persistent storage **308**.

Communications unit **310**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **310** is a network interface card. Communications unit **310** may provide communications through the use of either
5 or both physical and wireless communications links.

Input/output unit **312** allows for input and output of data with other devices that may be connected to data processing system **300**. For example, input/output unit **312** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device.
10 Further, input/output unit **312** may send output to a printer. Display **314** provides a mechanism to display information to a user.

Instructions for the operating system, applications, and/or programs may be located in storage devices **316**, which are in communication with processor unit **304** through communications fabric **302**. In these illustrative examples, the instructions are in a functional
15 form on persistent storage **308**. These instructions may be loaded into memory **306** for execution by processor unit **304**. The processes of the different embodiments may be performed by processor unit **304** using computer implemented instructions, which may be located in a memory, such as memory **306**.

These instructions are referred to as program code, computer usable program code, or
20 computer readable program code that may be read and executed by a processor in processor unit **304**. The program code in the different embodiments may be embodied on different physical or tangible computer readable media, such as memory **306** or persistent storage **308**.

Program code **318** is located in a functional form on computer readable media **320** that is selectively removable and may be loaded onto or transferred to data processing system **300** for
25 execution by processor unit **304**. Program code **318** and computer readable media **320** form computer program product **322** in these examples. In one example, computer readable media **320** may be in a tangible form, such as, for example, an optical or magnetic disc that is inserted or placed into a drive or other device that is part of persistent storage **308** for transfer onto a storage device, such as a hard drive that is part of persistent storage **308**.

30 In a tangible form, computer readable media **320** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory that is connected to data processing system **300**. The tangible form of computer readable media **320** is also referred to as

computer recordable storage media. In some instances, computer readable media **320** may not be removable.

Alternatively, program code **318** may be transferred to data processing system **300** from computer readable media **320** through a communications link to communications unit **310** and/or
5 through a connection to input/output unit **312**. The communications link and/or the connection may be physical or wireless in the illustrative examples. The computer readable media also may take the form of non-tangible media, such as communications links or wireless transmissions containing the program code.

In some illustrative embodiments, program code **318** may be downloaded over a network
10 to persistent storage **308** from another device or data processing system for use within data processing system **300**. For instance, program code stored in a computer readable storage medium in a server data processing system may be downloaded over a network from the server to data processing system **300**. The data processing system providing program code **318** may be a server computer, a client computer, or some other device capable of storing and transmitting
15 program code **318**.

The different components illustrated for data processing system **300** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing
20 system **300**. Other components shown in **Figure 3** can be varied from the illustrative examples shown.

The different embodiments may be implemented using any hardware device or system capable of executing program code. As one example, the data processing system may include organic components integrated with inorganic components and/or may be comprised entirely of
25 organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

As another example, a storage device in data processing system **300** is any hardware apparatus that may store data. Memory **306**, persistent storage **308** and computer readable media **320** are examples of storage devices in a tangible form.

In another example, a bus system may be used to implement communications fabric **302**
30 and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system.

Additionally, a communications unit may include one or more devices used to transmit and receive data, such as a modem or a network adapter. Further, a memory may be, for example, memory **306** or a cache such as found in an interface and memory controller hub that may be present in communications fabric **302**.

5 Turning now to **Figure 4**, a diagram of an aircraft network data processing system is depicted in accordance with an advantageous embodiment. Aircraft network data processing system **400** is a more detailed example of aircraft network data processing system **216** in **Figure 2**. The different data processing systems and line replaceable units within aircraft network data processing system **400** may be implemented using a data processing system, such as data
10 processing system **300** in **Figure 3**.

In this example, aircraft network data processing system **400** includes two networks, open data network **402** and isolated data network **404**. The computers, line replaceable units, and/or other devices in aircraft network data processing system **400** may be implemented using aircraft network data processing system **400** in **Figure 4**. These two networks may include physical
15 links, such as wired and optical links. Additionally, in some implementations, wireless links also may be present.

Open data network **402** allows data processing systems or devices outside of aircraft network data processing system **400** to access aircraft network data processing system **400**. In this depicted example, wireless access unit **405** and crew information system/maintenance
20 system **406** connect to open data network **402**. In these examples, wireless access unit **405** provides an ability to access various systems within aircraft network data processing system **400**. This access, of course, may be controlled by central server module **408** to present unauthorized access to various data processing systems within aircraft network data processing system **400**.

Isolated data network **404** only provides access to internal data processing systems, such
25 as crew information system/maintenance system **406** and line replaceable units, such as central server module **408**, electronic flight bag **410**, cabin services **412**, circuit breaker indication and controls **414**, rigging flight controls **416**, and file server **417**.

One or more of these line replaceable units can be used to control aircraft systems **418**. Aircraft systems **418** is any collection of electronic devices, computers, line replaceable units,
30 mechanical components, hydraulic components, structures, and/or other devices that can be directly or indirectly controlled and/or accessed by a line replaceable unit. In these illustrative examples, aircraft systems **418** include flight control surfaces **420**, cabin systems **422**, and circuit breakers and contactors **424**.

In these examples, a line replaceable unit is an electronic system on an aircraft and may take various forms other than those illustrated here. For example, line replaceable units also include a flight management system, an in-flight entertainment system, a navigation system, a flight controller, a flight recorder, and a collision avoidance system. Line replaceable units may use software or other programming to provide the logic or control for various operations and functions on the aircraft.

In these examples, central server module **408** is an example of a line replaceable unit that provides common networking functions for different networks within aircraft network data processing system **400**. For example, central server module **408** may provide packet routing, firewall services, and wireless access.

Electronic flight bag **410** is an electronic information management device that aids the flight crew in performing flight management tasks more efficiently with less paper. In these illustrative examples, electronic flight bag **410** is portable and removable from the aircraft in which aircraft network data processing system **400** is located. Electronic flight bag **410** may display aviation data or perform calculations.

Cabin services **412** is a line replaceable unit that provides a capability to control cabin systems **422** in the aircraft. Cabin systems **422** may include components, such as, for example, lighting, cabin doors, and a public address system. Circuit breaker indication and controls **414** may provide an identification of the state of various circuit breakers and contactors within circuit breakers and contactors **424** in the aircraft. The state information may be, for example, open, closed, and collared.

Circuit breakers and contactors **424** are spread throughout the aircraft. This line replaceable unit provides an ability to see the state of all circuit breakers and contactors **424** on the aircraft. With few exceptions, such as high current, thermal circuit breakers may not be visible from the system. Further, circuit breaker indication and controls **414** also may be used to change the state of the different circuit breakers and contactors in circuit breakers and contactors **424**.

Rigging flight controls **416** is another line replaceable unit, in these illustrative examples, that provides a capability for rigging or manipulating flight control surfaces **420** on the aircraft. Rigging of flight control surfaces **420** requires physical positioning of the surfaces to preset locations and establish null values which are stored in-flight control computers. Rigging flight controls **416** controls these manipulations to physically position flight control surfaces **420**.

Rigging flight controls **416** controls actuators and other mechanisms connected or coupled to the control surfaces.

Crew information system/maintenance system **406** is a data processing system that includes numerous functions and components. Examples of these are engine indicating and crew alerting system **425** and aircraft data **426**. Engine indicating and crew alerting system **425** provides information about the aircraft that is typically available only from flight deck displays in the cockpit.

Engine indicating and crew alerting system **425** is a line replaceable unit that provides access to maintenance pages and systems and synoptic system pages, such as those found in aircraft data **426**. These pages include, for example, aircraft information, such as the position of valves, fluid quantities on board, electrical bus configurations, tire pressures, and other suitable information that may be needed for maintenance operations. This information is typically accessed by mechanics during routine and unscheduled maintenance and troubleshooting activities. File server **417** may store data files, logs, documents, manuals, and/or programs in the aircraft.

The illustration of aircraft network data processing system **400** in **Figure 4** is not meant to imply physical or architectural limitations on the manner in which different advantageous embodiments may be implemented. Other components in addition and/or in place of the ones illustrated may be used. Some components may be unnecessary in some advantageous embodiments. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined and/or divided into different blocks when implemented in different advantageous embodiments.

Turning now to **Figure 5**, a functional block diagram of a laptop computer is depicted in accordance with an advantageous embodiment. In this example, laptop computer **500** is an example of a portable computer that can be implemented using data processing system **300** in **Figure 3**. Of course, any portable computer can be used in the different advantageous embodiments. A portable computer is any data processing system that is designed to be moved from one location to another location.

A portable computer typically includes a display and an input device. The input device may be, for example, a touch screen, a keyboard, a touch pad, and/or some other suitable device. Other illustrative examples of portable computers include, for example, a pocket computer, a personal digital assistant, a smartphone and/or some other suitable device.

In these illustrative examples, laptop computer **500** provides a capability to communicate information with an aircraft network data processing system in an aircraft. The information may be, for example, without limitation, data, commands, programs, logs from onboard maintenance systems of an aircraft, supporting maintenance information, and/or other suitable systems and/or functions used to operate an aircraft.

In these illustrative examples, laptop computer **500** provides a capability to access information and control various systems in an aircraft. Further, laptop computer **500** may be used to transport software to and from an aircraft.

Laptop computer **500** is capable of accessing and controlling various systems within aircraft network data processing system **400** in **Figure 4** through a wired connection or a wireless communications link established with wireless access unit **405** in **Figure 4** in these examples. Laptop computer **500** is capable of executing a number of applications through the desktop of laptop computer **500**. A number used with reference to an item means one or more items. For example, a number of applications may be one or more applications.

Laptop computer **500** is capable of implementing applications such as, for example, without limitation, maintenance control display function **501**, software maintenance tool **503**, flight recorder download **505**, maintenance logbook **507**, software configuration extract **509**, in-flight entertainment maintenance (IFE) **511**, internet browser application **513**, network manager **515**, laptop computer user guide **517**, core network initial data loader **519**, virtual private network (VPN) **521**, and/or other suitable applications. These applications are examples of software programs capable of executing on laptop computer **500** independent of a connection to an aircraft.

In these illustrative examples, maintenance logbook **507** is an example of an application that provides a capability to store, monitor, and/or maintain an electronic logbook. This logbook contains fault data and maintenance operations performed on the aircraft in these illustrative examples. Core network initial data loader **519** is an application that transports software from the aircraft to laptop computer **500** through the aircraft network. Network manager **515** and virtual private network (VPN) **521** are applications used to establish a wired and/or wireless connection from laptop computer **500** to the aircraft.

In these examples, maintenance control display function **501** is an application displayed on the desktop of laptop computer **500** using user interface **512**. In these examples, user interface **512** may be an interface, such as, for example, Windows Explorer, or some other suitable user interface.

Maintenance control display function **501** is an interface used to operate functions provided by processes **522**. Processes **522** include, in this example, at least one of health and fault information process **502**, aircraft system information process **504**, aircraft support information access process **506**, circuit breaker and contactor process **508**, flight control rigging process **510**, instruction for continued airworthiness **514**, and/or other suitable applications or programs.

As used herein, the phrase “at least one of”, when used with a list of items, means that different combinations of one or more of the items may be used and only one of each item in the list may be needed. For example, “at least one of item A, item B, and item C” may include, for example, without limitation, item A, or item A and item B. This example also may include item A, item B, and item C, or item B and item C.

Health and fault information process **502** provides a capability for an operator of laptop computer **500** to view aircraft system health and fault information. This information may be obtained through a communications link to aircraft network data processing system **400** in **Figure 4** to communicate with crew information system/maintenance system **406** in **Figure 4**. Aircraft system information process **504** allows a user to view aircraft status information that is currently available only from the flight deck displays in the cockpit. This information, accessed by aircraft system information process **504**, may be obtained from crew information system/maintenance system **406** in **Figure 4**.

In particular, aircraft system information process **504** may allow communication with engine indicating and crew alerting system **425** in **Figure 4** as well as accessing aircraft data **426** in **Figure 4**. In this manner, remote access of this information allows an operator performing maintenance operations to access the information without entering the flight deck of the aircraft and displacing other crew members between flights.

With aircraft system information process **504**, an operator of laptop computer **500** may have control for specific tests or to configure the aircraft for maintenance operations. This component may display aircraft systems information and/or manipulate aircraft systems from outside of the flight deck through user interface **512**.

Aircraft support information access process **506** provides access support information. Support information is any information that may be used in providing maintenance operations. This information may be found in instruction for continued airworthiness **514**. Access to this information is a regulatory requirement for performing maintenance on an aircraft. Instruction

for continued airworthiness **514** includes documents, such as, for example, without limitation, aircraft maintenance manuals, equipment lists, and illustrative parts catalogs.

Additionally, other data sources also may be used and found within instruction for continued airworthiness **514** in addition to those required by regulatory requirements. These other sources include, fault isolation manuals, aircraft and maintenance logbooks, and other suitable information. This information may be displayed in conjunction with health information, status information, and/or other suitable information about the aircraft. Thus, this component provides for integration of aircraft systems information with relevant support instructions.

The different advantageous embodiments place this information on laptop computer **500** rather than off-site as currently stored. A maintenance operator may currently need to look at paper copies for this type of information. The different advantageous embodiments provide this information within laptop computer **500**. In other advantageous embodiments, this information may be accessible by laptop computer **500** at the maintenance facility or airport at the remote data processing system through the wireless communications links that laptop computer **500** may establish.

Further, aircraft support information access process **506** also may access aircraft data on the aircraft, such as, aircraft data **426** in **Figure 4**. This aircraft data may include, for example, log books or other information needed for maintenance operations. This data may be accessed at the same time the mechanic accesses the aircraft systems information to allow for concurrent viewing of the aircraft fault information and maintenance instructions to resolve the fault.

Additionally, this component is capable of integrating information about the aircraft with support information. In other words, this component may display status information about the aircraft with support information for the aircraft. The support information displayed may relate to the status information. This support information may provide, for example, data about parts, procedures, configurations, tests, and other information relating to the status information.

The information about the aircraft may be obtained through health and fault information process **502** and aircraft system information process **504**. The integration of information may occur through dynamically generated links formed between the aircraft generated system fault information and appropriate maintenance data as well as the necessary ground tests to confirm the repairs.

This linking of the aircraft information to support information as well as linking all the information resources available at a single location, increases the efficiency of maintenance operations. In these examples, the linking takes the form of hyperlinks directly from the

maintenance messages displayed from the aircraft to the supporting fault isolation manual or between different but related support information.

Circuit breaker and contactor process **508** allows an operator of laptop computer **500** to control and manipulate the state of circuit breakers and contactors on the aircraft. A contactor is a high energy, remote controlled switch. A contactor is often used for controlling where main aircraft power is routed in an aircraft. This process may interface or communicate with circuit breaker indication and controls **414** in **Figure 4**. Thus, this component provides for displaying and manipulating circuit breakers and contactors in an aircraft.

Flight control rigging process **510** allows a user to adjust the physical position of flight control surfaces as well as establish values for storage in the flight control computing systems. Flight control rigging process **510** may perform these operations by communicating with rigging flight controls **416** in **Figure 4**.

Currently, rigging of flight control surfaces without the different advantageous embodiments may require multiple mechanics to coordinate activities between the flight deck and the flight control surface being rigged. This process may require physical disassembly and adjustment of components in the mechanical elements of the flight control systems. With the use of rigging flight controls **416** in **Figure 4** and flight control rigging process **510**, this functionality may be performed remotely by a single maintenance operator using laptop computer **500**.

User interface **512** provides the user an ability to see the information accessed by the different components within laptop computer **500** as well as provide user input to manipulate and change various line replaceable units or other data processing systems within an aircraft. In this manner, user interface **512** allows a user to see and control various components in the aircraft.

The currently available systems involve the use of a maintenance access terminal which has limited access to aircraft information, such as fault information, condition monitoring information, data loading, and ground test interface. User interface **512** provides additional capabilities needed from maintenance operations to access interface with other aircraft systems, such as other data processing systems and line replaceable units. The systems include, for example, multifunction displays, circuit breakers, system configuration controls, and other suitable systems.

In this manner, an operator does not need to access the different areas of the aircraft. User interface **512** allows for the different features to be integrated with each other as well as with existing maintenance features.

Instead, the operator may perform these functions at laptop computer **500**. Further, user interface **512** allows an integration of displays from various systems being accessed and controlled rather than losing previous displayed information as in currently available systems.

For example, aircraft support information access process **506** may display various schematics or diagrams or instructions from instruction for continued airworthiness **514** while viewing information about the aircraft through health and fault information process **502** and/or aircraft system information process **504**. Maintenance often requires specific settings be applied to aircraft systems as a part of the maintenance process. Generally, these controls are in the flight deck.

In using laptop computer **500** and maintenance control display function **501**, many of these features can now be controlled remotely and without forcing the maintenance person to leave the work area. Also, laptop computer **500** may host many applications that can be accessed simultaneously if necessary. Thus, giving the operator maximum access to several features of choice at the same time.

In this manner, different features and functions used in performing maintenance operations that currently require the maintenance technician to be in one location in the aircraft to see information and in another location to perform tests, repairs, and or other maintenance operations may be performed in a single location. This location may be anywhere inside or outside of the aircraft where a wireless communications link can be established between a portable data processing system, such as a laptop computer, configured with software for the different functionalities and an aircraft network data processing system in the aircraft.

Further, laptop computer **500** also may be used to transport and load software aircraft parts onto an aircraft network data processing system. This process currently requires physical media, such as floppy disks and CD-ROMs, for transport to the aircraft. Conventional data loading also requires an onboard data loading unit, as well as a disk or CD drive to be installed in the aircraft or a portable data loader which can be carried to the aircraft. Laptop computer **500** replaces all of these items. System configuration also may be performed or maintained using the different advantageous embodiments.

Thus, with the different advantageous embodiments, maintenance personnel are not confined to a particular area of the aircraft to access and view data. The personnel can view and access data where the work takes place using different advantageous embodiments. Further, interrupts in the work of the flight crew do not occur because the maintenance person does not

have to enter the flight deck of the cockpit. One result, with some advantageous embodiments, is that less time is needed to get the aircraft ready between flights.

The illustration of laptop computer **500** in **Figure 5** is not meant to imply physical or architectural limitations on the manner in which different advantageous embodiments may be implemented. Other components in addition and/or in place of the ones illustrated may be used. Some components may be unnecessary in some advantageous embodiments. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined and/or divided into different blocks when implemented in different advantageous embodiments.

For example, laptop computer **500** may include other applications other than the ones presented. In other illustrative examples, maintenance control display function **501** may include processes in addition to the processes illustrated. In yet other examples, maintenance control display function **501** may not include flight control rigging process **510**. Still further, laptop computer **500** may include a second user interface in addition to user interface **512** allowing the operator to choose which user interface is used.

With reference now to **Figure 6**, a block diagram of a maintenance control display function is depicted in accordance with an advantageous embodiment. Maintenance control display function **600** is an example of a maintenance control display function such as, for example, maintenance control display function **501** for laptop computer **500** in **Figure 5**.

In these illustrative examples, maintenance control display function **600** is used in these examples as a tool for diagnosing, repairing, testing, and/or resolving issues for aircraft systems. Maintenance control display function **600** allows access and control of aircraft functions **602** and support functions **604**. In these examples, information about aircraft functions **602** is provided by health and fault information process **502** in **Figure 5**. Information about support functions **604** is provided by aircraft support information access process **506** in **Figure 5**, in this illustrative example.

Aircraft functions **602** include, without limitation, central maintenance computing function **606**, onboard data load function **608**, aircraft condition monitoring function **610**, onboard storage management **612**, circuit breaker indication and control **614**, display systems **616**, and cabin services system maintenance **618**.

Central maintenance computing function **606** provides several functions such as, for example, flight deck effect functions **620**, ground test functions **622**, and system configuration functions **624**. Flight deck effect functions **620** are used to compile and/or analyze aircraft

system faults and correlate these faults to defined system faults. A flight deck effect is the fault or discrepancy that has occurred in one or more of the aircraft systems. Ground test functions **622** may perform specific tests for an aircraft during verification of maintenance procedures. System configuration functions **624** may provide access to the configuration of an aircraft's maintenance systems.

In these illustrative examples, onboard data load function **608** allows an ability to install software onto an aircraft for the aircraft's systems and components. Aircraft condition monitoring function **610** allows access to selected aircraft system data for the purpose of monitoring, collecting, and reporting such data under selected parameters, rates, and/or conditions. Onboard storage management **612** provides a function to view, store, and/or delete data files stored on the file server of an aircraft. Circuit breaker indication and control **614** allows access to electronically open, close, and lock circuit breakers. Further, circuit breaker indication and control **614** also provides an ability to monitor the state of circuit breakers for an aircraft.

Display systems **616** may provide an ability to view system synoptics **626** and maintenance pages **628**. System synoptics **626** may include graphical representations of the real-time functions and status of aircraft systems. Maintenance pages **628** may include maintenance data pages for different types of information associated with specific aircraft systems, maintenance data pages for Air Transport Association (ATA) chapters, maintenance control pages, and/or other suitable maintenance pages or displays. In these examples, cabin services system maintenance **618** provides access to status and fault information for cabin services **412** in **Figure 4**. Further, cabin services system maintenance **618** provides an ability to load software for cabin services **412** onto an aircraft.

In these illustrative examples, support functions **604** provide access to minimum equipment list **630**, maintenance procedures **632**, structural repair information **634**, system description section **636**, parts information **638**, wiring and schematic information **640**, fault isolation procedures **642**, component locator **644**, and help system **646**.

Minimum equipment list **630** is the list of minimum aircraft equipment required for certified flight. Maintenance procedures **632** provide specific instructions on how to repair a given problem. Structural repair information **634** includes information on structural damage limits and repair information. System description section **636** provides background information describing how the various aircraft systems may work.

Parts information **638** contains information about parts that may be used to perform maintenance. For example, parts information may include information about a particular circuit that may be used to replace a faulty circuit on an aircraft. As another example, parts information **638** also contains information about how actions needed to reset a circuit. Of course, parts information **638** may be for any part on an aircraft. Schematic information **640** includes information about the layout of different circuits and systems on the aircraft.

Fault isolation procedures **642** include the procedures to be followed when diagnosing and repairing aircraft systems. Component locator **644** is used for determining the location of components within an aircraft's systems. Help system **646** may provide help information for the user of maintenance control display function **600** and laptop computer **500** in **Figure 5**.

In maintenance control display function **600**, aircraft functions **602** and support functions **604** is linked by electronic linkage **605**. For example, electronic linkage **605** may allow maintenance control display function **600** to display information from support functions **604** for a corresponding displayed fault message for a system within aircraft functions **602**.

The illustration of maintenance control display function **600** in **Figure 6** is not meant to imply physical or architectural limitations on the manner in which different advantageous embodiments may be implemented. Other components in addition and/or in place of the ones illustrated may be used. Some components may be unnecessary in some advantageous embodiments.

Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined and/or divided into different blocks when implemented in different advantageous embodiments. For example, aircraft functions **602** and support functions **604** may include functions in addition to, or in place of the functions depicted.

With reference now to **Figure 7**, an illustration of a display of a maintenance control display function is depicted in accordance with an advantageous embodiment. Maintenance control display function **700** is one example of one display for maintenance control display function **600** in **Figure 6**.

In these examples, maintenance control display function **700** may display aircraft functions window **702**, support functions window **704**, and banner window **706**. Aircraft functions window **702** may display a menu for accessing aircraft functions such as, for example, aircraft functions **602** in **Figure 6**. Support functions window **704** may display a toolbox for accessing information such as, for example, the information within support functions **604** in **Figure 6**.

Banner window **706** may have connection symbol **708**. Connection symbol **708** displays the status of the connection between maintenance control display function **700** and the aircraft. For example, the absence of connection symbol **708** may indicate that a connection is not active. Connection symbol **708** displayed as a clockwise turning symbol may indicate that a connection is active. Further, a stationary connection symbol **708** may indicate that the laptop computer on which maintenance control display function **700** is running is not operating properly or is frozen.

As illustrated, aircraft functions button **710** on banner window **706** is selected to display aircraft functions window **702**. Further, support functions button **712** on banner window **706** is selected to display support functions window **704**.

User ID tab **714** on banner window **706** indicates the user name of the operator of the laptop computer on which maintenance control display function **700** is displayed and running. Banner window **706** may also display tail ID tab **716**. Tail ID tab **716** may indicate the identification of the aircraft to which the laptop computer is connected. If the laptop computer is not connected to an aircraft network, tail ID tab **716** may not display a tail identification.

GND Test tab **718** on banner window **706** indicates the position of the ground test switch in the flight deck of the aircraft to which the laptop computer is connected. For example, GND Test tab **718** may indicate “Norm”, “Enable”, or “Dataload/Enable”. If the laptop computer is not connected to an aircraft network, GND Test tab **718** may not be displayed.

Banner window **706** may also display connection tab **720**. Connection tab **720** may indicate the type of connection made between the laptop computer and the aircraft network. For example, possible types of connections may include “None”, “Wireless Initial”, “Wireless Limited”, “Wireless Full”, and “Wired”.

In these illustrative examples, “Wired” and “Wireless Full” may be full connections that provide the laptop computer with the same full level of access to all aircraft systems within aircraft functions **602** in **Figure 6**. “Wireless Limited” may indicate a limited wireless connection in which laptop computer **500** in **Figure 5** may have full access to onboard storage management **612** in **Figure 6**, aircraft condition monitoring function **610** in **Figure 6**, and cabin services system maintenance **618** in **Figure 6**.

Further, a limited wireless connection may only provide partial access to central maintenance computing function **606** in **Figure 6** with all ground tests disabled. Thus, a limited wireless connection may not provide access to the other functions within aircraft functions **602** in **Figure 6**.

In these examples, banner window **706** may also include and display help link **722**, print screen link **724**, and exit MCDF link **726**. Help link **722** may provide a link to the laptop computer user guide for help with maintenance control display function **700**. Print screen link **724** provides an ability to print the contents of the laptop computer screen and the display of maintenance control display function **700** using a printer on the flight deck of an aircraft. Exit MCDF link **726** allows the operator to close maintenance control display function **700** and thus, close aircraft functions window **702** and support functions window **704**.

With reference now to **Figure 8**, an illustration of a ground test switch is depicted in accordance with an advantageous embodiment. Ground test switch **800** is a switch located on the flight deck of an aircraft. Ground test switch **800** may affect access of certain functions of aircraft systems from a laptop computer such as, for example, laptop computer **500** in **Figure 5**.

In these examples, ground test switch **800** may be set to NORM position **802**, ENABLE position **804**, and DATALOAD/ENABLE position **806**. The position of ground test switch **800** may be indicated on banner window **706** of maintenance control display function **700** in **Figure 7** for laptop computer **500** in **Figure 5**. The position of ground test switch **800** may only affect the number of aircraft functions accessible by a laptop computer when the laptop computer has established a full wireless connection to the aircraft. For example, laptop computer **500** in **Figure 5** may have access to different functions of aircraft functions **602** with maintenance control display function **600** in **Figure 6** at different positions of ground test switch **800**.

In NORM position **802**, circuit breaker indication and control **614** in **Figure 6** may only be partially accessible. For example, an operator may only be able to view the states of the circuit breakers and may not be able to monitor, open, close, or lock the electronic circuit breakers of the aircraft.

In NORM position **802** and ENABLE position **804**, onboard data load function **608** in **Figure 6** may not be accessible by laptop computer **500** in **Figure 5**. In DATALOAD/ENABLE position **806**, laptop computer **500** in **Figure 5** may have access to all functions within aircraft functions **602** using maintenance control display function **600** in **Figure 6**.

With reference now to **Figure 9**, a flowchart of a process for establishing a wireless connection between a laptop computer and an aircraft is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 9** may be implemented using a communications unit such as, for example, communications unit **310** in **Figure 3** for laptop computer **500** in **Figure 5** and aircraft **200** in **Figure 2**.

The process begins by the operator selecting a network managing application from the desktop of the laptop computer (operation **900**). In these examples, the network managing application may be network manager **515** in **Figure 5**. The operator then selects the desired aircraft from a list of possible wireless connections (operation **902**). The operator initiates a virtual private network connection from the desktop (operation **904**). This connection may be made by selecting virtual private network **521** in **Figure 5**.

Upon establishing a virtual private network connection, the laptop computer is wirelessly connected to the desired aircraft with a limited wireless connection in these illustrative examples. A determination is made as to whether to change the type of connection from a limited wireless connection to a full connection (operation **906**). If the operator does not wish to establish a full wireless connection, the process may return to operation **906** until such time that the operator does wish to establish a full wireless connection.

If the operator decides to change the connection to a full wireless connection, the operator selects the connection control in the banner window of the maintenance control display function (operation **908**). For example, the operator may select connection tab **720** on banner window **706** of maintenance control display function **700** in **Figure 7**. This selection may result in a series of dialog boxes guiding the operator through the process of entering a code into an interphone in the cabin of the aircraft within a selected period of time.

In this manner, a full wireless connection is only established when the laptop computer is operated within the aircraft. Thus, the operator is required to complete a physical verification in the aircraft. Upon completion of the physical verification, a full wireless connection is established (operation **910**), with the process terminating thereafter.

With reference now to **Figure 10**, a flowchart of a process for performing maintenance operations is depicted in accordance with an advantageous embodiment. The process may be implemented in a laptop computer such as, for example, laptop computer **500** in **Figure 5**.

The process begins by establishing a communications link with a network aircraft data processing system in an aircraft using a portable computer (operation **1000**). The process then receives information at the portable computer about the aircraft from the network aircraft data processing system (operation **1002**). The process controls a number of data processing systems in the aircraft using the portable computer to perform a maintenance operation (operation **1004**), with the process terminating thereafter.

With reference to **Figure 11**, a flowchart of a process for performing a maintenance solution using a laptop computer is depicted in accordance with an advantageous embodiment.

The process illustrated in **Figure 11** may be implemented using a laptop computer such as, for example, laptop computer **500** in **Figure 5**. This process may be implemented in a software component such as, for example, maintenance control display function **501** in **Figure 5**.

The process begins by receiving user input to a user interface identifying an aircraft system (operation **1100**). The process displays controls for the identified aircraft system on the user interface (operation **1102**). The process then waits for user input to the user interface (operation **1104**). When a user input is received, a determination is then made as to whether the user input is to perform a function using the identified aircraft system (operation **1106**). In these examples, the function may be to set a parameter, to reset a breaker, to change a position of a control surface, to obtain status information, to upload software, and/or to perform some other suitable function.

If the user input is to perform a function, the process generates a command for the function selected in the user input (**1108**). The process then sends the command to the aircraft system (operation **1110**). The command may be sent directly to the aircraft system or to a line replaceable unit that controls the aircraft system. The process then presents the response on the user interface (operation **1114**), with the process returning to operation **1106** as described above.

With reference again to operation **1106**, if the user input is not to perform a function, a determination is made as to whether the user input is to select a new aircraft system (operation **1112**). If the user input is to select a new aircraft system, the process returns to operation **1100** as described above. Otherwise, the process determines whether the user input terminates the process (operation **1116**). If the user input does not terminate the process, the process returns to operation **1106**. Otherwise, the process terminates.

With reference now to **Figure 12**, a flowchart of a process for performing a maintenance solution in an aircraft is depicted in accordance with an advantageous embodiment. This method may be implemented by an operator using a laptop computer such as, for example, laptop computer **500** in **Figure 5** and maintenance control display function **600** in **Figure 6**. Further, this method may be implemented after an operator has reviewed fault data for a flight deck effect.

The operator begins by taking the laptop computer to the flight deck of the aircraft (operation **1200**). The operator powers up the laptop computer and logs into the user interface (operation **1202**). The operator then establishes a wireless connection to the aircraft network (operation **1204**). The operator changes the position of the ground test switch to an enable

position to place the aircraft in maintenance mode (operation **1206**). The ground test switch position may be a factor in determining the accessibility of the aircraft functions.

Thereafter, the operator starts the maintenance control display function to gain access to the aircraft functions and the support functions (operation **1208**). The operator navigates to the page that allows for the entry of a code for the flight deck effect or fault (operation **1210**). The flight deck effect or fault is the error or discrepancy as observed at the flight deck. Each flight deck effect or fault may have a specific code or textual description identifying the specific flight deck effect or fault.

The operator enters the fault code and/or fault description to search for the appropriate fault isolation procedures (operation **1212**). The appropriate fault isolation procedures are displayed (operation **1214**). The operator performs the tasks as instructed by the fault isolation procedures (operation **1216**), with the process terminating thereafter. For example, the fault isolation procedures may instruct an operator to cycle a circuit breaker by opening and closing the circuit breaker. In other examples, the fault isolation procedures may instruct an operator to change the state of a circuit breaker.

As another example, in some advantageous embodiments, placing the aircraft in a maintenance mode in operation **1206** may be unnecessary or may be occur automatically when the laptop computer establishes a wireless connection to the aircraft. As another example, in other advantageous embodiments, a wired connection also may be used.

With reference now to **Figure 13**, a flowchart of a process for accessing and controlling aircraft systems is depicted in accordance with an advantageous embodiment. The process illustrated in **Figure 13** may be executed using a laptop computer such as, for example, laptop computer **500** in **Figure 5**. This process may be implemented in a software component such as for example, maintenance control display function **501** in **Figure 5**.

The process begins by receiving a user input to start the maintenance control display function to gain access to the aircraft functions and the support functions (operation **1300**). The process then displays the banner window, aircraft functions window, and support functions window for the maintenance control display function (operation **1302**). These windows are examples of banner window **706**, aircraft functions window **702**, and support functions window **704** for maintenance control display function **700** in **Figure 7**.

The process receives a user input through the support functions window identifying a fault (operation **1304**). For example, an operator may input a code or textual description indicating a specific fault. In these examples, the specific fault may be, for example, a tripped

circuit breaker, a control surface with a rigging out of tolerance, or some other suitable discrepancy. The process displays the associated fault isolation procedure (operation **1306**). For example, the process may display instructions for cycling a specific circuit breaker within the aircraft.

5 Thereafter, the process then receives a user input selecting a function within the aircraft functions window (operation **1308**). In this illustrative example, the selected function is a function within an aircraft system that is controlled to perform maintenance on the fault. For example, the operator may select circuit breaker indication and control **614** of airport functions **602** in **Figure 6**. The process displays a window associated with the selected function (**1310**).

10 Then, the process receives a user input to affect some change to the selected function (**1312**). For example, the process may receive a user input to open and close the circuit breaker in order to cycle the circuit breaker. The process implements this change through the wireless or wired connection of the laptop computer to the aircraft (operation **1314**). After operation **1314**, the process may receive user input to exit the maintenance control display function (operation **1316**) and may then exit the maintenance control display function (operation **1318**), with the process terminating thereafter.

 The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatus, methods and computer program products. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of computer usable or readable program code, which comprises one or more executable instructions for implementing the specified function or functions.

 In some alternative implementations, the function or functions noted in the block may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

 The different advantageous embodiments can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing both hardware and software elements. Some embodiments are implemented in software, which includes but is not limited to forms, such as, for example, firmware, resident software, and microcode.

 Furthermore, the different embodiments can take the form of a computer program product accessible from a computer-usable or computer-readable medium providing program

code for use by or in connection with a computer or any device or system that executes instructions. For the purposes of this disclosure, a computer-usable or computer readable medium can generally be any tangible apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

The computer usable or computer readable medium can be, for example, without limitation an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, or a propagation medium. Non limiting examples of a computer-readable medium include a semiconductor or solid state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk, and an optical disk. Optical disks may include compact disk – read only memory (CD-ROM), compact disk – read/write (CD-R/W) and DVD.

Further, a computer-usable or computer-readable medium may contain or store a computer readable or usable program code such that when the computer readable or usable program code is executed on a computer, the execution of this computer readable or usable program code causes the computer to transmit another computer readable or usable program code over a communications link. This communications link may use a medium that is, for example without limitation, physical or wireless.

A data processing system suitable for storing and/or executing computer readable or computer usable program code will include one or more processors coupled directly or indirectly to memory elements through a communications fabric, such as a system bus. The memory elements may include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some computer readable or computer usable program code to reduce the number of times code may be retrieved from bulk storage during execution of the code.

Input/output or I/O devices can be coupled to the system either directly or through intervening I/O controllers. These devices may include, for example, without limitation to keyboards, touch screen displays, and pointing devices. Different communications adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Non-limiting examples are modems and network adapters are just a few of the currently available types of communications adapters.

The description of the different advantageous embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art.

5 Although the different advantageous embodiments have been described with respect to aircraft, other advantageous embodiments may be applied to other types of objects. For example, without limitation, other advantageous embodiments may be applied to a mobile platform, a stationary platform, a land-based structure, an aquatic-based structure, a space-based structure and/or some other suitable object.

10 More specifically, the different advantageous embodiments may be applied to, for example, without limitation, a submarine, a bus, a personnel carrier, tank, a train, an automobile, a spacecraft, a space station, a satellite, a surface ship, a power plant, a dam, a manufacturing facility, a building and/or some other suitable object.

15 Further, different advantageous embodiments may provide different advantages as compared to other advantageous embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

- 5
1. An apparatus comprising:
a portable computer; and
program code stored on the portable computer, wherein the program code is capable of
being executed to establish a communications link with an aircraft network data processing
10 system in an aircraft, obtain information about the aircraft over the communications link, display
the information on a display device for the portable computer, receive user input to control a data
processing system on the aircraft network data processing system in the aircraft, and send a
number of commands to the data processing system in response to receiving the user input.

 - 15 2. The apparatus of claim 1, wherein the program code comprises program code for at least
one of a health and fault information process capable of accessing health and fault information
on the aircraft; an aircraft system information process capable of accessing status information for
the aircraft; an aircraft support information access process capable of accessing support
information for the aircraft; a flight control rigging process capable of rigging flight control
20 surfaces on the aircraft; and a circuit breaker and contactor process capable of obtaining and
manipulating a state of circuit breakers and contactors on the aircraft.

 3. The apparatus of claim 2, wherein the health and fault information comprises one of a
25 failure of a line replaceable unit, a status of the line replaceable unit, a status of an electrical
system.

 4. The apparatus of claim 2, wherein the support information comprises one of a
maintenance manual, a minimum equipment list, illustrations of parts, a fault isolation manual,
30 and an aircraft and maintenance log book.

5. The apparatus of claim 2, wherein the flight control rigging process is capable of controlling rigging flight controls on the aircraft through the rigging flight controls in the aircraft.
- 5 6. The apparatus of claim 2, wherein the circuit breaker and contactor process obtains and manipulates the state of circuit breakers and contactors on the aircraft through a circuit breaker indication and control in the aircraft.
7. The apparatus of claim 2, wherein the support information is stored on a laptop computer.
- 10 8. The apparatus of claim 2, wherein the aircraft support information access process is capable of integrating the support information with the status information accessed by the aircraft system information process.
- 15 9. An apparatus for performing maintenance operations on an aircraft, the apparatus comprising:
- a health and fault information process capable of accessing health and fault information on the aircraft;
 - an aircraft system information process capable of accessing status information for the
 - 20 aircraft;
 - an aircraft support information access process capable of accessing support information for the aircraft;
 - a flight control rigging process capable of rigging flight control surfaces on the aircraft;
 - a circuit breaker and contactor process capable of obtaining and manipulating a state of
 - 25 circuit breakers and contactors on the aircraft; and
 - a laptop computer, wherein the laptop computer is capable of establishing a wireless communications link with an aircraft network data processing system located within a selected distance of the laptop computer and wherein the health and fault information process, the aircraft support information access process, the aircraft system information process, the flight control
 - 30 rigging process, and the circuit breaker and contactor process execute on the laptop computer.

10. The apparatus of claim 9, wherein the health and fault information comprises one of a failure of a line replaceable unit, a status of the line replaceable unit, a status of an electrical system.
- 5 11. The apparatus of claim 9, wherein the support information comprises one of a maintenance manual, a minimum equipment list, illustrations of parts, a fault isolation manual, and an aircraft and maintenance log book.
- 10 12. The apparatus of claim 9, wherein the flight control rigging process is capable of controlling rigging flight controls on the aircraft through the rigging flight controls in the aircraft.
- 15 13. The apparatus of claim 9, wherein the circuit breaker and contactor process obtains and manipulates the state of circuit breakers and contactors on the aircraft through a circuit breaker indication and control in the aircraft.
14. The apparatus of claim 9, wherein the support information is stored on the laptop computer.
- 20 15. The apparatus of claim 9, wherein the aircraft support information access process is capable of integrating the support information with the status information accessed by the aircraft system information process.
- 25 16. A method for performing maintenance operations, the method comprising:
establishing a communications link with an aircraft network data processing system in an aircraft using a portable computer;
receiving information at the portable computer about the aircraft from the aircraft network data processing system; and
controlling a number of data processing systems in the aircraft using the portable
30 computer to perform a maintenance operation.
17. The method of claim 16, wherein the communications link is selected from one of a wired connection and a wireless connection.

18. The method of claim 16, wherein the number of data processing systems comprises at least one of a number of line replaceable units.

5 19. The method of claim 18, wherein the number of line replaceable units is at least one of rigging flight controls, a central server module, an electronic flight bag, cabin services, and circuit breaker and controls.

20. A computer program product for performing maintenance operations, the computer
10 program product comprising:
a computer recordable storage medium;
program code, stored on the computer recordable storage medium, for establishing a communications link with an aircraft network data processing system in an aircraft using a portable computer;
15 program code, stored on the computer recordable storage medium, for receiving information at the portable computer about the aircraft from the aircraft network data processing system; and
program code, stored on the computer recordable storage medium, for controlling a
number of data processing systems in the aircraft using the portable computer to perform a
20 maintenance operation.





Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12





Figure 13



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2009/032686

A. CLASSIFICATION OF SUBJECT MATTER
INV. G06Q10/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G06Q G05B G06F B64F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/003872 A1 (BRINKLEY ROGER R [US] ET AL) 2 January 2003 (2003-01-02) paragraph [0028] - paragraph [0029]; claims 1-9; figures 1,2 -----	1-20
X	WO 02/065683 A (BOEING CO [US]; BRINKLEY ROGER R [US]; MITCHELL TIMOTHY M [US]; PRICE) 22 August 2002 (2002-08-22) paragraph [0003] - paragraph [0022]; figures 1,2 -----	1-20
X	EP 1 840 755 A (BOEING CO [US]) 3 October 2007 (2007-10-03) abstract paragraph [0010] - paragraph [0040]; figures 1-5 ----- -/--	1-20

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

20 April 2009

Date of mailing of the international search report

24/04/2009

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Lavin Liermo, Jesus

INTERNATIONAL SEARCH REPORT

 International application No
 PCT/US2009/032686

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 426 870 A (BOEING CO [US]) 9 June 2004 (2004-06-09) paragraph [0010] - paragraph [0040]; figures 1-5 -----	1-20
X	US 2005/240555 A1 (WILDE BRUCE [US] ET AL) 27 October 2005 (2005-10-27) paragraph [0030] - paragraph [0058]; claims 26,27 -----	1-20
X	US 6 122 575 A (SCHMIDT DENNIS E [US] ET AL) 19 September 2000 (2000-09-19) abstract; claims 1-10 column 3 - column 7; figures 1-8 -----	1-20
X	DE 10 2006 019972 A1 (DAIMLER CHRYSLER AG [DE]) 8 November 2007 (2007-11-08) paragraph [0005] - paragraph [0011] paragraph [0016] - paragraph [0023] -----	1-20
X	US 2006/229777 A1 (HUDSON MICHAEL D [US] ET AL) 12 October 2006 (2006-10-12) paragraph [0017] - paragraph [0020] paragraph [0030] - paragraph [0053]; claims 1-13 -----	1-20
P,X	EP 2 012 236 A (HONEYWELL INT INC [US]) 7 January 2009 (2009-01-07) paragraph [0010] - paragraph [0019] -----	1-20
X	DE 20 2006 019993 U1 (BERGER ELEKTRONIK ING BUERO UN [DE]) 12 July 2007 (2007-07-12) abstract paragraph [0006] - paragraph [0025] -----	1-20
X	GB 2 327 788 A (HONDA MOTOR CO LTD [JP]) 3 February 1999 (1999-02-03) page 5 - page 12 -----	1-20
X	US 2005/273662 A1 (YI JASON K [US] YI JASON KYONG-MIN [US]) 8 December 2005 (2005-12-08) abstract paragraph [0025] - paragraph [0039] -----	1-20
X	GB 2 389 910 A (EUROCOPTER FRANCE [FR]) 24 December 2003 (2003-12-24) page 1 - page 8 -----	1-20

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2009/032686

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2003003872	A1	02-01-2003	US 2005026609 A1	03-02-2005
WO 02065683	A	22-08-2002	EP 1370953 A2	17-12-2003
			EP 1368725 A2	10-12-2003
			WO 02079918 A2	10-10-2002
EP 1840755	A	03-10-2007	NONE	
EP 1426870	A	09-06-2004	EP 2042430 A2	01-04-2009
			US 2004106404 A1	03-06-2004
US 2005240555	A1	27-10-2005	NONE	
US 6122575	A	19-09-2000	NONE	
DE 102006019972	A1	08-11-2007	EP 2013060 A1	14-01-2009
			WO 2007124839 A1	08-11-2007
US 2006229777	A1	12-10-2006	NONE	
EP 2012236	A	07-01-2009	CA 2636732 A1	02-01-2009
			US 2009012674 A1	08-01-2009
DE 202006019993	U1	12-07-2007	NONE	
GB 2327788	A	03-02-1999	CA 2243107 A1	24-01-1999
			JP 4015744 B2	28-11-2007
			JP 11094706 A	09-04-1999
			US 6175786 B1	16-01-2001
US 2005273662	A1	08-12-2005	BR PI0511463 A	26-12-2007
			CA 2566382 A1	15-12-2005
			EP 1754150 A2	21-02-2007
			JP 2008500639 T	10-01-2008
			WO 2005119449 A2	15-12-2005
GB 2389910	A	24-12-2003	FR 2841352 A1	26-12-2003
			US 2004153800 A1	05-08-2004