PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ³ :	14	(11) International Publication Number: WO 81/02022
C08L 33/14; C08F 265/06	A1	(43) International Publication Date: 23 July 1981 (23.07.81)
(21) International Application Number: PCT/US	81/000	(81) Designated States: AU, BR, JP.
(22) International Filing Date: 2 January 1981 ((02.01.8	1) Published With international search report
(31) Priority Application Number:	111,6	
(32) Priority Date: 14 January 1980 ([14.01.8	0)
(33) Priority Country:	τ	US
 (71) Applicants; and (72) Inventors: IBSEN, Robert, L. [US/US]; 1571	CE, W ve, San ckersha loor, Sa	il- ta m un

(54) Title: PROVISIONAL CROWN-AND-BRIDGE RESIN

(57) Abstract

A provisional crown-and-bridge resin comprising a liquid resin component and a powder component. The liquid resin component contains tetrahydrofurfuryl methacrylate as a major ingredient and is free from methyl methacrylate. It also contains an anti-oxidant and an accelerator. The powder component contains poly (ethyl methacrylate) as a major ingredient and a curing agent for the resin component. The powder is mixed with the resin shortly before application at a ratio of about two to about five parts of powder to one part of liquid resin by weight, to give a suitably flowing mixture. The resin component may also contain ethyl methacrylate as a major ingredient and may contain ethoxylated bisphenol A dimethacrylate as a major ingredient. The powder may include a substantial proportion of amorphous silica and preferably incorporates a substantial amount of X-ray opaque barium glass.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT AU BR CF CG CH DE DK FI FR GA GB HU JP	Austria Australia Brazil Central African Republic Congo Switzerland Cameroon Germany, Federal Republic of Denmark Finland France Gabon United Kingdom Hungary Japan	KP LI LU MC MG MW NL NO RO SE SN SU TD TG US	Democratic People's Republic of Korea Liechtenstein Luxembourg Monaco Madagascar Malaŵi Netherlands Norway Romania Sweden Senegal Soviet Union Chad Togo United States of America	
---	---	--	---	--

WO 81/02022 PCT/US81/00030

PROVISIONAL CROWN-AND-BRIDGE RESIN

Background of the Invention

This invention relates to a provisional crown-and-bridge resin comprising a powder-liquid restorative system.

Provisional crown-and-bridge resins are used in the mouth after a dentist has prepared the tooth, as a short-term filling-like structure for the patient to use during the time the laboratory is manufacturing the permanent crown or other prosthesis. Typically these resins are supposed to remain in place for several weeks, but may, in some cases, remain for as long as two years or more.

For some time the materials that have been used for temporary crown-and-bridge resins have been based on systems employing methyl methacrylate, for example, systems bases on methyl methacrylate resin and poly (methyl methacrylate) powder in conjunction with a peroxide and amine curing system. These systems have had high cure shrinkages, so that they have tended to pull away from the tooth as they cure.

A more serious difficulty has been that these prior art systems have tended to cause tissue irritation, apparently due to traces of the methyl methacrylate monomer remaining in the cured polymer. These traces may be due to the difficulty of getting an exactly stoichiometric amount of curing agent mixed with the resin or to less-than-perfect mixture of ingredients.

A recent system from Germany described as epimine has very low cure shrinkage, but it also has exhibited gingival irritation, apparently due to some toxic curing agent. This German material has also been somewhat weaker in impact strength than the materials previously used and is very translucent.

In 1978 some new systems appeared that were based on poly (ethyl methacrylate). These systems have been advertised as having low cure shrinkages compared to methyl methacrylate and also a lower exotherm than methyl methacrylate systems. They have not however, solved the gingival irritation problem.

Another problem common to all systems used heretofore has been that they are transparent to X-rays, so that X-ray



BUREAT

photographs do not detect their presence. This fact can become very serious if, as is not uncommon, a patient swallows the provisional crown or aspirates it into a lung, for it then becomes impossible to locate the crown with X-rays, or even know whether it is in a lung or in the digestive tract.

Among the objects of the invention are:

To provide an improved provisional crown-and-bridge resin,

To provide a provisional crown-and-bridge resin that does not irritate gingival tissue,

To provide a provisional crown-and-bridge resin with very low shrinkage upon cure,

To provide a suitably tough and adherent crown-and-bridge resin, and

To provide an X-ray opaque crown-and-bridge resin. Summary of the Invention

The present invention provides a provisional or temporary crown-and-bridge resin based, in most instances, upon an ethyl methacrylate resin and a poly (ethyl methacrylate) powder. In addition, the material has been made radio-paque by adding barium glass to the poly (ethyl methacrylate) powder.

The resin, usually based on ethyl methacrylate monomer, has a high percentage of tetrahydrofurfuryl methacrylate.

When properly used, this new resin results in very low cure shrinkage. Possibly, the furfuryl ring is somehow opened to effect this desirable result, although the precise reason for the small amount of shrinkage is not completely known at this time. In some forms of the resin, the tetrahydrofurfuryl methacrylate is the sole resin component, except for some minor ingredients, such as anti-oxident, accelerator, etc.

The resin also may contain ethoxylated bisphenol A dimethacrylate as a major component.

Unique properties of this provisional or temporary crown or bridge resin are: (1) very low cure shrinkage, (2) its X-ray opaqueness, (3) little or no gingival irritation,

and (4) toughness greater than other provisional crown and bridge resin materials.

The material is easy to handle. It sets into a putty or rubbery stage about 60 seconds to 2 1/2 minutes after activation and sets hard in about 3 1/2 to 6 minutes. Preferred Embodiments of the Invention

The invention comprises a liquid or resin and a powder which are mixed in proper proportions, typically in a ratio of about two parts of liquid to seven parts of powder, but this ratio may vary from about two to five parts of powder per part of liquid.

The composition of the liquid resin lies within the following ranges: LIQUID RESIN $% \left(\frac{1}{2}\right) =\frac{1}{2}\left(\frac{1}{2}\right) +\frac{1}{2}\left(\frac{1$

		Per cent range, parts
	Component	by weight
	Ethyl methacrylate	0-70.0
	Ethoxylated bisphenol A	
	dimethacrylate	0-40.0
	Tetrahydrofurfuryl	
	methacrylate	30-60
	Antioxident	0.01-5 (depending
		partly on specific
	·	antioxident used.)
	Ultra-violet light	
	absorbing agent	0-2.0
	'Cure accelerator	0.1 to 2.0 (depending
	•	partly on specific
		accelerator used)
POWDER		
	Poly (ethyl methacrylate)	39-100
	Amorphous silica or	
	barium glass	0-39
	Benzoyl peroxide (or	·
	other resin curing	
	agent)	enough to cure resin
		in liquid resin com-
		pound BUREA7

WO 81/02022 PCT/US81/00030

4.

Shortly before use, the powder is mixed with the liquid to achieve a thick but still favorable consistency, in an amount by weight of two to five parts of powder per part of liquid, typically in the ratio of seven parts of powder to two parts of liquid. The powder may be varied by adding suitable color materials, suitable dyes or pigments so as to match the color of the teeth, especially when used for a portion of a tooth that is to be at the front of the mouth and exposed to viewers. Suitable materials include brown and yellow dyes, titanium dioxide, cadmium sulfide, and black iron oxide, all used in small amounts.

The following examples show various formulations, all figures representing parts by weight: EXAMPLE 1.

Liquid Resin: Part	s by Weight
Tetrahydrofurfuryl methacrylate	60
Ethoxylated bisphenol A dimethacrylate	40
Butylated hydroxytoluene (anti-	
oxident)	0.1
2-hydroxy-4-methoxybenzophenone	
(e.g. U.V. 5411)	2.0
2-hydroxyethyl-p-toluidine (cure	
accelerator)	2.0
Powder:	
Poly (ethyl methacrylate)	98.5
Benzoyl peroxide (as curing agent)	1.5
Powder-to-Resin ratio	3.5:1.0
This composition set hard in two minute	s.

EXAMPLE 2.

	Liquid Resin:	Parts	by Weight
	Tetrahydrofurfuryl methacrylate		60
	Ethoxylated bisphenol A dimethacry	late	40
	Butylated hydroxytoluene		0.1
	2-hydroxy-p-toluidine		1.0
	- 2-hydroxy-4-methoxybenzophenone		2.0
	Powder:		
	Same as Example 1.		
J0	Powder-to-Resin ratio		3.5:1.0



This composition set hard in four minutes, but it went through a cheese-like stage instead of the more desirable rubbery stage.

EXAMPLE 3

Liquid Resin:	Parts by Weight
Tetrahydrofurfuryl methacrylate	60
Ethyl methacrylate	40
Butylated hydroxytoluene	0.1
2-hydroxy-4-methoxybenzophenone	2.0
2-hydroxyethyl-p-toluidine	1.0
Powder:	
Poly (ethyl methacrylate) with 1.5%	/ 0
benzoyl peroxide	50
90 to 10 mixture of poly (ethyl	
methacrylate) and poly (methyl	
methacrylate), without added	
benzoyl peroxide	50
Powder-to-Resin ratio:	3.5:1.0
This composition set hard in about	six minutes

This composition set hard in about six minutes after going through the desired rubbery stage.

EXAMPLE 4

Liquid Resin:	_	
pridata vestu:	Parts	by Weight
Tetrahydrofurfuryl methacrylate		40
Ethyl methacrylate		60
2-hydroxyethyl-p-toluidine		0.5
Powder:		
Same as Example 3.		
Powder-to-Resin ratio:		3.5-1.0

Cure shrinkage was 0.17% and 0.18%.

EXAMPLE 5

Liquid Resin:	Parts	by Weight
Tetrahydrofurfuryl methacrylate		50
Ethyl methacrylate		50
2-hydroxyethyl-p-toluidine		0.3
2-hydroxy-4-methoxybenzophenone		2.0
Powder:		

Poly (ethyl methacrylate) with 1.5%



Powder-to-Resin ratio:	3.5:1.0
Cure shrinkage was 0.43%.	
EXAMPLE 6	
Liquid Resin: Parts	s by Weight
Tetrahydrofurfuryl methacrylate	30
Ethyl methacrylate	70
2-hydroxyethyl-p-toluidine	1.0
2-hydroxy-4-methoxybenzophenone	2.0
Butylated hydroxytoluene	0.1
Powder:	
Same as in Example 5.	
Powder-to-Resin ratio:	3.5:1.0
Cure shrinkage was 0.63%	
EXAMPLE 7	
Liquid Resin: Parts	by Weight
Tetrahydrofurfuryl methacrylate	56
Ethyl methacrylate	85
N, N-3, 5-tetramethyl aniline	1.0
Butylated hydroxytoluene	0.14
Powder:	
Same as in Example 5.	•
Powder-to-Resin ratio:	3.5:1.0
For two specimens, shrinkage upon cure w	as 0.82%
and 0.88%.	
EXAMPLE 8	
Same as Example 7, but with $N,N-3,5-tetr$	amethyl
aniline at 2.0 parts.	
Cure shrinkages for two specimens were 0	.74% and
0.78%.	
EXAMPLE 9-12	
Same as Example 8, but with powder-to-re	sin ratios
at:	
Example 9 10 11 12	
Powder:Resin 2:1 3:1 4:1 5:1	
Cure Shrinkage	
$\%$ 1.33 0.50 0.51 $\{0.59\}$	
(0.53	



EXAMPLE 13	
Liquid Resin:	Parts by Weight
Ethyl methacrylate	40
Tetrahydrofurfuryl methacrylate	60
2-hydroxy-4-methoxybenzophenone	2.0
2-hydroxyethyl-p-toluidine	2.0
Powder:	
Poly (ethyl methacrylate) with 1.	5%
benzoyl peroxide	70
Ray-Sorb T-2000 Barium glass coat	ed
with 1.5% A-174 silane	30
Powder-to-Resin ratio:	4:1
Cure shrinkages in two specimens	was 0.53% and
0.53%.	
EXAMPLE 14	
Liquid Resin:	Parts by Weight
Ethyl methacrylate	34.83
Tetrahydrofurfuryl methacrylate	52.25
Ethoxylated bisphenol A dimethacr	ylate 9.68
Butylated hydroxytoluene	0.10
2-hydroxyethyl-p-toluidine	1,12
2-hydroxy-4-methoxybenzophenone	1.94
Powders:	
Poly (ethyl methacrylate) with a	dded
1.5% benzoyl peroxide	70
Kimble Ray-Sorb T-2000	30
Powder-to-Resin ratio:	3.5:1.0
This gave excellent results. It	
set in 5 minutes, became rubbery in about 1	1/2 minutes and
stays rubbery until nearly 5 minutes.	
EXAMPLE 15-23	
Liquid Resin:	Parts by Weight
Part 1	
Ethyl methacrylate	40
Tetrahydrofurfuryl methacrylate	60
2-hydroxy-4-methoxybenzophenone	2.0
Butylated hydroxytoluene	0.1
2-hydroxyethyl-p-toluidine	1.0



Part II							
Ethoxylated bisphenol A dimethacrylate				100			
2-hydroxy-4-methoxybenzophenone				2.0			
Butyla	ted hydroxyt	oluene		0.1 .			
2-hydr	oxyethyl-p-t	oluidine		2.0			
ler:							
.Same a	s Example 13	•					
ler-to-R	esin ratio			3.5:1.0			
. L	iquid Resin	Cure Cl	naracterist	ics			
ple R	atio of A:B	Stringy	Rubbery	Hard			
.5	1/9	200 sec		220 sec			
.6	2/8	200		230			
.7	3/7	170		185			
.8	4/6	80	180	210			
.9	5/5	80	175	.255			
0	6/4	80	135	265			
1	7/3	55	100	273			
2 .	8/2	70	100	280			
3	9/1	60	135	345			
EXAMPLE 24							
Liquid Resin: Par							
Ethyl 1	methacrylate			36			
Tetrah	ydrofurfuryl	methacryla	ite	54			
Ethoxy	lated bisphe	nol A dimet	:hacrylate	10			
Butyla	ted hydroxyt	oluene		0.10			
				1.25			
2-hydro	oxy-4-methox	ybenzopheno	one	2.0			
er:							
Poly (ethyl methacrylate) with 1.5%							
Ъ	enzoyl perox	ide		70			
Ray-So:	rb T-2000	•		30			
A-174	Silane			0.45			
er-to-R	esin ratio:			3.5:1.0			
Excellent. Becomes rubbery within two minutes							
hard in	3 1/2 to /	minutes					
	Ethoxy 2-hydr Butyla 2-hydr er: Same a er-to-R ple R 5 6 7 8 9 0 1 2 3 4 id Resi: Ethoxy Butyla 2-hydr 2-hydr er: Poly (Ray-So: A-174 Excell Excell	Ethoxylated bispher 2-hydroxy-4-methox Butylated hydroxyt 2-hydroxyethyl-p-ter: Same as Example 13 der-to-Resin ratio Liquid Resin mple Ratio of A:B 5 1/9 6 2/8 7 3/7 8 4/6 9 5/5 0 6/4 1 7/3 2 8/2 3 9/1 4 6 6 9 9/1 4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	Ethoxylated bisphenol A dimer 2-hydroxy-4-methoxybenzophenor Butylated hydroxytoluene 2-hydroxyethyl-p-toluidine der: Same as Example 13. Ser-to-Resin ratio Liquid Resin Cure Chaple Ratio of A:B Stringy 5 1/9 200 sec 6 2/8 200 7 3/7 170 8 4/6 80 9 5/5 80 0 6/4 80 1 7/3 55 2 8/2 70 3 9/1 60 4 60 4 60 60 60 60 60 60 60 60 60 60 60 60 60	Ethoxylated bisphenol A dimethacrylate 2-hydroxy-4-methoxybenzophenone Butylated hydroxytoluene 2-hydroxyethyl-p-toluidine der: Same as Example 13. er-to-Resin ratio Liquid Resin Cure Characterist uple Ratio of A:B Stringy Rubbery 1/9 200 sec 2/8 200 1/9 200 sec 2/8 200 1/7 3/7 170 8 4/6 80 180 9 5/5 80 175 0 6/4 80 135 1 7/3 55 100 2 8/2 70 100 3 9/1 60 135 4 id Resin: Part Ethyl methacrylate Tetrahydrofurfuryl methacrylate Ethoxylated bisphenol A dimethacrylate Butylated hydroxytoluene 2-hydroxyethyl-p-toluidine 2-hydroxyethyl-p-toluidine 2-hydroxy-4-methoxybenzophenone er: Poly (ethyl methacrylate) with 1.5% benzoyl peroxide Ray-Sorb T-2000 A-174 Silane er-to-Resin ratio:			

The benzoyl peroxide can be used at quantities from about 0.1% to about 5%. As the tertiary amine content decreases, the peroxide should increase.

The butylated hydroxytoluene can be used in amounts from about 0.01 to about 1.0%. Other usable antioxidents include:

Hydroquinone at about 0.1 to about 2.5% Methyl ether of hydroquinone at about 0.1 to about 5%.

Other usable accelerators may include:

N,N-3,5-tetramethylaniline at about 1/2 concentration of 2-HEPT.

N,N-dimethyl-p-toluidine at about 1/4-1/2 concentration of 2-HEPT.

As stated before, the material has been found to be non-irritative to the gingival tissue, which is very important, and it has excellent stability with virtually no shrinkage on curing, as will be shown below. This enables it to remain in place for periods of even longer duration than are ordinarily expected for the laboratory to make the prosthesis. Its hardness is quite satisfactory. Its toughness enables it to be used for its purpose with very satisfactory results, although it can easily be removed in the same manner as other previously used materials. The fact that it is X-ray opaque means that it not only can be detected by X-ray but also that it will look normal in the mouth when its appearance must be relied upon.

Cure Shrinkage

A quick and reproduceable measurement of cureshrinkage of polymeric dental restorative materials may be made with the aid of a quartz-tube dilatometer, such as that manufactured by Tinius-Olsen of Willow Grave, Pa. The device comprises a quartz tube into which a quartz rod is fitted. A fixture attached to the quartz tube enables positioning and locking of a dial indicator gage. A sample is placed into the bottom of the quartz tube, the quartz rod is placed atop the sample, and the dial gage is positioned to a mid-scale reading and locked. Any changes in sample length are recorded with an accuracy of 0.001 mm.

For this study, the samples were placed inside of 3-ml. glass syringes, manufactured by MPL Corporation, Chicago

OMFI WIFO IL. These syringes have a silicone-coated glass barrel, two end fixtures of polyethylene, and a silicone rubber plunger. The syringes were modified by removing the plunger and twisting off the rear polyethylene closure.

The following test procedure was employed:

- (1) Enough material was mixed to fill a syringe to a depth of approximately 10 mm. In practice, some trial and error may be required to determine the correct amount.
- (2) The mixed material was quickly inserted into the syringe from the back.
- (3) The plunger was inserted, and the syringe aspirated, as if it were filled with an injectable material.
- (4) A plastic tip cap was screwed onto the ferrule.
- (5) The assembly was dropped, tip first, into the quartz rod inserted to rest on the syringe plunger.
- (6) The dial indicator was adjusted to give an intermediate reading and was locked. The initial reading was recorded.
- (7) The dial reading was recorded every minute until it became constant. The final reading was subtracted from the initial reading.
- (8) The front closure was removed from the syringe and the cured polymer extracted from the syringe and its length measured.
- (9) A per cent shrinkage was calculated as follows: $\frac{\Delta \quad length}{cured \ length} \times 100 = \% \ linear \ shrinkage$

Since the syringe barrels are silicone coated, the curing material shrinks away from the barrel, so that only linear shrinkage is measured. This is, of course, quite adequate for comparing various materials of the same general type.

Test Results

A series of tests were run as described above comparing the cure shrinkage of the material of this invention

to two other well-known materials sold for the fabrication of provisional crowns and bridges. Their manufactures claim that these materials have low cure shrinkage. Results are tabulated below:

	Material of	1st compet-	2nd compet-
	this inventor	ing material	ing material
Linear Cure			_
Shrinkage, %	0.41	1.54	0.38
11	0.58	1.60	0.37
11	0.63		
11	0.58		
19	0.53		
Average	.0.55	1.57	0.37
Standard Deviat	ion 0.08	0.04	0.01

The data presented above allows the conclusion to be drawn that the material of this invention has a cure shrinkage better than one and nearly as good as the other competing material tested. Both of these other materials, however, tend to result in gingival reactivity.

To those skilled in the art to which this invention relates, many changes in construction and widely differing embodiments and applications of the invention will suggest themselves without departing from the spirit and scope of the invention. The disclosures and the description herein are purely illustrative and are not intended to be in any sense limiting.



WE CLAIM

1. A provisional crown-and-bridge resin comprising:

a liquid resin component and a powder component, said liquid resin component containing tetrahydro-furfuryl methacrylate as a major ingredient and being free from methyl methacrylate and also containing an anti-oxidant and an accelerator,

said powder component containing poly (ethyl methacrylate) as a major ingredient and a curing agent for the resin component, --

said powder being mixed with said resin shortly before application at a ratio of about two to about five parts of powder to one part of liquid resin by weight, to give a suitably flowing mixture.

- 2. The provisional crown-and-bridge resin of claim 1, wherein said resin component also contains ethyl methacrylate as a major ingredient.
- 3. The provisional crown-and-bridge resin of claim 2 wherein said resin component also contains ethoxylated bisphenol A dimethacrylate as a major component.
- 4. The provisional crown-and-bridge resin of claim 1 wherein said powder includes a substantial proportion of amorphous silica.
- 5. The provisional crown-and-bridge resin of claim I wherein said powder incorporates a substantial amount of X-ray opaque barium glass.
- 6. A provisional crown-and-bridge resin comprising:
- a liquid resin component, containing as its major ingredients ethyl methacrylate and tetrahydrofurfuryl methacrylate and, as minor ingredients, an anti-oxidant and a cure accelerator, and,
 - a powder component, containing as its major

ingredients poly (ethyl methacrylate) and X-ray opaque filler and, as a minor ingredient, a curing agent for said liquid resin component,

said resin and powder components being mixed to a desired consistency with the powder present in amounts by weight from about two to about five times the amount by weight of the resin.

- 7. The resin of claim 6 having, as a minor ingredient of the liquid resin component, an ultra-violet-light absorbing material.
- 8. A provisional crown-and-bridge resin comprising an intimate mixture of:
- a liquid resin component containing as its major ingredient a blend of ethyl methacrylate, tetrahydrofurfuryl methacrylate, and ethoxylated bisphenol A dimethacrylate, and, as minor ingredients an anti-oxidant and a cure accelerator, and
- a powder component having as its principal ingredient poly (ethyl methacrylate) and, as a minor ingredient, a curing agent for the liquid resin component,

the powder component being present in an amount of about two to about five times as much, by weight, as the liquid resin component.

- 9. The provisional crown-and-bridge resin of claim 8 wherein the powder component also includes a substantial amount of barium glass.
- 10. The provisional crown-and-bridge resin of claim 8 wherein the powder compound also includes a substantial amount of amorphous silica.
- 11. The provisional crown-and-bridge resin of claim 8 wherein said liquid resin compound also includes an ultra-violet-light absorbing agent.

Parts by Weight

0-70.0

14.

12. A provisional crown-and-bridge resin consisting essentially of a liquid resin component and a powder component mixed to a desired consistency, said liquid resin consisting essentially of:

Ingredient

Ethyl methacrylate

Ethoxylated bisphenol A dimethacry	late 40.0
Tetrahydrofurfuryl methacrylate	60.0
Anti-oxidant	sufficient to
· ~	prevent oxida-
•	tion
Cure accelerator	as desired
said powder component consisting essentially	of:
Ingredient	Parts by Weight
Poly (ethyl methacrylate)	39-100
Amorphous silica	0-39
Curing agent	enough to cure
	the curable resin
	in liquid resin
	component

13. The provisional crown-and-bridge resin of claim 12 wherein said anti-oxidant is chosen for the group consisting of:

<u>Ingredient</u>	Parts by Weight
Butylated hydroxytoluene .	0.01 to 1.0
'Hydroquinone	0.1 to 2.5
Methyl ether of hydroquinone	0.1 to 5.0

14. The provisional crown-and-bridge resin of claim 12 wherein the cure accelerator is chosen for the group consisting of:

<u>Ingredient</u>	Parts by Weight
2-hydroxyethyl-p-toluidine	0.3 to 1.94
N,N-3,5-tetramethylaniline	0.15 to .97
N, N-dimethyl-p-toluidine	0.07 to .97



- 15. The provisional crown-and-bridge resin of claim 12 wherein the curing agent is benzoyl peroxide at quantities from about 0.17% to about 5%, the amount increasing with decrease in the amount of tertiary amine in the liquid resin.
- 16. The provisional crown-and-bridge resin of claim 12 containing an effective amount of ultra-violet-light absorbing agent.
- 17. The provisional crown-and-bridge resin of claim 16 wherein said absorbing agent is 2-hydroxy-4-methoxy-benzophenone, up to 2.0 parts by weight.
- 18. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts	Ъу	Weight
Tetrahydrofurfuryl methacrylate		60	
Ethoxylated bisphenol A dimethacryl	.ate	40	
Butylated hydroxytoluene		٥,	1
2-hydroxy-4-methoxybenzophenone		2.	0 .
2-hydroxyethyl-p-toluidine		2.	0
and a powder component consisting e	ssenti	all	y of
poly (ethyl methacrylate) with 1.5% benzoyl p	eroxid	ie,	
the powder-to-resin ratio being abo	ut 3.5	5:1.	0.

19. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts	bу	Weight
Tetrahydrofurfuryl methacrylate		60	
Ethoxylated bisphenol A dimethacryl	.ate	40	
Butylated hydroxytoluene		0.	1
2-hydroxy-p-toluidine		1.	0
2-hydroxy-4-methoxybenzophenone		2.	0
and a powder component consisting e	ssenti	iall	v of

poly (ethyl methacrylate) with 1.5% benzoyl peroxide,

the powder-to-resin ratio being about 3.5:1.0.

20. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

<u>Ingredient</u>	Parts by Weight
Tetrahydrofurfuryl methacrylate	60
Ethyl methacrylate	40
Butylated hydroxytoluene	0.1
2-hydroxy-4-methoxybenzophenone	2.0
2-hydroxyethyl-p-toluidine	1.0
and a powder component consisting	essentially of:
Ingredient	Parts by Weight
Poly (ethyl methacrylate) with 1.5	5%
benzoyl peroxide	50
a 90 to 10 mixture of poly (ethyl	
methacrylate) and poly (methy	-1
methacrylate) without added	
benzoyl peroxide	50,
the powder-to-resin ratio being ab	out 3.5:1.0.

21. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts by Weight
Tetrahydrofurfuryl methacrylate	40
Ethyl methacrylate	60
2-hydroxyethyl-p-toluidine	0.5
and a powder component consisting	essentially of:
Ingredient	Parts by Weight
Poly (ethyl methacrylate) with	
1.5% benzoyl peroxide	50
a 90 to 10 mixture of poly (ethyl	
methacrylate) and poly (methyl	•
methacrylate) without added	
benzoyl peroxide	50,
the powder-to-resin ratio being ab	out 3.5:1.0.



22. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

<u>Ingredient</u>	Parts by Weight
Tetrahydrofurfuryl methacrylate	50
Ethyl methacrylate	50
2-hydroxyethyl-p-toluidine	0.3
2-hydroxy-4-methoxybenzophenone	2.0
and a powder component consisting	essentially of

and a powder component consisting essentially of poly (ethyl methacrylate) with 1.5% added benzoyl peroxide, the powder-to-resin ratio being about 3.5:1.0.

23. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

<u>Ingredient</u>	Parts by Weight
Tetrahydrofurfuryl methacrylate	30
Ethyl methacrylate	70
2-hydroxyethyl-p-toluidine	1.0
2-hydroxy-4-methoxybenzophenone	2.0
Butylated hydroxytoluene	0.1
and a mandan	

and a powder component consisting essentially of poly (ethyl methacrylate) with 1.5% added benzoyl peroxide, the powder-to-resin ratio being about 3.5:1.0.

24. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts by Weight
Tetrahydrofurfuryl methacrylate	56
Ethyl methacrylate	85
N, N-3, 5-tetramethyl aniline	1.0
Butylated hydroxytoluene	0.14
and a nowder component consisting	

and a powder component consisting essentially of poly (ethyl methacrylate) with 1.5% added benzoyl peroxide, the powder-to-resin ratio being about 3.5:1.0.



5:1.

25. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts by Weight
Tetrahydrofurfuryl methacrylate	56
Ethyl methacrylate	85
N, N-3, 5-tetramethyl aniline	2.0
Butylated hydroxytoluene	0.14
and a powder component consisting	essentially of
poly (ethyl methacrylate) with 1.5% added be	nzoyl peroxide,
the powder-to-resin ratios from ab-	out 2:1 to about

26. a provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts by Weight
Ethyl methacrylate	40
Tetrahydrofurfuryl methacrylate	60
2-hydroxy-4-methoxybenzophenone	2.0
and a powder component consisting	essentially of:
Ingredient	Parts by Weight
Poly (ethyl methacrylate) with 1.5	%
Poly (ethyl methacrylate) with 1.5 benzoyl peroxide	% 70
•	

27. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts	Ъу	Weight
Ethyl methacrylate		34.	83
Tetrahydrofurfuryl methacrylate		52.	25
Ethoxylated bisphenol A dimethacryl	Late	9.	68
Butylated hydroxytoluene		0.	10
2-hydroxyethyl-p-toluidine		1.	12
2-hydroxy-4-methoxybenzopherine		1.	94

BURLAU CICH V. PO V. PO

Ingredient	Parts by Weight		
Poly (ethyl methacrylate) with			
added benzoyl peroxide	70.0		
Barium glass coated with silane	30.0		
the powder-to-resin ratio being ab	out 3.5:1.0.		

28. A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

	Ingredient	Parts by Weight
	Part I	
٠	Ethyl methacrylate	40
	Tetrahydrofurfuryl methacrylate	60
-	2-hydroxy-4-methoxybenzophenone	2.0
	Butylated hydroxytoluene	0.1
•	2-hydroxyethyl-p-toluidine	1.0
	Part II	
	Ethoxylated bisphenol A dimethacryla	te 100.0
	2-hydroxy-4-methoxybenzophenone	2.0
	Butylated hydroxytoluene	0.1
	2-hydroxyethyl-p-toluidine	2 0
the ratio to 9:1,	of Part I and Part II lying in the r	ange of 1:9

and a powder component consisting essentially of: Ingredient Parts by Weight Poly (ethyl methacrylate) with 1.5% benzoyl peroxide 70 Barium glass coated with silane 30 the powder-to-resin ratio being about 3.5:1.0.

A provisional crown-and-bridge resin, consisting essentially of a liquid resin component consisting essentially of:

Ingredient	Parts by Weight
· Ethyl methacrylate	36
Tetrahydrofurfuryl methacrylate	54
Ethoxylated bisphenol A dimethacryl	ate 10
Butylated hydromytoluene	0.10

2-hydroxyethyl-p-toluidine		1.25		
2-hydroxy-4-methoxybenzophenone		2.0		
and a powder component consisting es	sent	iall	y of:	
Ingredient E	Parts	by	Weight	
Poly (ethyl methacrylate) with 1.5%				
benzoyl peroxide	•	70		
Barium glass		30		
Silane		0.	45	
the powder-to-resin ratio being abou	ıt 3.5	5:1.	0.	



INTERNATIONAL SEARCH REPORT

International Application No PCT/USS1,00030

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) 3					
According to international Patent Classification (IPC) or to both National Classification and IPC INT. CL. 3 COSL 33/14, COSF 265/06 US. CL. 260/42.52, 45.95R; 525/206,228,284,309					
	S SEAR			323/200/220/201/002	
				entation Searched 4	
Classificat	ion System	<u></u>	withingh bothing		
	1011 0 , 2	<u>"</u> †		Classification Symbols	
US			525/206, 228, 294, 3 260/42.52, 45.95R	309	
			Documentation Searched other to the Extent that such Document	than Minimum Documentation is are Included in the Fields Searched 5	
			•		
III. DOCI	JMENTS	COI	NSIDERED TO BE RELEVANT 14		
Category *			of Document, 16 with indication, where app	propriate, of the relevant passages 17	Relevant to Claim No. 18
A	i		4,001,939, PUBLISHE		1-29
А	03,	А,	GROSS	U II JANUARI 1977	1-23
A	US,	Α,	3,468,977, PUBLISHE BRUCKMANN ET AL	D 23 SEPTEMBER 1969	1-29
A	US,	Α,	3,265,768, PUBLISHE MOTTUS ET AL	D 09 AUGUST 1966	1-29
A Special of	1	RES NO	INHARDI, "IMPROVING STORATION" DENTAL ST . 4, JANUARY 1979, P.	UDENT, VOLUME 57,	1-29
* Special categories of cited documents: 15 "A" document defining the general state of the art "E" earlier document but published on or after the international filing date "L" document cited for special reason other than those referred to in the other categories "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but on or after the priority date claimed "T" later document published on or after the international filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention "X" document of particular relevance					
IV. CERTIFICATION					
Date of the	Actual C	ompi	etion of the International Search 2	Date of Mailing of this International Sea	rch Report 2
01	01 MAY 1981 0 7 MAY 1981				
Internation	International Searching Authority 1 Signature of Authorized Officer 20				
ISA/US C. J. SECCURO			•		