



US010735684B2

(12) **United States Patent**
Wang et al.

(10) **Patent No.:** **US 10,735,684 B2**
(45) **Date of Patent:** ***Aug. 4, 2020**

(54) **IMAGE READER COMPRISING CMOS BASED IMAGE SENSOR ARRAY**

(58) **Field of Classification Search**
None
See application file for complete search history.

(71) Applicant: **HAND HELD PRODUCTS, INC.,**
Fort Mill, SC (US)

(56) **References Cited**

(72) Inventors: **Ynjiun P. Wang,** Cupertino, CA (US);
William H. Havens, Syracuse, NY (US)

U.S. PATENT DOCUMENTS

3,684,868 A 8/1972 Christie et al.
3,716,669 A 2/1973 Watanabe
(Continued)

(73) Assignee: **Hand Held Products, Inc.,** Fort Mill, SC (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

AU 2004227423 A1 10/2004
CN 1504824 A 6/2004
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **16/728,810**

US 8,038,065 B2, 09/2011, Wang et al. (withdrawn)
(Continued)

(22) Filed: **Dec. 27, 2019**

Primary Examiner — Kristy A Haupt
(74) *Attorney, Agent, or Firm* — Alston & Bird LLP

(65) **Prior Publication Data**
US 2020/0137342 A1 Apr. 30, 2020

(57) **ABSTRACT**

Related U.S. Application Data


(60) Continuation of application No. 16/204,077, filed on Nov. 29, 2018, which is a continuation of application (Continued)

The invention features an image reader and a corresponding method for capturing a sharp distortion free image of a target, such as a one or two-dimensional bar code. In one embodiment, the image reader comprises a two-dimensional CMOS based image sensor array, a timing module, an illumination module, and a control module. The time during which the target is illuminated is referred to as the illumination period. The capture of the image by the image sensor array is driven by the timing module that, in one embodiment, is able to simultaneously expose substantially all of the pixels in the array. The time during which the pixels are collectively activated to photo-convert incident light into charge defines the exposure period for the sensor array. In one embodiment, at least a portion of the exposure period occurs during the illumination period.

(51) **Int. Cl.**
H04N 5/378 (2011.01)
G06K 7/10 (2006.01)
(Continued)

30 Claims, 30 Drawing Sheets

(52) **U.S. Cl.**
CPC **H04N 5/378** (2013.01); **G06K 7/10722** (2013.01); **G06K 7/1439** (2013.01);
(Continued)



Related U.S. Application Data

No. 15/401,779, filed on Jan. 9, 2017, now Pat. No. 10,171,767, which is a continuation of application No. 15/016,927, filed on Feb. 5, 2016, now Pat. No. 9,578,269, which is a continuation of application No. 14/221,903, filed on Mar. 21, 2014, now Pat. No. 9,465,970, which is a continuation of application No. 13/052,768, filed on Mar. 21, 2011, now Pat. No. 8,733,660, which is a division of application No. 12/534,664, filed on Aug. 3, 2009, now Pat. No. 7,909,257, which is a division of application No. 11/077,975, filed on Mar. 11, 2005, now Pat. No. 7,568,628.

(51) **Int. Cl.**

H04N 5/374 (2011.01)
G06K 7/14 (2006.01)
H04N 5/225 (2006.01)
H04N 5/232 (2006.01)
H04N 5/235 (2006.01)
H04N 5/376 (2011.01)

(52) **U.S. Cl.**

CPC **H04N 5/2253** (2013.01); **H04N 5/2256** (2013.01); **H04N 5/2353** (2013.01); **H04N 5/23245** (2013.01); **H04N 5/23293** (2013.01); **H04N 5/374** (2013.01); **H04N 5/3765** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,971,065 A 7/1976 Bayer
 4,047,203 A 9/1977 Dillon
 4,121,244 A 10/1978 Nakabe et al.
 4,253,447 A 3/1981 Moore et al.
 4,261,344 A 4/1981 Moore et al.
 4,350,418 A 9/1982 Taguchi et al.
 4,353,641 A 10/1982 Merlo
 RE31,289 E 6/1983 Moore et al.
 RE31,290 E 6/1983 Moore et al.
 4,390,895 A 6/1983 Sato et al.
 4,402,088 A 8/1983 McWaters et al.
 4,437,112 A 3/1984 Tanaka et al.
 4,491,865 A 1/1985 Danna et al.
 4,516,017 A 5/1985 Hara et al.
 4,523,224 A 6/1985 Longacre, Jr.
 4,546,379 A 10/1985 Sarofeen et al.
 4,605,956 A 8/1986 Cok
 4,630,307 A 12/1986 Cok
 4,760,411 A 7/1988 Ohmura et al.
 4,793,689 A 12/1988 Aoyagi et al.
 4,794,239 A 12/1988 Allais
 4,806,776 A 2/1989 Kley
 4,807,981 A 2/1989 Takizawa et al.
 4,823,186 A 4/1989 Muramatsu
 4,853,774 A 8/1989 Danna et al.
 4,854,302 A 8/1989 Allred, III
 4,858,020 A 8/1989 Homma
 4,862,253 A 8/1989 English et al.
 4,877,948 A 10/1989 Krueger
 4,877,949 A 10/1989 Danielson et al.
 4,941,456 A 7/1990 Wood et al.
 4,957,346 A 9/1990 Wood et al.
 4,962,419 A 10/1990 Hibbard et al.
 4,963,756 A 10/1990 Quan et al.
 5,018,006 A 5/1991 Hashimoto
 5,019,699 A 5/1991 Koenck
 5,059,146 A 10/1991 Thomas et al.
 5,059,779 A 10/1991 Krichever et al.
 5,124,539 A 6/1992 Krichever et al.
 5,144,190 A 9/1992 Thomas et al.

5,200,599 A 4/1993 Krichever et al.
 5,222,477 A 6/1993 Lia
 5,227,614 A 7/1993 Danielson et al.
 5,278,642 A 1/1994 Danna et al.
 5,288,985 A 2/1994 Chadima et al.
 5,291,008 A 3/1994 Havens et al.
 5,304,786 A 4/1994 Pavlidis et al.
 5,305,122 A 4/1994 Hayashi et al.
 5,308,962 A 5/1994 Havens et al.
 5,323,233 A 6/1994 Yamagami et al.
 5,337,361 A 8/1994 Wang et al.
 5,340,786 A 8/1994 Tsutsui et al.
 5,343,028 A 8/1994 Figarella et al.
 5,354,977 A 10/1994 Roustaei
 5,374,956 A 12/1994 D Luna
 5,378,883 A 1/1995 Batterman et al.
 5,393,965 A 2/1995 Bravman et al.
 5,399,846 A 3/1995 Pavlidis et al.
 5,401,944 A 3/1995 Bravman et al.
 5,406,032 A 4/1995 Clayton et al.
 5,406,062 A 4/1995 Hasegawa et al.
 5,410,141 A 4/1995 Koenck et al.
 5,452,379 A 9/1995 Poor
 5,471,533 A 11/1995 Wang et al.
 5,504,322 A 4/1996 Pavlidis et al.
 5,506,619 A 4/1996 Adams et al.
 5,513,264 A 4/1996 Wang et al.
 5,521,366 A 5/1996 Wang et al.
 5,527,262 A 6/1996 Monroe et al.
 5,541,777 A 7/1996 Sakamoto et al.
 5,572,006 A 11/1996 Wang et al.
 5,576,529 A 11/1996 Koenck et al.
 5,591,955 A 1/1997 Laser
 5,602,377 A 2/1997 Beller et al.
 5,602,379 A 2/1997 Uchimura et al.
 5,608,204 A 3/1997 Hoeflinger et al.
 5,629,734 A 5/1997 Hamilton et al.
 5,637,849 A 6/1997 Wang et al.
 5,646,390 A 7/1997 Wang et al.
 5,652,621 A 7/1997 Adams et al.
 5,654,533 A 8/1997 Suzuki et al.
 5,659,167 A 8/1997 Wang et al.
 5,662,586 A 9/1997 Monroe et al.
 5,691,773 A 11/1997 Wang et al.
 5,702,058 A 12/1997 Dobbs et al.
 5,702,059 A 12/1997 Chu et al.
 5,703,349 A 12/1997 Meyerson et al.
 5,714,745 A 2/1998 Ju et al.
 5,717,195 A 2/1998 Feng et al.
 5,739,518 A 4/1998 Wang
 5,756,981 A 5/1998 Roustaei et al.
 5,763,864 A 6/1998 O'Hagan et al.
 5,763,866 A 6/1998 Seo et al.
 5,770,847 A 6/1998 Olmstead
 5,773,810 A 6/1998 Hussey et al.
 5,773,814 A 6/1998 Phillips et al.
 5,777,314 A 7/1998 Roustaei
 5,783,811 A 7/1998 Feng et al.
 5,784,102 A 7/1998 Hussey et al.
 5,786,582 A 7/1998 Roustaei et al.
 5,786,586 A 7/1998 Pidhirny et al.
 5,793,033 A 8/1998 Feng et al.
 5,811,774 A 9/1998 Ju et al.
 5,811,784 A 9/1998 Tausch et al.
 5,811,828 A 9/1998 Laser
 5,814,801 A 9/1998 Wang et al.
 5,815,200 A 9/1998 Ju et al.
 5,818,023 A 10/1998 Meyerson et al.
 5,818,028 A 10/1998 Meyerson et al.
 5,821,518 A 10/1998 Sussmeier et al.
 5,825,006 A 10/1998 Longacre et al.
 5,831,254 A 11/1998 Karpen et al.
 5,834,754 A 11/1998 Feng et al.
 5,837,987 A 11/1998 Danielson et al.
 5,841,121 A 11/1998 Koenck
 5,861,960 A 1/1999 Suzuki et al.
 5,877,487 A 3/1999 Tani et al.
 5,883,375 A 3/1999 Knowles et al.
 5,914,476 A 6/1999 Gerst et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,914,773	A	6/1999	Kurosawa et al.	6,315,204	B1	11/2001	Knighton et al.
5,917,913	A	6/1999	Wang	6,318,635	B1	11/2001	Stoner
5,929,418	A	7/1999	Ehrhart et al.	6,340,114	B1	1/2002	Correa et al.
5,932,741	A	8/1999	Heckmann et al.	6,347,163	B2	2/2002	Roustaei
5,932,862	A	8/1999	Hussey et al.	6,375,075	B1	4/2002	Ackley et al.
5,936,218	A	8/1999	Ohkawa et al.	6,386,452	B1	5/2002	Kawamura
5,940,163	A	8/1999	Byrum	6,405,925	B2	6/2002	He et al.
5,942,741	A	8/1999	Longacre et al.	6,405,929	B1	6/2002	Ehrhart et al.
5,949,052	A	9/1999	Longacre et al.	6,419,157	B1	7/2002	Ehrhart et al.
5,949,056	A	9/1999	White	6,452,153	B1	9/2002	Lauxtermann et al.
5,969,326	A	10/1999	Ogami	6,456,798	B1	9/2002	Keech et al.
5,979,753	A	11/1999	Roslak	6,459,509	B1	10/2002	Maciej et al.
5,979,757	A	11/1999	Tracy et al.	6,460,766	B1	10/2002	Olschafskic et al.
5,979,763	A	11/1999	Wang et al.	6,473,126	B1	10/2002	Higashihara et al.
5,986,297	A	11/1999	Guidash et al.	6,474,865	B2	11/2002	Nakajo
5,988,506	A	11/1999	Schaham et al.	6,476,865	B1	11/2002	Gindele et al.
5,992,744	A	11/1999	Smith et al.	6,491,223	B1	12/2002	Longacre et al.
6,003,008	A	12/1999	Postrel et al.	6,493,114	B1	12/2002	Liu
6,006,990	A	12/1999	Ye et al.	6,505,778	B1	1/2003	Reddersen et al.
6,010,070	A	1/2000	Mizuochi et al.	6,522,323	B1	2/2003	Sasaki et al.
6,010,073	A	1/2000	Bianchi	6,522,441	B1	2/2003	Rudeen
6,019,286	A	2/2000	Li et al.	6,533,168	B1	3/2003	Ching
6,042,012	A	3/2000	Olmstead et al.	6,552,323	B2	4/2003	Guidash et al.
6,045,047	A	4/2000	Pidhirny et al.	6,561,428	B2	5/2003	Meier et al.
6,045,238	A	4/2000	Wheeler et al.	6,565,003	B1	5/2003	Ma
6,049,813	A	4/2000	Danielson et al.	6,575,367	B1	6/2003	Longacre, Jr.
6,053,407	A	4/2000	Wang et al.	6,575,368	B1	6/2003	Tamburrini et al.
6,053,408	A	4/2000	Stoner	6,598,797	B2	7/2003	Lee
6,058,498	A	5/2000	Nagasaki et al.	6,621,598	B1	9/2003	Oda
6,060,722	A	5/2000	Havens et al.	6,622,276	B2	9/2003	Nagasaki et al.
6,062,455	A	5/2000	Giannuzzi et al.	6,637,658	B2	10/2003	Barber et al.
6,062,475	A	5/2000	Feng	6,646,246	B1	11/2003	Gindele et al.
6,062,477	A	5/2000	Wike et al.	6,654,062	B1	11/2003	Numata et al.
6,073,851	A	6/2000	Olmstead et al.	6,655,597	B1	12/2003	Swartz et al.
6,075,240	A	6/2000	Watanabe et al.	6,665,012	B1	12/2003	Yang et al.
6,084,528	A	7/2000	Beach et al.	6,676,016	B1	1/2004	Coskrey, IV
6,088,058	A	7/2000	Mead et al.	6,681,994	B1	1/2004	Koenck
6,097,835	A	8/2000	Lindgren	6,694,064	B1	2/2004	Benkelman
6,097,839	A *	8/2000	Liu	6,695,209	B1	2/2004	La
			G06K 9/4604	6,713,747	B2	3/2004	Tanimoto
			235/462.01	6,714,239	B2	3/2004	Guidash
6,102,295	A	8/2000	Ogami	6,722,569	B2	4/2004	Ehrhart et al.
6,105,869	A	8/2000	Scharf et al.	6,729,546	B2	5/2004	Roustaei
6,118,552	A	9/2000	Suzuki et al.	6,752,319	B2	6/2004	Ehrhart et al.
6,123,261	A	9/2000	Roustaei	6,811,088	B2	11/2004	Lanzaro et al.
6,123,263	A	9/2000	Feng	6,813,046	B1	11/2004	Gindele et al.
6,128,414	A	10/2000	Liu	6,814,290	B2	11/2004	Longacre
6,128,420	A	10/2000	Shin et al.	6,821,810	B1	11/2004	Hsiao et al.
6,141,046	A	10/2000	Roth et al.	6,824,059	B2	11/2004	Jam et al.
6,142,934	A	11/2000	Lagerway et al.	6,832,725	B2	12/2004	Gardiner et al.
6,152,368	A	11/2000	Olmstead et al.	6,832,729	B1	12/2004	Perry et al.
6,155,488	A	12/2000	Olmstead et al.	6,834,807	B2	12/2004	Ehrhart et al.
6,155,491	A	12/2000	Dueker et al.	6,836,288	B1	12/2004	Lewis
6,157,027	A	12/2000	Watanabe et al.	6,853,293	B2	2/2005	Swartz et al.
6,176,429	B1 *	1/2001	Reddersen	6,877,664	B1	4/2005	Oliva
			G06K 7/10722	6,879,340	B1	4/2005	Chevallier
			235/462.25	6,880,759	B2	4/2005	Wilde et al.
6,179,208	B1	1/2001	Feng	6,889,904	B2	5/2005	Bianculli et al.
6,184,534	B1	2/2001	Stephany et al.	6,910,633	B2	6/2005	Swartz et al.
6,186,404	B1	2/2001	Ehrhart et al.	6,917,381	B2	7/2005	Acharya et al.
6,223,988	B1	5/2001	Batterman et al.	6,937,774	B1	8/2005	Specht et al.
6,225,670	B1	5/2001	Dierickx	6,956,544	B2	10/2005	Valliath et al.
6,230,975	B1	5/2001	Colley et al.	6,959,865	B2	11/2005	Walczyk et al.
6,234,394	B1	5/2001	Kahn et al.	6,976,626	B2	12/2005	Schmidt et al.
6,247,645	B1	6/2001	Harris et al.	6,976,631	B2	12/2005	Kashi et al.
6,250,551	B1	6/2001	He et al.	7,009,638	B2	3/2006	Gruber et al.
6,254,003	B1	7/2001	Pettinelli et al.	7,025,272	B2	4/2006	Yavid et al.
6,262,804	B1	7/2001	Friend et al.	7,044,378	B2	5/2006	Patel et al.
6,264,105	B1	7/2001	Longacre et al.	7,055,747	B2	6/2006	Havens et al.
6,276,605	B1	8/2001	Olmstead et al.	7,057,654	B2	6/2006	Roddy et al.
6,289,176	B1	9/2001	Martter et al.	7,073,715	B2	7/2006	Patel et al.
6,298,176	B2	10/2001	Longacre et al.	7,083,098	B2	8/2006	Joseph et al.
6,304,660	B1	10/2001	Ehrhart et al.	7,086,595	B2	8/2006	Zhu et al.
6,311,895	B1	11/2001	Olmstead et al.	7,086,596	B2	8/2006	Meier et al.
6,311,896	B1	11/2001	Mulla et al.	7,090,132	B2	8/2006	Havens et al.
6,313,917	B1	11/2001	Tang et al.	7,090,133	B2	8/2006	Zhu
6,315,203	B1	11/2001	Ikeda et al.	7,111,787	B2	9/2006	Ehrhart
				7,121,470	B2	10/2006	McCall et al.
				7,128,266	B2	10/2006	Zhu et al.

(56)		References Cited						
		U.S. PATENT DOCUMENTS						
	7,130,047	B2	10/2006	Chinnock et al.	9,286,497	B2	3/2016	Fukuba et al.
	7,137,555	B2	11/2006	Bremer et al.	9,305,199	B2	4/2016	Wang et al.
	7,148,923	B2	12/2006	Harper et al.	9,454,686	B2	9/2016	Wang
	7,159,783	B2	1/2007	Walczyk et al.	9,465,970	B2*	10/2016	Wang G06K 7/10722
	7,187,442	B2	3/2007	Chinnock et al.	9,659,199	B2	5/2017	Van Volkinburg et al.
	7,204,418	B2	4/2007	Joseph et al.	10,171,767	B2*	1/2019	Wang G06K 7/10722
	7,219,841	B2	5/2007	Biss et al.	2001/0003071	A1	6/2001	Mansutti et al.
	7,219,843	B2	5/2007	Havens et al.	2001/0003346	A1	6/2001	Feng
	7,222,789	B2	5/2007	Longacre et al.	2001/0013549	A1	8/2001	Harris et al.
	7,234,641	B2	6/2007	Olmstead	2001/0027999	A1	10/2001	Lee
	7,237,722	B2	7/2007	Zhu et al.	2002/0044689	A1*	4/2002	Roustaei G03F 7/705 382/199
	7,268,924	B2	9/2007	Hussey et al.	2002/0050518	A1	5/2002	Roustaei
	7,270,273	B2	9/2007	Barber et al.	2002/0051573	A1	5/2002	Sakai et al.
	7,270,274	B2	9/2007	Hennick et al.	2002/0079370	A1	6/2002	Wood et al.
	7,276,025	B2	10/2007	Roberts et al.	2002/0125317	A1	9/2002	Hussey et al.
	7,277,562	B2	10/2007	Zyzdryn	2002/0130957	A1	9/2002	Gallagher et al.
	7,281,661	B2	10/2007	Zhu et al.	2002/0171745	A1	11/2002	Ehrhart
	7,287,696	B2	10/2007	Attia et al.	2002/0179713	A1	12/2002	Pettinelli et al.
	7,293,712	B2	11/2007	Wang	2003/0004827	A1	1/2003	Wang
	7,296,744	B2	11/2007	He et al.	2003/0018897	A1	1/2003	Bellis et al.
	7,303,126	B2	12/2007	Patel et al.	2003/0019934	A1	1/2003	Hunter et al.
	7,303,131	B2	12/2007	Carlson et al.	2003/0020629	A1	1/2003	Swartz et al.
	7,327,504	B2	2/2008	Gallagher	2003/0022144	A1	1/2003	Cliff
	7,343,865	B2	3/2008	Shuert	2003/0022147	A1	1/2003	Segall et al.
	7,357,325	B2	4/2008	Zhu et al.	2003/0029917	A1	2/2003	Hennick et al.
	7,394,484	B2	7/2008	Soya et al.	2003/0034394	A1	2/2003	Gannon et al.
	7,416,125	B2	8/2008	Wang et al.	2003/0040275	A1	2/2003	Bridgelall
	7,428,093	B2	9/2008	Tegreene et al.	2003/0062413	A1	4/2003	Gardiner et al.
	7,428,997	B2	9/2008	Wiklof et al.	2003/0062419	A1	4/2003	Ehrhart et al.
	7,446,753	B2	11/2008	Fitch	2003/0085284	A1	5/2003	Bremer et al.
	7,460,130	B2	12/2008	Salganicoff	2003/0086008	A1	5/2003	Nagano
	7,490,774	B2	2/2009	Zhu et al.	2003/0089775	A1	5/2003	Yeakley et al.
	7,501,634	B1	3/2009	Reich et al.	2003/0095299	A1	5/2003	Oda et al.
	7,520,433	B2	4/2009	Knowles et al.	2003/0102376	A1	6/2003	Meier et al.
	7,523,866	B2	4/2009	Longacre et al.	2003/0127519	A1	7/2003	Ehrhart et al.
	7,527,203	B2	5/2009	Bremer et al.	2003/0132292	A1	7/2003	Gomez et al.
	7,527,206	B2	5/2009	Zhu et al.	2003/0168512	A1	9/2003	Longacre et al.
	7,527,207	B2	5/2009	Acosta et al.	2003/0169435	A1	9/2003	Kobayashi et al.
	7,568,628	B2	8/2009	Wang et al.	2003/0178492	A1	9/2003	Tamburrini et al.
	7,605,940	B2	10/2009	Silverbrook et al.	2003/0197063	A1	10/2003	Longacre
	7,611,060	B2	11/2009	Wang et al.	2003/0201328	A1	10/2003	Jam et al.
	7,636,486	B2	12/2009	Steinberg et al.	2003/0206150	A1	11/2003	Hussey et al.
	7,637,430	B2	12/2009	Hawley et al.	2003/0210332	A1	11/2003	Frame
	7,639,888	B2	12/2009	Steinberg et al.	2003/0222144	A1	12/2003	Meier et al.
	7,639,889	B2	12/2009	Steinberg et al.	2003/0222147	A1	12/2003	Havens et al.
	7,660,478	B2	2/2010	Steinberg et al.	2003/0226895	A1	12/2003	Havens et al.
	7,681,799	B2	3/2010	Zhu et al.	2004/0004128	A1	1/2004	Pettinelli et al.
	7,690,572	B2	4/2010	Meier et al.	2004/0020990	A1	2/2004	Havens et al.
	7,717,342	B2	5/2010	Wang	2004/0026510	A1	2/2004	Cheung et al.
	7,740,176	B2	6/2010	Wang et al.	2004/0031851	A1	2/2004	Bianculli et al.
	7,770,799	B2	8/2010	Wang	2004/0035933	A1	2/2004	Havens et al.
	7,773,118	B2	8/2010	Florea et al.	2004/0046881	A1	3/2004	Utagawa
	7,780,089	B2	8/2010	Wang	2004/0051801	A1	3/2004	Iizuka et al.
	7,784,696	B2	8/2010	Wang	2004/0109081	A1	6/2004	Sumi
	7,823,787	B2	11/2010	He et al.	2004/0118921	A1	6/2004	Breytman et al.
	7,840,647	B2	11/2010	Kloba et al.	2004/0118926	A1	6/2004	Yavid et al.
	7,841,532	B2	11/2010	Longacre et al.	2004/0129783	A1	7/2004	Patel
	7,845,563	B2	12/2010	Kotlarsky et al.	2004/0155110	A1	8/2004	Ehrhart et al.
	7,874,483	B2	1/2011	Wang et al.	2004/0164165	A1	8/2004	Havens et al.
	7,909,257	B2	3/2011	Wang et al.	2004/0174576	A1	9/2004	Kamisawa et al.
	7,984,855	B2	7/2011	Wang	2004/0190085	A1	9/2004	Silverbrook et al.
	8,002,188	B2	8/2011	Wang	2004/0190092	A1	9/2004	Silverbrook et al.
	8,016,196	B2	9/2011	Meier et al.	2004/0206821	A1	10/2004	Longacre et al.
	8,025,232	B2	9/2011	Wang	2004/0206825	A1	10/2004	Schmidt et al.
	8,146,820	B2	4/2012	Wang et al.	2004/0228508	A1	11/2004	Shigeta
	8,169,486	B2	5/2012	Corcoran et al.	2004/0251394	A1	12/2004	Rhodes
	8,196,839	B2	6/2012	Wang	2004/0262394	A1	12/2004	Longacre et al.
	8,218,027	B2	7/2012	Wang	2005/0001035	A1	1/2005	Hawley et al.
	8,282,006	B2	10/2012	Longacre et al.	2005/00041296	A1	2/2005	Hsiao et al.
	8,720,784	B2	5/2014	Wang	2005/0052554	A1	3/2005	Sakurai et al.
	8,720,785	B2	5/2014	Wang	2005/0072847	A1	4/2005	Barkan et al.
	8,733,660	B2	5/2014	Wang et al.	2005/0089322	A1	4/2005	Uenaka
	8,978,985	B2	3/2015	Wang et al.	2005/0103846	A1	5/2005	Zhu et al.
	9,058,527	B2	6/2015	Wang	2005/0103854	A1	5/2005	Zhu et al.
	9,092,654	B2	7/2015	Wang	2005/0103864	A1	5/2005	Zhu et al.
					2005/0121519	A1	6/2005	Shinohara
					2005/0134936	A1	6/2005	Haug et al.
					2005/0145698	A1	7/2005	Havens et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0161511	A1	7/2005	Parker et al.
2005/0167507	A1	8/2005	Swartz et al.
2005/0276475	A1	12/2005	Sawada
2005/0279836	A1	12/2005	Havens et al.
2005/0281474	A1	12/2005	Huang
2006/0001761	A1*	1/2006	Haba H01L 27/14618 348/340
2006/0011724	A1	1/2006	Joseph et al.
2006/0011725	A1	1/2006	Schnee
2006/0016335	A1	1/2006	Cox et al.
2006/0043194	A1	3/2006	Barkan et al.
2006/0071081	A1	4/2006	Wang
2006/0098954	A1	5/2006	Takagi
2006/0113386	A1	6/2006	Olmstead
2006/0118635	A1	6/2006	Joseph et al.
2006/0119738	A1	6/2006	Kido
2006/0163355	A1	7/2006	Olmstead et al.
2006/0180670	A1	8/2006	Acosta et al.
2006/0202036	A1	9/2006	Wang et al.
2006/0202038	A1	9/2006	Wang et al.
2006/0249581	A1	11/2006	Smith
2006/0255144	A1	11/2006	Meier et al.
2006/0274171	A1	12/2006	Wang
2006/0283952	A1	12/2006	Wang
2007/0002153	A1	1/2007	Dierickx
2007/0045424	A1	3/2007	Wang
2007/0108284	A1	5/2007	Pankow et al.
2007/0135866	A1	6/2007	Baker et al.
2007/0158428	A1	7/2007	Havens et al.
2007/0158535	A1	7/2007	Watkins
2007/0164111	A1	7/2007	Wang et al.
2007/0181692	A1	8/2007	Barkan et al.
2007/0205272	A1	9/2007	Daddabbo et al.
2007/0219417	A1	9/2007	Roberts et al.
2007/0242297	A1	10/2007	Eki
2007/0267501	A1	11/2007	Jovanovski et al.
2007/0284448	A1	12/2007	Wang
2007/0285698	A1	12/2007	Wang et al.
2008/0219581	A1	9/2008	Albu et al.
2008/0223933	A1	9/2008	Smith
2008/0239352	A1	10/2008	Jun
2008/0267495	A1	10/2008	Shimura
2008/0291499	A1	11/2008	Chang
2008/0296393	A1	12/2008	Jovanovski et al.
2008/0309769	A1	12/2008	Albu et al.
2008/0309770	A1	12/2008	Florea et al.
2009/0026267	A1	1/2009	Wang et al.
2009/0032597	A1	2/2009	Barber et al.
2009/0046185	A1	2/2009	Ota
2009/0072038	A1	3/2009	Li et al.
2009/0073516	A1	3/2009	Tanaka
2009/0086294	A1	4/2009	Sakakibara
2009/0121021	A1	5/2009	Wang et al.
2009/0179999	A1	7/2009	Albu et al.
2009/0212911	A1	8/2009	Min et al.
2009/0213811	A1	8/2009	Wang et al.
2010/0044440	A1	2/2010	Wang et al.
2010/0090007	A1	4/2010	Wang et al.
2010/0140356	A1	6/2010	Hawley et al.
2010/0141812	A1	6/2010	Hirota
2010/0219250	A1	9/2010	Wang
2010/0226345	A1	9/2010	Qu et al.
2010/0258633	A1	10/2010	Wang
2010/0259638	A1	10/2010	Wang
2010/0289915	A1	11/2010	Wang
2010/0309340	A1	12/2010	Border et al.
2010/0315536	A1	12/2010	Wang
2010/0316291	A1	12/2010	Deng et al.
2011/0049245	A1	3/2011	Wang
2011/0057039	A1	3/2011	Wang
2011/0073654	A1	3/2011	Wang et al.
2011/0080500	A1	4/2011	Wang et al.
2011/0102638	A1	5/2011	Susanu et al.
2011/0163166	A1	7/2011	Wang et al.
2011/0168779	A1	7/2011	Wang et al.

2011/0303750	A1	12/2011	Wang
2012/0002066	A1	1/2012	Wang
2012/0187190	A1	7/2012	Wang et al.
2012/0248196	A1	10/2012	Wang
2012/0293699	A1	11/2012	Blanquart et al.
2013/0010138	A1	1/2013	Bigioi et al.
2013/0021507	A1	1/2013	Wang et al.
2013/0112753	A1	5/2013	Wang
2013/0113967	A1	5/2013	Wang
2017/0169265	A1	6/2017	Wang

FOREIGN PATENT DOCUMENTS

CN	1511412	A	7/2004
CN	1564996		1/2005
CN	100334499	C	8/2007
CN	101031930	A	9/2007
CN	101069190	A	11/2007
CN	101073088	A	11/2007
CN	101147157	A	3/2008
CN	101171587	A	4/2008
CN	101171597	A	4/2008
CN	201117008	Y	9/2008
DE	19581524		6/1997
EP	0119862	A2	9/1984
EP	0472299	A1	2/1992
EP	0498366	A2	8/1992
EP	0690403	A2	1/1996
EP	0809303	A1	11/1997
EP	0858212	A1	8/1998
EP	0917087	A1	5/1999
EP	1128661	A1	8/2001
EP	1152471	A2	11/2001
EP	1152472	A2	11/2001
EP	1436768	A1	7/2004
EP	1784761		5/2007
EP	1828957		9/2007
EP	1856651		11/2007
EP	2364026	A2	9/2011
GB	2105143	A	3/1983
GB	2301691	A	12/1996
JP	59-040630	A	3/1984
JP	63-185285	A	7/1988
JP	03-250764	A	11/1991
JP	03-250983	A	11/1991
JP	06-231466	A	8/1994
JP	H06266879	A	9/1994
JP	07-021300	A	1/1995
JP	07-506932		7/1995
JP	08-235298	A	9/1996
JP	09-006891	A	1/1997
JP	09-134403	A	5/1997
JP	09-512372		12/1997
JP	10-070261	A	3/1998
JP	10-106919	A	4/1998
JP	10-198754	A	7/1998
JP	10-507560	A	7/1998
JP	10-223875	A	8/1998
JP	10-508133		8/1998
JP	2899113	B2	6/1999
JP	11-312212	A	11/1999
JP	11-345278	A	12/1999
JP	11-514461	A	12/1999
JP	2000-050028	A	2/2000
JP	2000-501209	A	2/2000
JP	2000-165754	A	6/2000
JP	2000-165755	A	6/2000
JP	2000-293622	A	10/2000
JP	2001-175803	A	6/2001
JP	2001-307014	A	11/2001
JP	2001-357345	A	12/2001
JP	2002-042052	A	2/2002
JP	2002-240913	A	8/2002
JP	2002-268201	A	9/2002
JP	2002-368201	A	12/2002
JP	2003-017677	A	1/2003
JP	2003-505771	A	2/2003
JP	2003-087148	A	3/2003
JP	2003-116059	A	4/2003

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	3395770 B2	4/2003
JP	2003-132301 A	5/2003
JP	2003-260822 A	9/2003
JP	2004-111590 A	4/2004
JP	2004-173172 A	6/2004
JP	2004-533031	10/2004
JP	2004-328657 A	11/2004
JP	2005-022802 A	1/2005
JP	2005-050506 A	2/2005
JP	2005-505061 A	2/2005
JP	3792753 B2	7/2006
JP	2008-511917 A	4/2008
JP	2008-181887 A	8/2008
JP	2008-533590 A	8/2008
SE	0103286	4/2003
TW	1393060 A	7/2006
WO	86/01678 A2	3/1986
WO	86/01965 A2	3/1986
WO	96/20454 A1	7/1996
WO	97/08647 A1	3/1997
WO	99/30269 A1	6/1999
WO	99/64980 A1	12/1999
WO	00/16241 A1	3/2000
WO	01/46899 A2	6/2001
WO	02/63543 A2	8/2002
WO	03/01435	1/2003
WO	03/30082	4/2003
WO	03/81520	10/2003
WO	03/81521	10/2003
WO	03/87713	10/2003
WO	2004/064382 A1	7/2004
WO	2006/026141 A1	3/2006
WO	2006/057863 A2	6/2006
WO	2006/065450 A2	6/2006
WO	2006/081466 A2	8/2006
WO	2006/098954 A2	9/2006
WO	2006/098955 A2	9/2006
WO	2008/131438 A2	10/2008

OTHER PUBLICATIONS

Office Action from U.S. Appl. No. 14/221,886, dated Feb. 25, 2015.
 Office Action from U.S. Appl. No. 14/273,631, dated Jul. 7, 2014.
 Office Action in Chinese Application No. 201110220834.X, dated Aug. 14, 2013, 11 pages.
 Office Communication (Notice of Transmission of Documents) for Chinese Application No. 200680016023.5 dated Jun. 4, 2015.
 Ohbuchi et al., Barcode Readers using the Camera Device in Mobile Phones, 6 pages.
 Order Granting/Denying Request for Ex Parte Reexamination in U.S. Appl. No. 90/009,996; dated Jun. 1, 2012.
 OV9640FBG Color CMOS 1.3 MegaPixel (VarioPixel™) Concept Camera Module, 2003, 24 pages.
 Panasonic's Integrated Smart Card Reader model No. ZU-9A36CF4 available from Matsushita Electrical Industrial Company, Ltd.
 Panasonic's Specification No. MIS-DG60C194 entitled, "Manual Insertion Type Integrated Smart Reader" dated Mar. 2004, revision 1.00.
 Partial European Search Report for European Patent Application No. 16183463.5 dated Jan. 12, 2017, 8 pages.
 Patentee Response to Observations by Petitioner, Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated Nov. 9, 2012.
 PB-MV13 20mm CMOS Active-Pixel Digital Image Sensor; Photobit; pp. 33; dated Aug. 2000; retrieved on Oct. 8, 2013 from <<http://fast-vision.com/clientuploads/PDFs/Pb-MV13 Product Specification.pdf>>.
 PC Card Standard 8.0 Release—Apr. 2001; Personal Computer Memory Card International Association (PCMCIA) Version 2.0 <<http://www.pcmcia.org>>; retrieved on Oct. 8, 2013 from <<http://www.pcmcia.org>>.
 narod.ru/09gu80.pdf>.

Pending claims for Chinese Application No. 2006800000503; dated May 13, 2009.

Report by Applicants dated Sep. 15, 2011 (reporting divisional application filings in SIPO). (1 page).

Respondents Notice of Prior Art, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 40 pages.

Respondents' Initial Markman Brief, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 136 pages.

Respondents' Claim Construction Exhibit, RXM-14, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Chandrajit Bajaj, 54 Pages.

Respondents' Claim Construction Exhibits, RXM-13, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Benjamin F. Goldberg, 24 pages.

Respondents' Claim Construction Exhibits, RXM-14, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Lambertus Hesselink, 94 Pages.

Respondents' Final Markman Exhibit RXM-21, Complainants' Opening Claim Construction Brief, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1061, 51 pages.

Respondents' Final Markman Exhibit RXM-22, Complainants' Reply Claim Construction Brief, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1061, 53 pages.

Respondents' Final Markman Exhibit RXM-28, U.S. Pat. No. 6,836,288, 41 pages.

Respondents' Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-16, The American Heritage Desk Dictionary and Thesaurus, 4 pages.

Respondents' Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-17, Webster's New World College Dictionary Fourth Edition, 4 pages.

Respondents' Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-18, Webster's II, New College Dictionary, 4 pages.

Respondents' Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-19, Collins English Dictionary, 5 pages.

Respondents' Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-20, The New Oxford American Dictionary, 5 pages.

Response and European Communication Pursuant to Article 94(3) EPC in European Application No. 06737300.0; dated Jul. 29, 2011.
 Response by Patent Owner with Exhibits as files in U.S. Appl. No. 90/009,996; dated Oct. 3, 2012.

Search Report for European Application No. 13 15 3147 dated Oct. 29, 2015.

Search Report for European Application No. 15 16 7739 dated Oct. 30, 2015.

Second Instance Judgment upholding the Decision for Invalidation made by the Patent Reexamination Board received from the Chinese IP Court, dated Nov. 7, 2018, 11 pages.

STMicronics, STMicronic Introduces Low-Cost High-Quality Mega Pixel CMOS Sensor for Digital Still Cameras and Camcorders, Introduction article on website <http://www.st.com/stoneline/press/news/year2002/p1239p.htm>, p. 1, Oct. 9, 2002.

Supplemental Observations by the Patentee; Proceedings on the Invalidation of Chinese Application No. 2006800160235; dated Nov. 2, 2012.

Text of the Observation by Patentee to Request for Invalidity Action in Chinese Application No. 200680016023.5; dated Aug. 20, 2012.

The Text of Observation, Beijing ZBSD Patent & Trademark Agent Ltd; dated Nov. 8, 2012; 29 pages; full translation.

The Text of the Observation, Beijing ZBSD Patent & Trademark Agent Ltd; dated Oct. 11, 2012; 233 pages; full translation.

U.S. Appl. filed Aug 23, 2016; In re: Wang entitled Apparatus Having Hybrid Monochrom and Color Image Sensor Array., U.S. Appl. No. 15/244,683.

U.S. Appl. filed Dec. 1, 2004., U.S. Appl. No. 60/632,696.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. filed Jul. 26, 2016; In re: Wang entitled Digital Picture Taking Optical Reader Having Hybrid Monochrome and Color Image Sensor Array., U.S. Appl. No. 15/219,827.

U.S. Appl. filed Jun. 22, 2005., U.S. Appl. No. 60/692,890.

Validity Search Report from the Chinese Patent Office for Application No. 200680016023.5; dated Mar. 15, 2012.

Written Response to Request for Invalidation of Chinese Application No. 200680016023.5; dated Apr. 19, 2013.

www.fillfactory.com, Dual Shop Dynamic Dynamic Range Expansion, Website, Feb. 28, 2005, pp. 1-3.

www.micron.com, Introducing A CMOS Image Sensor Specifically Designed for Automotive Scene—Understanding Systems, Website, Oct. 2, 2004, pp. 1-2.

www.photofocus.com, Linog(Trademark) Technology The Key to Programmable Linear, Logarithmic, or Combined Linear and Logarithmic Response Without Image Lag or Distortion, Website, Feb. 28, 2005, pp. 1-6.

Xscale PXA25X Processor IC Chip including Central Processing Unit (CPU) Intel; retrieved on Oct. 8, 2013 from <http://www.datasheetarchive.com/d1main/Datasheets-14/DSA-276710.pdf&g-t; Xscale PXA27X Processor IC Chip with ‘Quick Capture Camera Interface’; Intel; retrieved on Oct. 8, 2013 from <int.xscale-freak.com/XSDoc/PXA27X/28000304.pdf>.

Office Action for U.S. Appl. No. 16/728,797, dated Feb. 5, 2020, 16 pages.

Complainants’ Response to Order 18, Exhibit CXM-0115, OPTICON, 2D Scan Engine, MDI-3100-SR, Specifications Manual (Aug. 15, 2012), 25 pages, Dec. 20, 2019.

Complainants’ Response to Order 18, Exhibit CXM-0116, MDI-3000 Opticon Technical Support Portal, Specifications Manual (May 30, 2019), 2 pages, Dec. 20, 2019.

Complainants’ Response to the ALJ’s Questions Posed During the Markman Hearing, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 24 pages, Dec. 20, 2019.

Declaration of Dr. Benjamin F. Goldberg in the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 24 pages, Oct. 28, 2019.

Declaration of Dr. Lambertus Hesselink in the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 93 Pages, Oct. 28, 2019.

Respondents’ Initial Markman Brief, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 136 pages, Oct. 28, 2019.

Respondents’ Claim Construction Exhibit, RXM-14, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Chandrajit Bajaj, 54 Pages, Oct. 28, 2019.

Respondents’ Claim Construction Exhibits, RXM-13, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Benjamin F. Goldberg, 24 pages, Oct. 28, 2019.

Respondents’ Claim Construction Exhibits, RXM-14, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Lambertus Hesselink, 94 Pages, Oct. 28, 2019.

Respondents’ Final Markman Exhibit RXM-21, Complainants’ Opening Claim Construction Brief, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1061 (Oct. 27, 2017), 51 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit RXM-22, Complainants’ Reply Claim Construction Brief, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1061 (Nov. 6, 2017), 53 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit RXM-28, U.S. Pat. No. 6,836,288 (Issued Dec. 28, 2004), 41 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-16, The American Heritage Desk Dictionary and Thesaurus (2005), 4 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-17, Webster’s New World College Dictionary Fourth Edition (2004), 4 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-18, Webster’s II, New College Dictionary (2001), 4 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-19, Collins English Dictionary (2005), 5 pages, Dec. 3, 2019.

Respondents’ Final Markman Exhibit, Inv. No. 337-TA-1165, RXM-20, The New Oxford American Dictionary (2001), 5 pages, Dec. 3, 2019.

Panasonic’s Integrated Smart Card Reader model No. ZU-9A36CF4 available from Matsushita Electrical Industrial Company, Ltd., Mar. 2004.

Japanese Patent Application No. 63-185285 (cited with English Abstract and translation in corresponding U.S. Pat. No. 4,858,020—’020 patent granted Aug. 15, 1989).

VV6600 1.3 Megapixel CMOS Image Sensor IC Chip; STMicroelectronics, Oct. 9, 2002.

Administrative Ruling in Writing of Supreme People’s Court of the People’s Republic of China, Decision to Reject Retrial, No. ZGFXS 7309, 23 pages, Dec. 9, 2019.

Communication pursuant to Article 94(3) EPC for European Application No. 17193038.1; dated Oct. 10, 2019.

Notice of Reasons for Rejection for Japanese Application No. 2018-134033; dated Jul. 10, 2019.

Complainants’ Opening Claim Construction Brief, Corrected Exhibit CXM-0078, U.S. Pat. No. 7,219,841, 48 pages, Nov. 27, 2019.

Respondents Notice of Prior Art, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 40 pages, Sep. 9, 2019.

Ohbuchi et al., Barcode Readers using the Camera Device in Mobile Phones, Proceedings of the 2004 International Conference on Cyberworlds, 6 pages, Dec. 2004.

1/3-Inch Wide-VGA CMOS Digital Image Sensor, 64 pages, 2004.

Exhibit D Prior Art for U.S. Pat. No. 8,978,985, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 5 pages, Oct. 21, 2019.

Exhibit D-0 Invalidity Chart for U.S. Pat. No. 8,978,985, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 25 pages, Oct. 21, 2019.

Exhibit D-1 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 7,490,774, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 45 pages, Oct. 21, 2019.

Exhibit D-2 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 7,237,722, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 36 pages, Oct. 21, 2019.

Exhibit D-3 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 7,204,418, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 38 pages, Oct. 21, 2019.

Exhibit D-4 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 6,176,429, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 45 pages, Oct. 21, 2019.

Exhibit E Prior Art for U.S. Pat. No. 9,465,970, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 5 pages, Oct. 21, 2019.

Exhibit E-0 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,490,774, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 36 pages, Oct. 21, 2019.

(56)

References Cited

OTHER PUBLICATIONS

Exhibit E-1 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,490,774, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 64 pages, Oct. 21, 2019.

Exhibit E-2 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,237,722, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 38 pages, Oct. 21, 2019.

Exhibit E-3 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,240,418, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 47 pages, Oct. 21, 2019.

Exhibit E-4 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 6,176,429, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 52 pages, Oct. 21, 2019.

Exhibit E-5 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,527,207, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 34 pages, Oct. 21, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0006, Kodak Kac-9630 CMOS Image Sensor (Sep. 2004), Device Performance Specification, 23 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0023, U.S. Pat. No. 4,794,239 (Issued Dec. 27, 1988), 18 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0024, U.S. Pat. No. 5,304,786 (Issued Apr. 19, 1994), 52 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0054, Microsoft Press Computer Dictionary, The Comprehensive Standard for Business, School, Library, and Home (1991), 5 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0056, AIM, Uniform Symbology Specification Code 93 (Apr. 4, 2000), 16 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0064, International Standard, Information Technology—Automatic Identification and Data Capture Techniques—Bar Code Symbology—QR Code (Jun. 15, 2000), 123 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0072, Webster's II New College Dictionary (2001), 4 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0074, Microsoft Press Computer Dictionary, The Comprehensive Standard for Business, School, Library, and Home, Optical Communications (1991), 5 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0078, U.S. Pat. No. 7,446,753 (Issued Nov. 4, 2008), 28 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0079, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of R. Michael Guidash, 51 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0080, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Michael S. Kogan, 21 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0081, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Omid Kia, 30 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0001, U.S. Pat. No. 9,465,970 (Issued Oct. 11, 2016), 66 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0002, U.S. Pat. No. 8,978,985 (Issued Mar. 17, 2015), 62 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0003, U.S. Pat. No. 7,148,923 (Issued Dec. 12, 2006), 15 pages, Oct. 29, 2019.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0004, U.S. Pat. No. 7,527,206 (Issued May 5, 2009), 186 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0005, U.S. Pat. No. 9,659,199 (Issued May 23, 2017), 21 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0006, U.S. Pat. No. 7,159,783 (Issued Jan. 9, 2007), 22 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0010, Appendix C, Certified Copy of Prosecution History of U.S. Pat. No. 7,148,923, 380 pages, Oct. 28, 2019.

Complainants' Opening Claim Construction Brief, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 137 pages, Oct. 28, 2019.

Complainants' Response to Opticon's Response to Order No. 18, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 14 pages, Jan. 2, 2020.

Complainants' Response to Order 18, Exhibit CXM-0088, Bar Code 1: Plessey Code Specification Page (May 13, 2002), 6 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0102, United States Postal Services DMM 708 Technical Specifications (Jan. 6, 2005), 34 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0103, Royal Mail, Four State Customer Code Symbology Specification and Application, PE 5969 (Apr. 13, 1993), 30 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0104, Canada Post Corporation 4-State Bar Code Handbook (Feb. 8, 2005), 31 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0105, Koninklijke PTT Post BV KIX Specification (Aug. 16, 2003), 9 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0106, United States Postal Service DMM 503 Extra Services (Jan. 6, 2005), 40 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0109, Planet Depos, Transcript of Takashi Ushiki, Corporate Designee (Oct. 9, 2019), 6 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0110, U.S. Pat. No. 9,286,497 (Issued Mar. 15, 2016), 36 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0111, U.S. Pat. No. 6,729,546 (Issued May 4, 2004), 25 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0112, U.S. Pat. No. 6,254,003 (Issued Jul. 3, 2001), 24 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0113, U.S. Pat. No. 7,303,126 (Dec. 4, 2007), 13 pages, Dec. 20, 2019.

Complainants' Response to Order 18, Exhibit CXM-0114, U.S. Pat. No. 6,889,904 (Issued May 10, 2005), 13 pages, Dec. 20, 2019.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0079, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of R. Michael Guidash, 51 pages.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0080, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Michael S. Kogan, 21 pages.

Complainants' Opening Claim Construction Brief, Exhibit CXM-0081, In the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, Declaration of Dr. Omid Kia, 30 pages.

Complainants' Opening Claim Construction Brief, Exhibit JXM-0001, U.S. Pat. No. 9,465,970, 66 pages.

(56) **References Cited**

OTHER PUBLICATIONS

- Complainants' Opening Claim Construction Brief, Exhibit JXM-0002, U.S. Pat. No. 8,978,985, 62 pages.
- Complainants' Opening Claim Construction Brief, Exhibit JXM-0003, U.S. Pat. No. 7,148,923, 15 pages.
- Complainants' Opening Claim Construction Brief, Exhibit JXM-0004, U.S. Pat. No. 7,527,206, 186 pages.
- Complainants' Opening Claim Construction Brief, Exhibit JXM-0005, U.S. Pat. No. 9,659,199, 21 pages.
- Complainants' Opening Claim Construction Brief, Exhibit JXM-0006, U.S. Pat. No. 7,159,783, 22 pages.
- Complainants' Opening Claim Construction Brief, Exhibit JXM-0010, Appendix C, Certified Copy of Prosecution History of U.S. Pat. No. 7,148,923, 380 pages.
- Complainants' Opening Claim Construction Brief, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 137 pages.
- Complainants' Response to Opticon's Response to Order No. 18, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 14 pages.
- Complainants' Response to Order 18, Exhibit CXM-0088, Bar Code 1: Plessey Code Specification Page, 6 pages.
- Complainants' Response to Order 18, Exhibit CXM-0102, United States Postal Services DMM 708 Technical Specifications, 34 pages.
- Complainants' Response to Order 18, Exhibit CXM-0103, Royal Mail, Four State Customer Code Symbology Specification and Application, PE 5969, 30 pages.
- Complainants' Response to Order 18, Exhibit CXM-0104, Canada Post Corporation 4-State Bar Code Handbook, 31 pages.
- Complainants' Response to Order 18, Exhibit CXM-0105, Koninklijke PTT Post BV KIX Specification, 9 pages.
- Complainants' Response to Order 18, Exhibit CXM-0106, United States Postal Service DMM 503 Extra Services, 40 pages.
- Complainants' Response to Order 18, Exhibit CXM-0109, Planet Depos, Transcript of Takashi Ushiki, Corporate Designee, 6 pages.
- Complainants' Response to Order 18, Exhibit CXM-0110, U.S. Pat. No. 9,286,497, 36 pages.
- Complainants' Response to Order 18, Exhibit CXM-0111, U.S. Pat. No. 6,729,546, 25 pages.
- Complainants' Response to Order 18, Exhibit CXM-0112, U.S. Pat. No. 6,254,003, 24 pages.
- Complainants' Response to Order 18, Exhibit CXM-0113, U.S. Pat. No. 7,303,126, 13 pages.
- Complainants' Response to Order 18, Exhibit CXM-0114, U.S. Pat. No. 6,889,904, 13 pages.
- Complainants' Response to Order 18, Exhibit CXM-0115, Opticon, 2D Scan Engine, MDI-3100-SR, Specifications Manual, 25 pages.
- Complainants' Response to Order 18, Exhibit CXM-0116, MDI-3000 Opticon Technical Support Portal, Specifications Manual, 2 pages.
- Complainants' Response to the ALJ's Questions Posed During the Markman Hearing, In the Matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and the Components Thereof, USITC Inv. No. 337-TA-1165, 24 pages.
- Decision on Appeal for U.S. Pat. No. 7,568,628; dated Feb. 28, 2014.
- Declaration of Dr. Lambertus Hesselink in the Matter of Certain Bar Code Readers, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, , 93 Pages.
- Defendent's Evidence No. 1, Publication No. JPH10508133A, dated Aug. 4, 1998, for Japanese Application No. 1997JP-0510472, filed Aug. 23, 1996, 59 pages.
- Defendent's Evidence No. 2, Publication No. JP2002368201A, dated Dec. 20, 2002, for Japanese Application No. 2001JP-0171364, filed Jun. 6, 2001, 16 pages.
- Defendent's Evidence No. 3, Publication No. JP2004077633A, dated Mar. 11 2004, for Japanese Application No. 2002JP-0235420, filed Aug. 13, 2002, 27 pages.
- Design and Implementation of Driving Timing for High Frame Rate Video Camera; Northwest Institute of Nuclear Technology; dated 2004; pp. 2; abstract retrieved on Oct. 8, 2013 from <<http://en.cnki.com.cn/Article.sub.—en/CJFDTOTAL-DSSS200402031.htm>>.
- Dolphin 7300 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.legacyglobal.com/Uploads/ProductPDF/Honeywell%20-%20Dolphin%207300%20Series.pdf>>.
- Dolphin 7400 Series Mobile Computer available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/7400.pdf>>.
- DVT SmartImage Sensor Installation & User Guide, 2003, 157 pages.
- Eastman Kodak Company, Kodak Digital Science KAC-0311 Image Sensor, Fully Integrated Timing, Analog Signal Processing & 10 bit ADC, Technical Data; Revision 1; dated Aug. 5, 2002, pp. 1-56.
- Eastman Kodak Company, Ultra Sensitive Global Shutter 580 fps Monochrome CIS, Device Performance Specification, Sep. 2004, pp. 1-22; retrieved on Oct. 9, 2013 from <<http://www.datasheetarchive.com/dl/Datasheets-IS20/DSA00392870.pdf>>.
- Ex Parte Reexamination Certificate in 90/009,996 (Reissue U.S. Pat. No. 7,586,628 C1); dated Nov. 29, 2012.
- Ex Parte Reexamination Interview Summary in 90/009,996 (Reissue U.S. Pat. No. 7,586,628 C1); dated Mar. 26, 2013.
- Ex Parte Reexamination Office Action in U.S. Appl. No. 90/009,996; dated Aug. 3, 2012.
- Ex parte Request for Reexamination of U.S. Pat. No. 7,568,628 dated Apr. 23, 2012 (including Transmittal and PTO/SB/08).
- Exhibit D Prior Art for U.S. Pat. No. 8,978,985, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 5 pages.
- Exhibit D-0 Invalidity Chart for U.S. Pat. No. 8,978,985, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 25 pages.
- Exhibit D-1 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 7,490,774, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 45 pages.
- Exhibit D-2 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 7,237,722, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 36 pages.
- Exhibit D-3. Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 7,204,418, n the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 38 pages.
- Exhibit D-4 Invalidity Chart for U.S. Pat. No. 8,978,985 Based on U.S. Pat. No. 6,176,429, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 45 pages.
- Exhibit E Prior Art for U.S. Pat. No. 9,465,970, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 5 pages.
- Exhibit E-0 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,490,774, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165.
- Exhibit E-1 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,490,774, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 64 pages.
- Exhibit E-2 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,237,722, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 38 pages.
- Exhibit E-3 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,240,418, In the matter of Certain Barcode Scanners,

(56)

References Cited

OTHER PUBLICATIONS

- Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 47 pages.
- Exhibit E-4 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 6,176,429, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 52 pages.
- Exhibit E-5 Invalidity Chart for U.S. Pat. No. 9,465,970 Based on U.S. Pat. No. 7,527,207, In the matter of Certain Barcode Scanners, Scan Engines, Products Containing the Same, and Components Thereof, USITC Inv. No. 337-TA-1165, 34 pages.
- Extended European Search Report for European Patent Application No. 16183463.5 dated Apr. 19, 2017, 11 pages.
- Final Office Action for Japanese Patent Application No. 2014-046409 dated Aug. 24, 2016, with English translation, 16 pages.
- Final Office Action for Japanese Patent Application No. 2015-227211 dated Apr. 7, 2017, with English translation, 5 pages.
- Final Written Decision for U.S. Pat. No. 7,568,628, dated Feb. 18, 2015.
- First Instance Judgment upholding the Decision for Invalidation made by the Patent Reexamination Board received from the Chinese IP Court, dated Dec. 28, 2017, 53 pages.
- Fossum, E. R.; "CMOS Image Sensors: Electronic Camera-On-A-Chip;" IEEE Transaction on Electron Devices, vol. 44, No. 10; pp. 1689-1698; dated Oct. 1997.
- Fowler, B., et al.; "A CMOS Area Image Sensor with Pixel Level A/D Conversion;" Information Systems Laboratory, Electrical Engineering Department, Stanford University; dated Nov. 20, 1995.
- Gamal et al., CMOS Image Sensors, 2005, 15 pages.
- Gunturk, B. K., et al.; "Demosaicking: Color Filter Array Interpolation," IEEE Signal Processing Magazine; dated Jan. 2005.
- Gunturk, Bhadir K., John Glotzbach, Yucel Altunbasak, Ronald W. Shafer, and Russel M. Mersereau. "Demosaicking: Color Filter Array Interpolation" IEEE Signal Processing Magazine, Jan. 2005.
- Hamami, S., et al., "CMOS APS Imager Employing 3.3V 12 Bit 6.3 MS/S Pipelined ADC;" The VLSI Systems Center, Ben-Gurion University; ISCAS '04. Proceedings of the 2004 International Symposium on Circuits and Systems; dated May 2004.
- Hassan Aboushady, Single Stage Amplifiers, University of Paris VI, Sliders pp. 1-24, 2001 (date as indicated by the USPTO in U.S. Appl. No. 90/009,996).
- Heimann, T. K., et al.; "Color Filter Array and Color Correction for High Dynamic Range CMOS Image Sensors;" European Conference on Circuit Theory and Design; dated Aug. 2001.
- Imageteam 4710 two-dimensional reader available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <http://www.barcoding.com/prodpages/HHP/471_Ohd.pdf>.
- Imageteam 4710 two-dimensional reader available from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4710hd.pdf>>.
- Intel.RTM. Strong ARM RISC Processor; INTEL; dated 2000; retrieved on Oct. 8, 2013 from <<http://pdf.datasheetcatalog.com/datasheets/90/361041.sub.—DS.pdf>>.
- International Search Report and Written Opinion for Application No. PCT/US2006/008113; dated Oct. 26, 2006.
- International Search Report and Written Opinion for Application No. PCT/US2006/008114; dated Jul. 14, 2006.
- International Search Report for Application No. PCT/US2006/008113; dated Aug. 7, 2006.
- International Standard ISO/IEC 15420, 2000, 11 pages.
- International Standard ISO/IEC 18004, 2000, 122 pages.
- Invalidation Decision for Chinese Application No. 200680016023.5 dated Mar. 29, 2016.
- Japanese Office Action for Application No. 2018-134033, dated Jul. 8, 2019.
- Japanese Patent Application No. 63-185285 (cited with English Abstract and translation in corresponding U.S. Pat. No. 4,858,020).
- Kodak Image Sensor Solutions, Device Performance Specification for Kodak KAI0340S and Kodak KAI-0340D Image Sensor, pp. 1-54 Revision 1.0, Aug. 6, 2004.
- Kodak Image Sensor Solutions, Color Better through CMY Filters, www.kodak.com/go/ccd, pp. 1-2. Month and year unavailable but known to be published prior to earliest priority date of Jun. 3, 2005.
- Kodak Image Sensor Solutions, Device Performance Specification for Kodak DAC9630 CMOS Image Sensor, pp. 1-22, Revision 1.1, Sep. 2004.
- Kodak KAC-9630 CMOS Image Sensor, 2004, 22 pages.
- Kodak KLI-4104 Image Sensor Device Performance Specification dated Oct. 27, 2003.
- Lumenera USB Camera Users Manual—Release 3.5; Lumenera Corporation; dated 2004.
- Mar. 26, 2013 Ex Parte Reexamination Certificate in U.S. Appl. No. 90/009,996 (Reissue U.S. Pat. No. 7,568,628C1).
- Mar. 4, 2013 Second Request for Invalidation of Chinese Application No. 200680016023.5.
- Micron image sensor with TrueSNAP technology, 2004, 3 pages.
- Micron image sensor with TrueSNAP technology, pp. 1-3; dated Oct. 21, 2004; originally retrieved from <www.eetasia.com/ART.sub.—8800349851.sub.—765245.sub.—NP.sub.—d8379-d7c.htm>, presently retrieved from <<http://www.eetasia.com/articleLogin.do?artId=8800349851&fromWhere=/ART.sub-8800349851.sub.-765245.sub.—NP.sub.-b.-e5a216a1.HTM&catId=765245&newsType=NP&pageNo=null&encode=e5a216a1>> on Oct. 8, 2013.
- Micron Technology, Inc. MT9M111 SOC Megapixel Digital Image Sensor, Products and Specifications Preliminary Manual, pp. 1-61, 2004.
- Micron Technology, Inc., MT9M413 1.3 Megapixel CMOS Active Pixel Digital Image Sensor, Specification manual, Version 3.0, pp. 1-30, Jan. 2004.
- MotionPro HS Series User's Manual Ver. 1.12, 2005, 79 pages.
- MT9V022 Image Sensor IC Chip; Micron, Inc.; dated Oct. 2, 2004; . originally retrieved from <[http://download.micron.com/pdf/flyers/mt9v022_\(mi-0350\)_flyer.pdf](http://download.micron.com/pdf/flyers/mt9v022_(mi-0350)_flyer.pdf)>; currently retrieved from <[http://web.archive.org/web/20070404011812/http://download.micron.com/-pdf/flyers/mt9v022_\(mi-0350\)_flyer.pdf](http://web.archive.org/web/20070404011812/http://download.micron.com/-pdf/flyers/mt9v022_(mi-0350)_flyer.pdf)> on Oct. 8, 2013.
- Muniz et al., A Robust Software Barcode Reader using the Hough Transform, 1999, 8 pages.
- Notice of Allowance for U.S. Appl. No. 11/174,447 dated Mar. 5, 2010.
- Notice of Allowance for U.S. Appl. No. 11/445,930 dated Mar. 5, 2010.
- Notice of Allowance for U.S. Appl. No. 11/445,930 dated Nov. 17, 2009.
- Notice of Allowance and Fees Due (PTOL-85) dated May 8, 2020 for U.S. Appl. No. 15/980,213.
- Notice of Allowance for U.S. Appl. No. 12/403,459 dated Aug. 5, 2013.
- Notice of Allowance for U.S. Appl. No. 12/853,090 dated Jan. 27, 2012.
- Notice of Allowance for U.S. Appl. No. 12/853,090 dated Sep. 6, 2011.
- Notice of Allowance for U.S. Appl. No. 12/861,461 dated Apr. 4, 2011.
- Notice of Allowance for U.S. Appl. No. 13/052,768 dated Jul. 13, 2012.
- Notice of Allowance for U.S. Appl. No. 13/213,543 dated Feb. 19, 2013.
- Notice of Allowance for U.S. Appl. No. 13/213,543 dated Jan. 3, 2014.
- Notice of Allowance for U.S. Appl. No. 13/213,543 dated Jul. 10, 2013.
- Notice of Allowance for U.S. Appl. No. 13/213,543 dated Oct. 30, 2013.
- Notice of Allowance for U.S. Appl. No. 13/289,795 dated Dec. 16, 2013.
- Notice of Allowance for U.S. Appl. No. 13/437,439 dated Dec. 26, 2013.
- Notice of Allowance for U.S. Appl. No. 13/493,348 dated Dec. 23, 2013.
- Notice of Allowance for U.S. Appl. No. 13/493,348 dated Nov. 5, 2013.
- Notice of Allowance for U.S. Appl. No. 13/586,420 dated Oct. 24, 2013.

(56)

References Cited

OTHER PUBLICATIONS

- Notice of Allowance for U.S. Appl. No. 14/220,903 dated Jun. 3, 2016.
- Notice of Allowance for U.S. Appl. No. 14/221,886 dated Aug. 18, 2015.
- Notice of Allowance for U.S. Appl. No. 14/221,886 dated Nov. 27, 2015.
- Notice of Allowance for U.S. Appl. No. 14/221,903 dated Nov. 30, 2015.
- Notice of Allowance for U.S. Appl. No. 14/221,903 dated Oct. 5, 2015.
- Notice of Allowance for U.S. Appl. No. 14/273,631 dated Oct. 29, 2014.
- Notice of Allowance for U.S. Appl. No. 14/684,609 dated May 24, 2016.
- Notice of Allowance for U.S. Appl. No. 14/690,653 dated Apr. 26, 2016.
- Notice of Allowance for U.S. Appl. No. 13/493,348 dated Apr. 26, 2013.
- Notice of Allowance for U.S. Appl. No. 14/221,857 dated Jan. 22, 2015.
- Notice of Allowance for U.S. Appl. No. 15/244,683 dated Feb. 16, 2018.
- Notice of Allowance from U.S. Appl. No. 14/221,874, dated Jan. 14, 2015.
- Notification of Acceptance for Request for Invalidation for Chinese Application No. 200680016023.5; dated Jul. 3, 2012.
- Notification of Acceptance of Request for Invalidation of CN App. No. 2006800160215, dated Aug. 20, 2012. (In Chinese language).
- Notification of Oral Proceedings on the Request for Invalidation issued in Chinese Patent Application No. 200680016023.5 issued on Oct. 23, 2012. 5 pages. Full translation.
- Notification of Transfer of Documents issued in Chinese Patent Application No. 200680016023.5 issued on Oct. 24, 2012. 281 pages. Partial translation.
- Notification to Grant Patent for Chinese Application No. 201110220832.0 dated Sep. 5, 2016.
- Notification to Grant Patent for Chinese Application No. 201110220834.X dated Sep. 5, 2016.
- Notification to Grant Patent for Chinese Patent Application No. 201110220832.0 dated Sep. 5, 2016, with English Translation, 4 pages.
- Nov. 29, 2012 Ex Parte Reexamination Interview Summary in U.S. Reexamination Appl. No. 90/009,996 (U.S. Pat. No. 7,568,628).
- Observation Application No. 2006800160235. Title of invention "Bar Code Reading Device with Global Electronic Shutter Control." State observation directed to the Notification of Transferring the document (issue No. 2012111300206340) which was issued by the Patent Reexamination Board on the date of Nov. 16, 2012. 134 pages. Dec. 4, 2012. Full translation.
- Observation by Patentee in Response to the Notification of Acceptance of Request for Invalidation, Proceedings on the Request for Invalidation of Chinese Application No. 200680016023.5, Dec. 4, 2012 (Submitted with English Translation).
- Observation by the Petitioner; Proceedings on the Invalidation of Chinese Application No. 200680016023.5; dated May 29, 2013.
- Observations by Patentee, Proceedings on the Request for Invalidation of Chinese Application No. 200680016023.5, Nov. 2, 2012 (Submitted with English Translation).
- Office Action for Chinese Application No. 201110220834.X dated Sep. 18, 2015.
- Office Action for Chinese Application No. 201110220834.X dated May 27, 2014.
- Office Action for Chinese Application No. 2006800000502.3 dated Feb. 13, 2012.
- Office Action for Chinese Application No. 200680016023.5; dated Oct. 24, 2013.
- Office Action for Chinese Application No. 2006800160235; dated Jan. 23, 2009 (translation).
- Office Action for Chinese Application No. 201110220832.0 dated May 30, 2014.
- Office Action for Chinese Application No. 201110220832.0 dated Sep. 29, 2015.
- Office Action for European Application No. 06737299.5; dated Jul. 10, 2013.
- Office Action for European Application No. 10012906.3; dated Oct. 9, 2012.
- Office Action for European Application No. EP17193038.1 dated May 8, 2018.
- Office Action for Japanese Application No. 2008-500843; dated Jun. 22, 2012; translation.
- Office Action for Japanese Application No. 2008-500844; dated Jan. 24, 2012; translation.
- Administrative Ruling in Writing of Supreme People's Court of the People's Republic of China, Decision to Reject Retrial, No. ZFGXS 7309, 23 pages.
- "1/2-Inch VGA (With Freeze-Frame) CMOS Active-Pixel Digital Image Sensor: MT9V403," Micron, Rev. B, Jan. 2004, 33 pages.
- "1M28, 1M75, and 1M150 User's Manual," DALSA, Rev. 4, Sep. 30, 2003, 74 pages.
- "Cypress's LUPA-300 Image Sensor Earns 2005 Product of the Year Honors From analogZONE," Cypress, Feb. 23, 2006 (available at <https://www.cypress.com/news/cypress-lupa-300-image-sensor-earns-2005-product-year-honors-analogzone>), 2 pages.
- "DALSA 1M150-SA (Prelim.)," DALSA, Aug. 28, 2003, 2 pages.
- "DALSAIA-G1-VGACMOS Area Array Sensor," DALSA, undated (available at <https://www.datasheetarchive.com/pdf/download.php?id=c7dccf64051389eeae5b9c6e6dbfb3d1f64d24&type=P&term=25V12V>), 18 pages.
- "FillFactory's High Fill Factor N-Well Pixel® (U.S. Pat. No. 6,225,670)," Technology: FillFactory Technology Exclusivities, Nov. 5, 2005, 6 pages.
- "IBIS5-A-1300 Datasheet," Fillfactory Image Sensors, Rev. 1.3, Jan. 4, 2005, 67 pages.
- "Kodak KAC-1310 Image Sensor," Eastman Kodak Company, Rev. 4, Nov. 7, 2002, 78 pages.
- "Lumenera USB Camera User's Manual," Lumenera Corporation, Release 3.5, 2004, 31 pages.
- "LUPA 1.3 Mpixel @ 450 fps CMOS APS," Fillfactory Image Sensors, Jul. 4, 2003, 27 pages.
- "LUPA300 CMOS Image Sensor," ON Semiconductor, Rev. 11, Dec. 2016, 29 pages.
- "MT9V022: 1/3-Inch Wide-VGA Digital Image Sensor Features," Aptina Imaging, Rev.H 6/10 EN, 2005.
- Case of Demand for Rescission of Appeal Decision, Reiwa 1 (2019) (Gyo-ke) No. 10099, Plaintiff's First Brief, dated Sep. 13, 2019, 28 pages.
- Case of Demand for Rescission of Appeal Decision, Reiwa 1 (2019) (Gyo-ke) No. 10099, Plaintiff's Second Brief, dated Oct. 2, 2019, 3 pages.
- Case of Demand for Rescission of Appeal Decision, Reiwa 1 (2019) (Gyo-ke) No. 10099, Plaintiff's Third Brief, dated Feb. 4, 2020, 30 pages.
- Chappell Brown, "CMOS imager sports electronic shutter," EE Times, Sep. 8, 1998 (available at <https://web.archive.org/web/20040506082237/http://www.eetimes.com/news/98/1025news/cmso.html>), 3 pages.
- Henderson, R. K., et al.; "Pixel-Pixel Fixed Pattern Noise in CMOS Image Sensors due to Readout Parasitic Capacitance." IEEE Workshop on Charge-Coupled Devices and Advanced Image Sensors, Jun. 2005, 4 pages.
- Patent Owner's Appeal Brief Re: CN 200680016023.5, dated Jun. 29, 2016, 55 pages.
- S. Hamami, L. Fleshel and O. Yadid-Pecht, "CMOS APS imager employing 3.3 V 12 bit 6.3 MS/s pipelined ADC," 2004 IEEE International Symposium on Circuits and Systems (IEEE Cat. No. 04CH37512), Vancouver, BC, 2004, pp. IV-960, 4 pages.
- "1.3-Megapixel CMOS Active-Pixel Digital Image Sensor;" pp. 30; dated 2004; retrieved on Oct. 8, 2013 from <<http://www.digchip.com/datasheets/parts/datasheet/301/MT9M413-pdf.php>> .

(56)

References Cited

OTHER PUBLICATIONS

- "1/2-Inch 3-Megapixel CMOS Digital Image Sensor;" Micron, pp. 1-41; dated 2004; retrieved on Oct. 8, 2013 from <<http://www.neodomains.ca/domains/content/customizedTemplate/kinko/pdf/mt9t001p12stc.pdf>>.
- "417 Bar Code;" dated Dec. 25, 1997.
- "4600 Image Reader;" IMAGETEAM (Trademark) from Hand Held Products, Inc.; retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4600.pdf>>.
- "IT4000 Imaging Module & IT4300Laser Aiming Imaging Module;" Hand Held Products Inc.; Hand Held Products IMAGETEAM 4X00 Optical Subassembly; retrieved on Oct. 8, 2013 from <<http://www.racoindustries.com/hhpit4x00opt.htm>>.
- "IT4200 Image Engine & IT4250 Image Engine with decoder board;" IMAGETEAM 4200/4250 OEM 2D Image Engine; Hand Held Products, Inc.; dated 2001; retrieved on Oct. 8, 2013 from <<ftp://www.scansource.us/HandHeld%20Products/Data%20Sheets/Scanner%20%20Input%20Devices/English/4200-SS%20Rev%20B.pdf>>.
- "IT4200 Image Engine & IT4250 Image Engine with decoder board;" IMAGETEAM 4200/4250 OEM 2D Image Engine; Hand Held Products, Inc.; dated 2001; retrieved on Oct. 8, 2013 from <<ftp://www.scansource.us/HandHeld%20Products/Data%20Sheets/Scanners%20%20Input%20Devices/English/4200-SS%20Rev%20B.pdf>>.
- "Observation," Application No. 200680016023.5; Title of invention "Bar Code Reading Device with Global Electronic Shutter Control," State observation directed to the Notification of Acceptance of Request for Invalidation, which was issued by the Patent Reexamination Board on Nov. 27, 2012; 15 pages; dated Dec. 4, 2012; partial translation.
- "VV6600 1.3 Megapixel CMOS Image Sensor IC Chip;" STMicroelectronics.
- "XSCALE PXA25X Processor IC Chip including Central Processing Unit (CPU)" Intel 2002.
- "XSCALE PXA27X Processor IC Chip with 'Quick Capture Camera Interface';" Intel 2005.
- 1/2-Inch VGA (With Freeze Frame) CMOS Active-Pixel Digital Image Sensor; pp. 33; dated 2004; retrieved on Oct. 8, 2013 from <<http://www.datasheet4u.com/datasheet/M/T/9/MT9V403.sub.—Micron.pdf.h- tm1>>.
- 1/3-Inch Wide-VGA CMOA Digital Image Sensor—MT9V022; Aptina Imaging; 56 pages.; dated 2005.
- 1/3-Inch Wide-VGA CMOS Digital Image Sensor, 64 pages.
- 2003 IEEE Workshop on CCDs and Advanced Image Sensors Program, Schloss Elmau; pp. 1-5; dated May 15-17, 2003; retrieved on Oct. 8, 2013 from <<http://www.imagesensors.org/Past%20Workshops/2003%20Workshop/2003%20P-apers/2003%20Program.htm>>.
- 4000 OEM 2D Image Engine; IMAGETEAM (Trademark) from Hand Held Products, Inc.; dated 2005; retrieved on Nov. 26, 2013 from <<http://data.manualslib.com/pdf2/28/2788/278784-hand.sub.—held.sub.—products/it4000.pdf?57edd87f01d2468a84c2e0f75ef84d2c&take=binary>>.
- 4410 Image Reader; IMAGETEAM (Trademark) from Hand Held Products, Inc. retrieved on Oct. 8, 2013 from <<http://www.barcoding.com/prodpages/HHP/4410hd.pdf>>.
- A First Invalidation Request filed by Fujian Newland Auto-ID Tech. Co., Ltd ("Newland") in China submitted Apr. 18, 2012. 670 pages.
- A second invalidity request filed by Fujian Newland Auto-ID Tech. Co., Ltd. ("Newland") in China, dated Mar. 4, 2013.
- ABoushady, H.; "Single Stamp Amplifiers;" University of Paris VI, slides 1-24; dated 2001; retrieved on Oct. 8, 2013 from <<http://www-soc.lip6.fr/about.hassan/lec3.sub.—single.sub.—stage.pdf>>.
- Adams, J.E, et al.; "Color Processing in Digital Cameras;" IEEE Magazine, Eastman Kodak Company; dated 1998.
- Affidavit of Christopher Butler dated Jun. 12, 2013.
- Agilent Technologies, Pulsed Operating Ranges for AlInGaP LEDs vs. Projected Long Term Light Output Performance, Application Brief I-024, Nov. 1999, pp. 1-6.
- Appeal Decision for Japanese Application No. 2013-003616 dated Sep. 29, 2015.
- Applicants' Summary of Interview in U.S. Appl. No. 90/009,996 (U.S. Pat. No. 7,568,628); dated Dec. 14, 2012.
- Berezin, V., et al., "Dynamic Range Enlargement in CMOS Imagers with Buried Photodiode;" Micron Imaging, Micron Technology; pp. 1-3; dated 2003; retrieved on Oct. 8, 2013 from <<http://www.imagesensors.org/Past%20Workshops/2003%20Workshop/2003%20P-apers/47%20Berezin%20et%20al.pdf>>.
- Case of Demand for Rescission of Appeal Decision, Defendant's First Brief, dated Nov. 12, 2019, 92 pages.
- Chinese Office Action from Chinese Patent Application No. 201110220834.X dated Nov. 3, 2014.
- Claim set of U.S. Appl. No. 12/132,462, filed Jun. 3, 2008, 15 pages.
- Claim set of U.S. Appl. No. 12/132,480, filed Jun. 3, 2008, 18 pages.
- Comments of Statement of Reasons for Patentability and/or Confirmation in U.S. Appl. No. 90/009,996; dated Mar. 26, 2013.
- Communication Extended Search Report for European Application No. 10012906.3; dated Oct. 10, 2011.
- Communication Partial Search Report, European Patent Application No. 10012906.3; dated May 13, 2011 (5 pages).
- Communication Pursuant to Article 94(3) EPC for European Application No. 06 737 299.5; dated Jan. 11, 2008.
- Communication Pursuant to Article 94(3) EPC in European Application No. 06737300.1; dated Jan. 19, 2011.
- Communication under Rule 71(3) EPC for European Patent Application No. 13153147.7 dated Jun. 29, 2017, 7 pages.
- Communication under Rule 71(3) EPC for European Patent Application No. 15167739.0 dated May 17, 2017, 7 pages.
- Compact Flash Specification; Version 2.0; dated 2003; originally retrieved from <<http://www.compactflash.org>>; presently retrieved on Nov. 6, 2013 from <<https://www.google.com/search?q=CompactFlash+Specification%3B%E2%80%9D&rls=com.microsoft:en-us&ie=UTF-8&oe=UTF-8&startIndex=&startPage=1#q=Comp-actFlash+Specification&rls=com.microsoft:en-us>>.
- CompactFlash Specification; Version 2.0; dated 2003; originally retrieved from <<http://www.compactflash.org>>; presently retrieved on Nov. 6, 2013 from <<https://www.google.com/search?q=CompactFlash+Specification%3B%E2%80%9D&rls=com.microsoft:en-us&ie=UTF-8&oe=UTF-8&startIndex=8,startPage=1#q=Comp-actFlash+Specification&rls=com.microsoft:en-us>>.
- Complainants' Opening Claim Construction Brief, Corrected Exhibit CXM-0078, U.S. Pat. No. 7,219,841, 48 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0006, Kodak Kac-9630 CMOS Image Sensor, Device Performance Specification, 23 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0023, U.S. Pat. No. 4,794,239, 18 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0024, U.S. Pat. No. 5,304,786, 52 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0054, Microsoft Press Computer Dictionary, The Comprehensive Standard for Business, School, Library, and Home, 5 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0056, AIM, Uniform Symbology Specification Code 93, 16 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0064, International Standard, Information Technology—Automatic Identification and Date Capture Techniques—Bar Code Symbology—QR Code, 123 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0072, Webster's II New College Dictionary, 4 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0074, Microsoft Press Computer Dictionary, The Comprehensive Standard for Business, School, Library, and Home, Optical Communications. 5 pages.
- Complainants' Opening Claim Construction Brief, Exhibit CXM-0078, U.S. Pat. No. 7,446,753, 28 pages.
- Office Action for Japanese Application No. 2008-500844; dated Sep. 14, 2012; translation.
- Office Action for Japanese Application No. 2013-003616 dated May 19, 2014.
- Office Action for Japanese Application No. 2014-046409 dated Jan. 5, 2015.

(56)

References Cited

OTHER PUBLICATIONS

Office Action for Japanese Application No. 2014-046409 dated Jul. 17, 2015.

Office Action for Japanese Application No. 2015-227211 dated Jan. 15, 2018, 26 pages.

Office Action for Japanese Application No. 2015-227211 dated Oct. 24, 2016, with English translation, 7 pages.

Office Action for Japanese Application No. 2017-152142 dated Mar. 26, 2018.

Office Action for Japanese. Application No. 2015-227211 dated Sep. 14, 2018, 20 pages.

Office Action for U.S. Appl. No. 11/077,975; Notice of Allowance; dated Jul. 10, 2009.

Office Action for U.S. Appl. No. 11/174,447; dated Jan. 16, 2009.

Office Action for U.S. Appl. No. 11/445,930 dated May 13, 2009.

Office Action for U.S. Appl. No. 12/190,145 dated Nov. 14, 2013.

Office Action for U.S. Appl. No. 12/190,145; dated Aug. 12, 2008.

Office Action for U.S. Appl. No. 12/403,459 dated Mar. 7, 2012.

Office Action for U.S. Appl. No. 12/403,459 dated Oct. 2, 2012.

Office Action for U.S. Appl. No. 12/534,664; Notice of Allowance; dated Nov. 8, 2010.

Office Action for U.S. Appl. No. 12/853,090 dated Mar. 3, 2011.

Office Action for U.S. Appl. No. 12/853,590; dated Mar. 3, 2011.

Office Action for U.S. Appl. No. 12/861,461 dated Oct. 19, 2010.

Office Action for U.S. Appl. No. 13/052,768; Notice of Allowance; dated Mar. 21, 2013.

Office Action for U.S. Appl. No. 13/188,696 dated Apr. 24, 2013.

Office Action for U.S. Appl. No. 13/213,543; dated Mar. 30, 2012.

Office Action for U.S. Appl. No. 13/213,543; dated Sep. 20, 2012.

Office Action for U.S. Appl. No. 13/447,393 dated Jul. 16, 2012.

Office Action for U.S. Appl. No. 13/586,420 dated Sep. 5, 2013.

Office Action for U.S. Appl. No. 14/220,903 dated Apr. 16, 2015.

Office Action for U.S. Appl. No. 14/221,857 dated May 9, 2014.

Office Action for U.S. Appl. No. 14/221,857 dated Sep. 3, 2014.

Office Action for U.S. Appl. No. 14/221,874 dated May 9, 2014.

Office Action for U.S. Appl. No. 14/221,874 dated Sep. 15, 2014.

Office Action for U.S. Appl. No. 14/684,609 dated Oct. 25, 2015.

Office Action for U.S. Appl. No. 14/925,447 dated May 20, 2016.

Office Action for U.S. Appl. No. 15/016,927 dated May 3, 2016.

Office Action for U.S. Appl. No. 11/077,975; dated Dec. 10, 2008.

Office Action for U.S. Appl. No. 11/077,975; dated Feb. 25, 2008.

Office Action for U.S. Appl. No. 11/077,976; dated Apr. 2, 2008.

Office Action for U.S. Appl. No. 11/077,976; dated Aug. 6, 2008.

Office Action for U.S. Appl. No. 11/077,976; dated Dec. 10, 2008.

Office Action for U.S. Appl. No. 11/495,417; dated Apr. 15, 2008.

Office Action for U.S. Appl. No. 12/190,145; Advisory Action; dated Feb. 2, 2010.

Office Action for U.S. Appl. No. 12/190,145; dated Oct. 22, 2009.

Office Action for U.S. Appl. No. 12/610,892; Notice of Allowance; dated Jun. 15, 2011.

Office Action for U.S. Appl. No. 12/610,892; Notice of Allowance; dated Nov. 10, 2011.

Office Action for U.S. Appl. No. 13/188,696; dated Jan. 4, 2013.

Office Action for U.S. Appl. No. 13/437,439; dated Aug. 31, 2012.

Office Action for U.S. Appl. No. 15/244,683 dated Sep. 12, 2017.

Office Action for U.S. Appl. No. 15/401,779 dated Sep. 26, 2017.

Office Action for U.S. Appl. No. 15/244,683 dated Mar. 24, 2017, 39 pages.

Decision of Rejection for Japanese Application No. 2018-134033, dated Mar. 18, 2020, 6 pages.

Annex to the communication dated May 26, 2020 for EP Application No. 17193038.

Communication from the Examining Division dated May 26, 2020 for EP Application No. 17193038.

Notice of Allowance and Fees Due (PTOL-85) dated May 26, 2020 for U.S. Appl. No. 16/728,797.

* cited by examiner




FIG. 1A




FIG. 5A




FIG.1B




FIG. 1C





FIG.2B
Prior Art




FIG.3
Prior Art




FIG. 4A




FIG. 4B




FIG.5B




FIG.6




FIG. 7




FIG. 8A
Prior Art




FIG. 8B
Prior Art




FIG. 8C
Prior Art




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D



FIG. 10E




FIG. 11
Prior Art

FIG. 12
Prior Art




FIG.13







FIG. 14






FIG.16




FIG.17A




FIG.17B





FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG.21




FIG.22A




FIG.22B




FIG.29




FIG.30A




FIG.30B




FIG.23




FIG.24




FIG.25




FIG.26




FIG.27

FIG.28A




FIG.28B





FIG.28C






FIG.31








FIG.32



EMBODIMENT	AIMING BANK 1 LEDS 160A, 160B	BANK 2 LEDS 160C, 160E, 160H, 160J, 160L, 160N, 160O, 160Q	BANK 3 LEDS 160D, 160F, 160G, 160I, 160K, 160M, 160P, 160R	BANK 4 LEDS 160AS, 160T
1	GREEN EMITTING (GREEN)	RED EMITTING (RED)	BLUE EMITTING (BLUE)	WHITE EMITTING (WHITE)
2	GREEN	RED	RED	RED
3	RED	RED	RED	RED
4	GREEN	RED	GREEN	BLUE
5	BLUE	WHITE	WHITE	RED
6	GREEN	WHITE	RED	RED
7	WHITE	RED	RED	RED
8	GREEN	RED	RED	RED

FIG. 37

IMAGE READER COMPRISING CMOS BASED IMAGE SENSOR ARRAY

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/204,077, filed Nov. 29, 2018, (now U.S. Publication No. 2019/0174086) entitled “Image Reader Comprising CMOS Based Image Sensor Array,” which is incorporated by reference herein in its entirety, which application is a continuation of U.S. patent application Ser. No. 15/401,779, filed Jan. 9, 2017, (now U.S. Pat. No. 10,171,767) entitled “Image Reader Comprising CMOS Based Image Sensor Array,” which is incorporated by reference herein in its entirety, which application is a continuation of U.S. patent application Ser. No. 15/016,927, filed Feb. 5, 2016, (now U.S. Pat. No. 9,578,269) entitled “Image Reader Comprising CMOS Based Image Sensor Array,” which is incorporated herein by reference in its entirety, which application is a continuation of U.S. patent application Ser. No. 14/221,903, filed Mar. 21, 2014, (now U.S. Pat. No. 9,465,970) entitled “Image Reader Comprising CMOS Based Image Sensor Array,” which is incorporated herein by reference in its entirety, which application is a continuation of U.S. patent application Ser. No. 13/052,768, filed Mar. 21, 2011, (now U.S. Pat. No. 8,733,660) entitled “Image Reader Comprising CMOS Based Image Sensor Array,” which is incorporated herein by reference in its entirety, which application is a divisional of U.S. patent application Ser. No. 12/534,664, filed Aug. 3, 2009, (now U.S. Pat. No. 7,909,257) entitled “Apparatus Having Coordinated Exposure Period and Illumination Period,” which is incorporated by reference herein in its entirety, which application is a divisional of U.S. patent application Ser. No. 11/077,975, filed Mar. 11, 2005, (now U.S. Pat. No. 7,568,628) entitled “Bar Code Reading Device With Global Electronic Shutter Control,” which is incorporated herein by reference in its entirety. This application is related to U.S. patent application Ser. No. 11/077,976, filed Mar. 11, 2005, (now U.S. Pat. No. 7,611,060) entitled “System and Method to Automatically Focus an Image Reader,” which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

The invention relates to image data collection in general and particularly to an image data collector with coordinated illumination and global shutter control.

BACKGROUND OF THE INVENTION

Many traditional imager readers, such as hand held and fixed mounted bar code and machine code readers, employ charge-coupled device (CCDs) based image sensors. A CCD based image sensor contains an array of electrically coupled light sensitive photodiodes that convert incident light energy into packets of electric charge. In operation, the charge packets are shifted out of the CCD imager sensor for subsequent processing.

Some image readers employ CMOS based image sensors as an alternative imaging technology. As with CCDs, CMOS based image sensors contain arrays of light sensitive photodiodes that convert incident light energy into electric charge. Unlike CCDs, however, CMOS based image sensors allow each pixel in a two-dimensional array to be directly addressed. One advantage of this is that sub-regions of a full

frame of image data can be independently accessed. Another advantage of CMOS based image sensors is that in general they have lower costs per pixel. This is primarily due to the fact that CMOS image sensors are made with standard CMOS processes in high volume wafer fabrication facilities that produce common integrated circuits such as microprocessors and the like. In addition to lower cost, the common fabrication process means that a CMOS pixel array can be integrated on a single circuit with other standard electronic devices such as clock drivers, digital logic, analog/digital converters and the like. This in turn has the further advantage of reducing space requirements and lowering power usage.

CMOS based image readers have traditionally employed rolling shutters to expose pixels in the sensor array. In a rolling shutter architecture, rows of pixels are activated and read out in sequence. The exposure or integration time for a pixel is the time between a pixel being reset and its value being read out. This concept is presented in FIG. 2A. In FIG. 2A, the exposure for each of the rows “a” through “n” is diagrammatically represented by the bars $4a \dots 4n$ (generally 4). The horizontal extent 8 of each bar is intended to correspond to the exposure period for a particular row. The horizontal displacement of each bar 4 is suggestive of the shifting time period during which each row of pixels is exposed. As can be seen in FIG. 2A, the exposure period for sequential rows overlap. This is shown in more detail with respect to the timing diagrams for a rolling shutter architecture shown in FIG. 2B. The second 12 and third 16 lines of the timing diagram represent the reset timing signal and the read out timing signal, respectively, for row “a.” The fourth 20 and fifth 24 lines represent the reset and the read out timing signals, respectively for row “b.” As shown in both FIGS. 2A and 2B, the exposure for row “b” is initiated before the values for row “a” are read out. The exposure periods for adjacent rows of pixels typically overlap substantially as several hundred rows of pixels must be exposed and read during the capture of a frame of data. As shown by the illumination timing signal on the first line 28, the rolling shutter architecture with its overlapping exposure periods requires that the illumination source remain on during substantially all of the time required to capture a frame of data so that illumination is provided for all of the rows.

In operation, the rolling shutter architecture suffers from at least two disadvantages: image distortion and image blur. Image distortion is an artifact of the different times at which each row of pixels is exposed. The effect of image distortion is most pronounced when fast moving objects are visually recorded. The effect is demonstrated in the image shown in FIG. 3 that shows a representation of an image taken with a rolling shutter of a bus image pixels 50 passing through the field of view from right to left. As the top row of bus image pixels 54 of the bus was taken earlier than the bottom row of pixels 58, and as the bus was traveling to the left, the bottom row of bus image pixels 58 is displaced to the left relative to the top row of bus image pixels 54.

Image blur is an artifact of the long exposure periods typically required in a rolling shutter architecture in an image reader. As indicated above, in a rolling shutter architecture the illumination source must remain on during substantially all of the time required to capture a frame of data. Due to battery and/or illumination source limitations, the light provided during the capture of an entire frame of data is usually not adequate for short exposure times. Without a short exposure time, blur inducing effects become pronounced. Common examples of blur inducing effects

include the displacement of an image sensor due to, for example, hand shake with a hand held image reader.

What is needed is an image reader that overcomes the drawbacks of current CMOS image readers including image distortion and image blur.

SUMMARY OF THE INVENTION

In one aspect, the invention features a complementary metal oxide semiconductor (CMOS) based image reader for collecting image data from a target. The CMOS based imager reader comprises a CMOS based image sensor array; a timing module in electrical communication with the CMOS based image sensor array. The timing module is capable of simultaneously exposing an entire frame of pixels of the CMOS based image sensor array during an exposure period. The CMOS based image reader also comprises an illumination module capable of illuminating the target during an illumination period. The illumination module is in electrical communication with the timing module. The CMOS based image reader further comprises a control module in electrical communication with the timing module and the illumination module. The control module is capable of causing at least a portion of the exposure period to occur during the illumination period. In one embodiment of the CMOS based image reader, illuminating the target comprises overdriving light sources in the illumination module. In another embodiment of the CMOS based image reader, the light sources comprise light emitting diodes. In a further embodiment of the CMOS based image reader, the exposure period starts after the start of the illumination period and the exposure period ends before the end of the illumination period. In yet another embodiment of the CMOS based image reader, the illumination period starts after the start of the exposure period and the illumination period ends before the end of the exposure period. In yet an additional embodiment of the CMOS based image reader, the illumination period starts before the start of the exposure period and the illumination period ends before the end of the exposure period. In yet a further embodiment of the CMOS based image reader, the exposure period has a duration of less than 3.7 milliseconds. In various embodiments of the CMOS based image reader, the target includes a symbology such as a one-dimensional bar code such as a Code 39 or a UPC code or a two-dimensional bar code such as a PDF417 bar code, an Aztec symbol or Datamatrix symbol.

In another aspect the invention features a complementary metal oxide semiconductor (CMOS) based image reader for collecting image data from a target. The CMOS based imager reader comprises an integrated circuit including at least a CMOS based image sensor array and global electronic shutter control circuitry. The global electronic shutter control circuitry is capable of generating an exposure control timing pulse that is capable of causing the simultaneous exposure of substantially all of an entire frame of pixels of the CMOS based image sensor array. The CMOS based image reader also comprises light sources in electrical communication with the integrated circuit. The light sources are capable of illuminating the target including the symbology in response to an illumination control timing pulse. At least a portion of the illumination control timing pulse occurs during the exposure control timing pulse. In one embodiment of the CMOS based image reader, illuminating the target comprises overdriving light sources. In another embodiment of the CMOS based image reader, the light sources comprise light emitting diodes. In a further embodiment of the CMOS based image reader, the exposure period

starts after the start of the illumination period and the exposure period ends before the end of the illumination period. In yet another embodiment of the CMOS based image reader, the illumination period starts after the start of the exposure period and the illumination period ends before the end of the exposure period. In yet an additional embodiment of the CMOS based image reader, the illumination period starts before the start of the exposure period and the illumination period ends before the end of the exposure period. In yet a further embodiment of the CMOS based image reader, the exposure period has a duration of less than 3.7 milliseconds. In various embodiments of the CMOS based image reader, the target includes a symbology such as a one-dimensional bar code such as a Code 39 or a UPC code or a two-dimensional bar code such as a PDF417 bar code, an Aztec symbol or Datamatrix symbol.

In a further aspect, the invention features an image reader for collecting image data from a target. The imager reader comprises an integrated circuit including at least an image sensor array and exposure timing control circuitry. The exposure timing control circuitry is capable of generating an exposure control timing pulse that is capable of simultaneously exposing substantially all of the pixels in the image sensor array. The image reader also comprises an illumination module in electrical communication with the integrated circuit. The illumination module comprises light sources that are capable of illuminating the target in response to an illumination control timing pulse. At least a portion of the illumination control timing pulse occurs during the exposure control timing pulse. In one embodiment of the image reader, the illumination control timing pulse is generated by an illumination module. In another embodiment of the image reader, the overlap between the illumination control timing pulse and the exposure control timing pulse is coordinated by a control module that is in electrical communication with the integrated circuit and the illumination module. In a further embodiment of the image reader, the control module comprises a microprocessor. In one embodiment of the image reader, illuminating the target comprises overdriving light sources. In another embodiment of the image reader, the light sources comprise light emitting diodes. In a further embodiment of the image reader, the exposure period starts after the start of the illumination period and the exposure period ends before the end of the illumination period. In yet another embodiment of the image reader, the illumination period starts after the start of the exposure period and the illumination period ends before the end of the exposure period. In yet an additional embodiment of the image reader, the illumination period starts before the start of the exposure period and the illumination period ends before the end of the exposure period. In yet a further embodiment of the image reader, the exposure period has a duration of less than 3.7 milliseconds. In various embodiments of the CMOS based image reader, the target includes a symbology such as a one-dimensional bar code such as a Code 39 or a UPC code or a two-dimensional bar code such as a PDF417 bar code, an Aztec symbol or Datamatrix symbol.

In another aspect, the invention features a method for collecting image data from a target. The method comprises activating light sources to illuminate the target in response to an illumination control timing pulse. The activation of the light sources occurs for the duration of the illumination control timing pulse. The method also comprises simultaneously activating a plurality of pixels to photoconvert incident radiation. The activation of the plurality of pixels occurs in response to an exposure control timing pulse. The

method additionally comprises storing image data collected by each of the plurality of pixels in a shielded portion of each of the plurality of pixels. The storing of the image data occurs in response to the exposure control timing pulse. The method further comprises reading out image data from the plurality of pixels wherein at least a portion of the exposure control timing pulse occurs during the illumination control timing pulse. In one embodiment, the method further comprises coordinating the overlap between the illumination control timing pulse and the exposure control timing pulse. The coordination is directed by a control module. In one such embodiment of the method, the control module comprises a microprocessor. In another embodiment of the method, illuminating the target comprises overdriving light sources in an illumination module. In an additional embodiment of the method, the light sources comprise light emitting diodes. In a further embodiment of the method, the storing of image data occurs in response to a stop portion of the exposure control timing pulse. In an additional embodiment of the method, the exposure period starts after the start of the illumination period and the exposure period ends before the end of the illumination period. In yet another embodiment of the method, the illumination period starts after the start of the exposure period and the illumination period ends before the end of the exposure period. In yet an additional embodiment of the method, the illumination period starts before the start of the exposure period and the illumination period ends before the end of the exposure period. In yet a further embodiment of the method, the exposure period has a duration of less than 3.7 milliseconds. In various embodiments of the CMOS based image reader, the target includes a symbology such as a one-dimensional bar code such as a Code 39 or a UPC code or a two-dimensional bar code such as a PDF417 bar code, an Aztec symbol or Datamatrix symbol.

In another aspect, the invention features a bar code image reader for collecting and processing bar code data from a bar code symbol. The image reader comprises a two-dimensional array of pixels for receiving light radiation reflected from the bar code symbol, the two-dimensional array of pixels comprising a first plurality of pixels and a second plurality of pixels, the two-dimensional array capable of reading out the first plurality of pixels independently of reading out the second plurality, each of the pixels comprising a photosensitive region and an opaque shielded data storage region. The image reader also comprising an optics assembly for directing light radiation reflected from the bar code symbol onto the two-dimensional array of pixels. The image reader further comprising a global electronic shutter associated with the two-dimensional array of pixels, the global electronic shutter capable of simultaneously exposing substantially all of the pixels in the two-dimensional array. The image reader additionally comprising a processor module, the processor module in electronic communication with the two-dimensional array of pixels, the processor module capable of processing image data from the two-dimensional array of pixels to generate decoded bar code data. In one embodiment of the bar code image reader, the two-dimensional image sensor array is a complementary metal oxide (CMOS) image sensor. In another embodiment of the bar code image reader, processing the image data to generate output data comprises automatically discriminating between a plurality of bar code types.

In another aspect, the invention features a complementary metal oxide semiconductor (CMOS) based image reader for collecting image data from a target. The CMOS based imager reader comprises a CMOS based image sensor array,

the CMOS based image sensor array comprising a first plurality of pixels and a second plurality of pixels, the CMOS based image sensor array capable of reading out the first plurality of pixels independently of reading out the second plurality, each of the pixels of the CMOS based image sensor array comprising a photosensitive region and an opaque shielded data storage region. The CMOS based image reader also comprising a timing module in electrical communication with the CMOS based image sensor array, the timing module configured to simultaneously expose an entire frame of pixels of the CMOS based image sensor array during an exposure period. The CMOS based image sensor array further comprising an illumination module configured to illuminate the target during an illumination period, the illumination module in electrical communication with the timing module. The CMOS based image sensor array additionally comprising a control module in electrical communication with the timing module and the illumination module, the control module configured to cause at least a portion of the exposure period to occur during the illumination period.

In a further aspect, the invention features a complementary metal oxide semiconductor (CMOS) based image reader for collecting image data from a target. The CMOS based imager reader comprising an integrated circuit including at least a CMOS based image sensor array, the CMOS based image sensor array comprising a first plurality of pixels and a second plurality of pixels, the CMOS based image sensor array capable of reading out the first plurality of pixels independently of reading out the second plurality, each of the pixels of the CMOS based image sensor array comprising a photosensitive region and an opaque shielded data storage region. The CMOS based image sensor array also comprising a global electronic shutter control circuitry, the global electronic shutter control circuitry configured to generate an exposure control timing pulse that is capable of causing the simultaneous exposure of substantially all of an entire frame of pixels of the CMOS based image sensor array. The CMOS based image sensor array further comprising light sources configured to illuminate the target in response to an illumination control timing pulse, the light sources in electrical communication with the integrated circuit. In operation of the CMOS based image reader at least a portion of the illumination control timing pulse overlaps with at least a portion of the exposure control timing pulse. In one embodiment of the CMOS based image reader, illuminating the target comprises overdriving light sources in the illumination module. In another embodiment of the CMOS based reader the light sources comprise light emitting diodes. In a further embodiment of the CMOS based image reader, the exposure control timing pulse has a shorter duration than the illumination control timing pulse. In an additional embodiment of the CMOS based image reader, the illumination control timing pulse has a shorter duration than the exposure control timing pulse. In still another embodiment of the CMOS based imager reader, the illumination control timing pulse starts before the start of the exposure control timing pulse and the illumination control timing pulse ends before the end of the exposure control timing pulse. In still a further embodiment of the CMOS based imager reader, the exposure control timing pulse has a duration of less than 3.7 milliseconds. In still an additional embodiment of the CMOS based imager reader, the target includes a symbology. In one such embodiment, the symbology is a one-dimensional bar code. In another such

embodiment, the symbology is a two-dimensional bar code. In one such embodiment, the two-dimensional bar code is a PDF417 bar code.

In a further aspect, the invention features a bar code image reader for collecting image data from a bar code. The imager reader comprises an integrated circuit including at least a two-dimensional image sensor array, the two-dimensional image sensor array including a plurality of active pixels, each active pixel including at least a shielded data storage area, the two-dimensional image sensor array capable of employing a transfer function to convert an incident light intensity into an output voltage, the transfer function having a first region with a first slope and a second region with a second slope, the two-dimensional image sensor array capable of employing the second region of the transfer function when the incident light intensity is above a specified level and the two-dimensional image sensor array capable of employing the first region of the transfer function when the incident intensity is below a specified level. The bar code image reader also comprises an exposure timing control circuitry, the exposure timing control circuitry configured to generate an exposure control timing pulse that is capable of simultaneously exposing all or substantially all of the pixels in the image sensor array to photoconvert incident radiation. In one embodiment, the exposure control timing pulse has a duration of less than 3.7 milliseconds. In another embodiment, a dynamic range of the two-dimensional image array sensor is greater than 65 decibels.

In yet another aspect, the invention features a method for automatically focusing an image reader. The method comprises directing with an optical system light energy reflected from a target onto an image sensor. The method also comprises exposing sequentially a plurality of rows of pixels in the image sensor during a frame exposure period, the frame exposure period being defined as a time duration extending from the beginning of the exposure of the first of the plurality of rows to the end of the exposure of the last of the plurality of rows. The method further comprising varying in incremental steps an optical system from a first setting where a distinct image of objects located at a first distance from the image reader is formed on the image sensor to a second setting where a distinct image of objects located at a second distance from the image reader is formed on the image sensor. The method additionally comprising reading out a plurality of rows of image data from the plurality of rows of pixels in the image sensor, wherein the varying in incremental steps the optical system occurs during at least a portion of the frame exposure period. In one embodiment, the method further comprises analyzing the plurality of rows of image data to determine a proper setting for the optical system corresponding to a distinct image of the target being formed on the image sensor. In an additional embodiment, the method also comprises simultaneously exposing the plurality of rows in the image sensor to generate an image of the target. In one embodiment of the method, the exposure period for adjacent lines of pixels in image reader overlap. In another embodiment of the method, the target includes a symbology. In one such embodiment, the symbology is a one-dimensional bar code. In another such embodiment, the symbology is a two-dimensional bar code.

In another aspect, the invention features an image reader with an automatic focusing capability. The imager reader comprising an integrated circuit including at least an image sensor array. The image reader also comprising an optical system capable of directing light reflected from a target onto the image sensor array, the optical system having a plurality of focus settings, a first focus setting corresponding to

distinct images of objects located at a first distance from the image reader being formed on the image sensor array and a second focus setting corresponding to distinct images of objects located at a second distance from the image reader being formed on the image sensor array. The image reader further comprising a rolling shutter control module configured to sequentially expose a plurality of rows of pixels in the image sensor array to collect focusing image data. The imager reader additionally comprising an automatic focusing module configured to analyze the focusing image data to determine a focus setting for the target corresponding to a distinct image of the target being formed on the image sensor, wherein the optical system is capable of being varied in incremental steps from the first focus setting to the second focus setting during at least a portion of a time period during which the rolling shutter control module is sequentially exposing the plurality of rows of pixels. In one embodiment, the imager reader further comprises a global electronic shutter control module configured to simultaneously expose the plurality of lines of pixels in the image sensor array to collect a frame of image data once the focus setting for the target has been determined. In another embodiment of the image reader, the rolling shutter control module and the global electronic shutter control module are integrated on the same integrated circuit containing the image sensor array. In a further embodiment of the image reader, the rolling shutter control module and the global electronic shutter control module are combined in a single image array control module. In an additional embodiment of the image reader, the rolling shutter control module is capable of causing exposure periods for adjacent rows of pixels to overlap.

In another aspect, the invention features an image reader for minimizing ambient light image degradation. The image reader comprises an integrated circuit including at least an image sensor array, the image sensor array providing a signal suitable for light intensity determination. The image reader also comprises a rolling shutter control module configured to sequentially expose a plurality line of pixels in the image sensor array. The image reader further comprises a global electronic shutter control module configured to simultaneously expose the plurality of lines of pixels in the image sensor array, wherein one of the rolling shutter control module and the global electronic shutter control module is capable of being selected to control the image sensor array in response to the signal suitable for light intensity determination. In one embodiment of the image reader, the signal suitable for light intensity determination includes information related to an intensity of a light source of the image reader. In another embodiment of the image reader, the signal suitable for light intensity determination is useful for determining whether a minimum integration time is satisfied. In a further embodiment of the image reader, the signal suitable for light intensity determination is useful for determining whether the exposure time (also known as the integration time) for the current environmental condition is less than a calculated minimum integration time. In yet another embodiment of the image reader, the rolling shutter control module and the global electronic shutter control module are integrated on the same integrated circuit containing the image sensor array.

In still another aspect, the invention features a method for minimizing image data degradation collected by an image reader. The method comprises determining at least one parameter related to an ambient light intensity and analyzing the at least one parameter. The method also comprises switching control of an image sensor array in the image

reader from a global electronic shutter control module to a rolling shutter control module in response to the analysis of the at least one parameter. In one embodiment of the method, the at least one parameter includes an exposure time for current environmental conditions. In another embodiment of the method, the analyzing the at least one parameter includes calculating a ratio of the exposure time for current environmental conditions to a predetermined exposure time. In one such embodiment, the predetermined exposure time is based on illumination supplied by light sources of the image reader. In another embodiment of the method, analyzing the at least one parameter includes determining whether a ratio of the ambient light intensity to an intensity of a light source of the image reader exceeds a specified threshold.

The foregoing and other objects, aspects, features, and advantages of the invention will become more apparent from the following description and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects and features of the invention can be better understood with reference to the drawings described below, and the claims. The drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention. In the drawings, like numerals are used to indicate like parts throughout the various views.

FIG. 1A is a block diagram of one embodiment of an image reader constructed in accordance with the principles of the invention;

FIG. 1B is a schematic block diagram of an autodiscrimination module which may be utilized with the invention;

FIG. 1C is a process for practicing principles of the invention including automatically discriminating between different dataform types;

FIG. 2A illustrates the operation of an image sensor employing a rolling shutter architecture according to the prior art;

FIG. 2B is a timing diagram used in the prior art rolling shutter architecture presented with respect to FIG. 2A;

FIG. 3 is a representation of an image taken by a prior art image sensor;

FIG. 4A is a block electrical diagram corresponding to a specific embodiment of the invention;

FIG. 4B is a block electrical diagram corresponding to another specific embodiment of the invention;

FIG. 5A is a block diagram of one embodiment of an illumination module in an image reader constructed in accordance with the principles of the invention;

FIG. 5B is a block diagram of one embodiment of an image collection module in an image reader constructed in accordance with the principles of the invention;

FIG. 6 is a perspective drawing of one embodiment of a hand held image reader constructed in accordance with the principles of the invention;

FIG. 7 is a schematic block diagram of one embodiment of an image reader constructed in accordance with the principles of the invention;

FIG. 8A is a schematic diagram of a portion of one embodiment of an image sensor array from the prior art that can be employed in one embodiment of the image reader of FIG. 7;

FIGS. 8B and 8C are cross-sectional details of pixel architectures from the prior art that can be employed in one embodiment of the image reader of FIG. 7;

FIG. 9 is a flow chart illustrating one embodiment of a process for collecting image data according to the principles of the invention;

FIGS. 10A, 10B, 10C, and 10D are timing diagrams for various embodiments of the process of FIG. 9;

FIG. 10E illustrates an illumination control timing pulse including a plurality of individual pulses;

FIG. 11 is a schematic diagram of a portion of an image sensor according to the prior art;

FIG. 12 is a timing diagram for the prior art image sensor of FIG. 11;

FIG. 13 is a flow chart illustrating one embodiment of a process for automatic focusing according to the principles of the invention;

FIG. 14 is a flow chart illustrating one embodiment of a process for changing operational modes according to the principles of the invention;

FIGS. 15A, 15B, and 15C are various views of one embodiment of portable data terminal image reader constructed in accordance with the principles of the invention;

FIG. 16 is an electrical block diagram of one embodiment of the portable data terminal image reader of FIGS. 15A, 15B, and 15C;

FIG. 17A shows one embodiment of a plurality of curvilinear detector maps which may be utilized with the invention;

FIG. 17B shows another embodiment of a plurality of curvilinear detector maps which may be utilized with the invention;

FIG. 18 is a diagrammatic representation of a histogram analysis which may be performed in one embodiment of the invention;

FIGS. 19A-19D are diagrammatic representations of an image data segmentation process according to embodiments of the invention;

FIG. 20 is a schematic block diagram of one embodiment of a lens driver constructed in accordance with the principles of the invention;

FIGS. 21, 22A and 22B are diagram illustrations of a focus level detection process according to an embodiment of the invention;

FIGS. 23, 24, 25, 26 and 27 are flow diagrams illustrating various focusing processes which may be practiced according to the invention;

FIGS. 28A, 28B and 28C are representations of image sensor pixel array, wherein shaded regions indicate groups of positionally contiguous pixels that may be selectively addressed and read out when the image sensor array is operated in a windowed frame operating mode;

FIGS. 29, 30A and 30B are diagrams illustrating a focus level detection process which may be utilized in an embodiment of the invention;

FIGS. 31 and 32 are flow diagrams illustrating additional processes which may be practiced in accordance with the invention;

FIG. 33 is an exploded assembly view of an imaging module according to the invention;

FIG. 34 is a front view of the imaging module shown in FIG. 33;

FIG. 35 is a side view of an assembled imaging module as shown in FIG. 33;

FIG. 36 is a view of a substrate bearing a bar code symbol and having projected thereon an illumination pattern and an aiming pattern and having delineated thereon a full frame field of view of an image reader according to the invention that projects the illumination pattern and the aiming pattern; and

FIG. 37 is a chart describing various embodiments of the invention having LEDs which emit light in different wavelength bands.

DETAILED DESCRIPTION OF THE INVENTION

The invention features an image reader and a corresponding method for capturing a sharp non-distorted image of a target. In one embodiment, the image reader comprises a two-dimensional CMOS based image sensor array, a timing module, an illumination module, and a control module all in electrical communication with each other. The illumination module shines light on the target, such as a symbology such as one or two-dimensional bar code, so that reflected light that can be collected and processed by the image sensor array. The time during which the target is illuminated is referred to as the illumination period. The capture of the image by the image sensor array is driven by the timing module that, in one embodiment, is able to simultaneously expose all or substantially all of the pixels in the array. The simultaneous exposure of the pixels in the sensor array enables the image reader to capture a distortion free image. The time during which the pixels are collectively activated to photo-convert incident light into charge defines the exposure period for the sensor array. At the end of the exposure period, the collected charge is transferred to a shielded storage area until the data is read out. In one embodiment, the exposure period and the illumination period are under the control of the control module. In one such embodiment, the control module causes at least a portion of the exposure period to occur during the illumination period. By adequately shortening either the illumination period or the exposure period in an environment of low ambient lighting or the exposure period in an environment of high ambient lighting, the image reader of the present invention is able to capture an image substantially free of blurring.

Referring to FIG. 1A, a block diagram of a general image reader **100** constructed in accordance with the invention is shown. The general image reader includes one or more of: an illumination module **104**, an image collection module **108**, a control module **112**, a memory module **116**, an I/O module **120**, an actuation module **124**, a user feedback module **128**, a display module **132**, a user interface module **134**, a radio frequency identification (RFID) module **136**, a smart card module **140**, magnetic stripe card module **144**, a decoder module **150**, an autodiscriminating module **152**, and/or one or more power modules **168** and a lens driver module **165**. In various embodiments each of the modules is in combination with one or more of the other modules. In one embodiment, the image reader **100** comprises a bar code image reader with a full frame electronic global shutter based image sensor that is capable of simultaneously exposing substantially all of the pixels in the image sensor. In one such embodiment, the image sensor is a CMOS based image sensor. In another such embodiment, the image sensor is a CCD based image sensor.

Dataform decode module **150** (which may be a bar code symbol dataform decode module) when receiving image data transferred by control module **112** may search the image data for markers, such as a quiet zone, indicative of the presence of a dataform, such as a one or two-dimensional bar code. If a potential dataform is located, the dataform decode module **150** applies one or more dataform decoding algorithms to the image data. If the decode attempt is successful, the image reader outputs decoded dataform data

through I/O module **120** and signals a successful read with an alert, such as a beep tone through user interface module **134**.

Image reader **100** may also include an autodiscriminating module **152**. Referring to FIG. 1B, autodiscriminating module **152** may incorporate a dataform decode module **150** and an image processing and analysis module **1208**, that are in communication with one another.

As shown in this embodiment, the image processing and analysis module **1208** comprises a feature extraction module **1212**, a generalized classifier module **1216**, a signature data processing module **1218**, an OCR decode module **1222**, and a graphics analysis module **1224** that are in communication with each other. In addition as shown in FIG. 1B, the feature extraction module **1212** comprises a binarizer module **1226**, a line thinning module **1228**, and a convolution module **1230** that are in communication with each other.

FIG. 1C shows a process **1300** for employing one embodiment of the invention utilizing the autodiscrimination module shown in FIG. 1B. The process **1300** comprises an image reader recording an actuation event (step **1302**), such as a trigger pull as sensed by actuation module **124**, and in response collecting (step **1304**) image data from a target with the image reader **100**. The collecting of image data step may be in accordance with e.g., process **300**, process **400**, (this process is used twice, see FIG. 13 and FIGS. 23 and 24), process **600** or process **800**. After collection, the image data is transferred (step **1308**) to the dataform decode module **150**. The dataform decode module searches (step **1310**) the image data for markers, such as a quiet zone, indicative of the presence of a dataform, such as a one or two-dimensional bar code. If a potential dataform is located, the dataform decode module **150** applies (step **1314**) one or more dataform decoding algorithms to the ensuing image data. If the decode attempt is successful, the image reader **100** outputs (step **1318**) decoded dataform data and signals (step **1322**) a successful read with an alert, such as a beep tone.

In one embodiment if the decode attempt is not successful, the image data is transferred (step **1326**) to the image processing and analysis module **1208**. In another embodiment, the image data is processed in parallel with the attempt to decode the dataform data. In one such embodiment, the process that completes first (i.e., dataform decode attempt or the image processing) outputs its data (e.g., a decoded bar code or a captured signature) and the other parallel process is terminated. In a further embodiment, the image data is processed in response to the decoding of the dataform. In one such embodiment, a bar code encodes item information such as shipping label number and information indicating that a signature should be captured.

Within the image processing and analysis module **1208**, the image data is processed by the feature extraction module **1212**. In general, the feature extraction module generates numeric outputs that are indicative of the texture of the image data. As indicated above, the texture of the image data refers to the characteristics of the type of data contained in the image data. Common types of texture include one or two-dimensional bar code texture, signature texture, graphics texture, typed text texture, hand-written text texture, drawing or image texture, photograph texture, and the like. Within any category of textures, sub-categories of texture are sometime capable of being identified.

As part of the processing of the image data by the feature extraction module **1212**, the image data is processed (step **1328**) by the binarizer module **1226**. The binarizer module **1226** binarizes the grey level image into a binary image

according to the local thresholding and target image size normalization. With the image data binarized, the image data is processed (step 1332) by the line thinning module 1228 to reduce multi-pixel thick line segments into single pixel thick lines. With binarized line thinned image data, the image data is processed (step 1336) by the convolution module 1230.

In general, the convolution module 1230 convolves the processed image data with one or more detector maps designed according to the invention to identify various textural features in the image data. In one embodiment, the convolution module 1230 generates a pair of numbers, the mean and variance (or standard deviation), for each convolved detector map. FIG. 17A shows a set of 12 2x3 binary curvelet detector maps 1250 used to detect curved elements present in image data. As each of the curvelet detector maps 1250 is convolved with the image data, the mean value and the variance generated provide an indication of the presence or density of elements in the binarized line thinned image data having similar shapes to the curvelet detector maps 1250. As each pixel map generates a pair of numbers, the 12 curvelet detector maps 1250 generate a total of 24 numbers. According to one embodiment, these 24 numbers are representative of the curved or signature texture of the processed image data.

Further processing of the image data includes the outputs from the feature extraction module 1212 being fed (step 1340) into the generalized classifier module 1216. The generalized classifier module 1216 uses the numbers generated by the feature extraction module as inputs to a neural network, a mean square error classifier or the like. These tools are used to classify the image data into general categories. In embodiments employing neural networks, different neural network configurations are contemplated in accordance with the invention to achieve different operational optimizations and characteristics. In one embodiment employing a neural network, the generalized classifier module 1212 includes a $24+12+6+1=43$ nodes Feedforward, Back Propagation Multilayer neural network. The input layer has 24 nodes for the 12 pairs of mean and variance outputs generated by a convolution module 1230 employing the 12 curvelet detector maps 1250. In the neural network of this embodiment, there are two hidden layers of 12 nodes and 6 nodes respectively. There is also one output node to report the positive or negative existence of a signature.

In another embodiment employing a neural network, the 20 curvelet detector maps 1260 shown in FIG. 17B are used by the convolution module 1230. As shown, the 20 curvelet detector maps 1260 include the original 12 curvelet detector maps 1250 of FIG. 17A. The additional 8 pixel maps 1260 are used to provide orientation information regarding the signature. In one embodiment employing the 20 curvelet detector maps 1260, the generalized classifier module 216 is a $40+40+20+9=109$ nodes Feedforward, Back Propagation Multiplayer neural network. The input layer has 40 nodes for the 20 pairs of mean and variance outputs generated by a convolution module 1230 employing the 20 curvelet detector maps 1260. In the neural network of this embodiment, there are two hidden layers of 40 nodes and 20 nodes respectively, one output node to report the positive or negative existence of a signature, and 8 output nodes to report the degree of orientation of the signature. The eight output nodes provide $2^8=256$ possible orientation states. Therefore, the orientation angle is given in degrees between 0 and 360 in increments of 1.4 degrees.

In some embodiments, the generalized classifier module 1216 is capable of classifying data into an expanded collection of categories. For example in some embodiments, the

generalized classifier module 1216 specifies whether the image data contains various data types such as a signature; a dataform; handwritten text; typed text; machine readable text; OCR data; graphics; pictures; images; forms such as shipping manifest, bill of lading, ID cards, and the like; fingerprints, biometrics such as fingerprints, facial images, retinal scans and the like, and/or other types of identifiers. In further additional embodiments, the generalized classifier module 1216 specifies whether the image data includes various combinations of these data types. In some embodiments, the general classifier module 1216 specifies whether the image data contains a specified type of data or not. In one such embodiment, the image processing and analysis module 1208 is contained within an identification module that outputs an affirmative or negative response depending on the presence or absence of the specified data type, such as a signature or a biometric, in the image data.

In one embodiment once the presence of a signature has been confirmed and its general orientation determined, image data is transferred (step 1344) to the signature data processing module 1218. In one embodiment, the signature data processing module 1218 is used to detect the boundaries of the signature in the image data. In one embodiment, the signature boundary is detected using a histogram analysis. As shown in FIG. 18, a histogram analysis consists of a series of one-dimensional slices along horizontal and vertical directions defined relative to the orientation of the signature. In one embodiment, the value for each one-dimensional slice corresponds to the number of black (i.e., zero valued) pixels along that pixel slice. In some embodiments if no bar codes have been decoded, then some specified region of the full frame of image data, such as a central region is captured for signature analysis. Once completed, the histogram analysis provides a two-dimensional plot of the density of data element pixels in the image data. The boundary of the signature is determined with respect to a minimum density that must be achieved for a certain number of sequential slices. In one embodiment, the histogram analysis searches inwardly along both horizontal and vertical directions until the pixel density rises above a predefined cutoff threshold. So that the signature data is not inadvertently cropped, it is common to use low cutoff threshold values.

In one embodiment, once the boundaries of the signature have been determined, the signature data processing module 1218 crops the image data and extracts the signature image data. In one such embodiment, the cropping is performed by an image modification module that generates modified image data in which a portion of the image data not including the signature has been deleted. In other embodiments, various compression techniques are employed to reduce the memory requirements for the signature image data. One such technique includes the encoding of the signature image data by run length encoding. According to this technique, the length of each run of similar binarized values (i.e., the length of each run of 1 or 0) for each scan line is recorded as a means of reconstructing a bit map. Another encoding technique treats the signature image data as a data structure where the elements of the data structure consist of vectors. According this encoding technique, the signature is broken down into a collection of vectors. The position of each vector in combination with the length and orientation of each vector is used to reconstruct the original signature. In one such embodiment, the encoding process generates a new vector whenever the curvature for a continuous pixel run exceeds a specified value. A further com-

pression technique employs B-Spline curve fitting. This technique has the capacity to robustly accommodate curvature and scaling issues.

In various embodiments, the signature image data or a compressed or encoded version of the signature image data is stored locally on a dedicated memory device. In one such embodiment, the local memory device can be a detachable memory device such as a CompactFlash memory card or the like described in more detail below. In another embodiment, the signature image data is stored in a volatile or non-volatile portion of general purpose memory and downloaded at a future time. In a further embodiment, the signature image data can be transmitted via wired or wireless means either at the time of capture or at a later point, such as when a data collection session has been completed.

In another embodiment, the signature data processing module **218** does not perform a histogram analysis but simply stores in memory the entire image or a compressed version once the presence of a signature has been determined. In a further embodiment to save processing time, the initial image analysis is performed on a lower resolution image. Once the presence of a signature is determined in this embodiment, a higher resolution image is taken. In one embodiment, a signature extraction histogram analysis is performed on this image. Next, the image is stored in memory in either compressed or original format. In some embodiments, the image data is combined with other data to form a record for a particular item such as a package or shipping envelope. As mentioned above, some of the additional data that can be collected by the image reader **100** and stored with or separate from the signature data includes but is not limited to dataform data, handwritten text data, typed text data, graphics data, image or picture data, and the like.

As part of its operations, the image processing and analysis module **1208** can be designed to perform specialized tasks for different data types. For example, if the generalized classifier module **1216** determines that the image data contains typed or machine readable text, the image data can be collected, possibly histogram analyzed, and stored or alternatively the image data can be transferred to the OCR decoding module **1222**. Similarly, if the generalized classifier module **1216** determines that the image data includes a graphic element, the image data can be transferred to the graphics analysis module **1224** for processing. In one embodiment, the graphics analysis module **1224** is configured to recognize and decode predefined graphics. In one such embodiment, the graphics analysis can include determining which, if any, boxes have been selected in the billing and shipping instructions on a shipping label. In a further embodiment, the graphics analysis can include locating and decoding the typed or handwritten text contained in the zip code box on a shipping label. In an alternative embodiment, the image reader **100** can be configured to automatically attempt decode operations in addition to the dataform decode, such as OCR decoding or graphics decoding, prior to the activation of the feature extraction module **1212**.

In another embodiment, the image processing and analysis module **1208** segments the image data into regions and performs a feature extraction and general classification analysis on each region. In one embodiment as shown in FIG. **19A**, the standard rectangular image data window is divided into four equal sized sub-rectangles. In another embodiment shown in FIG. **19B**, the segmentation consists of overlapping regions so that the total area of the segmented regions is larger than that of the complete field of the image data. In FIG. **8B** there are seven shown overlapping regions where each identifying numeral is shown in the center of its

region. In a further embodiment shown in FIGS. **19C** and **19D**, the segmentation consists of sample regions (shown as cross-hatched) within the complete field of the image data. In another embodiment, the sampled regions can be based on a preloaded user template that, for example, identifies regions of interest such as a signature region and/or a bar code region, in for example, a shipping label.

In one embodiment, the segmentation process is used to identify the location of a signature in image data that might include additional elements such as dataforms including bar code dataforms, text, graphics, images and the like. In one such embodiment the generalized classifier module **1216** classifies the contents of each region of the segmented image data. The region containing the signature is then extracted by the signature data processing module **1218**. In one embodiment if multiple regions are indicated as containing signature data, the signature data processing module **1218** analyzes the arrangement of these regions to identify the region most likely to contain the image data. In a further embodiment when multiple regions are indicated as containing signature data, the image processing and analysis module establishes a feedback loop where additional segmented regions are generated and analyzed until a single segmented region containing signature data is located.

Additional image processing operations which may be carried out by image reader **100** are described in U.S. patent application Ser. No. 10/958,779, filed Oct. 5, 2004 entitled, "System And Method To Automatically Discriminate Between A Signature And A Bar code" and incorporated herein by reference in its entirety.

Referring to additional components of image reader **100** indicated in FIG. **1A** and FIG. **5A**, illumination module **104** can include light sources **160**, an illumination control module **164**, an illumination power module **168a**, and an interface module **172**. In various embodiments, the light sources **160** can include white or colored LEDs, such as 660 nm illumination LEDs, infrared LED, ultra-violet LED, lasers, halogen lights, arc lamps, or incandescent lights, capable of producing adequate intensity light given image reader power constraints and image sensor exposure/sensitivity requirements. In many embodiments, LEDs are chosen for the light source as their efficient operation enables relatively low power consumption. The illumination control module **164** controls the operation of illumination module **104** and can include timing and light source activation and deactivation circuitry. The illumination power module **168a** supplies the energy necessary to drive the light sources **160** and can include batteries, capacitors, inductors, transformers, semiconductors, integrated circuits and the like. In an alternative embodiment, some or all of the elements of the illumination power module **168a** are located external to the illumination module. An image reader **100** with a single common power source is one such embodiment. The interface module **172** is used for communication with the other modules of the image reader **100** such as those required to synchronize operations. This can include, for example, the coordination of the illumination and exposure periods discussed above.

Referring to the physical form views of FIGS. **33-36**, various components of illumination module **104** and image collection module **108** according to one embodiment of the invention are shown and described. An image reader **100** of the invention, as shown in the embodiment of FIGS. **15A-15C**, may include an imaging module such as imaging module **1802**. Imaging module **1802** as shown in FIGS. **33-35** incorporates certain features of an IT4000 imaging module as referenced herein and additional features. Imaging module **1802** includes first circuit board **1804** carrying

light sources **160a**, **160b**, while second circuit board **1806** carries light sources **160c**, **160d**, **160e**, **160f**, **160g**, **160h**, **160i**, **160j**, **160k**, **160l**, **160m**, **160n**, **160o**, **160p**, **160q**, **160r**, **160s**, and **160t** (hereinafter **160c** through **160t**). First circuit board **1804** also carries image sensor array **182**. Imaging module **1802** also includes support assembly **1810** including lens holder **1812**, which holds lens barrel **1814** that carries imaging lens **212**. Light sources **160a**, **160b** are aiming illumination light sources whereas light sources **160c** through **160t** are illumination light sources. Referring to FIG. **36**, illumination light sources **160c** through **160t** project a two-dimensional illumination pattern **1830** over a substrate, that carries a decodable indicia such as a bar code symbol **1835** whereas aiming illumination light sources **160a**, **160b** project an aiming pattern **1838**. In the embodiments shown and described in connection with FIGS. **33-36**, light from aiming illumination light sources **160a**, **160b** is shaped by slit apertures **1840** in combination with lenses **1842** which image slits **1840** onto substrate, s, to form aiming pattern **1838** which in the embodiment of FIGS. **33-36** is a line pattern **1838**. Illumination pattern **1830** substantially corresponds to a full frame field of view of image reader **100** designated by box **1850**. Aiming pattern **1838** is in the form of a line that extends horizontally across a center of field of view of image reader **100**. Illumination pattern **1830** may be projected when all of illumination light sources **160c** through **160t** are operated simultaneously. Illumination pattern **1830** may also be projected when a subset of light sources **160c** through **160t** are simultaneously energized. Illumination pattern **1830** may also be projected when only one of light sources **160c** through **160t** is energized such as LED **160s** or LED **160t**. LEDs **160s** and **160t** of imaging module **1802** have a wider projection angle than LEDs **160c** through **160t**.

As shown in FIG. **5B**, the image collection module **108** in one embodiment includes an optics module **178**, a sensor array module **182**, and a sensor array control module **186** all in electrical communication with each other. The optics module **178** includes an imaging lens or other optical elements used to direct and focus reflected radiation. In some embodiments, the optics module **178** includes associated circuitry and processing capacity that can be used, for example, as part of automatically determining the proper focus for an object, being imaged.

The sensor array control module **186** includes a global electronic shutter control module **190**, a row and column address and decode module **194**, and a read out module **198**, each of which modules is in electrical communication with one or more of the other modules in the sensor array control module **186**. In one embodiment, the sensor array module **182** includes components of an integrated circuit chip **1082** as shown in FIG. **4A** with a two-dimensional CMOS based image sensor array **182**. In various embodiments, associated circuitry such as analog-to-digital converters and the like can be discrete from the image sensor array or integrated on the same chip as the image sensor array. In an alternative embodiment, the sensor array module **182** can include a CCD sensor array capable of simultaneous exposure and storage of a full frame of image data. As indicated above in one embodiment, the global electronic shutter control module **190** is capable of globally and simultaneously exposing all or substantially all of the pixels in the image sensor array. In one embodiment, the global electronic shutter control module **190** includes a timing module. The row and column address and decode module **194** is used to select particular pixels for various operations such as collection activation, electronic shutter data storage and data read out. The read

out module **198** organizes and processes the reading out of data from the sensor array. In some embodiments, the sensor array control module **186** further includes a rolling shutter control module **202** that is capable of sequentially exposing and reading out the lines of pixels in the image sensor array.

A specific embodiment of image reader **100** is described with reference to FIG. **4A**. In the embodiment of FIG. **4A** and image sensor array **182**, **182a** having a two-dimensional array of pixels **250** is incorporated onto CMOS integrated circuit (IC) chip **1082**, **1082a**. As is described later with reference to FIG. **8A**, image sensor array **182a** is a CMOS image sensor array adapted to operate in a global shutter operating mode. Each pixel **250** of CMOS image sensor array **182a** has an on-chip pixel amplifier **254** (shown in FIG. **8A**) and an on-chip optically shielded storage area **286** (shown in FIG. **8B** and FIG. **8C**). Image sensor array **182a** may also have a two-dimensional grid of electrical interconnects **262** as shown in FIG. **8A** that are in electrical communication with pixels **250**. Image sensor array **182a** may also have an on-chip row circuitry **296** and column circuitry **270**. Row circuitry **296** and the column circuitry **270** may enable one or more various processing and operational tasks such as addressing pixels, decoding signals, amplification of signals, analog-to-digital signal conversion, applying timing, read out and reset signals and the like. Referring to further aspects of CMOS image sensor IC chip **182a**, CMOS image sensor IC chip **182a** includes, on the same chip as pixels **250** row circuitry **296**, column circuitry **270**, processing and control circuitry **254** including pixel amplifiers **255**, optically shields storage area **258**, interconnects **262**, a gain circuit **1084**, an analog-to-digital conversion circuit **1086** and line driver circuit **1090**, which generates a multi-bit (e.g., 8 bit 10 bit) signal indicative of light incident on each pixel **250** of array, the output being presented on a set of output pins of chip **1082a**. Referring to additional on-chip elements of image sensor IC chip **1082a**, CMOS image sensor IC chip **1082a** includes timing/control circuit **1092** which may include such components as a bias circuit, a clock/timing generation circuit, and an oscillator. Timing/control circuit **1092** may form part of sensor array control module **108** as described in connection with FIG. **5B**.

Referring to further aspects of image reader **100** of FIG. **4A**, image reader **100** includes a main processor IC chip **548**, memory module **116**, illumination module **104**, and actuation module **124**. Main processor IC chip **548** may be a multifunctional IC chip having an integrated frame grabber circuit **549** and central processing unit (CPU) **552**. Processor IC chip **548** with an integrated frame grabber may be an e.g., an XSCALE PXA27X processor IC chip with "Quick Capture Camera Interface" available from INTEL. Image reader **100** further includes actuation module **124** which generates a trigger signal that initiates a bar code decode process. Actuation module **124** may include a manually actuated trigger **216**. Image reader **100** further includes imaging lens **212** and memory module **116** including such memory devices as a RAM, EPROM, flash memory. Memory module **116** is in communication with processor IC chip **548** via a system bus **584**. Processor IC chip **548** may be programmed or otherwise configured to carry out various functions required of modules **104**, **108**, **112**, **120**, **124**, **128**, **132**, **134**, **136**, **140**, **144**, **150**, **152**, **168**, **165** described with reference to FIG. **1A**. In the embodiment of FIG. **4A**, the functions of dataform decode module **150** and autodiscrimination module **152** are carried by processor IC chip **548** operating in accordance with specific software stored in memory module

116. The combination of processor IC chip **548** and memory module **116** is, therefore, labeled **150**, **152** in the embodiment of FIG. **4A**.

Referring to FIG. **4B**, an embodiment of image reader **100** is shown which has a CCD image sensor chip **1082**, **1082b**. CCD image sensor IC chip **1082b**. CCD image sensor IC chip **1082b** includes an area array of pixels **250**, a register **1094** and an output amplifier **1096** incorporated onto chip **1082b**. Output register **1094** and associated circuitry sequentially converts the charge associated with each pixel into a voltage and sends pixel image signals to a component external to chip **1082b**. When actuated to read out image data, charges on a first row of pixels **250** are sequentially transferred to output register **1094**. Output register **1094** sequentially feeds charges to amplifier **1096** which converts pixel charges into voltages and supplies signals to image processing circuitry **1070**. When charges are transferred from a first row of pixels to output register **1094**, charges from a next row move down one row so that when a first row of charges has been converted into voltages, output register **1094** receives charges from a second row of pixels. The process continues until image data corresponding to pixels from all of the rows of image sensor array **182b** are read out. Image reader **100** further includes image signal processing circuit **1070** external to chip **1082b**. Image signal processing circuit **1070** includes such elements as a gain circuit **1072** an analog-to-digital converter **1074** and a line driver **1076**. Timing and control circuit **1078** of circuit **1070** may include such elements as a bias generator, an oscillator, a clock and timing generator. The gain circuit **1072** may also implement additional functionality such as correlated double sampling to reduce to effects of pixel offsets and noise. Additional components of image reader **100** are as shown in FIG. **4A**. Image signal processing circuit **1070** may be included in an integrated circuit chip (IC chip) external to image sensor IC chip **1082b**.

In one embodiment, components of image collection module **108** and illumination module **104** are provided by any one of the IMAGETEAM™ area (2D) imaging engines, such as the 4000 OEM 2D Image Engine available from Hand Held Products, Inc. of 700 Visions Drive, P.O. Box 208, Skaneateles Falls, N.Y., constructed in accordance with the principles of the invention.

Referring to FIG. **6**, a perspective drawing of a hand held image reader **100a** constructed in accordance with one embodiment of the invention is shown. The hand held image reader **100a** includes a housing **208**, a plurality of light sources **160**, a lens **212**, a trigger **216**, and an interface cable **200**. In various embodiments, the functionality of the image reader **100a** can be provided by any one of the area (2D) IMAGETEAM™ image readers such as the models 4410, 4600, or 4800 available from Hand Held Products, Inc. and constructed in accordance with the invention. All of the modules **104**, **108**, **112**, **116**, **120**, **124**, **128**, **132**, **134**, **136**, **140**, **144**, **150**, **152**, **165**, and **168** described in connection with FIG. **1A** may be incorporated into, and may be supported by hand held housing **208** or alternative housing **506** shown in FIG. **15A** such that housing **208** or housing **506** encapsulate and support the various modules. Likewise, all of the components shown in FIGS. **4A** and **4B** and FIG. **16** may be incorporated into and may be supported by housing **208** or housing **506** such that housing **208** or housing **506** encapsulate and support the various components. Lens **212** may comprise glass and/or polycarbonate. Lens **212** may be a lens singlet or else comprise a plurality of lens components; that is, lens **212** may be a lens doublet or lens triplet, etc.

Referring to FIG. **7**, a diagrammatic cross sectional view in combination with a schematic block diagram for the image reader **100** is shown. The image reader **100** includes the light sources **160**, an illumination control module **164**, a power module **168b**, and an interface module **172** all in electrical communication with each other. The light sources **160** direct light energy **162** towards a target **166** including a symbology **170**. Reflected radiation **174** from the target **166** is focused by a lens **212** onto an image sensor array **182** in electrical communication with a sensor array control module **186** and the power module **168b**. In one embodiment, the image sensor array **182** is a CMOS based image sensor array. In another embodiment, the image sensor array **182** is a CCD based image sensor array. The sensor array control module **186** is further in electrical communication with a memory module **116** and a control module **112** also in electrical communication with the power module **168b** and the interface module **172**. Often an optical window (not shown) is placed on the front of the scanner to reduce the likelihood of damage to the unit.

Referring to FIG. **8A**, a diagram of a portion of a CMOS based image sensor array **182a** is shown in more detail. The image sensor array **182a** includes a two-dimensional array of pixels **250**. Each pixel includes a photosensitive sensitive region **252**, processing and control circuitry **254** including amplifier **255** and a shielded storage area **258** (for clarity of presentation, the reference numerals **252**, **254**, **255**, and **258** are provided only with respect to a single pixel). The presence of amplifier **255** means that the CMOS image array **182a** is considered an active pixel array; that is, each pixel of the CMOS image array **182a** is able to amplify the signal generated from the photo-conversion of incident light energy. The charge-to-voltage conversion circuitry allows the CMOS image array **182a** to convert the collected charge into an output signal. The shielded storage area **258** stores collected pixel values until read out so that additional incident radiation impinging on the CMOS image array **182a** does not corrupt the value read during the defined exposure period. In addition to pixel amplifier **255**, the processing and control circuitry **254** for each pixel **250** may include, among other elements, a reset and select transistor.

In one embodiment, the dynamic range of the CMOS based image sensor array **182a** is extended by providing additional intelligence in the processing and control circuitry **254**. In particular, the processing circuitry is augmented to include the capacity to dynamically change the conversion factor between the incident radiation input intensity and the output voltage. That is, the processing circuitry employs a transfer curve with multiple slopes. The particular form of the transfer curve with its multiple slopes can take various forms including a series of linear relations joined at knee points, a linear section at low intensity connected to a logarithmic transfer curve at higher intensity, or a completely continuous curve of arbitrary shape with steeper slopes for low intensity and higher slopes at greater intensities.

In the multiple slope embodiment, the dynamic range of the CMOS based image sensor **182a** is significantly extended as each individual pixel is capable of independently employing a different section of the transfer curve depending on the intensity of radiation incident upon it. In operation, regions of the CMOS based image sensor **182a** that are receiving less incident radiation employ a steeper conversion slope corresponding to greater sensitivity and regions that are receiving more incident radiation employ a shallower conversion slope corresponding to less sensitivity. With a multiple slope transfer function, the CMOS based

image sensor **182a** can achieve a dynamic range of 65 to 120 dB. The operation of image sensors with transfer curves with multiple slopes are described in more detail in the technical document entitled "Dual Slope Dynamic Range Expansion" from FillFactory NV, Schalienhoevedreef 20B, B-2800 Mechelen, Belgium. This document is available from the Fill Factory (www.fillfactory.com), for example at <http://www.fillfactory.com/htm/technology/htm/dual-slope.htm> and is hereby herein incorporated in its entirety. The operation of image sensors with transfer curves with logarithmic slopes are described in more detail in the technical document entitled "LinLog Technology" from Photonfocus AG, Bahnhofplatz 10, CH-8853 Lachen, Switzerland. This document is available from the Photonfocus (www.photonfocus.com), for example at <http://www.photonfocus.com/html/eng/cmos/linlog.php> and is hereby herein incorporated in its entirety.

Overlaying the pixels **250** in FIG. **8A** is a two-dimensional grid of electrical interconnects **262** that are in electrical communication with the pixels **250**, the row circuitry **296** (see also FIG. **4A**) and the column circuitry **270**. The row circuitry **296** and the column circuitry **270** enable one or more processing and operational tasks such as addressing pixels, decoding signals, amplification of signals, analog-to-digital signal conversion, applying timing, read out and reset signals and the like. With on-chip row circuitry **296** and column circuitry **270**, CMOS based image sensor array **182a** may be operated to selectively address and read out data from individual pixels in an X-Y coordinate system. CMOS based image sensor array **182a** may also be operated by way of appropriate programming of image reader **100**, to selectively address and read out a portion of the full frame of pixels. For example, in these embodiments the portion of pixels read out can exclude undesired pixels external to a desired pixel region. The portion of pixels read can also represent a sampling of pixels in a region so that individual pixels, rows of pixels, or columns of pixels in the region of interest are not read out. Further details of image reader **100** operating in a windowed frame operating mode in which image reader **100** selectively addresses and reads out image data from less than all pixels of image sensor array **182** is described in connection with FIGS. **28A**, **28B**, and **28C**. In general, image reader **100** can be programmed or otherwise configured to selectively address and read out from CMOS based image sensor array **182a** image data from a first plurality of pixels in the array independently of selectively addressing and reading out a second plurality of pixels in the array.

In one embodiment, the pixel architecture can be as described in U.S. Pat. No. 5,986,297 assigned to Eastman Kodak Company and entitled "Color Active Pixel Sensor with Electronic Shuttering, Anti-blooming and Low Cross-talk." In particular at column 3 lines 35 to 55 and at column 5 lines 25 to 55, the patent describes the cross sections of the relevant regions of the pixel architectures shown in the patent's FIGS. **1A** and **2A** (herein reproduced as FIGS. **8B** and **8C**). The disclosure states that the pixel in FIG. **8B** comprises a photodiode **270** with a vertical overflow drain **274**, transfer gate **276**, floating diffusion **280**, reset gate **282**, reset drain **284**, and a light shield **286**. A light shield aperture **288**, color filter **290**, and micro lens **292** are placed over the photodetector such that light is focused through micro lens **292** into light shield aperture **288** after passing through color filter **290**. Therefore, the light entering photodiode **270** has a wavelength that is within a predetermined bandwidth as determined by the color filter **290**. The patent describes FIG. **8C** as showing a second pixel architecture that is similar in

many respects to the embodiment shown in FIG. **8B** except that there are two transfer gates **294**, **296**, and a storage region **298**. In both cases the light shield is constructed by effectively covering all regions except the photodetectors (photodiode **270** in this case), with an opaque layer or overlapping layers, so that incident light falls only on the photodiode area. Creation of an aperture in a light shield that limits the creation of photoelectrons to the photodetector region suppresses cross-talk between pixels. In FIG. **8C**, the floating diffusion is labeled **281**, the reset gate is labeled **283**, and the reset drain is labeled **285**. In some embodiments employing the pixel architecture described in U.S. Pat. No. 5,986,297, the color filter **290** may be omitted, and in other embodiments the microlens **292** may be omitted.

A process **300** for collecting image data from a target with the image reader **100** is presented with respect to FIGS. **9**, **10A**, **10B**, **10C** and **10D**. In various embodiments the target can contain a symbology such as a one or two-dimensional bar code. At step **302**, actuation module **124** initiates process **300** in response e.g., to trigger **216** being depressed or to a sensing of a presence of an object in a field of view of image reader **100**. In one embodiment, control module **112** may receive a trigger signal in response to a depressing of trigger **216** or the sensing of an object and responsively present a series of control signals to various modules, e.g., illumination module **104** and image collection module **108** in accordance with process **300**. The process **300** includes activating (step **304**) an illumination source to illuminate the target with illumination light **162**. In one embodiment, the activation of the illumination source occurs in response to an illumination control timing pulse **350**. The illumination of the target by the activated illumination source occurs for the duration of the illumination control timing pulse **350**. In one embodiment, the illumination source is the light source **160** and the illumination control timing pulse **350** is generated by the illumination control module **164** in the illumination module **104**. The process **300** also includes activating the global electronic shutter to simultaneously expose (step **312**) a plurality of pixels in a plurality of rows in an image sensor array to photoconvert incident radiation into electric charge. The simultaneous activation of the plurality of pixels occurs in response to an exposure control timing pulse **354**. In one embodiment, the simultaneous activation of the plurality of pixels occurs in response to a start portion **360** of the exposure control timing pulse **354**. In a further embodiment, the exposure control timing pulse **354** is generated by the global electronic shutter control module **190** (FIG. **5B**) of the sensor array control module **186**.

In one embodiment for collecting an image of a target that minimizes translational image distortion, the target is illuminated by overdriving the illumination sources, such as LEDs, to generate illumination several times brighter than standard operation. Referring to an example of the invention wherein image reader **100** includes imaging module **1802** as shown in FIGS. **33-35**, LEDs **160c** through **160t** (that is, **160c**, **160d**, **160e**, **160f**, **160g**, **160h**, **160i**, **160j**, **160k**, **160l**, **160m**, **160n**, **160o**, **160p**, **160q**, **160r**, **160s**, and **160t**) each may have a standard recommend maximum DC operation current draw rating of 40 mA (100% LED current) but may be overdriven to draw more than e.g., 60 mA (150% current), or 80 mA (200% current) throughout the duration of illumination timing pulse **350**, or any one of pulses **350'**, **350''**, **350'''** described herein. LEDs **160c** through **160t**, where LEDs **160c** through **160t** have a standard recommended maximum DC operating current draw rating of 40 mA, may also be overdriven to draw more than e.g., 120 mA (300% current), 160 mA (400% current), 200 mA (500%

current), or 500 mA (1,250% current) throughout the duration of timing pulse **350** or any one of pulses **350'**, **350''**, **350'''** described herein. Illumination timing pulse **350**, **350'**, **350''**, **350'''** are shown as DC drive current pulses. However, according to the invention as indicated by FIG. 10E, pulses **350**, **350'**, **350''**, **350'''** can also be pulse modulated or “strobed” pulses such that each pulse **350**, **350'**, **350''**, **350'''** comprise a series of short duration individual pulses for driving LEDs **160**. Substituting a pulsed driving signal for a DC driving signal reduces the duty cycle of LEDs, and thus the power dissipated in the LEDs. Since in many cases the LED operating life is determined by the maximum junction temperature of the LED die, reduced power dissipation reduces the junction temperature. The net effect is that a higher peak current can be tolerated while not exceeding the maximum operating junction temperature limit for the LED die. In general, reducing the duty cycle of LEDs **160** increases the amount of current that can be safely driven through LEDs. The strobing rate of a “strobed” or “pulsed” illumination control pulses as described herein may be, e.g., 1,000 Hz to 10,000 Hz. According to this embodiment, the overdriven illumination sources in combination with the electronic global shutter allows for short exposure periods. That is, the bright illumination allows for a short integration time for each pixel and the global electronic shutter allows for all of the pixels in the image sensor to be simultaneously sensitive. With a short exposure period for a brightly illuminated target, an image reader of the present invention is able to collect a sharp non-distorted image even when the target is moving relative to the image reader. In one embodiment, the exposure period is less than 3.7 milliseconds. In one embodiment in which the light sources are overdriven, light sources with different colors are employed. For example, in one such embodiment the image reader includes white and red LEDs, red and green LEDs, white, red, and green LEDs, or some other combination chosen in response to, for example, the color of the symbols most commonly imaged by the image reader. In this embodiment, the different colored LEDs are each alternatively pulsed at a level in accordance with the overall power budget. In another such embodiment, both colored LEDs are pulsed each time but each at a relatively lower power level so that the overall power budget is again maintained. In a further embodiment, red, green, and blue LED's can be interleaved to simulate white light.

Various embodiments of imaging module **1802** of image reader **100** are described with reference to FIG. 37. LEDs **160** of imaging module **1802** may be divided into banks as indicated in the chart of FIG. 37. Image reader **100** can be configured so that LEDs of each bank emits light in a certain emission wavelength band. In embodiment 8 depicted in the chart of FIG. 37, image reader **100** is configured so that aiming LEDs **160a**, **160b** emit green light and all illumination LEDs **160c** through **160t** emit red light. Additional embodiments are described in the chart of FIG. 37. Image reader **100** can be configured so that the light sources for the various banks may be energized simultaneously (e.g., bank 1, bank 2, bank 3, bank 4 simultaneously energized) or sequentially (e.g., bank 1, then bank 2, then bank 3, then bank 4) by the illumination timing control pulse **350**, **350'**, **350''**, **350'''**.

Referring again to FIGS. 9, 10A, 10B, 10C, and 10D the process **300** also includes processing (step **316**) the photo-conversion generated electric charge to produce image data. As discussed above, the processing can include, for example, amplifying the data generated from the incident radiation. The processing further includes storing the gen-

erated image data values in a shielded portion of each of the plurality of pixels. The process **300** additionally includes reading out and processing (step **320**) the stored image data values from the plurality of pixels. As discussed above, the processing can include amplifying the data generated from the incident radiation and converting the generated data into a digital signal. The processing (step **320**) can also include storing a set of digital signal values corresponding to incident light on the plurality of pixels of image sensor array module **182** as a frame of image data. Image reader **100** at step **320** may store into memory module **116** a frame of image data including a plurality of N-bit (grey scale) pixel values, each pixel value representing light incident at one of the plurality of pixels. In one embodiment, the reading out of the plurality of pixels is controlled by a read out timing control pulse **368** generated by the read out module **198** of the sensor array control module **186**. In one embodiment, the read out timing control pulse **368** includes a plurality of pulses transmitted to each of the plurality of pixels. In one embodiment, at least a portion of the illumination control timing pulse **350** occurs during the exposure control timing pulse **354**. In one such embodiment, the operation of the image collection module **104** including the sensor array control module **186** with the global electronic shutter control module **190** is coordinated with the operation of the illumination module **104** including the illumination control module **164** by the control module **112** to achieve the overlap in the illumination **350** and exposure **354** control timing signals.

In one embodiment as shown in FIG. 10A, the exposure control timing pulse **354** begins after and finishes before the illumination control timing pulse **350**. The read out control timing pulse **368** begins at the conclusion of the illumination control timing pulse **350**. In another embodiment as shown in FIG. 10B, the illumination control timing pulse **350'** begins after and finishes before the exposure control timing pulse **354'**. In this embodiment, the read out control timing pulse **368'** begins at the conclusion of the exposure control timing pulse **354'**. In further embodiments the exposure control timing pulse and the illumination control timing pulse overlap each other while occurring sequentially. In one such embodiment as shown in FIG. 10C, this sequential operation can include the illumination control timing pulse **350''** starting, the exposure control timing pulse **354''** starting, the illumination control timing signal pulse **350''** ending, and then the exposure control timing pulse **354''** ending. In this embodiment, the read out control timing pulse **368''** begins at the conclusion of the exposure control timing pulse **354''**. In a further such embodiment as shown in FIG. 10D, the sequential operation can include the exposure control timing pulse **354'''** starting, the illumination control timing pulse **350'''** starting, the exposure control timing pulse **354'''** ending, and then the illumination control timing signal pulse **350'''** ending. In this embodiment, the read out control timing pulse **368'''** begins at the conclusion of the illumination control timing signal pulse **350'''**. As discussed in connection with FIG. 10E, each illumination control timing pulse **350**, **350'**, **350''**, **350'''** described herein may comprise a plurality of short duration individual pulses.

Referring again to imaging module **1802**, an image reader **100** having imaging module **1802** may have an operating mode in which aiming LEDs **160a**, **160b** are controlled to be off or de-energized during exposure control timing pulse **354**, **354'**, **354''**, or **354'''** so that light from LEDs **160a**, **160b** does not influence an image that is collected and transferred to decode module **150** or autodiscrimination module **152**. In another embodiment, aiming illumination LEDs **160a**, **160b**,

in addition to illumination LEDs **160c** through **160t**, are controlled to be energized during exposure control timing pulse **354**, **354'**, **354"**, or **354'''**. Controlling aiming illumination LEDs **160c** through **160t** to be energized during exposure control timing pulse **354**, **354'**, **354"**, or **354'''** increases a signal strength of image data corresponding regions of substrate, *s*, onto which aiming pattern **1838** is projected.

With reference to process **300** (FIG. 9), image reader **100** may be configured so that illumination control pulse **350**, **350'**, **350"**, or **350'''** at step **304** simultaneously energizes at least one of aiming LED **160a** or **160b** and at least one of illumination LEDs **160c** through **160t** so as to increase the intensity of illumination on substrates, and specifically the regions of substrates, onto which illumination pattern **1830** and aiming pattern **1838** are simultaneously projected. A decoding process carried out by decode module **150** or autodiscrimination module **152** where an image is collected pursuant to an exposure period wherein aiming LEDs **160a**, **160b** and illumination LEDs **160c** through **160t** are simultaneously energized may include a process wherein image data corresponding pattern **1838** (that is, image data corresponding to pixels of array onto which pattern **1838** is imaged) is selectively subjected to a decoding process such as a finder pattern locating process, a linear bar code symbol decode attempt or a quiet zone locating process. For example, with aiming pattern **1838** horizontally extending across a field of view, decode module **150** processing a collected full frame image may selectively analyze image data corresponding to center rows of image sensor **182** (i.e., image data corresponding to rows **2802** shown in FIG. **28a**) for purposes of locating a finder pattern, decoding a linear bar code symbol, or locating a quiet zone where an image is collected pursuant to a frame exposure period wherein at least one aiming LED **160a**, **160b** and at least one illumination LED **160c** through **160t** are simultaneously energized. At step **320** of process **300** carried out with illumination control pulse **350**, **350'**, **350"**, or **350'''** simultaneously energizing at least one aiming illumination LED e.g., **160a** and at least one illumination LED, e.g., **160t**, image reader **100** may collect either a full frame or a "windowed frame" of image data as is described in greater detail in connection with FIGS. **28A-28C**. Image reader **100** may be configured so that where image reader **100** at step **320** collects a windowed frame of image data and at step **304** simultaneously illuminates at least one aiming illumination LED and at least one illumination LED, the windowed frame corresponds to the size and shape of illumination pattern **1838**. For example, where image reader **100** projects horizontal line aiming pattern **1838**, the windowed frame of image data readout at step **320** may be a windowed frame of image data corresponding to rows **2802** shown in FIG. **28A** onto which pattern **1838** is imaged which is then processed as described herein (e.g., by attempting to decode linear bar code symbol by locating a quiet zone or by locating a finder pattern). In embodiments of the invention wherein aiming illumination LEDs and illumination LEDs are simultaneously driven by illumination control pulse **350**, **350'**, **350"**, or **350'''**, the aiming LEDs **160a**, **160b** and illumination LEDs **160c** through **160t** may be overdriven throughout the duration of pulse **350**, **350'**, **350"**, or **350'''** as has been described herein.

In one embodiment the CMOS image array **182a** can be implemented with a KAC-0331 640x480 VGA CMOS image sensor available from the Eastman Kodak Company. The KAC-0311 is more fully described in a technical description entitled, "KAC-0311 640x480 VGA CMOS IMAGE SENSOR Fully Integrated Timing, Analog Signal

Processing & 10 bit ADC." Revision 1 dated Aug. 5, 2002 and available at <http://www.kodak.com/global/plugins/acrobat/en/digital/ccd/products/cmos/KAC-0311LongSpec.pdf>, hereby incorporated by reference in its entirety. The following is an edited summary of the operation of the KAC-0311 taken from the aforementioned "Full Specification." As summarized in this technical description, the KAC-0311 is a solid state active CMOS imager that integrates analog image acquisition, digitization, and digital signal processing on a single chip. The image sensor comprises a VGA format pixel array with 640x480 active elements. The image size is programmable by a user to define a window of interest. In particular, by programming the row and column start and stop operations, a user can define a window of interest down to a resolution of 1x1 pixel. In one embodiment of the KAC-0311 image sensor, the window can be used to enable a digital zoom operation of a viewport that can be panned. In another embodiment of the KAC-0311 image sensor, a constant field of view is maintained while subsampling is used to reduce the resolution of the collected image.

The pixels of the KAC-0311 image sensor are on a 7.8 μm pitch. The pixel architecture is Kodak's pinned photodiode architecture. The KAC-0311 image sensor is available in a Monochrome version without microlenses, or with Bayer (CMY) patterned Color Filter Arrays without microlenses. In one embodiment of the KAC-0311 image sensor, integrated timing and programming controls are used to enable progressive scan modes in either video or still image capture operation. In a further embodiment of KAC-0311 image sensor, a user can program the frame rates while maintaining a constant master clock rate.

In the KAC-0311 image sensor, the analog video output of the pixel array is processed by an on-chip analog signal pipeline. In one embodiment of the KAC-0311 image sensor, correlated double sampling is used to eliminate pixel reset temporal and fixed pattern noise. In a further embodiment of the KAC-0311 image sensor, a frame rate clamp is used to enable contemporaneous optical black level calibration and offset correction. In yet another embodiment, the programmable analog gain of the KAC-0311 image sensor includes a global exposure gain to map the signal swing to the analog-to-digital converter input range. The programmable analog gain further includes white balance gain to perform color balance in the analog domain. In an additional embodiment, the analog signal processing chain of the KAC-0311 image sensor consists of column op-amp processing, column digital offset voltage adjustment, white balancing, programmable gain amplification, global programmable gain amplification, and global digital offset voltage adjustment. In one embodiment, the digitally programmable amplifiers are used to provide contemporaneous color gain correction for auto white balance as well as exposure gain adjustment. The offset calibration in various embodiments is done on a per column basis and globally. In addition, the per column offset correction can be applied by using stored values in the on-chip registers, and a ten-bit redundant signed digit analog-to-digital converter converts the analog data to a ten-bit digital word stream. In various embodiments of the KAC-0311 image sensor, the differential analog signal processing pipeline is used to improve noise immunity, the signal to noise ratio, and the system's dynamic range. In one embodiment, the serial interface of the KAC-0311 is an industry standard two line I²C compatible serial interface. In another embodiment, power for the KAC-0311 image sensor is provided by a single 3.3V power

supply. In various embodiments, the KAC-0311 image sensor has a single master clock and operates at speeds up to 20 MHz.

The operational and physical details of image sensors that can be used in the present invention and that are assigned to Eastman Kodak Company are also described in the U.S. Pat. No. 6,714,239 entitled "Active Pixel Sensor with Programmable Color Balance" and U.S. Pat. No. 6,552,323 entitled "Image Sensor with Shared Output Signal Line," each of which is hereby herein incorporated by reference in its entirety. The following provides a brief summary of material from U.S. Pat. No. 6,522,323. In particular U.S. Pat. No. 6,552,323 discloses an image sensor comprising a plurality of pixels arranged in a plurality of rows and columns. The image sensor is further disclosed to include a global electronic shutter. Pixels in the same row of the disclosed image sensor share a pixel output node and an output signal line. Further, the disclosure indicates that image signal separation within a row is achieved by having two separate row select signal lines per row, one for every other pixel within a row, and a 1:2 column output signal line de-multiplexing scheme for each pair of columns. A schematic diagram, here reproduced as FIG. 11, shows two adjacent pixels 5. Identifiers used in the schematic include the following: reset transistor with a reset gate (RG), transfer gate (TG), signal transistor (SIG), row select transistor with a row select gate (RSEL), photodetector (PD), and floating diffusion (FD). The operation of the global shutter is described at column 3 lines 25-45 of U.S. Pat. No. 6,552,323 with respect to the embodiment presented in FIG. 11 and timing diagrams, here reproduced as FIG. 12. The disclosure indicates that readout commences by transfer of the integrated signal charge from the photodetectors 30a, 30b to the floating diffusions 10a, 10b in each pixel of the sensor simultaneously. Next, row select 1 (15) is turned on and the signal level of floating diffusion 1 (10a) is sampled and held by the column circuit 20a by pulsing SS1. Row select 1 (15) is then turned off and row select 2 (25) is turned on and the signal level of floating diffusion 2 (10b) is sampled and held by the column circuit 20b by pulsing SS2. The floating diffusions 10a, 10b in the row being read out are then reset by pulsing RG. Next row select 2 (25) is turned off and row select 1 (15) is turned on and the reset level of floating diffusion 1 (10a) is sampled and held by the column circuit 20a by pulsing SRL. Row select 1 (15) is then turned off and row select 2 (25) is turned on and the reset level of floating diffusion 2 (10b) is sampled and held by pulsing SR2. The readout of the sampled and held signals of the column circuits 20a, 20b is then done prior to the same pixel readout scheme commencing in the next row of the image sensor.

In another embodiment, the CMOS image array 182a can be implemented with a KAC-9630 128(H)x98(V) CMOS image sensor. The KAC-9630 is more fully described in a technical specification entitled, "Device Performance Specification—Kodak KAC-9630 CMOS Image Sensor," September 2004, revision 1.1. This document is hereby herein incorporated by reference in its entirety. This document is available from Eastman Kodak (www.kodak.com), for example at <http://www.kodak.com/global/plugins/acrobatien/digital/ccd/products/cmos/KAC-9630LongSpec.pdf>. This technical specification describes the KAC-9630 image sensor as a low power CMOS active pixel image sensor capable of capturing monochrome images at 580 frames per second. In addition the KAC-9630 image sensor is described as including an on-chip eight-bit analog-to-digital converter, fixed pattern noise elimination circuits and a video gain amplifier. The KAC-9630 is further described as having

integrated programmable timing and control circuitry that allows for the adjustment of integration time and frame rate. The read out circuit in the KAC-9630 image sensor is described as capable of supporting a full frame read out on a single eight-bit digital data bus in less than 2 milliseconds. As indicated above, the KAC-9630 image sensor is described as including an integrated electronic shutter.

In another embodiment, the CMOS image array 182a can be implemented with a Micron image sensor such as the Wide VGA MT9V022 image sensor from Micron Technology, Inc., 8000 South Federal Way, Post Office Box 6, Boise, Id. 83707-0006. The MT9V022 image sensor is describe in more detail in the product MT9V099 product flyer available from Micron Technology (www.micron.com), for example at http://download.micron.com/pdf/flyers/mt9v022_Jmi-0350_flyer.pdf. This document is hereby herein incorporated by reference in its entirety.

In some embodiments, the image reader 100 is capable of operating in either a rolling shutter mode or a global electronic shutter mode. In one such embodiment, the rolling shutter mode is used as part of an automatic focusing operation and the global electronic shutter mode is used to collect image data once the proper focus has been determined. The process of determining the proper focus and collecting a subsequent image is described by the process 400 shown in FIG. 13. Actuation module 124 may generate a trigger signal to initiate process 400 in response to e.g., a depressing of a trigger 216 by an operator or in response to an object being moved into a field of view of image reader 100. In operation when a new image is collected by the image reader 100, the image reader 100 illuminates (step 404) a target containing an object, such as a bar code, and enters (step 408) a rolling shutter operational mode in which a plurality of rows in the image reader's image sensor are sequentially exposed. As part of this operation, a frame exposure period can be defined as the time from the beginning of the exposure of the first row of the plurality of rows to the end of the exposure of the last row of the plurality of rows. In one embodiment, an imaging lens 212 of the image reader 100 is controlled to be in one of continuous motion or in stepwise continuous motion (step 414) during at least a portion of the frame exposure period. As shown in the embodiment of FIG. 20, image reader 100 may have a lens driver module 165 controlled by control module 112 or another module for moving imaging lens 212 to change a focus setting of image reader 100. In one such embodiment, the optical system has a plurality of discrete settings. For each discrete setting, lens 212 forms a distinct image on the image sensor for objects located at a particular distance from the image reader 100. In one embodiment, one extreme of the optical system's focusing range corresponds to focusing incident radiation from objects located at infinity. An object is considered to be at "infinity" if its incident light rays are essentially parallel. In one embodiment, another extreme of the optical system's focusing range is the near point of the optical system. The near point of the optical system is the closest distance an object can be brought with respect to the optical system where the optical system is still able to create a distinct image of the object. In another embodiment, the variation of in the focus of the optical system does not cover the entire range of the optical system. For example in one such embodiment, a focus setting of image reader 100 is varied between focus settings that are millimeters apart. In another embodiment, a focus setting of image reader 100 is varied between focus settings that are centimeters apart. Configuring reader 100 to include lens driver module 165 allows a scanner to operate over an extended depth of field.

With further reference to lens driver module **165**, various lens driving technologies and methods can be implemented. U.S. Pat. No. 4,350,418, incorporated by reference herein in its entirety, discloses a lens focus adjustment system including a distance adjusting ring, wherein position adjustment of a lens is achieved by rotation of the adjustment ring. U.S. Pat. No. 4,793,689, also incorporated herein by reference in its entirety, discloses a lens barrel having a hollow rotary ring rotatable about an optical axis that is disposed within a hollow of a hollow fixed cylinder with a bearing interposed there between, a moving cylinder moveable in response to rotation of the rotary ring, and a vibration wave motor disposed between the diametrical directions of the fixed cylinder and the rotary ring. U.S. Pat. No. 5,541,777, also incorporated herein by reference in its entirety, discloses an electromagnetic lens driver having a fixed member including an inside yoke and an outside yoke, an operationally disposed magnet, a moveable member for holding a body to be driven, a coil wound in an axial direction between the outside yoke and the inside yoke and position detector which detects the magnetic field of the operationally disposed magnet to generate a position indicating signal.

The process **400** also includes reading out (step **420**) image data from the plurality of exposed rows. This image data is analyzed (step **424**) by an automatic focusing algorithm, such as the contrast detection method or the phase detection method. Using the row focus image information, the image reader **100** establishes (step **428**) a proper focus setting of lens **212** e.g., by determining a proper focus setting based on collected data and then moving the lens **212** to that setting or by assessing the present row image data to determine whether at the present focus setting, the image reader is acceptably focused. In various embodiments, the analysis of the image data can be performed by the image collection module **108**, the optics module, the control module **112**, or a dedicated auto-focusing module (e.g., an ASIC or FPGA dedicated for purposes of performing focus calculations). With the position of lens **212** properly established, the image reader **100** enters (step **432**) a global electronic shutter operational mode. It will be seen that in certain instances according to process **400**, image reader **100** may cease operation in a rolling shutter and commence operation in a global electronic shutter operational mode prior to reading out image data from each pixel of image sensor array module **182**. In the global electronic shutter operational mode, the image reader **100** collects (step **436**) a full frame of image data that is stored in memory module **116** and subsequently transferred to decode module **150** or autodiscriminating module **152** by control module **112**. According to this embodiment in which row image information is read out and analyzed during a time that the reader imaging lens **112** is controlled to be in motion, automatically focusing the image reader to image the target may be achieved within one frame of data. In various embodiments, the automatic focusing operations can be handled by a dedicated automatic focusing module or the focusing module can be incorporated into other modules such as the image collection module **108** and/or the control module **112**.

With further reference to the steps of process **400**, the step **424** of analyzing row image data to determine focus characteristics is further described with reference to the flow diagram of FIG. **21**, and the histogram plots of FIG. **22a** and FIG. **22b**. At step **2102** image reader **100** may construct a histogram plot of pixel values of the present row of image data read out at step **420**. FIG. **22A** is a histogram plot of pixel values of a row of data corresponding to a bi-tonal image (such as in a bar code symbol on a monochrome

substrate) that is acceptably focused. Histogram plot **2108** represents a high contrast image and includes numerous pixel values at the high end of the grey scale, numerous pixel values at the low end of the grey scale, and few pixel values at the center grey scale range. FIG. **22B** is a histogram plot of pixel values of a row of data corresponding to a poorly focused bi-tonal image. The image data summarized by histogram **2110** is "flatter" lower contrast image data, meaning that it has fewer pixel values at extremes of the grey scale and a larger number of pixel values at a center of the grey scale. Accordingly, it can be seen that a focus level of an image can readily be determined utilizing image contrast information.

At step **2104** image reader **100** assesses the collected histogram data. At step **2104** image reader **100** may either determine an appropriate in-focus setting for lens **212** or else determine whether the histogram data extracted from the present row of image data indicates that the image reader is acceptably focused at the present lens setting or position. Where image reader **100** at step **2104** determines a proper setting for lens **212** based on the collected histogram data, the histogram data may be from the present row or based on a combination of present row data and preceding row data. In a further aspect, position or setting values of lens **212** are recorded so that the histogram information of each row of image data that is read out has associated lens position data indicating a position of lens **212** at the time at which the row information was collected. At step **2104**, a transfer function for determining an in-focus lens setting may utilize row contrast information as summarized in histogram plots, as well as lens position data indicating a position of lens **212** associated with each set of row data.

Referring to further steps of process **400**, image reader **100** at step **414** may control lens **212** to be in either continuous motion or in stepwise continuous motion. When controlled to be in continuous motion, lens **212** moves continuously throughout a time that sequentive rows of pixels of image sensor array module **182** are exposed and read out. When controlled to be in stepwise continuous motion, lens **212** repeatedly moves and stops throughout the time that rows of pixels of sensor module **182** are exposed and read out. In one embodiment of an image reader controlling lens **212** to be in stepwise continuous motion, image reader **100** continuously moves lens between two extreme points, a first, further field position and second, a nearer field position. In another embodiment of an image reader **100**, controlling lens **212** to be in stepwise continuous motion, image reader **100** continuously moves lens **212** between two extreme positions and intermittently stops lens **212** at one or more positions between the extreme positions. A lens **212** controlled to be in stepwise continuous motion can be considered to have motion periods, i.e., the times during which the lens moves, and stop periods, i.e., the times during which the lens is temporarily idle. In one embodiment of the invention, the motion of the lens **212** and a reading out of image data from rows of pixels are coordinated. For example, the lens movement and control of image sensor array module **182** can be coordinated such that an exposure period for one or more rows of image sensor array module **182** occurs during a stop period of lens **212** so that lens **212** is idle during an entire row exposure period. Further, while processing of image data corresponding to pixels exposed during motion phases of lens **212** is useful in certain embodiments, image reader **100** can be configured so that image data corresponding to pixels exposed during motion periods of lens **212** are discarded, e.g., during row analysis step **424**.

Specific embodiments of the process **400** generically described with reference to FIG. **13** are described with reference to the flow diagrams of FIGS. **23** and **24**. In the embodiment of FIG. **23**, image reader **100** at step **424** attempts to determine an in-focus lens setting based on collected row image data collected to that point. If at step **428a**, image reader **100** determines that enough information has been collected to determine an in-focus position of lens **212**, image reader **100** determines an in-focus setting for lens **212** and proceeds to step **428b** to move lens **212** to the determined in-focus position. If sufficient information has not been collected, image reader **100** returns to step **432** to collect additional row information. Image reader **100** may continue to read and process row image data while moving lens **212** at step **428b**, e.g., for purposes of confirming that the determined in-focus position is correct. When lens **212** has been moved to the determined in-focus position, image reader **100** proceeds to step **432** to enter a global electronic shutter operational mode of operation. At the time that image reader **100** enters the global shutter operating mode (step **432**) image reader **100** may halt the motion of lens **212**. The image reader then proceeds to step **436** to collect a full frame of image data, and then to step **438** to transfer image data to one of the dataform decode module **150** or autodiscriminating module **152**.

In the embodiment of process **400** described with reference to FIG. **24**, image reader **100** establishes an in-focus setting of lens **212** by assessing at step **424** present row data (the most recent collected row data) to determine whether the present row data indicates that image reader **100** is presently in-focus. If image reader **100** at step **428d** determines that image reader **100** is presently not in focus, image reader **100** returns to step **420** to collect additional row information. If at step **420** image reader **100** determines that the reader is presently in an in-focus position, image reader **100** proceeds to step **432** to enter a global electronic shutter mode of operation. At the time that image reader **100** enters the global shutter operating mode, (step **432**) image reader **100** may halt the motion of lens **212**. The image reader **100** then proceeds to step **436** to collect a full frame of image data, and then to step **438** to transfer image data to one of the dataform decode module **150** or autodiscriminating module **152**.

It will be understood with reference to process **400** or process **800** that image reader **100** in establishing an “in focus” position may designate a prospective or present position of lens **212** to be “in focus” on the basis of the prospective or present lens position rendering indicia in better focus than other available lens focus positions. Thus, where a lens focus position is not highly focused in a general sense, reader **100** may, nevertheless, designate the position as being “in focus” if it renders indicia more in focus than other available lens position. In one specific embodiment, lens **100** may be “toggled” between a limited number of discrete positions (e.g., two positions) when it is controlled to be in stepwise continuous motion. In such an embodiment, image reader **100** may designate one of the limited number of possible discrete positions to be the “in focus” positions if the lens position renders indicia more in focus than the remaining possible positions. Particularly in the configuration where lens **212** is “toggled” between a limited number of discrete positions, the focus determining steps may be omitted and the image data transferred directly to the decode module **150** or autodiscrimination module **152**. Particularly when there are a limited number of alternate focus positions, the in-focus position can readily be discriminated based on which position the results in a success-

ful decode. Discriminating an in-focus position by way of decode attempts may reduce average decode time.

In a variation of the invention, image reader **100** at step **420** reads out a predetermined number of rows of image data and analyzes the predetermined number of rows at step **424**. The predetermined number of rows may be e.g., 2 rows, 3 rows, 10 rows or all of the rows (100+) rows of image sensor array **182**. Image reader **100** at step **424** may select the best focused (e.g., highest contrast) row out of the plurality of rows and determine that the recorded focus setting associated with the best focused row is the “in-focus” setting of image reader **100**. Alternatively, image reader **100** may calculate—in-focus setting data utilizing data image collected over several rows. When a focus setting has been determined, in any one of the above variations, image reader **100** may first enter global electronic shutter operational mode at step **432**, and then move lens **212** into the determined focus position setting or else image reader **100** may alternatively move lens **212** to the determined lens setting prior to entering the global electronic shutter operational mode at step **432** or these two operations may occur at the same time.

In another embodiment of the automatic focusing operation, as described later in connection with FIGS. **25-30B**, the global electronic shutter operational mode may be used during both the focusing period and the data collection period. According to process **800** as described herein, during the autofocus period a limited, “windowed” frame of image data may be collected for each variation in the focus setting or position. For example, only the central region, or a central group of scan lines—such as the middle ten scan lines, of the image sensor is read out and analyzed by the focus determination algorithm. According to this embodiment, the limited frame of data provides adequate information for the focus determination algorithm while significantly decreasing the time required to collect the series of frames required to focus the image reader.

In alternative embodiments, the specific order of the steps in the process **400** or process **800** can be altered without departing from the inventive concepts contained therein. In various other embodiments, the circuitry implementing the rolling shutter operation and the circuitry implementing the global electronic shutter operation can be implemented on the same CMOS chip or one or both of the circuitry components can be implemented on separate dedicated chips. In an additional embodiment, the rolling shutter functionality and the global electronic shutter operation can be combined in a single module that includes hardware, software, and/or firmware.

In another embodiment of the image reader **100** that operates in either a rolling shutter or a global electronic shutter mode, the image reader **100** is able to dynamically shift between the global electronic shutter operational mode and the rolling shutter operational mode. In one such embodiment, the image reader **100** shifts from the default global electronic shutter operational mode to the rolling shutter operational mode when the integration time is shorter than a given threshold. Many commercially available imagers are implemented with light shields that allow some amount of light leakage into the storage element or with electronic switches that do not completely isolate the storage element from the photosensitive element. As a result of this, the contents of the storage element can be adversely influenced by the ambient illumination incident upon the imager after the charge has been transferred to the storage element. The following provides a numeric example of such operation.

In general, the shutter efficiency of a CMOS image sensor with global electronic shutter capabilities specifies the extent to which the storage area on the image sensor is able to shield stored image data. For example, if a shutter has an efficiency of 99.9%, then it takes an integration time (also known as exposure time) that is 1,000 times longer to generate the same amount of charge in the shielded portion as in the unshielded portion of the image sensor. Therefore, in an image capture cycle, the following equation provides an indication of the light irradiance on the imager from the ambient light that can be tolerated during the time period after the image is shifted into the storage region relative to the light irradiance on the imager from the object illuminated with the ambient illumination and the light sources **160** during the time period before the image is shifted into the storage region while not exceeding a desired degradation percentage. The equation can also address the case where the light incident upon the imager is the same during the entire imaging cycle. In both instances, one needs to know the minimum integration that can be used without the introduction of a maximum degradation.

$$(Amb.Irrad)*Tframe*(100\%-eff)=(Amb.Irrad+Light\ Source\ Irrad)*Texposure*(\% \ deg)$$

In many instances the light on the imager is unchanged during the exposure period and during the remainder of the frame. In this situation the light irradiance on the imager is constant, and it is possible to solve for the minimum integration time that can be used without the light leakage excessively perturbing the desired image. Solving the equation in this case, allows the calculation of the minimum integration period for a specific degradation. The following constant irradiance numeric example is for a shutter efficiency of 99.9%, a frame rate of 20 ms, and a maximum tolerated degradation of 5%.

$$20\ ms*(100\%-99.9\%)=(Texposure*5\%)$$

or solving for the minimum exposure time that can be used without incurring a degradation of more than 5%:

$$Texposure=0.4\ ms.$$

Thus if the integration time during image capture is shorter than 0.4 ms, then the degradation leakage (both optical or electrical) will cause an error to be introduced of 5% or greater.

In one embodiment that addresses image degradation introduced by excessive ambient light, the image reader **100** shifts to rolling shutter operation when the integration time becomes shorter than a level determined with respect to the frame rate, maximum allowable degradation and shutter efficiency of the image reader. A process **600** for shifting operational modes in response to short integration times is shown in FIG. **14**. Actuation module **124** may generate a trigger signal to initiate process **600** in response to e.g., a depressing of a trigger **216** by operator or in response to an object being provided into a field of view of image reader **100**. The process **600** includes storing (step **604**) a calculated minimum integration time. In one embodiment, this threshold is determined in accordance with the equations presented above. Some of the inputs to these equations, such as the shutter efficiency, maximum acceptable image degradation leakage, and frame rate, can be configured in the image reader **100** as part of its initial setup or at a later time. The process **600** also includes collecting (step **608**) image data. As part of the collection of image data, an exposure time for the current environmental conditions is established (step **612**) by the sensor array control module **186**. In various

embodiments, this exposure time is established by the global electronic shutter control module **190**, the optics module **178**, or another appropriate module in the image reader **100**. To determine whether the operational mode of the image reader **100** should shift from global shutter to rolling shutter, the established exposure time is compared (step **616**) with the minimum integration time threshold. If the established integration time is shorter than the calculated minimum integration time threshold, then the operational mode of the image reader **100** is shifted (step **620**) from global electronic shutter to rolling shutter. If the established integration time is greater than or equal to the calculated minimum integration time threshold, then the global electronic shutter operational mode (step **628**) is maintained.

Further embodiments of the invention are described with reference to FIG. **15A**, and the flow diagrams of FIGS. **31** and **32**. As shown in FIG. **15A**, image reader **100** can be configured to have user selectable configuration settings. For example, as shown in FIG. **15A**, image reader **100** may present on display **504** a graphical user interface (GUI) menu option display screen **3170** which presents to an operator the user selectable configuration options of a rolling shutter operational mode and a global shutter operational mode. GUI display screens may be configured with tool kits associated with certain available operating systems such as WINDOWS CE, which may be installed on image reader **100**. When reader **100** is configured to include a browser or is otherwise configured with suitable parsers and interpreters, GUI **3170** can be created using various open standard languages (e.g., HTML/JAVA, XML/JAVA). In the embodiment of FIG. **15A**, GUI icon **3152** is a rolling shutter selection button and GUI icon **3154** is a global electronic shutter menu option. When icon **3152** is selected, image reader **100** is configured so that when image reader **100** receives a next trigger signal as described herein to initiate a decode attempt, image reader **100** collects image data utilizing a rolling shutter operating mode without utilizing the global electronic operational mode. When icon **3154** is selected, image reader **100** is configured so that when image reader **100** receives a next trigger signal to initiate a decode attempt, image reader **100** collects image data utilizing the global electronic shutter operational mode without utilizing the rolling shutter operational mode. GUI **3170** can be created to permit additional user selectable configuration options. In the embodiment of FIG. **15A**, selection of button **3156** (which may be in text or icon form) configures image reader **100** so that process **300** is executed the next time a trigger signal is received. Selection of button **3158** configures image reader **100** so that process **400** is executed a next time a trigger signal is received. Selection of button **3160** configures image reader **100** so that process **600** is executed a next time a trigger signal is received. Selection of button **3162** configures image reader **100** so that process **800** is executed a next time a trigger signal is received. Selection of button **3164** configures image reader **100** so that image reader **100** is in "image capture" mode of operation such that a next time a trigger signal is received, image reader collects image data such as a 2D full frame of image data and outputs an image (e.g., to display **504** or a spaced apart device) without transferring the collected image data to module **150** or module **152**. In shipping applications, it may be beneficial to capture images in an "image capture" mode corresponding to moving objects (e.g., a moving delivery vehicle, a package on an assembly line). Accordingly, it will be seen that execution of an image capture mode utilizing a global shutter operational mode of operation yields significant advantages, in that image distortion is reduced using a global

shutter operational mode. The selection between a rolling shutter configuration and a global electronic shutter configuration or the configurations associated with buttons 3156, 3158, 3160, 3162, and 3164 can also be made with use of commands of a software development kit (SDK). A system can be created so that SDK-created commands (e.g., a “ROLLING SHUTTER” and a “GLOBAL SHUTTER” command) causing image reader 100 to be in one of a rolling shutter configuration and a global electronic shutter configuration can be selected at a host terminal spaced apart from image reader 100 and transmitted to image reader 100 to reconfigure reader 100.

Referring to the flow diagram of FIG. 31, an operator selects between a rolling shutter configuration and a global electronic shutter configuration at step 3102. If an operator selects the rolling shutter configuration, image reader 100 proceeds to step 3104. At step 3104 image reader 100 is driven from an idle state to an active reading state by the generation of a trigger signal (e.g., by manual actuation of trigger 216 or another method) and then automatically executes steps 3106 and 3108. At step 3106 image reader 100 collects image data utilizing a rolling shutter operational mode and at step 3108 the image data collected at step 3106 is transferred to dataform decode module 150 or autodiscrimination module 152 to decode or otherwise process the image data. If at step 3102 a global electronic shutter mode is selected, image reader 100 proceeds to step 3118. At step 3118 image reader 100 is driven from an idle state to an active reading state by the generation of a trigger signal (e.g., by manual actuation of trigger 216 or another method) and then automatically executes steps 3118 and 3120. At step 3118 image reader 100 collects image data utilizing a global electronic shutter operational mode and at step 3122 the image data collected at step 3118 is transferred to dataform decode module 150 or autodiscrimination module 152 to decode or otherwise process the image data.

Another embodiment of the invention is described with reference to the flow diagram of FIG. 32. In the embodiment described with reference to the flow diagram of FIG. 32, image reader 100 is configured to collect image data and attempt to decode image data utilizing a rolling shutter operational mode and a global shutter operational mode. At step 3202 a trigger signal is generated as described herein (e.g., by manual actuation of trigger 216 or another method) to drive image reader 100 from an idle state to an active reading state and all of steps 3204, 3206 may be automatically executed thereafter. At step 3204 image reader 100 enters a rolling shutter operational mode. At step 3206 image reader 100 collects image data such as a full frame of image data or a windowed frame of image data utilizing the rolling shutter operational mode. At step 3208 image reader 100 transfers the image data collected at step 3206 to dataform decode module 150 and/or autodiscrimination module 152. Dataform decode module 150 or autodiscrimination module 152 may decode or otherwise process the image data collected and output a result (e.g., output a decoded bar code message to display 504 and/or a spaced apart device). At step 3118 image reader 100 enters a global electronic shutter operational mode. At step 3212 image reader 100 collects image data utilizing the global electronic shutter operational mode. The image data collected at step 3212 may be full frame or a windowed frame image data. At step 3214 image reader 100 transfers the image data collected at step 3212 to dataform decode module 150 or autodiscrimination module 152. Dataform decode module 150 or autodiscrimination module 152 may decode or otherwise process the image data collected and output a result (e.g., output a decoded bar code

message to display 540 and/or a spaced apart device). As indicated by control loop arrow 3216, image reader 100 may automatically repeat steps 3204, 3206, 3208, 3210, 3212, and 3214 until a stop condition is satisfied. A stop condition may be e.g., the generation of a trigger stop signal (as may be generated by the release of trigger 216) or the successful decoding a predetermined number of bar code symbols.

Another process according to the invention is described with reference to the flow diagram of FIG. 25. Process 800 is similar to process 400 in that it involves the processing of a limited amount of image data collected during a time that lens 212 is controlled to be in motion. With process 400 and with process 800 an in-focus position of lens 212 is quickly established. Whereas process 400 involves utilization of an image sensor array module 182 operated, at different times during the course of the process, in a first rolling shutter operational mode and a second, subsequently executed global electronic operational mode, process 800 may be implemented with use of one of the selectively addressable image sensor array modules described herein operated throughout the process in either one of a rolling shutter mode of operation or in a global electronic mode of operation.

With further reference to process 800, actuation module 124 at step 802 initiates process 800 by generating a trigger signal, e.g., in response to a depression of a trigger 216, a sensing of an object in a field of view of image reader or receipt of a command from a spaced apart device. At step 814 image reader 100 sets lens 212 into motion. At step 814 image reader 100 may control lens 212 to be in one of continuous motion or stepwise continuous motion.

At step 820 image reader 100 reads out a “windowed frame” of image data from image sensor array module 182. CMOS image sensors can be operated in a windowed frame operating mode. In a windowed frame operating mode, image data corresponding to only a selectively addressed subset of all pixels of an image sensor array is read out. Examples of image reader 100 operating in windowed frame operating modes are described with reference to FIGS. 28A, 28B and 28C, wherein image sensor arrays are represented with each square of the grid representing a 10×10 block of pixels, and wherein shaded regions 2802, 2804, and 2806 represent pixels that are selectively addressed and selectively subjected to readout. In the embodiment of FIG. 28A, a windowed frame operating mode is illustrated wherein windowed image data is read out of image sensor array 182 by selectively addressing and reading out only centerline pattern of pixels consisting of a set of rows of pixels at a center of image sensor array module 182. Alternatively, in a windowed frame operating mode image reader 100 may selectively address and selectively read out image data from a single row of pixels of image sensor array module 182. Further, in a windowed frame operating mode, image reader 100 may selectively address, and selectively read out image data from rows 2802a and 2802b. In the embodiment of FIG. 28B, a windowed frame operating mode is illustrated wherein windowed image data is read out of image sensor array module 182 by selectively addressing and reading out only a collection of positionally contiguous pixels (i.e., a collection of pixels that are adjacent to one another) at a center of image sensor array module 182. In the embodiment of FIG. 28C, a windowed frame operating mode is illustrated wherein windowed image data is read out of image sensor array module 182 by selectively reading out spaced apart clusters of 10×10 blocks of positionally contiguous pixels. In all of the windowed frame operating modes described with reference to FIGS. 28A, 28B and 28C, image data corresponding to less than half of the pixels of the

image sensor is selectively addressed and read out. When operating in a windowed frame operating mode image reader **100** may collect image data corresponding to light incident on pixels in one or more of the patterns illustrated in FIG. **28A**, **28B** or **28C** or another pattern. Such collections of image data may include a collection of gray scale values and may be termed windowed frames of image data.

A windowed frame operating mode described herein is contrasted with an alternative operating mode in which a full frame of image data is stored into memory module **116**, and then a portion of that full frame of image data is designated as a region of interest (i.e., a “sample” region) which is subject to further processing. In a windowed frame operating mode a frame of image data may be collected in a fraction of the time required to collect a full frame of image data.

With further reference to process **800** image reader **100** at step **824** analyzes a windowed frame of image data to determine focus characteristics of image reader **100**. The step of analyzing windowed frame image data to determine focus characteristics is further described with reference to the flow diagram of FIG. **29**, and the histogram plots of FIG. **30A** and FIG. **30B**. At step **4102** image reader **100** may construct a histogram plot of pixel values of the present windowed frame of image data read out at step **820**. FIG. **30A** is a histogram plot of pixel values of a row of data corresponding to a bi-tonal image (such as in a bar code symbol on a monochrome substrate) that is acceptably focused. Histogram plot **4108** represents a high contrast image and includes numerous pixel values at the high end of the grey scale, numerous pixel values at the low end of the grey scale, and few pixel values at the center grey scale range. FIG. **30B** is a histogram plot of pixel values of a windowed frame of image data corresponding to a poorly focused bi-tonal image. The image data summarized by histogram **4110** is “flatter,” lower contrast image meaning that it has fewer pixel values at extremes of the grey scale and a larger number of pixel values at a center of the grey scale. Accordingly, it can be seen that a focus level of an image can readily be determined utilizing image contrast information.

At step **4104**, image reader **100** assesses the collected histogram data. At block **4104** image reader **100** may either determine an appropriate in-focus setting for lens **212** or else determine whether the histogram data extracted from the present row of image data indicates that the image reader **100** is acceptably focused at the present lens position. Where image reader **100** at step **4104** determines a proper setting for lens **212** based on the collected histogram data, the histogram data may be from the present windowed frame of image data or based on a combination of present windowed frame of image data and preceding data of previously collected one or more frames of windowed image data. In a further aspect, position or setting values of lens **212** are recorded so that the histogram information of each row of image data that is read out and analyzed has associated lens position data indicating a position of lens **212** at the time at which the windowed frame of image data information was collected. At step **4104** a transfer function for determining an in-focus lens setting may utilize windowed frame contrast information as summarized in histogram plots, as well as lens position data indicating a position of lens **212** associated with each collected windowed frame of image data.

Referring to further steps of process **800**, image reader **100** at step **814** may control lens **212** to be in either continuous motion or in stepwise continuous motion. When controlled to be in continuous motion, lens **212** moves continuously throughout a time that pixels corresponding to

a windowed frame of image data are exposed and read out. When controlled to be in stepwise continuous motion, lens **212** repeatedly moves and stops throughout the time that pixels corresponding to a windowed frame of image data are exposed and read out. In one embodiment of an image reader **100** controlling lens **212** to be in stepwise continuous motion, image reader **100** continuously moves lens between two extreme points, a first further-field position and second, a nearer-field position. In another embodiment of an image reader **100** controlling lens **212** to be in stepwise continuous motion, image reader **100** continuously moves lens **212** between two extreme positions and intermittently stops lens **212** at one or more positions between the extreme positions. A lens **212** controlled to be stepwise continuous motion can be considered to have motion periods, i.e., the times during which the lens moves, and stop periods corresponding to the time the lens is temporarily idle. In one embodiment of the invention, the motion of the lens **212** and a reading out of image data from rows of pixels are coordinated. For example, the stepwise movement of lens **212** and control of image sensor array module **182** can be coordinated such that a stop period of a lens in stepwise continuous motion occurs during an exposure period for exposing pixels corresponding to a windowed frame of image data and motion periods occur before and after such an exposure period. Further, while processing of image data corresponding to pixels exposed during motion periods of lens **212** is useful in certain embodiments, image reader **100** can be configured so that image data corresponding to pixels exposed during motion periods of lens **212** are discarded, e.g., during analysis step **824**.

Specific embodiments of the process **800** generically described with reference to FIG. **25** are described with reference to the flow diagrams of FIGS. **26** and **27**. In the embodiment of FIG. **26**, image reader **100** at step **824** attempts to determine an in-focus setting based on collected windowed frame image data collected to that point. If at block **828a** image reader **100** determines that enough information has been collected to determine an in-focus position of image reader **100**, image reader **100** proceeds to step **828b** to move the lens to the determined in-focus position. If sufficient information has not been collected, image reader returns to step **820** to collect additional windowed frame information. Image reader **100** may continue to read and process windowed frame image data while moving lens **212** at step **828b**, e.g., for purposes of confirming that the determined in-focus position is correct. When lens **212** has been moved to the determined in-focus position image reader **100** proceeds to step **836** to collect a full frame of image data (e.g., in accordance with process **300**), and then proceeds to step **838** to transfer the collected image data to one of dataform decode module **150** or autodiscriminating module **152**.

In the embodiment of process **800** described with reference to FIG. **27**, image reader **100** establishes an in-focus setting of lens **212** by assessing at step **824** present windowed frame image data (the most recent collected windowed frame data) to determine whether the present windowed frame image data indicates that image reader **100** is presently in-focus. If image reader **100** at step **828c** determines that image reader **100** is presently not in focus, image reader **100** returns to step **820** to collect additional windowed frame information. If at step **828** image reader **100** determines that the reader is presently in an in-focus position, image reader **100** proceeds to step **836** to collect a full frame of image data, (e.g., in accordance with process **300**),

and then proceeds to step **838** to transfer the collected image data to one of dataform decode module **150** or autodiscriminating module **152**.

In a variation of the invention, image reader **100** at step **820** may read out a predetermined number of windowed frames of image data, and at step **824** may analyze a predetermined number of windowed frames of image data. The windowed frames of image data may have the same pattern (e.g., always the pattern of FIG. **28A**) or may have alternating patterns (e.g., first the pattern of FIG. **28A**, next the pattern of FIG. **28B**, and next the pattern of FIG. **28C**). In another variation, image reader **100** may transfer each collected windowed frame of image data, subsequent to collection, to dataform decode module **150** and/or autodiscrimination module **152**. At step **824**, image reader **100** analyzes the predetermined number of frames of image data in order to determine an in-focus setting of image reader **100**. In determining an in-focus setting, image reader **100** may select the in-focus setting associated with the best focused (highest contrast) windowed frame of image data out of the plurality of windowed frames of image data or else image reader **100** may calculate a focus setting utilizing image data from the plurality of windowed frames collected. In any of the variations of process **800**, image reader **100** may collect a full frame of image data at step **836** after determining an in-focus setting of image reader **100** before or after moving lens **212** to the determined setting position to establish an in-focus setting.

It will be understood with reference to process **400** and process **800** that image reader **828** in establishing an “in focus” position may designate a prospective or present position of lens **212** to be “in focus” on the basis of the prospective or present lens position rendering target indicia in better focus than other available lens focus positions. Thus, where a lens focus position is not highly focused in a general sense reader **100** may, nevertheless, designate the position as being “in focus” if it renders target indicia more in focus than other available lens position. In one specific embodiment, lens **212** may be “toggled” between a limited number of discrete positions (e.g., two positions) when it is controlled to be in stepwise continuous motion. In such an embodiment, image reader **100** may designate one of the limited number of possible discrete positions to be the “in-focus” position if the lens position renders target indicia more in focus than the remaining possible positions. Particularly in the configuration where lens **212** is “toggled” between a limited number of discrete positions, the focus determining steps may be omitted and the image data transferred directly to the decode module **150** or autodiscrimination module **152**. Particularly when there are a limited number of alternate focus positions, the in-focus position can readily be discriminated based on which position the results in a successful decode. Discriminating an in-focus position by way of decode attempts may reduce average decode time.

It is recognized that some available image sensor arrays have configurations or operation modes in which a limited number of edge columns/and or rows are not read out because of packaging concerns (e.g., edge pixels are covered by packaging material of the chip) or because of a configuration to a particular aspect ratio. Where image data from an image sensor is read out from all of the pixels of the image sensor or substantially all the pixels excluding a limited number of row and/or column edge pixels, such image data collecting is regarded herein as a collecting of a full frame of image data.

With reference to process **400** and process **800**, it has been described that lens **212** can be controlled to be in one of continuous motion or stepwise continuous motion. It will be seen that when lens **212** is controlled to be in continuous motion, a focus setting of image reader **100** is controlled to vary over time. When lens **212** is controlled to be in stepwise continuous motion, a focus setting of lens **212** and, therefore, of image reader **100** is controlled to vary stepwise over time. Further, when lens **212** in accordance with process **400** or process **800** is in a motion period while being controlled to be in stepwise continuous motion, a focus setting of lens **212** is in a varying state. During a stop period of lens **212** while lens **212** is being controlled to be in stepwise continuous motion, a focus setting of image reader **100** is in a temporarily idle state.

Referring again to FIG. **1A**, the following description provides additional details on modules in the image reader **100** presented above. In various embodiments, the control module **112** can include a central processing unit including on-chip fast accessible memory, application specific integrated circuits (ASICs) for performing specialized operations, as well as software, firmware and digitally encoded logic. The memory module **116** can comprise any one or more of read-only (ROM), random access (RAM) and non-volatile programmable memory for data storage. The ROM-based memory can be used to accommodate security data and image reader operating system instructions and code for other modules. The RAM-based memory can be used to facilitate temporary data storage during image reader operation. Non-volatile programmable memory may take various forms, erasable programmable ROM (EPROM) and electrically erasable programmable ROM (EEPROM) being typical. In some embodiments, non-volatile memory is used to ensure that the data is retained when the image reader **100** is in its quiescent or power-saving “sleep” state.

The I/O module **120** is used to establish potentially bi-directional communications between the image reader **100** and other electronic devices. Examples of elements that can comprise a portion of the I/O module **120** include a wireless or wired Ethernet interface, a dial-up or cable modem interface, a USB interface, a PCMCIA interface, a RS232 interface, an IBM Tailgate Interface RS485 interface, a PS/2 keyboard/mouse port, a specialized audio and/or video interface, a CompactFlash interface, a PC Card Standard interface, a Secure Digital standard for memory, a Secure Digital Input Output for input/output devices and/or any other standard or proprietary device interface. A CompactFlash interface is an interface designed in accordance with the CompactFlash standard as described in the CompactFlash Specification version 2.0 maintained at the website <http://www.compactflash.org>. The CompactFlash Specification version 2.0 document is herein incorporated by reference in its entirety. A PC Card Standard interface is an interface designed in accordance with the PC Card Standard as described by, for example, the PC Card Standard 8.0 Release—April 2001 maintained by the Personal Computer Memory Card International Association (PCMCIA) and available through the website at <http://www.pcmcia.org>. The PC Card Standard 8.0 Release—April 2001 Specification version 2.0 document is hereby herein incorporated by reference in its entirety.

The actuation module **124** is used to initiate the operation of various aspects of the image reader **100** such as data collection and processing in accordance with process **300**, process **400**, process **600** or process **800** as described herein. All of the steps of process **300**, process **400**, process **600** and process **800** may be automatically executed in response to an

initiation of the respective process by actuation module **124**. Image reader **100** may be configured so that the steps of process **300**, process **400**, process **600**, and process **800** continue automatically when initiated until a stop condition is satisfied. A stop condition may be e.g., the generation of a trigger stop signal (as may be generated by the release of trigger **216**) or the successful decoding a predetermined number of bar code symbols. In the hand held image reader **100a** discussed above, the actuation module comprises the trigger **216** which, when depressed, generates a trigger signal received by control module **112** which, in turn, sends control signals to appropriate other modules of image reader **100**. In one embodiment of a fixed mounted embodiment of the image reader **100**, the actuation module **124** comprises an object sensing module that generates a trigger signal to initiate the operation of the image reader **100** when the presence of an object to be imaged is detected. When a trigger signal is generated, image reader **100** is driven from an idle state to an active reading state. Actuation module **124** may also generate a trigger signal in response to receipt of a command from a local or remote spaced apart device.

The user feedback module **128** is used to provide sensory feedback to an operator. In various embodiments, the feedback can include an auditory signal such as a beep alert, a visual display such as an LED flashing indicator, a mechanical sensation such as vibration in the image reader **100**, or any other sensory feedback capable of indicating to an operator the status of operation of the image reader **100** such as a successful image capture.

The display module **132** is used to provide visual information to an operator such as the operational status of the image reader **100** including, for example, a remaining battery and/or memory capacity, a mode of operation, and/or other operational or functional details. In various embodiments, the display module **132** can be provided by a LCD flat panel display with an optional touch-pad screen overlay for receiving operator tactile input coordinated with the display.

The user interface module **134** is used to provide an interface mechanism for communication between an operator and the image reader **100**. In various embodiments, the user interface module **134** comprises a keypad, function specific or programmable buttons, a joystick or toggle switch and the like. If the display module **132** includes a touch-pad screen overlay as mentioned above, the display module can incorporate some of the input functionality alternatively provided by elements in the user interface module **134**.

In some embodiments, the RFID module **136** is an ISO/IEC 14443 compliant RFID interrogator and reader that can interrogate a RFID contactless device and that can recover the response that a RFID tag emits. The International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC) are bodies that define the specialized system for worldwide standardization. In other embodiments, the RFID module **136** operates in accordance with ISO/IEC 10536 or ISO/IEC 15963. Contactless Card Standards promulgated by ISO/IEC cover a variety of types as embodied in ISO/IEC 10536 (Close coupled cards), ISO/IEC 14443 (Proximity cards), and ISO/IEC 15693 (Vicinity cards). These are intended for operation when very near, nearby and at a longer distance from associated coupling devices, respectively. In some embodiments, the RFID module **136** is configured to read tags that comprise information recorded in accordance with the Electronic Product Code (EPC), a code format proposed by the Auto-ID Center at MIT. In some embodiments, the RFID module **136**

operates according to a proprietary protocol. In some embodiments, the RFID module **136** communicates at least a portion of the information received from an interrogated RFID tag to a computer processor that uses the information to access or retrieve data stored on a server accessible via the Internet. In some embodiments, the information is a serial number of the RFID tag or of the object associated with the RFID tag.

In some embodiments, the smart card module **140** is an ISO/IEC 7816 compliant smart card reader with electrical contact for establishing communication with a suitably designed contact chip based smart card. The smart card module **140** is able to read and in some cases write data to attached smart cards.

In some embodiments, the magnetic stripe card module **144** is a magnetic stripe reader capable of reading objects such as cards carrying information encoded in magnetic format on one or more tracks, for example, the tracks used on credit cards. In other embodiments, the magnetic stripe card module **144** is a magnetic character reading device, for reading characters printed using magnetic ink, such as is found on bank checks to indicate an American Bankers Association routing number, an account number, a check sequence number, and a draft amount. In some embodiments, both types of magnetic reading devices are provided.

In some embodiments of the image reader **100**, the functionality of the RFID module **136**, the smart card module **140**, and the magnetic stripe card module **144** are combined in a single tribrid reader module such as the Panasonic's Integrated Smart Card Reader model number ZU-9A36CF4 available from the Matsushita Electrical Industrial Company, Ltd. The ZU-9A36CF4 is described in more detail in the Panasonic Specification number MIS-DG60C194 entitled, "Manual Insertion Type Integrated Smart Reader" dated March 2004 (revision 1.00). This document is hereby herein incorporated by reference in its entirety.

The decoder module **150** is used to decode target data such as one and two-dimensional bar codes such as UPC/EAN, Code 11, Code 39, Code 128, Codabar, Interleaved 2 of 5, MSI, PDF417, MicroPDF417, Code 16K, Code 49, MaxiCode, Aztec, Aztec Mesa, Data Matrix, Qcode, QR Code, UCC Composite, Snowflake, Vericode, Dataglyphs, RSS, BC 412, Code 93, Codablock, Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code, OCR A, OCR B, and the like. In some embodiments, the decoder module also includes autodiscrimination functionality that allows it to automatically discriminate between a plurality of bar code such as those listed above. Certain functionality of the decoder **150**, such as the measurement of characteristics of decodable indicia, is described in the related U.S. application Ser. No. 10/982,393, filed Nov. 5, 2004, entitled "Device and System for Verifying Quality of Bar Codes." This application is hereby herein incorporated by reference in its entirety.

Another example of an image reader **100** constructed in accordance with the principles of the invention is the portable data terminal **100b** shown in different perspective drawings in FIGS. **15A**, **15B**, and **15C**. FIG. **15A** shows a top perspective, FIG. **15B** shows a front perspective view, and FIG. **15C** shows a back perspective view. As shown, the portable data terminal **100b** in one embodiment includes interface elements including a display **504**, a keyboard **508**, interface buttons **512** for example for positioning a cursor, a trigger **216**, and a stylus **520** with a stylus holder **524** (not shown). The portable data terminal **100b** further includes a lens **212b** and light sources **160b**. In additional embodi-

ments, the portable data terminal can have its functionality enhanced with the addition of multiple detachable computer peripherals. In various embodiments, the computer peripherals can include one or more of a magnetic stripe reader, a biometric reader such as a finger print scanner, a printer such as a receipt printer, a RFID tag or RF payment reader, a smart card reader, and the like. In various embodiments, the portable data terminal **100b** can be a Dolphin 7200, 7300, 7400, 7900, or 9500 Series Mobile Computer available from Hand Held Products, Inc., of 700 Visions Drive, P.O. Box 208, Skaneateles Falls, N.Y. and constructed in accordance with the invention. Various details of a hand held computer device, in particular the device's housing, are described in more detail in the related U.S. application Ser. No. 10/938, 416, filed Sep. 10, 2004, entitled "Hand Held Computer Device." This application is hereby incorporated by reference in its entirety.

The portable data terminal **100b** further includes an electro-mechanical interface **532** such as a dial-up or cable modem interface, a USB interface, a PCMCIA interface, an Ethernet interface, a RS232 interface, an IBM Tailgate Interface RS485 interface, a CompactFlash interface, a PC Card Standard interface, a Secure Digital standard for memory interface, a Secure Digital Input Output for input/output devices interface and/or any other appropriate standard or proprietary device interface. In various embodiments, the electro-mechanical interface **532** can be used as part of attaching computer peripherals.

An electrical block diagram of one embodiment of the portable data terminal **100b** is shown in FIG. **16**. In the embodiment of FIG. **16**, an image collection module **108b** includes an image engine including two-dimensional image sensor **536** provided on image sensor chip **546** and associated imaging optics **544**. The associated imaging optics **544** includes the lens **212b** (not shown). Image sensor chip **546** may be provided in an IT4000 or IT4200 image engine of the type available from Hand Held Products, Inc. of Skaneateles Falls, N.Y. constructed in accordance with the invention and may be a suitable commercially available chip such as the Kodak KAC-0311 or the Micron MT9V022 image sensor array described above. The portable data terminal **100b** also includes an illumination module **104b** including the light sources **160b** and an illumination control module **164b**. These illumination modules are also an integral part of the IT4000 and IT4200 image engines referenced above. The portable data terminal **100b** further includes a processor integrated circuit (IC) chip **548** such as may be provided by, for example, an INTEL Strong ARM RISC processor or an INTEL PXA255 Processor. Processor IC chip **548** includes a central processing unit (CPU) **552**. For capturing images, the processor IC chip **548** sends appropriate control and timing signals to image sensor chip **546**, as described above. The processor IC chip **548** further manages the transfer of image data generated by the chip **546** into RAM **576**. Processor IC chip **548** may be configured to partially or entirely carry out the functions of one or more of the modules, e.g., modules **104**, **108**, **112**, **116**, **120**, **124**, **128**, **132**, **134**, **136**, **140**, **144**, **150**, **152**, **165**, **168** as described in connection with FIG. **1A**.

As indicated above, the portable data terminal **100b** may include a display **504**, such as a liquid crystal display, a keyboard **508**, a plurality of communication or radio transceivers such as a 802.11 radio communication link **556**, a Global System for Mobile Communications/General Packet Radio Service (GSM/GPRS) radio communication link **560**, and/or a Bluetooth radio communication link **564**. In additional embodiments, the portable data terminal **100b** may

also have the capacity to transmit information such as voice or data communications via Code Division Multiple Access (CDMA), Cellular Digital Packet Data (CDPD), Mobitex cellular phone and data networks and network components. In other embodiments, the portable data terminal **100b** can transmit information using a DataTAC™ network or a wireless dial-up connection.

The portable data terminal **100b** may further include an infrared (IR) communication link **568**. The keyboard **508** may communicate with IC chip **548** via microcontroller chip **572**. The portable data terminal **110b** may further include RFID circuitry **578** as described above for reading or writing data to a RFID tag or token and smart card circuitry **586** including electrical contacts **590** for establishing electrical communication with a smart card such as a circuitry enabled credit card. The portable data terminal **100b** further includes a memory **574** including a volatile memory and a non-volatile memory. The volatile memory in one embodiment is provided in part by the RAM **576**. The non-volatile memory may be provided in part by flash ROM **580**. Processor IC chip **548** is in communication with the RAM **576** and ROM **580** via a system bus **584**. Processor IC chip **548** and microcontroller chip **572** also include areas of volatile and non-volatile memory. In various embodiments where at least some of the modules discussed above, such as the elements in the control module **112**, are implemented at least in part in software, the software components can be stored in the non-volatile memories such as the ROM **580**. In one embodiment, the processor IC chip **548** includes a control circuit that itself employs the CPU **552** and memory **574**. Non-volatile areas of the memory **574** can be used, for example, to store program operating instructions.

In various embodiments, the processor IC chip **548** may include a number of I/O interfaces (not all shown in FIG. **16**) including several serial interfaces (e.g., general purpose, Ethernet, blue tooth), and parallel interfaces (e.g., PCMCIA, Compact Flash).

In one embodiment, the processor IC chip **548** processes frames of image data to, for example, decode a one or two-dimensional bar code or a set of OCR characters. Various bar code and/or OCR decoding algorithms are commercially available, such as by the incorporation of an IT4250 image engine with decoder board, available from Hand Held Products, Inc. In one embodiment, the decoder board decodes symbologies such as UPC/EAN, Code 11, Code 39, Code 128, Codabar, Interleaved 2 of 5, MSI, PDF417, MicroPDF417, Code 16K, Code 49, MaxiCode, Aztec, Aztec Mesa, Data Matrix, Qcode, QR Code, UCC Composite, Snowflake, Vericode, Dataglyphs, RSS, BC 412, Code 93, Codablock, Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code, OCR A, OCR B, and the like.

Among other operations, the infrared transceiver **568** facilitates infrared copying of data from a portable data terminal **100b** in a broadcasting mode to a portable data terminal **100b** in a receiving mode. Utilization of infrared transceiver **568** during a data copying session allows data broadcast from a single broadcast device to be simultaneously received by several receiving devices without any of the receiving devices being physically connected to the broadcasting device.

In an additional further embodiment, the image reader **100** can be contained in a transaction terminal such as the Transaction Terminal Image Kiosk 8870 available from Hand Held Products, Inc., of 700 Visions Drive, P.O. Box 208, Skaneateles Falls, N.Y. and constructed in accordance with the invention. In a further embodiment, the image

reader **100** can be contained in a fixed mount system such as the IMAGETEAM 3800E linear image engine or the IMAGETEAM 4710 two-dimensional reader available from Hand Held Products, Inc. of 700 Visions Drive, P.O. Box 208, Skaneateles Falls, N.Y.

In various embodiments, the modules discussed above including the illumination module **104**, the image collection module **108**, the control module **112**, the memory module **116**, the I/O module **120**, the actuation module **124**, the user feedback module **128**, the display module **132**, the user interface module **134**, the RFID module **136**, the smart card module **140**, the magnetic stripe card module **144**, the decoder module **150**, the illumination control module **164**, the power module **168**, the interface module **172**, the optics module **178**, the sensor array module **182**, the sensor array control module **186**, the global electronic shutter control module **190**, the row and column address and decode module **194**, and the read out module **198**, the rolling shutter control module **202**, and the auto-focusing module can be implemented in different combinations of software, firm-
ware, and/or hardware.

Machine readable storage media that can be used in the invention include electronic, magnetic and/or optical storage media, such as magnetic floppy disks and hard disks, a DVD drive, a CD drive that in some embodiments can employ DVD disks, any of CD-ROM disks (i.e., read-only optical storage disks), CD-R disks (i.e., write-once, read-many optical storage disks), and CD-RW disks (i.e., rewritable optical storage disks); and electronic storage media, such as RAM, ROM, EPROM, Compact Flash cards, PCMCIA cards, or alternatively SD or SDIO memory; and the electronic components (e.g., floppy disk drive, DVD drive, CD/CD-R/CD-RW drive, or Compact Flash/PCMCIA/SD adapter) that accommodate and read from and/or write to the storage media. As is known to those of skill in the machine-readable storage media arts, new media and formats for data storage are continually being devised, and any convenient, commercially available storage medium and corresponding read/write device that may become available in the future is likely to be appropriate for use, especially if it provides any of a greater storage capacity, a higher access speed, a smaller size, and a lower cost per bit of stored information. Well known older machine-readable media are also available for use under certain conditions, such as punched paper tape or cards, magnetic recording on tape or wire, optical or magnetic reading of printed characters (e.g., OCR and magnetically encoded symbols) and machine-readable symbols such as one and two-dimensional bar codes.

Those of ordinary skill will recognize that many functions of electrical and electronic apparatus can be implemented in hardware (for example, hard-wired logic), in software (for example, logic encoded in a program operating on a general purpose processor), and in firmware (for example, logic encoded in a non-volatile memory that is invoked for operation on a processor as required). The present invention contemplates the substitution of one implementation of hardware, firmware and software for another implementation of the equivalent functionality using a different one of hardware, firmware and software. To the extent that an implementation can be represented mathematically by a transfer function, that is, a specified response is generated at an output terminal for a specific excitation applied to an input terminal of a "black box" exhibiting the transfer function, any implementation of the transfer function, including any combination of hardware, firmware and software implementations of portions or segments of the transfer function, is contemplated herein.

While the present invention has been explained with reference to the structure disclosed herein, it is not confined to the details set forth and this invention is intended to cover any modifications and changes as may come within the scope and spirit of the following claims.

We claim:

1. An apparatus comprising:

a CMOS image sensor having a plurality of pixels in a two-dimensional array, wherein the CMOS image sensor is operable to capture image data in a global shutter mode, and wherein, in the global shutter mode, all or substantially all of the plurality of pixels in the CMOS image sensor are configured to be simultaneously exposed for a duration of an exposure period;

at least one illumination light source configured to illuminate at least a portion of a two-dimensional bar code for an illumination period, wherein the illumination period is dependent on the exposure period and at least one parameter related to an ambient light intensity;

a processor; and

a non-transitory memory including computer program instructions configured to, when executed by the processor, cause the apparatus to decode the image data, wherein the image data comprises at least a representation of the two-dimensional bar code.

2. The apparatus of claim 1, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to select a decoding algorithm for decoding the representation of the two-dimensional bar code from a plurality of decoding algorithms.

3. The apparatus of claim 1, wherein the at least one illumination light source is configured to project a two-dimensional observable illumination pattern over the two-dimensional bar code.

4. The apparatus of claim 1 further comprising an infrared filter.

5. The apparatus of claim 1, wherein the at least one illumination light source is configured to operate at a peak power level during at least a portion of the exposure period and is configured to be deactivated during another portion of the exposure period.

6. The apparatus of claim 1, wherein the illumination period is less than a frame time of the CMOS image sensor.

7. The apparatus of claim 1, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to at least decode an additional bar code detected in the image data.

8. The apparatus of claim 1, wherein the at least one illumination light source is configured to be substantially bright and the exposure period is configured to be substantially short so as to enable the image data to be substantially non-distorted.

9. The apparatus of claim 1, wherein the at least one illumination light source is configured to be operated above a maximum DC operation current draw rating.

10. The apparatus of claim 1, wherein a read out control timing signal begins at a conclusion of the exposure period.

11. The apparatus of claim 1, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a quiet zone is identifiable in the image data.

12. The apparatus of claim 1, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause

the apparatus to perform feature extraction such that a finder pattern is identifiable in the image data.

13. An apparatus comprising:

a CMOS image sensor having a plurality of pixels in a two-dimensional array, wherein the CMOS image sensor is operable to capture image data in a global shutter mode, and wherein, in the global shutter mode, all or substantially all of the plurality of pixels in the CMOS image sensor are configured to be simultaneously exposed for a duration of an exposure period, wherein at least one instance of the exposure period has a duration of less than 3.7 milliseconds;

at least one illumination light source configured to illuminate at least a portion of a two-dimensional bar code for an illumination period, wherein the illumination period is dependent on the exposure period and at least one parameter related to an ambient light intensity;

a processor; and

a non-transitory memory including computer program instructions configured to, when executed by the processor, cause the apparatus to decode the image data, wherein the image data comprises at least a representation of the two-dimensional bar code.

14. The apparatus of claim 13, wherein the at least one illumination light source is configured to be operated above a maximum DC operation current draw rating.

15. The apparatus of claim 13 further comprising an infrared filter.

16. The apparatus of claim 13, wherein the at least one illumination light source is configured to project a two-dimensional observable illumination pattern over the two-dimensional bar code and wherein the at least one illumination light source is configured to be substantially bright and the exposure period is configured to be substantially short so as to enable the image data to be substantially non-distorted.

17. The apparatus of claim 13, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a quiet zone is identifiable in the image data.

18. The apparatus of claim 13, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a finder pattern is identifiable in the image data.

19. An apparatus comprising:

a CMOS image sensor having a plurality of pixels in a two-dimensional array, wherein the CMOS image sensor is operable to capture image data in a global shutter mode, and wherein, in the global shutter mode, all or substantially all of the plurality of pixels in the CMOS image sensor are configured to be simultaneously exposed for a duration of an exposure period;

at least one illumination light source configured to illuminate at least a portion of a two-dimensional bar code for an illumination period, wherein the illumination period is dependent on at least one parameter related to an ambient light intensity;

a processor; and

a non-transitory memory including computer program instructions configured to, when executed by the processor, cause the apparatus to:

search the image data for one or more markers; and in an instance in which at least one marker of the one or more markers is detected, decode the image data

based on the at least one marker, wherein the image data comprises at least a representation of the two-dimensional bar code.

20. The apparatus of claim 19, wherein the at least one illumination light source is configured to be operated above a maximum DC operation current draw rating.

21. The apparatus of claim 19 further comprising an infrared filter.

22. The apparatus of claim 19, wherein the at least one illumination light source is configured to project a two-dimensional observable illumination pattern over the two-dimensional bar code and wherein the at least one illumination light source is configured to be substantially bright and the exposure period is configured to be substantially short so as to enable the image data to be substantially non-distorted.

23. The apparatus of claim 19, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a quiet zone is identifiable in the image data.

24. The apparatus of claim 19, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a finder pattern is identifiable in the image data.

25. An apparatus comprising:

a CMOS image sensor having a plurality of pixels in a two-dimensional array, wherein the CMOS image sensor is operable to capture image data in a global shutter mode, and wherein, in the global shutter mode, all or substantially all of the plurality of pixels in the CMOS image sensor are configured to be simultaneously exposed for a duration of an exposure period;

at least one illumination light source configured to illuminate at least a portion of a two-dimensional bar code for an illumination period, wherein the illumination period is dependent on the exposure period and at least one parameter related to an ambient light intensity;

a processor; and

a non-transitory memory including computer program instructions configured to, when executed by the processor, cause the apparatus to:

binarize the image data to create a binarized image according to at least one of local thresholding or target image size normalization;

search the binarized image for one or more markers; and

in an instance in which at least one marker of the one or more markers is detected, decode the binarized image based on the at least one marker, wherein the image data comprises at least a representation of the two-dimensional bar code.

26. The apparatus of claim 25 further comprising an infrared filter.

27. The apparatus of claim 25, wherein the at least one illumination light source is configured to project a two-dimensional observable illumination pattern over the target and wherein the at least one illumination light source is configured to be substantially bright and the exposure period is configured to be substantially short so as to enable the image data to be substantially non-distorted.

28. The apparatus of claim 25, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a quiet zone is identifiable in the image data.

29. The apparatus of claim 25, wherein the non-transitory memory including the computer program instructions is further configured to, when executed by the processor, cause the apparatus to perform feature extraction such that a finder pattern is identifiable in the image data.

5

30. The apparatus of claim 25, wherein the at least one illumination light source is configured to be operated above a maximum DC operation current draw rating.

* * * * *