

[54] **APPARATUS FOR DEMONSTRATING THE MODE OF OPERATION OF SAFETY SKI BINDINGS MOUNTED ON SKIS OR WOOD SPECIMENS**

[76] Inventors: **Egon Heckl**, Riedwiesenstrasse 10, 81 Garmisch-Partenkirchen, Burgrain; **Roland Jungkind**, Torlenstrasse 43, 81 Garmisch-Partenkirchen; **Bernd Payrhammer**, Westermuhlstrasse 13, 8 Munich 2, all of Germany

[22] Filed: **June 19, 1973**

[21] Appl. No.: **371,381**

[30] **Foreign Application Priority Data**

July 4, 1972 Germany..... 2232783

[52] U.S. Cl. **35/49**

[51] Int. Cl. **G09b 25/00**

[58] Field of Search..... 35/49, 13

[56] **References Cited**

UNITED STATES PATENTS

3,605,288 9/1971 Smolka 35/49

FOREIGN PATENTS OR APPLICATIONS

1,578,854 2/1971 Germany 35/49

Primary Examiner—Harland S. Skogquist
Attorney, Agent, or Firm—Fleit & Jacobson

[57] **ABSTRACT**

A dummy which corresponds to at least the sole of a skiing boot in shape and size and is provided with means by which the dummy when held in the binding can be deflected upwardly at its rear end and laterally at its forward end. A lever for operating the deflecting means is mounted in known manner in the rear one-third of the dummy on a horizontal transverse axis and in a normal position extends upwardly in an at least approximately vertical direction and can be pivotally shifted forwardly and rearwardly against spring force. A lever arm is connected to and angled from the operating lever and adapted to deflect the dummy upwardly. A bar linkage is connected to the operating lever and adapted to deflect the dummy laterally as the operating lever is shifted in the opposite sense. An abutment for the bar linkage is adapted to be secured to the ski or to the wood specimen.

7 Claims, 4 Drawing Figures







