

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2014/081593 A1

(43) International Publication Date

30 May 2014 (30.05.2014)

(51) International Patent Classification:

F16K 39/02 (2006.01) F16K 1/34 (2006.01)

(21) International Application Number:

PCT/US2013/069789

(22) International Filing Date:

13 November 2013 (13.11.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/681,795 20 November 2012 (20.11.2012) US

(71) Applicant: DRESSER, INC. [US/US]; 15455 Dallas Parkway, Suite 1100, Addison, TX 75001 (US).

(72) Inventor: CUNNINGHAM, Thomas, Henry; 9 Fencourt Road, Canton, MA 02021 (US).


(74) Agents: DOMBROWSKI, Joanna, M. et al.; General Electric Company, Global Patent Operation, Patent Counsel, 2 Corporation Drive, Suite 648, Shelton, CT 06484 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR REDUCING ACTUATOR THRUST REQUIREMENTS IN A CONTROL VALVE



(57) Abstract: A trim assembly is provided with a cage with an internal surface and a cage port. A plug having an external surface is disposed in the cage and is operable between a closed position, a pressure balancing position and an open position. The trim assembly also includes a low friction flow restrictor disposed between the cage and the plug and a pressure energized seal disposed between the cage and the plug. A seal balancing volume defined by the internal surface of the cage, the external surface of the plug, the low friction flow restrictor and the pressure energized seal is provided. The seal balancing volume is in fluid communication with the cage port through the low friction flow restrictor and is maintained at a seal balancing volume pressure. The trim assembly further includes a pressure control assembly configured to vent the seal balancing volume.



Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))* — *with international search report (Art. 21(3))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

APPARATUS AND METHOD FOR REDUCING ACTUATOR THRUST
REQUIREMENTS IN A CONTROL VALVE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This invention is related to U.S. patent application Serial No. _____ of Christopher Edward Wolfe, Nuo Sheng, Xuele Qi, Azam Mihir Thatte, James Albert Stares, Thomas Henry Cunningham and Henry Boger, filed concurrently herewith, assigned to the same assignee as the present invention that is hereby incorporated by reference.

TECHNICAL FIELD

[0002] The subject matter disclosed herein generally relates to control valves and more particularly to control valves with reduced actuator requirements.

BACKGROUND

[0003] Control valves are used to control the flow of fluids in systems used in the oil and gas processing, power generation, refining, petrochemical, and water control industries. Conventional control valves typically include a valve body with an inlet and an outlet. A cage and a seat ring are disposed between the inlet and outlet. The cage has at least one port allowing fluid communication between inlet and outlet of the control valve. The term “fluid communication” means allowing fluid to pass between or through as in fluid passing from one volume to another volume through a conduit. A plug is concentrically disposed in the cage and allowed to axially translate exposing the cage port(s) and modulating the fluid flow. The plug is connected to an actuator by means of a stem. The actuator is a device that supplies force and motion to open or close a valve, and may be powered by mechanical, pneumatic, hydraulic or electrical means.

[0004] Some control valves are designed to balance the pressure across the valve plug to reduce the amount of force necessary to open and close the valve with the actuators. Balanced control valves typically include a cage, a plug, a stem, a seat ring, and a balance seal. The plug has at least one conduit or orifice allowing fluid communication between the top and bottom which will balance the pressure across it. A seal ring may be provided between the plug and the cage to minimize fluid leakage. Balanced control valves, typically will have two main possible fluid leakage paths when closed. The first leakage path is between the plug and seat ring, where sufficient actuator force will provide hard metal-to-metal contact to impede flow. This leakage

may occur even when the plug is in contact with the valve seat. A second possible leakage path is the seal ring disposed between the plug and cage.

[0005] The American National Standards Institute ("ANSI") has established leakage classifications (ANSI/FCI 70-2) for control valves. The standard categorizes seat leakage into six classes (Class I to Class VI). The leakage criteria become more stringent as the class number increases. Class V represents what is commonly referred to as an "effectively zero-leakage" control valve. The standard for Class V valves requires that the maximum leakage allowed through a valve is 0.0005 ml of water per minute, per inch of port diameter, per PSI differential pressure as measured from an inlet port of the valve to an outlet port of the valve.

[0006] Balanced valves may be used with a number of different seals disposed between the plug and the cage, such as for example a piston ring seal. Piston ring seals may be manufactured from a variety of materials - such as Teflon, metal, and graphite - depending on the valve application (i.e., type of fluid, temperature, pressure). Teflon piston ring seals, for instance, may allow for a reasonably tight shutoff but be limited in usage by fluid temperature. Graphite and metal piston ring seals may allow for the valve to be used in higher temperature applications, but such materials may not allow for tight shut-off.

[0007] A typical piston ring seal may generate considerable friction while in contact with its sealing surface. This friction may be acceptable for applications that allow for leakage higher than the leakage requirements of FCI 70-2 Class V. For example, Class II, Class III or even Class IV, require less contact pressure to meet their respective leakage requirements, but Class V is several orders of magnitude tighter in comparison. To achieve Class V shutoff with a piston ring type sealing member at temperatures above the usable range of elastomers or thermoplastics will typically result in high friction resulting in a high actuation requirement (i.e. a high force is required to open and close the valve) making it difficult to operate the valve.

BRIEF DESCRIPTION OF THE INVENTION

[0008] The disclosure provides a solution to the problem of maintaining a Class V seal without requiring a high actuator thrust. Additionally the disclosure provides a solution to the problem of maintaining a tight seal with lower actuation thrust requirements at temperatures above the upper usable limits of elastomeric or thermoplastic materials.

[0009] In accordance with one exemplary non-limiting embodiment, the invention relates to a trim assembly having a cage with an internal surface and a cage port. A plug having an external surface is disposed in the cage and is operable between a closed position, a pressure balancing position and an open position. The trim assembly also includes a low friction flow

restrictor disposed between the cage and the plug and a pressure energized seal disposed between the cage and the plug. A seal balancing volume defined by the internal surface of the cage, the external surface of the plug, the low friction flow restrictor and the pressure energized seal is provided. The seal balancing volume is in fluid communication with the cage port through the low friction flow restrictor and is maintained at a seal balancing volume pressure. The trim assembly further includes a pressure control assembly configured to pressurize the seal balancing volume.

[0010] In another embodiment, a trim assembly is provided having a cage with an interior surface and a cage port. A plug having an outer surface, a top portion and a bottom portion is disposed within the cage. The plug is movable between a closed position, a pressure balancing position and an open position. The trim assembly also includes a low friction flow restrictor disposed between the interior surface of the cage and the outer surface of the plug, and a pressure energized seal disposed between the interior surface of the cage and the outer surface of the plug, the pressure energized seal being maintained at a seal pressure. A pressure control assembly configured to control a differential pressure acting on the pressure energized seal is also included.

[0011] In another embodiment, a method of operating a trim assembly includes maintaining a downstream pressure at a cage port formed on a cage. The method also includes maintaining an upstream pressure above and below a plug disposed in the cage. The plug is movable between a closed position, a pressure balancing position and an open position. The method includes balancing a differential pressure acting on a pressure energized seal disposed in a seal balancing volume when the plug is in the pressure balancing position and in the open position.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Other features and advantages of the present invention will be apparent from the following more detailed description of the preferred embodiment, taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of certain aspects of the invention.

[0013] Figure 1 is a cross section of an embodiment of a valve trim in the closed position.

[0014] Figure 2 is a cross section of an embodiment of a valve trim in the pressure balanced position.

[0015] Figure 3 is a cross section of an embodiment of a valve trim in the open position.

[0016] Figure 4 is a flowchart of an embodiment of a method of operating a trim assembly.

DETAILED DESCRIPTION OF THE INVENTION

[0017] In a preferred embodiment the trim assembly of the disclosure is provided with a cage, a plug disposed in the cage, a low friction flow restrictor, and a high friction pressure energized seal. The interior of the cage, the exterior of the plug the low friction flow restrictor, and the high friction pressure energized seal define a seal balancing volume. When the trim assembly is in the closed position the pressure in the seal balancing volume is maintained at the downstream pressure. When the trim assembly is in a pressure balancing position the seal balancing volume is pressurized and maintained at an upstream pressure. Pressure balancing of the high friction pressure energized seal is accomplished by allowing fluid at an upstream pressure to flow through a balancing port into the seal balancing volume between the high friction pressure energized seal and the low friction flow restrictor. Leakage of the fluid through low friction flow restrictor is less than the inflow to the seal balancing volume so that, after an interval of time, the pressure in the seal balancing volume is increased to the upstream pressure thereby reducing or eliminating the pressure differential acting on the pressure energized seal. The result is that the pressure exerted against the cage by the pressure energized seal is significantly reduced or the contact between the pressure energized seal and the cage is eliminated before main plug travel occurs. Balancing of the pressure in the seal balancing volume with the upstream pressure reduces the pressure differential acting on the high friction pressure energized seal thereby reducing or eliminating contact between the seal and the cage resulting in reduced friction. Reduction of the friction reduces the actuator thrust required to move the trim assembly to the open position and during throttling.

[0018] Illustrated in Figure 1 is an embodiment of a trim assembly 11 with reduced actuator thrust requirements. The trim assembly 11 includes a cage 13 having a cage port 15, and a plug 17 disposed within the cage 13. The plug 17 is configured to slide within the cage 13.

[0019] The plug 17 is provided with a seating surface 19 that engages a seat ring 21 disposed below the cage 13. The plug 17 includes a balancing conduit 23 having an opening 24 and a longitudinal conduit 25. The plug 17 may also be provided with a plug platform 27 at the bottom of the plug 17.

[0020] The trim assembly 11 is provided with a high friction, pressure energized seal 29 disposed in a sealing gland 31 formed in the plug 17 or the cage 13. As increasing pressure is applied to the high friction pressure energized seal 29, it deforms and continues to seal against

the seal surfaces with higher internal stress and contact pressure thereby increasing friction. The trim assembly 11 is also provided with a low friction flow restrictor 33 disposed in a restrictor gland 35 formed in the plug 17 or the cage 13. In an embodiment the low friction flow restrictor 33 may be a piston seal. The interior of the cage 13, the exterior of the plug 17 together with the high friction, pressure energized seal 29 and the low friction flow restrictor 33 define a seal balancing volume 37 (corresponding to the dashed line 37 in Figure 1). Disposed below the plug 17 is an upstream volume 39 (corresponding to the dashed line 39 in Figure 1) which is maintained at an upstream pressure. Disposed above the plug 17 is a pressurizing volume 41 (corresponding to the dashed line 41 in Figure 1) that is also maintained at an upstream pressure due to fluid communication with the upstream volume 39 via conduit 25. The terms "above" and "below" are used to refer to relative locations of identified elements with reference to the drawings and are not intended to denote the orientation of the components of the trim assembly 11 in actual use.

[0021] The trim assembly 11 also includes a stem assembly 43 having a stem 45, a sealing flange 47, and a nut 49. The stem assembly 43 may be biased with a spring 51 that engages the sealing flange 47. The stem assembly 43 may be coupled to an actuator 53 that drives the stem assembly 43 and causes the stem assembly 43 to slide within the cage 13.

[0022] Figure 1 illustrates an embodiment of the trim assembly 11 with the plug 17 in the closed position. In the closed position, upstream volume 39 is maintained at the upstream pressure P1, and the cage port 15 is maintained at a downstream pressure (P2). The pressure in upstream volume 39 (P1) will be higher than the pressure at the cage port 15 (P2). The seating surface 19 of the plug 17 is seated against the seat ring 21 forming a tight seal. The plug 17 is forced against the seat ring 21 by the actuator 53. The sealing flange 47 seals the balancing conduit 23. The high friction pressure energized seal 29 and the low friction flow restrictor 33 seals off the seal balancing volume 37. It should be noted that the low friction flow restrictor 33 permits a limited flow of fluid so that the pressure of the seal balancing volume 37 is substantially the same as the downstream pressure of the fluid at the cage port 15 (P2). Pressurizing volume 41 is in fluid communication with the upstream volume 39 through longitudinal conduit 25, thereby maintaining the pressure in the pressurizing volume 41 at the upstream pressure P1. The pressure differential between the pressure in the seal balancing volume 37 (P2) and the pressure in pressurizing volume 41 (P1) keeps the high friction pressure energized seal 29 fully pressurized and in a tight sealing relationship with the cage 13.

[0023] Figure 2 shows the trim assembly 11 with the plug 17 in a pressure balancing position. In this position, the stem assembly 43 has been displaced and the attached sealing

flange 47 is also displaced thereby uncovering the balancing conduit 23. The seal balancing volume 37 is then fluidly coupled with the pressurizing volume 41 that is at upstream pressure P1. The low friction flow restrictor 33 restricts the fluid flow from seal balancing volume 37 to the cage port 15 to a rate sufficiently lower than the rate at which fluid flows from the upstream volume 39 through conduit 23 thereby pressurizing the seal balancing volume 37. The net result is that the pressure of the fluid at the seal balancing volume 37 is balanced with the pressure of the fluid at the pressurizing volume 41 thereby reducing the differential pressure acting on the high friction pressurized seal 29. For the purposes of this disclosure “balanced” means that the difference between the seal pressure and the upstream pressure is reduced.

[0024] Illustrated in Figure 3 is the trim assembly 11 with the plug 17 in an open throttling position. The stem assembly 43 is displaced upwardly and the nut 49 engages the bottom of the plug 17. The seal pressure acting on the high friction pressure energized seal 29 has been balanced thereby reducing or eliminating the contact of the high friction pressure energized seal 29 with the cage 13. The friction between the high friction pressurized seal 29 and the cage 13 is consequently reduced. The reduction in friction reduces the thrust required by the actuator 53 to displace the plug 17. The thrust provided by the actuator may be provided by mechanical, pneumatic, hydraulic or electrical means.

[0025] Illustrated in Figure 4 is a method 101 of operating a trim assembly 11 in accordance with one embodiment. The method 101 is implemented by the trim assembly 11.

[0026] In step 103 the trim assembly 11 maintains a downstream pressure at a cage port 15 formed on a cage 13.

[0027] In step 105 the trim assembly 11 maintains an upstream pressure about a balanced plug 17 disposed in the cage 13, the balanced plug 17 being movable between a closed position, a pressure balancing position and an open position.

[0028] In step 107 the trim assembly 11 balances a seal pressure differential acting on a high friction pressure energized seal 29 disposed in a seal balancing volume 37 so that when the plug 17 is closed the pressure differential acting on the balance seal 29 is equal to the full pressure differential $P_1 - P_2$, and the pressure differential is minimized or removed when the plug 17 is in the pressure balancing or open position. This may be accomplished by pressurizing the seal balancing volume 37 to the upstream pressure. To control the pressure in the seal balancing volume 37 the plug 17 may be provided with an opening 24 at the top of the plug 17 and in fluid communication with the pressurizing volume 41. The opening 24 may be sealed by sealing flange 47 when the plug 17 is in the closed position. The opening 24 may be uncovered when the plug 17 is in the pressure balancing position. Although in the description of the

preceding embodiments a sealing flange 47 is described as a means for sealing the opening 24, it would be apparent to one of ordinary skill in the art to provide other sealing members – for example a plug – without departing from the scope of the present invention.

[0029] Where the definition of terms departs from the commonly used meaning of the term, applicant intends to utilize the definitions provided below, unless specifically indicated.

[0030] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. Where the definition of terms departs from the commonly used meaning of the term, applicant intends to utilize the definitions provided herein, unless specifically indicated. The singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be understood that, although the terms first, second, etc. may be used to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. The term “and/or” includes any, and all, combinations of one or more of the associated listed items. The phrases “coupled to” and “coupled with” contemplates direct or indirect coupling.

[0031] This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements.

What is Claimed:

1. A trim assembly, comprising:
a cage with an internal surface and a cage port;
a plug disposed in the cage, the plug having an external surface and being
operable between a closed position, a pressure balancing position and an
open position;

a low friction flow restrictor disposed between the cage and the plug;
a pressure energized seal disposed between the cage and the plug;
a seal balancing volume; and
a pressure control assembly configured to pressurize the seal balancing volume.

2. The trim assembly of claim 1, wherein the seal balancing volume is defined by the
internal surface of the cage, the external surface of the plug, the low friction flow restrictor and
the pressure energized seal, the seal balancing volume being in fluid communication with the
cage port through the low friction flow restrictor and being maintained at a seal balancing
volume pressure.

3. The trim assembly of claim 1, wherein the pressure control assembly is configured
to balance a differential pressure acting on the pressure energized seal before any movement of
the plug.

4. The trim assembly of claim 2, wherein the pressure control assembly is configured
to balance the seal balancing volume pressure acting on the pressure energized seal during any
movement of the plug.

5. The trim assembly of claim 1, further comprising a conduit in fluid
communication with a volume at an upstream pressure when the plug is in the pressure balancing
position, and wherein the pressure control assembly is configured to allow fluid at an upstream
pressure to flow into the seal balancing volume at a rate in which leakage of a fluid through the
low friction flow restrictor is less than flow of the fluid into the seal balancing volume.

6. The trim assembly of claim 5, wherein the seal balancing volume and the volume at an upstream pressure are fluidly coupled through a conduit extending through plug, the conduit having a balancing port.

7. The trim assembly of claim 6, wherein the pressure control assembly comprises:
a stem coupled with the plug;
a sealing component coupled to the stem and disposed to close off the balancing port when the plug is in the closed position.

8. The trim assembly of claim 7, wherein the sealing component is disposed to open the balancing port when the plug is in the pressure balancing position prior to any movement of the plug.

9. A trim assembly, comprising:
a cage having an interior surface and a cage port;
a plug disposed within the cage, the plug being movable between a closed position, a pressure balancing position and an open position;
a low friction flow restrictor disposed between the cage and the plug
a pressure energized seal disposed between cage and the plug; and
a pressure control assembly configured to control a differential pressure acting on the pressure energized seal.

10. The trim assembly of claim 9, wherein an interior surface of the cage, an outer surface of the plug, the low friction flow restrictor and the pressure energized seal define a seal balancing volume in fluid communication with a downstream volume.

11. The trim assembly of claim 10, wherein the pressure control assembly maintains the seal balancing volume at a downstream pressure when the plug is in the closed position.

12. The trim assembly of claim 10, wherein the pressure control assembly comprises a conduit extending from the seal balancing volume to a volume at an upstream pressure.

13. The trim assembly of claim 12, wherein the pressure control assembly comprises a stem assembly having a closure member closing the conduit when the plug is in the closed

position and opening the conduit when the plug is in the pressure balancing position and in the open position.

14. The trim assembly of claim 13, wherein the stem assembly comprises a stem and the closure member comprises a sealing member coupled to the stem, the sealing member being disposed in contact with the conduit when the plug is in the closed position.

15. The trim assembly of claim 14, further comprising a spring that biases the flange away from the opening.

16. A method of operating a trim assembly, comprising:
maintaining a downstream pressure at a cage port formed on a cage;
maintaining an upstream pressure about a balanced plug disposed in the cage, the balanced plug being movable between a closed position, a pressure balancing position and an open position; and
balancing a differential pressure acting on a pressure energized seal disposed in a seal balancing volume when the plug is in the pressure balancing position and in the open position.

17. The method of claim 16, wherein balancing comprises controlling the differential pressure so that the differential pressure on the pressure energized seal is equal to the upstream pressure minus the downstream pressure when the balanced plug is in the closed position, and the differential pressure acting on the pressure energized seal is balanced when the balanced plug is in the pressure balancing position and in the open position.

18. The method of claim 16, wherein balancing comprises controlling fluid flow through a conduit in fluid communication with the seal balancing volume.

19. The method of claim 18, wherein controlling fluid flow comprises controlling a sealing member on the conduit.

20. The method of claim 18, wherein controlling fluid flow comprises opening the conduit when the balanced plug is in the pressure balancing position.

1/4




Fig. 1

2/4




Fig. 2

3/4




Fig. 3

4/4




Fig. 4

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2013/069789

A. CLASSIFICATION OF SUBJECT MATTER
INV. F16K39/02 F16K1/34
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
F16K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 564 674 A (KAELIN RUDOLF [CH] ET AL) 15 October 1996 (1996-10-15) column 1, line 62 - column 3, line 54; figures 1-2b -----	1-20
A	US 2007/210270 A1 (STEPHENSON DWIGHT B [US] ET AL) 13 September 2007 (2007-09-13) figure 1 -----	1,9,16
A	US 3 624 753 A (BRUMM RICHARD S) 30 November 1971 (1971-11-30) figures 1-4 -----	1,9,16
A	EP 0 900 962 A2 (HUSCO INT INC [US]) 10 March 1999 (1999-03-10) figures 1-3 ----- -/-	1,9,16

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier application or patent but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search 27 February 2014	Date of mailing of the international search report 07/03/2014
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Heneghan, Martin

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2013/069789

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 017 868 A1 (SPERRY VICKERS [DE]) 29 October 1980 (1980-10-29) figure 2 -----	1,9,16

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2013/069789

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 5564674	A	15-10-1996	CA DE EP ES JP US WO	2163312 A1 59504334 D1 0726413 A1 2125580 T3 H09512329 A 5564674 A 9625615 A1		14-08-1996 07-01-1999 14-08-1996 01-03-1999 09-12-1997 15-10-1996 22-08-1996
US 2007210270	A1	13-09-2007	DE JP US	102007011127 A1 2007239996 A 2007210270 A1		31-10-2007 20-09-2007 13-09-2007
US 3624753	A	30-11-1971	NONE			
EP 0900962	A2	10-03-1999	BR CA CN DE DE EP JP JP US	9803131 A 2240929 A1 1208141 A 69819433 D1 69819433 T2 0900962 A2 3182398 B2 H1172102 A 5878647 A		08-03-2000 11-02-1999 17-02-1999 11-12-2003 09-09-2004 10-03-1999 03-07-2001 16-03-1999 09-03-1999
EP 0017868	A1	29-10-1980	AU AU CA DE EP JP JP US	532488 B2 5748080 A 1122880 A1 2915783 A1 0017868 A1 S6352272 B2 S55149403 A 4340086 A		29-09-1983 23-10-1980 04-05-1982 06-11-1980 29-10-1980 18-10-1988 20-11-1980 20-07-1982