

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 1/72		A1	(11) International Publication Number: WO 99/31859 (43) International Publication Date: 24 June 1999 (24.06.99)
(21) International Application Number: PCT/US98/18059		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 1 September 1998 (01.09.98)			
(30) Priority Data: 60/069,684 12 December 1997 (12.12.97) US			
(71) Applicant (for all designated States except US): THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 10330 North Meridian Street, Indianapolis, IN 46290-1024 (US).			
(72) Inventors; and		Published	
(75) Inventors/Applicants (for US only): RAMASWAMY, Kumar [IN/US]; 9417 College Drive #B, Indianapolis, IN 46240 (US). KNUTSON, Paul, Gothard [US/US]; 148 South Emerson Avenue, Indianapolis, IN 46219 (US). KAPADIA, Maneck, Behram [US/US]; 538 Arbor Drive, Carmel, IN 46032 (US).		With international search report.	
(74) Agents: TRIPOLI, Joseph, S. et al.; GE & RCA Licensing Management Operation, Inc., P.O. Box 5312, Princeton, NJ 08540 (US).			

(54) Title: INITIALIZATION OF HANDSETS IN A MULTI-LINE WIRELESS PHONE SYSTEM FOR SECURE COMMUNICATIONS

(57) Abstract

A wireless telephone system, having one or more wireless handsets and a base unit. Each handset has a handset transceiver, and the base unit has a base transceiver and a handset docking station, which has a wired interface. The base unit digitally communicates over an RF channel with a handset via its handset transceiver only if the handset has previously been initialized by the base unit. The handset is initialized via the wired interface when it is physically docked in the docking station.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INITIALIZATION OF HANDSETS IN A MULTI-LINE WIRELESS PHONE SYSTEM FOR SECURE COMMUNICATIONS

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to multi-line wireless telephone systems and, in particular, to providing secure communications in a time-division multiplexed (TDM) wireless telephone system.

Description of the Related Art

10 The use of telephones and telephone systems, including wireless telephone systems, is widespread. In wireless telephone systems, a cordless or wireless telephone handset unit communicates via either analog or digital radio signals with a base unit, which is typically connected via a standard telephone line to an external telephone network. In this manner, a user may employ the wireless handset to engage in a telephone call with another user through the base unit and the telephone network.

20 Multi-line wireless telephone systems are in use in various situations, such as businesses with many telephone users. Such systems employ a handset that communicates with up to N handsets simultaneously, typically with digital communications schemes, such as a spread-spectrum, time division multiple access (TDMA). In a TDMA system, a single RF channel is used, and each handset transmits and receives data during a dedicated time slice or slot within an overall cycle or epoch. It is desirable to provide various features, such as private branch exchange (PBX) features and capabilities, in a 25 multi-line wireless telephone system.

One problem that may be encountered in such situations is breach of security. For example, an unauthorized third party may use a "bootleg" wireless handset to communicate via the base unit. Without adequate security, these and other types of security breaches 5 may occur.

SUMMARY

A wireless telephone system, having one or more wireless handsets and a base unit. Each handset has a handset transceiver, 10 and the base unit has a base transceiver and a handset docking station, which has a wired interface. The base unit digitally communicates over an RF channel with a handset via its handset transceiver only if the handset has previously been initialized by the base unit. The handset is initialized via the wired interface when it is 15 physically docked in the docking station.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of TDMA multi-line wireless telephone system for initializing wireless handsets of the system, in accordance with an embodiment of the present invention;

20 Fig. 2 is a schematic representation of the message format for an initialization message exchange between the base unit and a handset of the telephone system of Fig. 1 via a wired link, for initializing the handset, in accordance with an embodiment of the present invention;

25 Fig. 3 is a flow diagram illustrating the handset initialization performed by the system of Fig. 1, from the point of view of the base station, in accordance with an embodiment of the present invention; and

Fig. 4 is a flow diagram illustrating the handset initialization performed by the system of Fig. 1, from the point of view of the handset being initialized, in accordance with an embodiment of the present invention.

5

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to Fig. 1, there is shown a block diagram of spread spectrum TDMA multi-line digital wireless telephone system 100, in accordance with an embodiment of the present invention. 10 TDMA system 100 comprises a base unit 110, which has receiver and transmitter units 112 and 111, respectively, and is coupled to external telephone network 116 via telephone line(s) 115. Base unit 110 also comprises docking station 118, for receiving a wireless handset and providing a wired interface between base unit 110 and 15 the handset. In addition, base unit 110 also has a controller/microprocessor 113 for controlling and monitoring the overall functions of the base unit 110.

System 100 also comprises N wireless handsets 120₁, 120₂, . . . 120_N. Each has a transmitter and receiver unit (transceiver), 20 such as transmitter 121 and receiver 122 of handset 120₁. In one embodiment, receiver unit 112 comprises N logical receivers, and transmitter unit 111 comprises N logical transmitters, so that receiver and transmitter units 112 and 111 provide N logical transceiver units, one for each of N wireless handsets. At any given time, M handsets (0 25 ≤ M ≤ N) are operating or active (i.e., in the process of conducting a telephone call).

The telephone system provided by system 100 preferably operates in the 900 MHz unlicensed band, and preferably provides

features like that of a small PBX, in conjunction with PC 140. In one embodiment, system 100 employs a combination of time division multiplexing (TDM), such as TDMA, and frequency band selection to overcome interfering sources and to maintain reliable links between 5 the base-station and the handsets. In a digital TDMA scheme, each handset only transmits or receives data during its own "time slice" or slot. System 100 thus provides a wireless network between the base station 110 and each handset 120_i (1 ≤ i ≤ N). In one embodiment, N=4, so that system 100 comprises a maximum of 4 wireless handsets, 10 each having unique time slots in the TDMA epoch dedicated thereto.

As explained above, lack or breach of security in such a system is undesirable. Therefore, the telephone system of the present invention is configured to minimize this problem and to provide secure and robust communications between handsets and the base 15 unit. In the present invention, the base unit 110 is configured so that it will communicate only with handsets that are able to provide certain unique identifier (ID) information, or security code. This ID information may include information such as the slot number assigned to the handset (e.g., one of numbers 1-4 in a 4-line, 4-slot, 4- 20 handset system), as well as the handset serial number and/or the base serial number (or security codes based on the serial number), and the like. Only handsets 120_i that have been initialized by base unit 110 will be able to provide this information to the base unit 110; all non-initialized handsets will therefore not be able to communicate 25 as part of the telephone system 100.

In an alternative embodiment, in addition to the use of security codes such as the serial number, and slot number, a user-programmable scrambler code is employed. In this embodiment,

during initialization, the user of the handset is prompted to enter a random scrambler seed. This scrambler seed is then stored in both handset and base unit, and is used to scramble all future TDMA communications between the two. Since only the initialized handset 5 and the base unit know the scrambler seed, an unauthorized handset or other transceiver device will be unable to eavesdrop on the channel or use the handset's slot. Thus, the user-programmable scrambler provides an extra layer of security. In an alternative embodiment, the scrambler code or seed may be selected 10 automatically by the base unit and/or handset, without prompting the human user for input.

System 100 is configured so that base unit 110 has a physical docking station 118 or receptacle/port into which a non-initialized handset 120_i may be physically placed, to provide a wired link and 15 interface between the handset 120_i and base unit 110. The handset is then initialized by the base unit via the wired link. Because the physical location of the base unit and its docking station or port may be controlled and access thereto limited to authorized persons, and because a handset must be physically docked to the docking station in 20 order to engage in initialization, only an authorized person will be able to initialize a handset. Therefore, in the present invention, only handsets that have been initialized by the handset via the wired link, as a result of actions of an authorized user, will be able to engage in 25 telephone communications with the telephone system, thus providing communication security. The present invention is described in further detail below, with reference to Figs. 2-4.

Referring now to Fig. 2, there is shown a schematic representation of the message format 200 for an initialization

message exchange between the base unit 110 and a handset 120_i of the telephone system 100 of Fig. 1 via a wired link, for initializing the handset 120_i, in accordance with an embodiment of the present invention. Message format 200 comprises a plurality of fields 201-209 for the exchange of information between base unit 110 and a handset 120_i via the wired link provided by port 118, which are exchanged in order to initialize the handset. Messages sent to a docked handset 120_i from base unit 110 have message format 200, as do messages sent to base unit 110 from a docked handset 120_i. Port 118 may also double as the recharging port or cradle into which a handset may be placed to recharge its battery.

Whenever a non-initialized handset 120_i is placed in port 118 and is to be initialized, the base unit 110 provides information to the handset, and vice-versa, to initialize the handset so that future TDMA communication may be conducted. In one embodiment, this information includes a security code or ID 205, a slot number 204, and a scrambler seed 207. In one embodiment, the security code is based on the serial number of the handset, and is preferably a 32 bit number. The security code may be identical to the serial number, or a part or subset thereof. In an alternative embodiment, the security code is based on the serial number for the base unit, instead of or in addition to that of the handset. The security code is used to authenticate the handset every time any messages are to be exchanged between the base and a handset. In addition to the time slot mechanism, this security code provides a secure exchange of messages from the base to the handset.

The slot number for the handset is a 3 bit number, which is assigned by base unit 110, and transmitted via the wired link to the

handset. The slot number is a unique time slot number, which distinguishes handset 120_i from other handsets in system 100. The scrambler seed is an 8-bit number, also based on the serial number of the base unit, or, alternatively, user programmable through a serial computer interface or other input (e.g. the keypad of the wireless phone), and is used to generate the code that randomizes the spectrum of transmitted information. Since such encoding employs a deterministic mapping, which is known only to the transceivers of the handset and base unit, it can provide additional security, as described above.

Message format is, in one embodiment, a 72-bit field 200 having an unused field 208 for future expansion as shown in Fig. 2. Message number field 201 is a 4-bit field, modulo generated at each end of a transmission, which helps keep track of the state of the other end. This field is also used for positive acknowledgments. Message type field 202 is a 4-bit field, used to signal different types of messages that can possibly be exchanged between base and handsets. New/existing field 203 is a 1-bit field that indicates whether the handset is a new handset or existing handset, where 0 = new handset. For packets originating from base unit 110, this field is always set to 0.

As described previously, local number field 204 is a 3-bit field that indicates the local (slot) number assigned to an existing handset. This number is ignored if new/existing field 203 is set to 0. 32-Bit ID field 205 indicates the security code or ID, which is derived from the factory designated ID for handset 120_i. This will form the basis for secure communications between the base and handsets registered with the base (i.e., initialized). A 5-bit ack message field 206 contains

the 4-bit message number that is being acknowledged, plus an ack bit. In this format, bits 0-3 represent the message number being acknowledged, and bit 4 represents negative ack if 0, and positive ack if 1. The generation of the acknowledgment is based on the CRC check 5 done at the receiving end. Scrambler seed field 207 is an 8-bit field used to seed the scrambler in the RF link. It forms an additional layer of security. This may be default generated from the factory code or programmed through the serial computer interface by a user. CRC code field 209 is an 8-bit cyclic redundancy check code used for error 10 detection and correction.

Referring now to Fig. 3, there is shown a flow diagram 300 illustrating the handset 120_i initialization performed by system 100 of Fig. 1 under the control of CPU 113, from the point of view of base station 110, in accordance with an embodiment of the present 15 invention. A handset placed or "docked" into port 118 may be already initialized and docked only for recharging. Alternatively, a non-initialized handset (i.e., either a "new" handset that has never been initialized, or a handset previously initialized for a different base unit) may be docked in port 118 in order to initialize the 20 handset for base unit 110. Additionally, an already-initialized handset may be docked in port 118 in order to re-program or change some of the initialization parameters, i.e. to re-initialize the handset. In the latter cases, the handset may still need recharging.

Thus, base unit 110 first polls the relevant I/O device to detect 25 the presence of the handset on the recharge cradle, i.e. port 118 (step 301). When a handset 120_i is docked in port 118 (i.e., the recharge cradle), base unit 110 first checks to see if the voltage level of the battery of handset 120_i is above a certain threshold that would

permit normal functioning of the handset (step 302). If not, no further processing steps take place until the handset recharges to a sufficient voltage.

Once the threshold voltage requirement is satisfied (step 302),
5 base unit 110 initiates the messaging protocol, in accordance with message format 200, by sending the initial message through the wired interface of port 118 to the handset 120_i (step 303). This message is a sign on message which is indicated in the message type field 202 with 0. This starts a sequence of events that are described
10 from the viewpoint of base unit 110 in Fig. 3 and from the viewpoint of handset 120_i in Fig. 4. All messages exchanged between the handset and base are asynchronous in nature. The general goal of this procedure is to either allow for a normal recharge or to initialize
15 a non-initialized handset. In the initial message, base unit 110 fills in the following fields: message number field 201, message type filed 202 (where sign on message = 0), and the CRC field 209. (If the CRC does not match at the handset, it sends a negative acknowledge back to base unit 110 with the message number, in which case base unit 110 sends a retransmit message to the handset (not shown in Fig. 3).
20 All messages with CRC need acknowledgment even where not indicated in Fig. 3.)

At this point, base unit 110 expects an acknowledge from handset 120_i (step 304). If an acknowledge is not received before a timer times out, the procedure starts again (steps 305, 306, 301). If
25 an acknowledge is received before time out (step 304), then base unit 110 can determine whether the docked handset is "new" or has already been initialized (step 311). Handset 120_i at step 311 may have one of 3 states: it may be a new handset, it may be already

10

initialized by base unit 110, or it may have been initialized previously by a different base unit.

In case the handset's message indicates a new handset (in which case the handset's message contains the handset's ID in field 205), the 5 base needs to check if it has a local number or slot available (step 312). For example, in a 4-handset system, if 4 handsets are already initialized and thus registered with base unit 110, no slot will be available. If the base unit 110 has an available local number, then the base unit 110 will assign it to the handset by updating the 10 message fields (step 313). In this case, base unit 110 fills out the following fields for the message: message number field 201, message type field 202, unique system ID field 205, local slot number assignment field 204, scrambler seed field 207, and CRC field 209. In this case, ID field 205 contains the serial number of base unit 110.

15 If it is determined that handset 120_i is new, but there is no slot available (step 312), base unit 110 assumes that the user is trying to replace an existing handset with handset 120_i. In this case, the user is prompted to provide information about what local number needs to be replaced. This is accomplished by a message sent from the base to 20 the handset which then displays a Local Number request and an audio warning (step 321). Once a response with a valid slot number is received from the handset as a result of this query (steps 322, 323), base unit 110 completes the local slot number assignment and fills out the specified fields for the message (step 313). If no response is 25 received from the handset, a timeout is issued and the base starts at the top of its execution (step 324).

When handset 120_i is not a new handset (step 311), base unit 110 checks the 32 bit ID, local number, and scrambler seed

11

transmitted by handset 120_i. If these numbers match the information stored in base unit 110's memory, the base program exits (step 331). If there is a mismatch, then the base sends a reprogram message (message type = 8) to the handset (steps 331, 332). This 5 message is filled in the following fields: message number field 201, message type field 202, and CRC field 209.

If base unit 110 receives a positive acknowledgment, it follows the processing chain as if it is dealing with a new handset, so that it can re-initialize the handset (steps 333, 312). In case it receives a 10 negative acknowledge or times out, it exits the service routine (steps 333, 334, 335).

Referring now to Fig. 4, there is shown a flow diagram 400 illustrating the handset 120_i initialization performed by system 100 of Fig. 1, from the point of view of handset 120_i, in accordance with 15 an embodiment of the present invention. As will be appreciated, the processing flow in handset 120_i mirrors that in base unit 110, described above with reference to Fig. 3. Once the initial sign-on message is received correctly from the base (step 403), handset 120_i responds with an acknowledgment including old/new and related 20 handset information (step 404). In particular, if the handset is new, it responds (step 404) with a message having the following fields filled in: message number field 201, message type field 202 (=1), new/existing handset field 203 (=0; "new"), and CRC field 209. If handset 120_i has already been initialized, it responds with a message 25 having the following fields filled in: message number field 201, message type field 202, new/existing handset field 203 (=1; "preinitialized"), unique system ID field 205, local slot number assignment field 204, scrambler seed field 207, and CRC field 209.

The rest of the processing chain shown in Fig. 4 (steps 405 *et seq.*) is a reflection of actions requested by the base. As discussed above, handset 120_i needs to have a response for each of the possible states that it can be in. In particular, depending on its initial status 5 (which is one of 3 possible conditions discussed in the previous section), the base may request the following actions: local slot number assignment (step 406); User to Provide Local Message Assignment (step 407); or HS vs. Base ID Mismatch (step 408) (implying a requirement for a possible reprogramming of the handset 10 based on the user's request). This allows a handset to be recharged in another base with the user prompting such an action only. Also, in the case where only a recharging function is carried out, there is no unique ring tone at the completion of the action. All other actions in the handset on completion result in a unique ring tone (step 425) 15 which signals to the user that the handset and base have completed their actions.

One skilled in the art will recognize that the wireless system described above according to the principles of the invention may be a cellular system where base unit 110 represents a base station serving 20 one of the cells in a cellular telephone network.

It will be understood that various changes in the details, materials, and arrangements of the parts which have been described and illustrated above in order to explain the nature of this invention may be made by those skilled in the art without departing from the 25 principle and scope of the invention as recited in the following claims.

CLAIMS

1. A wireless telephone system, comprising:
 - 5 (a) one or more wireless handsets, each handset comprising a handset transceiver; and
 - (b) a base unit comprising a base transceiver for communicating over a channel with each handset via its handset transceiver only if the handset has previously been initialized by the base unit; a handset docking station having a wired interface; and
- 10 means for initializing the handset via the wired interface.
2. The system of claim 1, wherein:
 - 15 the means for initializing obtains from the handset and stores locally a unique handset security code; and
 - the base unit allows a given handset to communicate over the channel only if the handset provides to the base unit the handset security code.
- 20
3. The system of claim 2, wherein:
 - the means for initializing further provides a unique base unit security code to the handset; and
 - the base unit allows a given handset to communicate over the channel only if the handset provides to the base unit the base unit security code and the handset security code.
- 25

4. The system of claim 2, wherein:

the base transceiver establishes a time-division multiple access (TDMA) link with each handset via the handset transceiver in accordance with a TDMA epoch allocating exclusive audio packet time slots to each handset;

5 the means for initializing obtains from the handset and stores locally a unique handset security code and provides to the handset an exclusive audio packet slot number corresponding to its audio packet time slot; and

10 the base unit allows a given handset to communicate over the RF channel only if the handset provides to the base unit the handset security code and the audio packet slot number.

15

5. The system of claim 2, wherein:

digital communications between the base transceiver and the handset are scrambled in accordance with a scrambler seed unique to the handset that must be known to both the base transceiver and the handset; and

20 the means for initializing provides to the handset and stores locally the scrambler seed for the handset.

6. The system of claim 2, wherein the handset security code is
25 based on a unique handset serial number.

7. The system of claim 1, wherein:

the means for initializing provides to the handset a unique base unit security code based on a unique base unit serial number; and

the base unit allows a given handset to conduct digital communications over the RF channel only if the handset provides to the base unit the base unit security code and the handset security code.

10

8. The system of claim 1, wherein:

each handset is battery powered by a rechargeable battery; and the docking station comprises a charging means for recharging the battery of a handset physically docked in the docking station.

15

9. The system of claim 8, wherein:

the base unit comprises means for determining whether the battery of the handset physically docked in the docking station has a voltage below a threshold level, wherein the means for initializing waits until after the battery voltage has been recharged above the threshold level before initializing the handset.

20

10. The system of claim 1, wherein the handset and base unit exchange messages during the initialization in accordance with a message format comprising a plurality of fields.

11. In a wireless telephone system having a base unit and one or more wireless handsets, the base unit comprising a base transceiver and a handset docking station having a wired interface, each handset comprising a handset transceiver, a method comprising
5 the steps of:

- (a) initializing a handset via the wired interface when the handset is physically docked in the docking station; and
- (b) conducting digital communications, over an RF channel,
10 between the base unit and the handset via the base unit and handset transceivers, respectively, only if the handset has previously been initialized by the base unit.

12. A base unit for communicating with one or more wireless handsets, each handset comprising a handset transceiver, comprising:

- (a) a base transceiver for digitally communicating over an RF channel with each handset via its handset transceiver only if the handset has previously been initialized by the base unit; and
- (b) a handset docking station having a wired interface, wherein
15 the base unit initializes the handset via the wired interface when the handset is physically docked in the docking station.

1/3




FIG. 1

200

MESSAGE NUMBER 4 BITS	MESSAGE TYPE 4 BITS	NEW/ EXISTING 1 BITS	LOCAL NUMBER 3 BITS	32 BIT ID	ACK MESSAGE 5 BITS	SCRAMBLER SEED 8 BITS	UNUSED 7 BITS	8 BIT CRC
201	202	203	204	205	206	207	208	209

FIG. 2




FIG. 3

400




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/18059

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04M1/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 304 998 A (PHILIPS NV) 1 March 1989 see column 2, line 29 - column 3, line 3	1,8,10
Y	see column 4, line 5-10; figure 1 see column 5, line 43 - column 6, line 49; figure 5	2,3,11, 12
A	see column 6, line 18-22 ---	9
Y	US 5 495 520 A (KOJIMA SUSUMU) 27 February 1996 see abstract; figure 1 see column 2, line 5-54 ---	2,3
Y	US 5 625 888 A (RUETHER RALF ET AL) 29 April 1997 see column 2, line 10-41; claim 1 ---	11,12
A	---	4
	-/-	

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

^o Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

8 December 1998

Date of mailing of the international search report

18/12/1998

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

De Biolley, L

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/18059

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 301 573 A (NIPPON ELECTRIC CO) 1 February 1989 see column 1, line 32 - column 2, line 3 -----	6,7
A	US 5 371 783 A (HEUNG CHARLEY ET AL) 6 December 1994 see abstract see column 3, line 13-17 see column 3, line 54 - column 5, line 57 -----	1,5,8, 11,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int'l Application No

PCT/US 98/18059

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP 0304998	A 01-03-1989	GB 2209109 A		26-04-1989
		DE 3882182 A		12-08-1993
		DE 3882182 T		27-01-1994
		HK 140294 A		16-12-1994
		JP 1071331 A		16-03-1989
		KR 9702755 B		10-03-1997
		SG 146694 G		16-06-1995
		US 4905272 A		27-02-1990
US 5495520	A 27-02-1996	JP 2531349 B		04-09-1996
		JP 7038955 A		07-02-1995
US 5625888	A 29-04-1997	DE 4236778 A		05-05-1994
		AU 673202 B		31-10-1996
		AU 5148093 A		24-05-1994
		CA 2148278 A		04-05-1994
		CA 2148287 A		11-05-1994
		WO 9410785 A		11-05-1994
		DE 59306696 D		10-07-1997
		DK 667078 T		29-12-1997
		EP 0667078 A		16-08-1995
		ES 2103491 T		16-09-1997
		FI 952050 A		28-04-1995
		JP 2726160 B		11-03-1998
		JP 7508631 T		21-09-1995
EP 0301573	A 01-02-1989	JP 1036130 A		07-02-1989
		JP 2564839 B		18-12-1996
		JP 1129557 A		22-05-1989
		JP 1926895 C		25-04-1995
		JP 6054925 B		20-07-1994
		AU 594624 B		08-03-1990
		CA 1291834 A		05-11-1991
		DE 3880038 A		13-05-1993
		HK 143194 A		23-12-1994
		SG 153194 G		28-04-1995
		US 4864599 A		05-09-1989
US 5371783	A 06-12-1994	CA 2059734 A,C		30-11-1992
		CA 2151516 A		30-11-1992
		GB 2257332 A,B		06-01-1993
		GB 2268370 A,B		05-01-1994
		JP 7087561 A		31-03-1995
		US 5297203 A		22-03-1994