



US010009635B2

(12) **United States Patent**
Lee

(10) **Patent No.:** **US 10,009,635 B2**
(45) **Date of Patent:** ***Jun. 26, 2018**

(54) **METHODS AND APPARATUS FOR GENERATING SIGNATURES TO IDENTIFY MEDIA CONTENT USING TEMPORAL SIGNAL CHARACTERISTICS**

(58) **Field of Classification Search**
None
See application file for complete search history.

(71) Applicant: **The Nielsen Company (US), LLC**,
New York, NY (US)

(56) **References Cited**
U.S. PATENT DOCUMENTS

(72) Inventor: **Morris Lee**, Palm Harbor, FL (US)

3,919,479 A 11/1975 Moon et al.
4,602,297 A 7/1986 Reese
(Continued)

(73) Assignee: **The Nielsen Company (US), LLC**,
New York, NY (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days. days.

WO 2005/041109 5/2005
WO 2005/046201 5/2005

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **15/431,463**

European Patent Office, "Extended European Search Report," issued in connection with European Application No. 09013712.6, Feb. 19, 2013, 8 pages.

(22) Filed: **Feb. 13, 2017**

(Continued)

(65) **Prior Publication Data**
US 2017/0155934 A1 Jun. 1, 2017

Primary Examiner — Hoang Vu A Nguyen Ba
(74) *Attorney, Agent, or Firm* — Hanley, Flight and Zimmerman, LLC

Related U.S. Application Data

(63) Continuation of application No. 14/537,566, filed on Nov. 10, 2014, now Pat. No. 9,576,197, which is a (Continued)


(57) **ABSTRACT**

(51) **Int. Cl.**
H04N 21/234 (2011.01)
H04N 21/442 (2011.01)
(Continued)

Methods and apparatus to identify media content using temporal signal characteristics are disclosed. An example method includes generating a reference signature based on a reference signal corresponding to known media, generating sums based on peaks in a media signal corresponding to media, identifying signal peaks based on the generated sums, generating a second signature based on normalized curve features, wherein the normalized curve features respectively correspond to the identified signal peaks at a corresponding temporal locations of the corresponding signal peak, and determining whether the media signal corresponds to the reference signal based on a comparison of the reference signature and the second signature.

(52) **U.S. Cl.**
CPC **H04N 21/23418** (2013.01); **G06K 9/0053** (2013.01); **G06K 9/00543** (2013.01);
(Continued)

15 Claims, 14 Drawing Sheets



Related U.S. Application Data

continuation of application No. 13/337,890, filed on Dec. 27, 2011, now Pat. No. 8,887,191, which is a continuation of application No. 12/261,899, filed on Oct. 30, 2008, now Pat. No. 8,108,887.

2009/0234649	A1 *	9/2009	Goodhew	G10L 19/018 704/243
2010/0115542	A1	5/2010	Lee	
2012/0096482	A1	4/2012	Lee	
2015/0067712	A1	3/2015	Lee	

OTHER PUBLICATIONS

Goss et al., "Spectral Retrieval by Fuzzy Matching," Analytical Proceedings Including Analytical Communications, vol. 31, Jan. 1994, 4 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 13/337,890, dated Jan. 27, 2014, 23 pages.

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 13/337,890, dated Jul. 9, 2014, 18 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 12/261,899, dated Apr. 21, 2011, 19 pages.

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 12/261,899, dated Dec. 12, 2011, 20 pages.

European Patent Office, "Communication pursuant to Article 94(3) EPC," issued in connection with European Patent Application No. 09 013 712.6, dated Sep. 28, 2016, 4 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 14/537,566, dated Jun. 18, 2015, 22 pages.

United States Patent and Trademark Office, "Non-Final Office Action," issued in connection with U.S. Appl. No. 14/537,566, dated Jan. 21, 2016, 7 pages.

United States Patent and Trademark Office, "Final Office Action," issued in connection with U.S. Appl. No. 14/537,566, dated Jul. 19, 2016, 7 pages.

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 14/537,566, dated Oct. 24, 2016, 20 pages.

United States Patent and Trademark Office, "Notice of Allowance," issued in connection with U.S. Appl. No. 14/537,566, dated Nov. 13, 2015, 6 pages.

(51) **Int. Cl.**

G06K 9/00 (2006.01)
H04N 21/439 (2011.01)
H04N 21/84 (2011.01)

(52) **U.S. Cl.**

CPC ... **H04N 21/4394** (2013.01); **H04N 21/44204** (2013.01); **H04N 21/84** (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,697,209	A	9/1987	Kiewit et al.	
5,581,658	A *	12/1996	O'Hagan	G06K 9/00536 704/232
5,612,729	A *	3/1997	Ellis	G06K 9/00711 725/18
6,226,608	B1	5/2001	Fielder et al.	
6,512,796	B1	1/2003	Sherwood	
6,513,161	B2	1/2003	Wheeler et al.	
6,597,405	B1	7/2003	Iggulden	
6,968,564	B1	11/2005	Srinivasan	
7,065,544	B2	6/2006	Moreno	
7,174,293	B2	2/2007	Kenyon et al.	
7,194,752	B1	3/2007	Kenyon et al.	
7,647,604	B2	1/2010	Ramaswamy	
8,108,887	B2	1/2012	Lee	
8,769,294	B2 *	7/2014	Samari	H04H 60/37 348/161
8,887,191	B2	11/2014	Lee	
9,576,197	B2	2/2017	Lee	
2005/0044561	A1 *	2/2005	McDonald	H04H 60/58 725/18
2005/0238320	A1 *	10/2005	Shultz	H04N 5/76 386/213
2006/0195861	A1 *	8/2006	Lee	G06K 9/00523 725/19

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

1

**METHODS AND APPARATUS FOR
GENERATING SIGNATURES TO IDENTIFY
MEDIA CONTENT USING TEMPORAL
SIGNAL CHARACTERISTICS**

RELATED APPLICATIONS

This patent arises from a continuation of U.S. patent application Ser. No. 14/537,566, filed Nov. 10, 2014 (now U.S. Pat. No. 9,576,197), which is a U.S. patent application Ser. No. 13/337,890, filed Dec. 27, 2011 (now U.S. Pat. No. 8,887,191), which is a continuation of U.S. patent application Ser. No. 12/261,899, filed Oct. 30, 2008 (now U.S. Pat. No. 8,108,887). The entireties of U.S. patent application Ser. No. 14/537,566, U.S. patent application Ser. No. 13/337,890, and U.S. patent application Ser. No. 12/261,899 are incorporated herein by reference.

FIELD OF THE DISCLOSURE

The present disclosure relates generally to identifying media content and, more specifically, to methods and apparatus for identifying media content using temporal signal characteristics.

BACKGROUND

The metering of media content (e.g., television programs, radio programs, audio information, video information, etc.) is typically performed by collecting consumption records (e.g., viewing records) or other consumption information from a group of statistically selected households. These viewing records are typically generated by identifying the media content displayed in these households.

Some techniques for identifying displayed media content are based on the use of audio and/or video signatures. In general, signature-based media content identification techniques use one or more characteristics of presented (but not yet identified) media content to generate a substantially unique signature (e.g., a series of digital values, a waveform, etc.) for that content. The signature information for the content being presented or rendered is then typically compared to signature information generated for known media content. When a substantial match is found, the media content can, with a relatively high probability, be identified as the known media content having substantially matching signature information.

Although the use of signatures to identify consumed media content is growing, known computationally efficient signature-based program identification techniques are not sufficiently reliable because these known techniques typically ignore important distinguishing characteristics of the media signal. As a result, such known techniques may limit or prevent the identification of media content and/or may result in an incorrect identification of that content.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of an example system within which the media content identification apparatus and methods described herein may be implemented.

FIG. 2 is a block diagram of an example system that may be used to implement the monitored site of FIG. 1.

FIG. 3 is a flow diagram illustrating an example method to generate and collect signatures.

2

FIG. 4 is a block diagram illustrating an example manner in which the audio signature processor of FIG. 2 may be implemented.

FIG. 5 is a flow diagram illustrating an example method to process audio signatures.

FIG. 6 is a flow diagram illustrating an example method to select media content.

FIG. 7 is a flow diagram illustrating an example method to generate signatures.

FIG. 8 is a flow diagram illustrating an example method to generate an interval sum.

FIG. 9 is an example graph that depicts an audio signal that may be processed by the example signature generator shown in FIG. 4.

FIG. 10 illustrates an example graph that depicts zero crossing data that may be generated by the example signature generator of FIG. 4 from an audio signal.

FIG. 11 illustrates the example smoothed zero crossing energy curve of FIG. 10 and peaks identified from the smoothed zero crossing energy curve.

FIG. 12 illustrates an example signature generated by the audio signature processor of FIG. 4 utilizing the peaks illustrated in FIG. 11.

FIG. 13 is a block diagram of another example implementation of the audio signature processor of FIG. 2.

FIG. 14 is a flowchart illustrating an example method to identify media content.

DETAILED DESCRIPTION

For purposes of clarity, the following discussion describes systems, methods, apparatus, and articles of manufacture for identifying media content using temporal characteristics of an audio signal. However, the systems, methods, apparatus, and articles of manufacture described herein may be extended and/or modified to use temporal characteristics of any signal associated with the media content. For example, temporal characteristics of a video signal and/or a digital signal may be used instead of the example audio signal described herein.

Some example systems, methods, apparatus, and articles of manufacture described herein may be used to generate a signature from a media content signal by identifying the peaks and zero crossings of the media content signal and generating sums of the peaks. The sums may then be smoothed to form a curve, and the amplitudes or magnitudes and temporal locations of peaks in the curve may be identified to generate normalized curve features with equal height at the locations of the peaks. The height of the example signatures is set to zero at locations other than the locations of the peaks. The generated signatures may then be correlated with or compared to reference signatures to generate an index. If a correlation or comparison yields an index higher than a threshold, it may be determined that the media content signal is the same as the media content represented by the reference signature.

FIG. 1 is a block diagram of an example system 100 within which the media content identification apparatus and methods described herein may be implemented. The example system 100 shown in FIG. 1 includes a content delivery/distribution system 102 that receives video and/or audio content from a plurality of media content providers 104 and 106. The content delivery/distribution system 102 may be any form of audio and/or video content delivery/distribution system. For example, the content delivery/distribution system 102 may include a radio broadcast station, a television broadcast station, a point-to-point network, a

multipoint network, etc. The media content providers **104** and **106** may provide media content such as television programs, advertisements, audio (e.g., radio) programs, still image information (e.g., web pages), etc. in known manners to the content delivery/distribution system **102**. The content delivery/distribution system **102** may transmit one or more media signals containing digital and/or analog media content information to a reference site **108** and at least one monitored site **110** via respective communication paths or links **112** and **114**.

The communication paths or links **112** and **114** may include any combination of hardwired or wireless links such as, for example, satellite links, wireless land-based links, cable links, the Internet, etc. The signals conveyed via the links **112** and **114** may contain multi-program analog signals and/or digital data streams, which are commonly employed with existing broadcast systems as well as other types of media content delivery/distribution systems.

As shown in FIG. 1, the reference site **108** may include a plurality of receivers (e.g., set-top boxes or the like) **116**, **118** and **120** that simultaneously demodulate, demultiplex and/or decode audio, video and/or other information received via the communication link **112** from the content delivery/distribution system **102**. In one example, each of the receivers **116**, **118** and **120** receives audio information associated with a different portion of the media content (e.g., a different program) that is currently being transmitted (e.g., broadcast) and provides the audio information to a reference site processor **122**. For example, the receiver **116** may provide audio information associated with a first program while the receivers **118** and **120** provide audio information associated with respective second and third programs. In any case, the reference site processor **122** is configured to control and/or has information indicating to which portion of the media content (e.g., which channel, program, etc.) conveyed via the link **112** each of the receivers **116**, **118** and **120** is currently tuned.

In general, the reference site processor **122** includes the apparatus and methods described herein for collecting or generating reference signature information for a plurality of simultaneously broadcast programs. The reference site processor **122** sends the generated or collected reference signature information to a central processing facility **124** via a communication link **126**. In turn, the central processing facility **124** may store the reference signature information in a database **130** and, as described in greater detail below, may process the reference signature information together with information received from the reference site processor **122** to generate information related to the consumption of media content.

The monitored site **110** could be, for example, a statistically selected home, business, etc. containing a television, a radio, a computer, etc. However, it should be recognized that, while the monitored site **110** is depicted in FIG. 1 as receiving media content from a remotely situated content delivery/distribution system **102** (e.g., a broadcast station) via the communication link **114**, the monitored site **110** may alternatively or additionally receive media content from one or more local media content delivery systems or devices **128**. The local sources **128** may include one or more DVRs, DVD players, VCRs, etc. In addition, while the example system **100** shown in FIG. 1 depicts a single monitored site (i.e., the monitored site **110**), multiple monitored sites may receive media content via the link **114** and may be communicatively coupled to the central processing facility **124**.

FIG. 2 is a block diagram of an example system **200** that may be used to implement the monitored site **110** of FIG. 1.

As shown in FIG. 2, the example system **200** includes a media delivery, presentation or output device **202** such as, for example, a television or a video monitor that receives a media content signal **203**, which may be derived directly or indirectly via the communication link **114** of FIG. 1. For example, the media content signal **203** may be provided by a low noise block coupled to a satellite receiving dish in the case where the link **114** is a satellite communication link. A receiver, decoder or set-top box **204** may be serially interposed between the media content signal **203** received via the link **114** and the output device **202**. For example, in the case where the media content signal **203** received via the link **114** is a digital satellite or cable television transmission, the set-top box **204** demodulates the broadcast signal, demodulates multi-program data streams and selectively parses video and/or audio data packets associated with a desired channel and/or program. The selected data packets are processed to form an output signal **206** that can be processed and output (e.g., played, displayed, or otherwise presented) by the output device **202**. For example, in the case where the output device **202** is a television, the output signal **206** may be a composite video signal, a component video signal, an S-video signal, a red, green, blue (RGB) signal, a digital visual interface (DVI) signal, a high definition multimedia interface (HDMI) signal, or any other displayable or renderable video signal applied to the appropriate input(s) of the output device **202**. In the case where the media content signal **203** received via the link **114** is a conventional analog television transmission or signal, the set-top box **204** may not be required and the media content signal **203** may be directly coupled to the output device **202** (e.g., directly coupled to UHF/VHF inputs). In addition to signal processing functions, the set-top box **204** may also perform access control functions such as, for example, determining the media content to which a user of the example system **200** is permitted access to based on subscription status or subscription information associated with the example system **200**, generating displayable program guide information, etc.

The example system **200** also includes an audio signature processor **208** that may be configured to perform audio signature collection or generation, comparison and/or signature match detection functions to identify the media content (e.g., what channel, program, etc.) presented or delivered by the output device **202**. More specifically, the audio signature processor **208** receives the media content signal **203** and an audio output signal **210**, which may be provided directly by the output device **202**. The audio output signal **210** contains audio information associated with the media content currently consumed via or presented by the output device **202**. For example, in the case where the media content signal **203** received via the link **114** is delivered via a broadcast signal, the audio information provided by the audio output signal **210** may be associated with a television channel or program to which the example system **200** is currently tuned. Alternatively, the audio signature processor **208** may be coupled to an acoustic transducer **212** such as, for example, a microphone that is proximate to an acoustic output device (e.g., a speaker) associated with the output device **202**. In that case, the acoustic transducer **212** supplies an audio output signal **214** containing information associated with the media content currently presented by the output device **202** instead of, or in addition to, the audio output signal **210**.

As described in greater detail below, the audio signature processor **208** generates media content signature information, and may also collect or generate reference signature information from the media content signal **203** received via

the link 114. In some examples, the audio signature processor 208 sequentially generates reference signatures for programs, channels or, more generally, media content extracted or otherwise derived from the media content signal 203 and compares the reference signatures to the signature information associated with the media content currently being consumed via the output device 202. If the comparison of reference signature information to the signature information associated with the media content currently being consumed yields at least a substantial match, the audio signature processor 208 may identify the media content currently being consumed as the media content (e.g., the channel or program) associated with the reference signature information to which the currently viewed media content signature information is substantially matched.

The audio signature processor 208 is coupled to a site unit 218 via a communication link or connection 220. The audio signature processor 208 periodically or continuously sends consumption information (e.g., media content, channel and/or program information) associated with media content presented by or consumed via the output device 202 to the site unit 218. In turn, the site unit 218 processes the consumption information it receives from the audio signature processor 208 and sends, for example, consumption records or information to a central facility such as, for example, the central processing facility 124 of FIG. 1, via a communication link 222. The communication link 222 may include one or more wireless communication links (e.g., cellular, satellite, etc.), hardwired communication links (e.g., phone lines), or any other combination of communication hardware and technology platforms that employ any desired combination of communication protocols.

While FIG. 2 depicts the audio signature processor 208 as being located at a monitored site, some or all of the functions of the audio signature processor 208 can be distributed among a plurality of physical locations. For instance, as discussed in greater detail in connection with the example system shown in FIG. 4 below, the reference signature generation function, the signature comparison function and/or the signature match detection function may be performed by different physical systems, some or all of which may be located in different physical locations.

FIG. 3 is a flow diagram illustrating an example method 300 to generate and collect signatures. The example method 300 may be executed by the example monitored site 200 of FIG. 2 to generate and collect signatures. Initially, the audio signature processor 208 of FIG. 2 obtains (e.g., generates, collects, etc.) signatures or signature information from a plurality of signals (e.g., the audio output signals 210 and/or 214, and the media content signal 203) (block 302). As described in greater detail in connection with FIG. 5 below, the signatures output by the audio signature processor 208 are sent to the site unit 218 of FIG. 2 via the communication link or connection 220 of FIG. 2. The site unit 218 adds the signatures, received from the audio signature processor 208, to a collection of signatures (block 304). Such a collection of signatures may be implemented using a database file, a text file, a serialized data structure, or one (or any combination) of many well-known data storage mechanisms or techniques. The signatures stored in the collection may be time stamped and stored along with other consumption information such as, for example, channel numbers, program identification information, etc.

If the site unit 218 determines that all the required signatures have not been collected (block 306), the site unit 218 returns control to the audio signature processor 208 and waits for the additional signatures to be obtained (block

302). On the other hand, if the site unit 218 determines that all required signatures have been collected (block 306), the site unit 218 sends the collection of signatures to the central processing facility 124 of FIG. 1 via the link 222 of FIG. 2 (block 308). The site unit 218 may determine at block 306 whether all signatures have been collected by using a time limit, such as a number of minutes, hours, days, weeks, months, etc., to delimit when all signatures that have been collected are ready to be sent to the central processing facility 124. After sending the collection of signatures at block 308, the site unit 218 may return control to block 302 and continue to obtain additional signatures.

While FIG. 3 depicts an example manner by which signatures are collected or generated for a period of time and then sent in groups to the central processing facility 124, other manners of conveying signature information to the central processing facility 124 may be used instead. For example, signatures may be collected and conveyed to the central processing facility 124 on a continuous basis (e.g., on a streaming basis) rather than in groups sent on a periodic basis. However, any other suitable manner of conveying signatures may be used instead. Additionally, as noted above in connection with FIG. 1, the central facility 124 may perform statistical analyses using the collected signatures to derive media content consumption behavior information, or any other desired information, therefrom.

FIG. 4 is a more detailed block diagram that illustrates an example manner in which the audio signature processor 208 shown in FIG. 2 may be implemented. The example audio signature processor 208 of FIG. 4 includes a media content selector 402 (e.g., a scanning tuner) that receives the media content signal 203 (e.g., the reference signal), which may contain a plurality of channels and audio and/or video programs available for consumption (e.g., viewing, listening, etc.), and selects a portion of the media content contained therein (e.g., a channel, program, etc.) for further processing. In particular, in the case where the media content signal 203 is a multi-program analog signal, the media content selector 402 may vary a demodulator mixing frequency to selectively tune to particular channels and programs. On the other hand, if the media content signal 203 is a multi-program digital data stream, the media content selector 402 may include digital receiver functions that demodulate, demultiplex and selectively parse the data stream to extract audio and/or video data packets associated with particular channels or programs. In either case, the techniques for processing such multi-program analog signals and digital signals are well known and, thus, are not described in greater detail herein.

In general, the media content selection process performed by the media content selector 402 results in the sequential generation of signature information for a plurality of channels and/or media programs. Also, generally, the media content selection process (as described in greater detail below in connection with FIG. 5) continues until the audio signature processor 208 determines that a substantial match has been identified (i.e., that the media content currently being consumed via the output device 202 of FIG. 2 can be identified with a relatively high degree of certainty), or until the audio signature processor 208 determines that a substantial match cannot be identified (e.g., all available media content has been selected, processed to form audio signatures and none of those audio signatures substantially matches the signature information of the media content currently being consumed). In one example, the media content selection performed by the media content selector 402 may be based on a predetermined numerical sequence

(e.g., a sequence of channel numbers or program numbers). In another example, the media content selection may be based on a probability of matching. For example, the media content selector **402** may select channels associated with recently consumed media content. Additionally or alternatively, the media content selector **402** may select channels based on the historical frequency with which media content has been consumed via those channels.

The media content selector **402** outputs a media content signal **404** to a signature generator **406**. The media content signal **404** contains audio information associated with the media content currently selected by the media content selector **402**. The signature generator **406** processes the received audio information to generate audio signature information therefrom. As described in greater detail below, the signature generator **406** uses one or more characteristics (e.g., peak magnitudes, zero crossings, temporal characteristics) of one or more audio features of the signal **404** to generate signatures or signature information.

The example signature generator **406** uses the signal **404** to generate a signature characteristic of the signal **404**. To this end, the example signature generator **406** identifies signals peaks and zero crossings in each of several time intervals of the signal and sums the magnitudes of the signal peaks. The signature generator **406** then generates a curve based on the interval sums, smoothes the curve, and generates a signature by generating a normalized curve feature (e.g., triangular-shaped peak) at a temporal location of identified peaks in the smoothed curve, each of which has a normalized height (i.e., magnitude) and width. The signature has a height of zero at locations other than the normalized curve features. The resulting signatures are substantially uniquely characteristic of the media content contained within the signal **404** and, thus, may be used as a reference to compare the media content currently selected by the media content selector **402** to the media content currently being consumed by an audience member (e.g., via the audio output signals **210** and **214**).

A second signature generator **408** receives an audio output signal from the output device **202** (e.g., the audio output signal **210** or, alternatively, the signal **214** from the acoustic transducer **212**). As described above, the signals **210** and **214** are associated with or representative of the media content being presented by or consumed via the output device **202**. The signature generator **408** is substantially the same or identical to the signature generator **406** and, thus, generates audio signatures or information in a substantially similar or identical manner to that of the signature generator **406**.

A time stamper **410** may be configured to provide time stamps that are used by the signature generators **406** and **408** to time stamp signature data generated thereby. For example, each signature may have one or more time stamps associated therewith to facilitate subsequent signature comparison operations, correlation operations, matching operations, etc. In some examples, the time stamper **410** may generate relatively fine time intervals such as, for example, $\frac{1}{64}^{th}$ of one second increments, each of which may correspond to an absolute time or a relative time based on some reference time.

The signature generators **406** and **408** provide respective collections of signatures or signature information **412** and **414** to a signature comparator **416**. The signature comparator **416** compares the signature information **412** associated with or generated from the signal **404** to the signature information **414**, which is associated with or generated from one or both of the signals **210** and **214**. As noted above, the

signal **404** contains audio information associated with the media content (e.g., the channel, program, etc.) currently selected by the media content selector **402** from the media content signal **203**, and the signals **210** and **214** contain audio information associated with the media content currently being consumed via the output device **202**.

The comparison of audio signatures or information can be performed using any known or desired technique. In one example, the signature comparator **416** performs a normalized correlation between the reference signature information **412** and the signature information associated with the media content currently being consumed (i.e., the signature information **414**) over a predetermined interval or time period. If the result of the correlation is greater than or equal to a predetermined and/or dynamically determined threshold, the signature comparator **416** may provide an output signal or information **418** indicating that at least a substantial match has been detected (i.e., that the known media content currently selected by the media content selector **402** is substantially similar or identical to the media content currently being consumed via the output device **202**).

In another example, the signature comparator **416** calculates a difference signal or an error signal and then calculates an average error, a peak or maximum error, a standard deviation of error, or any other parameters characteristic of the differences, if any, between the signature information **412** and **414**. One or more of those parameters or characteristics may be compared to one or more threshold values and a determination of whether a substantial match or an identical match exists is indicated via the output **418** based on whether those parameters or characteristics are less than or greater than one or more of the threshold values.

The signature comparator **416** may also provide a feedback signal or information **420** to the media content selector **402** to facilitate the selection of media content (e.g., channels, programs, etc.) from the reference media content signal **203**. For example, in the event that the signature comparator **416** determines that the signature information **412** and **414** are not substantially similar or identical (i.e., the media content currently selected or tuned from the reference or media content signal **203** by the media content selector **402** does not substantially match the media content currently being consumed via the output device **202**), the feedback signal **420** may indicate a non-match condition to the media content selector **402**. In turn, the media content selector **402** may select or tune the next portion of media content (e.g., a next channel or program) in its media content search or scan sequence.

A media content identifier **424** is coupled to the audio signature comparator **416** and receives the match information output **418**. If the media content identifier **424** receives information (via the output **418**) indicating that a substantial or identical match has been identified, the media content identifier **424** determines the identity of the media content currently being consumed via the output device **202**. More specifically, the media content currently being consumed via the output device **202** may be identified as a particular broadcast channel, program, website, etc.

The media content identifier **424** is coupled to the site unit **218** (FIG. 2) and provides the media content identification information to the site unit **218** (FIG. 2) via the communication link **220**. The site unit **218** may use the media content identification information provided by the media content identifier **424** to generate consumption records and the like.

FIG. 5 is a flow diagram illustrating an example method **500** to process audio signatures. Initially, the signature generators **406** and **408** (FIG. 4) collect or generate signa-

tures and send the signatures to the signature comparator 416 (FIG. 4) (block 502). As described in greater detail in connection with FIG. 7 below, the signature collection or generation process (block 502) may use the characteristics of audio features such as, for example, temporal characteristics such as the temporal locations of signal peaks, zero crossings of the signal, and signal peak magnitudes.

The signature comparator 416 then compares signature information received from the signature generator 406 to signature information received from the signature generator 408 (block 504).

An example audio signal may be divided into a plurality of successive time intervals, each of which may be an equal or unequal number of seconds, minutes, etc. Signatures may be generated within the confines of these time intervals or sampling periods to facilitate efficient matching of signatures. For example, one signature per second may be generated. In such a case, a matching process can match a reference signal signature (e.g., a signature derived from the media content signal 203 of FIG. 4) generated within a time interval (e.g., a one second interval) to a consumption signal (e.g., one or both of the signals 210 and 214) signature generated within that same time interval. Alternatively or additionally, the signature matching algorithm can match the reference signal signature generated within a predetermined time interval to signatures generated for one or both of the consumption signals 210 and 214 of FIG. 4 over a plurality of time intervals.

Regardless of the particular signature matching technique employed by the signature comparator 416 of FIG. 4, if the signature comparator 416 determines that a signature received from the signature generator 406 of FIG. 4 matches (either substantially or identically) a signature received from the signature generator 408 (block 508), the signature comparator 416 conveys the matching information 418 to the media content identifier 424 of FIG. 4. In turn, the media content identifier 424 identifies the media content (e.g., the channel, program, etc.) to which the media content selector 402 of FIG. 4 is currently tuned and, thus, the media content currently being consumed via the output device 202 of FIG. 2 (block 510). For example, if the signature comparator 416 and the media content identifier 424 are implemented using separate processor-based systems, the signature comparator 416 may convey an interrupt to the media content identifier 424. Alternatively, if the signature comparator 416 and the media content identifier 424 are implemented within the same processor-based system, a software function call may be used to indicate to the media content identifier 424 that a matching condition has occurred within the signature comparator 416. After the media content has been identified (block 510), the media content identifier 424 sends the signatures or signature information along with any other desired media content identification information (e.g., program identifiers, time stamps, etc.) to the site unit 218 of FIG. 2 via the communication link or connection 220 (block 512).

On the other hand, if at block 508 the signature comparator 416 determines that a signature received from the signature generator 406 does not match a signature received from the signature generator 408, the signature comparator 416 transfers control to block 514 to invoke a media content selection process, which is described in greater detail in connection with FIG. 6. After the media content selector 402 performs the media content selection process at block 514, control returns to block 502, at which the signature generators 406 and 408 again generate signature information or signatures.

FIG. 6 is a flow diagram illustrating an example method 600 to select media content. Initially, the media content selector 402 of FIG. 4 identifies all media content portions (e.g., channels, programs, etc.) that have not yet been compared to the signal(s) (e.g., the signals 210 and 214) that are associated with the media content currently being consumed via the output device 202 of FIG. 2 (block 602). If the media content selector 402 determines that the reference media content signal 203 contains media content that has not yet been compared to the consumption signal 210, 214 (block 604), the media content selector 402 selects another portion of media content (e.g., tunes to another broadcast channel or program) (block 606) and then returns control to block 502 of FIG. 5 to generate a signature of the selected media content. The media content selector 402 may, for example, determine if broadcast channels exist that have not yet provided media content for comparison to the consumption signal (e.g., the signals 210 and 214) by scanning or searching a series of broadcast channels in a predetermined sequence. If the media content selector 402 determines at block 604 that all of the media content supplied on each of the available broadcast channels has already been compared to the media content currently being consumed (e.g., the signals 210 and 214), the media content selector 402 may perform one or more error handling techniques (block 608) and then return control to block 502 of FIG. 5.

FIG. 7 is a flow diagram illustrating an example method 700 to generate signatures. The example method 700 may be executed by the example audio signature processor 208 of FIG. 4 to implement block 502 of the example method 500 of FIG. 5. For clarity and brevity, this example will refer to the signature generator 408 generating a signature for the consumption signal 210 or 214. However, the example method 700 may also be implemented by the signature generator 406 to generate reference signatures for signals received from the media content selector 402.

The signature generator 408 receives a media content signal (i.e., the consumption signal 210, 214) for which a signature is to be generated (block 702). While receiving the media content signal, the signature generator 408 samples the media content signal to generate a digital representation of the signal (block 704). Block 704 may be omitted if, for example, the media content signal is received in digital format in block 702. After sampling the signal (if necessary), the signature generator 408 generates an interval sum for each of multiple intervals of the media content signal (block 706). For example, a media content signal may be sampled at 8000 samples per second (block 704). The signature generator 408 then creates signal intervals every $\frac{1}{64}$ th of one second, using 125 samples per interval. As described in detail below in FIG. 8, the generated interval sum is based on peak magnitudes and zero crossings of the samples in the corresponding interval. After generating the interval sum (block 706), the signature generator 408 determines whether there are more intervals in the media content signal (block 708). If there are more intervals (block 708), control returns to block 706 to generate another interval sum.

If there are no more intervals (block 708), the signature generator 408 smoothes the curve represented by the interval sums generated in block 706 (block 710). For example, the signature generator 408 may perform a low pass filter function to eliminate noise and other spurious interference or signal components that may adversely affect signature match detection. One particularly useful smoothing function may be based on the formula $y(t)=a*x(t)+b*y(t-1)$, where y represents the smoothed data, x represents the interval sum data generated in block 706, and $a+b=1$. Preferably,

$a=b=0.5$. However, a and b may be different values if desired to suit the needs of a particular application. A smoothing function such as the example function set forth above may be successively applied to the data multiple times (e.g., ten times) to achieve a desired smoothness.

The signature generator **408** then identifies the peaks (e.g., peak amplitude) in the smoothed curve (block **712**). For example, the signature generator **408** determines the temporal locations of the peaks in the smoothed curve and the associated magnitudes of the peaks. The signature generator **408** may use any technique to determine the peaks of the curve. When the peaks have been identified (block **712**), the signature generator **408** selects an identified peak (block **714**) and generates a normalized curve feature at the temporal location of the selected peak (block **716**). An example normalized curve feature represents a triangular-shaped peak having a width and a height, with the peak or apex of the triangle at the temporal location of the peak identified in block **712**. The signature generator **408** determines whether there are more peaks (block **718**) and, if so, returns control to block **714** to select another identified peak. The signature generator **408** continues to execute blocks **714-718** for each peak identified at block **712**. The example triangular-shaped peaks or curve features generated by the signature generator **408** at block **716** are substantially identical and, thus, have equal or substantially equal widths and heights.

When the signature generator **408** has generated normalized curve features for each identified peak (blocks **714-718**), the signature generator **408** sets the height of the signal curve to zero at all temporal locations that do not correspond to a signal peak (block **720**). Thus, the signal curve generated by the signature generator **408** resembles a series of triangular-shaped peaks having equal or substantially equal widths and heights regardless of the amplitude of the original signal peaks to which they correspond. After generating the signature, the example method **700** ends and control returns to block **504** of FIG. **5** to compare the generated signatures.

FIG. **8** is a flow diagram illustrating an example method **800** to generate an interval sum. The example method **800** may be used to implement block **706** of the example method of FIG. **7**. In the example implementation, the method **800** is called from block **704** after the signature generator **408** of FIG. **4** samples the received media content signal, or from block **708** when the signature generator **408** determines there are more intervals for which to determine an interval sum.

Initially, the signature generator **408** resets a sample interval sum to zero (block **802**) and then waits for a zero crossing of the audio signal for which a signature is to be generated (e.g., the example consumption signal **210** or **214**, the example reference signal **404**) (block **804**). Upon detection of a zero crossing (block **804**), the signature generator **408** continuously or periodically acquires the peak magnitude of the signal (block **806**) until a subsequent zero crossing is detected (block **808**). After the subsequent zero crossing is detected (block **808**), the example signature generator **408** adds the peak magnitude acquired at block **806** to an interval sum (block **810**). The signature generator **408** then determines if the sample interval has expired (e.g., a predetermined amount of time has elapsed, a predetermined number of samples have been acquired, etc.) (block **812**). The sample interval may be a predetermined amount of time during which peak magnitudes are summed. If the sample interval has not expired (block **812**), the signature generator **408** returns control to block **806** to continue to acquire the peak magnitude. On the other hand, if the sample

interval has expired (block **812**), the signature generator **408** sends the current interval sum to a smoothing function (block **814**) and then returns control to block **708** of the example method **700** of FIG. **7** to determine whether there are more intervals in the sampled media content signal.

FIG. **9** is an example graph **900** that depicts an audio signal **902** that may be processed by the example signature generator **406** or the example signature generator **408** shown in FIG. **4**. The described example of FIG. **9** will refer to the signature generator **408**. The signal **902** may be provided as the consumption signal **210** or **214** to the signature generator **408**. The signal **902** may additionally or alternatively be provided as the reference signal **404** to the signature generator **406** of FIG. **4**.

By way of example, at a time to the interval sum retained by the signature generator **408** is reset to zero. Then, at a first zero crossing **904**, the signature generator **408** resets the peak value to zero. Following the first zero crossing **904**, the signal **902** increases in magnitude until it reaches a peak value "a." The signature generator **408** retains the peak value "a" while the signal **902** decreases between "a" and a second zero crossing **906**. At the second zero crossing **906**, the signature generator **408** adds the magnitude of the peak value "a" to the interval sum and then resets its retained peak value to zero. Following the second zero crossing **906**, the signal **902** decreases in value until it reaches a negative peak "b," the absolute value of which is retained by the signature generator **408** as the signal **902** increases to zero at a third zero crossing **908**. At the third zero crossing **908**, the signature generator **408** adds the magnitude of "b" to the interval sum and resets the retained peak value to zero.

This process continues for peaks "d," through "k" up to time a t_1 (which may correspond to a predetermined time interval or sample interval including, for example, 125 samples), at which point the signature generator **408** stores the interval sum as a data point for later smoothing and resets the interval sum to zero. It should be noted that the peak "e" represents the peak magnitude between zero crossings and not "e' ("e" prime)".

The signature generator **408** repeats this process over the predetermined time interval, sample interval, or number of samples between times t_1 and t_2 for peaks "l" through "r," which results in a second sum being stored for smoothing. Of course, the process depicted graphically in FIG. **9** could be carried out for any desired number of intervals, which do not necessarily have to be immediately successive or contiguous. Further, in general, as the number of sums used to provide signature information for a particular audio signal increases, the certainty with which that signature uniquely identifies that particular audio signal increases.

FIG. **10** illustrates an example graph that depicts zero crossing data that may be generated by the example signature generator **408** of FIG. **4** from an audio signal such as, for example, the example signal **902** of FIG. **9**. More specifically, the sequence of interval sums generated by the signature generator **408**, which may be generally referred to as a zero crossing energy curve, is depicted at reference numeral **1002**. Again, as noted above, in the case where the signal **902** is processed as a series of discrete data values, the zero crossing energy curve **1002** has fewer discrete data values in any given time period or sample period because a plurality of samples or peak magnitude values from the signal **902** are summed to form each data value making up the zero crossing energy curve **1002**. In the case where 125 samples from the signal **902** are summed, a data reduction ratio of 125:1 (i.e., from the signal **302** to the zero crossing energy curve **1002**) is realized. A data reduction ratio of

125:1, using the 8000 samples per second sampling rate described above yields a 64 sample per second zero crossing energy curve **1002**. However, as noted above, any other data reduction ratio may be used instead. The zero crossing energy curve **1002** may then be processed by the signature generator **408** using a smoothing function to form a smoothed zero crossing energy curve **1004**.

FIG. **11** illustrates the example smoothed zero crossing energy curve **1004** of FIG. **10** and peaks identified from the smoothed zero crossing energy curve **1004**. The example smoothed zero crossing energy curve **1004** includes peaks **1102**, **1104**, **1106**, **1108**, and **1110**, which may be identified by the example signature generator **408** of FIG. **4**. After smoothing the zero crossing energy curve **1002** of FIG. **10**, the signature generator **408** identifies the peaks **1102-1110** formed by, for example, 500 samples at 64 samples per second.

FIG. **12** illustrates an example signature **1200** generated by the audio signature processor **208** of FIG. **4** utilizing the peaks **1102-1110** illustrated in FIG. **11**. The example signature **1200** includes normalized curve features **1202**, **1204**, **1206**, **1208**, and **1210** corresponding to respective signal peaks **1102**, **1104**, **1106**, **1108**, and **1110**. The normalized curve features **1202-1210** may be generated by the signature generator **408** by executing the example method **700** described in FIG. **7** based on the example audio signal **900** of FIG. **9** and the zero crossing energy curve **1002** of FIG. **10**.

As illustrated in FIG. **12**, the normalized curve features **1202**, **1204**, **1206**, **1208**, and **1210** have equal heights h and equal widths w . Further, the center location of each of the example normalized curve features **1202-1210** is at the temporal location of the respective curve peaks **1102**, **1104**, **1106**, **1108**, and **1110**. Additionally, the example signature **1200** has a height of zero at temporal locations other than those corresponding to normalized curve features. When the signature generator **408** has finished generating the example signature **1200** (e.g., via the example method **700** of FIG. **7**), the signature comparator **416** of FIG. **4** compares the signature **1200** to known signatures to identify the example audio signal **900**.

Although the example normalized curve features **1202-1210** of FIG. **12** have equal heights and widths, the normalized curve features **1202-1210** may be generated having, for example, heights equal to or proportional to the heights and/or temporal locations of the corresponding peaks, widths equal to or proportional to the heights and/or temporal locations of the corresponding peaks, and/or any combination thereof.

FIG. **13** is a block diagram of another example implementation of the audio signature processor **208** of FIG. **2**. The example audio signature processor **208** receives a media content signal (e.g., the consumption signal **210** and/or **214** of FIG. **2**, or the reference signal **404** of FIG. **4**), identifies the media content signal, and outputs consumption information to the site unit **218** of FIG. **2**. For ease of reference, the discussion of the example audio signature processor **208** of FIG. **13** will refer to the example consumption signal **210** of FIG. **2**. However, other signals (e.g., the signal **214** of FIG. **2**) could be processed by the audio signature processor **208**.

The example audio signature processor **208** shown in FIG. **13** receives a media content signal (e.g., the audio output signal or reference signal **203**, or the consumption signals **210** or **214** of FIG. **4**), which is sent to a signal conditioner **1302**. The signal conditioner **1302** may include analog and or digital circuitry for filtering (e.g., noise

filtering, anti-aliasing filtering, transient filtering, etc.). One particularly useful filtering circuit may provide a bandpass filter characteristic from 300 hertz to 3000 hertz. Additionally or alternatively, the signal conditioner **1302** may include protection circuitry (e.g., surge protection circuitry), level shifting circuitry, amplification circuitry, attenuation circuitry, or any other known or desired signal conditioning circuitry. Of course, the signal conditioner **1302** may be eliminated from the audio signature processor **208** in the event that the media content signals provided to the audio signature processor **208** do not require conditioning.

Conditioned signal(s) output by the signal conditioner **1302** are provided to a zero crossing detector **1304** and a peak detector **1306**. The zero crossing detector **1304** may use a one-shot multi-vibrator or the like to output a pulse to the peak detector **1306** each time a zero crossing occurs within the conditioned signal(s). The peak detector **1306** may be implemented using any desired peak detection circuit to detect peak signal magnitude. For example, in the case where the conditioned signals are analog signals, a diode, capacitor and bleed resistor combination may be used to detect peak value. On the other hand, in the case where the conditioned signals are digital values, the peak detector **1306** may simply retain the largest numerical value following a reset. The peak detector **1306** resets (e.g., to zero) in response to zero crossing pulses or other signals provided by the zero crossing detector **1304**. As a result, the peak detector **1306** outputs a series of signal peak magnitudes, each of which occurs between successive zero crossings.

A summer **1308** receives the series of peak signal magnitudes from the peak detector **1306** and generates interval sums of these peak signal magnitudes for each of the predetermined time intervals or sample intervals. In one example, the summer **1308** may sum a plurality of peak magnitudes (absolute values) occurring within a predetermined number of samples (e.g., 125 samples) collected at a predetermined rate (e.g., 8000 samples per second) from the conditioned signal. However, other sample sizes and sample rates may be used instead to suit the needs of a particular application. The summer **1308** outputs a series of positive interval sum values at a rate equal to the sample rate divided by the sample size for each interval sum. Thus, in the example where the sample rate is 8000 samples/second and the sample size per sum is 125, the summer **1308** provides interval sums at a rate of 64 per second. Additionally, as depicted in FIG. **13**, the summer **1308** may also receive a time stamp from a time stamper **1310** that enables the summer **1308** to associate time stamp values with one or more of the interval sums.

The example signature generator **208** may also include a smoother **1312** that performs a smoothing function on the series of sums output by the summer **1308**. For example, the smoother **1312** may perform a low pass filter function to eliminate noise and other spurious interference or signal components that may adversely affect signature match detection. The smoother **1312** may successively smooth the data multiple times (e.g., ten times) to achieve a desired smoothness.

The filtering performed by the smoother **1312** may be implemented using any desired combination of passive components (i.e., resistors, capacitors, inductors, etc.), active components (i.e., transistors, operational amplifiers, etc.) and/or digital components (i.e., digital logic, processing units, memory, etc.). There are many well-known analog and numerical (i.e., digital) filtering techniques that may be used to implement the smoother **1312** and, thus, such implementation details are not discussed in greater detail herein.

The example audio signature processor **208** further includes a peak identifier **1314** that receives the smoothed curve from the smoother **1312**. The peak identifier **1314** also receives time stamps from the time stamper **1310**. Using the time stamps, the peak identifier **1314** identifies the signal peak(s) in the smoothed curve and outputs the magnitude(s) and temporal location(s) of the identified peak(s) to a feature generator **1316**.

The feature generator **1316** receives the signal peaks and temporal location information, and generates normalized curve features based on the signal peaks and temporal locations. An example set of normalized curve features that may be generated by the feature generator **1316** is shown in FIG. **12**. After generating the normalized curve features, the feature generator **1316** generates the remaining signature time by assigning a height or magnitude of zero to the signature locations not associated with the normalized curve features (e.g., triangular-shaped portions). The feature generator **1316** then outputs the signature to a correlator **1318**.

The correlator **1318** receives the signature from the feature generator **1316** and performs a comparison between the signature and one or more reference signatures. An example comparison that may be performed by the correlator **1318** is a normalized cross-correlation function. However, the correlator **1318** may also perform other comparisons, such as calculating the Mahalanobis distance between the signatures. The reference signatures may be generated by applying a known reference media signal to the signal conditioner **1302**, zero crossing detector **1304**, peak detector **1306**, summer **1308**, smoother **1312**, peak identifier **1314**, and the feature generator **1316** to generate a signature of the reference media as described above. Alternatively or additionally, the correlator **1318** may receive one or more reference signatures from a reference signature database **1320**. The reference signature database **1320** may be provided to store known signatures of media content to facilitate identification of an unidentified consumption signal. The correlator **1318** generates an index (e.g., a cross-correlation coefficient) based on the correlation of the consumption signal with a reference signal.

The index value generated by the correlator **1318** is sent to an index comparator **1322**. The index comparator **1322** determines whether the index is greater than a threshold indicative of a match. For example, if the correlator **1318** performs a correlation on a signature generated by the feature generator **1316** with a reference signature from the reference signature database **1320**, the correlator **1318** may calculate an index of 0.47. The index comparator **1322** compares the index 0.47 to an example threshold value of 0.45. Because the calculated index is greater than the threshold, the index comparator **1322** determines that the media content represented by the generated signature is the same as the media represented by the reference signature. If the index is not greater than the threshold, the correlator **1318** may then perform another correlation with the generated signature and another reference signature to generate another index. Correlation and comparison may repeat until matching media content is determined.

The example threshold used by the index comparator **1322** may be a predetermined value or may be dynamically generated and modified. For example, a first threshold value may be used to determine media exposure during time intervals in a given time period (e.g., every 15 seconds during a day). In the example, using the first threshold value, the audio signature processor **208** is capable of identifying media content during 50% of a monitored time period. The index comparator **1322** may then use a second threshold

value to identify media content for time intervals that could not be identified using the first threshold value, thus enabling the index comparator **1322** to identify media content during certain time intervals.

After the index comparator **1322** has identified the media associated with the consumption signal, the index comparator **1322** outputs consumption information to, for example, the site unit **218** of FIG. **2**.

FIG. **14** is a flowchart illustrating an example method **1400** to identify media content. The example method **1400** may be executed by the example audio signature processor **208** described in FIG. **13** to identify media content associated with a consumption signal (e.g., the consumption signal **210** of FIG. **2**). The example method **1400** begins by receiving a media content signal (e.g., via the signal conditioner **1302**), such as the consumption signal **210** or the reference signal **203** (block **1402**). On receiving the media content signal (block **1402**), the example signal conditioner **1302**, the example zero crossing detector **1304**, the example peak detector **1306**, the example summer **1308**, the example time stamper **1310**, the example smoother **1312**, the example peak identifier **1314**, and the example feature generator **1316** generate a signature of the media content signal (block **1404**). Block **1404** may be performed by executing the example method **700** of FIG. **7** using the example signal conditioner **1302**, the example zero crossing detector **1304**, the example peak detector **1306**, the example summer **1308**, the example time stamper **1310**, the example smoother **1312**, the example peak identifier **1314**, and the example feature generator **1316**.

After generating the signature from the media content signal (block **1404**), the example correlator **1318** of FIG. **13** selects a reference signature from, for example, the reference signature database **1320** or a signature generated from a reference signal (block **1406**). Once a reference signature is selected, the correlator **1318** performs a correlation on the generated signature and the reference signature to generate a correlation index (block **1408**). The example correlation index is passed to the index comparator **1322**, which determines if the correlation index is greater than a threshold (block **1410**). If the index is greater than the threshold (block **1410**), the index comparator **1322** determines the media content signal is the same as the reference signal (block **1412**), and the example method **1400** may end.

However, if the index comparator **1322** determines the index is not greater than the threshold (block **1410**), the correlator **1318** determines whether there are additional reference curves for comparison (block **1414**). Additional reference curves may come from additional media sources or from the reference signature database **1320**. If there are additional reference curves for comparison (block **1414**), control returns to block **1406** to select a reference signature. If there are no additional reference curves (block **1414**), the index comparator **1322** determines that the media signal is unknown (block **1416**). In such a case, the unknown media content signal and/or the signature generated therefrom may be sent to a central location (e.g., the site unit **218** of FIG. **2**) for additional processing.

Although the example normalized curve features are shown as triangular-shaped peaks, other shapes, heights, and/or widths may be used to, for example, further increase detection accuracy or increase correlation speed.

The example systems, methods, apparatus, and articles of manufacture are useful in identifying unknown media content based on known media content. In one example application, the systems described above may be used to verify exposure of advertisements in a retail store. The example

application may have an audio and video playback device (e.g., a television set) to show video advertisements to in-store customers. Advertisers that want to verify that their paid advertisements are given sufficient exposure in-store may utilize the example systems, methods, apparatus, and articles of manufacture to monitor the advertisements shown on the playback device and identify them by comparing each exposed advertisement to a small library (e.g., 10-20 advertisements) of known advertisements. Each identified advertisement is then counted and the total counts can be reported to the advertiser to verify sufficient exposure.

More generally, the example systems, methods, apparatus, and articles of manufacture may be used to identify a clip or short segment of unidentified media content within a large library of known media content. Such identification may be useful in digital rights management, in detecting copyright infringement, or in any other application that may benefit from media content identification. To identify a clip or short segment, the example system generates a signature of at least a portion of the media to be identified, and performs a correlation or other comparison between the signature and a library of reference signatures.

Although this patent discloses example systems including software or firmware executed on hardware, it should be noted that such systems are merely illustrative and should not be considered as limiting. For example, it is contemplated that any or all of these hardware and software components could be embodied exclusively in hardware, exclusively in software, exclusively in firmware or in any combination of hardware, firmware and/or software. Accordingly, while the above specification described example systems, methods, apparatus, and articles of manufacture, the examples are not the only way to implement such systems, methods, apparatus, and articles of manufacture. Therefore, although certain example systems, methods, apparatus, and articles of manufacture have been described herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, methods, apparatus and articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents.

What is claimed is:

1. An apparatus, comprising:
 - a peak detector to detect peaks of a media signal during time intervals and to output absolute values of the detected peaks;
 - a summer to generate interval sums respective to the time intervals based on the absolute values;
 - a peak identifier to identify signal peaks based on the interval sums; and
 - a feature generator to generate a first signature to identify the media signal, the first signature including first normalized curve features based on the signal peaks, at least one of the peak detector, the summer, the peak identifier or the feature generator being implemented with hardware, wherein the first normalized curve features have respective heights, widths, and center locations, the respective heights are equal, and the respective widths are equal.
2. The apparatus of claim 1, further including a correlator to generate an index based on a comparison of the first normalized curve features of the first signature and second normalized curve features of a reference signature.
3. The apparatus of claim 2, further including an index comparator to compare the index to a threshold to determine whether the first signature matches the reference signature.

4. The apparatus of claim 1, further including a smoother to smooth the interval sums.

5. The apparatus of claim 1, wherein the first signature has a substantially zero value except at temporal locations corresponding to the normalized curve features.

6. A method, comprising:
 - determining, by executing one or more instructions with a processor, absolute values of peaks of a media signal, the peaks detected during respective time intervals;
 - determining, by executing one or more instructions with the processor, interval sums respective to the time intervals based on the absolute values;
 - identifying, by executing one or more instructions with the processor, signal peaks based on the interval sums; and
 - generating, by executing one or more instructions with the processor, a first signature to identify the media signal, the first signature including first normalized curve features based on the signal peaks, wherein the first normalized curve features have respective heights, widths, and center locations, the respective heights are equal, and the respective widths are equal.

7. The method of claim 5, further including generating an index based on a comparison of the first normalized curve features of the first signature and second normalized curve features of a reference signature.

8. The method of claim 6, further including determining whether the first signature matches the reference signature based on the index.

9. The method of claim 5, further including smoothing the interval sums.

10. The method of claim 5, wherein the first signature has a substantially zero value except at temporal locations corresponding to the normalized curve features.

11. A computer readable storage device or storage disk comprising instructions, which, when executed, cause a processor to at least:

- determine absolute values of peaks of a media signal, the peaks detected during respective intervals;
- determine interval sums respective to the time intervals based on the absolute values;
- identify signal peaks based on the interval sums; and
- generate a first signature to identify the media signal, the first signature including first normalized curve features based on the signal peaks, wherein the first normalized curve features have respective heights, widths, and center locations, the respective heights are equal and the respective widths are equal.

12. The computer readable storage device or storage disk of claim 11, further including instructions to cause the processor to generate a match index based on a comparison of the first normalized curve features of the first signature and second normalized curve features of a reference signature.

13. The computer readable storage device or storage disk of claim 12, further including instructions to cause the processor to determine whether the first signature matches the reference signature based on the match index.

14. The computer readable storage device or storage disk of claim 11, further including instructions to cause the processor to smooth the interval sums.

15. The computer readable storage device or storage disk of claim 11, wherein the first signature has a substantially zero value except at temporal locations corresponding to the normalized curve features.