



- (51) **International Patent Classification:**
E21B 7/08 (2006.01) *E21B 47/02* (2006.01)
- (21) **International Application Number:**
PCT/US2009/040802
- (22) **International Filing Date:**
16 April 2009 (16.04.2009)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/045,478 16 April 2008 (16.04.2008) US
12/423,439 14 April 2009 (14.04.2009) US
- (71) **Applicant (for all designated States except US):** **BAKER HUGHES INCORPORATED** [US/US]; P.O. Box 4740, Houston, TX 77210-4740 (US).
- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** **SANTELMANN, Bernd** [DE/DE]; Altenwahlen 21, 29693 Boehme (DE).
- (74) **Agents:** **CARSON, Matt, W.** et al.; Baker Hughes Incorporated, P.O. Box 4740, Houston, TX 77210-4740 (US).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ,

EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) **Title:** STEERING DEVICE FOR DOWNHOLE TOOLS



- (57) **Abstract:** An apparatus for drilling a wellbore may include a first section, a second section, and a third section, all of which are rotatably interconnected with pivot bearings and positioned along a drill string. The second section and the third section may be configured to form a controllable bend angle in the drill string. The first section, the second section, and the third section may be configured as sleeves that surround a portion of the drill string. One or more sections may include locking pads that selectively engage a wall of the wellbore. A hydraulic locking device for controlling a direction of rotation of the second section may include one or more brake elements and a reverse spinning sleeve. A first brake element may be used engage the reverse spinning sleeve and a second brake element may be used to engage a drive shaft.

STEERING DEVICE FOR DOWNHOLE TOOLS

BACKGROUND OF THE DISCLOSURE

1. Field of the Disclosure

5 This disclosure relates generally to oilfield downhole tools and more particularly to modular drilling assemblies utilized for directionally drilling wellbores.

2. Description of the Related Art

10 To obtain hydrocarbons such as oil and gas, boreholes or wellbores are drilled by rotating a drill bit attached to the bottom of a drilling assembly (also referred to herein as a "Bottom Hole Assembly" or "BHA"). The drilling assembly is attached to the bottom of a tubing, which is usually either a jointed rigid pipe or a relatively flexible spoolable tubing commonly referred to in the art as "coiled tubing." The string, which includes the
15 tubing and the drilling assembly, is usually referred to as the "drill string." When jointed pipe is utilized as the tubing, the drill bit is rotated by rotating the jointed pipe from the surface and/or by a mud motor contained in the drilling assembly. In the case of a coiled tubing, the drill bit is rotated by the mud motor. During drilling, a drilling fluid (also referred to as "mud") is
20 supplied under pressure into the tubing. The drilling fluid passes through the drilling assembly and then discharges at the drill bit bottom. The drilling fluid provides lubrication to the drill bit and carries to the surface rock pieces disintegrated by the drill bit in drilling the wellbore. The mud motor is rotated by the drilling fluid passing through the drilling assembly. A drive
25 shaft connected to the motor and the drill bit rotates the drill bit.

A substantial proportion of current drilling activity involves drilling deviated and horizontal wellbores to more fully exploit hydrocarbon reservoirs. Such boreholes can have relatively complex well profiles. To drill such complex boreholes, some drilling assemblies utilize a plurality of independently
30 operable pads to apply force on the wellbore wall during drilling of the wellbore to maintain the drill bit along a prescribed path and to alter the

drilling direction. For rotating drill stings, such pads may be positioned on a non-rotating sleeve disposed around the rotating drive shaft. These pads are moved radially to apply force on the wellbore in order to guide the drill bit and/or to change the drilling direction outward by electrical devices or electro-hydraulic devices.

The present disclosure addresses the certain other apparatus and methods for steering a drill bit.

SUMMARY OF THE DISCLOSURE

In aspects, the present disclosure provides an apparatus conveyed via a drill string configured to form a wellbore in an earthen formation. The apparatus may include a first section positioned along the drill string; a second section coupled to the first section; and a third section rotatably coupled to the second section. The second section may be selectively rotated relative to the first section. Also, the second section and the third section may be configured to form a controllable bend angle in the drill string. In embodiments, the first section, the second section and the third section may be configured as sleeves that surround a portion of the drill string. In aspects, the first section, the second section and the third section may be configured to be rotatably mounted on the drill string. In configurations, the first section and the third section may include at least one anchoring element or pad that is configured to engage a wall of the wellbore. In arrangements, a hydraulic locking device may be used to control a direction of rotation of the second section. The hydraulic locking device may include one or more brake elements and a reverse spinning sleeve. A first brake element may be used to engage the reverse spinning sleeve and a second brake element may be used to engage a drive shaft. In embodiments, a pivot bearing connects one or both of: the first section to the second section, and the second section to the third section. The pivot bearing may be configured to selectively lock adjoining sections.

In aspects, the present disclosure provides a method for forming a wellbore in an earthen formation. The method may include positioning a

first section, a second section, and a third section on a drill string; rotatably coupling the first section to the second section; rotatably coupling the second section to the third section; conveying the drill string into the wellbore; and rotating the second section relative to the third section to
5 form a controllable bend angle in the drill string.

Illustrative examples of some features of the disclosure thus have been summarized rather broadly in order that the detailed description thereof that follows may be better understood, and in order that the contributions to the art may be appreciated. There are, of course, additional features of
10 the disclosure that will be described hereinafter and which will form the subject of the claims appended hereto.

BRIEF DESCRIPTION OF THE DRAWINGS

For detailed understanding of the present disclosure, references should be made to the following detailed description of the preferred embodiment,
15 taken in conjunction with the accompanying drawings, in which like elements have been given like numerals and wherein:

FIGS. 1A-C schematically illustrate an operation of a steering device made in accordance with one embodiment of the present disclosure;

20 **FIG. 2** isometrically illustrates elements of a steering device made in accordance with one embodiment of the present disclosure;

FIG. 3 schematically illustrates a sectional view of a portion of a steering device made in accordance with one embodiment of the present disclosure;

25 **FIG. 4** schematically illustrates a sectional view of a more detailed portion of a steering device made in accordance with one embodiment of the present disclosure; and

FIG. 5 schematically illustrates a drilling system using a steering device made in accordance with one embodiment of the present
30 disclosure.

DETAILED DESCRIPTION OF THE DISCLOSURE

The present disclosure relates to devices and methods for directional drilling of wellbores. The present disclosure is susceptible to embodiments of different forms. There are shown in the drawings, and
5 herein will be described in detail, specific embodiments of the present disclosure with the understanding that the present disclosure is to be considered an exemplification of the principles of the disclosure, and is not intended to limit the disclosure to that illustrated and described herein. Further, while embodiments may be described as having one or more
10 features or a combination of two or more features, such a feature or a combination of features should not be construed as essential unless expressly stated as essential.

Referring now to **FIGS. 1A-1C**, there is schematically illustrated a steering unit **100** that incorporates aspects of the present teachings. As will be
15 described in greater detail below, the steering unit **100** points a drill bit in a selected drilling direction by bending a section of the steering unit **100**. The bend, which may be on the order of a one degree to a ten or more degree angle relative to a long axis **13** of a wellbore, can be rotated as needed to obtain a desired direction according to a selected reference
20 frame or orientation (e.g., azimuthal direction, gravity tool face, etc.). The steering unit **100** may include a first or upper section **110**, a second or middle section **120** and a third or lower section **130**. The upper section **110** may include adjustable pads **140** that lock the upper section **110** into engagement with a wall **15** of the wellbore **12**. The lower section **130** may
25 also include pads **142**. The pads **140**, **142** may be fixed or adjustable.

A pivot bearing **102** separates the upper section **110** from the middle section **120** and a pivot bearing **104** separates the middle section **120** from the lower section **130**. Each pivot bearing **102**, **104** allows their respective adjacent sections to selectively rotate relative to one another. The pivot
30 bearings **102**, **104** may include internal devices that may allow such selective interlocking. The pivot bearing **102** allows relative rotation

between the upper section **110** and the middle section **120**, which controls the direction of drilling by controlling the direction (e.g., azimuth, inclination, gravity) in which the drill bit (not shown) is pointing. The pivot bearings **102**, **104** may also be used to compensate for undesirable sleeve rotation due to friction. The pivot bearing **104** allows relative rotation between the middle section **120** and the lower section **130**, which controls the magnitude of tilt or angular bend in the steering device **100**.

Referring to **FIG. 1A**, the steering device **100** is shown in a "straight ahead" drilling mode. The middle section **120** and the lower section **130** have end faces **122** and **132** respectively that incorporate a tilt of the same angle. The tilt is relative to a plane perpendicular to the axial tool line **106**. As shown, the end faces **122** and **132** have the slope of their respective tilts in the same direction, which has the effect of canceling their relative tilts. Thus, the axial centerline **106** of the steering device **100** is generally parallel with a centerline **13** of the wellbore **12**.

Referring to **FIG. 1B**, the steering device **100** is shown in a directional drilling mode of operation. Upper section **110** and middle section **120** have end faces **112** and **123** which are perpendicular to the axial tool line **106**, thereby enabling relative rotation of the upper section **110** and middle section **120** without affecting a magnitude of the bend angle. As shown, with respect to middle section **120** and lower section **130**, end faces **122** and **132** have their direction of tilt aligned to maximize a tilt or bend angle caused in the steering device **100**. That is, the end faces **122** and **132** have the slope of their respective tilts in opposite directions, which has the effect of compounding their relative tilts. This may be achieved by rotating the middle section **120** one-hundred eighty degrees relative to the upper section **110**. Thus, the axial centerline **106** of the steering device **100** is generally angularly offset with the centerline **13** of the wellbore **12** and the drilling direction will generally follow the axial centerline **106**, which will change the trajectory of the wellbore **12**. In some embodiments, the amount of bend angle to be applied to the steering device **100** may be

fixed. In other embodiments, the bend angle may be adjustable. That is, an offset between zero and one hundred eighty degrees will produce a proportionately smaller tilt or bend angle in the steering device **100**.

As should be appreciated, the relative rotation between the middle section
5 **120** and the lower section **130** controls the magnitude of a change in drilling direction relative to a long axis **13** of the wellbore. The relative rotation between the upper section **110** and the middle section **120**, on the other hand, controls the direction for drilling.

In **FIG. 1C**, the drilling direction is shown in what may be considered a
10 wellbore highside direction. This drilling direction may be changed or adjusted by rotating the middle section **120** relative to the upper section **110**. Referring to **FIG. 1C**, the end faces **122** and **132** still have their direction of tilt aligned to maximize a tilt or bend angle caused in the steering device **100**. However, the middle section **120** has been rotated
15 one-hundred eighty degrees relative to the upper section **110**. The drilling direction will still generally follow the axial centerline **106** to change the trajectory of the wellbore **12**. However, the azimuthal drilling direction is now the wellbore lowside direction, or one hundred eighty degrees offset from the direction shown in **FIG. 1B**. It should be appreciated that the
20 relative rotation between the upper section **110** and the middle section **120** may be set at any value between zero and three hundred sixty degrees to drill in a desired azimuthal direction.

Referring now to **FIG. 2**, there is shown the steering device **100** in greater detail. As described previously, the steering unit **100** may include an
25 upper section **110**, a middle section **120** and a lower section **130**. The pivot bearing **102** provides a rotational interface between the upper section **110** and the middle section **120** and the pivot bearing **104** provides a rotational interface between the middle section **120** and the lower section **130**. The upper section **110** may include adjustable pads **140** that are
30 circumferentially arranged along its outer circumference. The lower section **130** may also include pads **142**. An upper drive shaft **150** may be

configured to connect with a drill string (not shown) and a lower drive shaft **152** may be configured to connect with and rotate a drill bit (not shown).

In embodiments, the pads **140**, **142** may be configured to extend and engage a wall of the wellbore to maintain the upper section **110** and / or the lower section **130** stationary relative to the wellbore. In one arrangement, the pad **140** may be formed as ribs that pivot or rotate into engagement with the wellbore wall **15** (**FIG. 1A**) to generate and/ or support the steering force. In other embodiments, the pad **140** may be formed as a piston or pad that extends or retracts in a radial direction.

5 Suitable actuating devices for the pads **140** may include hydraulic actuators, electric motors, and electro-mechanical linkages. The pads **140** may be independently adjustable or may move in unison. While three pads **140** may be utilized in many applications, some applications may require a greater or a fewer number of pads **140**. Generally speaking, the

10 pads **140** and **142** are merely illustrative of any number of anchoring members that may be suitable. Other anchoring members may include inflatable packers, slips, etc.

Referring now to **FIG. 3**, there is sectionally shown the steering device **100** illustrated in **FIG. 2**. The steering device **100** surrounds and is supported

20 by the upper drive shaft **150** and the lower drive shaft **152**. The upper drive shaft **150** and the lower drive shaft **152** include a bore **154** through which pressurized drilling mud pumped from the surface is conveyed to the drill bit (not shown). The upper section **110** is shown with illustrative pads **140** and a power unit **144**, such as a hydraulic actuator, electrical actuator, etc.

25 Similarly, the lower section **130** is shown with illustrative pads **142** that a power unit **146**, such as a hydraulic actuator, an electrical actuator, etc. The pads may be independently actuated to engage the well wall **15**. The steering device **100** may include thrust bearings (not shown) and journal bearings (not shown) and other suitable elements that allow the upper

30 drive shaft **150** and the lower drive shaft **152** to rotate when the steering device **100** is anchored to the wellbore wall via the pads **140** and/or **142**.

Referring now to **FIG. 4**, there is sectionally shown the middle section **120** in greater detail. In one arrangement, the middle section **120** has a face **122** that engages the lower section **130** via the pivot bearing **104**, and a face **124** that engages the upper section **110** via the pivot bearing **102**. A
5 face **106** of the pivot bearing **104** includes an incline that is complementary to an incline of the middle section face **122**. By inclined, it is meant that the surfaces of the face **122** and **106** are not perpendicular to an axial tool line. In embodiments, the space between seals (not shown) in **FIG. 4** may be pressurized in order to lock the pivot bearings **102**, **104**.

10 In embodiments, the rotation of the upper drive shaft **150** may be utilized to selectively rotate several components of the steering device **100**. For example, the steering device **100** may include a hydraulic locking or clamping device **136** that selectively rotates the middle section **120** relative to the upper section **110** as well as selectively rotating the middle section
15 **120** relative to the lower section **130**. When actuated, the hydraulic clamping device **136** may engage and rotate with the upper drive shaft **150**. Thus, the pivot bearing **104** and lower section **130**, for example, may rotate one-hundred eighty degrees relative to the middle section **120** when the hydraulic clamping device **136** is engaged. Also, the steering device
20 **100** may include a reverse spinning sleeve **121** that may be used to rotate the middle section **120** in a direction counter to the rotation of the upper drive shaft **150**. In one arrangement, the reverse spinning sleeve **121** may include a pinion **114** disposed on the upper section **110** that engages a gear **116** disposed on the middle section **120**. The rotation of the upper
25 drive shaft **150**, therefore is converted into a counter-rotation of the reverse spinning sleeve **121**. Brake elements **160**, **161** may be disposed in the middle section **120** to prevent or allow rotation in a selected rotational direction (e.g., clockwise or counter clockwise). These brake elements **160**, **161** may be used to control, adjust or change tool face
30 direction and / or tilt angle by selectively engaging the middle section **120** with the drive shaft **150** in a manner described below.

Referring still to **FIG. 4**, it should be appreciated that the combined steering device **100** provides a relative movement between its sections **110**, **120**, **130** and the upper drive shaft **150**. In embodiments, the reverse spinning sleeve **121** is positioned between the middle section **120** and the drive shaft **150**. The reverse spinning sleeve **121** is configured to rotate in a direction opposition of the rotation of the drive shaft **150** as previously described. In an exemplary mode of operation, to turn the middle section **120** anticlockwise, the brake pad **160** is actuated to increase the friction between the middle section **120** and the reverse spinning sleeve **121**. Thus, the middle section **120** rotates with the reverse spinning sleeve **121**. In another exemplary mode of operation, to turn the middle section **120** clockwise, the brake **161** is actuated to apply friction to the drive shaft **150**. Thus, the middle section **120** rotates with the drive shaft **150** in a clockwise direction. Suitable stops or bumpers may be used to control the stopping positions for the middle section **120**. It should be appreciated that the brake elements **160**, **161** need not lock the middle section **120** with either the reverse spinning sleeve **121** or the drive shaft **150**. The brake elements **160**, **161** may be configured to provide sufficient friction to generate frictional forces of sufficient magnitude to cause the middle section **120** to rotate.

An exemplary mode for adjusting tool face may include actuating the pads **140** of the upper section **110** to engage a wellbore wall, actuating the pivot bearing **102** to allow free rotation between the upper section **110** and the middle section **120**, and deactivating the pads **142** of the lower section **130** to disengage from the wellbore wall. Thereafter, the brake pads **160** or **161** may be activated to rotate the middle section **120** and the lower section **130**.

An exemplary mode for adjusting tilt angle correction may include actuating the pads **140** of the upper section **110** to engage a wellbore wall, actuating the pivot bearings **102** and **104** to allow free rotation between the upper section **110** and the middle section **120** as well as the middle

section **120** and the lower section **130**, and activating the pads **142** of the lower section **130** to engage from the wellbore wall. Thereafter, the brake pads **160** or **161** may be activated to rotate the middle section **120** relative to the lower section **130** to increase or decrease the bend angle.

- 5 In another embodiment not shown, hydraulic power may be used to energize a suitable rotation device. For example, the hydraulic actuator **146** (**Fig. 3**) may supply pressurized hydraulic fluid to a piston cylinder arrangement. The displacement of the piston may be used to rotate the pivot bearing **104**. Likewise, the hydraulic actuator **144** may supply
- 10 pressurized hydraulic fluid to a piston cylinder arrangement that rotates the pivot bearing **102**.

Referring now to **FIG. 2**, in embodiments, the steering device **100** may include electronics and other equipment that enable surface and / or closed-loop downhole control. In one arrangement, an electronics unit **200**

15 may be positioned in the upper section **110** and include processing devices that may estimate the relative position and orientation of the elements forming the steering unit **100** based on sensor measurements. The sensors may be distributed along the steering device **100**. Exemplary sensors for determining position or orientation parameters include

20 rotational speed sensors (RPM), azimuth sensors, inclination sensors, gyroscopic sensors, magnetometers, and three-axis accelerometers. The electronics unit **200** may include a controller **202** that receives inputs such as sensor signals and command signals and operates the devices such as the hydraulic clamp **136** or the drive unit to obtain the desired position and

25 orientation for the steering device **100**.

Referring now to **FIG. 5**, there is shown an embodiment of a drilling system **10** utilizing a steerable drilling assembly or bottomhole assembly (BHA) **80** made according to one embodiment of the present disclosure to directionally drill wellbores. While a land-based rig is shown, these

30 concepts and the methods are equally applicable to offshore drilling systems. The system **10** shown in **FIG. 5** has a drilling assembly **80**

conveyed in a borehole **12**. The drill string **22** includes a jointed tubular string **24**, which may be drill pipe or coiled tubing, extending downward from a rig **14** into the borehole **12**. The drill bit **82**, attached to the drill string end, disintegrates the geological formations when it is rotated to drill the borehole **12**. The drill string **22**, which may be jointed tubulars or coiled tubing, may include power and/or data conductors such as wires for providing bi-directional communication and power transmission. The drill string **22** is coupled to a draw works **26** via a kelly joint **28**, swivel **30** and line **32** through a pulley (not shown). The operation of the drawworks **26** is well known in the art and is thus not described in detail herein.

During drilling operations, a suitable drilling fluid **34** from a mud pit (source) **36** is circulated under pressure through a channel in the drill string **22** by a mud pump **34**. The drilling fluid passes from the mud pump **38** into the drill string **22** via a desurger **40**, fluid line **42** and Kelly joint **28**. The drilling fluid **34** is discharged at the borehole bottom through an opening in the drill bit **82**. The drilling fluid **34** circulates uphole through the annular space **46** between the drill string **22** and the borehole **12** and returns to the mud pit **36** via a return line **48**. The drilling fluid acts to lubricate the drill bit **82** and to carry borehole cutting or chips away from the drill bit **82**. A sensor **S₁** typically placed in the line **42** provides information about the fluid flow rate. A surface torque sensor **S₂** and a sensor **S₃** associated with the drill string **22** respectively provide information about the torque and rotational speed of the drill string **22**. Additionally, sensor **S₄** associated with line **29** is used to provide the hook load of the drill string **22**.

A surface controller **50** receives signals from the downhole sensors and devices via a sensor **52** placed in the fluid line **42** and signals from sensors **S₁**, **S₂**, **S₃**, hook load sensor **S₄** and any other sensors used in the system and processes such signals according to programmed instructions provided to the surface controller **50**. The surface controller **50** displays desired drilling parameters and other information on a display/monitor **54**

and is utilized by an operator to control the drilling operations. The surface controller **50** contains a computer, memory for storing data, recorder for recording data and other peripherals. The surface controller **50** processes data according to programmed instructions and responds to user commands entered through a suitable device, such as a keyboard or a touch screen. The controller **50** is preferably adapted to activate alarms **56** when certain unsafe or undesirable operating conditions occur.

Still referring to **FIG. 5**, the sensor sub **86** may include sensors for measuring near-bit direction (e.g., BHA azimuth and inclination, BHA coordinates, etc.), dual rotary azimuthal gamma ray, bore and annular pressure (flow-on & flow-off), temperature, vibration/dynamics, multiple propagation resistivity, and sensors and tools for making rotary directional surveys. The formation evaluation sub **90** may includes sensors for determining parameters of interest relating to the formation, borehole, geophysical characteristics, borehole fluids and boundary conditions. These sensor include formation evaluation sensors (e.g., resistivity, dielectric constant, water saturation, porosity, density and permeability), sensors for measuring borehole parameters (e.g., borehole size, and borehole roughness), sensors for measuring geophysical parameters (e.g., acoustic velocity and acoustic travel time), sensors for measuring borehole fluid parameters (e.g., viscosity, density, clarity, rheology, pH level, and gas, oil and water contents), and boundary condition sensors, sensors for measuring physical and chemical properties of the borehole fluid.

The subs **86** and **90** may include one or memory modules, and a battery pack module to store and provide back-up electric power may be placed at any suitable location in the BHA **80**. Additional modules and sensors may be provided depending upon the specific drilling requirements. Such exemplary sensors may include an rpm sensor, a weight on bit sensor, sensors for measuring mud motor parameters (e.g., mud motor stator temperature, differential pressure across a mud motor, and fluid flow rate through a mud motor), and sensors for measuring vibration, whirl, radial

displacement, stick-slip, torque, shock, vibration, strain, stress, bending moment, bit bounce, axial thrust, friction and radial thrust. The near bit inclination devices may include three (3) axis accelerometers, gyroscopic devices and signal processing circuitry as generally known in the art.

5 These sensors may be positioned in the subs **86** and **90**, distributed along the drill pipe, in the drill bit and along the BHA **80**. Further, while subs **86** and **90** are described as separate modules, in certain embodiments, the sensors above described may be consolidated into a single sub or separated into three or more subs. The term "sub" refers merely to any
10 supporting housing or structure and is not intended to mean a particular tool or configuration.

Processor **202** processes the data collected by the sensor sub **86** and formation evaluation sub **90** and transmit appropriate control signals to the steering device **100**. The processor **202** may be configured to decimate
15 data, digitize data, and include suitable PLC's. For example, the processor may include one or more microprocessors that uses a computer program implemented on a suitable machine-readable medium that enables the processor to perform the control and processing. The machine-readable medium may include ROMs, EPROMs, EAROMs, Flash
20 Memories and Optical disks. Other equipment such as power and data buses, power supplies, and the like will be apparent to one skilled in the art. The processor **202** may positioned in the sensor sub **86** or elsewhere in the BHA **80**. Moreover, other electronics, such as electronics that drive or operate actuators for valves and other devices may also be positioned
25 along the BHA **80**.

The bidirectional data communication and power module ("BCPM") **88** transmits control signals between the BHA **80** and the surface as well as supplies electrical power to the BHA **80**. For example, the BCPM **88** provides electrical power to the steering device **100** and establishes two-
30 way data communication between the processor **202** and surface devices such as the controller **50**. In one embodiment, the BCPM **88** generates

power using a mud-driven alternator (not shown) and the data signals are generated by a mud pulser (not shown). The mud-driven power generation units (mud pursers) are known in the art and thus not described in greater detail. In addition to mud pulse telemetry, other suitable two-way
5 communication links may use hard wires (e.g., electrical conductors, fiber optics), acoustic signals, EM or RF. Of course, if the drill string **22** includes data and/or power conductors (not shown), then power to the BHA **80** may be transmitted from the surface.

In one configuration, the BHA **80** includes a drill bit **82**, a drilling motor **84**,
10 a sensor sub **86**, a bidirectional communication and power module (BCPM) **88**, and a formation evaluation (FE) sub **90**. To enable power and/or data transfer to the other making up the BHA **80**, the BHA **80** includes a power and/or data transmission line (not shown). The steering device **100** may be operated to steer the BHA **80** along a selected drilling
15 direction by applying an appropriate tilt to the drill bit **82**.

Referring now to **FIGS. 1A-C** and **4**, in an exemplary manner of use, the BHA **80** is conveyed into the wellbore **12** from the rig **14**. During drilling of the wellbore **12**, the steering device **100** steers the drill bit **82** in a selected direction. The drilling direction may follow a preset trajectory that is
20 programmed into a surface and/or downhole controller (e.g., controller **50** and/or controller **202**). The controller(s) use directional data received from downhole directional sensors to determine the orientation of the BHA **80**, compute course correction instructions if needed, and transmit those instructions to the steering device **100**.

25 An exemplary mode of operation of the steering unit **100** will now be described. As an arbitrary starting point, the drill string **22** may be drilling the wellbore without curvature, e.g., drilling a straight wellbore. In such a condition, the pivot bearing **104** is operated to set the face **132** of the lower section **130** in a position that cancels the tilt of the face of the middle
30 section **120**.

To initiate directional drilling, a drilling direction is first selected. This may be performed by first determining the directional information such as azimuth and inclination from the directional sensor on-board the BHA **80**. The drilling direction may be selected by a downhole controller and / or by
5 personnel at the surface. Thereafter, a downhole controller and / or personnel at the surface may determine the azimuthal orientation and the amount of tilt required to steer the drill string **22** in the selected direction. Thereafter, one or more controllers may determine the current angular or rotational positions of the pivot bearings **102** and **104**. Once the relative
10 angular positions have been determined, the control unit **200** may operate the hydraulic clamp **136** to shift the pivot bearing **104** into a one-hundred eighty degree offset relative to the face **122** of the middle section **120**. Next, the control unit **200** actuates the gear unit **116** to rotate the middle section **120** into a rotational alignment with the upper section **110** to obtain
15 the necessary azimuthal direction.

The relative alignment or position of the steering unit **100** and related components may be periodically or continually monitored by the control unit **200** or other downhole processors. The control unit **200** or other downhole processors may adjust the steering unit **100** to account for any
20 variations or discrepancies that may arise to thereby maintain the desired drilling direction. Similarly, if the direction of drilling requires change, the control unit **200** may operate the gear unit to set the desired azimuthal direction or actuate the hydraulic clamp to remove the tilt to the drill bit.

The foregoing description is directed to particular embodiments of the
25 present disclosure for the purpose of illustration and explanation. It will be apparent, however, to one skilled in the art that many modifications and changes to the embodiment set forth above are possible without departing from the scope of the disclosure. It is intended that the following claims be interpreted to embrace all such modifications and changes.

CLAIMS

What is claimed is:

- 1 1. An apparatus configured to be conveyed in a wellbore via a drill
2 string, comprising:
3 a first section;
4 a second section coupled to the first section, wherein the second
5 section is configured to be selectively rotated relative to the first
6 section; and
7 a third section rotatably coupled to the second section, wherein the
8 second section and the third section are configured to form a
9 controllable bend angle in the drill string.
- 1 2. The apparatus of claim 1 wherein the first section, the second
2 section and the third section are sleeves configured to surround a portion
3 of the drill string.
- 1 3. The apparatus of claim 1 wherein the first section includes at least
2 one anchoring element configured to anchor the first section to a wall of
3 the wellbore.
- 1 4. The apparatus of claim 1, further comprising a drive unit configured
2 to rotate the second section relative to the first section.
- 1 5. The apparatus of claim 1, further comprising a clamping device
2 configured to selectively rotate one of the first section and the third section
3 relative to the second section.
- 1 6. The apparatus of claim 5, further comprising a drive shaft through
2 the second section and wherein the clamping device is configured to
3 engage and rotate with the drive shaft.
- 1 7. The apparatus of claim 6, further comprising a spinning sleeve
2 configured to rotate the second section in a direction counter to a rotation
3 of the drive shaft.

1 8. The apparatus of claim 1, further comprising a brake element in the
2 second section configured to control rotation of the second section in a
3 selected direction.

1 9. The apparatus of claim 8 wherein the brake element is further
2 configured to selectively engage the second section to a drive shaft placed
3 in the second section to control one of a tool face direction and a tilt angle.

1 10. The apparatus according to claim 1, further comprising a pivot
2 bearing connecting one of: (i) the first section to the second section, and
3 (ii) the second section to the third section, wherein the pivot bearing is
4 configured to selectively lock adjoining sections.

1 11. The apparatus of claim 1 wherein the first section, the second
2 section and the third section are configured to be rotatably mounted on the
3 drill string.

1 12. A method for forming a wellbore in an earth formation, comprising:
2 positioning a first section, a second section, and a third section on a
3 drill string;
4 rotatably coupling the first section to the second section and the
5 second section to the third section;
6 conveying the drill string into the wellbore; and
7 rotating the second section relative to the third section to form a
8 controllable bend angle in the drill string.

1 13. The method of claim 12 wherein the first section, the second
2 section and the third section are configured as sleeves that surround a
3 portion of the drill string.

1 14. The method of claim 12, further comprising locking the first section
2 to a wall of the wellbore.

1 15. The method of claim 12, further comprising locking the second
2 section of a wall of the wellbore.

1 16. The method of claim 12, further comprising using a clamping device
2 to rotate the third section relative to the second section.

- 1 17. A system for forming a wellbore in an earth formation, comprising:
2 a drill string;
3 a first section, a second section coupled to the first section, wherein
4 the second section is configured to be selectively rotated relative to
5 the first section, and a third section rotatably coupled to the second
6 section, wherein the second section and the third section are
7 configured to form a controllable bend angle in the drill string.
- 1 18. The apparatus of claim 17, further comprising a drive unit
2 configured to rotate the second section relative to the first section.
- 1 19. The apparatus of claim 17, further comprising a clamping device
2 configured to selectively rotate one of the first section and the third section
3 relative to the second section.
- 1 20. The apparatus of claim 17, further comprising a brake element in
2 the second section configured to control rotation of the second section in a
3 selected direction.
- 1 21. The system of claim 17, further comprising a control unit configured
2 to control rotation of the second section relative to the third section.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4




FIG. 5