



US010141904B2

(12) **United States Patent**
Barabas et al.

(10) **Patent No.:** **US 10,141,904 B2**
(45) **Date of Patent:** ***Nov. 27, 2018**

(54) **METHOD AND SYSTEM FOR ACCURATE GAIN ADJUSTMENT OF A TRANSIMPEDANCE AMPLIFIER USING A DUAL REPLICA AND SERVO LOOP**

(58) **Field of Classification Search**
USPC 330/308, 110, 59
See application file for complete search history.

(71) Applicant: **Luxtera, Inc.**, Carlsbad, CA (US)
(72) Inventors: **Stefan Barabas**, West Melbourne, FL (US); **Joseph Balardeta**, Encinitas, CA (US); **Simon Pang**, San Diego, CA (US); **Scott Denton**, Carlsbad, CA (US)

(56) **References Cited**
U.S. PATENT DOCUMENTS
7,158,729 B2* 1/2007 Yokomizo H04B 10/6931 398/202
7,961,053 B1 6/2011 Tsai et al.
(Continued)

(73) Assignee: **Luxtera, Inc.**, Carlsbad, CA (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS
JP 2006/261866 A 9/2006
WO 2006/119786 A1 11/2006

(21) Appl. No.: **15/707,309**
(22) Filed: **Sep. 18, 2017**

OTHER PUBLICATIONS
European Patent Office, Communication with extended European Search Report in Application No. 16151743.8 dated May 20, 2016 (13 pages).
Primary Examiner — Hieu Nguyen
(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy

(65) **Prior Publication Data**
US 2018/0026597 A1 Jan. 25, 2018

(57) **ABSTRACT**
Methods and systems for accurate gain adjustment of a transimpedance amplifier using a dual replica and servo loop is disclosed and may include, in a transimpedance amplifier (TIA) circuit comprising a first TIA, a second TIA, and a third TIA, each comprising a configurable feedback impedance, and a control loop, where the control loop comprises a gain stage with inputs coupled to outputs of the first and second TIAs and an output coupled to the configurable feedback impedance of the second and third TIAs: configuring a gain level of the first TIA by configuring its feedback impedance, configuring a gain level of the third TIA by configuring a reference current applied to an input of the first TIA, and amplifying a received electrical signal to generate an output voltage utilizing the third TIA. The reference current may generate a reference voltage at one of the inputs of the gain stage.


Related U.S. Application Data

(63) Continuation of application No. 14/997,938, filed on Jan. 18, 2016, now Pat. No. 9,768,747.
(Continued)

(51) **Int. Cl.**
H03G 3/30 (2006.01)
H03F 3/08 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H03G 3/30** (2013.01); **H03F 1/086** (2013.01); **H03F 1/42** (2013.01); **H03F 1/56** (2013.01);
(Continued)

20 Claims, 6 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 62/125,290, filed on Jan. 16, 2015.

(51) **Int. Cl.**

H03F 1/42 (2006.01)

H03F 1/08 (2006.01)

H03F 1/56 (2006.01)

(52) **U.S. Cl.**

CPC *H03F 3/08* (2013.01); *H03F 3/082*
(2013.01); *H03F 3/087* (2013.01); *H03G*
3/3084 (2013.01); *H03F 2200/129* (2013.01);
H03F 2200/156 (2013.01); *H03F 2200/453*
(2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

9,030,263 B2 5/2015 Robinson
2006/0001493 A1 1/2006 Harms et al.
2014/0306760 A1 1/2014 Piepenstock

* cited by examiner

130




FIG. 1B







FIG. 1C



200




FIG. 2




FIG. 4

1

**METHOD AND SYSTEM FOR ACCURATE
GAIN ADJUSTMENT OF A
TRANSIMPEDANCE AMPLIFIER USING A
DUAL REPLICA AND SERVO LOOP**

CROSS-REFERENCE TO RELATED
APPLICATIONS/INCORPORATION BY
REFERENCE

This application is a continuation of U.S. application Ser. No. 14/997,938 filed on Jan. 18, 2016, which claims priority to and the benefit of U.S. Provisional Application 62/125,290 filed on Jan. 16, 2015, which is hereby incorporated herein by reference in its entirety.

FIELD

Certain embodiments of the disclosure relate to semiconductor photonics. More specifically, certain embodiments of the disclosure relate to a method and system for accurate gain adjustment of a transimpedance amplifier using a dual replica and servo loop.

BACKGROUND

As data networks scale to meet ever-increasing bandwidth requirements, the shortcomings of copper data channels are becoming apparent. Signal attenuation and crosstalk due to radiated electromagnetic energy are the main impediments encountered by designers of such systems. They can be mitigated to some extent with equalization, coding, and shielding, but these techniques require considerable power, complexity, and cable bulk penalties while offering only modest improvements in reach and very limited scalability. Free of such channel limitations, optical communication has been recognized as the successor to copper links.

Further limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of such systems with the present disclosure as set forth in the remainder of the present application with reference to the drawings.

BRIEF SUMMARY

A system and/or method for accurate gain adjustment of a transimpedance amplifier using a dual replica and servo loop, substantially as shown in and/or described in connection with at least one of the figures, as set forth more completely in the claims.

Various advantages, aspects and novel features of the present disclosure, as well as details of an illustrated embodiment thereof, will be more fully understood from the following description and drawings.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF
THE DRAWINGS

FIG. 1A is a block diagram of a photonically-enabled integrated circuit with accurate gain adjustment of transimpedance amplifiers using a dual replica and servo loop, in accordance with an example embodiment of the disclosure.

FIG. 1B is a diagram illustrating an exemplary photonically-enabled integrated circuit, in accordance with an example embodiment of the disclosure.

FIG. 1C is a diagram illustrating a photonically-enabled integrated circuit coupled to an optical fiber cable, in accordance with an example embodiment of the disclosure.

2

FIG. 2 is a block diagram of a photodiode sensed using a transimpedance amplifier with feedback impedance, in accordance with an example embodiment of the disclosure.

FIG. 3 illustrates a transimpedance amplifier with accurate gain adjustment using a dual replica and servo loop, in accordance with an example embodiment of the disclosure.

FIG. 4 is a flow chart illustrating example steps in providing accurate gain adjustment for a transimpedance amplifier using a dual replica and servo loop, in accordance with an example embodiment of the disclosure.

DETAILED DESCRIPTION

Certain aspects of the disclosure may be found in a method and system for accurate gain adjustment of a transimpedance amplifier using a dual replica and servo loop. Exemplary aspects of the disclosure may comprise, in a transimpedance amplifier (TIA) circuit comprising a first TIA, a second TIA, and a third TIA, each comprising a configurable feedback impedance, and a control loop, where the control loop comprises a gain stage with inputs coupled to outputs of the first and second TIAs and an output coupled to the configurable feedback impedance of the second and third TIAs: configuring a gain level of the first TIA by configuring its feedback impedance, configuring a gain level of the third TIA by configuring a reference current applied to an input of the first TIA, and amplifying a received electrical signal to generate an output voltage utilizing the third TIA. The reference current may generate a reference voltage at one of the inputs of the gain stage. The reference voltage may control the output of the gain stage that is coupled to the configurable feedback impedance of the third TIA. The configurable impedance of the first TIA may comprise a configurable array of resistors and the configurable impedances of the second and third TIAs may each comprise a resistor and a transistor. The configurable impedances of the second and third TIAs may be configured by configuring a gate voltage of the transistor utilizing the output of the gain stage. The output voltage may be coupled to a first input of a second gain stage wherein a second input of the second gain stage is coupled to an output of a fourth TIA. A differential signal may be generated utilizing the output voltage and an output of the second gain stage. The output of the second gain stage may be configured by configuring an input current of the third TIA. The electrical signal may be received from a photodetector.

FIG. 1A is a block diagram of a photonically-enabled integrated circuit with accurate gain adjustment of transimpedance amplifiers using a dual replica and servo loop, in accordance with an example embodiment of the disclosure. Referring to FIG. 1A, there are shown optoelectronic devices on a photonically-enabled integrated circuit **130** comprising optical modulators **105A-105D**, photodiodes **111A-111D**, monitor photodiodes **113A-113D**, and optical devices comprising couplers **103A-103C** and grating couplers **117A-117H**. There are also shown electrical devices and circuits comprising amplifiers **107A-107D**, analog and digital control circuits **109**, and control sections **112A-112D**. The amplifiers **107A-107D** may comprise transimpedance and limiting amplifiers (TIA/LAs), for example.

In an example scenario, the photonically-enabled integrated circuit **130** comprises a CMOS photonics die with a laser assembly **101** coupled to the top surface of the IC **130**. The laser assembly **101** may comprise one or more semiconductor lasers with isolators, lenses, and/or rotators for directing one or more continuous-wave (CW) optical signals to the coupler **103A**. A CW optical signal may comprise an

unmodulated optical signal comprising a coherent frequency component at a wavelength λ_1 , for example. The photonically enabled integrated circuit **130** may comprise a single chip, or may be integrated on a plurality of die, such as with one or more electronics die and one or more photonics die.

Optical signals are communicated between optical and optoelectronic devices via optical waveguides **110** fabricated in the photonically-enabled integrated circuit **130**. Single-mode or multi-mode waveguides may be used in photonic integrated circuits. Single-mode operation enables direct connection to optical signal processing and networking elements. The term "single-mode" may be used for waveguides that support a single mode for each of the two polarizations, transverse-electric (TE) and transverse-magnetic (TM), or for waveguides that are truly single mode and only support one mode. Such one mode may have, for example, a polarization that is TE, which comprises an electric field parallel to the substrate supporting the waveguides. Two typical waveguide cross-sections that are utilized comprise strip waveguides and rib waveguides. Strip waveguides typically comprise a rectangular cross-section, whereas rib waveguides comprise a rib section on top of a waveguide slab. Of course, other waveguide cross section types are also contemplated and within the scope of the disclosure.

In an example scenario, the couplers **103A-103C** may comprise low-loss Y-junction power splitters where coupler **103A** receives an optical signal from the laser assembly **101** and splits the signal to two branches that direct the optical signals to the couplers **103B** and **103C**, which split the optical signal once more, resulting in four roughly equal power optical signals.

The optical power splitter may comprise at least one input waveguide and at least two output waveguides. The couplers **103A-103C** shown in FIG. 1A illustrate 1-by-2 splitters, which divide the optical power in one waveguide into two other waveguides evenly. These Y-junction splitters may be used in multiple locations in an optoelectronic system, such as in a Mach-Zehnder interferometer (MZI) modulator, e.g., the optical modulators **105A-105D**, where a splitter and a combiner are needed, since a power combiner can be a splitter used in reverse.

The optical modulators **105A-105D** comprise Mach-Zehnder or ring modulators, for example, and enable the modulation of the continuous-wave (CW) laser input signal. The optical modulators **105A-105D** may comprise high-speed and low-speed phase modulation sections and are controlled by the control sections **112A-112D**. The high-speed phase modulation section of the optical modulators **105A-105D** may modulate a CW light source signal with a data signal. The low-speed phase modulation section of the optical modulators **105A-105D** may compensate for slowly varying phase factors such as those induced by mismatch between the waveguides, waveguide temperature, or waveguide stress and is referred to as the passive phase, or the passive biasing of the MZI.

In an example scenario, the high-speed optical phase modulators may operate based on the free carrier dispersion effect and may demonstrate a high overlap between the free carrier modulation region and the optical mode. High-speed phase modulation of an optical mode propagating in a waveguide is the building block of several types of signal encoding used for high data rate optical communications. Speed in the several Gb/s may be required to sustain the high data rates used in modern optical links and can be achieved

in integrated Si photonics by modulating the depletion region of a PN junction placed across the waveguide carrying the optical beam.

One output of each of the optical modulators **105A-105D** may be optically coupled via the waveguides **110** to the grating couplers **117E-117H**. The other outputs of the optical modulators **105A-105D** may be optically coupled to monitor photodiodes **113A-113D** to provide a feedback path. The IC **130** may utilize waveguide based optical modulation and receiving functions. Accordingly, the receiver may employ an integrated waveguide photo-detector (PD), which may be implemented with epitaxial germanium/SiGe films deposited directly on silicon, for example.

The grating couplers **117A-117H** may comprise optical gratings that enable coupling of light into and out of the photonically-enabled integrated circuit **130**. The grating couplers **117A-117D** may be utilized to couple light received from optical fibers into the photonically-enabled integrated circuit **130**, and the grating couplers **117E-117H** may be utilized to couple light from the photonically-enabled integrated circuit **130** into optical fibers. The grating couplers **117A-117H** may comprise single polarization grating couplers (SPGC) and/or polarization splitting grating couplers (PSGC). In instances where a PSGC is utilized, two input, or output, waveguides may be utilized.

The optical fibers may be epoxied, for example, to the CMOS chip, and may be aligned at an angle from normal to the surface of the photonically-enabled integrated circuit **130** to optimize coupling efficiency. In an example embodiment, the optical fibers may comprise single-mode fiber (SMF) and/or polarization-maintaining fiber (PMF).

In another exemplary embodiment illustrated in FIG. 1B, optical signals may be communicated directly into the surface of the photonically-enabled integrated circuit **130** without optical fibers by directing a light source on an optical coupling device in the chip, such as the light source interface **135** and/or the optical fiber interface **139**. This may be accomplished with directed laser sources and/or optical sources on another chip flip-chip bonded to the photonically-enabled integrated circuit **130**.

The photodiodes **111A-111D** may convert optical signals received from the grating couplers **117A-117D** into electrical signals that are communicated to the amplifiers **107A-107D** for processing. In another embodiment of the disclosure, the photodiodes **111A-111D** may comprise high-speed heterojunction phototransistors, for example, and may comprise germanium (Ge) in the collector and base regions for absorption in the 1.3-1.6 μm optical wavelength range, and may be integrated on a CMOS silicon-on-insulator (SOI) wafer and/or die.

The analog and digital control circuits **109** may control gain levels or other parameters in the operation of the amplifiers **107A-107D**, which may then communicate electrical signals off the photonically-enabled integrated circuit **130**. The control sections **112A-112D** comprise electronic circuitry that enables modulation of the CW laser signal received from the splitters **103A-103C**. The optical modulators **105A-105D** may require high-speed electrical signals to modulate the refractive index in respective branches of a Mach-Zehnder interferometer (MZI), for example.

In operation, the photonically-enabled integrated circuit **130** may be operable to transmit and/or receive and process optical signals. Optical signals may be received from optical fibers by the grating couplers **117A-117D** and converted to electrical signals by the photodetectors **111A-111D**. The electrical signals may be amplified by transimpedance amplifiers in the amplifiers **107A-107D**, for example, and

subsequently communicated to other electronic circuitry, not shown, in the photonically-enabled integrated circuit **130**.

Transimpedance amplifiers (TIAs) may be operable to receive electrical current signals, amplify, and convert them to voltage signals. In optical transceivers, tight gain calibration limits may be imposed on the TIAs, which usually limit the receiver dynamic range (DR), and at data rates beyond 10 GB/s and with input photo current levels in a 30 dB range, linear TIA performance adequate for optoelectronics applications is challenging. The TIA dynamic range may be defined as the ratio of maximum to minimum photocurrent that can be properly sensed.

The TIA linearity limits the receiver cascade dynamic range for large input currents. In scaled CMOS technologies, and under large level input currents, it may be difficult to prevent TIA output saturation due in part to the nonlinearity of the short channel transistors, but mainly to the reduced supply voltages. The low end of the dynamic range is determined by the TIA input referred noise. A low-noise topology TIA is necessary in order to meet input sensitivity.

A shunt-feedback (SF)-based TIA may provide such a low-noise topology. This architecture is based on a voltage-inverting amplifier with a feedback network. The feedback network impedance directly affects the dynamic range of the TIA and gain may be controlled using a DC control voltage generated in a servo loop using two TIA replicas.

In an example scenario, the TIA topology disclosed herein may control the value of the feedback network impedance, thus enhancing the TIA linearity under large levels of input photocurrent. The gain control method is digital, non-intrusive, i.e. does not affect the signal path, and may be integrated with other process calibration and temperature control mechanisms.

FIG. 1B is a diagram illustrating an exemplary photonically-enabled integrated circuit, in accordance with an example embodiment of the disclosure. Referring to FIG. 1B, there is shown the photonically-enabled integrated circuit **130** comprising electronic devices/circuits **131**, optical and optoelectronic devices **133**, a light source interface **135**, a chip front surface **137**, an optical fiber interface **139**, CMOS guard ring **141**, and a surface-illuminated monitor photodiode **143**.

The light source interface **135** and the optical fiber interface **139** comprise grating couplers, for example, that enable coupling of light signals via the CMOS chip surface **137**, as opposed to the edges of the chip as with conventional edge-emitting/receiving devices. Coupling light signals via the chip surface **137** enables the use of the CMOS guard ring **141** which protects the chip mechanically and prevents the entry of contaminants via the chip edge.

The electronic devices/circuits **131** comprise circuitry such as the amplifiers **107A-107D** and the analog and digital control circuits **109** described with respect to FIG. 1A, for example. The optical and optoelectronic devices **133** comprise devices such as the couplers **103A-103C**, optical terminations, grating couplers **117A-117H**, optical modulators **105A-105D**, high-speed heterojunction photodiodes **111A-111D**, and monitor photodiodes **113A-113D**.

In an example scenario, the electronic devices/circuits **131** may comprise TIAs with accurate gain control using dual replicas and a servo loop. Accordingly, a feedback impedance for the TIA may directly affect the dynamic range of the TIA and gain may be controlled using a DC control voltage generated in the servo loop using two TIA replicas.

FIG. 1C is a diagram illustrating a photonically-enabled integrated circuit coupled to an optical fiber cable, in accordance with an example embodiment of the disclosure. Refer-

ring to FIG. 1C, there is shown the photonically-enabled integrated circuit **130** comprising the chip surface **137** and the CMOS guard ring **141**. There are also shown a fiber-to-chip coupler **145**, an optical fiber cable **149**, and an optical source assembly **147**.

The photonically-enabled integrated circuit **130** comprises the electronic devices/circuits **131**, the optical and optoelectronic devices **133**, the light source interface **135**, the chip surface **137**, and the CMOS guard ring **141** may be as described with respect to FIG. 1B.

In an example embodiment, the optical fiber cable may be affixed, via epoxy for example, to the CMOS chip surface **137**. The fiber chip coupler **145** enables the physical coupling of the optical fiber cable **149** to the photonically-enabled integrated circuit **130**.

FIG. 2 is a block diagram of a photodiode sensed using a transimpedance amplifier with feedback impedance, in accordance with an example embodiment of the disclosure. Referring to FIG. 2, there is shown receiver front-end **200** comprising a photodetector **201**, feedback impedance **203**, and a gain stage **205**. The photodetector may comprise a semiconductor photodiode, for example, comprising silicon or silicon-germanium for receiving optical signals and converting them to an electrical current. The photodetector **201** may be on the same chip, such as the chip **130**, as the gain stage **205** or may be off-chip.

The gain stage **205** may comprise circuitry for receiving an electrical current signal at its input and providing a voltage at its output that is proportional to the input current. In an example scenario, the gain stage **205** may comprise a voltage-in-voltage-out gain stage and may comprise a CMOS inverter, although the disclosure is not so limited, as any gain stage compatible with the source signal may be utilized.

The feedback impedance **203** may comprise a feedback path for the gain stage **205**, and may be implemented in a passive or active mode, with three examples shown by feedback impedances **203A-203C**. Feedback impedance **203A** comprises a passive impedance with a fixed resistor, while feedback impedances **203B** and **203C** represent active impedances, where impedance **203B** is a resistor in series with a transistor. The transistor may comprise a PMOS, NMOS, or other type of transistor, with the control terminal of the transistor being utilized to configure the impedance of the series structure. In an example scenario, an NMOS/PMOS transistor may be utilized and the resistance controlled by varying the gate voltage when operating in its linear region, or triode mode.

Similarly, the feedback impedance **203C** comprises an array of selectable resistors, such as a trimmed resistor network. In this example, discrete resistors may be selected utilizing an array of switches coupled to the resistors in the network, as indicated by the input terminal.

The feedback impedance **203** and gain stage **205** may be utilized in TIA implementations, as show further with respect to FIG. 3.

FIG. 3 illustrates a transimpedance amplifier with accurate gain adjustment using a dual replica and servo loop, in accordance with an example embodiment of the disclosure. Referring to FIG. 3, there is shown receiver **300** comprising a photodetector **301**, TIAs **310A-310D**, and amplifiers **311** and **313**. There is also shown an optical input signal, a reference voltage V_{ref} at the output of TIA **310A**, a control current I_{ctrl} for TIA **310C**, a servo loop voltage V_{gs} , and an output voltage V_{out} .

In an example scenario, the TIAs **310A-310D** are substantially similar to the TIA described with respect to FIG.

2, as indicated by the symbols within the boxes for each TIA, where the feedback impedance is configured depending on the function of the TIA. For example, TIA 310A may comprise a trimmed resistor network, such as feedback impedance 203C, while TIAs 310B, 310C, and 310D each comprise an active feedback impedance, such as feedback impedance 203B. In this manner, the gain of TIA 310A, once selected, may remain essentially constant providing a stable and known gain, while that of TIAs 310B, 310C, and 310D

may be configured dynamically using a control voltage, the servo loop voltage V_g . The TIAs 310B and 310D may be replicas of TIA 310C, with nominally identical components being located in close proximity on the chip, for example. The amplifiers 311 and 313 may comprise operational amplifiers or digital feedback, for example, with circuitry that generates an output signal proportional to the difference between its input voltages. For amplifier 311, therefore, the output voltage V_g , is proportional to the difference between the output of TIA 310A, Ref, and the output of TIA 310B.

The TIA circuit comprising TIAs 310A-310D in the receiver 300 may comprise a CMOS shunt-feedback TIA, whose low-frequency gain (trans-impedance ZT) is correlated to the feedback network impedance. This approximation is correct for a large enough gain for the gain stages in the TIAs 310A-310D, $A > 10$, for example. For $A > 10$, ZT is approximately equal to the feedback impedance.

The main TIA, TIA 310C, and the two TIA replicas, TIAs 310B and 310D in this example, comprise a voltage-controlled feedback impedance, comprising a series combination of a voltage-controlled resistance and a fixed resistor, as shown by impedance 203B in FIG. 2, where the triode-mode n-MOS transistor creates the voltage control portion of the impedance and the poly resistor portion further linearizes the impedance, under overload input signals, as well as compensates the n-MOS temperature coefficient.

The main TIA 310C and TIA replicas 310B and 310D are configured by the servo loop voltage V_g , which is coupled to the voltage control inputs of the feedback impedances of the TIAs, thereby providing an accurate representation of a trimmed target feedback impedance. This control voltage V_g imparts the same trimmed impedance value to the impedance networks in the TIA 310C and TIA replicas 310B and 310D, within process and layout matching limits.

The impedance resistance trim servo loop employs a reference TIA 310A that generates an output voltage proportional to $I_{ref} \times$ target impedance. In an example scenario, I_{ref} and I_{ref1} are small fixed currents, generated by a current digital-to-analog converter (DAC), resulting in a known and accurate current. I_{ref} and I_{ref1} may be injected into TIA 310A and TIA 310B reference inputs, respectively, as a means to increase the matching between the four TIAs, as well as a means to control the TIA 310C gain within a narrow range around the trimmed point.

The main TIA 310C gain may be controlled by the control voltage V_g . This voltage in turn may be adjusted by changing the reference voltage (REF) in the servo-loop. REF is generated by the product of I_{ref} and the transimpedance value of the TIA 310A with the trimmed resistance network. The servo-loop equalizes the two voltages seen by the amplifier 311, to the level of REF, generating the control voltage V_g . This voltage is proportional to the TIA 310B gain, and it imparts an equal value to the main TIA 310C gain, within matching limits.

Note that the above TIA gain trim approach described here does not affect the high-speed operation of the main TIA 310C in the signal path, since the gain control is applied as a DC voltage on the gate of the feedback n-MOS

transistor. This control voltage V_g has a precise value correlated to the trimmed poly resistor, and a temperature coefficient that tracks the same resistor. Also, the control voltage V_g has a variable component, due to its dependence on I_{ref} that is used to control the TIA 310C gain around the trimmed value.

In operation, an optical signal may be directed to the photodetector 301 via an optical waveguide for example, and a resulting electrical signal may be communicated to the TIA 310C. Reference currents I_{ref} and I_{ref1} may be supplied to the inputs of the TIAs 310A and 310B, respectively. The feedback impedance of the TIA 310A, comprising a trim resistor network, may be preselected to configure the gain, while the control voltage V_g acts to equalize the gain of TIA 310B. This same control voltage controls the gain of the main TIA 310C, which receives the electrical signal from the photodetector 301, resulting in an amplified signal V_{out} proportional to the gain of the TIA 310C.

The gain of the main TIA 310C may be adjusted by configuring I_{ref} , such that the reference voltage V_{ref} changes and V_g adjusts accordingly to equalize the inputs to the amplifier 311. This change in V_g thus changes the gain of TIA 310C.

In addition, a "pseudo-differential" output may be generated by configuring the output of the amplifier 313 to follow the average of the output signal V_{out} . This may be accomplished by coupling the output signal V_{out} to one input of the amplifier 313 and coupling the output of the TIA 310D to the other input of the amplifier 310D. By configuring the current I_{ctrl} for the TIA 310C to sink or source current at the input of the TIA, the DC value of the output voltage V_{out} may be adjusted, and with the input to the TIA 310D being open, the output of the amplifier 313 is therefore inverted from the change in DC value of the output voltage and provides a feedback control voltage, DC_{ctrl}. The differential output is therefore defined by the outputs of the TIAs 310C and 310D.

FIG. 4 is a flow chart illustrating example steps in providing accurate gain adjustment for a transimpedance amplifier using a dual replica and servo loop, in accordance with an example embodiment of the disclosure. In step 403, after start step 401, the feedback impedance of TIA 310A may be configured by selecting a resistance in a resistor network to set the reference TIA gain. In step 405, reference currents I_{ref} and I_{ref1} may be applied to reference and replica TIAs 310A and 310B. In step 407, an electrical signal may be received from the photodetector 301, thereby generating an electrical signal, which may be amplified by TIA 310C in step 409. In addition, a control current may be supplied to the main TIA 310C to provide a configurable DC output, thereby enabling a pseudo-differential output. In step 411, the amplified and pseudo-differential signal may be communicated at the output of the main TIA 310C, followed by end step 611.

In an example embodiment, a method and system are disclosed for accurate gain adjustment of a transimpedance amplifier using a dual replica and servo loop. In this regard, aspects of the disclosure may comprise a transimpedance amplifier (TIA) circuit comprising a first TIA, a second TIA, and a third TIA, each comprising a configurable feedback impedance, and a control loop. The control loop comprises a gain stage with inputs coupled to outputs of the first and second TIAs and an output coupled to the configurable feedback impedance of the second and third TIAs. The TIA circuit is operable to: configure a gain level of the first TIA by configuring its feedback impedance, configure a gain level of the third TIA by configuring a reference current

applied to an input of the first TIA, and amplify a received electrical signal to generate an output voltage utilizing the third TIA.

The reference current may generate a reference voltage at one of the inputs of the gain stage. The reference voltage may control the output of the gain stage that is coupled to the configurable feedback impedance of the third TIA. The configurable impedance of the first TIA may comprise a configurable array of resistors and the configurable impedances of the second and third TIAs may each comprise a resistor and a voltage-controlled resistance.

The configurable impedances of the second and third TIAs may be configured by configuring a gate voltage of the transistor utilizing the output of the gain stage. The output voltage may be coupled to a first input of a second gain stage where a second input of the second gain stage is coupled to an output of a fourth TIA. A differential signal may be generated utilizing the output voltage and an output of the second gain stage. The output of the second gain stage may be configured by configuring an input current of the third TIA. The electrical signal may be received from a photodetector.

In another example embodiment, a system is disclosed for accurate gain adjustment of a transimpedance amplifier using a dual replica and servo loop. In this regard, aspects of the disclosure may comprise a transimpedance amplifier (TIA) circuit, where the TIA circuit comprises: a first TIA comprising a first configurable impedance and an output coupled to a first input of a first gain stage, a second TIA comprising a second configurable impedance and an output coupled to a second input to the first gain stage, a third TIA comprising a third configurable feedback impedance, an input for receiving an input electrical current, and an output that generates an output voltage of the TIA circuit, and a control loop for controlling the gain of the third TIA. The control loop comprises the first gain stage with its output coupled to the second and third configurable impedances.

As utilized herein the terms “circuits” and “circuitry” refer to physical electronic components (i.e. hardware) and any software and/or firmware (“code”) which may configure the hardware, be executed by the hardware, and or otherwise be associated with the hardware. As used herein, for example, a particular processor and memory may comprise a first “circuit” when executing a first one or more lines of code and may comprise a second “circuit” when executing a second one or more lines of code. As utilized herein, “and/or” means any one or more of the items in the list joined by “and/or”. As an example, “x and/or y” means any element of the three-element set $\{(x), (y), (x, y)\}$. In other words, “x and/or y” means “one or both of x and y”. As another example, “x, y, and/or z” means any element of the seven-element set $\{(x), (y), (z), (x, y), (x, z), (y, z), (x, y, z)\}$. In other words, “x, y and/or z” means “one or more of x, y and z”. As utilized herein, the term “exemplary” means serving as a non-limiting example, instance, or illustration. As utilized herein, the terms “e.g.,” and “for example” set off lists of one or more non-limiting examples, instances, or illustrations. As utilized herein, circuitry or a device is “operable” to perform a function whenever the circuitry or device comprises the necessary hardware and code (if any is necessary) to perform the function, regardless of whether performance of the function is disabled or not enabled (e.g., by a user-configurable setting, factory trim, etc.).

While the disclosure has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the

present disclosure. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without departing from its scope. Therefore, it is intended that the present disclosure not be limited to the particular embodiments disclosed, but that the present disclosure will include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A method for communication, the method comprising: in a receiver comprising:
 - a first transimpedance amplifier (TIA);
 - a second TIA;
 - a third TIA;
 - a fourth TIA, each TIA comprising a configurable feedback impedance;
 - a control loop, the control loop comprising a gain stage with inputs coupled to outputs of the first and second TIAs and an output of the gain stage coupled to the configurable feedback impedance of the second and third TIAs; and
 - a second gain stage with a first input coupled to an output of the third TIA and a second input coupled to an output of the fourth TIA:
2. The method according to claim 1, wherein the reference current generates a reference voltage at one of the inputs of the gain stage.
3. The method according to claim 2, wherein the reference voltage controls the output of the gain stage that is coupled to the configurable feedback impedance of the third TIA.
4. The method according to claim 1, wherein the configurable impedance of the first TIA comprises a configurable array of resistors.
5. The method according to claim 1, wherein the configurable impedances of the second and third TIAs each comprise a fixed resistor and a voltage-controlled resistance.
6. The method according to claim 5, comprising configuring the configurable impedances of the second and third TIAs by configuring a gate voltage of a transistor of the voltage-controlled resistance utilizing the output of the gain stage.
7. The method according to claim 1, comprising generating a differential signal utilizing the output voltage and an output of the fourth TIA.
8. The method according to claim 1, comprising configuring the output of the second gain stage by configuring an input current of the third TIA.
9. The method according to claim 1, comprising receiving an optical signal via a photodetector coupled to an input of the third TIA.
10. The method according to claim 9, comprising receiving the electrical signal generated by the optical signal received by the photodetector.
11. A system for communication, the system comprising:
 - a receiver comprising a first transimpedance amplifier (TIA);
 - a second TIA;
 - a third TIA;
 - a fourth TIA, each TIA comprising a configurable feedback impedance;

11

a control loop, the control loop comprising a gain stage with inputs coupled to outputs of the first and second TIAs and an output coupled to the configurable feedback impedance of the second and third TIAs; and
 a second gain stage with a first input coupled to an output of the third TIA and a second input coupled to an output of the fourth TIA, the receiver being operable to:
 configure a gain level of the first TIA by configuring its feedback impedance;
 configure a gain level of the third TIA by configuring a reference current applied to an input of the first TIA; and
 amplify a received electrical signal to generate an output voltage utilizing the third TIA.

12. The system according to claim 11, wherein the reference current generates a reference voltage at one of the inputs of the gain stage.

13. The system according to claim 12, wherein the reference voltage controls the output of the gain stage that is coupled to the configurable feedback impedance of the third TIA.

14. The system according to claim 11, wherein the configurable impedance of the first TIA comprises a configurable array of resistors.

15. The system according to claim 11, wherein the configurable impedances of the second and third TIAs each comprise a fixed resistor and a voltage-controlled resistance.

16. The system according to claim 15, wherein the TIA circuit is operable to configure the configurable impedances of the second and third TIAs by configuring a gate voltage of a transistor of the voltage-controlled resistance utilizing the output of the gain stage.

12

17. The system according to claim 11, wherein the received electrical is generated by a photodetector coupled to an input of the third TIA.

18. The system according to claim 11, wherein the TIA circuit is operable to generate a differential signal utilizing the output voltage and an output of the fourth TIA.

19. The system according to claim 11, wherein the TIA circuit is operable to configure the output of the second gain stage by configuring an input current of the third TIA.

20. A system for communication, the system comprising:
 a receiver comprising:

a first transimpedance amplifier (TIA) comprising a first configurable impedance and an output coupled to a first input of a first gain stage;

a second TIA comprising a second configurable impedance and an output coupled to a second input to the first gain stage;

a third TIA comprising a third configurable feedback impedance, an input for receiving an input electrical current, and an output that generates an output voltage of the TIA circuit;

a fourth TIA comprising a fourth configurable impedance;

a second gain stage with a first input coupled to an output of the third TIA and a second input of the second gain stage coupled to an output of a fourth TIA; and

a control loop for controlling the gain of the third TIA, the control loop comprising the first gain stage with its output coupled to the second and third configurable impedances.

* * * * *