

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2008252932 B2**

(54) Title
Appliance for conditioning a milk-based liquid

(51) International Patent Classification(s)
A47J 27/00 (2006.01) **A47J 43/046** (2006.01)
A47J 43/042 (2006.01)

(21) Application No: **2008252932** (22) Date of Filing: **2008.05.23**

(87) WIPO No: **WO08/142154**

(30) Priority Data

(31) Number	(32) Date	(33) Country
202007007337.2	2007.05.23	DE
202007007338.0	2007.05.23	DE
202007007339.9	2007.05.23	DE
202007007340.2	2007.05.23	DE
07124050.1	2007.12.24	EP

(43) Publication Date: **2008.11.27**

(44) Accepted Journal Date: **2014.07.24**

(71) Applicant(s)
Nestec S.A.

(72) Inventor(s)
Piller, Roland;Helf, Gerd;Becker, Dietmar;Krauchi, Frank

(74) Agent / Attorney
Shelston IP, L 21 60 Margaret St, Sydney, NSW, 2000

(56) Related Art
US 2006/0018187
US 2001/0036124
EP 1520498

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 November 2008 (27.11.2008)

PCT

(10) International Publication Number
WO 2008/142154 A1

(51) International Patent Classification:

A47J 27/00 (2006.01) A47J 43/046 (2006.01)
A47J 43/042 (2006.01)

(21) International Application Number:

PCT/EP2008/056349

(22) International Filing Date: 23 May 2008 (23.05.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

202007007340.2 23 May 2007 (23.05.2007) DE
202007007339.9 23 May 2007 (23.05.2007) DE
202007007338.0 23 May 2007 (23.05.2007) DE
202007007337.2 23 May 2007 (23.05.2007) DE
07124050.1 24 December 2007 (24.12.2007) EP

(71) Applicant (for all designated States except US): NESTEC S.A. [CH/CH]; Avenue Nestlé 55, CH-1800 Vevey (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KRÄUCHI, Frank

[CH/CH]; Rue des Saugettes 10C, CH-1417 Epautheyres (CH). **HELF, Gerd** [DE/DE]; Kreuzweg 47, 46359 Heiden (DE). **BECKER, Dietmar** [DE/DE]; Ispringrader-Str. 43c, 42477 Radevormwald (DE). **PILLER, Roland** [CH/CH]; Impasse des Vignes 16, CH-1720 Corminboeuf (CH).

(74) Agent: SCHNYDER, Frank; Avenue Nestlé 55, CH-1800 Vevey (CH).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: APPLIANCE FOR CONDITIONING A MILK-BASED LIQUID

Fig. 1



(57) Abstract: An appliance for conditioning a liquid made of or based on milk, in particular for preparing heated liquid and/or a cold or heated frothed liquid, comprises: a tank (10) for receiving the liquid that is to be conditioned; a closed compartment (20) secured to the tank; and an electric device (30) located therein for imparting a conditioning effect to the liquid - The compartment is made water impervious and washable under running water without infiltration thereof into the compartment containing the electric device.

WO 2008/142154 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*
- *of inventorship (Rule 4.17(iv))*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Appliance for Conditioning a Milk-based LiquidField of the Invention

5 The present invention relates to an electric appliance
for conditioning a milk-based liquid, in particular for
heating and/or frothing such liquid, to be used for
example in the context of the preparation of beverages
such as cappuccinos, milky coffees, café latte and
10 macchiato, chocolate and other hot or cold beverages.

Background Art

Speciality beverages in which at least a portion is
15 made up of frothed or heated milk are becoming more and
more popular. The best-known beverage of this type is a
coffee of the cappuccino type. It comprises a liquid
portion consisting of coffee topped by a layer of
frothed milk which, because of its very much lower
20 density, floats atop the surface of the liquid. In
general, preparing one takes time, manipulation
operations and cleaning.

The most customary way of preparing a milk-based froth
25 is to pour the desired amount of milk into the
container, immerse a steam outlet pipe from a coffee
machine in the container, agitating it up and down to
introduce the air needed to form the froth.

30 There also exists mechanical stirring appliances which
are usually intended for domestic use for beating froth
from more or less viscous food products such as eggs,
ice, juices or the like. The problem with these
appliances is of several natures which means that they
35 are ill-suited to producing froth from a milk-based
liquid for making a beverage. One disadvantage, for
example, stems from the fact that these appliances stir
a liquid or a paste in the cold state, considerably
limiting their potential use. In addition, milk does

not froth as convincingly when cold or at ambient temperature.

Another disadvantage stems from the fact that these
5 appliances are ill-suited to frothing the
microbiologically sensitive liquids such as milk.
Regular cleaning of the tank of the appliance needs to
be envisaged in order to remove any solid food residue.
In addition, heating the milk has a tendency to
10 increase the extent to which cooked or burnt proteins
are deposited on and adhere to the surfaces. The
existing appliances are not, for the most part, well
suited to reducing the encrustation of this solid
residue, making cleaning troublesome.

15 These appliances also have a stirring and drive
mechanism which is fixed and intrudes into the tank,
and this presents several disadvantages: the
removal/refitting time is not insignificant, they have
20 a tendency to become soiled more quickly, they entail
additional cost as a result of the multiplicity of
components, and the stirring means are difficult to
clean.

25 Another disadvantage with these appliances stems from
the fact that frothing in these appliances is not
optimal for reasons associated with the arrangement of
the stirring means. Some appliances have a stirring
means positioned in the middle of the tank. Such an
30 arrangement is not efficient in quickly converting a
volume of milk-based liquid into a rich froth.

Other appliances have several stirrers. These
arrangements are generally mechanical with gearing
35 means needed to coordinate the rotation of the
stirrers, and this makes the system intrusive, and
therefore less hygienic, increases the number of parts
and makes cleaning a more painstaking operation.

US Patent 6'318'247 relates to an appliance for preparing hot beverages or food with stirring such as hot chocolate, for example. The appliance comprises a system for driving a stirrer of the magnetic effect type. It does, however, have several disadvantages. Firstly, in such an appliance, the liquid or froth is stirred coaxially with respect to the central axis of the tank, and this causes a circulation in which some layers of liquid or froth, particularly the peripheral layers, are not stirred as extensively as others, particularly the layers near the middle, because of the centrifuging effect produced by the stirrer. Such a circulation is therefore not suited to producing a froth of sufficient quality or to reducing the time needed to produce this froth. In addition, the structure of the appliance is not hygienic for treating a milk-based liquid and cleaning is not made any easier by such a construction. Other devices for stirring food products which have more or less the same disadvantages are described in patent documents WO2004/043213 or DE 196 24 648.

Stirring systems with a magnetic engagement type are described in documents US 2 932 493, DE 1 131 372, US 4 537 332 and US 6 712 497 but none of these provide solutions suited to producing a quality froth in a short time and hygienically.

Utility model DE 89 15 094 relates to a refrigerated pot for dispensing a milk-based beverage. The pot comprises refrigerating means and forced-convection means in the form of a magnetic rotor. Such a device is not suited to converting the liquid into a froth but simply keeps the liquid uniformly at the refrigeration temperature for preservation.

US Patent 3,356,349 discloses a stirring device that has a heated tank, magnetic drive means positioned under the tank for driving a hub located in the middle of the tank. The hub is associated with a stirring

element which is offset with respect to the hub, causing the element an oscillatory movement. Such a principle of stirring may create a loss in magnetic coupling because of the high moment of inertia
5 generated by the offset position of the stirring means with respect to the axis of rotation of the drive means. This problem increases with increasing speed. Such a stirring device can therefore work to stir certain liquids or other substances at low speed but
10 may prove ill-suited to converting liquid into a froth at sufficiently high speed. Incidentally, the document does not mention the conversion of a liquid into a froth using this device.

15 More recently, an improved appliance for preparing froth from a milk-based liquid or milk has been proposed in WO2006/050900. The device has: a tank for receiving the liquid that is to be frothed, in which liquid a rotatable stirrer is positioned; a stand
20 holding the tank; drive and control means which are in a cavity located between the inner tank and the outer stand, and which communicate with a switch and electrical connections located on the outer surface of the stand; and disturbance means to optimise
25 circulation of the milk during frothing. This invention provides a solution to the abovementioned problems. It also recognises the hygiene issues that are raised the handling of milk, in particular heated milk that deposits against inner the walls of the tank. Hence,
30 the device disclosed in the above publication has a tank for containing the milk which has no joining lines or connections between the tank's walls and generally no gaps that would attract the deposition of solids, such as burnt milk.

35

However, despite the recent hygiene-related improvements regarding the preparation of the froth, it has been found that while the apparatus is handled by users, in particular un-cautious handling of the
40 apparatus, for example when frothed milk is removed

2008252932 20 Jun 2014

5 from the tank, milk may spill and stain the stand and other external parts and raise hygiene problems. The same problems may arise due to presence of the disturbance means that induce and increase agitation in the liquid and thus splashing. This problem is particularly acute in relation with switches, electrical connections and other parts of the stand that may attract milk deposits over time and cause cleaning problems and are in addition hard to clean properly without damaging the electric appliance. One way to solve this problem, at least in part, may involve the use of an appropriate lid and dispensing arrangement configured to avoid spills on the outer part of the appliance. This would however still require special attention by the user to avoid such spills.

20 Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common general knowledge in the field.

25 It is an object of the present invention to overcome or ameliorate at least one of the disadvantages of the prior art, or to provide a useful alternative.

Summary of the Invention

30 It is an object of a preferred form of the invention to alleviate the disadvantages of the prior art by proposing an appliance better suited for the production of froth from a milk-based food liquid, particularly for producing a beverage, that solves the problem of hygiene resulting from unwanted milk spills and stains that soil external parts of the appliance.

35 This preferred object is generally achieved by configuring the appliance for conditioning milk or a milk-based liquid so that it can be properly washed with water, and optionally with a detergent and even in 40 a dishwasher. In order to render this electric kitchen

2008252932 20 Jun 2014

appliance properly washable, i.e. not limiting cleaning of the external part by merely wiping its surface with a dry or humid towel like with prior art electric appliances, the sensible parts of the appliance, including the electric and electronic parts, are made water impervious in such a way that even the electric connections and interfaces that extend from the internal electric device through the appliance's housing, may be washed without damaging the appliance. Hence, the appliance may be safely washed, inside and outside, to remove any milk-based stains and spills so as to avoid any hygiene-related problems including on the external part of the appliance.

According to a first aspect of the invention there is provided an appliance for conditioning a liquid comprising:

- a tank for receiving the liquid that is to be conditioned;
- a closed compartment secured to the tank; and
- an electric device for imparting a conditioning effect to the liquid, said device being located in the compartment, the compartment being made water impervious and washable under running water without infiltration thereof into the compartment containing the electric device,

wherein the electric device is arranged to:

- impart the conditioning effect to the liquid which is made of or based on milk; and
- drive a stirrer in rotation in the tank for generating froth in the tank from the milk-made or milk-based liquid.

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise", "comprising", and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to".

2008252932 20 Jun 2014

Therefore, the invention relates to an appliance for conditioning a liquid made of or based on milk, in particular for preparing heated liquid or a cold or heated frothed liquid. The appliance comprises: a tank
5 for receiving the liquid that is to be conditioned; a closed compartment secured to the tank; and an electric device for imparting a conditioning effect to the liquid, which device is located in the compartment. In accordance with the invention the compartment is made
10 water impervious and washable under running water without infiltration thereof into the compartment containing the electric device.

In other words, all passages leading from outside to
15 inside the compartment, whether they result for example from the assembly of the appliance or whether they are for instance used for connecting the inner part of the compartment to its external part, which passages would allow water infiltration into the compartment, are
20 sealed off.

In any case, the appliance should be washable under running water by hand. Should the appliance also be washable in a dishwasher machine and/or using
25 detergents, the exposed surfaces of the appliance should be made of detergent-resistant materials.

Usually, the electric device has one or more connection means which extend through a through-opening in an
30 outer wall of the compartment. Typically, such through-openings can be made water impervious by a sealing element (or gasket) located between a peripheral part of the connection means and the outer wall. In contrast to prior art deformable covering parts that merely
35 extend over opening in the housing and that can easily

be moved away or torn away into such a position as to allow water infiltration through the opening into the inner part of the appliance during normal handling of the appliance, the sealing elements used for the present invention ensures water imperviousness, even when the appliance is thoroughly washed under running water, by hand or even in a dishwasher.

The through-opening may be delimited by a surface of the compartment's wall, the delimitation surface extending from inside to outside the chamber and having a periphery. In such a case, the sealing element may be located inbetween the peripheral part of the connection means and this delimitation surface and extend along the entire periphery of this delimitation surface around the connection means. In other words, the sealing member may advantageously fill any gap in the through-opening between the connection means and the wall through which the connection means extend. To improve the water-imperviousness of this arrangement, the sealing element is preferably deformable and compressed by and between the peripheral part of the connection means and this delimitation surface of the corresponding through-opening. By having a deformed sealing member under permanent compression constraint and tension in the through-opening, i.e. expanding between the connection means and the facing wall, no infiltration passages are left or can be formed during use or handling for water to enter the chamber via the through-opening along the connection means.

Typically, the sealing element is made of or comprises an elastic material, such as a silicon-based material or NBR. The sealing element may also comprise a plastic deformable material. The highest imperviousness is obtained when after deformation, the sealing member is compressed and remains under constraints between and against facing walls of the passage that is to be made impervious, i.e. that is to be sealed off to prevent water penetration. The sealing element can also be made

of plastic and/or elastic material, such as silicone, that is cast between a peripheral part of said connection means and the outer wall.

5 At least one connection means may comprise an electric conductor, in particular a copper and/or aluminium based conductor, for supplying electric power from a power supply to the electric device and/or for communicating a signal from and/or to the electric
10 device.

There are different possibilities to supply electrical power to the appliance (or exchange electric data to and from the appliance's electric device). For example,
15 the appliance can be connected directly via a cable to the mains (or data treatment unit). The cable may be permanently connected with the electric device or it may be linked via a plug and socket connection on the appliance to the electric device. Alternatively, the
20 appliance has a cordless electrical connection assembly that is connectable to an electrical power supply base support to the mains (or data treatment unit). In any case, the imperviousness of the electric connection exiting the appliance's chamber must be ensured to
25 avoid any water infiltration during washing. Further details relating to suitable cordless electrical connections are disclosed in the abovementioned WO2006/050900.

30 As mentioned above, the electric conductor may extend through a through-opening which contains a sealing element that is cast and/or deformed in compression between and by the conductor rod or cable and a wall's surface delimiting the through-opening. Optionally, The
35 sealing element is located in a cavity of the through-opening that extends transversally to the conductor rod or cable. The cavity may be partly covered on both sides, i.e. the cavity extending sideways within the wall, or only on one side of the wall. In the latter
40 case, the cavity leads to a narrower aperture on one

side of the wall and is entirely uncovered on the other side of the wall.

Typically, at least one connection means comprises or
5 leads to a user interface for controlling the electric device. Such interface may be a switch or a button or any means that is suitable for controlling the electric device contained in the appliance's chamber.

10 A suitable button may extend into the through-opening. For instance, the button comprises a rigid support element, in particular a rigid annular element, which has a peripheral surface that faces the wall's surface delimiting the through-opening, the sealing element
15 being compressed around the entire peripheral surface between and by said peripheral surface and said wall's surface. In such a case, the sealing element is located and compressed between two facing rigid structures, the wall and the rigid support member. To simplify the
20 manufacture, the button may be directly moulded on the rigid support element. Moreover, the sealing element can be integral with or bonded to the button. In an advantageous configuration, the button, rigid support element and sealing element are formed as a unit that
25 can be force-fitted into the through-opening, i.e. involving the compression of the sealing element, and possibly safely clipped inside the chamber to prevent any later unwanted dislodgement of the water-impervious sealed button.

30 The button may comprise a movable member that extends through the through-opening, the support element being located around the movable member, the movable member being arranged to communicate into the compartment a
35 user command by displacement of the movable member. The movable member can be movable in translation along the through-opening and/or in rotation, in particular about a rotational axis extending through the through-opening or parallel thereto. In any case, the button can be a
40 push button and/or a rotational button. For instance,

the button may be pushed or rotated to provide different commands to the appliance, e.g. heating by pushing and stirring by rotating the button or vice versa.

5

Likewise, the electric device in the chamber may also have a timer function, preset or set by the user using an interface linked via a connection means to the appliance's electric device as outlined above. Control signals relating to the operation of the appliance may also be communicated via a connection means to an interface accessible by the user.

Typically, the compartment is formed by the assembly of at least two casing parts, the casing parts being so assembled to be water impervious.

In an embodiment, at least one casing part is formed by at least a part of the tank, at least one further casing part being assembled with the tank to form with the tank, the impervious chamber containing the electric device. For example, the tank for conditioning the liquid is located above the chamber and forms or delimits the upper part of the chamber. The chamber may be formed by a tubular member that holds in its upper inner part the tank and a bottom part that is integral or assembled therewith and that delimits the bottom of the chamber located under the tank. At least one casing part can be a lid or, as mentioned, a bottom element of the chamber.

To ensure water imperviousness, two such casing parts can be assembled together by welding to seal off the chamber. Two of such casing parts may have connection portions that are made of thermoplastic material and that are welded together, in particular by ultrasonic welding. Moreover, two such casing parts can have connection portions that are made of a metal-based material and that are welded together.

40

When welding is not desired or not possible, for instance because of the specific material combination, the casing parts can be assembled via a sealing element that seals off the chamber. Usually, the sealing
5 element is elastic and/or plastic deformable and compressed by and between cooperating connection portions of the casing parts, as generally discussed above in relation with the through-openings.

10 Typically, the casing parts have connection portions with substantially facing surfaces that compress the sealing element.

In one embodiment, the sealing element comprises: a
15 body that extends over the surface of one connection portion and that is placed thereagainst; and a plurality of transverse members that protrude from said body to the surface of the facing connection portion and that are compressed between said body and the
20 surface of the facing connection portion. Providing several transverse members that are individually compressed in the passage between the connection portions increases the reliability of the imperviousness of the sealing element. Such a
25 configuration may be used for all deformable sealing elements used for the purpose of the present invention.

A rigid support member may be secured to the connection portion of one of such casing parts to hold the
30 cooperating connection portion of the other casing part, this cooperating connection portion being urged against the rigid support member by the compressed sealing element that is located and compressed between the cooperating connection portions.

35 Furthermore, a first casing part can be mechanically secured or further secured to or against a second casing part by a mechanical assembly member, such as a screw or rivet, that extends through a through-opening
40 in this first casing part, the through-opening being

made water impervious by a sealing element located between a peripheral part of said mechanical assembly member and said first casing part. The particular arrangement of the sealing member can be achieved in a similar manner like for the above discussed connection means.

The appliance may comprise a rotatable stirrer for generating froth in the tank. The electric device in the chamber is then arranged to drive the stirrer in the tank, in particular by generating a rotating magnetic field in the chamber that drives the stirrer in the tank without any mechanical transmission element extending through the tank's walls between the electric device and the stirrer, the stirrer being removably mounted on a stirrer positioning element in the tank, such as a relief or recess in a bottom part of the tank.

Usually the electric device comprises heating means for heating the tank and a drive means for imparting a rotational movement to the stirrer located in the tank.

Further details of suitable drive means and heating means are described in WO2006/050900.

In an advantageous embodiment, the heating means and the drive means are operable independently from one another. In addition to providing the option of heating milk or the milk-based liquid without frothing it, the appliance also permits the frothing of such liquids without heating. It has been discovered that when a sufficient stirring is imparted to milk or a milk-based liquid an acceptable froth may be obtained even from a cold liquid. Therefore, the user is preferably given the possibility to stir the liquid with or without heating thereof.

Another aspect of the invention concerns a rotatable stirrer for an appliance as described above. The

stirrer comprises: a positioning bottom part that is arranged to be removably mounted on said positioning element of the tank; and a peripheral part having stirring elements, such as turns of toroidally-shaped wire, impellers, blades, gratings or needles. Further details relating to suitable configurations of the bottom part and of this peripheral part can be found in WO2006/050900.

10 In accordance with the invention, the stirrer further comprises a top part extending generally upright from this peripheral part. This top part has a holding portion that is arranged to accommodate for human fingers so as to facilitate extraction and insertion of
15 said stirrer on said positioning element of the tank.

Such a top part enabling enhanced gripping, is particularly useful when the stirrer gets stuck on the bottom, for instance when milk product gets burnt or
20 stick between the stirrer and the positioning element.

For instance, the top part is generally in the shape of an arched member that forms generally an upright loop, optionally the loop forming generally a circle or a
25 fraction of a circle (e.g. half a circle) extending upwards from adjacent opposite sides of the peripheral part. Moreover, the top part forming a loop can further comprise an elongated upright member extending upwards from an upper end of the loop. Such an upright member
30 is optionally topped with a laterally protruding element to facilitate seizure by human fingers, for example a spherical element.

For some yet not fully understood reason, the presence
35 of this generally arched top part improves the quality of the froth produced with such stirrers. This effect is particularly interesting when the appliance is used to produce cold froth, which is significantly more difficult to obtain, if at all obtainable with an

acceptable quality, than hot froth using prior art appliances.

5 A further aspect of the invention relates to an electric device for an appliance as described above. The electric devices comprises: a drive means for imparting a rotational movement to a stirrer associated therewith; and a heating means for heating a tank associated therewith. In accordance with the invention,
10 the heating means and the drive means are operable independently from one another, as discussed above.

The electric device can be associated with a user interface which is arranged to allow independent
15 control of the drive means and of the heating means. The user interface may comprise a first button for controlling the drive means and a second button for controlling the heating means, or a single button with different positions for controlling the drive means and
20 the heating means.

Brief Description of the Drawings

The invention will now be described with reference to
25 the schematic drawings, wherein:

- Figure 1 shows a section of the appliance according to the invention;
- Figure 1a shows a perspective view of part of
30 the appliance shown in Figure 1.
- Figure 2 shows an enlarged view of a button arrangement of the appliance shown in Figure 1, Figure 2a showing a variation according to the invention of such a button;
- 35 - Figure 3 shows an enlarged view of the assembly according to the invention of the stand and bottom of the appliance shown in Figure 1.
- Figure 4 shows a prior art button arrangement;
- Figure 5 shows a section of another appliance
40 according to the invention;

- Figures 6 to 8 show various enlarged views of parts of the section of Figure 5;

- Figure 9 shows a perspective view of a stirrer of the invention, Figure 10 showing a cross-section of a part of this stirrer; and

- Figure 11 shows another stirrer of the invention.

Detailed description

10

An appliance 1 for conditioning a liquid made of or based on milk, in particular for preparing heated liquid and/or a cold or heated frothed liquid, according to the invention is shown in Figures 1 and 1a, Figures 2 and 3 showing enlarged views of parts A and B, respectively, of Figure 1.

Appliance 1 has a tank 10 for receiving the liquid that is to be conditioned, a closed compartment 20 located under tank 10; and an electric device 50 for imparting a conditioning effect to a liquid contained in tank 10. Electric device 50 is located in compartment 20. In accordance with the invention compartment 20 is made water impervious and washable with running water without infiltration thereof into the compartment 20 containing the electric device 50.

As shown in Figure 1, compartment 20 is formed by a generally tubular stand 21 assembled to a rigid plastic bottom 30. The upper part of compartment 20 is delimited by tank 10 which is located inside and secured to stand 21. Thus, tubular stand 21, bottom 30 and tank 10 are three casing parts, which when assembled, form together chamber 20.

35

Tank 10 and stand 21 are made of metal and welded together at their upper end so that the assembly of the two parts is made water impervious in accordance with the invention. Bottom 30 is made of rigid material, such as rigid plastic material. Tank 10 is covered with

40

a removable lid 11, typically made of plastic, that has a peripheral sealing ring 12.

As depicted in Figure 3 that shows an enlarged view of portion B of Figure 1, bottom 30 has an upright peripheral wall 31 facing the inner bottom end of tubular stand 21. Wall 31 has a peripheral groove 32 that faces stand 21 and that extends around the entire bottom 30. A peripheral sealing ring 33 (e.g. an o-ring type gasket) located in groove 32 extends around the entire wall 31. Sealing ring 33 is made of elastic deformable material such as NBR. Ring 33 is squeezed and compressed in groove 32 by the inner bottom end of stand 21 that urges ring 33 into groove 32, especially against the groove's surface 34 facing bottom end of stand 21 and substantially parallel thereto. Thus, compressed sealing ring 33 seals off any gap or passage between stand 21 and bottom 30, so that no water infiltration may occur between stand 21 and bottom 30 during washing, by hand or even in a dishwasher.

Also shown in Figs 1 and 3, the bottom end 22 of tubular stand 21 is slightly angled out and the upper end of upright bottom wall 31 has a bevel 35 to facilitate the introduction of bottom 30 into stand 21.

Moreover, as shown in Figure 1a, to avoid undesirable opening of chamber 21 by the user, bottom 30 may be permanently clipped in stand 21. For this purpose, bottom 30 includes a plurality of clips 90 arranged spaced apart around a peripheral part of bottom 30. Each clip 90 has a pair of generally upright fingers 91,92 with upper hooks 93 and a central rod-shaped abutment member 94 that are arranged for engaging, by clipping, with a corresponding hanger 95 that has a support member 96 mechanically secured, e.g. by welding, against the inner side of stand 21.

From this description, it is apparent that the assembly of the bottom 30 into stand 21 is carried out in a

direction that is different, in particular generally perpendicular, to the main compression direction of sealing ring 33 between bottom 30 and stand 21. Hence, the assembly functions and the sealing functions of bottom 30 in stand 21 are dissociated. In other words, sealing is achieved already when ring 33 is entered into stand 21 so as to be effective independently of the precise positioning of bottom 30 in stand 21 and independently of the clipping of clips 90 on hanger 95.

10

Furthermore, appliance 1 is of the cordless type and intended to be removably placed and powered by an electric base unit 2 that may be connected to the mains via an electric cable 3, as illustrate in Figure 1a. Therefore, bottom 30 includes a plurality of cordless connector pins 51, one of which is shown in Figure 1, that are connected to electric device 50 and that are made of an electrically highly conductive material typically metal, such as copper or aluminium or an alloy based thereon. Connector pins 51 extend from inside to outside chamber 20 through a through-opening or passage 36 in bottom 30 for connecting electric device 50 to external base unit 2.

To avoid water infiltration into chamber 20 along a connector pin 51, trough-opening or passage 36 is so arranged as to be water-impervious. Trough-opening or passage 36 includes a top aperture 37 leading into chamber 20, a lower aperture 37' leading outside chamber 20 and an intermediate cavity containing a sealing element 38 between upright walls 39 of bottom 30. The sealing member 38 is made of elastic material, such as silicone that is directly cast around connector pin 51 into the intermediate cavity between upright walls 39 and pin 51 so as to firmly adhere to pin 51 and the surfaces of the cavity, in particular of walls 39, and thus render the intermediate cavity of through-opening or passage 36 water impervious. Moreover, pin 51 comprises an abutment 52 adjacent lower aperture 37' to avoid displacement of pin 51 in through-opening or

40

passage 36. Furthermore, pins 51 are associated with vertical walls 39' that delimit in combination with walls 39 and pins 51 grooves for mounting appliance 1 onto base unit 2 that will support and provide electrical power to the cordless appliance 1. Details of such cordless connectors are for example disclosed in WO2006/050900 and the references cited therein.

Furthermore, appliance 1 comprises a plurality of push-buttons 60, one of which is shown in Figure 1 and in Figure 2 that shows an enlarged view of portion A of Figure 1, for controlling electric device 50 from outside appliance 1.

Push-button 60 extends into chamber 20 through a through-opening in stand 21. Button 60 has a core 61 made of elastic material mounted or injected or cast onto on a rigid ring 67 made of metal, ceramic, hard plastic and/or another hard material.

Core 61 comprises a button head 62 which can be pushed by the user, and a movement transmission rod 63 integral therewith. Button head 62 is integral with a peripheral sealing element 64 and connected therewith via elastic deformable hinge 65 integral with sealing element 64 and button head 62.

As shown in Figure 2, sealing element 64 is deformed in compression between rigid ring 67 and a (rigid) portion 23 of stand 21. Portion 23 delimits the through-opening that houses push-button 60 and has a surface that faces and is substantially parallel to the surface of rigid ring 67, these two surfaces squeezing sealing element 64 making the through-opening for button 60 water impervious. Moreover, sealing element 64 has a bevelled arrow-like end portion that extends transversally for facilitating the insertion of button 60 into the through-opening and permanently clipping button 60 in stand 21 so as to avoid any displacement or

misplacement thereof that would impair the water-imperviousness.

5 Furthermore, rod 63 of button 60 extends inside chamber 20 between guide members 53 towards a contact element 55 that is connected with electric device 50 and that can be operated by pressing button head 62 and transmission rod 63 thereagainst, thereby deforming hinge 65.

10

Figure 2a, in which the same numeric references designate the same elements, shows another button arrangement according to the invention.

15 Push-button 60'' is secured in a through-opening delimited by a rigid wall portion 23 of stand 21 using a rigid annular clipping arrangement 67'. Clipping arrangement 67' has an annular neck 67a which extends along sealing ring 64 and which urges sealing ring 64
20 against an outside surface 23b of wall 23. Annular neck 67a is formed by a series of spaced apart clipping fingers, one of which is shown in the lower part of Figure 2a, having an arm 67a with a hook 67b, a bevel 67d, an end 67e extending over the edge of wall portion
25 23 and a circular flange 67c extending over a ledge 23a of wall portion 23. Flange 67c is covered with a peripheral extension 65a of the button's elastic hinge 65. Sealing ring 64 is connected to button head 62 via connecting portions 64a that extend between the roots
30 of arms 67a which roots join arms 67a to circular flange 67c.

Each clipping finger is slightly resilient and has a bevel 27d to allow insertion of the annular clipping
35 arrangement 67' into the through-opening delimited by wall portion 23 up to ledge 23 and for clipping hook 67b over the edge of wall portion 23.

40 Furthermore, button head 62 is assembled to a movement transmission hard rod 63' whose end 63'' is arranged to

push contact element 55 when button-head 62 is pressed by a user.

5 Figure 4, in which the same numeric references designate the same elements, shows an arrangement of a comparative prior art button 60'. Similar buttons are disclosed in the abovementioned WO2006/050900.

10 Button 60' is secured in a through-opening extending through stand 21 by an a peripheral integral part 64' of button 60' that is clipped on edge 23' of stand 21, edge 23' delimiting the through-opening for button 60'. As can be readily seen in Figure 4, the peripheral integral part 64' is not urged and compressed against
15 edge 23'. This integral part 64' does not firmly obstruct the passage along button 60' into chamber 20, and therefore no water-impervious sealing can be provided, especially when button 60' is pressed, causing a flexion and displacement of peripheral part
20 64' around edge 23'. This is all the more problematic when the button is exposed to milk spills that may infiltrate chamber 20 and durably soil the electric part of the appliance.

25 Figures 5 in which the same numeric references designate the same elements, shows another appliance 1 according to the invention. Appliance 1 is shown without lid on tank 10. As opposed to prior art appliances splashes of milk on the external parts of
30 the appliance in not problematic anymore, so that the appliance can be operated without lid, giving the user access to the liquid during the conditioning treatment.

35 Generally tubular stand 21' is made of a material, typically a plastic material, that cannot be welded to the material of tank 10, typically a metal-based material. Nevertheless, to ensure water-imperviousness of the assembly of stand 21' and tank 10 located therein, a peripheral sealing element 15 is used along
40 the entire junction between tank 10 and stand 21', i.e.

around the entire tank 10. Sealing element 15 is made of elastic material such as NBR and is permanently compressed between tank 10 and stand 21'.

5 As shown in greater details in Figure 6, sealing element 15 has a body 16 that extends over a portion of the surface of tank 10 and that is placed thereagainst; and three peripheral transverse members 17 that protrude from body 16 to the inner surface of the upper
10 end of stand 21'. The peripheral transverse members 17 extend along body 16 around the entire tank 10. The inner surface of stand 21' faces and is generally parallel to said surface of tank 10. These two surfaces compress the transverse members 17 and body 16 of
15 sealing element 15 that is located between these surfaces.

Incidentally, sealing element 64 securing push-button 60 in the through-opening in stand 21 has similar
20 peripheral transverse members that are compressed against portion 23 of stand 21.

Furthermore, the upper end of tank 10 is associated with a down-coming peripheral rigid support member 10'
25 that extends along tank 10 with a lower part 10'' that is angled away from tank. The rigid support member 10',10'' helps to position and secure tank 10 on stand 21'. Support member 10',10'' urges stand 21' against sealing member 15 and tank 10 and, at the same time,
30 stands on a shoulder 23 of stand 21' to secure tank 10 on stand 21'. Sealing element 15 further comprises at its upper end flexible transverse member 18 that seals off the gap between tank 10 and the lower part 10'' angling away therefrom.

35

Appliance 1 has a bottom 30' that is connected to stand 21' by ultrasonic welding. Stand 21' and bottom 30' are, at least where they are welded together, of thermoplastic materials that are compatible for the
40 purpose of welding.

As can be seen in greater detail in Figure 7 which is an enlarged view of par D of Figure 5, bottom 30' has two parallel upright peripheral walls 301,302 that delimit thereinbetween a peripheral groove 303. These walls 301,302 and groove 303 extend along the entire periphery of bottom 30'. The bottom part of stand 21' has a generally angled, in particular right-angled connecting member 25 protruding from the inner surface of the bottom part of stand 21', extending along the entire inner surface of stand 21', thereby forming an inner loop over the peripheral part of bottom 30', and having an end portion 26 shaped to accommodate into the groove 303. However, as the width of end portion 26 is prior to assembly larger than the width of groove 303, connecting member 25 and bottom 30' are assembled with the help of an ultrasound welder that causes superficial melting of the surfaces of end portion 26 which, during the welding process, come into contact with correspondingly melting surfaces of peripheral walls 301,302. Such welding provides a perfectly water-impervious bond between stand 21' and bottom 30'.

One or more screws 70 can be used to further secure bottom 30' in appliance 1. As shown in Figure 7 which is an enlarged view of par D of Figure 5, screw 70 extends through a through-opening in bottom 30'. This through-opening is made water impervious by a sealing ring (e.g. an o-ring type gasket) 71 that is fitted around screw 70 and that is compressed between screw 70 and the facing walls delimiting the through-opening. Furthermore, the bottom part of tank 10 is welded, or otherwise connected, to feet 13, one of which is shown in Figures 5 and 8, that extend down along stand 21' to bottom 30' and are provided with a threaded hole 14 for securing screw 70 therein.

Moreover, tanks 10 shown in Figures 1 and 5 are provided with a stirrer positioning element 80 for a stirrer 85, 85' which is removably mounted thereon.

Stirrer 85,85' includes a peripheral part having stirring elements 86, such as turns of toroidally-shaped wire, impellers, blades, gratings or needles. Suitable drive means and configuration of the rotating stirrer, in particular the magnetic transmission arrangement between the electric device in the chamber and the stirrer in the tank, are disclosed in greater details in the abovementioned WO2006/050900.

However, as opposed to prior art stirrers, stirrers 85,85' have a top part 87,88,89 extending generally upright from peripheral part 86. This top part has a holding portion 87,88,89 that is arranged to accommodate for human fingers so as to facilitate extraction and insertion of stirrer 85,85' on the positioning element 80 of the tank 10.

The top part 87,88,89 includes a generally semi-circular arched member 87. In contrast to stirrer 85 shown in Figure 1, stirrer 85' depicted in Figure 5 further comprises an elongated upright rod 88 extending upwards from an upper end of the arched member 87. Moreover, upright rod 88 is topped with a laterally protruding generally spherical element 89 to facilitate seizure by human fingers.

Figures 9 and 10, in which the same numeric references designate the same elements, show stirrer 85 in greater detail. Stirring element 86 is in the form of a spring element in a loop arranged on a ring 86' that is secured via second connecting member 87c to a support member 87a. Arched member 87 is secured to support member 87a via first connecting members 87b. Furthermore, support member 87a has a through-opening D for the passage of stirrer positioning element 80.

Arched member 87, which is shown in cross-section in Figure 10, and connecting members 87b have a convex outer surface 87' and optionally a concave or straight inner surface 87''. Without being bound to any theory,

it is believed that that such a cross-section promotes the generation of cavitations during rotation of stirrer 85 in a liquid such as milk, especially nearby connecting members 87b that are subjected to the greatest tangential speed during rotation, leading to the formations of fine bubbles and an improved foaming of the liquid.

Figure 11, in which the same numeric references designate the same elements, shows another embodiment of a stirrer 85'' of the invention. In particular, stirrer 85'', instead of having a spring stirring element like in Figure 9, has two blade-like elements 86''.

In a further variation (not shown) of the invention, the arched member of the stirrer can have a generally parabolic, semi-elliptic or tapered shape or like shape, instead of a semi-circular shape.

Also shown in Figures 1 and 5, the appliances are fitted with heating elements that are connected to electric device 50. Details of suitable heating elements are described in greater details in the abovementioned WO2006/050900.

Heating element 56 and stirrer 85,85' may be controlled via push buttons 60 by the user. A stirrer may be associated with one or more buttons, for instance when the user is given the possibility to choose among several rotating speeds of the stirrer. Likewise, several buttons may be provided to choose a desired heating temperature. It will be apparent to the skilled person that many variations are possible to select and configure the control means so as to allow the user to choose, for example a desired heating temperature, stirring speed and conditioning duration and conditioning profile.

2008252932 20 Jun 2014

Claims

1. An appliance for conditioning a liquid comprising:
- a tank for receiving the liquid that is to be
5 conditioned;
- a closed compartment secured to the tank; and
- an electric device for imparting a conditioning
effect to the liquid, said device being located in the
compartment,
10 the compartment being made water impervious and
washable under running water without infiltration
thereof into the compartment containing the electric
device,
wherein the electric device is arranged to:
15 - impart the conditioning effect to the liquid which
is made of or based on milk; and
- drive a stirrer in rotation in the tank for
generating froth in the tank from the milk-made or
milk-based liquid.
20
2. The appliance according to claim 1 wherein the
conditioning effect is for preparing heated liquid
and/or a cold or heated frothed liquid.
- 25 3. The appliance according to claim 1 or claim 2,
wherein the electric device has one or more connection
means, the or each connection means extending through a
through-opening in an outer wall of the compartment,
said through-opening being made water impervious by a
30 sealing element located between a peripheral part of
said connection means and the outer wall.
4. The appliance according to claim 3, wherein said
through-opening is delimited by a surface of the wall,
35 the delimitation surface extending from inside to
outside the compartment and having a periphery, said
sealing element being located inbetween the peripheral
part of the connection means and the delimitation
surface and extending along the entire periphery of
40 said surface around the connection means, the sealing

2008252932 20 Jun 2014

element being optionally deformable and compressed by and between the peripheral part of the connection means and the delimitation surface of the corresponding through-opening.

5

5. The appliance according to claim 3 or 4, wherein the sealing element is made of plastic and/or elastic material, optionally silicone, that is cast between a peripheral part of said connection means and the outer wall.

10

6. The appliance according to any one of claims 3 to 5, wherein at least one connection means comprises an electric conductor, for supplying electric power from a power supply to the electric device and/or for communicating a signal from and/or to the electric device.

15

7. The appliance according to claim 6, wherein the electric conductor is a copper and/or aluminium based conductor.

20

8. The appliance according to claim 6 or claim 7 wherein the electric conductor extends through a through-opening which contains a sealing element that is cast and/or deformed in compression between and by the conductor rod or cable and a wall's surface delimiting the through-opening, said sealing element being optionally located in a cavity of the through-opening that extends transversally to the conductor rod or cable.

25

30

9. The appliance according claim 8, wherein at least one connection means comprises or leads to a user interface for controlling the electric device.

35

10. The appliance according to claim 9 wherein the user interface is a button, which extends into the through-opening.

40

2008252932 20 Jun 2014

11. The appliance according to claim 10, wherein said
button extending into the through opening comprises a
rigid support element, comprising a rigid annular
element, which has a peripheral surface that faces the
5 wall's surface delimiting the through-opening, the
sealing element being compressed around the entire
peripheral surface between and by said peripheral
surface and the delimitation surface, the sealing
element being optionally integral with or bonded to the
10 button.

12. The appliance according to claim 11, wherein the
button comprises a movable member that extends through
the through-opening, the support element being located
15 around the movable member, the movable member being
arranged to communicate into the compartment a user
command by displacement of the movable member, the
movable member being optionally movable in translation
along the through-opening and/or in rotation about a
20 rotational axis extending through the through-opening or
parallel thereto.

13. The appliance according to any one of preceding
claims, wherein the compartment is formed by the
25 assembly of at least two casing parts, the casing parts
being so assembled to be water impervious, at least one
casing part being:

- formed by at least part of the tank, at least one
further casing part being assembled with the tank to
30 form with the tank the compartment containing the
electric device; and/or
- a lid or a bottom element of the compartment.

14. The appliance according to claim 13 wherein two of
35 said casing parts are assembled together by welding to
seal off the compartment, two of said casing parts
having connection portions that are made of:

- thermoplastic material and that are welded together,
optionally by ultrasonic welding; or
- 40 - a metal-based material and that are welded together.

2008252932 20 Jun 2014

15. The appliance according to claim 13 or claim 14,
wherein the casing parts are assembled via a sealing
element that seals off the compartment, the casing
5 parts comprising a clip arrangement for securing them
together, optionally a rigid support member being
secured to the connection portion of one of said casing
parts and holding the cooperating connection portion of
the other casing part, said cooperating connection
10 portion being urged against the rigid support member by
the compressed sealing element located between the
cooperating connection portions.

16. The appliance according to claim 15, wherein the
15 sealing element is elastic and/or plastic deformable
and cast and/or compressed by and between cooperating
connection portions of the casing parts, the casing
parts having connection portions with substantially
facing surfaces that compress the sealing element that
20 optionally comprises:

- a body that extends over the surface of one
connection portion and that is placed thereagainst; and
- a plurality of transverse members that protrude from
said body to the surface of the facing connection
25 portion and that are compressed between said body and
the surface of the facing connection portion.

17. The appliance according to any one of claims 13 to
16, wherein a first casing part is mechanically secured
30 or further secured to or against a second casing part
by a mechanical assembly member, that extends through a
through-opening in said first casing part, said
through-opening being made water impervious by a
sealing element located between a peripheral part of
35 said mechanical assembly member and said first casing
part, said through-opening being delimited by a surface
of the first casing part, the delimitation surface
extending from one side to an opposite side of the
first casing part and having a periphery, said sealing
40 element being located inbetween the peripheral part of

2008252932 20 Jun 2014

5 the mechanical assembly member and the delimitation surface and extending along the entire periphery of said delimitation surface around the mechanical assembly member, the sealing element being optionally deformable and cast and/or compressed by and between the peripheral part of the mechanical assembly member and said delimitation surface.

10 18. The appliance according to claim 17 wherein the mechanical assembly member is a screw or rivet.

15 19. The appliance according to any one of the preceding claims, wherein the electric device in the chamber is arranged to drive the stirrer in the tank by generating a rotating magnetic field in the compartment that drives the stirrer in the tank without any mechanical transmission element extending through the tank between the electric device and the stirrer, the stirrer being removably mounted on a stirrer
20 positioning element in the tank.

25 20. The appliance according to claim 19 wherein the stirrer positioning element is a relief or recess in a bottom part of the tank.

30 21. The appliance according to any one of the preceding claims, wherein the electric device comprises heating means for heating the tank and a drive means for imparting a rotational movement to the stirrer located in the tank, the heating means and the drive means being operable independently from one another.

35 22. An appliance for conditioning a liquid substantially as herein described with reference to any one of the embodiments of the invention illustrated in the accompanying drawings and/or examples.

Fig. 1




Fig. 3






Fig. 4

Fig. 2






Fig. 1a

Fig. 2a




Fig. 6




Fig. 7




Fig. 8





Fig. 5






Fig. 9




Fig. 10




Fig. 11