

## (19) AUSTRALIAN PATENT OFFICE

(54) Title  
Hollow fiber membrane cassette

(51) 6 International Patent Classification(s)  
B01D 63/02 060101BHAU  
(2006.01) PCT/US02/0211  
B01D 63/02 2  
20060101AFI20

(21) Application No: 2002236864 (22) Application Date: 2002.01.23

(87) WIPO No: WO02/058827

(30) Priority Data

(31) Number (32) Date (33) Country  
60/263,192 2001.01.23 US

(43) Publication Date: 2002.08.06

(43) Publication Journal Date: 2003.02.06

(71) Applicant(s)  
Amersham Biosciences Membrane Separations Corp.

(72) Inventor(s)  
Herczeg, Attila

(74) Agent/Attorney  
Davies Collison Cave, Level 15 1 Nicholson Street, MELBOURNE,  
VIC, 3000

(56) Related Art  
WO 94/19094  
US 6103118 A  
US 6325928 A

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
1 August 2002 (01.08.2002)

PCT

(10) International Publication Number  
WO 02/058827 A1

(51) International Patent Classification<sup>7</sup>: B01D 63/02 (81) Designated States (national): AE, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CI, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, IC, IE, IS, FI, GB, GD, GE, GH, GM, IIR, IUU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, IT, LU, IV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PT, PL, PI, RO, RU, SD, SE, SG, SI, SK, SL, TI, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/US02/02112 (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(22) International Filing Date: 23 January 2002 (23.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 60/263,192 23 January 2001 (23.01.2001) US

(71) Applicant (for all designated States except US): INNOVASEP TECHNOLOGY CORPORATION [US/US]; 420 Maple Street, Unit #15, Marlborough, MA 01752 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): HERCZEG, Attila [US/US]; 4 Jacobs Lane, Southborough, MA 01772 (US).

(74) Agent: JAY, Jeremy, M.; Leydig, Voit & Mayer, Ltd., 700 Thirteenth Street, NW, Suite 300, Washington, DC 20005 (US).


Published:  
— with international search report  
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: HOLLOW FIBER MEMBRANE CASSETTE



WO 02/058827 A1



(57) Abstract: Hollow fiber membrane cassettes (1000) comprising an exterior casing (400), a filter (20) comprising two or more hollow fiber membranes (21), and an internal manifold (50) comprising first and second cassette headers (51, 52), wherein the cassette is arranged to allow feed flow, retentate flow, and permeate flow, and methods for making and using the cassettes, are disclosed.



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## HOLLOW FIBER MEMBRANE CASSETTE

## CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

[0001] This patent application claims the benefit of U.S. Provisional Patent Application No. 60/263,192, filed January 23, 2001, which is incorporated by reference.

## FIELD OF THE INVENTION

[0002] This invention pertains to cassettes comprising porous hollow fiber membranes.

## BACKGROUND OF THE INVENTION

[0003] Cassettes or other plate and frame formats incorporating a plurality of flat sheet membranes arranged between external stainless steel flat end plates and stainless steel manifolds (or between manifolds supported by stainless steel flat end plates) are utilized for a variety of filtration applications, particularly tangential flow filtration applications (also referred to as cross flow applications). In tangential flow filtration applications (TFF), the fluid to be filtered is passed through the inlet of the manifold and into the cassette and tangentially to the first (or upstream) surface of the membranes, such that a portion of the fluid passes through each of the membranes from the first surface to the second (or downstream) surface, through the cassette and one outlet of the manifold, and another portion passes tangentially to the first surface, through the cassette and another outlet of the manifold without passing through the membranes. The fluid passing into the inlet of the manifold and into the cassette is commonly referred to as the feed (the feed contains various sized molecules and possibly debris), the fluid passing from the first surface to the second surface is commonly referred to as the permeate or the filtrate (the permeate/filtrate contains the smaller molecules that will pass through the pores of the membrane), and the fluid passing parallel to the first surface of the membrane without passing to the second surface is commonly referred to as the retentate (the retentate contains the larger molecules that do not pass through the pores of the membrane).

[0004] However, conventional flat sheet membrane cassettes (including open channel cassettes and screen channel cassettes) have suffered from a number of deficiencies, particularly due to non-uniform flow distribution and/or fouling of at least one surface of the membranes. Fouling typically refers to the accumulation of material on the inside surface of the membrane. This accumulated material can block the pores of the membrane. Once the surface is fouled, filtration efficiency is decreased, and the membranes and

cassettes need to be cleaned or replaced. Additionally, some membranes and cassettes are difficult to clean.

[0005] The present invention provides for ameliorating at least some of the disadvantages of the prior art. These and other advantages of the present invention will be apparent from the description as set forth below.

#### BRIEF SUMMARY OF THE INVENTION

[0006] In accordance with an embodiment of the invention, a hollow fiber cassette is provided comprising an exterior casing comprising an internal manifold, and a filter comprising a plurality of hollow fiber membranes, the filter communicating with internal manifold, wherein the cassette is arranged to allow feed flow and permeate flow, and, in a preferred embodiment, retentate flow.

[0007] A hollow fiber cassette according to an embodiment of the invention comprises a filter housing, the filter housing including a plurality of filter housing permeate ports, a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes, an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports, the first cassette header further comprising at least one cassette feed port, and the second cassette header further comprising at least one cassette retentate port.

[0008] In accordance with an embodiment of the invention, a hollow fiber cassette is provided comprising a filter housing, the filter housing including a plurality of filter housing permeate ports, a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes, an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports and a cassette permeate connector, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports, and the cassette permeate ports are in fluid communication with the cassette permeate connector, the first cassette header further comprising a plurality of cassette feed ports and a cassette feed connector, wherein the cassette feed ports are in fluid communication with the cassette feed connector, and the second cassette header further comprising a plurality of cassette retentate ports and a cassette retentate connector, wherein the cassette retentate ports are in fluid communication with the cassette retentate connector. In a preferred embodiment, each of the connectors is a sanitary fitting.

[0009] Embodiments of the hollow fiber membrane cassette can be interchanged with flat sheet based cassettes or packets without the need to replace existing conventional flat end plate and external manifold or dual flat sheet external manifold systems or arrangements. Moreover, in some embodiments of the invention, the hollow fiber membrane cassette can be utilized without an external manifold.

[0010] The hollow fiber membrane cassettes can be utilized individually, stacked together and/or arranged on opposing sides of a central flat sheet manifold.

In another aspect, there is provided a hollow fiber cassette comprising an exterior 10 casing comprising an internal manifold, and a filter comprising a plurality of hollow fiber membranes, the filter communicating with internal manifold, wherein the cassette is arranged to allow feed flow, retentate flow, and permeate flow, wherein a plurality of ends of the plurality of hollow fiber membranes are pre-potted by a potting material in the filter housing, wherein the filter housing includes the plurality of outer surfaces covered with a 15 removable material; and wherein the removable material is configured to be removed from the plurality of ends of the plurality of hollow fiber membranes to remove an excess of the potting material.

In another aspect, there is provided a hollow fiber cassette system comprising: at least one first hollow fiber cassette comprising a filter housing, the filter housing including 20 a plurality of filter housing permeate ports; a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes; an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports; the first cassette header 25 further comprising at least one cassette feed port; and the second cassette header further comprising at least one cassette retentate port; and, in fluid communication therewith, an additional hollow fiber cassette comprising a filter housing, the filter housing including a plurality of filter housing permeate ports; a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes; an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each

- 3A -

comprising a plurality of cassette permeate ports and a cassette permeate sanitary fitting, wherin the filter housing permeate ports are in fluid communication with the cassette permeate ports, and the cassette permeate ports are in fluid communication with the cassette permeate sanitary fitting; the first cassette header further comprising a plurality of 5 cassette feed ports and a cassette feed sanitary fitting, wherein the cassette feed ports are in fluid communication with the cassette feed sanitary fitting; and the second cassette header further comprising a plurality of cassette retentate ports and a cassette retentate sanitary fitting, wherein the cassette retentate ports are in fluid communication with the cassette retentate sanitary fitting.

10 In another aspect, there is provided a method of processing a fluid comprising passing the fluid through a cassette, as described above, and obtaining a permeate passing through the filter.

In another aspect, there is provided a method for separating a fluid into a permeate and a retentate comprising: passing a feed fluid into a hollow fiber cassette comprising a 15 filter comprising a plurality of hollow fiber membranes, wherein each of the plurality of hollow fiber membranes has an inside surface and an outside surface; and an internal manifold including at least two permeate ports and at least one retentate port, the internal manifold being in fluid communication with the filter; passing a permeate through the inside and outside surfaces of the hollow fiber membranes and through the permeate ports; 20 passing a retentate through the retentate port; pre-potting a plurality of ends of the plurality of hollow fiber membranes in the filter by utilising a potting material, wherein the filter has a plurality of outer surfaces covered with a removable material; and providing the removable material in order to remove an excess of the potting material from the plurality of ends of the plurality of hollow fiber membranes.

- 3B -

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Figure 1 shows an exploded view of a hollow fiber cassette according to an embodiment of the invention, comprising a casing comprising an internal manifold comprising first and second cassette headers, the first cassette header including a plurality of feed ports, the second cassette header including a plurality of retentate ports, the first and second cassette headers also including a plurality of permeate ports, a filter housing including a plurality of permeate ports; and a filter comprising a plurality of hollow fiber membranes.

[0012] Figure 2 shows an assembled top view of the cassette shown in Figure 1.

[0013] Figure 3 illustrates a cross-sectional view along line 3-3 in Figure 2, showing the permeate flow path from the inside surfaces to the outside surfaces of the hollow fiber membranes and through the permeate ports in the filter housing and the first and second cassette headers, wherein a flat end plate (shown in dotted lines) is placed against one side of the cassette during use.

[0014] Figure 4 illustrates a cross-sectional view along line 4-4 in Figure 2, showing the retentate flow path from the first cassette header along the bores of the membranes and through the retentate ports of the second cassette header, wherein a flat end plate (shown in dotted lines) is placed against one side of the cassette during use.

[0015] Figure 5 shows a detailed isometric view of one of the cassette headers of the internal manifold shown in Figures 1 and 2, showing a plurality of feed or retentate ports, and a plurality of permeate ports, each permeate port comprising an inside permeate port and an outside permeate port, each set of inside and outside permeate ports being offset, and communicating via an intermediate permeate conduit.

[0016] Figure 6 shows an exploded view of a hollow fiber cassette according to an embodiment of the invention, comprising a casing comprising an internal manifold comprising first and second cassette headers, the first cassette header including a plurality of feed ports and a feed sanitary fitting, the second cassette header including a plurality of

retentate ports and a retentate sanitary fitting, the first and second cassette headers also including a plurality of permeate ports (permeate sanitary fitting, and permeate conduits for each cassette header not shown), a filter housing including a plurality of permeate ports; and a filter comprising a plurality of hollow fiber membranes.

[0017] Figure 7 shows an assembled view of the cassette shown in Figure 6 (also showing the permeate sanitary fitting for each cassette header).

[0018] Figure 8 shows a detailed isometric view of one of the cassette headers of the internal manifold shown in Figures 6 and 7, showing a plurality of feed or retentate ports communicating with a feed or retentate sanitary fitting; a permeate sanitary fitting, a plurality of permeate ports, each permeate port comprising an inside permeate port and an outside permeate port, each set of inside and outside permeate ports being offset, and communicating via an permeate intermediate conduit, and also showing additional permeate conduits, in fluid communication with the permeate intermediate conduits and the permeate sanitary fitting.

[0019] Figure 9 shows a plurality of hollow fiber cassettes as shown in Figure 2 stacked together as a cassette system for use with a conventional external manifold and flat end plate as used with flat membrane cassettes.

[0020] Figure 10 shows a plurality of hollow fiber cassettes as shown in Figures 2 and 7 stacked together as a cassette system wherein one hollow fiber cassette has a plurality of sanitary fittings, the cassettes being disposed between conventional flat membrane cassette system end plates, wherein a flat membranc cassette external manifold is not used.

[0021] Figures 11-14 show one embodiment of a method for sealing or potting a filter comprising a plurality of hollow fiber membranes in a filter housing. Figure 11 shows a plurality of hollow fiber membranes, each membrane being pre-potted at one end, arranged in a filter housing. Figure 12 shows potting one end of the filter housing, wherein the pre-potted hollow fiber membranes and the filter housing of Figure 11 are disposed in a potting cup containing encapsulant therein. Figure 13 shows a filter housing potted at opposing ends and having pre-potted hollow fiber membranes therein, the ends of the membranes extending from the opposing ends of the filter housing, wherein the membranes are cut to remove the pre-potted ends and provide open-ended membranes. Figure 14 shows the potted filter housing of Figure 13 with the filter therein, also showing the open ends of the hollow fibers.

## DETAILED DESCRIPTION OF THE INVENTION

[0022] In accordance with an embodiment of the present invention, a hollow fiber cassette is provided comprising a casing comprising an internal manifold, and a filter comprising a plurality of hollow fiber membranes, the filter communicating with internal manifold, wherein the cassette is arranged to allow feed flow, retentate flow, and permeate flow. In another embodiment, a hollow fiber cassette is provided comprising a casing comprising an internal manifold, and a filter comprising a plurality of hollow fiber membranes, the filter communicating with the internal manifold, wherein the cassette is arranged to allow feed flow, and permeate flow.

[0023] In preferred embodiments of the cassette, the filter is disposed in a filter housing, the internal manifold comprises a first cassette header and a second cassette header, and the casing further comprises a filter housing, wherein the cassette headers are disposed at opposing ends of the filter housing. More preferably, the filter housing comprises a plurality of filter housing permeate ports, and the first and second cassette headers each comprise a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports.

[0024] A hollow fiber cassette according to an embodiment of the invention comprises a filter housing, the filter housing including a plurality of filter housing permeate ports; a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes; an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports; the first cassette header further comprising at least one cassette feed port; and the second cassette header further comprising at least one cassette retentate port.

[0025] In preferred embodiments, the first cassette header includes at least two cassette feed ports, and the second cassette header includes at least two cassette retentate ports.

[0026] In accordance with another embodiment, a hollow fiber cassette is provided comprising a filter housing, the filter housing including a plurality of filter housing permeate ports; a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes; an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports and a cassette permeate connector, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports, and the cassette permeate ports are in fluid communication with the cassette permeate connector; the first cassette header further comprising a plurality of cassette feed ports and a cassette feed connector, the

cassette feed ports being in fluid communication with the cassette feed connector; and the second cassette header further comprising a plurality of cassette retentate ports and a cassette retentate connector, the cassette retentate ports being in fluid communication with the cassette retentate connector. In a preferred embodiment, the cassette permeate connectors, the cassette feed connector, and the cassette retentate connector, comprise sanitary fittings.

[0027] A hollow fiber cassette system according to an embodiment of the invention comprises at least two cassettes. The cassettes can be stacked together or separated, e.g., arranged on opposing sides of a bi-directional external flat membrane cassette manifold. One embodiment of a hollow fiber cassette system comprises (a) at least one first hollow fiber cassette comprising a filter housing, the filter housing including a plurality of filter housing permeate ports; a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes; an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports; the first cassette header further comprising at least one cassette feed port; and the second cassette header further comprising at least one cassette retentate port; and, in fluid communication therewith, (b) an additional hollow fiber cassette comprising a filter housing, the filter housing including a plurality of filter housing permeate ports; a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes; an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports and a cassette permeate sanitary fitting, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports, and the cassette permeate ports are in fluid communication with the cassette permeate sanitary fitting; the first cassette header further comprising a plurality of cassette feed ports and a cassette feed sanitary fitting, wherein the cassette feed ports are in fluid communication with the cassette feed sanitary fitting; and the second cassette header further comprising a plurality of cassette retentate ports and a cassette retentate sanitary fitting, wherein the cassette retentate ports are in fluid communication with the cassette retentate sanitary fitting.

[0028] In accordance with embodiments of the invention, methods for processing a fluid, e.g., to provide a permeate, more preferably, a permeate and a retentate, and methods for making a hollow fiber cassette, are also provided.

[0029] A method for separating a fluid into a permeate and a retentate according to an embodiment of the invention comprises passing a feed fluid into a hollow fiber cassette

comprising a filter comprising a plurality of hollow fiber membranes, wherein each of the plurality of hollow fiber membranes has an inside surface and an outside surface; and an internal manifold including at least two permeate ports and at least one retentate port, the internal manifold being in fluid communication with the filter; passing a permeate through the inside and outside surfaces of the hollow fiber membranes and through the permeate ports; and passing a retentate through the retentate port.

[0030] Typically, the cassette has a generally regular polygon configuration, for example, a generally rectangular configuration. In accordance with embodiments of the invention, the hollow fiber cassettes can be used with or without conventional external manifolds as used for flat sheet membrane cassettes. For example, in one embodiment, the hollow fiber membrane cassette is arranged such that it has similar dimensions to that of a flat sheet filtration cassette, flat sheet packet, or flat sheet plate and frame device, wherein the hollow fiber membrane cassette has a port design and geometry suitable for use as a retrofit of flat sheet filtration cassette or plate and frame installations, particularly those within the biopharmaceutical industry. Accordingly, there is no need to alter existing flat sheet manifolds, end plates, plumbing, or the like. However, in a preferred embodiment of the invention, the cassette is adapted for use without an external manifold, and can be used with existing end plates.

[0031] The casing (including the filter housing, and the internal manifold, e.g., the cassette header(s)) can be formed from any suitable polymeric material as is known in the art, e.g., molded and/or machined plastic (including thermoplastic), that is compatible with the fluid being processed. In a preferred embodiment, the casing is a polymer, preferably a transparent or translucent polymer, such as an acrylic, polypropylene, sulfone (including polysulfone, polyethersulfone, polyphenylsulfone, and polyarylsulfone), polystyrene, or a polycarbonated resin. Such a casing is easily and economically fabricated, and allows observation of the passage of fluid through the cassette.

[0032] In a preferred embodiment, the casing components or elements are joined to form an integral shell including ports, typically located on at least one side (preferably on opposing sides, in some embodiments, on three or four sides) of the casing. In accordance with the invention, the casing (e.g., the first and second cassette headers) is typically retained between a flat end plate and a flat cassette manifold designed for housing flat sheet membrane cassettes (e.g., as shown in Figure 9), or between a pair of flat end plates (e.g., as shown in Figure 10). If desired, the exterior casing can include one or more holes, grooves and/or cutouts, e.g., allowing the bolts for end plates to fit in the holes, grooves and/or cutouts. Such an arrangement can be useful in reducing the potential that the cassettes will

shift during use. Alternatively, or additionally, the casing can be adapted for ease of stacking cassettes, wherein the cassette headers include, for example ribs and/or grooves that allow stacked headers to fit together.

[0033] The internal manifold (preferably comprising a first cassette header and a second cassette header) comprises a series of ports, channels and/or internal conduits geometrically placed to optimize flow distribution to and from the filter, and, when used in retrofit applications, preferably has dimensions, porting, and geometry similar to that of the industry standard flat sheet installations, and carries the flow to and from the pre-disposed porting of the existing flat sheet manifold system.

[0034] The internal manifold includes at least one feed port and at least one permeate port, and typically also includes at least one retentate port. The internal manifold can have any number of ports. For example, each cassette header typically has 1 to 10 permeate ports, and 1 to 10 feed or retentate ports, and embodiments can have variations combinations of the types of ports, e.g., each cassette header can have 3 permeate ports, and 4 feed or retentate ports. Other embodiments can have fewer ports, or a greater number of ports. Typically, the first and second cassette headers each include at least 2 filtrate ports and at least two feed or retentate ports.

[0035] In some embodiments of the invention, the casing, more preferably, the first and/or second cassette headers, includes at least one connector, such as a barbed or threaded connector, a sanitary fitting, or a non-sanitary fitting. In one preferred embodiment, wherein the first and second cassette headers each comprise a cassette permeate connector, the first cassette header also including a cassette feed connector, the second cassette header also including a cassette retentate connector, each connector, i.e., the cassette permeate connectors, the cassette feed connector, and the cassette retentate connector, comprises a sanitary fitting.

[0036] Preferably, the first and second cassette headers each have opposing planar, or generally planar, top and bottom walls (e.g., the walls adapted for contacting the flat end plates). The first and second cassette headers can each have planar, or generally planar, opposing side walls. Typically, the opposing top and bottom walls have a larger planar area than the opposing side walls. If desired, any of the top, bottom, and side walls of the filter housing can be generally coplanar with the walls of the cassette headers.

[0037] The filter comprises at least one, and more preferably, two or more hollow fiber membranes. The filter is sealed in the filter housing which is potted at both ends with an encapsulant such as an adhesive (e.g., urethane and/or epoxy), thus sealing the feed and retentate from the permeate.

[0038] A variety of hollow fiber membranes, preferably porous hollow fiber membranes, can be utilized in the cassette, and a cassette can include two or more membranes having different characteristics. The hollow fiber membranes can comprise substantially smooth inner and outer surfaces, convoluted inner and/or outer surfaces, spiraled inner and/or outer surfaces, membranes having a spiral shape, or combinations thereof. The hollow fiber membranes, that are polymeric, or non-polymeric, can be skinned or unskinned. Alternatively, or additionally, the hollow fiber membranes can be symmetric or asymmetric.

[0039] The hollow fiber membranes can be produced in accordance with a variety of methods, including conventional melt spinning, dry-wet spinning, and wet-wet spinning processes. The membranes can be produced from any suitable metal, ceramic, polymer and/or combinations thereof. Preferably, the membranes are porous hollow fiber polymer membranes.

[0040] The membranes in the cassette can have any suitable pore structure, and the cassette can be used in microfiltration, ultrafiltration, and reverse osmosis applications.

[0041] In some embodiments of the cassette according to the invention, the filter comprises hollow fiber membranes having pores in the inner surface and inner portion that are larger than the pores at the outer surface and outer portion, providing efficient filtration (retaining and/or capturing larger molecules, species and debris, while allowing the smaller molecules and/or species to pass in the permeate) and advantageously providing increased capacity and resistance to fouling. In preferred embodiments, the membranes efficiently retain the larger molecules or species while allowing the smaller molecules or species of interest to pass through at a high concentration or throughput.

[0042] In an embodiment of the invention, the hollow fiber cassette provides a self-contained module, and a plurality of cassettes can be utilized without the use of external hardware manifolds for each cassette.

[0043] Embodiments of the invention can provide volume to filter surface area ratios and hold up volumes similar to that of conventional flat sheet cassette systems while providing a foot print similar to those conventional flat sheet systems. Moreover, since a single casing can be used, rather than a plurality of cylindrical housings or modules for hollow fibers (including the associated external conduits and fittings), the invention can have a smaller foot print and less fluid hold up than the plurality of cylindrical hollow fiber modules. Additionally, in many applications, the inventive cassette can allow the operator to reduce the pressure drop within a system, as hollow fiber membrane systems can exhibit lower resistance to flow through the feed channels than conventional flat sheet devices.

[0044] Embodiments of the invention are particularly suitable for filtering viscous solutions, solutions with high particulate loadings, and solutions sensitive to high shear. Cassettes according to the invention have a variety of applications, including, for example, gas and/or liquid filtration, for example, water filtration (e.g., particulate and/or microorganism removal from municipal water, or preparation of pure water for microelectronics), filtration of paint, waste water, and particulate, pyrogen, virus and/or microorganism removal from other fluids, including biological fluids such as blood.

[0045] In preferred embodiments, the cassettes are useful in filtering fluids for protein concentration and purification, e.g., for biopharmaceutical applications, e.g., to isolate cell expression products from cells and undesirable cellular matter. Other applications include, for example, cell-virus separation, cell-macromolecule separation, virus-macromolecule separation, and macromolecule-macromolecule separation.

[0046] While the cassettes are preferably used in tangential flow filtration applications, they can also be used in dead end flow applications. They can be used in single pass and multiple pass applications.

[0047] Each of the components of the invention will now be described in more detail below, wherein like components have like reference numbers. In accordance with the invention, the terms "permeate" and "filtrate" (including, for example, "permeate port" and "filtrate port") are used interchangeably.

[0048] Figures 1 and 2 show, respectively, exploded and assembled top views of a hollow fiber cassette or module 1000 according to an embodiment of the invention, comprising an external casing 400 comprising a filter housing 40, the filter housing having arranged therein a filter 20 comprising a plurality of hollow fiber membranes 21. The casing 400 also comprises an internal manifold 50 comprising first and second cassette headers 51, 52 communicating with the ends of the filter housing 40. An encapsulant (potting material) provides a seal 30 between the outside surfaces of the ends of the membranes and the inside of the filter housing 40.

[0049] In accordance with the embodiment shown in Figures 1 and 2, the filter housing 40 comprises a plurality of housing filtrate ports 202a-202e, 204a-204e (on one side of the housing), and 203a-203e, 205a-205e (on the opposing side of the housing), the first cassette header 51 comprises a plurality of feed ports 100a-100e and filtrate ports 200a-200d, and the second cassette header 52 comprises a plurality of retentate ports 102a-102e, and filtrate ports 206a-206d. While not shown in Figures 1 and 2, since a preferred embodiment of the cassette also has ports on the bottom side, the first header also comprises (as partially shown in Figures 3 and 4) a plurality of feed ports 101a-101e, and filtrate ports 201a-201e, and the

second header comprises a plurality of retentate ports 103a-103e, and filtrate ports 207a-207d.

[0050] In those embodiments wherein the hollow fiber cassette is used in a flat sheet cassette retrofit system (e.g., comprising an external flat cassette manifold and end plate), the cassette 1000 is arranged to receive feed flow from an external flat cassette manifold and subsequently direct retentate and permeate flow to the external manifold (e.g., as shown in Figure 9, showing external cassette manifold 500 with feed port 502 and retentate port 504, wherein the cassette 1000 is arranged between external manifold 500 and end plate 501; external manifold bolts and external manifold filtrate ports not shown). Thus, using Figures 9, 1, and 2 for reference, the cassette 1000 is arranged to receive feed flow from the external manifold 500 and provide feed flow through feed ports 100a-100e, retentate flow through ports 102a-102e, and filtrate flow through filtrate ports 200a-200d, and 206a-206e. As noted above, since an embodiment of the cassette also has ports on the bottom side, it is also arranged to provide feed flow through feed ports 101a-101e, retentate flow through ports 103a-103e, and filtrate flow through filtrate ports 201a-201c, and 207a-207d.

[0051] In the embodiment illustrated in Figures 1 (exploded view) and 2 (assembled view), the cassette 1000 is arranged for “inside-out” flow, i.e., wherein feed is directed into the bores of the hollow fiber membranes 21 of filter 20, filtrate passes from the inside surfaces of the membranes to the outside surfaces, and retentate passes tangentially to the inside surfaces and along the bores of the membranes. Figures 3 and 4 show cross-sectional views of the assembled cassette showing the feed, retentate, and permeate flow paths in more detail.

[0052] Accordingly, using Figures 1 and 3 for reference, wherein Figure 3 also shows an external flat cassette end plate 501 compressed against one side (e.g., the planar top walls) of the first and second cassette headers 51 and 52, feed is directed from the external manifold (not shown) through feed ports 101a-101e, feed chamber 160, and into the inner bores of the hollow fiber membranes 21. Filtrate passes from the inside surfaces of the membranes through the outside surfaces, through housing filtrate ports 203a-203e, and first cassette header filtrate ports 201a-201c, and through housing filtrate ports 205a-205e and second cassette header filtrate ports 207a-207d. Filtrate is subsequently passed through the filtrate ports of the external manifold (not shown).

[0053] In those embodiments wherein a flat end plate is not compressed against the cassette headers, e.g., wherein a plurality of cassettes are stacked together and feed is initially passed into the lower cassette, feed also passes through feed ports 100a-100e into the upper cassette(s), and filtrate from the upper cassette(s) passes into the lower cassette. If

desired, each of the cassettes can include at least one additional filtrate port arranged to allow the flow of filtrate from the upper cassette(s) to the lower cassette(s).

[0054] Retentate, i.e., the fluid not passing through the inner and outer surfaces of the membranes, passes tangentially to the inner surfaces of the membranes, and through the retentate ports. Accordingly, using Figures 1 and 4 for reference (wherein Figure 4 also shows the external flat cassette end plate 501 compressed against one side of the first and second cassette headers 51, 52), retentate passes tangentially to the inner surfaces of the membranes, along the hollow bores, into the retentate chamber 180, and through the retentate ports 103a-103e. The retentate can subsequently be passed through the retentate port(s) of the flat cassette manifold (e.g., retentate port 504 shown in Figure 9). In those embodiments wherein a flat end plate is not compressed against the cassette headers, e.g., wherein a plurality of cassettes are stacked together and feed passes from the lower cassette into the upper cassette(s), retentate also passes from the upper cassette(s), through retentate ports 102a-102e, into the retentate chamber and through retentate ports 103a-103e.

[0055] In those embodiments wherein a plurality of hollow fiber cassettes are stacked together, fluid can be passed through any number of cassettes.

[0056] In some embodiments, at least one cassette header, typically both cassette headers, include offset ports, e.g., to provide desirable flow and flow separation for the feed, permeate and retentate. Figure 5 shows a more detailed view of the embodiment of the cassette header, e.g., second cassette header 52, shown in Figure 1 (preferably, the first and second headers are arranged similarly, or identically), wherein each cassette filtrate port (206a-206e, 207a-207e) comprises an outside filtrate port (220a-220e and 221a-221e, respectively), an inside filtrate port (222a-222e and 223a-223e, respectively), and a filtrate intermediate conduit or channel (224a-224e and 225a-225e, respectively) providing fluid communication between the outside port and the inside port. For example, cassette filtrate port 206a comprises outside filtrate port 220a, inside filtrate port 222a, and filtrate intermediate conduit 224a interposed between the outside and inside filtrate ports. On the opposite side of the second cassette header, cassette filtrate port 207a comprises outside filtrate port 221a, inside filtrate port 223a, and filtrate intermediate conduit 225a interposed between the outside and inside filtrate ports.

[0057] Since the first and second cassette headers are preferably arranged similarly, using the embodiments illustrated in Figures 1 and 5 for reference, an embodiment of the first cassette header 51 comprises cassette filtrate ports (200a-200e, 201a-201e) comprising outside filtrate ports (212a-212e and 211a-211e, respectively), inside filtrate ports (214a-214e and 213a-213e, respectively), and filtrate intermediate conduits or channels

(216a-216e and 215a-215e, respectively) providing fluid communication between the outside port and the inside port. For example, cassette filtrate port 200a comprises outside filtrate port 212a, inside filtrate port 214a, and filtrate intermediate conduit 216a interposed between the outside and inside filtrate ports. On the other side of the first cassette header, cassette filtrate port 201a comprises outside filtrate port 211a, inside filtrate port 213a, and filtrate intermediate conduit 215a interposed between the outside and inside filtrate ports.

[0058] Such an offset port arrangement for the first and second cassette headers improves the space for flow between the feed and retentate ports of the cassette header and the internal bores of the membranes in the housing without interfering with the flow between the filtrate ports of the housing and the filtrate ports of the internal manifold. Once the filter housing is potted and the cassette assembled, the cassette is arranged such that the filtrate is isolated from the feed and retentate.

[0059] Figures 6-8 show another embodiment of a hollow fiber cassette or module 1000 according to the invention, also comprising an external casing 400 comprising a filter housing 40, having arranged therein a filter 20 comprising a plurality of hollow fiber membranes 21 (the filter being sealed in the housing as described above), wherein the casing 400 also comprises an internal manifold 50 comprising first and second cassette headers 51, 52 communicating with the ends of the filter housing 40. However, the embodiment of the cassette illustrated in Figures 6-8 also includes a plurality of sanitary fittings as shown in more detail in Figure 7, i.e., first cassette header 51 also comprises a feed sanitary port 150 and a filtrate sanitary port 250, and second cassette header 52 also comprises a retentate sanitary port 152 and a filtrate sanitary port 252. The sanitary fittings allow direct connections (without external manifolds) for feed, retentate, and permeate flow.

[0060] Figure 8 shows a more detailed view of the embodiment of a cassette header, e.g., second cassette header 52, shown in Figure 7. Similar to the embodiment of the second cassette header 52 shown in Figure 5, second cassette header 52 shown in Figure 8 comprises offset ports, wherein each filtrate port (206a-206e, 207a-207e) comprises an outside filtrate port (220a-220e and 221a-221e, respectively), an inside filtrate port (222a-222e and 223a-223e, respectively), and a filtrate intermediate conduit or channel (224a-224e and 225a-225e, respectively) providing fluid communication between the exterior port and the interior port. Thus, cassette filtrate port 206a comprises outside filtrate port 220a, inside filtrate port 222a, and filtrate intermediate conduit 224a interposed between the outside and inside filtrate ports. On the opposing side of the cassette header, cassette filtrate port 207a comprises outside filtrate port 221a, inside filtrate port 223a, and filtrate intermediate conduit 225a interposed between the outside and inside filtrate ports.

However, in accordance with the embodiment shown in Figure 8, the second cassette header 52 also comprises retentate sanitary port 152, a filtrate sanitary port 252, and additional filtrate conduits 251a-251e and 253a-253e. The additional filtrate conduits provide fluid communication between filtrate conduits 224a-224e, 225a-225e, and the filtrate sanitary port 252, and retentate sanitary port 152 is in fluid communication with retentate chamber 180. The first cassette header can have a similar arrangement of ports and conduits, wherein the feed sanitary port 150 is in fluid communication with feed chamber 160.

[0061] Illustratively, since the first and second cassette headers are preferably arranged similarly, using the embodiments illustrated in Figures 7 and 8 for reference, an embodiment of the first cassette header 51 comprises cassette filtrate ports (200a-200e, 201a-201e) comprising outside filtrate ports (212a-212e and 211a-211e, respectively), inside filtrate ports (214a-214e and 213a-213e, respectively), and filtrate intermediate conduits or channels (216a-216e and 215a-215e, respectively) providing fluid communication between the outside port and the inside port. The first cassette header 51 also comprises feed sanitary port 150 in fluid communication with feed chamber 160, as well as a filtrate sanitary port 250, and additional filtrate conduits 254a-254e and 256a-256e. The additional filtrate conduits provide fluid communication between filtrate intermediate conduits 214a-214e, 213a-213e, and the filtrate sanitary port 250, and feed sanitary port 150 is in fluid communication with feed chamber 160.

[0062] As with the embodiment illustrated in Figures 1, 2, and 5, the embodiment shown in Figures 6-8 can be utilized as a retrofit in flat sheet cassette applications, and can be used with conventional flat cassette systems. However, the embodiment shown in Figures 6 and 7 is especially advantageous in that it can be utilized with conventional flat end plates, without requiring the use of external flat plate manifolds. For example, as shown in Figure 10, since an embodiment of the inventive cassette includes a plurality of sanitary fittings, it can be placed between conventional flat end plates (flat plates 501 and 511), and feed, retentate, and filtrate lines can be connected without using an external manifold. Since typical external manifolds are stainless steel, with drilled ports designed for particular applications, the manifolds can be bulky, heavy, expensive, and unsuitable for a variety of applications. In accordance with this embodiment of the invention, the flat plates are merely used to hold the cassettes in place, and the same plates can be used to retain a variety of hollow fiber cassette configurations.

[0063] In accordance with the embodiments illustrated in Figures 6-8 and 10, feed is passed through feed sanitary port 150, feed chamber 160, and into the inner bores of the hollow fiber membranes 21. Filtrate passes from the inside surfaces of the membranes

through the outside surfaces, through housing filtrate ports 202a-202e, and first cassette header filtrate ports 200a-200e, and through housing filtrate ports 204a-204e and second cassette header filtrate ports 206a-206d. Filtrate passes through the associated permeate intermediate channels and additional filtrate conduits and through the permeate sanitary ports 250 and 252. Feed also passes through feed ports 100a-100e into the upper cassettes, and filtrate from the upper cassettes passes into the lower cassette after passing from the inside surfaces of the membranes through the outside surfaces. If desired, each of the cassettes can include at least one additional filtrate port arranged to allow the flow of filtrate from the upper cassette(s) to the lower cassette(s).

[0064] Retentate passes tangentially to the inner surfaces of the membranes, along the hollow bores, into the retentate chamber 180, and through the retentate sanitary fitting 152. Since feed passes from the lower cassette to the upper cassette(s), retentate passing from the upper cassette(s) passes into the lower cassette through the retentate ports 102a-102e and through the retentate sanitary fitting 152.

[0065] In accordance with the invention, any embodiments of the hollow fiber cassette can be used individually, or stacked together. In one illustrative arrangement, as shown in Figure 10, one or more cassettes as shown in Figure 2 can be stacked on one of the cassettes as shown in Figure 7. In yet another embodiment, as shown in Figure 9, two or more cassettes as shown in Figure 1 are stacked together.

[0066] It should be clear that while the illustrated embodiments show cassettes arranged for "inside-out" flow, in another embodiment of the invention (not shown) the hollow fiber cassette is arranged for "outside-in" flow, i.e., feed is directed to the outside surfaces of the membranes, and the filtrate passes from the outside surfaces of the membranes to the inside surfaces and through the bore of the membranes. Additionally, while the illustrated embodiments show tangential flow filtration, other embodiments of the cassette are arranged for dead-end filtration.

[0067] Figures 11-14 show an exemplary embodiment of a method for preparing the cassette, particularly for arranging the filter in the filter housing. For example, an empty filter housing 40 is obtained, and a plurality of hollow fiber membranes 21 is disposed therein, preferably such that both ends of each of the fiber membranes extend beyond the end of the housing 40. If desired, the ends of the membranes can be sealed, e.g., filled with an encapsulant (sometimes referred to as "pre-potting," which typically comprises placing the end of the membrane in a potting material, removing the end from the material, and letting the potting material harden) before disposing the membranes in the casing. Alternatively, the membranes can be pre-potted after disposing the membranes in the filter

housing. Figure 12 shows a plurality of hollow fiber membranes (each membrane having one end 90 pre-potted) arranged in the housing. The encapsulant in the ends of the membranes should not extend to the end of the housing 40, since, as is shown in Figure 13, after the housing has been removed from the potting material and the material has hardened, the membranes (e.g., the potted ends 90) will be trimmed flush with the ends of the housing 40 such that the ends of the membranes are open.

[0068] After pre-potting, the housing is potted such that the housing ends are sealed, i.e., the area between the membranes and the area between the inside surface of the housing and the outside surface of the membranes is sealed. For example, each end of the housing, having a plurality of pre-potted membranes extending from the end, can be placed in an encapsulant. Figure 12 shows one end of the housing placed in a potting cup 600 having encapsulant 30a (potting adhesive) therein. In this illustrated embodiment, the housing is arranged in the potting cup such that the filtrate ports of the housing are above the level of the encapsulant, thus preventing the filtrate ports from being sealed with encapsulant while allowing the end of the housing to be sealed. If desired, the outer surfaces of the ends of the housing can be covered with a removable material such as teflon tape, e.g., to subsequently allow excess hardened encapsulant to be neatly removed.

[0069] The other end of the filter housing can be potted in a similar manner. As shown in Figure 13, after the ends of the housing have been removed from the potting cup and the potting material has hardened, the ends of the hollow fiber membranes are then trimmed flush with the ends of the housing, providing (as shown in Figure 14) potted housing ends without blocking the internal bores of the membranes.

[0070] Subsequently, the internal manifold 50, comprising first and second cassette headers 51 and 52, is mated with the ends of the filter housing, such that the filtrate ports in the headers communicate with the respective filtrate ports in the housing, and the feed and retentate ports in the headers communicate with the respective internal bores of the membranes. Typically, the cassette headers and the filter housing are configured so that there is a tight fit between the outer surfaces of the filter housing, and the inner surfaces of the cassette headers.

[0071] Preferably, the filter housing 40 is sealed to the internal manifold 50, more preferably using an adhesive. Once the hollow fiber cassette is assembled, it can be utilized in filtration applications, e.g., wherein the cassette headers are mated with external manifolds and/or end plates or holders, e.g., end plates designed for housing flat sheet membrane cassettes. Since the cassette preferably has a configuration (e.g., dimensions and porting) similar to that of the industry standard flat sheet installations (e.g., flat sheet

cassettes or plate and frame devices), embodiments of the invention can be utilized with conventional systems without additional parts, adapters, and/or modifications.

[0072] The cassette can have any suitable configuration, e.g., any number of feed, retentate and filtrate ports, any number of fibers (wherein the fibers have similar or different characteristics such as pore structure, asymmetry, symmetry, wall thickness, tensile strength, inner diameter, outer diameter). While Figures 5 and 8 shows embodiments of a cassette header having offset inside and outside cassette filtrate ports each connected via a substantially horizontal permeate intermediate conduit, other embodiments lack offset port and/or conduits. Alternatively, or additionally, the filtrate ports can be connected via other conduit configurations, e.g., diagonal conduits, curved conduits, and combinations thereof.

[0073] All references, including publications, patent applications, and patents, cited herein are hereby incorporated by reference to the same extent as if each reference were individually and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

[0074] The use of the terms "a" and "an" and "the" and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., "such as") provided herein, is intended merely to better illuminate the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention.

[0075] Preferred embodiments of this invention are described herein, including the best mode known to the inventors for carrying out the invention. Of course, variations of those preferred embodiments will become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate, and the inventors intend for the invention to be practiced otherwise than as specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as

permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

"The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates."

Throughout this specification and claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated integer or group of integers or steps but not the exclusion of any other integer or group of integers.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A hollow fiber cassette comprising:  
a filter housing, the filter housing including a plurality of filter housing permeate ports;  
a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes;  
an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports;  
the first cassette header further comprising at least one cassette feed port; and  
the second cassette header further comprising at least one cassette retentate port.
2. A hollow fiber cassette comprising:  
a filter housing, the filter housing including a plurality of filter housing permeate ports;  
a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes;  
an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports and a cassette permeate connector, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports, and the cassette permeate ports are in fluid communication with the cassette permeate connector;  
the first cassette header further comprising a plurality of cassette feed ports and a cassette feed connector, wherein the cassette feed ports are in fluid communication with the cassette feed connector; and  
the second cassette header further comprising a plurality of cassette retentate ports and a cassette retentate connector, wherein the cassette retentate ports are in fluid communication with the cassette retentate connector.
3. A hollow fiber cassette system comprising;  
the hollow fiber cassette of claim 1, in fluid communication with the hollow fiber cassette of claim 2.
4. A hollow fiber cassette comprising an exterior casing comprising an internal manifold, and a filter comprising a plurality of hollow fiber membranes, the filter

communicating with internal manifold, wherein the cassette is arranged to allow feed flow, retentate flow, and permeate flow, wherein a plurality of ends of the plurality of hollow fiber membranes are pre-potted by a potting material in the filter housing, wherein the filter housing includes the plurality of outer surfaces covered with a removable material; 5 and wherein the removable material is configured to be removed from the plurality of ends of the plurality of hollow fiber membranes to remove an excess of the potting material.

5. The cassette of claim 4, wherein the exterior casing comprises a filter housing and the internal manifold, the filter housing including a plurality of filter housing permeate 10 ports, the internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports.

15 6. A hollow fiber cassette system comprising:  
at least one first hollow fiber cassette comprising a filter housing, the filter housing including a plurality of filter housing permeate ports;

a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes;

20 an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette permeate ports, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports; the first cassette header further comprising at least one cassette feed port; and the second cassette header further comprising at least one cassette retentate 25 port; and, in fluid communication therewith,

an additional hollow fiber cassette comprising a filter housing, the filter housing including a plurality of filter housing permeate ports;

a filter disposed in the housing, the filter comprising a plurality of hollow fiber membranes;

30 an internal manifold comprising a first cassette header and a second cassette header, the first and second cassette headers each comprising a plurality of cassette

2002236864 15 May 2006

- 20A -

permeate ports and a cassette permeate sanitary fitting, wherein the filter housing permeate ports are in fluid communication with the cassette permeate ports, and the cassette permeate ports are in fluid communication with the cassette permeate sanitary fitting; the first cassette header further comprising a plurality of cassette feed ports and a cassette feed sanitary fitting, wherein the cassette feed ports are in fluid communication with the cassette feed sanitary fitting; and the second cassette header further comprising a plurality of cassette retentate ports and a cassette retentate sanitary fitting, wherein the cassette retentate ports are in fluid communication with the cassette retentate sanitary fitting.

7. The cassette of any of claims 1, 2, 4 and 5, wherein the first and/or second cassette header permeate ports comprise offset inside and outside permeate ports.
8. The cassette of any of claims 1, 2, 4, 5, and 7, wherein the first and/or second cassette headers comprise at least one sanitary fitting.
9. The cassette of claim 8, wherein the first and second cassette headers each comprise a permeate sanitary fitting.
10. The cassette of claim 9, wherein the first cassette header further comprises a feed sanitary fitting, and the second cassette header further comprises a retentate sanitary fitting.
11. The cassette of any of claims 1, 2, 4, 5, and 7-10, adapted for use with a flat membrane cassette manifold system.
12. The cassette of any of claims 1, 2, 4, 5, and 7-11, adapted for use with a two flat end plates.
13. The cassette of any of claims 1, 2, 4, 5, and 7-12, wherein the hollow fiber membranes each have an inner bore, an inner surface and an outer surface, and the cassette is arranged to direct feed flow into the bores of the membranes.
14. The cassette of any of claims 1, 2, 4, 5, and 7-12, wherein the hollow fiber membranes each have an inner bore, an inner surface and an outer surface, and the cassette is arranged to direct feed flow to the outer surfaces of the of the membranes.
15. The cassette of any preceding claim, wherein the internal manifold comprises first and second cassette headers, the first and second cassette headers each comprising opposing planar top and bottom walls.
16. A method of processing a fluid comprising:  
passing the fluid through the cassette of any of claims 1, 2, 4, 5 and 7-15; and  
obtaining a permeate passing through the filter.

2002236864 15 May 2006

17. A method for separating a fluid into a permeate and a retentate comprising:  
passing a feed fluid into a hollow fiber cassette comprising  
a filter comprising a plurality of hollow fiber membranes, wherein each of the  
plurality of hollow fiber membranes has an inside surface and an outside surface; and  
5 an internal manifold including at least two permeate ports and at least one retentate  
port, the internal manifold being in fluid communication with the filter;  
passing a permeate through the inside and outside surfaces of the hollow fiber  
membranes and through the permeate ports;  
passing a retentate through the retentate port; pre-potting a plurality of ends of the  
10 plurality of hollow fiber membranes in the filter by utilising a potting material, wherein the  
filter has a plurality of outer surfaces covered with a removable material; and providing the  
removable material in order to remove an excess of the potting material from the plurality  
of ends of the plurality of hollow fiber membranes.

15 18. A hollow fiber cassette, substantially as described with reference to the drawings  
and/or examples.

19. A method for processing a fluid, substantially as described with reference to the  
drawings and/or examples.

20 20. A method for separating a fluid, substantially as described with reference to the  
drawings and/or examples.

DATED this 15th day of May 2006

25 **Amersham Biosciences Membrane Separations Corp.**  
by DAVIES COLLISON CAVE  
Patent Attorneys for the applicant

1






FIG. 2








FIG. 5





FIG. 6







FIG. 8






FIG. 11




FIG. 12

