

**(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. AU 2004210661 B2

(54) Title
Vascular clamp for caesarian section

(51) International Patent Classification(s)
A61B 17/08 (2006.01)

(21) Application No: **2004210661** (22) Date of Filing: **2004.02.03**

(87) WIPO No: **WO04/071275**

(30) Priority Data

(31) Number
10/359,386 (32) Date
2003.02.05 (33) Country
US

(43) Publication Date: **2004.08.26**
(44) Accepted Journal Date: **2009.12.10**

(71) Applicant(s)
Vascular Control Systems, Inc.

(72) Inventor(s)
Jones, Michael L.;Altieri, Greig;Serra, R. J.;Uyeno, Jill;Burbank, Fred H.

(74) Agent / Attorney
Watermark Patent & Trademark Attorneys, Level 2, 302 Burwood Road, Hawthorn, VIC, 3122

(56) Related Art
US2002/0183771
US6299621

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
26 August 2004 (26.08.2004)

PCT

(10) International Publication Number
WO 2004/071275 A3

(51) International Patent Classification⁷: A61B 17/08 (74) Agent: LYNCH, Edward, J.; Duane Morris LLP, One Market, Spear Tower, Suite 2000, San Francisco, CA 94105 (US).

(21) International Application Number: PCT/US2004/003023 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 3 February 2004 (03.02.2004) (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English (26) Publication Language: English


(30) Priority Data: 10/359,386 5 February 2003 (05.02.2003) US

(71) Applicant: VASCULAR CONTROL SYSTEMS, INC. [US/US]; 32236-E Paseo Adelanto, San Juan Capistrano, CA 92675 (US).

(72) Inventors: BURBANK, Fred, H.; 12 Old Ranch Road, Laguna Niguel, CA 92677 (US). JONES, Michael, L.; 6332 Camino Marinero, San Clemente, CA 92673 (US). SERRA, R., J.; 17 Misty Meadow, Irvine, CA 92612 (US). ALTIERI, Greig; 1102 Temple Hills Drive, Laguna Beach, CA 92651 (US). UYENO, Jill; 27550 Hillcrest #4Q, Mission Viejo, CA 92691 (US).



(54) Title: VASCULAR CLAMP FOR CEASARIAN SECTION



WO 2004/071275 A3

(57) Abstract: The invention provides devices, systems and methods for clamping arteries which are useful in reducing or abolishing blood flow in an artery, and may be used to control hemorrhage flowing a caesarian delivery. A clamping device embodying features of the invention includes a pair of clamping members with opposed pressure-applying members having facing pressure-applying surfaces, at least one of which is a yieldable pressure-applying surface. The yieldable pressure-applying surface is preferably resilient. The clamping members are configured to adjust the distance between pressure-applying surfaces, and a blood flow sensor is disposed on at least one of the pressure-applying members to aid in locating the target artery and also to monitor blood flow through the artery. The clamping device is particularly suitable for occluding uterine arteries by compressing the broad ligament which contains the uterine artery and which is connected to the patient's uterus with the arterial clamp.

[Continued on next page]



— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

24 March 2005

VASCULAR CLAMP FOR CAESARIAN SECTION

FIELD OF THE INVENTION

[0001] The invention relates generally to the field of treatment of diseases and conditions by the regulation of blood flow in blood vessels. In particular, the invention is directed to the treatment of uterine hemorrhage by reducing blood flow in a uterine artery.

BACKGROUND OF THE INVENTION

[0002] Delivery of a baby is followed by separation of the placenta from the uterine wall, usually resulting in a significant loss of blood. Fortunately, the uterus is resistant to anoxic damage caused by reduced blood flow. For example, uterine muscle is typically poorly perfused during labor contractions, yet typically suffers no lasting ill effects from this situation. However, hemorrhage from the uterus following delivery may cause loss of a significant fraction of the mother's blood if it is not stopped quickly. Blood loss from prolonged hemorrhage following delivery presents a serious threat to the life and health of the mother.

[0003] The muscular contractions and hormonal changes accompanying vaginal delivery promote rapid cessation of post-partum hemorrhage. However, caesarian delivery is typically not accompanied by such contractions and hormonal changes, and also entails physical injury to the uterus additional to that caused by placental separation. Delivery by caesarian section is thus often accompanied by hemorrhage from the placental attachment site and from the uterine incision required for delivery of the infant. Medical intervention is typically required to reduce blood loss following caesarian deliveries.

[0004] The primary blood supply to the uterus, both in the non-gravid uterus and in the pregnant uterus, is from the uterine arteries. A small communicating artery arising from each ovarian artery reaches uterus but in gravid and non-gravid states supplies less than 10% of uterine blood flow. The uterine arteries arise from the internal iliac arteries and reach the uterus through the base of the broad ligament in a space that can not be seen from a surgical perspective looking down on the uterus from within the peritoneal cavity or from a gynecological perspective looking up at the cervix from the vagina. The uterine arteries are, therefore, not visible.

[0005] Once the uterine arteries reach the uterus, they give rise to a large ascending branch that supplies the uterus and a smaller descending branch that supplies the cervix. These branches, in turn, give rise to anterior and posterior arcuate arteries. Right and left anterior arcuate arteries anastomose in the anterior sagittal midline of the uterus; posterior arcuate arteries, in the posterior sagittal uterine midline. Consequently, to reduce blood loss following caesarian delivery from the hysterotomy site and from the placenta attachment site, right and left uterine arteries must both be occluded.

[0006] Attempts have been made to reduce caesarian delivery blood loss. One method has been to initiate uterine contractions by administering oxytocin or oxytocin-like drugs following caesarian delivery. Another method has been blind clamping of the uterine and ovarian arteries using rubber covered arterial clamps, which was proposed as early as 1922. Similarly, intestinal clamps have been applied to the uterus along its right and left lateral borders, across the entire broad ligament, to minimize caesarian blood loss. Another method includes bilateral surgical ligation of the internal iliac arteries to diminish hemorrhage following caesarian delivery. Bilateral surgical ligation of the uterine arteries, or of the

ascending branches of the uterine arteries, to reduce hemorrhaging has been performed from abdominal cavity and from transvaginal approaches. Intravascular balloon occlusion of the aorta and embolic occlusion of the uterine arteries have also been used to treat caesarian hemorrhage. However, all of these methods have met with only limited adoption for a variety of reasons.

[0007] For example, many physicians do not possess the training or equipment necessary to perform catheter-based uterine artery embolization under radiologic direction. In addition, such treatments are not appropriate in the case of caesarian hemorrhage, where rapid treatment can be critical and arterial catheterization may not be practical.

[0008] Location of the uterine arteries in a patient immediately following a caesarian delivery may be difficult; in addition to being located within the broad ligament that supports the uterus, the uterine arteries are near or within the caesarian surgical field, and so are typically covered with blood, amniotic fluid, and the like which can impede visual identification and medical access following caesarian section. Rapid identification and location of the uterine arteries is required in order to prevent unchecked hemorrhage.

[0009] Accordingly, there is need for devices and methods to control blood flow in blood vessels such as uterine arteries by physicians with little training in a simple medical setting or environment.

Any discussion of documents, devices, acts or knowledge in this specification is included to explain the context of the invention. It should not be taken as an admission that any of the material formed part of the prior art base or the common general knowledge in the relevant art in Australia on or before the priority date of the claims herein.

SUMMARY OF THE INVENTION

[0010] In accordance with an aspect of the invention there is provided An arterial clamping system including:

a) a clamping device for at least partially occluding a target vessel in a patient's body, including a pair of opposed pressure-applying members configured to at least partially occlude the target vessel by applying pressure thereto, with at least one of the pressure-applying members having a floating,

pressure-applying jaw with a continuos pressure applying surface movable mounted thereto and having a resilient connection between the floating, pressure-applying jaw and the pressure applying member, the resilient connection being at least partially surrounded by side walls extending from the continuos pressure applying surface of the floating, pressure-applying jaw and toward the pressure-applying member, wherein the side walls have a plurality of slots and the at least one of the pressure-applying members has a plurality of pins projecting from lateral edges thereof that are disposed in the slots for guiding movement of said floating, pressure-applying jaw; and a sensor on at least one of the pressure-applying jaws fro locating the target vessel, wherein the sensor is movable mounted to a distal end of the clamping device; and

b) a sensor controller operatively connected to the sensor and including a source of power.

[0010a] In accordance with a further aspect of the invention there is provided a device for treating a female patient's uterus by occluding a uterine artery thereof including:

a pair of opposed clamping elements;

at least one of the clamping elements having a floating pressure-applying jaw movable mounted thereto, wherein the jaw includes a continuous pressure-applying surface and is adapted to at least partially occlude a target uterine artery by applying pressure thereto;

a resilient connection between the clamping element and the jaw movable mounted thereto, the resilient connection being at least partially surrounded by side walls extending between the continuous pressure-applying surface of the floating pressure-applying jaw and one of the opposed clamping elements;

a guide assembly coupled with the floating pressure-applying jaw for guiding movement of the floating pressure-applying jaw toward and away from the at least one of the opposed clamping elements; and

a blood flow sensor disposed on at least one of the pressure applying jaws for locating the target uterine artery to be clamped, wherein the blood flow sensor is attached to the floating pressure-applying jaw for moving with the floating pressure-applying jaw.

[0010b] In accordance with a still further aspect of the invention there is provided a device for treating a female patient's uterus after caesarean section by occluding the patient's uterine artery including:

a pair of opposed clamping elements having pressure-applying jaws configured to at least partially occlude a target uterine artery by applying pressure thereto;

at least one of the pressure-applying jaws being a floating jaw movably mounted to one of the clamping elements and having a resilient connection with the one of the clamping elements; and

a blood flow sensor disposed on at least one of the pressure applying jaws for locating the target uterine artery to be clamped, wherein the floating jaw has side walls extending from a clamping surface thereof, the side walls being slid able over lateral edges of the one of the clamping elements.

[0010c] In accordance with a still further aspect of the present invention, there is provided a clamping device for occluding a target vessel including:

a pair of opposed pressure-applying members;

at least one of said pressure-applying members having a distal end including a yieldable pressure-applying surface;

a guide assembly coupled with the at least one of said pressure-applying members for guiding movement of said yieldable pressure-applying surface toward and away from the at least one of said pressure applying members.

[0010d] As used herein the terms "yieldable" and "resilient" or words of similar import refer to being yieldable or resilient under the conditions of use. The invention is particularly suitable for occluding a patient's uterine artery after a caesarian delivery.

[0011] The pressure-applying surfaces yield with pressure upon contact with tissue, so that the surface moves, or is deformed, or compresses upon contact with tissue and application of pressure to tissue. Such surfaces may be resilient, in that they at least partially recover their original configuration or position following release of pressure. The pressure-applying surface or surfaces attached to the pressure-applying members of the clamping device can be pressed against the target vessel such as a uterine artery to be occluded or

against a tissue bundle containing the target vessel to be occluded in order to partially or completely stop blood flow through the target vessel. The procedure and the instruments for such procedure are suitable for occluding an artery such as a uterine artery to prevent or at least minimize blood loss during a surgical procedure. The procedure is particularly suitable to partially or completely occlude a female patient's uterine or ovarian artery during a caesarian delivery.

[0012] In one embodiment of the invention, at least one of the pressure-applying surfaces is provided with a sensor to locate the blood

[0013] The yieldably (e.g., movably, compressibly, or otherwise giving in response to pressure) and preferably resiliently mounted pressure-applying surface can be applied to tissue to facilitate location of a blood vessel to be occluded without applying a significant clamping force on the blood vessel which can significantly affect blood flow through the blood vessel. Once the blood vessel is located by a sensor on the one or more pressure-applying surfaces, more pressure may be applied to the one or more pressure-applying surfaces to partially or totally occlude the blood vessel. The distance between the opposed pressure-applying members is adjustable, by, for example, the pressure-applying members being connected by a pivot and able to rotate around it effective to apply adequate pressure to tissue.

[0014] The pressure-applying surfaces may themselves be yieldable or resilient surfaces. In addition, or alternatively, the pressure-applying surfaces may be joined with the pressure-applying members by a yieldable connection, preferably configured to allow transverse motion of the pressure-applying surface with respect to its supporting pressure-applying member. In preferred embodiments, the yieldable connection joining the pressure-applying surfaces with the pressure-applying members comprises a resilient connection. In this way, the pressure-applying surfaces provide a floating jaw attached to the pressure-applying members by a yieldable, and preferably resilient, connection. Such a floating jaw is configured to engage tissue and to lightly contact tissue with minimal pressure to locate the blood vessel, and, upon application of greater amounts of force that more fully compress the yieldable or resilient connection, to apply pressure to tissue sufficient to occlude a blood vessel within or adjacent the contacted tissue.

[0015] The sensors suitable for use with the clamping devices of the invention are preferably blood flow sensors, more preferably Doppler ultrasound blood flow

sensors, and may be a sensor/transducer. A Doppler sensor may provide audible identification of an artery; for example, a Doppler sensor with a sensor controller having a speaker may provide audible identification of the uterine arteries through the broad ligament without the need for tissue dissection in the broad ligament and visual identification of the blood vessel. The sensor may be a sensor/transducer including a source of energy, or may be a passive sensor, responding to energy supplied externally of the sensor.

[0016] Each of the pressure applying members of the clamping device embodying features of the invention preferably has a handle which are pivotally connected. The proximal ends of the handles may include a locking mechanism such as ratcheting mechanisms to lock the pressure applying members in a closed or partially closed condition. Preferably, the locking mechanism is releasable so at the completion of the procedure the clamping device may be removed from the patient.

[0017] An arterial clamp embodying features of the invention is useful for sensing the location of a uterine artery within or adjacent the broad ligament secured to the uterus, and is useful to compress and occlude a uterine artery within the broad ligament.

[0018] One method of occluding an artery comprises clamping the artery effective to compress it so that blood flow through the vessel is reduced, or is abolished. Arterial occlusion is temporary, being relieved after removal of the device, and may be partial or complete.

[0019] A controller may be provided for the blood flow sensor to aid in detecting the location of a uterine artery, by generating a signal related to the output of the sensor that can be readily used by an operator. The sensor controller may also include an energy source for the blood flow sensor, such as a source of ultrasound

energy, electrical energy, or electromagnetic energy. The energy may be directly provided by the energy source or may be provided by the sensor with the aid of the energy source.

[0020] Utilization of the clamping device having features of the invention to occlude a uterine artery following a caesarian delivery can prevent excessive blood loss and importantly with such prevention of blood loss, allows increased time for improved suturing of the uterus. For example, a two-or three-layer surgical closure can be performed without the worries of excessive bleeding. This can affect better closure with less complication from incisions or scarring of the uterus which can lead to abortions or uterine rupture during future pregnancies.

"Comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof."

[0021] The devices, systems and methods embodying features of the invention may be effectively used with little or no training. These and other advantages of the invention will become more apparent from the following detailed description of the invention when taken in conjunction with the accompanying exemplary drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] Figure1 is a plan view of a blood vessel occluding system including an arterial clamp embodying features of the invention which is disposed in an open configuration.

[0023] Figure 2A is a fragmentary sectional view of a distal portion of an arterial clamp embodying features of the invention having a pressure-applying member with an "O"-ring providing resiliency.

[0024] Figure 2B is a fragmentary sectional view of a distal portion of an arterial clamp embodying features of the invention having a pressure-applying member with a plurality of springs providing resiliency.

[0025] Figure 2C is a fragmentary sectional view of a distal portion of an arterial clamp embodying features of the invention having a pressure applying member with a flexible bladder to provide resiliency.

[0026] Figure 2D is a fragmentary sectional view of a distal portion of an arterial clamp embodying features of the invention having a pressure applying member with an elastic layer providing resiliency.

[0027] Figure 3 is a perspective view of an angled distal portion of an arterial clamp embodying features of the invention disposed in an open configuration.

[0028] Figure 4 is a transverse cross-sectional view of one jaw of the angled distal portion of the clamping device of Figure 3 taken at line 4-4.

[0029] Figure 5 is schematic diagram of a reproductive system of a human female including major uterine arteries providing blood flow to the uterus showing the deployment of the arterial clamp shown in Fig. 1 in a female patient's anatomy.

DETAILED DESCRIPTION OF THE INVENTION

[0030] Figures 1-4 show a uterine artery-occluding system 10 embodying features of the invention which includes a clamping device 12 having clamping members 14, handles 16 with finger grips 17, pressure-applying members 18 and floating jaws 20 on the pressure applying members. Floating jaws 20 have serrated pressure-applying surfaces 22 configured to engage and hold onto tissue when floating jaws 20 are pressed into a patient's body tissue. Clamping members 14 are pivotally interconnected at pivot point 24. Clamping members 14 are preferably formed with the handles 16 integral with the pressure applying members 18. The operator squeezes the finger grips 17 on clamping members 14 to cause pressure-applying surfaces 22 to approach one another as the separation distance between pressure-applying members 18 decreases. Each of the handles 16 are provided

with releasable locking mechanism 26 including two complementary ratchet portions 27 configured to engage with each other and to lock clamping members 14 in a closed or partially closed position, maintaining pressure or force between pressure-applying surfaces 22 while the locking mechanism 26 is engaged.

[0031] Floating jaws 20 are movably joined to pressure-applying members 18 by a connection 28. Connection 28 is a yieldable connection, so that pressure on pressure-applying surface 22, or contact with a surface by pressure-applying surface 22 while pressure is applied by pressure-applying members 18, causes motion of a floating jaw 20 with respect to a pressure-applying member 18 as shown by the arrows 19. Thus, closure of pressure-applying surface 22 onto a surface affected by movement of pressure-applying arm 18 causes motion of a floating jaw 20 with respect to a pressure-applying member 18 so as to decrease the separation between the pressure-applying surface 22 and the pressure-applying member 18. A yieldable connection 28 provides a floating jaw 20 with a range of motion with respect to a pressure-applying member 18 with little or no pressure on tissue initially but increased pressure as the floating jaw 20 collapses onto the pressure applying member 18.

[0032] Yieldable connection 28 is preferably a resilient connection, so that compression is met with some resistance to such compression and so connection 28 at least partially resumes its original configuration upon release of compression. For example, where connection 28 is a resilient connection, movement of floating jaw 20 with respect to a pressure-applying member 18 is met with resistance when movement of pressure-applying arm 18 presses pressure-applying surface 22 onto tissue. A resilient connection may be provided by a spring, rubber, elastic, or other resilient material or members disposed between a pressure-applying member 18 and

floating jaw 20. Following relief of pressure on a resilient yieldable connection 28, the separation between the pressure-applying surface 22 and the pressure-applying member 18 increases.

[0033] Artery-occluding system 10 also includes a sensor 30 and an energy transmitting member such as an electrical conductor 32. The conductor 32 has a proximal connector 34 configured to operably engage with sensor controller 36. Sensor 30 is configured to sense the location a uterine artery and generate a signal representing the location which provides an output representing the signal received from the sensor. Preferably, the sensor 30 also to determine the degree of occlusion of the uterine artery after clamping the device on the artery or tissue containing the artery and generates a signal representing such occlusion which the controller 36 also converts to an output representative thereof. Sensor 30, preferably a Doppler ultrasound sensor, is connected via an electrical conductor 32 and connector 34 configured to readily engage and disengage with a Doppler ultrasound controller 36. Alternatively, the proximal end of cable 32 may directly and permanently engage or be secured to the sensor control device 36 without having a connector 34.

[0034] The sensor controller 36 is configured to supply power required by a sensor 30, to receive signals from a sensor 30, and to provide sensor signal outputs for interpretation by an operator. In addition, sensor controller 36 may produce signals or signal energy used for sensing (e.g., ultrasound or infra-red signals or energy) or may provide energy to a sensor 30 to aid the sensor 30 to produce or provide signals or signal energy.

[0035] Figures 2A-2D illustrate a distal part of system 10 embodying features of the invention, showing a variety of resilient members 29. Yieldable connection 28 joins pressure-applying surface 22 to pressure-applying member 18, and is

preferably configured to allow a range of movement of the pressure-applying surface 22 with respect to its supporting pressure-applying member 18 as indicated by the arrows 19. Light pressure between a pressure-applying surface 22 and body tissue, such as a uterine artery or tissue adjacent or surrounding a uterine artery, is effective to cause movement of a pressure-applying surface 22 towards a pressure-applying member 18 as a pressure-applying member 18 urges a pressure-applying surface 22 towards body tissue. However, yieldable connection 28 compresses under such light pressure, at least during an initial application of light pressure, allowing pressure-applying surface 22 to move relative to pressure-applying member 18 so as to contact tissue without substantially compressing the tissue. The yieldable, preferably resilient connection 28 is thus effective to maintain contact between the pressure-applying surface 22 and tissue under the influence of light pressure from the pressure-applying members 18 without substantially compressing the artery and without occluding it. This allows for utilization of the sensor to locate the blood vessel without interfering with blood flow through the blood vessel.

[0036] In the embodiments illustrated in Figures 2A-2D, a yieldable connection 28 includes a resilient member 29 compressed between pressure-applying member 18 and floating jaw 20. In preferred embodiments, for example, as illustrated in Figure 2A, resilient member 29 comprises an "O"-ring compressed between a pressure-applying member 18 and a floating jaw 20. Floating jaw 20 is constrained to move substantially only in a single direction by pins 31 attached to pressure-applying member 18 and disposed within slots 33 in lateral sides 35 of floating jaw 20. Alternatively, a pressure-applying member 18 may have slots configured to receive pins attached to a floating jaw 20.

[0037] As illustrated in Figure 2B, resilient members 29 are springs, which may be coil springs, leaf springs, or other springs. In Figure 2C, the resilient member 29 shown is a flexible bladder filled with a compressible fluid such as a gas. In Figure 2D, the resilient member 29 shown is a layer formed of resilient material placed between pressure-applying member 18 and floating jaw 20. A resilient member 29 can be formed of an elastic material (e.g., silicone rubber, latex, or other rubber or elastomer, a sponge or spongy material).

[0038] In the embodiments shown in Figure 2A-2D, floating jaws 20 meet pressure-applying members 18 at an angle, unlike the embodiment shown in Fig. 1 where floating jaws 20 meet pressure-applying members 18 to form approximately straight angles. It will be understood that floating jaws 20 may be disposed at any suitable angle with respect to pressure-applying members 18 to accommodate a variety of anatomical conditions.

[0039] A sensor 30 may be disposed on a pressure-applying member 18, a floating jaw 20, or other distal portion of a clamping device 12. The sensor 30 for locating a uterine artery, including a sensor for measuring blood flow, is preferably disposed in or on a pressure-applying member 18, and is preferably mounted to the face of a pressure-applying surface 22, such as the face of a floating jaw 20 of a clamping device 12. Clamping devices 12 embodying features of the invention may include more than one blood flow sensor 30.

[0040] By providing a blood flow sensor on at least one of the yieldable, and preferably resilient pressure application members, they may be disposed proximate to the patient's uterine artery to maintain contact with the tissue without occluding the artery, and thereby readily sense blood flow therein and thereby locate the uterine artery. Increasing pressure on pressure-applying surface 22 provides better contact

between sensor 30 and tissue, but within the compressible range of motion of yieldable connection 28, the partial clamping of the device does not occlude a blood vessel. Further increase in pressure on pressure-applying surface 22, so as to compress yieldable connection 28 near to or to its limit of motion, is effective to apply the pressure directly to the tissue and so to occlude an artery within or near the contacted tissue. The sensor 30 may then be employed to monitor blood flow through the artery and thereby follow the occlusion of the artery.

[0041] A clamping member 14 is preferably configured for manipulating a pressure-applying member 18. In some embodiments of devices 12 having features of the invention, a pressure-applying member 18 is attached to a connecting portion that is configured so that a pressure-applying member 18 or pressure-applying surface 22 may be placed on or adjacent an artery while a handle 16 is distally disposed and available for use by an operator.

[0042] Bringing clamping members 14 together is effective to dispose pressure-applying surfaces 22 in close apposition to one another. In this way, with clamping device 12 placed near to tissue, pressure-applying surfaces 22 may be placed in contact with tissue disposed between floating jaws 20, such as a portion of a uterine artery. Partial or complete closure of floating jaws 20 causes pressure-applying surfaces 22 to apply pressure or force to the tissue effective to compress a uterine artery or the tissue around a uterine artery; the application of pressure or force is effective to compress the tissue and to occlude the uterine artery, reducing or abolishing blood flow through at least a portion of the uterine artery.

[0043] A sensor 30 disposed on a floating jaw 20 is also shown in each of Figures 2A-2D, with a portion of conductor 32 shown disposed along a portion of a pressure-applying member 18. A sensor 30 is effective to detect the location of an artery

within tissue adjacent a pressure-applying surface 22. For example, placement of a sensor 30 disposed on or in a pressure-applying surface 22 onto a broad ligament containing a uterine artery is effective to detect blood flow in a uterine artery. Such detection is useful in order to direct the placement of a system 10 so as to ensure that body tissue including a portion of a uterine artery to be occluded is between floating jaws 20 of the clamping device 12. In preferred methods of use, the uterine artery and surrounding tissue is disposed between floating jaws 20 and pressure or force is applied to the tissue by pressure-applying surfaces 22, applying pressure to the tissue, effective to compress a portion of a uterine artery and to at least partially occlude the uterine artery. Such compression and resulting occlusion of a uterine artery is effective to reduce or abolish blood flow in the vessel. Sensor 30, disposed on floating jaws 20, is effective to sense the reduction or abolition of blood flow in a compressed uterine artery.

[0044] Figure 3 illustrates in greater detail the distal portion of clamping device 12 having pressure-applying members 18 with floating jaws 20 having pressure-applying surfaces 22. A sensor 30 is shown disposed on a jaw 20 on the pressure-applying surface 22, with a distal portion of a cable 32 disposed opposite the pressure-applying surface 22.

[0045] Figure 4 is a cross-sectional view of a jaw 20, taken through a sensor 30 along line 4-4 of Figure 3 illustrating movement of floating jaw 20 with respect to pressure-applying surface 22. Such movement is allowed by pin 31 slidably received within slot 33 in lateral side 35 of floating jaw 20. However, movement of floating jaw 20 in other directions is constrained by pin 31 slidably received within slot 33 in lateral side 35 of floating jaw 20. Resilient member 29 shown in Figure 4 is an "O"-ring.

[0046] Sensor 30 is connected with conductor 32 by connection 38, shown in the figure as a wire. In alternative embodiments, a connection 38 may comprise a plurality of wires, an optical fiber or fibers, a waveguide, or other connection effective to carry signals and/or energy or power between a sensor 30, a conductor 32, and a sensor controller 36. Preferably, connection 38 is a continuation of at least a portion of conductor 32. Connection 38 is preferably configured to accommodate transverse movement of sensor 30 disposed within floating jaw 20, and thus is preferably a flexible or slidable connection. Alternatively, a sensor 30 may be disposed on a pressure-applying member 18 and a floating jaw 20 configured to permit operation of sensor 30 through or around pressure-applying surface 22. For example, a floating jaw 20 may include a portion transparent to sensing energy, a passage, a window, or other feature allowing operation of a sensor 30.

[0047] A sensor 30 is termed a passive sensor where it is configured to detect intrinsic signals indicating the presence of a uterine artery (i.e., a sound sensor, a pressure sensor, a motion sensor, a pH sensor, or other sensor configured to detect a physical, chemical, electrical, or physiological indication of the location of a uterine artery). A sensor 30 is an active sensor where it is configured to emit a signal, and to detect a signal in response to, or derived from, the emitted signal. An emitted signal may be pulsed or continuous. In alternative embodiments, for example where a sensor 30 senses an optical or electromagnetic signal, conductor 32 may include an optical fiber, a waveguide, other conduit for carrying energy or signals, or a combination of these. A sensor 30 is preferably an active sensor.

[0048] A sensor 30 that produces, at least in part, the energy used to produce the signal sensed by the sensor (i.e., an active sensor) may be called a sensor/transducer. A sensor/transducer may have a source of ultrasound and an

ultrasound sensor or a source of infrared radiation and an infrared detector. For example, an infrared blood-flow sensor is sensitive to electromagnetic energy having a wavelength of between about 500 nanometers (nm) and about 2000 nm, preferably between about 700 nm and about 1000 nm.

[0049] A sensor 30 is preferably a Doppler ultrasound sensor. A Doppler ultrasound sensor operating at ultrasound frequencies less than or equal to about 20 MHz, such as between about 5 MHz and about 20 MHz, preferably between about 6 MHz and about 10 MHz. a typical frequency of about 8 Hz, is suitable for detecting blood flow in an artery with apparatus embodying features of the invention.

[0050] The operation of a sensor may be aided by an energy source (e.g., provided by a sensor controller 36), which may directly provide the energy detected by the sensor, or which may aid the sensor to provide the energy to be sensed. For example, an energy source may provide electrical energy which aids an ultrasound sensor to produce and to detect ultrasound energy (as, e.g., in the MedaSonics® CardioBeat® Blood Flow Doppler with Integrated Speaker (Cooper Surgical, Inc., Trumbull CT 06611)). Other commercially available Doppler ultrasound sensors suitable for use in the present invention include the Koven model ES 100X MiniDop VRP-8 probe (St. Louis, MO) and the DWL/Neuro Scan Medical Systems' Multi-Dop B+ system (Sterling, VA).

[0051] When used to reduce uterine hemorrhage following caesarian section, a clamping device 12 having features of the invention must close the uterine artery within the broad ligament and stay in-place to maintain closure of the vessel. In preferred embodiments, a clamping device 12 having features of the invention is configured so as to allow an operator to "feel" the broad alignment during placement to allow contact by the Doppler chip without premature closure of the uterine artery.

Light pressure of the pressure-applying surfaces 22 onto tissue such as the broad ligament, allows detection of blood flow in an artery (e.g., the uterine artery) without occluding it. Resilient connection 28 maintains the light pressure with tissue, and allows an operator to readily probe multiple locations during detection of a target artery. The resilient connection 28 aids in audible identification of the uterine artery within a broad ligament by allowing an operator to press a clamping device 12 into tissue sufficiently to sense blood flow without occluding it.

[0052] Closure of a uterine artery may be partial or total. Sufficient pressure or force applied to tissue is effective to apply pressure to that tissue and to underlying tissues and so to compress and to at least partially occlude a uterine artery. An amount of pressure applied to effect closure of a uterine artery may be between about 1 pound per square inch (psi) and about 60 psi, and may preferably be between about 3 psi and about 30 psi. For example, where the pressure-applying surface has a surface area of about 0.16 square inches (e.g., a surface with dimensions of about 0.2 inches by about 0.8 inches), the amount of force applied by an artery occluding device embodying features of the invention is preferably between about 0.2 pounds and about 10 pounds, and more preferably between about 0.6 pounds and about 5 pounds.

[0053] A sensor 30 may detect a uterine artery, or blood flow, or signals related to the location of a uterine artery or of blood flow, in a particular direction. For example, a sensor 30 disposed on a pressure-applying surface 22 of a floating jaw 20 may detect signals from a direction perpendicular to the surface, and so be effective to locate uterine arteries or detect blood flow opposite the floating jaw 20. Such an orientation is effective to insure that a uterine artery to be occluded is positioned opposite a floating jaw 20, and between a pair of floating jaws 20, and so is properly

placed for occlusion. A sensor 30 may also be configured to detect signals from directions parallel to a pressure-applying surface 22, or at some other angle with respect to a pressure-applying surface 22; such configurations are useful, for example, for directing the movement of a clamping device 12 towards a uterine artery.

[0054] A clamping device 12 embodying features of the invention may be configured to lock into a clamping position. Such a locked configuration may be temporary and releasable, or may be permanent. Clamping devices 12 embodying features of the invention may have a locking mechanism 26, such as a ratchet, configured to hold at least one pressure-applying member 18 in a pressure-applying position. Such locking mechanisms 26 should include a release mechanism effective to allow the cessation of pressure or force application when desired.

[0055] The apparatus and systems of the present invention are configured for use within a patient's body cavity. The dimensions of a clamping device 12 embodying features of the invention are chosen to facilitate use within the surgical field after caesarian section, so that the clamping device 12 may readily reach, detect and occlude a uterine artery when manipulated by an operator's hand or hands. Clamping devices 12 may be of any suitable size consistent with such a preferred use, and may also be determined in part by the location and dimension of the artery to be occluded. For example, a clamping device 12 configured to allow access to tissue adjacent a uterine artery and to apply pressure or force to the tissue sufficient to reduce or abolish blood flow in the uterine artery may be between about 1 inch and about 12 inches in length, preferably between about 3 inches and about 8 inches in length.

[0056] A sensor is preferably mounted to and oriented perpendicularly to the pressure-applying surface 22 of a floating jaw 20. For example, a blood flow sensor may be mounted between about 0.1 inch and about 1 inch from the distal end of a floating jaw 20, and is preferably mounted about 0.1 inch to about 0.6 inch, more preferably about 0.3 inch to about 0.5 inch from the distal tip of a floating jaw 20. A floating jaw 20 may be configured to tightly engage tissue, i.e., may have a tissue contacting surface 22 that is serrated, scored, roughened, coated with a rough material including sandpaper, or otherwise configured to grip tissue.

[0057] It will be understood that methods and devices embodying features of the invention may be used to occlude a variety of arteries; but is particularly suitable for occluding a uterine artery. Figure 5 illustrates a typical human female reproductive system, including a uterus 40, vagina 42, right ovary 44, and left ovary 46. Blood is supplied to the uterus 40 primarily via the right uterine artery 48 and the left uterine artery 50, and secondarily via the right ovarian artery 52 and the left ovarian artery 54, all of which are supplied by the aorta 56. Uterine arteries 48 and 50 contact the uterus 40 and pass near to the vaginal fornix 58 and to the uterine cervix 60.

[0058] At least a portion of the uterus 40 is exposed and made accessible to a physician during caesarian section. The uterine arteries 48 and 50 may also be made accessible by the surgical procedures necessary for performing a caesarian delivery. However, even if this does not occur during the normal course of the operation, the uterine arteries 48 and 50 may readily be accessed by a physician during or following delivery of the baby and placenta. Tissue near a uterine artery, such as broad ligament tissue, or, where the broad ligament has been dissected away over at least a portion of a uterine artery, uterine artery tissue, may be contacted by a clamping device having features of the invention when a physician

determines that occlusion of one or both uterine arteries is indicated. Typically, this would not occur until after delivery of the baby and the clamping of the umbilical cord, and, in most cases, also after cutting the umbilical cord and after separation of the placenta from the uterus.

[0059] Placement of a pressure-applying surface 22 having a sensor 30, such as a pressure-applying surface 22 of a floating jaw 20 with a sensor 30 such as a Doppler ultrasound sensor, against tissue allows a physician to locate a uterine artery 48 or 50 despite visual obstructions such as blood, amniotic fluid, tissue, and other impediments to locating an artery in a caesarian-section patient. A yieldable connection 28 (preferably a resilient yieldable connection 28) joining floating jaw 20 with a pressure-applying member 18 allows for initially light contact between a device 12 and tissue. A yieldable connection 28 allows effective contact between sensor 30 and tissue to provide blood flow sensing without substantial occlusion of blood flow. Thus, pressure applied by pressure-applying members 18 keeps pressure-applying surface 22 and sensor 30 in contact with tissue without applying such pressure as would occlude a uterine artery 48 or 50 during the location process. It may be desirable to observe blood flow in a uterine artery 48 or 50 for a period of time before occluding it. For example, blood flow in a uterine artery 48 or 50 may be observed with a sensor 30 at different locations to determine an optimal location for occlusion; in addition, such observation of blood flow over time may allow a physician to determine when to begin applying pressure to occlude a uterine artery 48 or 50, or whether such occlusion is indicated under the circumstances. Application of increased pressure is effective to occlude a uterine artery 48 or 50. Increased pressure applied by pressure-applying members 18 is effective to

compress a yieldable connection 28 near to or to the limit of its range of motion and to compress tissue in contact with a pressure-applying surface 22.

[0060] Thus, a method of occluding a blood vessel includes contacting tissue with a pressure-applying surface 22 of a device 12 and locating a blood vessel within or adjacent the tissue without occluding blood flow in it, and compressing the tissue with the device 12 to occlude blood flow in the blood vessel.

[0061] A method of occluding an artery of a patient includes contacting tissue near an artery, without substantially compressing the artery, with a pressure-applying surface of a clamping device having features of the invention. A sensor disposed on the pressure-applying surface is effective to locate the artery. At least a portion of the artery may be compressed by applying pressure to tissue adjacent the artery with the clamping device. Compressing an artery may include grasping tissue near to an artery, and may include compressing tissue surrounding an artery effective to compress the artery. Compressing tissue with an artery occluding device is preferably effective to compress the artery so that blood flow through the artery is reduced, or is abolished. A method of occluding a uterine artery would thus comprise this method, where the artery was a uterine artery.

[0062] Figure 5 illustrates the use of an artery occluding device embodying features of the invention to occlude blood flow in a uterine artery 48. A clamping device 12 with clamping members 14, handles 16, and pressure-applying members 18 with floating jaws 20 having pressure-applying surfaces 22 is shown in place within the abdominal cavity of a patient after delivery of an infant by caesarian section. A clamping device 12 is shown with floating jaws 20 having pressure-applying surfaces 22 disposed on tissue around a uterine artery 48. The clamping device 12 also includes a sensor 30 on a floating jaw 20 facing the patient's tissue,

and communicating with other parts of the system 10 (not shown in Figure 5) via a cable 32.

[0063] Compressing a uterine artery may be accomplished by compressing a portion of the broad ligament around a portion of a uterine artery 48 or 50, or by compression via direct contact between the device and a uterine artery 48 or 50. As illustrated in Figure 5, sensor 30 is effective to detect the presence of and to locate uterine artery 48, and to detect blood flow in the artery 48. Sensor 30 is used to aid in positioning floating jaws 20 and pressure-applying surfaces 22 to best surround uterine artery 48. Closing floating jaws 20 presses pressure-applying surfaces 22 more strongly into tissue, compressing uterine artery 48 effective to occlude uterine artery 48. Sensor 30 may be used to detect the resulting reduction or abolition of blood flow in uterine artery 48, and to adjust the amount of pressure or force used in order to provide the desired amount of reduction in blood flow and to confirm abolition of blood flow if desired. Locking mechanism 26 is used to maintain the desired amount of pressure or force on the tissue for a desired amount of time. Blood flow in the left uterine artery 50 may be similarly occluded, by the same clamping device 12 (after release of the occlusion of the right uterine artery 48) or by a different clamping device 12 (thus allowing simultaneous clamping and occlusion of both uterine arteries).

[0064] Clamping devices 12 embodying features of the invention may be made from any suitable material or combination of materials, including metals such as stainless steel and shape memory alloys such as nickel titanium alloys, plastics, ceramics, and other materials known in the art. Biocompatible polymers, such as for example, polycarbonate, polysulfone, polyester, polyacetal, and other polymers may be particularly suitable for embodiments of the invention. The device or system may

be designed for single use (disposable) or may be sterilizable and capable of multiple use.

[0065] While particular forms of the invention have been illustrated and described, it will be apparent that various modifications can be made without departing from the spirit and scope of the invention. Accordingly, it is not intended that the invention be limited to the specific embodiments illustrated. It is therefore intended that this invention be defined by the scope of the appended claims as broadly as the prior art will permit, and in view of the specification if need be. Moreover, those skilled in the art will recognize that features shown in one embodiment may be utilized in other embodiments. Terms such as "element", "member", "device", "sections", "portion", "section", "steps" and words of similar import when used herein shall not be construed as invoking the provisions of 35 U.S.C. §112(6) unless the following claims expressly use the terms "means" or "step" followed by a particular function without specific structure or action.

2004210661 19 Nov 2009

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An arterial clamping system including:
 - a) a clamping device for at least partially occluding a target vessel in a patient's body, including a pair of opposed pressure-applying members configured to at least partially occlude the target vessel by applying pressure thereto, with at least one of the pressure-applying members having a floating, pressure-applying jaw with a continuous pressure applying surface movable mounted thereto and having a resilient connection between the floating, pressure-applying jaw and the pressure applying member, the resilient connection being at least partially surrounded by side walls extending from the continuos pressure applying surface of the floating, pressure-applying jaw and toward the pressure-applying member, wherein the side walls have a plurality of slots and the at least one of the pressure-applying members has a plurality of pins projecting from lateral edges thereof that are disposed in the slots for guiding movement of said floating, pressure-applying jaw; and a sensor on at least one of the pressure-applying jaws fro locating the target vessel, wherein the sensor is movable mounted to a distal end of the clamping device; and
 - b) a sensor controller operatively connected to the sensor and including a source of power.
2. The system of claim 1, wherein the sensor includes a Doppler ultrasound sensor and the sensor controller includes a Doppler ultrasound controller.
3. A clamping device including:
 - a) pressure-applying means for applying pressure to tissue;
 - b) a floating tissue-contacting means movable mounted to the pressure applying means, the floating tissue-contacting means having a continuous pressure applying surface;
 - c) a resilient connection between the floating tissue-contacting means and the pressure-applying means, the resilient connection being at least partially surrounded by side walls extending from the continuous pressure applying

2004210661 19 Nov 2009

25

surface of the floating tissue-contacting means and toward the pressure applying means;

5 d) sensor means disposed on the tissue-contacting means for locating an artery to be clamped, wherein the sensor means is moveable with the tissue-contacting means.

4. The clamping device of claim 3, wherein the sensor means includes sensor-transducer means for providing signals and for sensing reflected signals for locating a uterine artery to facilitate location of the uterine artery to be occluded.

10 5. A device for treating a female patient's uterus by occluding a uterine artery thereof including:

a pair of opposed clamping elements;

15 at least one of the clamping elements having a floating pressure-applying jaw movable mounted thereto, wherein the jaw includes a continuous pressure-applying surface and is adapted to at least partially occlude a target uterine artery by applying pressure thereto;

20 a resilient connection between the clamping element and the jaw movable mounted thereto, the resilient connection being at least partially surrounded by side walls extending between the continuous pressure-applying surface of the floating pressure-applying jaw and one of the opposed clamping elements;

a guide assembly coupled with the floating pressure-applying jaw for guiding movement of the floating pressure-applying jaw toward and away from the at least one of the opposed clamping elements; and

25 25 a blood flow sensor disposed on at least one of the pressure applying jaws for locating the target uterine artery to be clamped, wherein the blood flow sensor is attached to the floating pressure-applying jaw for moving with the floating pressure-applying jaw.

30 6. The clamping device of claim 5, wherein the blood flow sensor includes sensor/transducer means for providing signals and for sensing reflected signals for locating the target uterine artery.

2004210661 19 Nov 2009

26

7. The clamping device of claim 5 or claim 6 wherein each of the clamping elements has an elongated handle.

8. The clamping device of claim 7 wherein the handles of the clamping elements are pivotally secured together.

5 9. A device for treating a female patient's uterus after caesarean section by occluding the patient's uterine artery including:

 a pair of opposed clamping elements having pressure-applying jaws configured to at least partially occlude a target uterine artery by applying pressure thereto;

10 at least one of the pressure-applying jaws being a floating jaw movably mounted to one of the clamping elements and having a resilient connection with the one of the clamping elements; and

 a blood flow sensor disposed on at least one of the pressure applying jaws for locating the target uterine artery to be clamped, wherein the floating jaw has side walls extending from a clamping surface thereof, the side walls being slidable over lateral edges of the one of the clamping elements.

10. The system of claim 1 or claim 2, wherein the side walls extend from the pressure-applying surface of the floating, pressure applying jaw and are slidable over the lateral edges of the pressure-applying member.

20 11. The system of claim 10, wherein the opposing side walls of the floating, pressure-applying jaw have slots that receive pins projecting from the lateral edges of the at least one of the pressure-applying members.

12. The system of claim 11, wherein the pins are slideable in the slots for guiding movement of the continuos pressure applying surface of the floating,

25 pressure-applying jaw toward and away from the at least one of the pressure-applying members.

13. The system of claim 1 or claim 2, wherein the sensor is flexibly connected with the clamping device for being movable relative to a distal end of the

2004210661 19 Nov 2009

27

clamping device.

14. The system of claim 1 or claim 2, wherein the sensor is connected with the pressure-applying jaw for moving with the pressure-applying jaw and is movable relative to a distal end of the at least one of the pressure-applying members.
- 5 15. The device of claim 5, wherein the floating pressure-applying jaw includes opposing side walls extending from the continuous pressure-applying surface thereof to lateral edges of the at least one of the clamping elements.
- 10 16. The device of claim 15, wherein the opposing side walls of the floating pressure-applying jaw have slots that receive pins projecting from the lateral edges of the at least one of the clamping elements.
17. The system of claim 16, wherein the pins are slideable in the slots for guiding movement of the continuous pressure applying surface of the floating pressure-applying jaw toward and away from the at least one of the clamping elements.
- 15 18. The system of claim 5, wherein the blood flow sensor is flexibly connected with the device for being movable relative to a distal end of the device.
19. The device of claim 9, wherein the opposed side walls of the floating jaw have slots that receive pins projecting from the lateral edges of the one of the clamping elements.
- 20 20. The device of claim 19, wherein the pins are slideable in the slots for guiding movement of a continuous pressure applying surface of the floating jaw toward and away from the one of the clamping elements.
21. The device of claim 9, wherein the blood flow sensor is connected with the floating jaw for moving with the floating jaw, and wherein the blood flow sensor is movable relative to a distal end of the one of the clamping elements.

2004210661 19 Nov 2009

28

22. The device of claim 9 including:
at least one of said pressure-applying jaws having a distal end including a yieldable pressure-applying surface;
a guide assembly coupled with the at least one of said pressure-applying
5 jaws for guiding movement of said yieldable pressure-applying surface toward
and away from the at least one of said pressure applying jaws.

23. The clamping device as claimed in claim 22, wherein said guide assembly
constrains movement of said yieldable pressure-applying surface in a single
direction relative to the at least one of said pressure applying jaws associated
10 therewith.

24. The clamping device as claimed in claim 22 or claim 23, further including a
floating jaw coupled with the at least one of said pressure-applying jaws, wherein
said floating jaw includes said yieldable pressure-applying surface.

25. The clamping device as claimed in claim 24, wherein said floating jaw is
15 mounted over an inner face of the at least one of said pressure-applying jaws,
and wherein said floating jaw includes side walls extending from said yieldable
pressure-applying surface toward the at least one of said pressure-applying jaws
associated therewith.

26. The clamping device as claimed in claim 25, wherein each of said side
20 walls of said floating jaw has slots formed therein, wherein said slots in each of
said side walls are parallel with one another and extend away from said yieldable
pressure-applying surface.

27. The clamping device as claimed in claim 26, wherein the at least one of
said pressure-applying jaws includes lateral edges having pins projecting
25 therefrom, and wherein said pins are disposed in said slots in each of said side
walls of said floating jaw for guiding movement of said floating jaw in a single
direction.

2004210661 19 Nov 2009

29

28. The clamping device as claimed in claim 27, wherein said side walls extending from said pressure-applying surface of said floating jaw are slideable over said lateral edges of said pressure-applying member.
29. The clamping device as claimed in claim 27 or claim 28 wherein said pins 5 are slideable in said slots for guiding movement of said floating jaw relative to the at least one of said pressure-applying jaws.
30. The clamping device as claimed in claim 26, wherein said slots extend along axes that are substantially perpendicular to said yieldable pressure-applying surface of said floating jaw.
- 10 31. The clamping device as claimed in claim 25, further including a resilient connection between said floating jaw and the inner face of the at least one of said pressure-applying jaws for normally urging said yieldable pressure-applying surface away from the inner face of the at least one of said opposed pressure-applying jaws.
- 15 32. The clamping device as claimed in claim 31, wherein said resilient connection is a resilient connection selected from the group consisting of springs, O-rings, hydraulic connections, compressed gas connections, and resilient members.
33. The clamping device as claimed in claim 22, further including a sensor on 20 at least one of said opposed pressure-applying jaws for locating a vessel.
34. The clamping device as claimed in claim 33, wherein said yieldable pressure-applying surface defines an area, and wherein said sensor is substantially centered within the area of said yieldable pressure-applying surface.
35. The clamping device as claimed in claim 25, wherein the inner face of the 25 at least one of said pressure-applying jaws has a recess formed therein, and wherein a part of said resilient connection is seated within the recess.

2004210661 19 Nov 2009

30

36. The clamping device of claim 22, wherein each of said pressure-applying jaws has a floating jaw movable mounted thereto with a resilient connection between said pressure applying jaw and said floating jaw.

37. The clamping device of claim 33, wherein said sensor is a Doppler 5 ultrasound sensor.

38. An arterial clamping system according to claim 1, or a device according to any one of claim 5, claim 9 or claim 22, and substantially as herein described with reference to the accompanying drawings.

10


VASCULAR CONTROL SYSTEMS INC

WATERMARK PATENT & TRADE MARK ATTORNEYS

P25955AU00

15

1/4



2/4




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D

3/4




FIG. 3




FIG. 4

4/4




FIG. 5