

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/048844 A1

(51) International Patent Classification⁷: A61B 6/03

Bhanu Prakash Kirgaval [IN/SG]; Block 709, Jurong West Street 71, #04-32, Singapore 640709 (SG). NOWINSKI, Wieslaw, Lucjan [PL/SG]; 111 Clementi Road, NUS Kent Vale, Block C #10-06, Singapore 129792 (SG).

(21) International Application Number:
PCT/SG2004/000361

(22) International Filing Date:
1 November 2004 (01.11.2004)

(74) Agent: WATKIN, Timothy, Lawrence, Harvey; Lloyd Wise, Tanjong Pagar, P.O. Box 636, Singapore 910816 (SG).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
200306861-6 19 November 2003 (19.11.2003) SG

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): AGENCY FOR SCIENCE, TECHNOLOGY AND RESEARCH [SG/SG]; 20 Biopolis Way #07-01, Centros, Singapore 138668 (SG).


(72) Inventors; and

(75) Inventors/Applicants (for US only): NAGARAJA RAO,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: AUTOMATIC IDENTIFICATION OF THE ANTERIOR AND POSTERIOR COMMISSURE LANDMARKS



(57) Abstract: The AC and/or PC landmarks are identified in a midsagittal MRI image by firstly identifying structures in the brain (specifically the fornix and/or brainstem) as groups of pixels in a radiological image which have an intensity in ranges defined by one or more thresholds and which obey predefined geometrical criteria. The thresholds are varied until the predefined geometrical criteria are met. Initial estimates of the position of the AC and/or PC are derived from the identified structures. These estimates can be improved in various ways, especially by making use of axial and/or corona/ radiological images in planes including, and/or proximate to, the initial estimated position of the AC and/or PC.

WO 2005/048844 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Automatic Identification of the Anterior and Posterior Commissure Landmarks

Field of the invention

The present invention is related to methods and apparatus for identifying anterior commissure (AC) and/or posterior commissure (PC) landmarks from
5 an image of a portion of a brain.

Background of Invention

Identification of the AC and PC are critical for operations such as targeting stereotactic and functional neurosurgery, localisation, analysis in human brain
10 mapping, structure segmentation and labelling in neuroradiology. The Talairach atlas has been widely used as a common standard by neuroscientists and neurosurgeons. To perform spatial normalisation using either standard or modified Talairach transformations, the MSP (midsagittal plane), AC and PC have to be identified.

15

Currently experts perform the detection of these structures manually. However, observer reproducibility is less accurate and prohibitively time-consuming when large sets of data have to be analysed. Furthermore, there is a certain degree of variability among different experts in tracing these
20 landmarks. For these reasons, there is a need to automate the process of identification with accurate, robust and efficient algorithms.

Sun Y. H. et al, in the article "Anatomic labelling of PET brain images with automatic detection of AC and PC", J. Digit Imaging, 1998 Aug; 11 (3 Suppl
25 1):56-58, describe an automatic detection method for finding the AC and PC from positron emission tomography (PET) brain images. However, the resolution of PET images is very low, and the AC and PC are particularly

difficult to identify in such images. Thus, the algorithm is only able to identify the AC and PC with a high level of uncertainty.

Verard L. et al., in the article "Fully Automatic Identification of AC and PC landmarks on Brain MRI using scene analysis", IEE Trans MI, 16(5), 610:616, 1997, describe a method for automatically finding the AC and PC which assumes that high resolution magnetic resonance imaging (MRI) images are available. An automatic algorithm uses the data to estimate the MSP. In a first stage, two easily detectable structures - the corpus callosum (CC) and brain stem (BS) - are identified using intensity-based recognition. From these, a small structure - the superior colliculus (Co) - is detected. The PC is obtained from the resultant locations using template matching. The position of the AC is then found by a further template matching step. This method suffers from a number of disadvantages, one of which is the need for the high resolution images.

Summary of the Invention

The present invention aims to provide a new and useful method for identification of the AC and/or PC landmarks. In particular, the invention aims to make it possible to provide a fast, accurate, robust and clinically practical algorithm.

A first aspect of the invention proposes, in general terms, that the AC and/or PC landmarks are found by firstly identifying structures in the brain (specifically the fornix and/or brainstem) as groups of pixels in an MRI image which have an intensity in ranges defined by one or more thresholds and which obey predefined geometrical criteria. The thresholds are varied until the predefined geometrical criteria are met. The positions of the AC and PC are then estimated based on the identified structures.

A second aspect of the invention proposes, in general terms, that estimates of the positions of the AC and/or PC landmarks are first found using an midsagittal MRI image, but that these estimates are modified using axial and/or coronal MRI images in planes including, and/or proximate to, the
5 estimated positions of the AC and/or PC landmarks.

A specific expression of the first aspect of the invention is a method of estimating the position of a brain landmark which includes:

- (i) defining at least one initial threshold value;
- (ii) determining whether a region of a midsagittal radiological image
10 including a brain structure includes a group of pixels having intensity values in a range defined by the initial threshold value and which obey one or more predefined geometrical criteria describing the structure;
- (iii) if not, then at least once modifying the threshold value and performing step (ii) again;
- 15 (iv) if so, identifying the group of identified pixels as the structure; and
- (v) generating a first estimate of the position of the landmark as a point on the identified structure.

A second expression of the invention is a method of estimating the position of the AC and/or PC landmarks which includes:

- 20 (a) using a midsagittal radiological image to estimate the position of the AC and/or PC landmarks in the midsagittal plane;
- (b) using the estimated position of the AC and/or PC landmarks to generate one or more axial and/or coronal MRI images, including at least one image including the estimated position of the AC and/or PC landmarks; and

(c) analysing the axial and/or coronal MRI images to improve the estimate of the position of the AC and/or PC landmarks.

5 Either, or both, of the methods may be supplemented by a step of generating a sub-image from the midsagittal MRI image including the first estimated position of the AC landmark or PC landmark, and identifying an improved estimate of the position of the AC landmark or PC landmark from the intensity values in that sub-image.

The two aspects of the invention are independent, but may be freely combined, as discussed below.

10 In the following detailed description of examples of the invention the term AC landmark and PC landmark are for conciseness referred to simply as the AC and PC respectively.

Brief Description of The Figures

Preferred features of the invention will now be described, for the sake of illustration only, with reference to the following figures in which:

- 15 Fig. 1 is the midsagittal MRI image of a brain;
Fig. 2 is a binarised version of Fig. 1;
Fig. 3 is an enlarged view of a part of Fig. 2;
Fig. 4 is an enlarged view of a part of Fig. 1;
20 Fig. 5 shows steps of the first part of a method which is an embodiment of the invention;
Fig. 6, which is composed of Figs. 6(a) and 6(b), shows a binarised version of a first MRI image of the CC, and a horizontal projection of this image;
25 Fig. 7, which is composed of Figs. 7(a) and 7(b), shows a binarised version of a second MRI image of the CC, and a horizontal projection of this image;

Fig. 8 is a portion of Fig. 1 with the fornix highlighted;

Fig. 9 is a portion of Fig. 1 with the brainstem highlighted;

Fig. 10 is a portion of the MRI image including an estimate of the position of the AC;

5 Fig. 11 is a portion of the MRI image including an estimate of the position of the PC ;

Fig. 12 shows a process carried out on the image of Fig. 11;

Fig. 13 is steps of a process for improving initial estimates of the positions of the AC and PC in the method which is an embodiment of the
10 invention;

Fig. 14 shows steps of a further process for improving initial estimates of the positions of the AC and PC in the method which is an embodiment of the invention;

Fig. 15 shows 5 axial MRI images derived using an estimate of the
15 position of the AC.

Fig. 16, which is composed of Fig. 16(a) to 16(d), shows a process applied to one of the images of Fig. 15;

Fig. 17 shows a further step of a process using the images of Fig. 15;

Fig. 18 which is composed of Fig. 18 (a) to Fig. 18(d), shows a process
20 applied to one of the PC axial images (of the 5 slices) obtained using initial estimate of the position of the PC;

Fig. 19 shows a further step of a process using the images of Fig. 15;

Fig. 20 shows steps of a further process for improving initial estimates of the positions of the AC and PC in the method which is an embodiment of
25 the invention;

Fig. 21 shows 5 coronal MRI images derived using an estimate of the position of the AC;

Fig. 22 shows 5 coronal MRI images derived using an estimate of the position of the PC;

Fig. 23 shows a symmetry line imposed on a part of the images of Fig. 21.

Fig. 24 shows intensity values along a symmetry line shown in Fig. 23;

Fig. 25 shows a symmetry line imposed on a part of the images of Fig. 22; and

Fig. 26 shows intensity values along a symmetry line shown in Fig. 25.

Detailed Description of the embodiments

Steps in a method which is an embodiment of the invention are now described. The starting point of the method is a radiological image such as the MRI image shown in Fig. 1. The MRI image is assumed to be oriented according to the radiological convention i.e. with the subject's nose pointing left and his or her neck towards bottom of the image.

15

The MRI image is an MSP image, meaning that it represents data lying in an estimated mid-sagittal plane. The equation of the MSP can be obtained according to any known estimation algorithm, such as the one described in WO 03/60827 (based on PCT/SG02/00006). However, the invention is not limited to this method of obtaining the MSP.

20

A first step of the method is to use progressive thresholding to binarise the image. This is illustrated in Figs. 2 to 3. The method is carried out by the following steps, which are illustrated in Fig. 5:

25

a) A window of size 11 X 11 is moved over the entire image of Fig. 1 in an overlapping manner and the mean value of the pixels in the window at every location is recorded.

b) The maximum among the means derived in step (a) recorded is computed.

30

c) An initial threshold is fixed as 80% of the maximum mean (step 1 in Fig. 5).

d) A binary image is derived from Fig. 1 in which each pixel above the initial threshold is set to white, and each pixel below the threshold is set to black (this is step 2 in Fig. 5, and the result is shown in Fig. 2).

In the binary image, an attempt is made (step 3) to identify the Corpus Callosum (CC) as the structure having the following properties (based on the observations and validation of data):

10

a) The length of the CC (from the genu to the splenium, i.e. along the major axis) is about 7 to 9 cm.

b) The width of the CC (from the superior point of body or trunk to the inferior point of the genu, i.e. the minor axis) is about 2 to 4 cm.

15 c) The orientation of the CC (angle of major axis with respect to horizontal axis) is from 5 to 40 degrees.

d) The area of the CC in the binarised image is about 600 to 1000 mm².

If such a structure is not identified, then it is determined whether the threshold is less than 40% of the initial value, and if not the threshold is reduced by 10% of its current value (step 4), and steps 2 and 3 are repeated.

Steps 2 to 4 are repeated until the CC is detected or the threshold value is less than 40% of the initial value. If the threshold value is less than 40 % of initial value and CC is not found, the program quits, stating that CC is not found.

25

For example, if the starting image is Fig. 1, then a CC will be identified by this procedure. It is shown in Fig. 3. The major axis is marked (as the line LA-RA),

as is the minor axis. The points marked RB and LB are the right bottom and left bottom parts.

More generally, if the CC is found, the method proceeds to step 5 in which a check is carried out to determine whether the CC and fornix are attached:

- a) Define a subregion (S1) around CC. Fig. 4 shows this area for the case that the initial MSP image is as in Fig. 1. The height of the sub-region is selected in such a way that the brainstem (BS) and fornix are included. Specifically, the width of the region S1 is selected to be equal to the major axis, and the height was set to 2.5 times the minor axis.
- b) For each column in the binary image of S1, the horizontal projection of the columns (i.e. for each row, the sum of the values in that row) is calculated.

Figs. 6 and 7 show two cases. Figs. 6(a) and 7(a) show the binary image of the region S1 for two different initial MRI images, and Figs. 6(b) and 7(b) show the corresponding projections.

If there are 3 peaks, or if the centre point of the projection is higher than the mean of the two end points, as in the case of Fig. 7(b), then the fornix and CC are attached together.

If the fornix is separated from the CC, the method passes to the set of steps shown in Fig. 13. Otherwise, prior to doing this, a step 6 is carried out in which the CC and fornix are separated by boundary tracing and morphological operations.

In a first of the steps of Fig. 13 (step 7) the fornix is identified as follows.

- a) Within the sub-region S1, a region of interest (ROI) for fornix detection is defined. Fig. 8 shows the sub-region S1, with the parts of S1 which are not

within the ROI shown as black. The ROI is defined as the region between 20% and 80% of CC's major axis. The CC structure is subtracted from the ROI.

- 5 b) The ROI region is binarised using a progressive thresholding algorithm, resembling the one used above. In this case, pixels are set to white or black according to whether the corresponding value of the MRI image is above or below an initial threshold, and the threshold gradually reduced until a fornix structure can identified in the image. The fornix is identified as a structure in
- 10 the ROI having the following properties.
- i) It is elongated white matter structure
 - ii) It is located in between the two ends of CC.
 - iii) It has an orientation > 5 degrees & < 90 degrees.
 - iv) It has a major-axis to minor-axis ratio > 2 .

15

The entire fornix structure may be not be seen by thresholding, hence to get the complete structure of fornix we do region growing. The intensity values of pixels which are expected to be in the identified fornix structure region are collected and their mean value is computed. From this mean value, two

20 thresholds for region growing of the fornix are calculated. This process involves defining a parameter M_F which is the mean of the pixel intensities in the possible fornix region, and a second parameter σ which is the standard deviation of the intensity values in the same region. Then a lower threshold L_f is defined as $M_F - 2\sigma$, and an upper threshold U_f is defined as $M_F + 2\sigma$. Using

25 these thresholds the full fornix region is obtained by "region growing" as shown in Fig. 8. In this process the pixel values of all regions between the thresholds are assumed to be part of the fornix. The inferior most tip of the fornix is identified as a first estimate of position of the AC (step 8).

Once fornix region, is identified, CC and fornix structures are subtracted from the subregion S1. The result is the region of S1 which is not black in Fig. 9. The brainstem (BS) is identified in this region using anatomical information, that BS is located inferio-posteriorly to CC. The BS is composed of grey and white matter pixels, having higher variance in intensity values than in CC and fornix. Similar to fornix identification, we initially detect the possible BS region using thresholding and perform region growing to extract complete structure. The BS region is characterized by the location of a centroid, intensity variation and width of the region. The lower and upper limits for region growing using 8-neighborhood were calculated as by defining a first parameter MBS which is the mean of the pixel intensities in the possible BS region, and a second parameter σ which is the standard deviation of the pixel intensities in the possible BS region σ . Using these two parameters, we set a lower threshold L_{BS} which is $MBS - 3\sigma$, and an upper threshold U_{BS} which is $MBS + 2\sigma$. All pixels for which the values of the MRI image are between these thresholds are assumed to be part of the BS. The values of the thresholds given above are proposed based on the composition of grey and white matter pixels in BS. Our observation from the data showed a larger deviation of grey values to the lower side of the mean than to the upper side.

20

For the MRI image of Fig. 1, this gives the estimate for the BS as the points shown in white in Fig. 9 (step 9). The upper right most point of BS is defined as our initial estimate of the PC point (step 10).

25 A next step is to obtain an improved estimate of the positions of the AC and PC. To do this, we generate two sub-images of the initial MRI image (step 11). For the MRI image of Fig. 1, these sub-images are shown in Figs. 10 and 11 respectively. The sub-images are selected as ROIs respectively around the initial estimates of the positions of the AC and PC. The AC sub-image 30 (Fig. 10) is centered at the initial estimate of the position of the AC, and has a

size large enough (e.g. 12 X 12 mm, which are values which selected based on the observations and anatomy) to include surrounding structures for processing. The construction of PC sub-image is based on variability information that the PC is situated at a distance of 17- 42 mm posterior to the AC. The initial estimate of the PC derived above was checked, to see it obeys the above condition, and if so an area large enough (eg. 16 X 16 mm) to include this point and surrounding structures was defined as PC image. If the condition is not met, the BS region growing is carried out with new thresholds and a re-estimate the initial position of the PC. For all the cases for which we have tested our algorithm, the initial position of the PC obeyed the condition.

The position of the AC is below the inferior tip of fornix, but due to partial volume or imaging artifacts the AC is indistinguishable from the inferior tip of fornix. The AC will usually be manifested as a bright point in the AC image, which can be located by binarising the image and region growing the foreground pixels. An improved estimate of the position of the AC is the inferior-most point of the largest region in the AC sub-image. Around this initial position of the AC we check to see if there are any points with a higher intensity. If such a point is found, it is considered as an improved estimate of the position of the AC. Otherwise, the previous estimate of the AC point itself is retained (step 12).

An improved estimate of position of the PC is obtained by performing a horizontal projection of the PC image (step 13). In other words, for each row of the PC sub-image we find the respective sum of the corresponding MRI intensities. The resultant plot is shown in Fig. 12(b). The PC image contains a part of the brainstem and the superior colliculus. The point where, the slope changes significantly indicates the row of PC image containing the position of the PC, at least for cases where the superior colliculus is well separated from BS. This row is designated as an initial estimate of the PC row of the PC sub-

image. In cases where the superior colliculus is not separated, the slope change is not significant. Hence, two adjacent rows of the identified PC_row, in the PC image are also considered for final refinement. The PC is identified as the point having the maximum change in grey value with the neighbour
5 pixels in the identified PC_row and its adjacent rows. After identifying the PC row, the intensity profile along the rows is taken, as shown in Fig. 12(a), and the column number of the PC in the image is found using Fig. 12(a), as the maximum intensity along the PC row.

10 The final coordinates of the positions of the AC and PC are mapped back to the volume data using the MSP equation. The corresponding axial slices where the AC and PC are manifested are identified using the MSP equation, voxel size and the volume dimensions.

15 Fig. 14 shows the steps of an optional technique for improving the estimates of the estimates of the positions of the AC and PC derived above by processing axial slices.

In a first step (step 14), the axial slices containing the positions of the AC and
20 PC estimated above are found by using the coordinates of the estimated positions of the AC and PC in the midsagittal plane and MSP equation. These two axial slices are termed "reference slices".

In a second step (step 15), for each of these AC and PC axial slices, five
25 further slices are defined: two slices above each of the AC and PC axial slices, and two slices below each of the AC and PC axial slices. The resultant five slices derived from the AC reference slice are shown in Fig. 15.

In a third step (step 16), for the AC reference slice and each of the four slices
30 derived from it, we form a mean ventricular line (MVL) passing through the

third ventricle, by using the horizontal and vertical projections of the corresponding slice. This is shown in Fig. 16, where a slice (shown in Fig. 16(a)) is used to produce a horizontal projection (shown in Fig. 16(c)) and a binary version of the slice (shown in Fig. 16(b)) is used to produce a vertical projection (shown in Fig. 16(d)). The binary version of the slice is produced using a threshold which is selected to be 70% of the region of the mean intensity of the region-of-interest, and pixels below this threshold are shown in Fig. 16(b) as white, and pixels above the threshold as black.

- 10 Using the MVL profile, a set of evaluations is performed checking:
1. whether Massa Intermedia is present or the third ventricle is complete, and
 2. whether there is a cistern before the AC or the slice has gray matter.

To evaluate the first condition, check along the MVL for continuity of white pixels in the binary image. If the continuity or the length of white pixels is at least 85% of the distance between AC and PC then there is no Massa Intermedia present. If the continuity is broken then Massa Intermedia is present. The distance between the AC and PC is found by the initial estimates of the positions of the AC and PC. The second condition is evaluated by checking the MVL profile before an initial position of the AC. If there are CSF intensity pixels, it is assumed that a cistern is present; else if the pixel intensity is of gray matter then a gray matter is present. These conditions are necessary to decide on what will be the nature of a profile along the MVL and it is used as a reference while searching for the AC and PC.

25 In a fourth step, we examine the profile plot of image values along the MVL (shown in Fig. 17). That is, starting from the midpoint of the profile (i.e. a point in the third ventricle or on the Massa Intermedia) we move leftwards to locate a WM (white matter) peak. This peak is the one end point of the AC. Following the peak, we use the second derivative of the profile to identify the starting point of the AC. Similarly we find the start and end points in all the 5 other

30

slices considered for processing. The AC is assumed to have a width of about 3 mm. Using, these starting and end points and the value of intensity in between these points, region growing is carried out to extract the complete structure of AC (step 17).

5

To form an improved estimate of the position of the PC (step 18), we use the MVL profile plot for the PC reference slice, and the four axial slices around the PC reference slice. This is shown, for one of those five axial slices, in Fig. 18. Fig. 18(a) shows one of the axial slices, Fig. 18(c) shows a horizontal projection of it (i.e. summing the values in respective rows), Fig. 18(b) shows a binarised version of it (produced in the same way as Fig 16(b) described above), and Fig. 18(d) shows a vertical projection of the binarised version (i.e. summing the values in respective columns). This is performed in the same manner as how the MVL is obtained for AC slices. Fig. 19 shows the intensity profile along the MVL. Starting from the middle of the profile and moving towards the right side of the plot, we trace the PC. Since the third ventricle has a cerebro spinal fluid (CSF) which manifests itself as dark matter, the WM peak is identified as the PC location. As in AC identification, the PC too is identified using region growing, as a structure which is cylindrical in shape and having radius of about 1mm.

10

15

20

Fig. 20 shows the steps of a corresponding technique for improving the estimates of the positions of the AC and PC derived above by processing coronal slices.

25

From the coordinates of the structures (AC & PC) the corresponding coronal reference slices are identified (step 20).

For each of the AC and PC coronal reference slices, two further slices in the anterior direction and two further slices in the posterior direction are defined.

30

Thus, there are a total of 5 slices for the AC, and 5 slices for PC (step 21). The five slices for the AC are shown in Fig. 21, and the five slices for the PC are shown in Fig. 22.

5 For all the five slices selected a region of interest is selected, consisting of CC, lateral ventricle and AC is selected using the MSP equation. A binarised version of each slice is formed, and the binarised ROIs are used to locate the symmetrical line This is the white line on Fig. 23. The AC and PC are assumed to be on this symmetrical line.

10

Using the intensity information of CC, a rough estimate of intensity of the AC is obtained as both CC and AC are white matter structures and CC is more homogeneous structure.

15 The intensity value along the symmetry line (shown in Fig. 24) is scanned (step 22) to obtain a white matter peak in the opposite direction of CC. This point is considered as a good estimate for the position of the AC if it has intensity close to white matter intensity and third ventricle can be identified after the AC (low gray value due to CSF).

20

The further slices around AC reference slice are checked for the above condition. The slices which meet the above conditions are considered to have the AC and from this the radius of the AC is found out (step 23).

25 From the PC slices, the ROI around the MSP line is extracted to find the symmetrical line passing through the ROI (the white line on Fig. 25). The PC is assumed to be on the symmetry line. The location of the CC is known from earlier processing, and hence can be used as a reference to locate white matter structures. The symmetry line (shown in Fig. 26) is scanned (step 24)

to locate the CC and find its intensity value. The intensity value of CC is used as a reference to locate the PC as follows.

5 A scan is done along the symmetry line away from CC position. The CSF region separates the CC and PC. Hence the intensity values will be low in this region. After the CSF region, a small region of pixels of white matter and gray matter mix can be located. After this point, a few pixels of low intensity corresponding to CSF are located which represents the aqueduct. The PC is the region between the CSF matter and the aqueduct.

10

The above conditions are checked in the PC coronal slices considered for processing. The slices which satisfy the conditions are marked as possessing PC. From the number of slices having the PC the dimensions of the PC structure is found out (step 25).

15

The final positions of the AC and PC are found using the information obtained from all the three orientations. This is the best position estimate found above in each of the three directions.

20 Using the final positions of AC and PC, 3D extraction of the AC and PC is carried out. The PC is assumed to be cylindrical with diameter of about 2mm. The AC is assumed to be a bent cylinder with diameter about 3mm. This is based on anatomical knowledge. Primarily we are interested in determining the width of the AC and PC, rather than their height (i.e. length in axial slices).

25

Although only a single embodiment of the invention has been described in detail, many variations are possible within the scope of the invention as will be clear to a skilled reader.

Claims

1. A method of estimating the position of a brain landmark which includes:
 - (i) defining at least one initial threshold value;
 - 5 (ii) determining whether a region of a midsagittal radiological image including a brain structure includes a group of pixels having intensity values in a range defined by the initial threshold value and which obey one or more predefined geometrical criteria describing the structure;
 - (iii) if not, then at least once modifying the threshold value and
10 performing step (ii) again;
 - (iv) if so, identifying the group of identified pixels as the structure; and
 - (v) generating a first estimate of the position of the landmark as a point on the identified structure.
2. A method according to claim 1 in which the structure is the fornix, and
15 the landmark is the anterior commissure (AC).
3. A method according to claim 2 further including a step of determining whether within the MRI image the fornix is distinguishable from the corpus callosum (CC), and if so excluding the CC from the image.
4. A method according to claim 1 in which the structure is the brainstem,
20 and the landmark is the posterior commissure (PC).
5. A method according to any of claims 1 to 4, further including a step of generating a sub-image within the midsagittal radiological image including the first estimated position of the landmark, and identifying an improved estimate of the position of the landmark from the intensity values in the sub-image.

6. A method of estimating the position of the AC and/or PC landmarks which includes:
- (a) using a midsagittal radiological image to estimate the position of the AC and/or PC landmarks in the midsagittal plane;
- 5 (b) using the estimated position of the AC and/or PC landmarks to generate one or more axial and/or coronal radiological images, including at least one image including the estimated position of the AC and/or PC landmark; and
- (c) analysing the axial and/or coronal radiological images to improve
10 the estimate of the position of the AC and/or PC landmarks.
7. A method according to claim 6 in which the images are axial images, and step (c) includes deriving a mean ventricular line (MVL), and determining the position of the AC and/or PC landmarks by scanning intensity values along the MVL.
- 15 8. A method according to claim 7 in which there are a plurality of images relating to different axial slices including a first axial image of an axial slice containing estimates of the position of the AC and/or PC landmarks, and second images of neighbouring axial slices, the method further including the steps of determining dimensions of the AC and/or PC landmarks using the
20 second images.
9. A method according to claim 6 in which the images are coronal images, and step (c) includes deriving a symmetry line within a first coronal image including estimates of the position of the AC and/or PC landmarks, and determining the position of the landmark by scanning intensity values along
25 the symmetry line.

10. A method according to claim 9 in which there are a plurality of images relating to different coronal slices including second images of coronal slices neighbouring the first coronal slice, the method further including the step of determining dimensions of the AC and/or PC landmarks using the
5 second images.
11. A method according to any of claims 6 to 10 in which the landmark is the AC.
12. A method according to any of claims 6 to 10 in which the landmark is the PC.
- 10 13. A method according to any of claims 6 to 12 in which step (a) is performed by a method according to any of claims 1 to 5.
14. A computing apparatus including a processor arranged to perform a method according to any preceding claim.
- 15 15. A computer program product including program instructions which are readable by a computer and cause the computer to perform a method as defined by any of claims 1 to 14.




Fig. 1



Fig. 2




Fig. 3




Fig. 4




Fig. 5

3/12




Fig. 6




Fig. 7

4/12




Fig. 8




Fig. 9




Fig. 10






Fig. 11



(a)



(b)

Fig. 12

5/12




Fig. 13

6/12




Fig. 14

7/12




Fig. 15




Fig. 16

8/12




Fig. 17




Fig. 18

9/12




Fig. 19




Fig. 20

10/12




Fig. 21




Fig. 22




Fig. 23




Fig. 24

12/12




Fig. 25




Fig. 26

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG2004/000361

A. CLASSIFICATION OF SUBJECT MATTER	
Int. Cl. 7: A61B 6/03	
According to International Patent Classification (IPC) or to both national classification and IPC	
B. FIELDS SEARCHED	
Minimum documentation searched (classification system followed by classification symbols)	
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched	
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DWPI IPC A61B, G06T, G06F, G06K & keywords: tomograph, brain, landmark and similar terms Medline keywords: tomograph, brain, landmark and similar terms	
C. DOCUMENTS CONSIDERED TO BE RELEVANT	
Category*	Citation of document, with indication, where appropriate, of the relevant passages
X	IEEE Transactions on Medical Imaging, Volume 16(5) pages 610-616. October 1997 "Fully automatic identification of AC and PC landmarks on brain MRI using scene analysis" Verard et al Page 613 column 2
X	Journal of Digital Imaging, Volume 11(3 supp 1) pages 56-58. August 1998 "Anatomic labelling of PET brain images with automatic detection of AC and PC" Sun et al Figure 3
A	Psychiatry Research: Neuroimaging. Volume 67(2) pages 145-54. July 1996 "Landmark-based registration and measurement of magnetic resonance images: a reliability study" Arndt et al Whole document
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex	
* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	
Date of the actual completion of the international search 30 November 2004	Date of mailing of the international search report 3 DEC 2004
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustrialia.gov.au Facsimile No. (02) 6285 3929	Authorized officer XAVIER GISZ Telephone No : (02) 6283 2064

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG2004/000361

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A, P	Journal Magnetic Resonance Imaging. Volume 20(4):572-80. October 2004 "Automatic registration of brain magnetic resonance images based on Talairach reference system" Han et al Whole document	
A	US 5,262,945 A (DeCARLI et al) 16 November 1993 Abstract	
A	US 2003/0210820 A1 (LACHNER et al) 13 November 2003 Abstract	
A	US 6,584,216 B1 (NYUL et al) 24 June 2003 Abstract	
A	US 2003/0009098 A1 (JACK et al) 9 January 2003 Abstract	
A	Patent Abstracts of Japan JP 2000126150 A (GE YOKOGAWA MEDICAL SYSTEMS LTD) 9 May 2000	

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG2004/000361

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

First Invention: Claims 1-5

Second invention: Claims 6-15

See extra sheet.

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- The additional search fees were accompanied by the applicant's protest.
- No protest accompanied the payment of additional search fees.

Supplemental Box

(To be used when the space in any of Boxes I to VIII is not sufficient)

Continuation of Box No:

The international application does not comply with the requirements of unity of invention because it does not relate to one invention or to a group of inventions so linked as to form a single general inventive concept. In coming to this conclusion the International Searching Authority has found that there are different inventions as follows:

1. Claims 1-5 are directed to a method of estimating the position of a brain landmark including the steps of determining whether a region of a midsagittal radiological image includes a group of pixels having intensity values in defined range. It is considered that determining whether a group of pixels have an intensity in a defined range comprises a first "special technical feature".
2. Claims 6-15 are directed to a method of estimating the position of AC and PC landmarks including the steps of using midsagittal radiological images to estimate the position of the AC and PC landmarks and generating axial radiological images and using these images to improve the estimate of the position of the AC and PC landmarks. It is considered that forming axial radiological images from midsagittal images and using these to improve the estimate of the position of the AC and PC landmarks comprises a second special technical feature.

Since the abovementioned groups of claims do not share any of the technical features identified, a "technical relationship" between the inventions, as defined in PCT rule 13.2 does not exist. Accordingly the international application does not relate to one invention or to a single inventive concept, *a priori*.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/SG2004/000361

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report	Patent Family Member
US 5262945	
US 2003210820	EP 1363242
US 6584216	
US 2003009098	
JP 2000126150	

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.

END OF ANNEX