


(51) Cl.Int./Int.Cl. *A61F 2/16* (2006.01)

(72) Inventeurs/Inventors:
GERAGHTY, EDWARD, US;
BRADY, DANIEL G., US;
BUMBALOUGH, TIMOTHY R., US;
CALI, DOUGLAS S., US

(73) Propriétaire/Owner:
ABBOTT MEDICAL OPTICS INC., US

(74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : LENTILLE INTRAOCULAIRE ACCOMMODANTE MULTIFOCALE
(54) Title: MULTIFOCAL ACCOMMODATING INTRAOCULAR LENS



An intraocular lens for providing accommodative visions to a subject includes an adjustable optic and a haptic that is operably coupled to the optic. The adjustable optic comprises an optical axis, a central zone disposed about the optical axis, and an annular zone surrounding the central zone. The optic may also comprise additional annular zones disposed about the central zone and the first annular zone. The haptic comprises a transparent portion protruding into the adjustable optic. The intraocular lens has a disaccommodative configuration in which the central zone has a base optical power and an accommodative configuration in which the central zone has an add optical power that is at least about 1 Diopter greater than the base optical power, preferably at least about 2 Diopters greater than the base optical power. In some embodiments, the add optical power is at least 3 Diopters, or even 4 Diopters, greater than the base optical power. The central zone and the annular zone have different optical powers when the adjustable intraocular lens is in the accommodative configuration and/or when the adjustable intraocular lens is in the disaccommodative configuration.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 July 2008 (10.07.2008)

PCT

(10) International Publication Number
WO 2008/083283 A2

(51) International Patent Classification:
A61F 2/16 (2006.01)

(74) Agent: WEBER, David; Advanced Medical Optics, Inc.,
1700 E. St. Andrew Place, Santa Ana, CA 92705 (US).

(21) International Application Number:
PCT/US2007/089060

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
28 December 2007 (28.12.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/882,839 29 December 2006 (29.12.2006) US

(71) Applicant (*for all designated States except US*): ADVANCED MEDICAL OPTICS, INC. [US/US]; 1700 E St. Andrew Place, Santa Ana, CA 92705 (US).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): GERAGHTY, Edward [US/US]; 30 El Morro, Rancho Santa Margarita, CA 92688 (US). BRADY, Daniel, G. [US/US]; 30121 Saddleridge Drive, San Juan Capistrano, CA 92675 (US). BUMBALOUGH, Timothy, R. [US/US]; 321 N. Drake Avenue, Fullerton, CA 92832 (US). CALI, Douglas, S. [US/US]; 25702 Morales, Mission Viejo, CA 92691 (US).

Published:

— without international search report and to be republished upon receipt of that report

(54) Title: MULTIFOCAL ACCOMMODATING INTRAOCULAR LENS



(57) Abstract: An intraocular lens for providing accommodative visions to a subject includes an adjustable optic and a haptic that is operably coupled to the optic. The adjustable optic comprises an optical axis, a central zone disposed about the optical axis, and an annular zone surrounding the central zone. The optic may also comprise additional annular zones disposed about the central zone and the first annular zone. The haptic comprises a transparent portion protruding

into the adjustable optic. The intraocular lens has a disaccommodative configuration in which the central zone has a base optical power and an accommodative configuration in which the central zone has an add optical power that is at least about 1 Diopter greater than the base optical power, preferably at least about 2 Diopters greater than the base optical power. In some embodiments, the add optical power is at least 3 Diopters, or even 4 Diopters, greater than the base optical power. The central zone and the annular zone have different optical powers when the adjustable intraocular lens is in the accommodative configuration and/or when the adjustable intraocular lens is in the disaccommodative configuration.

Multifocal Accommodating Intraocular Lens

Background of the Invention

Field of the Invention

5 The present invention is directed to intraocular lenses, and more particularly to accommodating intraocular lenses having more than one focus or an extended depth of focus.

Description of the Related Art

10 A human eye can suffer diseases that impair a patient's vision. For instance, a cataract may increase the opacity of the lens, causing blindness. To restore the patient's vision, the diseased lens may be surgically removed and replaced with an artificial lens, known as an intraocular lens, or IOL. An IOL may also be used for presbyopic lens exchange or other elective ocular surgical procedures.

15 Monofocal IOLs have a single focal length, or, equivalently, a single power. Unlike the eye's natural lens, which can adjust its focal length within a particular range in a process known as accommodation, these single focal length IOLs cannot accommodate and provide clear vision only over a limited range of distances. As a result, distant objects may appear in focus, while objects at a normal reading distance from the eye may appear blurred.

20 Vision over a broader range of distances can be obtained either through the use of a multifocal lens, which provides different foci configured to produce focused images for different object distances, or an aspheric lens configured to provide an extended depth of focus or depth of field. While such lenses can improve the overall vision range, there may also be an associated reduction in visual acuity or overall visual quality.

25 Another approach is to use an accommodating IOL, which can adjust its axial position and/or optical power within a particular range, similar to the eye's natural lens. As a result, the patient can clearly focus on objects in a range of distances from the eye, rather than at a single distance. This ability to accommodate is of tremendous benefit for the patient, and more closely approximates the patient's natural vision than a single focal length IOL. One of the challenges in accommodating IOL's is providing a sufficient range of
30 accommodation with the limited amount of ocular force available from the ciliary muscle. One solution to this problem is to combine an accommodating IOL with a multifocal or

extended focus lens. Such approaches are disclosed in U.S. Patent Numbers 6,503,276, 6,554,859, 6,638,305, and 7,018,409.

Another consideration is the location of the IOL within the eye. In the case of a pseudophakic eye, the IOL that replaces the eye's natural lens is commonly implanted within the capsular bag of the eye. The IOL has an optic, which refracts light that passes through it and forms an image on the retina, and a haptic, which mechanically couples the optic to the capsular bag. In the case of an accommodating IOL, the ciliary muscle and zonules exert a force on the capsular bag, which in turn exerts a force on the optic. The force may be transmitted from the capsular bag directly to the optic, or from the capsular bag through the haptic to the optic.

A desirable optic for an accommodating IOL is one that distorts in response to a squeezing or expanding radial force applied to the optic (i.e., by pushing or pulling on or near the edge of the optic, circumferentially around the optic axis). Under the influence of a squeezing force, the optic bulges slightly in the axial direction, producing more steeply curved anterior and/or posterior faces, and producing an increase in the power of the optic. Likewise, an expanding radial force produces a decrease in the optic power by flattening the optic. This change in power is accomplished in a manner similar to that of the natural eye and is well adapted to accommodation. Furthermore, this method of changing the lens power may reduce undesirable pressures exerted on some of the structures in the eye.

One challenge in implementing such an optic is designing a suitable haptic to couple the optic to the capsular bag. The haptic should allow distortion of the optic in an efficient manner, so that a relatively small ocular force from the ciliary muscle, zonules, and/or capsular bag can produce a relatively large change in power and/or axial location of the image. This may reduce fatigue on the eye, which is generally desirable.

Accordingly, there exists a need for an intraocular lens having a haptic with increased accommodative range and enhanced efficiency in converting a zonular force to a change in power and/or a change in axial location of the image. Better methods of implementing multifocal and extended focal IOL's into accommodating IOL's are also needed as a means for supplementing the overall accommodative range available to the eye.

Summary of the Invention

Embodiments of the present invention are directed to devices and methods for providing accommodative vision. One aspect of the present invention involves an intraocular lens that comprises an adjustable optic and a haptic or mounting structure that is

operably coupled to the optic. The adjustable optic comprises an optical axis, a central zone disposed about the optical axis, and an annular zone surrounding the central zone. The optic may also comprise additional annular zones disposed about the central zone and the first annular zone. The haptic comprises a transparent portion protruding into the adjustable optic. The intraocular lens has a disaccommodative configuration in which the central zone has a base optical power and an accommodative configuration in which the central zone has an add optical power that is at least about 1 Diopter greater than the base optical power, preferably at least about 2 Diopters greater than the base optical power, and even more preferably at least 3 Diopters, or even 4 Diopters, greater than the base optical power. The central zone and the annular zone have different optical powers when the adjustable intraocular lens is in the accommodative configuration and/or in the disaccommodative configuration.

As used herein "base optical power" or "base power" means power (in Diopters) of an IOL or other ophthalmic lens or lens system that is required to provide distant vision at the retina of a subject eye. As used herein "add optical power" or "add power" means a difference in power (in Diopters) between power required provide distant vision and the power of the lens portion having the add optical power. When the add optical power is a positive quantity, it is the difference in power between power required provide distant vision and the power required to focus light from an object at some finite distance from the eye. Alternatively, the add optical power may be a negative quantity.

In another aspect of the present invention, an intraocular lens comprises an adjustable optic and a haptic that is operably coupled to the optic. The optic comprises an optical axis, a central zone disposed about the optical axis, and an annular zone surrounding the central zone. The optic may also comprise additional annular zones disposed about the central zone and the first annular zone. The haptic comprises a transparent portion protruding into the adjustable optic. The intraocular lens has a natural configuration in which the central zone has a base optical power and a stressed configuration in which the central zone has an add optical power that is at least 1 to 4 Diopters greater than the base optical power. The central zone and the annular zone have different optical powers when the intraocular lens is in the stressed configuration and/or when the optic is in the natural configuration. Alternatively, the intraocular lens may have a natural configuration in which the central zone has the add optical power and a stressed configuration in which the central

zone has a base optical power, wherein the add optical power is at least 1 to 4 Diopters greater than the base optical power.

In yet another aspect of the present invention, a method of providing accommodative vision to a subject comprises providing an intraocular lens according to an embodiment of the invention that includes an optic having a central zone and an annular zone surrounding the central zone. The method also comprises placing the intraocular lens into the eye of a subject in a disaccommodated configuration in which the central zone has a base optical power. The method further comprises adjusting the intraocular lens to an accommodated configuration in which the central zone has an add optical power that is at least 1 to 4 Diopters greater than the base optical power. The central zone and the annular zone simultaneously have different optical powers when the intraocular lens is in the accommodated configuration and/or when the optic is in the disaccommodative configuration. Alternatively, the intraocular lens may be placed into the eye in an accommodated configuration in which the central zone has the add optical power, wherein the intraocular lens is adjusted to a disaccommodated configuration in which the central zone has a base optical power that is suitable for providing intermediate and/or distant vision. In any event, when the intraocular lens is in the accommodated configuration, the central zone and/or surrounding zone is suitable for providing vision for objects that are relatively close to the subject (e.g., 12 to 24 inches from the subject) or objects at intermediate distances (e.g., 2 to 5 feet from the subject). When the intraocular lens is in the disaccommodated configuration, the central zone and/or surrounding zone is suitable for providing vision for objects that are distant (e.g., greater than 20 feet from the subject) and/or objects at intermediate distances.

Brief Description of the Drawings

Embodiments of the present invention may be better understood from the following detailed description when read in conjunction with the accompanying drawings. Such embodiments, which are for illustrative purposes only, depict novel and non-obvious aspects of the invention. The drawings include the following figures.

FIG. 1 is a plan drawing of a human eye having an implanted intraocular lens in an accommodative or "near" state.

FIG. 2 is a plan drawing of the human eye of FIG. 1 in a disaccommodative or "far" state.

FIG. 3 is an isometric view of an intraocular lens according to a first embodiment of the invention showing an optic operably coupled to a haptic.

FIG. 4 is an isometric view of the haptic only from the intraocular lens shown in FIG. 3.

5 FIG. 5 is a cross-sectional isometric view of the intraocular lens of FIG. 3 showing a haptic segment operably coupled to an optic segment.

FIG. 6 is a cross-sectional view through the section 6-6 of FIG. 3 showing a portion of a haptic protruding into an optic and the intraocular lens in a disaccommodative state.

10 FIG. 7 is a cross-sectional view of the intraocular lens shown in FIG. 6 in an accommodative state.

FIG. 8 is a block diagram of a method implanting an intraocular lens and providing accommodative vision.

FIG. 9 is a front view of an intraocular lens according to a second embodiment of the invention.

15 FIG. 10 is a cross-sectional view through the section 10-10 of FIG. 9.

FIG. 11 is a front view of the haptic only from the intraocular lens shown in FIG. 9.

FIG. 12 is a cross-sectional view through the section 12-12 of FIG. 11.

FIG. 13 is an isometric view of an intraocular lens according to a third embodiment of the invention.

20 FIG. 14 is a cross-sectional isometric view of the intraocular lens of FIG. 13 showing a haptic segment operably coupled to an optic segment.

FIG. 15 is a front view of the intraocular lens shown in FIG. 13

Detailed Description of the Drawings

25 In a healthy human eye, the natural lens is housed in a structure known as the capsular bag. During natural accommodation, the capsular bag is driven by a ciliary muscle and zonular fibers (also known as zonules) in the eye, which can pull on the capsular bag to change its shape. The motion of the capsular bag generally deforms the natural lens in order to change its power and/or the location of the lens, so that the eye can focus on objects at varying distances away from the eye in a process known as accommodation. Embodiments
30 of the present invention are directed to intraocular lenses that advantageously utilize the ocular forces produced by the ciliary muscle, zonules, and/or capsular bag to change the shape of the lens optic. Such an accommodating lens may produce vastly improved vision over a lens with a fixed power and location that does not accommodate. As used herein the

term "ocular force" means a force that is sufficient to provide accommodation in the eye of a healthy human subject.

FIG. 1 shows a human eye 10, after an accommodating intraocular lens 11, according to an embodiment of the present invention, has been implanted. Prior to surgery, the natural lens occupies essentially the entire interior of the capsular bag 18. After surgery, the capsular bag 18 may house the intraocular lens 11. Alternatively, the intraocular lens 11 may be configured to directly engage the zonules or ciliary muscle.

Light enters from the eye 10 from the left of FIG. 1 and passes through the cornea 12, the anterior chamber 14, the iris 16, and is directed onto the intraocular lens 11. After passing through the intraocular lens 11, light exits the posterior wall 20 of the capsular bag 18, passes through the posterior chamber 32, and strikes the retina 22, which detects the light and converts it to a signal transmitted through the optic nerve 24 to the brain.

A well-corrected eye forms an image at the retina 22. If the intraocular lens 11 has too much or too little power, the image shifts axially along the optical axis away from the retina, toward or away from the lens 11. Note that the total power of the eye (e.g., the combined power of cornea 12 + intraocular lens 11) required to focus on a close or near object is more than the power required to focus on a distant or far object. The difference between the "near power" and "far power" is known typically as the range of accommodation or the add power. A typical range of accommodation or add power is about 2 to 4 diopters, but may be significantly larger for younger human subjects.

The intraocular lens 11 may be designed so that its relaxed or natural state is the "far" or "distant" condition (sometimes referred to as a "disaccommodative biased" intraocular lens), the "near" condition (an "accommodative biased" intraocular lens), or some condition in between the two. As used herein, the terms "natural state", "natural configuration", "relaxed state", and "relaxed condition" refer to a condition of an intraocular lens in which no external forces (e.g., ocular forces from the ciliary muscle, zonules, or capsular bag) are acting upon the intraocular lens 40 or haptic 44.

The capsular bag 18 is acted upon by the ciliary muscle 25 via the zonules 26, which distort the capsular bag 18 by stretching it radially in a relatively thick band about its equator. Experimentally, it is found that the ciliary muscle 25 and/or the zonules 26 typically exert a total force of up to about 10 grams of force, which is generally distributed uniformly around an equatorial region of the capsular bag 18. Although the range of ocular force may vary from patient to patient, the range of accommodation for each subject is

generally limited by the total ocular force available. Therefore, it is generally preferred that the intraocular lens 11 be configured to vary its power over the full range of accommodation in response to this limited range of ocular forces (e.g., to provide at least 3 Diopters or 4 Diopters of accommodative power). In other words, it is desirable to have a relatively large
5 change in power for a relatively small driving force. Alternatively, the effective range of accommodation may be increased by incorporating a lens having a multifocal or extended depth-of-focus configuration.

The intraocular lens 11 generally has two components: an optic 28 made of a transparent, deformable and/or elastic material, and a haptic 30 configured to hold the optic
10 28 in place and to mechanically transfers forces from the eye (e.g., from the capsular bag 18 or ciliary muscle 25) to the optic 28. The haptic 30 may have an engagement member with a central recess that is sized to receive the peripheral edge of the optic 28.

When the eye 10 is focused on a relatively close object, as shown in FIG. 1, the ciliary muscle 25 is compressed, which causes the zonules 26 to relax and allow the
15 equatorial region of the capsular bag 18 to contract. The capsular bag 18 in this state is thicker at its center and has more steeply curved sides. As a result, the power of the lens is relatively high (e.g., the radii of curvature of one or both of the lens surfaces can decrease, and/or the lens can become thicker, and/or the lens can move axially), placing the image of the relatively close object at the retina 22. Note that if the lens could not accommodate, the
20 image of the relatively close object would, for an emmetropic eye, be located behind the retina, and would appear blurred.

FIG. 2 shows a portion of the eye 10 focused on a relatively distant object. To focus on the distant object, the zonules 26 are retracted and the shape of the capsular bag 38 is thinner at its center and has less steeply curved sides. This reduces the lens power by
25 flattening (i.e., lengthening radii of curvature and/or thinning) the lens, placing the image of the relatively distant object at the retina (not shown).

For both the "near" case of FIG. 1 and the "far" case of FIG. 2, the accommodating intraocular lens deforms and changes shape in response to the ciliary muscle 25 and/or to the distortion of the capsular bag 18. For the "near" object, the haptic 30 compresses the optic
30 28 at its edge, increasing the thickness of the optic 28 at its center and more steeply curving its anterior face 27 and/or its posterior face 29. As a result, the lens power increases. For the "far" object, the haptic 30 expands, pulling on the optic 28 at its edge, and thereby decreasing the thickness of the optic 28 at its center and less steeply curving (e.g.,

lengthening one or both radius of curvature) its anterior face 27 and/or its posterior face 29. As a result, the lens power decreases.

Note that the specific degrees of change in curvature of the anterior and posterior faces 27, 29 depend on the nominal curvatures. Although the optic 28 is drawn as bi-convex, they may also be plano-convex, meniscus or other lens shapes. In all of these cases, the optic 28 is compressed or expanded by forces from the haptic to the edge and/or faces of the optic 28. In addition, there may be some axial movement of the optic 28. In some embodiments, the haptic 30 is configured to transfer the generally symmetric radial forces symmetrically to the optic 28 to deform the optic 28 in a spherically symmetric way. However, in alternate embodiments the haptic 30 is configured non-uniformly (e.g., having different material properties, thickness, dimensions, spacing, angles or curvatures), to allow for non-uniform transfer of forces by the haptic 30 to the optic 28. For example, this could be used to compensate for astigmatism, coma or other asymmetric aberrations of the eye/lens system. The optics 28 may optionally have one or more diffractive, multifocal, and/or aspheric elements or surfaces.

Referring to FIGS. 3-7, in certain embodiments, an intraocular lens 40 comprises an adjustable optic 42 and a haptic 44. The optic 42 has a clear aperture 43 that includes an anterior surface 45 and a posterior surface 46. The clear aperture includes a central zone 48 disposed about an optical axis OA and a surrounding or annular zone 50 surrounding the central zone 48.

The haptic 44 may comprise a plurality of arms 52 that protrude into the adjustable optic 42 and into the clear aperture 43. In order to provide a large clear aperture, the haptic 44 and arms 52 includes transparent portions 53 that protrude into the adjustable optic 42 and into the clear aperture 43. The haptic 44 and arms 52 generally protrude into the annular zone 50 but may also partially protruded into the central zone 48. The haptic 44 and arms 52 are configured to deform the central zone 48 in response to an ocular force from the ciliary muscle and/or capsular bag, thereby changing the power of the central zone 48 by at least 1 Diopter, preferably by at least 2 Diopters or at least 4 Diopters. By contrast the annular zone 50 does not change shape in response to an ocular force or changes shape by an amount that produces less accommodative power change than the power change of the central zone 48 (e.g., changes power by less than 1 Diopter in response to an ocular force, less than 0.5 Diopters in response to an ocular force, or less than 0.25 Diopters in response to an ocular force).

The transparent portion 53 preferably has a transmissivity of at least about 80%, more preferably of at least 90% or even 95%. In some embodiments, the haptic 44 is made of a material that has a refractive index that is substantially equal to the refractive index of the optic 42, thus reducing or eliminating glare and aberration problems that could be introduced by a mismatch in refractive indices.

As used herein, the term "clear aperture" means the opening of a lens or optic that restricts the extent of a bundle of light rays from a distant source that can be imaged or focused by the lens or optic. The clear aperture is usually circular and specified by its diameter. Thus, the clear aperture represents the full extent of the lens or optic usable for forming the conjugate image of an object or for focusing light from a distant point source to a single focus or to a plurality of predetermined foci, in the case of a multifocal optic or lens. It will be appreciated that the term clear aperture does not limit the transmittance of lens or optic to be at or near 100%, but also includes lenses or optics having a lower transmittance at particular wavelengths or bands of wavelengths at or near the visible range of the electromagnetic radiation spectrum. In some embodiments, the clear aperture has the same or substantially the same diameter as the optic 42. Alternatively, the diameter of the clear aperture may be smaller than the diameter of the optic 42, for example, due to the presence of a glare or PCO reducing structure disposed about a peripheral region of the optic 42.

The intraocular lens 40 and the optic 42 may be adjusted between an accommodative state and a disaccommodative state. For example, referring to FIG. 6, the optic 42 has a disaccommodative configuration or state in which the central zone 48 has a base optical power suitable for distant vision. Referring to FIG. 7, the intraocular lens 40 has an accommodative configuration or state in which the central zone 48 has an add optical power suitable for near or intermediate vision. The base optical power is generally selected to provide a subject with distant vision (e.g., for objects at distances greater than 20 feet from the subject), while the add optical power of central zone 48 may be exploited to provide a subject with better vision for near objects (e.g., for objects at distances between 12 to 24 inches from the subject) and/or intermediate distances (e.g., for objects at distances between 2 to 5 feet from the subject). Accordingly, the add power is preferably at least about 1 Diopter greater than the base optical power, more preferably at least 2 Diopters greater than the base optical power, and even more preferably at least 3 Diopters or 4 Diopters greater than the base optical power. In the illustrated embodiment, the add optical power is produced by the decreasing radius of curvature of the anterior and posterior surfaces 45, 46,

as illustrated by comparing FIG. 7 to FIG. 6. In some embodiments, the optical add power may be supplemented by accommodative movement of the optic 40 in the anterior direction (e.g., away from the retina of the eye). While the add optical power will generally comprises a positive change in the accommodative power, the add optical power may alternatively be a negative add power.

In certain embodiments, the surrounding zone 50 also has a base optic power when the intraocular lens 40 is in a disaccommodative state and an add optical power when the intraocular lens 40 is in an accommodative configuration. The add optical power of the surrounding zone 50 may be equivalent to the add optical power of the central zone 48. Alternatively, the add optical power of the surrounding zone 50 may be greater than or less than the add optical power of the central zone 48. This difference in the add power between the central and surrounding zones 48, 50 may be the result of differences in how forces on the haptic 44 are transferred to the zones 48, 50.

In addition to providing accommodative power, the central and annular zones 48, 50 generally combine to provide a multifocal lens when the intraocular lens is in the accommodative state, the disaccommodative states, and/or at intermediate states therebetween. Thus, for any given state or configuration of the central and annular zones 48, 50, the intraocular lens 40 may be configured to generally provide an extended depth of focus or multiple foci that allows resolution of objects at varying distances (e.g., simultaneously providing near and intermediate vision, or simultaneously providing intermediate and distant vision).

The multifocality of the intraocular lens 40 (e.g., the differences in optical power of the central and surrounding zones 48, 50) may be produced by a radius of curvature between the anterior and/or posterior surfaces 45, 46 of the central zone 48 and the surrounding zone 50. For example, referring to FIGS. 6 and 7, the radius of curvature of the anterior and posterior surfaces 45, 46 in the region of central zone 48 is less than the radius of curvature of those surfaces in the region of the surrounding zone 50, both in the accommodative state (FIG. 6) and disaccommodative state (FIG. 7). It will be appreciated that the difference in the radius curvatures in the central and annular zones 48, 50 have been exaggerated for illustrative purposes. In some embodiments, the larger radius of curvature in the surrounding zone 50 is selected to provide distant vision, while the smaller radius of curvature of the central zone 48 is selected to provide a larger optical power suitable for intermediate vision and/or near vision. In some embodiments, the difference in optical

power of the two zones 48, 50 is at least partially provided by a diffractive grating or phase plate that is placed on one or both surfaces of the central zone 48 and/or the surrounding zone 50.

5 In the illustrated embodiment, the central zone 48 has a greater optical power than the surrounding zone 50. Alternatively, the central zone 48 may have the same or less optical power than the surrounding zone 50 when the intraocular lens 40 is in the accommodative configuration, the disaccommodative configuration, or in some state between the accommodative and disaccommodative configurations. In some embodiments, the zones 48, 50 are configured to have the same optical power (e.g., to be a monofocal lens
10 having substantially a single focus) when the intraocular lens 40 is in either the accommodative state or disaccommodative state. Alternatively, the zones 48, 50 may be configured to have the same optical power at an intermediate state of the intraocular lens 40 and different optical powers when the intraocular lens 40 is in either the accommodative state or disaccommodative state.

15 The diameter of central and surrounding zones 48, 50 may be selected to provide a predetermined mix of near, distant, and/or intermediate vision that varies as a function of lighting conditions (e.g., as a function of the amount of the optic 42 exposed as the iris of the eye varies in size). For example, diameter of the central zone 48 may be at least about 2 millimeters. Alternatively, the diameter of the central zone 48 may be greater than 3
20 millimeters or greater than 4 millimeters. In some embodiments, the outer diameter of the surrounding zone is greater than about 4 millimeters, preferably greater than or equal to 5 millimeters or greater than or equal to 6 millimeters. In certain embodiments, the optic 42 comprises one or more additional zones surrounding the zones 48, 50, for example, to further adjust the mixture of near, distant, and/or intermediate vision as a function of lighting
25 conditions. In some embodiments, the optic 42 further comprises an intermediate or transition zone disposed between the central and surrounding zones 48, 50 that is configured, for example, to preclude discontinuities between the zones 48, 50 that could produce glare or other unwanted optic effects.

In some embodiments, the central zone 48 and/or the surrounding zone 50 has at
30 least one surface 45, 46 that is aspheric and/or toric in shape and that may be configured to correct an aberration of the eye (e.g., astigmatism, spherical aberrations, coma, and the like). The aspheric or toric shape and associated correction may be present when the intraocular lens 40 is in the accommodative configuration, the disaccommodative configuration, or both

the accommodative and disaccommodative configurations. The central zone 48 and/or the surrounding zone 50 may comprises a diffractive grating or phase plate that is configured to increase or decrease the optical power of the one zone as compared to the remaining zone (which may also include a diffractive zone or grating having a different power). In some
5 embodiments, the diffractive grating or phase plate may be configured to correct for a chromatic aberration.

The optic 42 and the haptic 44 may be integrally made of a single material. Alternatively, the optic 42 may be made of material from one family and the haptic 44 may be made of material from another family (e.g., one from an acrylic family member and the
10 other from a silicone family member). One or both of the optic 42 and the haptic 44 may be made of a hydrophilic material. In some embodiments, the intraocular lens 40 is fabricated such that the optic 42 is stressed by the haptic 44 when the intraocular lens 40 is in a natural state in which there are no external forces acting on the intraocular lens 40. Examples of this type of pre-stressing of an optic are discussed in co-pending U.S. Patent Publication
15 2008/0161914. Other haptic configurations may be incorporated into embodiments of the present invention such as, for examples, those discussed in co-pending U.S. Patent 7,713,299.

The optic 42 may be made from a relatively soft material and configured so that at
20 least a portion of the optic 42 distorts or changes shape readily under the limited deforming force initiated by the ciliary muscle and/or capsular bag and transmitted through the haptic 44. An exemplary material is a relatively soft silicone material, although other suitable materials may be used as well. The stiffness of the optic 42 may be less than 500 kPa, or preferably may be between 0.5 kPa and 500 kPa, or more preferably may be between 10 kPa
25 and 200 kPa, or even more preferably may be between 10 kPa and 50 kPa or between 25 kPa and 50 kPa. In contrast with the optic 42, the haptic 44 may be made from a relatively stiff material, so that it can efficiently transmit the deforming forces from the capsular bag to the optic 42. An exemplary material is a relatively stiff silicone material, although other suitable materials may be used as well, such as acrylic, polystyrene, or clear polyurethanes. The
30 haptic 44 may preferably be stiffer than the optic 42. The stiffness of the haptic 44 may be greater than 500 kPa, or preferably may be greater than 3000 kPa.

Various types of materials, haptic configurations, and/or optic configurations may be utilized to provide a predetermined amount of optic distortion or shape change in response to

an ocular force, either to the optic 42 or to any other optic embodiment discussed or suggested herein. Examples of such materials and mechanisms for providing a desired amount of optic shape change or distortion due to ocular forces may be found in USPN 7,125,422 and in US Patent Application Numbers 2004/0082993, 2004/0111153, and
 5 2005/0131535. As an

example, the optic 42 may comprise an optic body and a liquid or gel material disposed within a void of the optic body. Such an optic structure may be configured to both provide a low optic stiffness and to maintain an overall optic shape that is suitable for vision.

In certain embodiments, a method 100 of implanting an intraocular lens and
 10 providing accommodative vision to a subject comprises an operational block 110 of providing the intraocular lens 40 having a central zone 38 and a surrounding zone 40. The method also comprises an operational block 120 of placing the intraocular lens 40 into the eye of a subject in a disaccommodated configuration in which the central zone has a base optical power. The method 100 further comprise an operational block 130 of adjusting or
 15 causing the intraocular lens to have an accommodated state within the eye, wherein the central zone 48 has an add optical power that is at least 1 Diopter greater than the base optical power, preferably 2 Diopters greater than the base optical power, and even more preferably 3 to 4 Diopters greater than the base optical power. Generally the central zone 48 and the surrounding zone 50 simultaneously have different optical powers when the optic 42
 20 is in the accommodated configuration and/or when the optic 42 is in the disaccommodative configuration.

The method 100 is generally used in conjunction with an intraocular lens having a disaccommodative bias. For example, the intraocular lens 42 may be configured to have a
 25 disaccommodative bias such that the surrounding zone 40 has an optical power that is selected to provide distant vision when the intraocular lens 40 is in a natural configuration in which there are no external forces on the haptic 44. Thus, when the intraocular lens 40 is placed into the eye 10, it has a relatively elongate shape in a direction that is perpendicular to the optical axis OA, as illustrated in FIG. 6.

In operational block 130, the intraocular lens is adjusted to have an accommodative
 30 configuration as an ocular force F (illustrated in FIG. 7) radially pushes the haptic 44 toward the optical axis OA. This places the intraocular lens 40 in a stressed state or configuration so that the adjustable optic 42 deforms and/or thickens into a more oval shape that will increase the optical power of the central zone 48 and optionally increase the optical power of

the surrounding zone 50. The ocular force F is typically within a range of at least about 1 gram to about 10 grams, preferably within a range of 5 to 10 grams. In some embodiments, the ocular force is relatively small, for example, within a range of about 1 to 5 gram or about 1 to 3 grams. Within the art, an understanding of the physiology of the eye is still
5 developing. Thus, other ranges of ocular forces able to provide the above ranges of relative and/or absolute thickness change are anticipated as the physiology of the eye is better understood. Such ranges of ocular forces are also consistent with embodiments of the present invention as disclosed herein.

The intraocular lens 40 may be placed in the capsular bag 18 of the eye 10, such that
10 an outer periphery 54 of the haptic 44 is in contact with an equatorial region of the capsular bag 18. In such embodiments, a contraction of the ciliary muscle 25 causes the capsular bag 18 to produce the ocular force F , causing the intraocular lens 40 into the accommodating configuration. Alternatively, the intraocular lens 40 may be configured for placement in another portion of the eye 10. For example, the intraocular lens 40 may be configured for
15 placement in front of the capsular bag 18 so that the haptic 44 is in direct contact with the ciliary muscle 25 or even the zonules 26.

Referring to FIGS. 9-12, an intraocular lens 240 comprising an adjustable optic 242 and a haptic 244 may be configured to have a disaccommodative bias when placed into the eye 10. The optic 242 includes a central zone 248 and a surrounding zone 250 that are
20 similar to the zones 48, 50, respectively. The intraocular lens 240 is similar to the intraocular lens 40 with at least the exception that it includes an inner ring 246. At least a portion of the inner ring 246 is transparent and has a transmissivity of at least 80%, preferably at least 90% or even 95%. The haptic 244 further comprises a plurality of arms 252 that connect the inner ring 246 with the peripheral portion 251. In the illustrated
25 embodiment, there are eight arms 252; however, more or fewer arms may be used (e.g., 4 arms or 16 arms).

The inner ring 246 is configured to deform an optic 242 in response to an ocular force acting on a peripheral portion 251 of the haptic 244. The inner ring 246 is shown in the form of a contiguous ring in FIGS. 9 and 11. Alternatively, the inner ring 246 may be in
30 the form of a broken ring with radial voids between ring segment, for example, with a radial void disposed between each of the arms 252. The peripheral portion 251 may be in the form of a contiguous ring, as shown in the illustrated embodiment, or in the form of a broken ring.

Either or both rings 246, 251 may have shapes that are not circular and may be shaped to distribute an ocular force about the optic 242 in a predetermined manner.

The arms 252 may include void portions 254 configured to reduce the mass of the intraocular lens 240 and the haptic 244. Such reduction in mass may be utilized to allow the ocular force F to be more completely transmitted to the inner ring 246 and optic 242. The void portions may be triangular in shape, as illustrated in FIGS. 9 and 11, or may have some other shape (e.g., circular or rectangular) that may be selected to provide a desired mass reduction and/or distribution of forces on the inner ring 246 and/or adjustable optic 242.

The thickness along the optical axis OA of inner ring 246 (and/or of portions of the haptic 244 disposed within the adjustable optic 242) may be selected to control the amount and/or distribution of an ocular force acting on the intraocular lens 240. For example, in some embodiments, the performance (e.g., the change Diopter power of the intraocular lens 240 between accommodative and disaccommodative configurations) increases as the edge thickness increases. In such embodiments, other design constraints (e.g., optical performance or physical constraints of the eye) may, however, place an upper limit on the maximum optic edge thickness. In some embodiments, the ring portion 246 of the haptic 244 has a maximum axial thickness that is at least one half a maximum axial thickness of the central zone, as illustrated in FIG. 10. In other embodiments, the ring portion 246 of the haptic 244 has a maximum axial thickness that is at least 75% of a maximum axial thickness of the central zone. These and other predetermined relationships between axial thicknesses of the protruding portions of the haptic 244 and the axial thicknesses of the optic 242 may also be advantageously applied to other embodiments of the invention discussed or suggested herein. Also, where applicable, any of the features, limits, and so forth disclosed with regard to the intraocular lens 40 may also be applied to the intraocular lens 240.

Referring to FIGS. 13-15, an intraocular lens 340 comprising an adjustable optic 342 and a haptic 344 may be configured to have an accommodative bias when placed into the eye 10. The optic 342 includes a central zone 348 and a surrounding zone 350 that are similar to the zones 48, 50, respectively, of the previous embodiment. The haptic 344 comprises a plurality of arms 358 connected together at their distal ends by an external ring 360 and at their proximal ends by an inner ring 362 disposed within the optic 342. In the illustrated embodiment, there are eight arms 358; however, more or fewer arms may be used. Similar to the intraocular lens 240, at least a portion 354 of the ring 362 is transparent and has a transmissivity of at least about 80%, preferably at least 90% or even 95%. Preferably, the

refractive index of the inner ring is substantially the equal to the refractive index of the adjustable optic 342.

5 In contrast to the intraocular lens 240, the outer surface of the haptic 344 is configured to contact a relatively larger region of a capsular bag 18, for example, a region that extends beyond an equatorial region of the capsular bag 18. In the illustrated embodiment, the haptic comprises an outer surface 364 that is configured to conform to at least one of the anterior and posterior capsules of a capsular bag into which the intraocular lens is placed. The relatively large surface area of the outer surface 364 of the haptic 344 may be utilized to provide increased adhesion between the capsular bag and the intraocular
10 lens 340.

Because of this increased adhesion, the intraocular lens 340 may be better suited for use as an accommodatively biased intraocular lens or other configurations where the intraocular lens is pulled outwardly by the capsular bag. In certain embodiments, a method implanting the intraocular lens 340 and providing accommodative vision is similar to that of
15 the method 100, except that the intraocular lens 340 is placed into the eye in an accommodated configuration and adjusted to a disaccommodative configuration by using the walls of a capsular bag to pull radially outward on the inner ring 362 and the adjustable optic 342. Where applicable, any of the features, limits, and so forth disclosed with regard to the intraocular lenses 40, 240 may also be applied to the intraocular lens 340.

20 The description of the invention and its applications as set forth herein is illustrative and is not intended to limit the scope of the invention. Variations and modifications of the embodiments disclosed herein are possible, and practical alternatives to and equivalents of the various elements of the embodiments would be understood to those of ordinary skill in the art upon study of this patent document. The scope of the claims should not be limited by
25 the preferred embodiments or the examples but should be given the broadest interpretation consistent with the description as a whole.

What is claimed is:

1. An intraocular lens, comprising:

an adjustable optic disposed about an optical axis comprising a clear aperture that includes a central zone disposed about the optical axis and an annular zone surrounding the central zone; and

a haptic comprised of a plurality of arms, each arm comprised of a proximal end and a distal end, wherein the proximal ends of each arm protrude into the adjustable optic, and wherein the distal ends of each arm are connected by an external ring;

the intraocular lens having a disaccommodative configuration in which the central zone has a base optical power and an accommodative configuration in which the central zone has an add optical power that is at least 1 Diopter greater than the base optical power;

the central zone and the annular zone simultaneously having different optical powers when the adjustable intraocular lens is in the accommodative configuration or when the adjustable intraocular lens is in the disaccommodative configuration.

2. The intraocular lens of claim 1, wherein the intraocular lens is configured to produce one of the lens configurations in response to an ocular force produced by the eye of a subject into which the intraocular lens is placed.

3. The intraocular lens of claim 2, wherein the ocular force is less than about 6 grams.

4. The intraocular lens of claim 2, wherein the ocular force is produced by a deformation of the capsular bag of the eye.

5. The intraocular lens of claim 1, wherein the add optical power is at least 3 Diopters greater than the base optical power thereof.

6. The intraocular lens of claim 1, wherein the intraocular lens has a disaccommodative bias in which the intraocular lens has the disaccommodative configuration when the lens is in a natural state.

7. The intraocular lens of claim 1, wherein the haptic portion has an inner diameter that is equal to an outer diameter of the central zone.
8. The intraocular lens of claim 1, wherein the optical power of the central zone, for at least one of the lens configurations, is greater than the optical power of the annular zone.
9. The intraocular lens of claim 1, wherein the add power of central zone is at least 3 Diopters greater than the base optical power thereof.
10. The intraocular lens of claim 1, wherein the haptic portion has a maximum axial thickness that is at least one half a maximum axial thickness of the central zone.
11. The intraocular lens of claim 1, wherein the haptic portion has a refractive index that is substantially equal to a refractive index of the adjustable optic.
12. The intraocular lens of claim 1, wherein the haptic comprises an outer surface that is configured to conform to at least one of the anterior capsule and the posterior capsule of a capsular bag into which the intraocular lens is placed.
13. The intraocular lens of claim 1, wherein the haptic protrudes into the edge of the adjustable optic.
14. The intraocular lens of claim 1, wherein the haptic is stiffer than the adjustable optic.
15. The intraocular lens of claim 1, wherein the haptic comprises at least two materials having different stiffnesses.
16. The intraocular lens of claim 1, wherein the adjustable optic comprises a material having a stiffness that is less than 50 kPa.
17. The intraocular lens of claim 1, wherein the adjustable optic comprises a material having a stiffness that is less than 100 kPa.
18. An intraocular lens, comprising:

an adjustable optic disposed about an optical axis comprising a clear aperture that includes a central zone disposed about the optical axis and an annular zone surrounding the central zone; and

a haptic comprised of a plurality of arms, each arm comprised of a proximal end and a distal end, wherein the proximal ends of each arm protrude into the adjustable optic, and wherein the distal ends of each arm are connected by an external ring;

the intraocular lens having a natural configuration in which the central zone has a base optical power and a stressed configuration in which the central zone has an add optical power that is at least 1 Diopter greater than the base optical power;

the central zone and the annular zone simultaneously having different optical powers when the intraocular lens is in the stressed configuration and/or when the optic is in the natural configuration.

19. The intraocular lens of claim 18, wherein the intraocular lens has a disaccommodative bias.

20. Use of an intraocular lens comprising:

an adjustable optic disposed about an optical axis comprising a clear aperture that includes a central zone disposed about the optical axis and an annular zone surrounding the central zone; and

a haptic comprised of a plurality of arms, each arm comprised of a proximal end and a distal end, wherein the proximal ends of each arm protrude into the adjustable optic, and wherein the distal ends of each arm are connected by an external ring;

for providing accommodative vision to a subject, wherein the intraocular lens is adapted for placement into the eye of a subject in a disaccommodated configuration in which the central zone has a base optical power and adapted for subsequent adjustment to an accommodated configuration in which the central zone has an add optical power that is at least 1 Diopter greater than the base optical power;

wherein the central zone and the annular zone simultaneously have different optical powers when the intraocular lens is in the accommodated configuration and/or when the optic is in the disaccommodative configuration.




FIG. 1







FIG. 2






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12






FIG. 15

