

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2014/152239 A2

(43) International Publication Date
25 September 2014 (25.09.2014)

WIPO | PCT

(51) International Patent Classification:

F28D 7/16 (2006.01)

(21) International Application Number:

PCT/US2014/027108

(22) International Filing Date:

14 March 2014 (14.03.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/789,235 15 March 2013 (15.03.2013) US

(71) Applicant: THAR ENERGY LLC [US/US]; 150 Gamma Drive, Pittsburgh, PA 15238 (US).

(72) Inventors: CHORDIA, Lalit; 60 Long Meadow Drive, Pittsburgh, PA 15238 (US). DAVIS, John, C.; 9 Rodgers Drive, Pittsburgh, PA 15238 (US).

(74) Agents: VERNON, Deborah, M. et al.; McCarter & English, LLP, 265 Franklin Street, Boston, MA 02110 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- without international search report and to be republished upon receipt of that report (Rule 48.2(g))



WO 2014/152239 A2

(54) Title: COUNTERCURRENT HEAT EXCHANGER/REACTOR

(57) Abstract: Counter-flow heat exchanger is constructed with plenums at either end that separate the opposing fluids, the channels of which are arrayed in a checkerboard patterns, such that any given channel is surrounded by channels of opposing streams on four sides - laterally on both sides and vertically above and below.

COUNTERCURRENT HEAT EXCHANGER/REACTOR**CROSS-REFERENCE TO RELATED APPLICATION**

[0001] This application claims benefit of and priority to US Provisional Application Serial No. 61/789,235, filed March 15, 2013, incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

[0002] This invention relates to the field of single-pass countercurrent heat exchangers, more particularly, this invention relates to such devices that exhibit high areal density.

BACKGROUND

[0003] It is well known that heat can be transferred between fluids within a given volume more efficiently as the size of the channels that conduct these fluids decreases and the number of channels increases. At channel dimensions that are considered by most as “microchannel” in size, meaning less than 5 millimeters and more likely less than 2 millimeters in diameter, design problems multiply rapidly. For example, header design (i.e., separation of opposing streams) is one of the most challenging of problems. Especially in the case of countercurrent flow, it is difficult to maintain separation between opposing streams. The usual remedy has been to arrange the opposing streams in cross-flow configuration; i.e., one stream flowing in the X-direction, while the other flows in the Y-direction, so that their respective inlets and outlets are separated. A hybrid of the countercurrent and cross-flow design is the conventional shell-and-tube heat exchanger with baffles including those of multi-pass and serpentine configuration. The problem with these approaches, however, is that heat transfer efficiency suffers either from a poor pattern of temperature difference or flow distribution, or both. The ideal pattern is to arrange the channels in such a way that the hot stream enters from one end while the cold stream enters from the other, along the same axis, such as along the longitudinal axis of the

exchanger. This is single-pass countercurrent flow with little or no cross-flow mixing of either stream.

[0004] In shell-and-tube heat exchangers, one stream enters the “tube side” via tubes that extend through a vessel that is filled with another fluid flowing generally in the opposite direction. The opposing fluid flows on the so-called “shell-side” of the heat exchanger. Typically, fluid enters the shell at the opposite end from the fluid entering the tube side. Tubes penetrate a “tube sheet” that contains the shell-side fluid within the vessel, thereby preventing shell-side fluid from leaking into headers that distribute the tube-side fluid to and from the tubes. Countercurrent flow is somewhat achieved in this configuration by ensuring that shell-side fluid flows outside the tubes in an opposite direction to the flow of fluid inside the tubes. However, flow is poorly distributed because of the introduction of the fluid via side ports. To improve flow distribution, internal baffles deflect flow along a serpentine rather than straight axial, path. This results in hybrid of counter-current and cross-flow, as previously described. Increasing the number of baffles, increases the degree of countercurrent flow and the associated heat transfer. This results in an increase in pressure drop as the number of baffles increases. However, there is a practical limit to the number of baffles that one can use.

[0005] The shell-and-tube configuration has been practiced at a microchannel level using hollow fibers that are typically spun from a polymeric melt. Squeezing the mass of fibers at either end achieves the same effect as a tube sheet. Heat exchangers of this type, however, are limited in both temperature and pressure. For high temperatures or pressure, typically metal channels and metal tube sheets are required. For microchannel heat exchangers the separation of the streams becomes more difficult because of the high density of channels penetrating the tube sheet. The usual remedy is to resort to a parallel-plate configuration in which opposing streams flow through alternating layers. For example, small microchannels can be achieved by etching or stamping a channel pattern into a thin plate and then bonding that plate to another smooth plate. Depending on the depth of the

microchannel, the plates can be bonded by either brazing or diffusion bonding. The use of small microchannels improves efficiency in a compact design, but the device may be heavy due to the space taken up by solid, unetched metal underneath the channels.

SUMMARY OF THE INVENTION

[0006] The present invention discloses a method of heat transfer between two fluids streaming in a single-pass countercurrent flow, wherein the opposing streams are arranged in a bundle such that they exchange heat in four directions, laterally on both sides, above and below. At either end of the bundle one of the opposing streams remains confined within closed channels that penetrate an open plenum area while the other opposing stream is free to flow into the plenum area and between the confining channels of the first stream. Also at either end of the bundle the confined stream enters or exits through a cavity that is distinct from the plenum area. The plenum area is positioned between the bundle and the cavity through which the confined stream flows. As the cross sectional area of the tube decreases, the areal density of the channel bundle increases. For example, channel dimensions in the microchannel range (less than 5 millimeters) are needed to achieve areal densities greater than $400 \text{ m}^2/\text{m}^3$ (total heat-transfer surface area as a ratio of overall volume). The heat transfer coefficient of at least one of the opposing streams can be preferably enhanced by any of means that are known to increase flow turbulence, such that the heat transfer coefficients of both streams are within one order of magnitude of each other. That is, in some embodiments, modification, alterations and/or additions to the channels (e.g., roughening of channels walls, modification of interior shape of the channel, addition of porous media within the channel, etc.) can be made to some portion of the channels to increase turbulence therein.

[0007] Also disclosed is a method of chemical reaction and simultaneous heat transfer between two streams in countercurrent flow, but with the at least one of the opposing streams undergoing chemical reaction within the

channel bundle. One of the opposing streams provides energy to the other stream.

[0008] Also disclosed is a device composed of channels arranged for countercurrent flow, wherein fluids flow in opposite directions through a bundle of channels whereby the opposing streams of fluid are arranged in a checkerboard pattern, such that for any given channel there exist alongside, in four directions, laterally on both sides, above and below, channels containing the opposite fluid. At either end of the bundle, channels confine one of the opposing streams through the plenum area and extend into a cavity through which the stream enters or exits the device by ports that are in the cavity wall. The channels that continue through the plenum may be modified in size and shape so as to allow fluid from the other opposing stream to flow around them to or from ports that are in the plenum wall. The heat transfer coefficient is enhanced by one or more means including: increased surface roughness of the channel walls; fins extending from channel walls; porous media that is fixed within channels

[0009] This device may be formed by a first set of half-checkerboard channels in the shape of a hollow polygon of no more than four sides, while complementary half-checkerboard pattern takes the form of the similar polygon both in shape and size.

[0010] Also disclosed is a device formed by a first set of half-checkerboard channels in the shape of a hollow polygon of no more than four sides, while complementary half-checkerboard pattern takes the form of the similar polygon in shape but not in size.

[0011] Also disclosed is a device formed by a first set of half-checkerboard channels in the shape of a hollow polygon of no more than four sides, while complementary half-checkerboard pattern takes the form of the polygon that is neither similar in size or shape or even take the shape of the voids created between the first set of channels.

[0012] Also disclosed is a device composed of channels similarly arranged for countercurrent flow, but with the difference that at least one set of the channels is blocked in the axial direction and redirected transversely to a collection zone along the side of said end, impervious to the enclosed cavity. Channels of the axially blocked set or sets travel diagonally between channels of the opposing set without intersecting them and terminate in a common header that forms area collection zone. The outer wall of this collection zone contains a port through which fluid can enter or exit the device. This heat transfer coefficient is similarly enhanced by one or more means including: increased surface roughness of the channel walls; fins extending from channel walls; porous media that is fixed within channels.

[0013] Embodiments of the present disclosure are directed to a countercurrent flow single pass heat exchanger. In some embodiment, the heat exchanger includes a bundle of channels, a first fluid receiving member and a second fluid receiving member. The bundle of channels includes a first plurality of channels and a second plurality of channels. Individual channels of the first plurality are arranged with respect to individual channels of the second plurality to form a checkerboard pattern substantially through a transversal cross-section of the bundle. The individual channels of the first plurality of channels are in fluid communication with first flowstream ports and individual channels of the second plurality of channels are in fluid communication with second flowstream ports, wherein the first flowstream ports are distinct from and not in fluid communication with the second flowstream ports. The bundle, the first fluid receiving member, and the second fluid receiving member are arranged such that the first fluid receiving member is positioned between the second fluid receiving member and an end of the bundle; and wherein the second plurality of channels extend pass the end of the bundle and through the first fluid receiving member. It is noted that the first plurality of channels extends through the bundle and is in fluid communication with a collection area of the first fluid receiving member. The collection area is fluidly connected to at least one of the first flowstream ports.

[0014] In another embodiment, the heat exchanger includes a bundle of channels, a first fluid receiving member and a second fluid receiving member. The bundle of channels includes a first plurality of channels and a second plurality of channels. Individual channels of the first plurality of channels are in fluid communication with first flowstream ports and individual channels of the second plurality of channels are in fluid communication with second flowstream ports. The first flowstream ports being distinct from and not in fluid communication with the second flowstream ports; wherein the individual channels of the first plurality are arranged with respect to the individual channels of the second plurality to exchange heat within an interior region of the bundle (i.e., any region which excludes an outer boundary/edge of the bundle) along a longitudinal axis of the bundle in four directions with respect to each channel without mixing the first and second streams. The four directions includes above a selected channel in the interior region, below the selected channel, and along at least a portion of each lateral side of the selected channel. The bundle of channels, the first fluid receiving member and the second fluid receiving member are arranged such that the first fluid receiving member is positioned between the second fluid receiving member and an end of the bundle; wherein the second plurality of channels extends pass the end of the bundle and through the first fluid receiving member. It is noted that the first plurality of channels extends through the bundle and is in fluid communication with a collection area of the first fluid receiving member. The collection area being fluidly connected to at least one of the first flowstream ports.

[0015] Embodiments of the above heat exchangers can include one or more of the following features. In some embodiments, an areal density of the bundle of channels is greater than $400 \text{ m}^2/\text{m}^3$. In certain embodiments, at least a portion of the channels within the bundle of channels include walls with increased surface roughness. In some embodiments, at least a portion of the channels within the bundle of channels include fins extending from channel walls. Some embodiments also include porous media fixed within at least a portion of the channels. The porous media can increase turbulence.

In some embodiments the porous media can be a catalyst for a reaction. Some embodiments include channels that have a modified or varying size and/or shape. For example, in some embodiments, at least a portion of the second plurality of channels within the collection area have a different cross-section size and/or shape than within the bundle. In certain embodiments, a cross-sectional shape of individual channels of the first plurality of channels differs from a cross-sectional shape of individual channels of the second plurality of channels. In some embodiments, a cross-sectional area of individual channels of the first plurality of channels differs from a cross-sectional area of individual channels of the second plurality of channels. Other embodiments include channels formed at least in part with rows of elongate members. For example, in some embodiments, the second plurality of channels includes a plurality of elongate members spaced along a plurality of sheets to form rows of elongate members and the first plurality of channels comprises a plurality of voids, each of the voids being confined to form a channel by adjacent sheets within the plurality of sheets and by walls of two adjacent elongate members within rows of elongate members. Certain embodiments feature diagonal pathways. For example, in certain embodiments, the collection area is formed within a chamber defined by walls forming the first fluid receiving member; axial flow within the first fluid receiving member of the first plurality of channels is obstructed to force the first flowstream along diagonal pathways in fluid connection with the collection area. Some embodiments include a cavity for the collection of fluid from the second plurality of channels. The cavity is in fluid communication with at least one of the second flowstream ports and is defined by the second fluid receiving member.

[0016] Other embodiments of the present disclosure are directed to a method of manufacturing a bundle of channels for a heat exchanger. The method includes: additively manufacturing a first and second plurality of metal channels, wherein individual channels of the first plurality are arranged with respect to the individual channels of the second plurality to form a checkerboard pattern through a transversal cross-section of the bundle, the

first and second plurality of channels being fluidly distinct, each of the channels of the second plurality of metal channels extending in length past an end of the first plurality of channels and at least one of size or shape of the transversal cross-sectional area of the individual channels of the second plurality changing along a longitudinal direction.

[0017] Embodiments of the above method of manufacturing can include one or more of the following features. In some embodiments, the first and second plurality of metal channels are additively manufactured out of (at least in part) Inconel. In other embodiments, the first and second plurality of metal channels are additively manufactured out of (at least in part) stainless steel. In certain embodiments, the heat exchanger is additively manufactured such that a wall thickness of the individual channels of the second plurality of channels increases along the longitudinal direction.

[0018] Other embodiments of the present disclosure are directed to a method of heat transfer between a first fluid stream and a second fluid stream in a countercurrent single pass heat exchanger. The method includes the following steps: (a) flowing the first fluid stream and the second fluid stream in a bundle of channels such that the first and second fluid streams flow countercurrently to each other to exchange heat within an interior region of the bundle along a longitudinal axis of the bundle in four directions with respect to an individual channel without mixing the first and second fluid streams, the four directions comprising above the individual channel, below the individual channel, and along at least a portion of each lateral side of the individual channel; (b) collecting the first fluid stream in a first fluid receiving member, the second fluid stream being confined within a plurality of channels extending through the first fluid receiving member to separate the first and second fluids; and (c) collecting the second fluid stream in a second fluid receiving member.

[0019] Embodiments of the above method of heat transfer can include one or more of the following features. In some embodiments, the above method can include an additional step of: increasing flow turbulence of the

first fluid stream such that a heat transfer coefficient of the first flow stream is modified to a value which is within one order of magnitude of a heat transfer coefficient value of the second fluid stream. Some embodiments of the method include a chemical reaction. For example, in some embodiments, a chemical reaction occurs in the first fluid stream and the second fluid stream absorbs energy therefrom. In certain embodiments, a chemical reaction occurs in the first fluid stream and the second fluid stream provides thermal energy to the first fluid stream.

[0020] The above embodiments can include one or more of the following advantages. A heat exchanger of the type disclosed herein is useful in many different applications that demand compactness; *i.e.*, high rates of heat transfer in a small package. For example, in utility power generation, recuperators are often employed to recover heat from working fluid from a turbine exhaust and recycle that energy to working fluid that is being heated ahead of the turbine. In these applications, recuperation heat duties can be several times that of the power generated. Without a compact design, these recuperators could become much too large for economical feasibility. This technology is also applicable to heat exchangers that move heat in and out of phase-change materials (PCMs). By minimizing the boundaries of solid-liquid interfaces through the use of microchannels, heat transfer efficiency is maximized and working-fluid flow rates are minimized. This facilitates huge savings at several points around a power cycle – a smaller solar receiver, smaller compressor, smaller recuperator and less waste heat. The manufacturing technology disclosed herein will also extend the commercial applications of microchannel construction to air-to-air and air-to-steam heat exchangers, as might be encountered in waste heat applications.

BRIEF DESCRIPTION OF THE FIGURES

[0021] Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings for the purpose of illustrating the embodiments, and not for purposes of limiting the invention, wherein:

[0022] Figures 1A and 1B are perspective views of one embodiment of a heat exchanger in accordance with the present disclosure. Figure 1A includes a set of end caps, whereas in Figure 1B, the end caps are removed to expose a separator plate.

[0023] Figure 2 is a cross-sectional illustration (i.e., medial view) of one portion of the heat exchanger of Figure 1A.

[0024] Figures 3A, 3B, 3C, and 3D are cross-sectional views taken along lines A-A, B-B, C-C, and D-D of Figure 2, respectively.

[0025] Figure 3E is an enlarged view showing the cross-sectional view of Figure 3C.

[0026] Figures 4A-D illustrate different representative cross-sectional patterns (i.e., different checkerboard patterns), wherein size and shape of flow cross sectional areas between the complementary sets of channels forming the checkerboard pattern are similar.

[0027] Figure 5 illustrates another embodiment of a checkerboard pattern of channels. In the embodiment illustrated in Figure 5, channels forming one set within the checkerboard have a cross-sectional shape that is similar to its complementary set but the sizes of the channels in each set are different.

[0028] Figures 6A and 6B are cross-sectional of two different embodiments in which the cross-sectional shape and size of two sets of channels forming a checkerboard pattern are different.

[0029] Figure 7 is a cross-sectional illustration of another embodiment of one portion of a heat exchanger in accordance with the present disclosure.

[0030] Figures 8A, 8B, 8C, and 8D are cross-sectional views taken along lines A-A, B-B, C-C, and D-D of Figure 7, respectively.

[0031] Figures 9A and 9B are cross-sectional views of an embodiment of a heater exchanger in accordance of the present disclosure. In Figure 9A, the cross-sectional view is taken within a first stream fluid collection area. In Figure 9B, the cross-sectional view shows both the fluid collection area of the first stream (from Figure 9A) overlapped with a fluid receiving and distribution area for a second stream, which flows in the opposite direction from the first flow stream.

DETAILED DESCRIPTION OF THE INVENTION

[0032] An illustration of an exemplary heat exchanger, heat exchanger 10, of the present invention is shown in Figures 1A and 1B. Figure 1A shows the relationship of a channel bundle 1 to headers 2 and end caps 3. Specifically, the channel bundle 1 is positioned between the headers 2, which are disposed on each end of the channel bundle 1. End caps 3 are located adjacent to the headers 2. In Figure 1B, the end caps 3 are removed to show openings within a separator plate 5 and to further identify terminal planes 4, which define the ends of the channel bundle 1. In general, heat exchangers in accordance with the present disclosure provide single-pass counter-current heat exchange between two opposing fluids which are kept separate from each other.

[0033] Figure 2 is a cross-sectional view of one-half or one end of the heat exchanger 10. (The other half of heat exchanger 10 not shown is its mirror image.) The cross-sectional view is take along the medial plane to show various flow paths therethrough. In particular, heat exchanger 10 includes channel bundle 1, where channels 12A, 12B conduct opposing streams 14, 16 (respectively). Channels 12A and 12B are constrained within walls 18 so that they flow only in one axial direction (Z) – the longitudinal axis of the exchanger 10. At an end 1A of the channel bundle 1, is positioned one of the two headers 2. Within the headers 2 stream 14 is unconfined by channels 12A and is free to flow in a transverse direction (T) in plenum area 9 toward side ports 6. Stream 16 however is confined in channels 12B and thus is still separate from stream 14 within the plenum area 9. Following the header 2 is one of the two

end caps 3. Opposing stream 16 is injected into heat exchanger 10 through axial port 7 within end cap 3 and into a collection zone 22 to be fed into channels 12B to carry the opposing stream 16 axially through channel bundle 1 and on through the axial port (not shown) at the other end of heat exchanger 10. Thus, as shown in Figures 1A, 1B, and 2, channel bundle 1 has two sets of longitudinally extending channels 12A and 12B for the transportation and separation of two fluids 14 and 16. Channel bundle 1 extends between two terminal planes 4 (Figure 1B shows both terminal planes, whereas the view shown in Figure 2 is limited to just a single terminal plane 4). Extending from the end 1A of the channel bundle 1 is the header 2, where stream 14 flows into the plenum 9 and out port 6. (In the mirror half of the heat exchanger 10 not shown, port 6 is an inlet instead of an outlet for stream 14). To maintain separation of the two streams, channels 12B extend through the header 2 past a separator plate 5 and into the end cap. Fluid 16, which is transported in channels 12B enters the heat exchanger 10 through port 7 in end cap 3. The fluid 16 is contained within the collection zone 22 for the distribution of stream 16 into channels 12B (for this end 10A of the heat exchanger). In end 10B, not shown in Figure 2, fluid 16 passes through channels 12B and empties into collection zone 22 prior to exiting the device through outlet 7. Channels 12A and 12B are arranged within heat exchanger 10 to create a checkerboard pattern. That is, channels 12A and 12B do not only alternate type of channel (e.g., 12A or 12B) vertically along the transverse direction (T) as shown in Figure 2, but also horizontally, such that each channel within an interior of the bundle is surrounded on four sides by a channel of the opposite type to create a checkerboard pattern.

[0034] A discriminating feature of this heat exchanger design is that every channel for each set of half checkerboard receives its own fluid that does not mix with the flow from an adjacent channel. In conventional shell-and-tube heat exchangers, one or more horizontal baffles may serve to delineate separate compartments of shell-side flow -- usually for the purpose of reversing flow of the shell-side between compartments -- but not for the purpose of ensuring single-pass axial counter-current flow.

[0035] Below are definitions of terms used herein to describe the invention:

[0036] Checkerboard - a pattern in which zones of opposite characteristics, such as fluid properties, exist side-by-side in four directions – laterally on both sides, above and below – in the same way as the colors of a checkerboard game table are arrayed.

[0037] Half-checkerboard - just one of the two complementary patterns that make up the full checkerboard pattern.

[0038] Channel bundle - a collection of channels, arrayed in a checkerboard pattern.

[0039] Header - a zone within which the opposing fluids are distributed separately to the channels of one half-checkerboard pattern or the other. It is composed of two distinct spaces that are impervious to each other.

[0040] Separator plate - a wall, penetrable only by a set of channels dedicated to one of the two half-checkerboard patterns. It is analogous to the “tube sheet” of conventional shell-and-tube heat-exchanger designs.

[0041] Areal density - the ratio of total internal surface area of channels of the smaller cross-sectional perimeter of the two channel patterns, to the total outside volume dimension of the channel bundle, expressed as square meters per cubic meters.

[0042] Plenum - a space that is open to more than one channel. It can be used as a distribution point for fluid entering or exiting channels. For purposes of this disclosure, the plenum is the space directly adjacent to the channel bundle that distributes fluid that enters or exits the heat exchange transverse to a longitudinal axis of the channel bundle.

[0043] As noted above Figure 2 shows in cross-section one end of the heat exchanger (end 10A), including one of the two end caps 3, one of the two separation plates 5, one of the two plenums 6 and a portion of the channel

bundle 1. The countercurrent flow of opposing streams 14, 16 is represented by the opposing arrows running through channels 12A, 12B from right-to-left and from left-to-right (respectively). Only one vertical plane of channels 12A, 12B is represented in Figure 2. Figures 3A, 3B, 3C, and 3D are provided to show cross-sections containing both the vertical and horizontal planes along different locations along the longitudinal axis of the heat exchanger 10. For demonstration purposes, Figures 3A-3D show an embodiment which includes an 5 x 5 array of channels of the 12B type. It is understood that there is no theoretical limit to the number of channels 12A and 12B, nor is the pattern limited to identical squares as shown. There could be hundreds or thousands, limited only by the capacity of fabrication machinery. In Figures 3A-D walls 18 between channels 12A, 12B are shown in black. Open areas 24 are in white. The purpose of Figures 2 and 3A-D is to show the means of keeping the opposing streams 14, 16 separate.

[0044] In particular, Sect. A-A of Figure 2 is shown in Figure 3A and illustrates an embodiment of a channel array 26 as it exists within channel bundle 1. Individual channels 12A are shown as square, although they could be round, oval, trapezoidal, or half-moon-shaped, as well as filleted inside. Opposing channels 12B are of a complementary shape and are disposed about channels 12A in four directions (above, below, and on either side) to form the checkerboard pattern.

[0045] The termination of channel bundle 1 occurs at the terminal plane 4, shown as Sect. B-B in Figure 2 and represented in cross-sectional view as Figure 3B. At this point, channels 12A end abruptly and are open to plenum area 9 of the header 2. Inside the plenum area 9 there exist unobstructed spaces 24 between the continuation of channels 12B that confine the opposing stream 16 while streams 14 from the multitude of channels 12A can comingle and mix to form plenum fluid 28. Channels 12B extend through plenum area 9 to separator plate 5. An important requirement of the continuing channels 12B is that they do not join together or coalesce, so as to permit flow of plenum fluid 28 between the continuing channels 12B and through plenum area 9 to side ports 6. Plenum fluid 28 (i.e., collected fluid 14

from channels 12A) finds its way to or from ports 6 through this labyrinth of continuous channels 12B. (See also Figures 3C and 3E. Figure 3C is a cross-section taken along line C-C in Figure 2 and depicts a portion of the plenum area. Figure 3E provides an enlarged view of Figure 3C to illustrate the flow path of the plenum fluid 28.) For this reason, the contour of the continuing channels 12B might change to circular, oval or some other shape in the segment that runs through the plenum area 9, if it is not already so. It might also change to a smaller area while maintaining the same basic contour. Or, it might do both – shrink in size and change in shape. Any of these modifications is for the purpose of ensuring free space completely around confining channels 12B, such that the other opposing stream 14 is free to flow into the plenum area 9 and between the confining channels 12B of the stream 16 to or from ports 6 that are in plenum wall 30. This is shown in Figure 3B, where channels 12A of stream 14 that terminate at this plane are shown in square shape, while the continuing channels 12B of stream 16 are round. The contour of the continuing channels 12B remains round or ovate through the plenum area 9, as shown in Figure 3C (a cross-section taken along line C-C in Figure 2), and through the separator plate 5, as shown in Figure 3D (a cross-section taken along line D-D in Figure 2). An end cap 3, comprising an axial port 7 and enclosing an open chamber, collection zone 22, through which fluid flows from or into channels 12B. Additional containment measures, including a vessel that encloses this device (not shown), may be used to hold pressure around the entire body of heat exchanger 10.

[0046] In the above embodiments of heat exchanger 10, flow paths of streams 14 and 16 have been described as either entering and exiting the exchanger through one of ports 6 or 7. For example, stream 14 has been described as entering the heat exchanger device through port 6 in end 10B (see Figure 1A) and exiting the exchanger 10 through port 6 in end 10A (in a direction transverse to the longitudinal axis), whereas stream 16 enters the exchanger 10 through port 7 in end 10A and exits through port 7 in end 10B (in a direction parallel to the longitudinal axis). However, other embodiments are possible. For example, it may be preferable to include an transverse and

parallel component to inlet/outlet flow for each stream. For example, in some embodiments, stream 14 enters the exchanger 10 through port 7 on end 10B, flow through the plurality of channels 12A and exit through port 6 on end 10A, while stream 16 enters the exchanger 10 through port 7 on end 10A, flow through the plurality of channels 12B, and exit through port 6 on end 10B. In this embodiment, the plurality of channels 12A and 12B in the bundle would be fluidly connected to their respective port to allow for fluid inlet and outlet flow. That is, channels 12A would extend from end cap 3 in end 10B, through header 2 in end 10B, through the bundle 1, and be fluidly connected to the fluid receiving area/plenum area 9 of header 2 in end 10A. Similarly, in this embodiment, channels 12B would extend from end cap 3 in end 10A, through header 2 in end 10A, through the bundle 1, and be fluidly connected to the fluid receiving area/plenum area 9 of header 2 in end 10B.

[0047] Various configurations of channel bundles that fall within the scope and definition of a checkerboard pattern are described in Figures 4A-D. Some of the patterns described herein may not look like checkerboards at first glance.

[0048] Figures 4A-D show contiguous channels 32, meaning that adjacent channels share the same walls 34. Contiguous channels 32 can be either circular, triangular or quadrilateral (including trapezoidal). Opposing channels are shaded differently in the figures so as to highlight the checkerboard flow pattern. In the case of quadrilateral channel (Fig. 4A, 4B), the presence of opposing channel on four sides, laterally on either side, above and below, is reasonably obvious. In the case of triangular channels (Fig. 4C), the pattern is clear if one imagines that one of the four sides of an otherwise quadrilateral shape shrinks to a point. In the case of circular channels (Fig. 4D), even though channels 46 (containing a first stream) and channels 48 (containing a second separate stream) have a circular perimeter, heat transfer happens throughout the entire perimeter and thus four sides or portions corresponding to the four sides are provided.

[0049] The contiguous channels 32 need not have the same cross-sectional area; one set of channels can be smaller than the other set of channels. Figure 5 shows circular contiguous channels 32 that are adjacent to each other but are of different sizes. (Channels 46 containing the first stream are of a different size than channels 48 containing the second stream.) Contiguous channels 32 can be either circular, triangular or quadrilateral (including trapezoidal).

[0050] Fig 6A and Fig. 6B show contiguous channels 32 of different shape and size. Virtually any tubular shape – circular (Fig. 6A), ovate and polygonal (Fig. 6B) to any number of sides – may be applied to one of the opposing streams 16, then assembled in layers that are separated by sheets 40. The void spaces 42 between channels 44, for example tubes, become the channels of the stream 14. The overall checkerboard pattern is evident from the differential shading applied to the channels in Figures 6A and 6B. In the sheet-separated channel configuration 38, some segments of the separator sheet 40 will be shared by channels of the same stream rather than the opposing stream. Such segments, however, are either very short or tend to occur at points where flow would be constrained by geometrical irregularity. In the case of tubes 44 held between separator sheets 40 (Figure 6A) these areas are in the form of sharply pointed wedges.

[0051] For example, stream 16 can be directed through round or ovate tubes 44 (acting as channels) that may be welded to thin sheets 40 above and below, forming a sandwich of tubes 44 held between metal sheets 40. The spaces 42 between the tubes 44 can then be used to convey the other stream 14 counter-currently. In this case, void spaces 42 between tubes 44 would look something like an hourglass. The relative area of tube cross-section versus that of the hourglass cross-section is variable according to the pitch, or distance between tubes. The basic pattern of the checkerboard is retained in that each channel exists in proximity to channels of opposing flow, exchanging heat in four directions, laterally on both sides, above and below.

[0052] In an exemplary embodiment of the sheet-separated channel configuration 38, each stream, 14 and 16, would enter via a side port 6 and exit via an axial port 7 at the other end, or vice-versa. This configuration may improve pressure drop, depending on conditions of temperature, pressure and viscosity. The alternative is to have the streams 14 and 16 enter and exit via the same type of collector, be it located on the sides to handle fluid that flows transversely through a header 2, or axially at the end caps 3 of the heat exchanger 10.

[0053] In the configuration shown in Figs. 7 and 8A-D a different header design is shown. As an alternative to the open plenum at the axial end 1A of the channel bundle 1 (as shown in Figure 2), diagonal channels 52 are cut near the ends 1A of the channel bundles 1 such that only one set of half-checkerboard channels 46 is intersected. The end 1A of the channel bundle 1 is then capped with a plate 5 that has holes only for the complementary set of half-checkerboard channels 48 while the other set of channels 46 is redirected in a collection zone 54 *within* the channel bundle to a manifold 58 alongside the ends of the bundle, as illustrated in Figure 8C. Figure 7 describes the flow paths for the opposing streams 14, 16 in a manner analogous to Figure 2. One difference between the two designs is that the shape of the continuing channel 12B need not change as it passes through the collection zone 6, as it does in case of contiguous channels 32, because in this case the stream 14 flowing through the side ports 60 is guided by the diagonal channels 52 that are cut within the channel bundle 1. Thus, cross-sectional views taken along lines A-A and B-B of Figure 7 and shown as Figures 8A and 8B, respectively, are identical. The cross-sectional view in the collection zone 54 and manifold 58 where the diagonal guide channels 52 exist is shown in Figure 8C (a cross-sectional view taken along line C-C in Figure 7). The outer dimensions (X) of the heat exchanger 10 will expand somewhat to accommodate the collection zone 54 and manifold 58. This extra girth is also indicated in Figure 7. The manifold 58, shown in Figure 8C, directs stream 14 to port 60. Immediately following the collection zone 6 is a separator plate 72 (see Figure 8D, which is a cross-section taken along line

D-D in Figure 7)) through which only the channels 48 of the half-checkerboard array 66 of the opposing stream 16 can penetrate or pass through. Separator plate 72 in Figure 7 is analogous to separator plate 5 in Figure 2. These channels 48 ultimately empty into the cavity 22 of the heat exchanger's end cap 3.

[0054] Referring to Figure 8C, a flow pattern for the case of one stream flowing in or out of the heat exchanger in a axial direction while the other stream flows out through a side port is shown. Figure 9A repeats this embodiment, in which one fluid stream flows to a collection zone 54 and out a port 60. Figure 9B is an illustration of an embodiment in which both streams flow into or out from the heat exchanger via diagonal channels. The manifold flow patterns of the two streams are mirror images of each other. That is, Fig. 9B shows that a first flow stream is collected in collection zone 54 of manifold 58, in fluid communication with side port 60, while a second flow stream, separated from the first flow stream accumulates in collection zone 55 fluidly connected to side port 59.

[0055] In any of the configurations described, the present invention 10 can also be used to facilitate chemical reaction in at least one of the opposing streams 14, 16 together with simultaneous heat transfer between two streams 14, 16 in countercurrent flow, such that one of the opposing streams provides energy to the other stream. An example of such a reaction is the endothermic syngas process for producing carbon monoxide and hydrogen from methane and water. In one embodiment, a feedstock mixture would be fed to one complementary set of half-checkerboard channels (e.g., 12, Fig. 2A), while a hot fluid – perhaps a waste-heat combustion stream – flows countercurrently through the other complementary set of half-checkerboard channels (e.g., 12B, Fig. 2) so as to provide heat from the syngas reaction. Another example of a chemical reaction which can be carried out in devices (e.g., heat exchangers) of the present disclosure is the exothermic Fischer-Tropsch process for producing hydrocarbons of varying chain length from a feed mixture of carbon monoxide and hydrogen. In this embodiment, the complementary stream would absorb heat from the reaction. That is, one

fluid stream (i.e., a reaction stream) would carry out the chemical reaction within the flow path (i.e., along the longitudinal axis of one set of the half-checkerboard) while the complementary set of half-checkerboard channels would contain a fluid that absorbs the heat from the reaction. Depending on the type of reaction being sought, porous catalyst material might be required to be placed in the channel that carries the reaction stream, as is the case in Fischer-Tropsch synthesis. Additionally, in an embodiment of the present invention, an endothermic reaction stream may be fed to one set of half-checkerboard channels while an exothermic reaction stream is fed through the other complementary set of half-checkerboard channels.

[0056] A heat exchanger 10 according to this disclosure can be manufactured to areal densities of greater than $400 \text{ m}^2/\text{m}^3$. Depending of the form applied, areal density can reach up to $2,000 \text{ m}^2/\text{m}^3$ and possibly higher. Such a heat exchanger exhibits superior performance over conventional shell-and-tube heat exchanger in terms of pressure drop. For the shell side of a conventional shell-and-tube heat exchanger especially, pressure drop increases rapidly as the channel size decreases. Table 1 provides data calculated for a hypothetical heat exchanger designed in accordance with an embodiment of the present invention: that is, for a hypothetical microchannel heat exchanger providing single-pass countercurrent flow and having a bundle of channels in which the channels are arranged to form the checkerboard pattern with opposing flows that are kept separate. Table 1 describes a hypothetical cases of a microchannel heater exchanger according to the present disclosure and a conventional shell-and-tube heat exchanger, both being of equal outer dimension and flow conditions. The microchannel countercurrent heat exchanger, longitudinally baffled at each row, serves as a baseline case for comparison with transversely baffled shell-and-tube heat exchangers of varying tube diameters (see Table 2 below). These cases exemplify heat recuperation with opposing streams of carbon dioxide – one stream hotter than the other and at different pressure, but both at the same

flow rate. The tube outside diameter of this base-case microchannel heat exchanger is 1.07 mm. The envelope is large enough to contain a bundle of 40,000 such tubes.

[0057] Table 2 compares the pressure drop of the longitudinally baffled microchannel heat exchanger of *fixed* tubing size (1-mm diameter) with the transversely baffled shell and tube heat exchange of *varying* tube sizes from 20 mm to as narrow as 1 mm in outside diameter. Because the outer dimension of the tube bundled remains fixed according to Table 1, the tube count for the shell-and-tube case decreases as the tube outside diameter increases. At about the 12-mm-OD tube size (approximately $\frac{1}{2}$ -inch), the shell-side pressure drop of the conventional heat exchanger is equal to the pressure drop at the “shell-side” of the hypothetical microchannel device presented in Table 1. While the pressure drop between the two exchangers may be equivalent, the areal density of the exchanger in accordance to the present disclosure and provided in Table 1, is over 5 times greater (compare $1,493 \text{ m}^2/\text{m}^3$ to $289 \text{ m}^2/\text{m}^3$). At the 1-mm size, the transversely baffled shell and tube heat exchanger (having 5 baffles) has a pressure drop that is 18 times greater than the exchanger described in Table 1 and in accordance with an embodiment of the present disclosure. (Note however, that the areal densities between the two different exchangers is substantially equivalent.) For a given shell dimension, the areal density increases as tube OD decreases. Thus as a general rule, heat exchanger 10 according to this disclosure operates with less pressure drop at areal densities of $400 \text{ m}^2/\text{m}^3$ or greater.

[0058] It is also the case that the heat duty capability of conventional shell-and-tube heat exchangers cannot match counter-current microchannel heat exchangers 10 according to this disclosure unless the areal density is greater than $400 \text{ m}^2/\text{m}^3$ (see Table 3). Looking at it another way, a microchannel heater exchanger 10 according to this disclosure can achieve a high degree of heat duty in a compact envelope without the high pressure drop that would result from a conventional shell-and-tube design. As can be seen in Table 3, the conventional shell-and-tube heat exchanger (with 5 baffles) does not achieve equivalent heat duty performance as the microchannel heat

exchanger unless the tubes are less than 4 mm in outside diameter, but at this size the shell-side pressure drop is much higher than that of the longitudinally baffled design. Therefore, conventional shell-and-tube design exchangers (i.e., including one or more transverse baffles) can not provide similar or equivalent heat duty performance while maintaining an acceptable pressure drop.

Table 1
Baseline specification:
Longitudinally baffled microchannel heat exchanger

Tube bundle OD	0.33	meters
Tube bundle length	1.5	meters
Tube OD	1.07	Millimeter
Tube count	40,000	
Areal density	1,493	m^2/m^3
Heat duty	Carbon dioxide (both sides)	
Flow rate	15	kg/s (both sides)
Heat duty	2,783	kW

Tube side	Inlet	200.0	C
		285.0	Bar
	Outlet	336.0	C
		284.8	Bar
Tube side pressure drop:		0.2	Bar
Shell side	Inlet	450.0	C
		115.0	Bar
	Outlet	292.1	C
		114.7	Bar
Shell side pressure drop:		0.3	Bar

Table 2

Comparative performance: Pressure drop
40,000-tube Baseline horizontally baffled microchannel
HX (A)
versus Transversely baffled shell-and-tube HX (B) of varying tube
size

HX B:			Shell side		Tube side	
Tube OD mm	Tube count	Areal density m^2/m^3	Press. drop, bar	Times baseline microHX	Press. drop, bar	Times Baseline microHX
1	41,660	1,500	5.38	17.93	0.57	2.85
2	10,420	750	2.36	7.87	0.27	1.35
3	4,630	500	1.46	4.87	0.18	0.90
4	2,610	376	1.04	3.47	0.13	0.65
5	1,670	301	0.80	2.67	0.11	0.55
6	1,160	251	0.65	2.17	0.10	0.50
7	860	217	0.55	1.83	0.08	0.40
8	660	190	0.47	1.57	0.08	0.40
9	520	168	0.41	1.37	0.07	0.35
10	417	150	0.37	1.23	0.07	0.35
11	344	136	0.33	1.10	0.06	0.30
12	289	125	0.30	1.00	0.06	0.30
13	246	115	0.27	0.90	0.06	0.30
14	213	107	0.25	0.83	0.06	0.30
15	185	100	0.23	0.77	0.05	0.25
16	163	94	0.22	0.73	0.05	0.25
17	144	88	0.20	0.67	0.05	0.25
18	129	84	0.19	0.63	0.05	0.25
19	115	79	0.18	0.60	0.05	0.25
20	104	75	0.17	0.57	0.05	0.25

A base line of under 1.00 (e.g., see above lines) denotes comparative underperformance by transversely baffled shell-and tube heat exchanger

Table 3
Comparative performance: Heat
exchange duty
40,000-tube Baseline longitudinally baffled
microchannel HX (A)
versus Transversely baffled shell-and-tube HX (B) of
varying tube size

HX B:				
Tube OD mm	Tube count	Areal density m^2/m^3	Heat duty, kW	Times baseline microHX
1	41660	1,500	2,787	1.00
2	10420	750	2,786	1.00
3	4630	500	2,766	0.99
4	2610	376	2,693	0.97
5	1670	301	2,569	0.92
6	1160	251	2,418	0.87
7	860	217	2,263	0.81
8	660	190	2,108	0.76
9	520	168	1,959	0.70
10	417	150	1,815	0.65
11	344	136	1,688	0.61
12	289	125	1,574	0.57
13	246	115	1,470	0.53
14	213	107	1,379	0.50
15	185	100	1,292	0.46
16	163	94	1,216	0.44
17	144	88	1,144	0.41
18	129	84	1,083	0.39
19	115	79	1,020	0.37
20	104	75	998	0.36

Area below the line denotes comparative under-performance by transversely baffled heat exchanger

[0059] EXAMPLE 1. A heat exchanger as shown in Figure 1 was fabricated according to the contiguous channel configuration, comprising an array of 25 x 25 square channels, each 0.6-mm inside height and width, occupying an outside dimension of 1-in by 1-in. The size and shape of the channels (see Fig. 2, 12A) for holding a first stream (14) are substantially the same along the longitudinal axis (z). The size and shape of the channels (12B) are altered as shown in Figs. 3B-3D. The heat exchanger was additively manufactured. In particular, Inconel 718 was used to form the channels (both 12A and 12B). The total length of the bundle was 6.57 inches. Total internal surface area for one of the two countercurrent streams is 0.1202 m². Overall areal density (surface area divided by overall volume) is thus 1,116 m²/m³. In a test with water flowing at rates of 0.38 to 1.08 gallons per minute (see Table 4), the power density ranged from 25.1 to 32.4 MW/m³.

Table 4

Heat duty: Tests with water

25x25 channels, 1"x1"x6.57" outer dimensions

Case	Stream	Flowrate [GPM]	Inlet [F]	Outlet [F]	Heat duty [kW]	Power density MW/m ³
A1	Hot Side	1.08	91.4	73.2	-2.9	
	Cold Side	1.08	60.8	79.1	2.88	26.8
B1	Hot Side	0.48	124.4	85.9	-2.71	
	Cold Side	0.48	64.4	102.7	2.7	25.1
C1	Hot Side	0.9	96.1	74.4	-2.86	
	Cold Side	0.9	60.1	81.8	2.86	26.6
D1	Hot Side	0.67	110.7	79.3	-3.09	
	Cold Side	0.67	60.3	91.6	3.08	28.6
E1	Hot Side	0.29	180.4	98	-3.5	
	Cold Side	0.29	62.4	144.1	3.47	32.4
F1	Hot Side	0.38	148.4	93.8	-3.04	
	Cold Side	0.38	66.7	120.9	3.02	28.1

[0060] **EXAMPLE 2.** A stainless steel microchannel heat exchanger constructed in accordance with the present disclosure, and having an areal density of 1,351 m²/m³ in a bundle volume of 65.7 cubic inches, weighing 8.5 lbs., was tested under the conditions described in Table 5. Power density for these cases is in the range of 10 to 11 MW/m³.

Table 5

Heat duty: Tests with carbon dioxide
32x20 channels, 1.04"x2.155"x29.43" outer dimensions

Case	Stream	Flowrate [GPM]	Inlet [F]	Outlet [F]	Heat duty [kW]	Power density MW/m ³
A2	Hot Side	3.45	175.6	97.0	-10.8	
	Cold Side	2.22	77.8	112.9	11.1	10.1
B2	Hot Side	3.37	178.9	97.3	-10.9	
	Cold Side	2.19	79.7	115.4	10.7	10.0
C2	Hot Side	6.87	167.4	101.5	-12.1	
	Cold Side	2.23	83.3	142.5	12.1	11.2

[0061] While the disclosure has been described in detail and with reference to specific embodiments thereof, it will be apparent to one skilled in the art that various changes and modifications can be made therein without departing from the spirit and scope of the embodiments. Thus, it is intended that the present disclosure cover the modifications and variations of this disclosure provided they come within the scope of the appended claims and their equivalents.

CLAIMS

What is claimed is:

1. A countercurrent flow single pass heat exchanger comprising:

a bundle of channels comprising a first plurality of channels and a second plurality of channels, individual channels of the first plurality being arranged with respect to individual channels of the second plurality to form a checkerboard pattern substantially through a transversal cross-section of the bundle; the individual channels of the first plurality of channels being in fluid communication with first flowstream ports and individual channels of the second plurality of channels being in fluid communication with second flowstream ports, wherein the first flowstream ports are distinct from and not in fluid communication with the second flowstream ports;

a first fluid receiving member; and

a second fluid receiving member, the first fluid receiving member, the second fluid receiving member and the bundle of channels being arranged such that the first fluid receiving member is positioned between the second fluid receiving member and an end of the bundle;

and wherein the second plurality of channels extends pass the end of the bundle and through the first fluid receiving member; the first plurality of channels extends through the bundle and is in fluid communication with a collection area of the first fluid receiving member, the collection area being fluidly connected to at least one of the first flowstream ports.

2. The heat exchanger of claim 1, wherein the areal density of the bundle of channels is greater than 400 m²/m³.

3. The heat exchanger of claim 1, wherein at least a portion of the channels within the bundle of channels include walls with increased surface roughness.
4. The heat exchanger of claim 1, wherein at least a portion of the channels within the bundle of channels include fins extending from channel walls.
5. The heat exchanger of claim 1, wherein at least a portion of the channels within the bundle of channels include porous media fixed therein.
6. The heat exchanger of claim 1, wherein at least a portion of the second plurality of channels within the collection area have a different cross-section size and/or shape than within the bundle.
7. The heat exchanger of claim 1, wherein a cross-sectional shape of individual channels of the first plurality of channels differs from a cross-sectional shape of individual channels of the second plurality of channels.
8. The heat exchanger of claim 1, wherein a cross-sectional area of individual channels of the first plurality of channels differs from a cross-sectional area of individual channels of the second plurality of channels.
9. The heat exchanger of claim 1, wherein the second plurality of channels comprises a plurality of elongate members spaced along a plurality of sheets to form rows of elongate members and the first plurality of channels comprises a plurality of voids, each of the voids being confined to form a channel by adjacent sheets within the plurality of sheets and by walls of two adjacent elongate members within rows of elongate members.
10. The heat exchanger of claim 1, wherein the collection area is formed within a chamber defined by walls forming the first fluid receiving member, and wherein axial flow within the first fluid receiving member of the first

plurality of channels is obstructed to force the first flowstream along diagonal pathways in fluid connection with the collection area.

11. The heat exchanger of claim 1, wherein the second fluid receiving member defines a cavity for the collection of fluid from the second plurality of channels, the cavity being in fluid communication with at least one of the second flowstream ports.

12. A method of manufacturing a bundle of channels for a heat exchanger, the method comprising:

additively manufacturing a first and second plurality of metal channels, wherein individual channels of the first plurality are arranged with respect to the individual channels of the second plurality to form a checkerboard pattern through a transversal cross-section of the bundle, the first and second plurality of channels being fluidly distinct, each of the channels of the second plurality of metal channels extending in length past an end of the first plurality of channels and at least one of size or shape of the transversal cross-sectional area of the individual channels of the second plurality changing along a longitudinal direction.

13. The method of manufacturing of claim 12, wherein the first and second plurality of metal channels comprise Inconel.

14. The method of manufacturing of claim 12, wherein the first and second plurality of metal channels comprise stainless steel.

15. The method of manufacturing of claim 12, wherein a wall thickness of the individual channels of the second plurality of channels increases along the longitudinal direction.

16. A method of heat transfer between a first fluid stream and a second fluid stream in a countercurrent single pass heat exchanger, the method comprising:

flowing the first fluid stream and the second fluid stream in a bundle of channels such that the first and second fluid streams flow countercurrently to each other to exchange heat within an interior region of the bundle along a longitudinal axis of the bundle in four directions with respect to an individual channel without mixing the first and second fluid streams, the four directions comprising above the individual channel, below the individual channel, and along at least a portion of each lateral side of the individual channel;

collecting the first fluid stream in a first fluid receiving member, the second fluid stream being confined within a plurality of channels extending through the first fluid receiving member to separate the first and second fluids; and

collecting the second fluid stream in a second fluid receiving member.

17. The method of heat transfer between the first and second fluid streams of claim 16 further comprising:

increasing flow turbulence of the first fluid stream such that a heat transfer coefficient of the first flow stream is modified to a value which is within one order of magnitude of a heat transfer coefficient value of the second fluid stream.

18. The method of claim 16, wherein a chemical reaction occurs in the first fluid stream and the second fluid stream absorbs energy therefrom.

19. The method of claim 16, wherein a chemical reaction occurs in the first fluid stream and the second fluid stream provides thermal energy to the first fluid stream.

20. A countercurrent flow single pass heat exchanger comprising:

a bundle of channels comprising a first plurality of channels and a second plurality of channels, individual channels of the first plurality of channels being in fluid communication with first flowstream ports and individual channels of the second plurality of channels being in fluid communication with second flowstream ports, the first flowstream ports being distinct from and not in fluid communication with the second flowstream ports; wherein the individual channels of the first plurality are arranged with respect to the individual channels of the second plurality to exchange heat within an interior region of the bundle along a longitudinal axis of the bundle in four directions with respect to each channel without mixing the first and second streams, the four directions comprising above a selected channel in the interior region, below the selected channel, and along at least a portion of each lateral side of the selected channel

a first fluid receiving member; and

a second fluid receiving member, the first fluid receiving member, the second fluid receiving member and the bundle of channels being arranged such that the first fluid receiving member is positioned between the second fluid receiving member and an end of the bundle;

and wherein the second plurality of channels extends pass the end of the bundle and through the first fluid receiving member; the first plurality of channels extends through the bundle and is in fluid communication with a collection area of the first fluid receiving member, the collection area being fluidly connected to at least one of the first flowstream ports.

21. A method of heat transfer between two fluids streaming in countercurrent flow, wherein:

a. the opposing streams pass through a bundle of channels such that they flow countercurrently to each other to exchange heat in

four directions, laterally on both sides, above and below, and without mixing of the opposing streams;

- b. at either end of the bundle (1) one of the opposing streams remains confined within channels that penetrate an open plenum area (6) such that the other opposing stream is free to flow into the plenum area (6) and between the confining channels of the first stream while the other opposing stream is free to flow into the plenum area (6) and between the confining channels of the first stream;
- c. at either end of the plenum area (6) the confined stream enters or exits through a cavity (7) that is distinct from the plenum itself;
- d. said plenum area (6) is positioned between the bundle (1) and the cavity (7) through which the confined stream flows;

22. The method as in claim 21 wherein the areal density of the channel bundle is greater than $400 \text{ m}^2/\text{m}^3$.

23. The method according to claim 21 whereby the heat transfer coefficient of at least one of the opposing streams is enhanced, such that the heat transfer coefficients of both streams are within one order of magnitude of each other.

24. The method according to claim 21 whereby chemical reaction occurs in at least one of the opposing streams together with simultaneous heat transfer between two streams in countercurrent flow, such that one of the opposing streams provides energy to the other stream.

25. A device composed of channels arranged for countercurrent flow, wherein:

fluids flow counter-currently in opposite directions through a bundle of channels (1) whereby the opposing streams of fluid are arranged in a checkerboard pattern, such that for any given

channel there exist alongside, in four directions, laterally on both sides, above and below, channels containing the opposite fluid;

at either end of the bundle (1), channels confine one of the opposing streams through the plenum area (6) and extend into a cavity (7) through which the stream enters or exits the device by ports that are in the cavity wall;

the confining channels that penetrate the open plenum area (6) may be altered in size or shape, or both size and shape, so as to ensure free space completely around the confining channels, such that the other opposing stream is free to flow into the plenum area (6) and between the confining channels of the first stream to or from ports that are in the plenum wall.



26. The device as in claim 25 wherein the areal density of the channel bundle is greater than $400 \text{ m}^2/\text{m}^3$.


27. The device as described in claim 25 wherein the heat transfer coefficient is enhanced by means of structural changes in the channel walls, leading to increased turbulence in the flowing stream.

28. The device as described in claim 25 wherein the cross-sectional shape of individual channels in a first set of half-checkerboard channels is a hollow polygon of no more than four sides, while the cross-sectional shape of the complementary half-checkerboard pattern takes the form of any shape and size including the voids created between the walls of the first set of channels.

29. The device as described in claim 25 wherein the checkerboard pattern is formed by alternating layers of sheets and rows of tubes, said tubes of which may be round, ovate or polygonal in cross section and separated laterally by void spaces, while sheets positioned above and below these rows separate them vertically, such that alternating layers of tubes are staggered.

30. The device as described in claim 25 wherein the manifold for either of the streams at one or both ends is formed by means of obstructing axial flow of a first set of complementary channels in half-checkerboard pattern and redirecting it in the transverse direction via channels that pass diagonally between the channels of the second set of complementary channels in half-checkerboard pattern, such that flow from the first set converges to side ports alongside the ends of the tube bundle.









Fig. 3B





Fig. 3D








Fig. 3E







Fig. 5






Fig. 7

