Aug. 8, 1972 E. W. STONE 3,682,596

BODY FLUID COLLECTOR AND SEPARATOR HAVING IMPROVED FLOW RATE

Filed July 31, 1970 3 Sheets-Sheet 1




FIG. 2




FIG. 1

INVENTOR
ELLERY W. STONE
BY Stowell & Stowell
ATTORNEYS

BODY FLUID COLLECTOR AND SEPARATOR HAVING IMPROVED FLOW RATE

Filed July 31, 1970 3 Sheets-Sheet 2

FIG. 3




FIG. 4





FIG. 5



INVENTOR
ELLERY W. STONE

BY Stowell & Stowell


ATTORNEYS

Aug. 8, 1972 E. W. STONE 3,682,596

BODY FLUID COLLECTOR AND SEPARATOR HAVING IMPROVED FLOW RATE

Filed July 31, 1970 3 Sheets-Sheet 3

Fig 6.



INVENTOR
ELLERY W. STONE

BY Stowell & Stowell

ATTORNEYS

United States Patent Office 3,682,596 Patented Aug. 8, 1972

3,682,596

BODY FLUID COLLECTOR AND SEPARATOR HAVING IMPROVED FLOW RATE

Ellery W. Stone, Cohasset, Mass., assignor to Schering Corporation, Bloomfield, N.J.

Continuation-in-part of application Ser. No. 677,196, Oct. 23, 1967. This application July 31, 1970, Ser. No. 60,044

Int. Cl. B01d *29/00*; G01n *33/16*

U.S. Cl. 23—253 R 8 Claims

ABSTRACT OF THE DISCLOSURE

Diagnostic body fluid collector and analytical sample separator including an evacuated body fluid collecting tube and an evacuated analytical sample cup. The collecting tube and the sample cup are physically separated from each other by one or more selectively permeable barriers through which only a portion of the collected fluid will pass. The assembly also includes a hollow conduit for directing body fluids into the body fluid collecting tube.

This application is a continuation-in-part of my application Ser. No. 677,196, filed Oct. 23, 1967 and now U.S. Pat. No. 3,539,300, issued Nov. 10, 1970.

It is a principal object of the present invention to overcome a major drawback of existing automated or semi-automated tehniques for chemical, microbiological, hematological or other analyses of blood or other body fluids, all of which depend upon extensive and time-consuming manipulation of the body fluid for the purpose of separating it into the analytical sample or samples prior to presentation to an automated analytical machine or a skilled analyst. It is a further object of this invention to minimize the chances of error by providing a means for positive identification of the analytical sample with the patient from whom the body fluid was withdrawn.

To achieve the objects specified above and thereby relieve the shortage of skilled physicians and allied health personnel it is a further object of the present invention to provide a device for collecting a body fluid and automatically producing an analytical sample therefrom, which sample is formed without first removing the collected body fluid from the collector device and in general without manipulation by the collecting physician or allied health worker. A particularly useful application of the present invention is as a disposable device for collecting a portion of blood or other body fluid and automatically producing a sample of serum, plasma, protein free filtrate, or other fraction by automatic processing of the collected body fluid as it is being transported from the patient to the laboratory. Such automatic processing can include filtration, fluid flow through a selectively permeable barrier or barriers, and/or reaction with selected chemical reagents.

A second particularly useful application of the present invention is as a disposable device for collecting a portion of blood or other body fluid and automatically producing a concentrated sample of microorganisms for microbiological analysis and a separation of microorganisms of different size such as bacteria, rickettsia, and viruses by automatic filtration of the collected body fluid through one or more selectively permeable membranes or porous separators for individual analysis.

It is a further object of the present invention to reduce the dangers of laboratory induced infection when dealing with potentially pathogenic body fluids by providing a self contained system for body fluid collection and analytical sample separation.

It is a further object of the present invention to provide a body fluid collector and analytical sample separation means which is extremely simple in construction, automatic in operation and relatively inexpensive to manufacture whereby the device may be discarded after a single use.

Another object of the present invention is to provide a releasable sample cup designed to be marked with a pencil or other writing instrument or label to directly identify the body fluid and the analytical sample with the patient at the time the body fluid is collected from the patient and to carry such positive identification directly to automatic analytical instrumentation where so applied, by being designed to fit the turntable or other sample container holder of such automatic analytical instrumentation.

These and other objects and advantages are provided by a body fluid collector and analytical sample separator device including an evacuated body fluid collecting tube, an especially designed evacuated analytical sample cup releasably secured to one end of the collecting tube, one or more sample separating, selectively permeable barriers forming a passage between the tube and cup, and means forming a conduit for directing a body fluid into the other end of the body fluid collecting tube.

The invention will be more particularly described in reference to the accompanying drawings wherein:

FIG. 1 is an assembled view of one version of the body fluid collector and analytical sample separator device of the invention;

FIG. 2 is an enlarged partial fragmentary exploded view of the structure shown in FIG. 1;

FIG. 3 is an enlarged view substantially on line 3—3 of FIG. 1;

FIG. 4 is a section on line 4—4 of FIG. 3;

FIG. 5 is an enlarged fragmentary sectional view of a modified form of closure means for a device of the type illustrated in FIG. 1; and

FIG. 6 is an enlarged partial fragmentary exploded view of another version of the body fluid collector and analytical sample separator provided with a series of selectively permeable barriers in such a manner that several different analytical samples can be obtained.

Referring to the drawing **10** generally designates an improved diagnostic body fluid collector and sample separator. Beginning at the rear end of the device it includes an analytical sample cup **12**, a porous support **16**, a selectively permeable barrier disc **14**, a collector tube **18**, and a resilient stopper **20**. This unit, when in use, is assembled with a barrel member **22**, a double ended needle **24**, and a needle holder **26**. Each of the foregoing elements will be more particularly described hereinafter.

Referring particularly to FIG. 3 of the drawings, the sample collecting tube **18** consists of a generally cylindrical member having an internal flange **30** adjacent one of its ends. The tube **18** is preferably formed of a transparent or translucent plastic material and in the case of a blood collecting device the tube **18** would be approximately 4" long and have an internal diameter of about ¾". The upper or front end **32** of the tube **18** receives a conventional resilent rubber stopper **20** of the type adapted to be punctured by the inner sharpened end **34** of the double ended hollow needle **24**.

The analytical sample receiving cup **12** is also cast or injection molded of plastic and its upper end, as viewed in FIG. 3, is provided with a flange **38**. A portion **39** of the outer surface of the analytical sample cup **12** is provided with a roughened surface or other suitable surface for marking with a pencil or other writing instrument, or for application of a label to permit identification of the sample with the patient at the time the body fluid is collected. This identifying mark or marking can include a magnetic label or other designation capable of being interpreted by a computer or computer input device. The

external diameter of the upper end of the sample cup **12** is such that it is snugly receivable within the bore **40** in the collector tube **18** and the upper surface of the flange **38** is adapted to abut against the lower peripheral edge of the tube. The atmosphere inside the tube **18** and the cup **12** is maintained, prior to use, at an absolute pressure of from about 0.5 to about 5 inches of mercury. The lower surface of the flange **38** and the outer diameter of the sample cup **12** below the flange are designed so that the cup can be inserted into a hole in a turntable or other sample container holder of automated analytical equipment, and will be retained by the flange **38**. This portion of the assembly also includes, as hereinbefore described, a selectively permeable barrier disc **14** and a porous support disc **16**. The upper surface, as viewed in FIG. 3, of the selectively permeable barrier disc **14** shoulders against the internal flange **30** and the peripheral edge of the porous support **16** also as viewed in FIG. 3, is fitted snugly against the bore **40** in the collector tube **18** whereby the porous support and the selectively permeable barrier disc are immovably maintained within the lower portion of the bore **40** in the sample receiving tube **18**. The lower peripheral surface of the porous support disc **16** is seated against the upper edge of the cup **12**.

The barrel member **22**, as shown in FIGS. 1 and 2 of the drawing, is of generally conventional design and is of the type adapted to be used with vacuum blood sampling tubes. The lower end of the barrel member **22** is closed except for a threaded bore which receives the threads **44** on the needle retaining member **26**. When the threads **44** of the member **26** are screwed into the end of the barrel portion **22** the double ended needle projects outwardly and inwardly generally as illustrated in FIG. 2 of the drawings. The internal diameter of the barrel member **22** is such that the outer cylindrical surface of the resilient rubber stopper member **20** snugly engages the inner surface, and once the barrel portion **22** is positioned such that the lower extended end **44** of the needle **24** is within a patient's vein, telescopic movement of the sample collector tube **18** inwardly of the barrel portion **22** such that the inner portion **34** of the needle **24** pierces the resilient stopper **20**, as illustrated in FIG. 3 of the drawings, blood is drawn from the patient into the sample collecting tube **18** by a vacuum produced within the tube during its manufacture and/or assembly.

After the collecting tube **18** is filled with the desired quantity of blood from the patient, the tube may be removed from the barrel portion **22** and placed in a storage rack with the sample cup **12** pointing downwardly. At this stage the stopper **20** is removed from the end **32** of the tube **18** or is vented so that atmospheric pressure will assist in forcing a part of the collected blood through the filter or other selectively permeable barrier. When the device is used for microbiological applications the original stopper is replaced with a cotton plug or other protective closure to prevent contamination of the body fluid with additional microorganisms. During this process a portion of the blood such as serum, plasma or other analytical sample, will be drawn through the selectively permeable barrier **14** and the porous support **16** into the sample cup.

Atfer the analytical sample has collected in the sample cup **12**, the sample cup **12** may be removed from the tube **18** at the telescopic connection between these two elements.

The type of selectively permeable barrier, or filter, that is employed in the collector is determined by the nature of the fluid being filtered and the type of filtrate desired. In general, there are two classes of filters which can be used advantageously in the diagnostic collection and separation of blood. The two general classes comprise:

(1) microporous membrane filters and,

(2) thin skin diffusion membrane filters.

The first group, microporous membrane filters, are well known in commerce and have been used in many types of analytical chemistry procedures and for clarifying liquids, purifying air supplies, and pasteurizing beer by the removal of yeast particles therefrom. Although a variety of polymers can be used to fabricate such filters, the majority of the commercial microporous membranes are made of cellulose derivatives, especially cellulose diacetate and triacetate. A wide range of pore size is commercially available and the pore size range of microporous membrane filters are generally from about 0.22 to about 10 microns.

In addition to the polymer microporous membrane filters discussed above, microporous metal filters, sintered ceramic and sintered glass filters may also be employed in the device of the invention.

In order to exclude blood cells from the serum or other sample, a microporous membrane filter must have a pore size small enough to retain cells approximately 5 to 8μ in diameter and yet large enough to permit relatively rapid flow of the liquid analytical sample. Where blood plasma is to comprise the filtrate, a flow time for 3 mls. of sample in the neighborhood of about 20 minutes has been obtained with a microporous membrane filter disc of approximately ¾" diameter.

In the alternative version of the device to be used to prepare samples for microbiological analysis, several microporous membrane filters are arranged in series as shown in FIG. 6 so that large malignant cells are retained by the first filter **61**, erythrocytes, leukocytes and platelets are retained by the second filter **62**, and bacteria are retained by the third filter **63**. If desired, rickettsia would be retained by a fourth filter and viruses by a fifth filter. A greater or lesser number of filters are used as appropriate for the application. The filters are held by flanged plastic cylinders **65** releasably secured to the body fluid connecting tube **18**, the sample cup **12**, and to each other such that each forms a sample chamber when removed from the assembly. These chambers are designed in such a way that the sample of microorganisms can be transferred directly to the appropriate culture medium for growth and analysis.

The thin skin diffusion membrane filter differs from microporus varieties in that the membrane filter has a thin, unbroken skin on one surface and graded porosity through the body of the filter material. Such membranes have been used for the reverse osmosis processes used for desalination of sea water and a number of methods of making such membranes have been described in the technical literature.

The thin skin diffusion membrane filters have advantages when used with the structure of the present invention as there are no pores on the surface of the skin which could become clogged by red cells or protein molecules. Furthermore thin skin diffusion membrane filters can be made with selective permeability based on the molecular weight and/or other physicochemical properties of the components of the body fluid sample. The thin skin diffusion membrane used in the device is appropriately selected to be permeable to the component or components of the body fluid which are sought in the analysis of the sample. For example, a thin skin diffusion membrane permeable to species with molecular weight less than 200,000 is used to separate fibrinogen and all other higher molecular weight constituents from blood for the preparation of sermum using the present device. In cases where it is desired to obtain several analytical samples each containing different sets of constituents then the form of the device illustrated in FIG. 6 is used with appropriately selected thin skin diffusion membrane filters. Another version of the device incorporates a series of selectively permeable barriers some of which are microporous membrane filters and some of which are thin skin diffusion membrane filters. For example, a device designed to separate malignant cells, normal blood cells, and a protein free filtrate from blood, includes two selectively permeable barriers in series. The first such barrier is a microporous membrane filter with pore size of approximately 10 microns which retains malignant

cells and transports other constituents. The second barrier is a thin skin diffusion membrane filter permeable to those constituents of blood with molecular weight less than approximately 10,000, which retains normal blood cells and proteins and transports electrolytes, glucose, urea, and other low molecular weight constituents.

It will also be appreciated by those skilled in the art that where higher flow rates are desired the disc shape filter **14** may be replaced by a dished, conical or cup shaped filter which would be maintained within the structure by, for example, the flange means illustrated in FIG. 3.

Referring for example to FIG. 5 of the drawings, a modified form of stopper is illustrated., In FIG. 5 the stopper **50**, which may be constructed of plastic, synthetic or natural rubber or the like, is provided with an opening **52** therethrough which opening is adapted to snugly receive a resilient elastomeric closure member **54**. The closure member **54** has a thin cross web **56** through which the sharp end of the needle **24** may be readily pressed and, once the tube **18** is filled with blood, the entire resilient closure member **54** may then be removed as shown in broken lines at A, to vent the interior of the tube **18** to atmospheric pressure. It will also be noted that in the illustrated form of the stopper **50** the resilient closure member **54** is positioned off center. The needle **24** in the needle holding barrel member **22** would also be positioned off center and can thereby be inserted at an acute angle to, for example, the arm of the patient. A protrusion **57** on the rim of the stopper **50** opposite to the closure member **54** facilitates the alignment of the off center needle **24** with the off center closure member **54** by sliding in a groove provided in the barrel member **22**.

From the foregoing description of a preferred and of a modified form of the body fluid collector and separator of the present invention, it will be seen that the objects and advantages hereinbefore set forth are fully accomplished. It will be appreciated that body fluid, the permeable barrier and the analytical sample may be selected for clinical chemical analysis; microbiological analysis; hematological analysis, or cytological analysis.

I claim:

1. A body fluid collector and analytical sample separator device including an evacuated body fluid collecting tube having a first end and an opposing second end, means sealingly closing said first end, an evacuated analytical sample cup having a closed end and an opposing end, said sample cup being releasably secured at it opposing end to the second end of the collecting tube, a sample separating, permeable barrier closing off the second end of the collecting tube and forming a strain flow passage between the interiors of the tube and the cup when the cup is secured to the tube, and means for directing a body fluid into the interior of the body fluid collecting tube through the first end thereof.

2. The invention defined in claim **1** wherein said sample-separating, permeable barrier comprises a microporous membrane.

3. The invention defined in claim **1** wherein said sample separating, permeable barrier comprises a thin skin diffusion membrane.

4. The invention defined in claim **1** wherein a series of said barriers are provided and are spaced apart lengthwise of the tube adjacent the second end thereof, said series of said barriers being comprised of both microporous membranes and thin skin diffusion membranes.

5. The invention defined in claim **1** wherein said second end of the tube is provided with an internal flange and said sample cup is telescopically insertable at its open end in said second end of the tube and the separating permeable barrier is maintained between said internal flange and the end edge of the inserted end of the sample cup.

6. The invention defined in claim **1** including a series of barriers spaced apart lengthwise of the tube and the cup and forming the passage between the tube and the cup.

7. The invention defined in claim **6** wherein said permeable barriers are releasably secured to the tube, the sample cup, and each other such that several analytical samples are separated from the collected body fluid.

8. A body fluid collector and analytical sample separator device including an evacuated body fluid collector tube having a first end and an opposing second end, a resilient stopper sealing fitted on and closing off the first end of the tube, an evacuated analytical sample cup having a closed end and an opposing end, said sample cup being releasably secured at its opposing end to the second end of the collecting tube, and a sample separating permeable barrier closing off the second end of the tube and forming a strain flow separation passage between the interior of the tube and the interior of the cup when the cup is secured to the tube, said sealing stopper being formed so as to be pierced by a hollow needle for directing a body fluid into the body fluid collecting tube through the first end thereof.

References Cited

UNITED STATES PATENTS

3,200,813	8/1965	Christakis	128—2 F
3,300,051	1/1967	Mitchell	210—339
3,448,041	6/1969	Swank	210—335 X

MORRIS O. WOLK, Primary Examiner

R. M. REESE, Assistant Examiner

U.S. Cl. X.R.

23—230 B, 259; 128—2; 210—314, 335