



(11) **EP 2 455 230 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
14.05.2014 Bulletin 2014/20

(51) Int Cl.:
B32B 29/02 ^(2006.01) **B44C 5/04** ^(2006.01)
E04F 15/10 ^(2006.01) **B44F 9/02** ^(2006.01)
B32B 38/06 ^(2006.01) **B32B 3/30** ^(2006.01)
B44F 5/00 ^(2006.01) **E04F 15/02** ^(2006.01)
B32B 38/00 ^(2006.01)

(21) Application number: **12155940.5**

(22) Date of filing: **28.01.2004**

(54) **Flooring system having sub-panels with complementary edge patterns and non-coplanar upper surfaces**

Fussbodensystem mit Unterplatten mit ergänzenden Kantenmustern und Oberflächen unterschiedlicher Höhe

Système de plancher doté de sous-panneaux dotés de motifs de bord complémentaires et de surfaces non-coplanaires

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

(30) Priority: **28.01.2003 US 352248**
27.02.2003 US 374751
21.10.2003 US 689510

(43) Date of publication of application:
23.05.2012 Bulletin 2012/21

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
04705871.4 / 1 590 187

(73) Proprietor: **Faus Group**
47600 Ganadia (ES)

(72) Inventors:
• **Sabater Vicente**
46006 Valencia (ES)
• **Garcia Eugenio Cruz**
16001 Cuenca (ES)

(74) Representative: **Carpintero Lopez, Francisco et al**
Herrero & Asociados, S.L.
Alcalá 35
28014 Madrid (ES)

(56) References cited:
WO-A1-01/48333 DE-U1- 20 008 837
US-A- 2 108 226 US-A- 4 131 705
US-A- 5 858 160 US-A1- 2002 014 047
US-A1- 2002 100 231 US-B1- 6 401 415

EP 2 455 230 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

DescriptionBACKGROUND OF THE INVENTIONField of the Invention

[0001] The present invention relates to a flooring system comprising at least two flooring panels, each flooring panel comprising a plurality of side surfaces and at least one partial sub-panel.

Discussion of the Related Art

[0002] Because of their look and feel, traditional building and finishing flooring materials such as fine woods, slate, granite, stones, brick, and concrete are generally preferred by consumers. However, such traditional building and finishing flooring materials tend to be expensive to produce and install. For example, while a solid wood floor has a highly valued luxurious appearance, the materials and labor required to install such floors can be prohibitively expensive.

[0003] Many alternatives to traditional building and finishing flooring materials are available, including laminates such as high-pressure laminates (HPL), direct-pressure laminates (DPL), and continuous-pressure laminates (CPL). However, such alternatives typically do not possess the realistic look and texture of the traditional building and finishing flooring materials. For example, most alternatives having an outer surface with a wood motif look fake and can readily be identified as something other than authentic wood. Furthermore, while high quality HPL, DPL, or CPL boards may visually look like wood, their textures readily reveal that they are not.

[0004] One problem with most alternatives to traditional building and finishing flooring materials is that their surface textures do not match their decorative motifs. For example, visual depictions of wood knots in alternative flooring materials are not matched with surface textures characteristic of the wood knots. Accordingly, the attractiveness of these alternative materials is significantly reduced.

[0005] One approach used to match the surface texture of alternative flooring materials to their decorative motifs includes a technique known as chemical embossing. In chemical embossing, the surface texture of the alternative material is developed by chemically reacting an ink that forms the decorative motif with an agent added to a subsurface layer. While somewhat successful, the resulting surface texture tends to lack the textual sharpness and three-dimensional characteristics of traditional materials.

[0006] As an alternative to the traditional building and finishing flooring materials laminated materials may be mechanically embossed to produce a surface texture. See, for example U. S. Patent Application 09/903,807 and U. S. Patent No. 6,401,415,. Such methods produce embossed-in-registration laminated materials having

decorative motifs and matching high-quality three-dimensional textures. Embossed-in-registration laminated materials require accurate registration of mechanical embossment and the decorative motif. An advantage of embossed-in-registration laminated materials is that they can realistically reproduce the look and feel of traditional products.

[0007] No matter what type of flooring system is used, the flooring system must be easily moved to a work site while being easy and quick to install. To this end, assembly and locking mechanisms may be incorporated within flooring systems to facilitate onsite installation. One type of assembly and locking mechanism is the tongue and groove system used for connecting panels. It is understood that such tongue and groove systems are disclosed in Cherry, U. S. Pat. No. 2,057,135, and in Urbain, U. S. Pat. No. 2,046,593. For example, Figure 1 can be interpreted to illustrate a tongue and groove system 11 that uses clips 12 to secure panels together.

[0008] Another type of assembly and locking mechanism is understood to be disclosed in Chevaux, U. S. Pat. No. 3,946,529 where a flooring system 13 appears to be connected using a tongue and groove system arranged underneath the flooring, reference Figure 2.

[0009] Still another assembly and locking mechanism is taught in Kajiwara, U. S. Pat. No. 5,295,341. There, it is understood that laminated boards are provided with a snap-together system such as a groove-tongue joint. As a result the laminated boards can be assembled without glue. Referring to Figure 3, the laminated boards are provided with a locking means in the form of a groove connector 16, and a tongue connector 18. The groove connector 16 has forwardly protruding grooves 20, while the tongue 18 is provided with a pair of forwardly diverging sidewalls 22 and 24 that are separated by an elongated groove 26. The sidewalls include rear locking surfaces 28 and 36. The sidewalls can be compressed together to enable locking.

[0010] Another type of assembly and locking mechanism is the snap-together joint suggested in Martensson, U. S. Pat. No. 6,101,778. As shown in Figure 4, it is understood that laminated boards are provided with a locking means comprised of a groove 6 and a tongue 7 that form a tongue-groove assembly. The groove 6 and tongue 7 may be made of water tight material and snapped together with a portion 9 fitting in a slot 4.

[0011] While the aforementioned assembly and locking mechanisms have proven useful, they have not been used with embossed-in-registration laminate systems in which embossed-in-registration decorative motifs or graphics align across joints between the individual embossed-in-registration laminates. This significantly detracts from the visual and textural impression of systems comprised of embossed-in-registration laminate boards. Therefore, a new embossed-in-registration laminate system in which the visual and textural patterns cross joints while retaining the embossed-in-registration aspects would be beneficial. Even more beneficial would be an

embossed-in-registration laminate system comprised of interlocking embossed-in-registration laminate boards in which the visual and textural patterns cross joints while retaining embossed-in-registration aspects.

[0012] Further, the aforementioned flooring systems have a relatively low ability to resist wear. While not wishing to be bound by any particular theory, it is hypothesized that premature aging (wear) begins at or near the perimeter edges and/or along tongue and groove lines. The aforementioned flooring systems have a substantially even (level) surface texture such that the center and perimeter of each panel contact users (e. g. , pedestrians) an equal amount. The perimeter of each panel, however, is substantially weaker than the center of the panel and therefore deteriorates first.

[0013] Accordingly, there is a need for workable alternative building or finishing materials where the alternatives have the realistic look and feel of traditional products and have an increased capacity to resist premature wear.

[0014] The US patent US-4.131.705 refers to a structural laminate having a groove impressed on its surface useful as an external siding.

[0015] The US patent application US-2002/100231 describes a decorated floor panel having a core with a top surface and an opposite bottom surface.

[0016] The US patent application US-2002/014047 A refers to a flooring system having a plurality of flooring planks.

SUMMARY OF THE INVENTION

[0017] The present invention is defined in the attached claim 1.

[0018] More in detail, the invention refers to a flooring system, comprising:

at least two flooring panels,
each flooring panel comprising:

a plurality of side surfaces;
a first upper surface adjacent at least a portion of the plurality of side surfaces;
a second upper surface adjacent at least a portion of the plurality of side surfaces, wherein the first upper surface is lower than the second upper surface; and
at least one partial sub-panel, wherein neighboring partial sub-panels of adjacent flooring panels are complementary such that at least one of at least one decorative motif and at least one embossed surface texture is substantially continuous across at least a portion of a neighboring partial sub-panel.

[0019] In addition, each flooring panel comprises at least three subpanels, wherein at least one of said subpanels is a unitary sub-panel and wherein at least two of said sub-panels are partial sub-panels.

[0020] At least two neighboring partial subpanels of respective flooring panels are complementary to each other such that they provide a substantially complete decorative motif and/or surface texture and appear as a substantially continuous, unitary sub-panel, and wherein said first upper surfaces beveled.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

[0022] In the drawings:

Figure 1 illustrates a related art assembly and locking mechanism;

Figure 2 illustrates another related art assembly and locking mechanism;

Figure 3 illustrates yet another related art assembly and locking mechanism;

Figure 4 illustrates still another related art assembly and locking mechanism;

Figure 5 illustrates a perspective view of components in an embossed-in-registration flooring plank;

Figure 6 illustrates a press machine capable of fabricating embossed-in-registration flooring planks;

Figure 7 illustrates an embossed-in-registration flooring plank;

Figure 8 illustrates a top view of a system of embossed-in-registration flooring planks;

Figure 9 illustrates a cross-sectional view along line 9-9 shown in Figure 8;

Figure 10 illustrates a top view of a system of embossed-in-registration flooring planks;

Figure 11 illustrates a cross-sectional view along line 11-11 shown in Figure 10;

Figures 12A and 12B illustrate schematic views including a perimeter surface portion of a flooring plank;

Figures 13A and 13B illustrate a flooring system according to the present invention;

Figures 14A-14C illustrate an exemplary plank of a

flooring system according to the present invention and

Figures 15A-15D illustrate an exemplary method of forming patterns on a flooring plank in accordance with the principles of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0023] Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

[0024] Figure 5 generally illustrates components of a flooring plank according to the principles of the present invention.

[0025] Referring to Figure 5, an embossed-in-registration flooring system may, for example, include at least one flooring plank. Each flooring plank may include a board substrate 40 made out of a substrate material (e.g., a medium or high density fiberboard, chipboard), at least one base sheet 48 (e.g., a kraft paper sheet) impregnated with predetermined resins and arranged over and/or under the board substrate 40, a decorative paper sheet 44 about 0.15 mm thick and impregnated with a polymerizable resin (e.g., phenols such as melamine) arranged over the board substrate, and at least one protective overlay sheet 46 arranged over the decorative paper sheet 44. Each protective overlay sheet 46 may be formed from a highly resistant paper impregnated with a melamine solution containing e.g. corundum (Al_2O_3), silica.

[0026] Different papers may be arranged between the decorative paper sheet 44 and the board substrate 40. The at least one protective overlay sheet 46 and the base sheet 48 may be impregnated with a resin. The resin impregnating the at least one protective overlay sheet 46 and the base sheet 48 may be different from the melamine resin used to impregnate the decorative paper sheet 44.

[0027] Flooring planks within a flooring system may be fabricated from substantially the same paper, resin. For example, flooring planks within a flooring system may be fabricated using paper made from substantially the same paper fibers (having, for example, substantially the same ash content, color, and orientation) on the same on the same paper making machine.

[0028] Further, flooring planks within a flooring system may be fabricated using paper originating from a single, contiguous section on the manufacturing spool. All of the aforementioned paper use restrictions that may be employed in fabricating flooring planks of a flooring system ensure that impregnated papers will always have substantially the same final dimensions after they are pressed and cured. The warehousing of paper used to fabricate flooring planks within a flooring system may be controlled such that the time, temperature, and humidity in which the paper is stored is maintained to facilitate consistent flooring plank dimensions. Flooring

planks within a flooring system may be fabricated using cellulose paste made from the same manufacturer. Flooring planks within a flooring system may be fabricated using resins made from the same manufacturer. The resins may contain powder originating from substantially the same source, have substantially the same chemical and physical qualities, and be mixed in the same reactor. Further, flooring planks within a flooring system may be fabricated using resins have a substantially constant solids content.

[0029] All of the aforementioned resin use restrictions that may be employed in fabricating the flooring planks ensure that impregnated papers will always have substantially the same final dimensions after they are pressed and cured. Each of the flooring planks within a flooring system may be fabricated using substantially the same impregnation process. For example, when dipping the various sheets of paper into melamine resin, the paper should experience a constant, uniform melamine load. Further, a band tension and oscillation of the impregnation machine should be precisely controlled as they influence the degree to which the various paper sheets are impregnated with the resin.

[0030] The aforementioned sheets and substrates may be fabricated into an embossed-in-registration flooring system including a plurality of interlocking flooring planks. To produce such a flooring system, a press machine, such as a press machine shown in Figure 6, may be used to mechanically emboss each flooring plank in registration with a decorative motif arranged on the decorative paper sheet 44.

[0031] Referring to Figure 6, the press machine may, for example, include a base 42 a top press 54, and an upper press plate 56. The upper press plate may include an embossing pattern (e.g., a three-dimensionally textured surface). Accordingly, the embossing pattern may, for example, include elevated ridges, dots, depressions, of any design capable of being aligned with a decorative motif formed on the decorative paper sheet 44.

[0032] The impregnated decorative paper sheet 44 arranged on the board substrate 40 must be accurately positioned relative to the embossing pattern of the upper press plate to enable an embossed-in-registration flooring plank. Alignment between the embossing pattern of the press plate and the decorative motif must be ensured when the press is in a locked position and the board is under pressure. The degree of control required may vary depending on the type of decorative motif used. For example, alignment of a wood grain embossed-in-registration motif across adjacent embossed-in-registration flooring planks requires a higher degree of alignment than alignment of a wood grain embossed-in-registration motif that is not aligned with adjacent flooring planks.

[0033] Alignment between the decorative motif on the decorative paper sheet 44 and the embossing pattern on the upper press plate 56 may be achieved by removing about 2 to 3 millimeters of material around the perimeter of the board substrate 40 in a milling process thereby

yielding several reference planes (e.g., board edges) and a board substrate having tightly controlled dimensions. Next, an impregnated decorative paper sheet 44 having exterior dimensions about 8 or 10 mm smaller than the board substrate 40 is arranged on the board substrate 40. The impregnated decorative paper sheet 44 may be arranged on the board substrate 40 using the board edges as alignment means. Alignment marks may be arranged on the board substrate 40 and be alignable with alignment marks provided on the decorative paper sheet 44.

[0034] The decorative paper sheet 44 may be attached to the board substrate 40 via static electricity. After they are attached, the decorative paper sheet 44 and the board substrate 40 are arranged on a carriage feeding into the press machine. The static electricity may substantially prevent the decorative paper sheet 44 from being accidentally displaced as the board substrate 40 is moved with the carriage. The carriage may be stopped just before it enters into the press machine such that the decorative paper sheet 44 may be precisely arranged over the board substrate 40 using, for example, tweezers (not shown). The tweezers may be used to precisely arrange the decorative paper sheet 44 over the board substrate 40 arranged on the lower press plate. The decorative paper sheet 44, the at least one protective overlay sheet 46, and the optional base sheet 48 may be arranged over the board substrate 40 prior to being arranged within the press machine. After the decorative paper sheet 44 is arranged over the board substrate 40, the carriage may be moved out of the press machine. Next, an alignment system substantially aligns the decorative paper sheet 44/board substrate 40 system with the embossing pattern in the upper press plate 56.

[0035] The alignment system may use the board edges to substantially align the decorative motif 44 with the embossing pattern on the upper press plate 56. The press machine may be operated after the alignment is complete.

[0036] After the components illustrated in Figure 5 are arranged within the press machine and aligned with the embossing pattern, the various sheets and substrate may be pressed and cured for predetermined amount of time until the resins set, yielding an extremely hard and wear resistant flooring plank. For example, after being inserted into the press machine and aligned with the embossing pattern, the board substrate 40, decorative paper sheet 44, protective overlay sheet 46, and optional base sheet 48 may be heated at a temperature of about 160-220 °C and pressed together under a pressure of about 20-40 Kg/cm² for about 20 to 60 seconds. Accordingly, the top press 54 presses the embossing pattern of the upper press plate 56 into the decorative paper sheet 44 and board substrate 40 structure. The combination of the applied heat and pressure fuses the decorative paper sheet 44 and the board substrate 40 together. The alignment system ensures that the decorative paper sheet 44 is substantially aligned with the embossing pattern in the

upper press plate 56. Accordingly, melamine resin within the various sheets may be cured and an embossed-in-registration plank may be produced.

[0037] Porosity within the fused piece may be minimized by slowly curing the resins (e.g., the melamine). Accordingly, as the operating temperature is reduced, the time during which the various sheets within the press machine are pressed is increased. As the press plate 56 is heated to about 160-220 °C the embossing pattern included within the press plate may expand. Accordingly, the embossing pattern on the press plate 56 may be provided so as to compensate for the expansion of the pattern.

[0038] Therefore, the dimensions of the embossing pattern are provided such that they substantially correspond to the design of the decorative motif when the resins within the components of Figure 5 are cured.

[0039] A mechanically embossed surface texture may be imparted to an individual flooring plank having a decorative motif. The mechanically embossed surface texture may be provided in registration with the decorative motif.

[0040] Accordingly, an embossed-in-registration flooring plank may be fabricated. A plurality of embossed-in-registration flooring planks may be joined together to form an embossed-in-registration flooring system. At least a portion of embossed-in-registration patterns of adjacent flooring planks may be substantially aligned with each other to form substantially contiguous embossed-in-registration patterns across adjacent flooring planks within the flooring system.

[0041] While the embossed-in-registration process described above is suitable for embossed surface textures that are less than about 0.2 mm deep, deeper surface textures may be problematic. Embossing patterns capable of imparting deep surface textures, for example, require relatively large press plate protrusions that tend to disturb the pressure homogeneity applied across the board surface. This pressure disturbance can cause distortions in the final product. Embossed surface textures may be formed greater than about 0.2 mm deep by hollowing out the board substrate 40 at locations where deep surface textures are desired. The hollowing out process may be performed before, during, or after the perimeter of the board substrate 40 is milled as described above. The board edges may be used to locate the boundaries of the hollowed out portions of the board substrate 40.

[0042] Referring to Figure 7, an embossed-in-registration flooring plank 60, fabricated according to the process described above may optionally include a protective padding layer 50 on one side. The mechanically embossed surface texture is registered with the decorative motif 68 of the decorative paper sheet 44. By registration, it is meant that the embossed surface texture is substantially aligned with the decorative motif of the decorative paper sheet 44. By providing an embossed-in-registration flooring plank, a realistic representation of a natural material may be provided to individual flooring planks. While the dec-

orative motif illustrated in Figure 7 realistically represents the image and texture of a wood grain, it should be appreciated that other embossed-in-registration designs such as ceramic planks, concrete, marble, may be produced.

[0043] Each of the individual flooring planks may, for example, include at least one locking mechanism.

[0044] Locking mechanisms may be incorporated within the board substrate 40 before the embossing pattern is imparted to the surface of the board substrate 40 in registration with the decorative motif.

[0045] Accordingly, locking mechanisms may be fabricated within individual board substrates 40. Next, the locking mechanisms may be used to join individual board substrates together to form a plank structure. The plank structure may then be inserted into the press 54. After the embossing pattern is imparted to the plank structure and the fused components are fused together, the plank structure is removed from the press 54. Next, embossed-in-registration flooring planks 60 within the fused plank structure are separated by unlocking the locking mechanisms. Cutting tools may be used to assist in the separation and to ensure the decorative motif is not damaged.

[0046] The locking mechanisms may be incorporated within the board substrate 40 after the embossing pattern is imparted to the surface of the board substrate 40 in registration with the decorative motif. Accordingly, a board substrate 40 having relatively large dimensions of, for example, 4'x8', may be embossed by the press 54. Next, the resulting embossed-in-registration substrate may be cut into a plurality of individual embossed-in-registration flooring planks 60. Edges of the individual embossed-in-registration flooring planks 60 may have smooth edges and precise dimensions. The cutting may be performed using shaping tools, milling tools, cutting tools, breaking tools. The board substrate may be cut by the press machine.

[0047] Accordingly, the board substrate 40 may be cut into units (e.g., strips) having dimensions of, for example, 300 x 300 mm, 400 x 400 mm, 600 x 600 mm, 1,200 x 300 mm, 1,200 x 400 mm. Next, the locking mechanisms may be incorporated within the individual embossed-in-registration flooring planks 60. The locking mechanisms may be hidden beneath the surface of the flooring planks or they may be visible.

[0048] The locking mechanisms may be incorporated within the individual embossed-in-registration flooring planks 60 by aligning the at least one of the board edges, alignment marks, decorative motifs, and surface textures of the flooring plank with a milling tool. By aligning the milling tool with any of the aforementioned alignable features, locking mechanisms may be milled into the sides of the board substrates 40 such that, when flooring planks 60 are joined together the at least a portion of the decorative motifs form a continuous pattern and at least a portion of the embossed-in-registration patterns form a substantially continuous surface texture across adjacent

flooring planks.

[0049] The embossed-in-registration flooring plank 60 may include a locking mechanism 64 (e.g., at least one of a tongue and groove locking system, a snap-together locking system) extending along all four sides of the embossed-in-registration laminate 60. For example, a snap-together locking system may be added to all four sides of the embossed-in-registration flooring plank 60 and used to connect multiple embossed-in-registration flooring planks 60 into an embossed-in-registration flooring system 300 (as shown in Figure 8). The number and location of locking mechanisms may depend on the desired configuration of the embossed-in-registration flooring system. For example, when an embossed-in-registration flooring system abuts a corner, only two locking mechanisms are required (along the sides).

[0050] Referring to Figure 8, the embossed-in-registration flooring planks A and B may, for example, include locking mechanisms along four sides (e.g., along joints J1, J2, J3, and J4). Embossed-in-registration flooring planks C and D may, for example, include locking mechanisms along four sides (e.g., along joints J1, J2, J3, and another joint not shown).

[0051] Embossed-in-registration flooring planks including the aforementioned locking mechanisms may be securely attached together with or without glue to form an embossed-in-registration laminate system 300. Multiple embossed-in-registration flooring planks may be joined together to obtain any desired shape for flooring or planking. The embossed-in-registration flooring planks may be joined to each other such that at least portions of embossed-in-registration patterns of adjacent flooring planks are substantially aligned with each other and form a substantially continuous image and embossed surface texture across flooring planks within a flooring system.

[0052] Figures 8 and 9 illustrate an exemplary embossed-in-registration flooring system 300 incorporating one type of locking mechanism on each of the individual embossed-in-registration flooring planks 60. Figure 9 illustrates an exemplary embossed-in-registration flooring system including flooring planks incorporating a snap-type tongue and groove locking mechanism. The snap-type tongue and groove locking mechanism may be integrated into the sidewalls of each embossed-in-registration laminate 60 so as to ensure that embossed-in-registration patterns of adjacent flooring planks are substantially aligned with each other and substantially continuous within the flooring system.

[0053] Figure 9 illustrates a cross sectional view of Figure 8 taken along line 9-9. As shown, the locking mechanism may be fabricated by forming a groove 230, a tongue 200, a channel 210, and a lip 220 along the edges of the embossed-in-registration flooring planks 60. The locking mechanisms on the embossed-in-registration flooring planks 60 may be joined together by inserting the tongue 200 into the groove 230 of an adjacent embossed-in-registration flooring plank 60.

[0054] Subsequently, the lip 220 is secured within channel 210, thereby joining adjacent embossed-in-registration flooring planks 60 into an embossed-in-registration flooring system 300. The embossed-in-registration flooring planks 60 labeled A, B, C and D may be joined together with or without glue.

[0055] It should be appreciated that other types of locking mechanisms may be incorporated within the sides of the individual embossed-in-registration flooring planks 60.

[0056] Referring back to Figure 8, each of the embossed-in-registration flooring planks 60 may, for example, exhibit an embossed-in-registration ceramic plank motif G1. The ceramic plank motif may comprise a plurality of planks in the shape of squares, rectangles, triangles, circles, ovals, any other shape or design that are separated by grout lines. Widths of grout lines W_h , W_v , and the intraboard grout width W may be substantially equal. When incorporating the snap-type tongue and groove locking mechanism into the embossed-in-registration flooring planks 60 the grout width adjacent the joints J1, J2, J3, and J4 on each embossed-in-registration laminate A, B, C, and D are approximately one-half the intraboard grout width W . For example, the vertical plank grout width (W_v) across joint J1 is made up of grout lines on embossed-in-registration laminates A, B, C and D, such that when the embossed-in-registration laminates A, B, C, and D are joined at J1 the vertical grout width (W_v) is approximately equal to (W).

[0057] Accordingly, the grout width on any individual embossed-in-registration flooring plank 60 adjacent a joint is one-half of intraboard grout width (W). The horizontal and vertical grout widths W_h and W_v may be controlled such they are substantially equal to the dimensions of the intraboard grout width W . It should be appreciated, however, that the dimensions of the grout widths in the embossed-in-registration flooring planks depend on the type of locking mechanism incorporated and the decorative motif exhibited.

[0058] In addition to grout lines, many other decorative motifs may be used in the embossed-in-registration flooring system of the present invention. Referring to Figures 10 and 11, a decorative motif exhibiting, for example, a wood grain surface G2 substantially aligned across joints J5 and J6 of adjacent flooring planks may be provided. Wood grain patterns generally include more elements (e.g., wood grain lines, wood knot 423) that extend to the perimeters of the flooring planks that need to be aligned than ceramic plank motifs. Accordingly, aligning the wood grain motif is generally more difficult than aligning grout line portions of the ceramic plank motifs. For example, aligning a first portion of a wood knot 423 on embossed-in-registration flooring plank E with a second portion of the wood knot 423 on embossed-in-registration flooring plank F is generally more complex than aligning grout line widths across joints of adjacent flooring planks. Accordingly, when fabricating a locking mechanism, consideration of all the graphic elements (e.g., wood grains

lines and wood knots 423) must be considered to ensure a realistic embossed-in-registration flooring system 400. At least one portion of the decorative motif may be used as an alignment marks ensuring consistent alignment of adjacent flooring planks.

[0059] Individual flooring planks within the embossed-in-registration flooring system 400 may be joined together with a snap-type mechanical system as illustrated in Figure 11 depicting a cross sectional view of Figure 10 along line 11-11. Again, alignment techniques used in the fabrication of the locking mechanism such that the embossed-in-registration laminate system 400 has a surface texture surface 423 that is substantially continuous across joints, J5 and J6. Optionally, the embossed-in-registration laminates 60 have a protective padding layer 70 under the base sheet 48.

[0060] Figures 12A and 12B illustrate schematic views of a flooring plank in accordance with the principles of the present invention.

[0061] Referring to Figures 12A and 12B, an upper surface at the perimeter, P, of each embossed-in-registration flooring plank may be recessed below an upper surface at the portions of the flooring plank surrounded by the perimeter. An object O (e.g., a user's shoe, a wheel) contacting the major surface, M_s , of a flooring plank does not generally contact the surface of the perimeter P_s , due to the perimeter's recessed surface. The perimeter, may include a portion of the flooring plank extending from the edge of the flooring plank approximately 3.175 mm toward the center of the flooring plank. The depth to which the surface of the perimeter of the flooring plank is recessed is approximately 0.794 mm. The surface of at least one portion of the perimeter of a flooring plank may not be recessed, as will be discussed in greater detail below with reference to Figure 13.

[0062] Accordingly, the embossed-in-registration pattern may be provided to the edges of the flooring plank and may be aligned with embossed-in-registration patterns formed on adjacent flooring planks while the edges of each individual flooring plank may be prevented from prematurely wearing.

[0063] Although it has been shown in Figures 8 and 10 that individual flooring planks within a flooring system are substantially the same size and shape and are joined to each other such that each side of each flooring plank is joined to only one adjacent flooring plank, it should be appreciated that individual flooring planks within a flooring system may vary in size (e.g., width and/or length) and shape (e.g., rectangular, square, triangular, hexagonal, etc.). Individual flooring planks may have complementary shapes capable of being assembled similar to a puzzle or mosaic. Further, sides of individual flooring planks may contact more than one adjacent flooring plank.

[0064] Flooring planks within a flooring system may be arranged such that at least one side of each plank includes at least one sub-panel adjacent at least two other sub-panels. Each plank includes, either entirely or par-

tially, at least one sub-panel, as will be described in greater detail below.

[0065] In Figure 13A, partial sub-panel 134A of plank 130A is a complementary sub-panel with respect to neighboring partial sub-panel 136B of plank 130B, adjacent plank 130A. With this arrangement, the partial sub-panels 134A and 136B are made to appear as one unitary sub-panel.

[0066] Still referring to Figure 13A, each of the planks 130A-F comprises at least three sub-panels wherein at least one of the sub-panels is a unitary sub-panel and at least two of the sub-panels are partial sub-panels. For example, 132A is a unitary sub-panel and 134A and 136A are partial sub-panels.

[0067] The unitary sub-panel 132A may provide a complete decorative motif with or without an embossed surface texture that may or may not be in registration with the decorative motif. The partial sub-panels 134A and 136A of a plank may provide separated, incomplete decorative motifs with or without embossed surface textures that may or may not be in registration with the decorative motifs. Neighboring partial sub-panels of adjacent planks may be complementary to each other such that they provide a substantially complete decorative motif and/or surface texture and appear as a substantially continuous, unitary sub-panel. Complementary partial sub-panels may have complementary decorative motifs and/or embossed surface textures.

[0068] Accordingly, when complementary partial sub-panels of adjacent planks are properly aligned, a substantially continuous (i.e., complete) decorative motif and/or embossed surface texture may be formed across neighboring complementary partial sub-panels.

[0069] Sub-panels within a plank may or may not comprise substantially the same decorative motif and/or embossed surface texture.

[0070] Figure 13B illustrates a schematic view of an exemplary plank 130 such as that shown in Figure 13A.

[0071] Portions of the perimeter surface of each plank may be recessed at locations where neighboring sub-panels are not complementary. Portions of the perimeter surface of each plank are non-recessed at locations where neighboring sub-panels are complementary. Referring to Figure 13B, portions of the upper surface of the perimeter "P" of each of the planks 130 indicated by reference numeral 138a may be slightly recessed compared to the major surface of each of the planks (see also Figure 12B) to prevent premature wear of each of the planks. Further, portions of the upper surface of the perimeter of each of the planks 130 indicated by reference numeral 138b may be non-recessed and substantially coplanar with the major surface of the sub-panels. Recessing only portions of the perimeter surface of each of the planks at positions not occupied by the decorative motifs and/or embossed surface textures of partial sub-panels of a plank allows complementary partial sub-panels to appear as a part of a unitary sub-panel while not significantly detracting from the overall durability of each of the planks.

Portions of the surface of each plank may be recessed at locations where sub-panels of a plank are adjacent one another. Referring to Figure 13B, portions of the upper surface of each of the planks 130 indicated by reference numeral 138c may be slightly recessed compared to the major surface of each of the planks (see also Figure 12B) to provide a visual and textural effect that each of the sub-panels of the plank are not a part of the same plank.

[0072] Figures 14A-14C illustrate an exemplary plank of a flooring system according to the present invention.

[0073] Referring to Figures 14A-14C, similar to the plank shown in Figures 13A and 13B, portions of the upper surface of the perimeter "P" of each of the planks 130 indicated by reference numeral 138a may be beveled to prevent premature wear of each of the planks. Further, portions upper surface of the perimeter of each of the planks 130 indicated by reference numeral 138b may not be beveled such that they are substantially coplanar with the major surface of the sub-panels. Beveling the perimeter surface of each of the planks at positions corresponding to the decorative motifs and/or embossed surface textures of partial sub-panels of a plank allows complementary partial sub-panels to appear as a part of a unitary sub-panel while not significantly detracting from the overall durability of each of the planks. Portions of the surface of each plank may be provided with a groove at locations where sub-panels of a plank are adjacent to one another.

[0074] Figures 14B and 14C illustrate cross-sectional views of plank 130 taken across lines I-I' and II-II', respectively. Referring to Figures 14B and 14C, portions of the upper surface of each of the planks 130 indicated by reference numeral 138c may be beveled to form a groove. This groove may also prevent premature wear of each of the planks. Thus, the groove provides a visual and textural effect that sub-panels of a plank are separate. The bevel at 138c may produce a groove having a substantially V-shaped groove. It is appreciated, however, that the bevel may produce other groove topographies (e.g., U-shaped grooves). The beveling of each of the planks 130 at perimeter surface portion 138a creates a groove between adjacent planks. Accordingly, the groove formed between adjacent ones of the planks, via beveling at 138a, has substantially the same width and topography as grooves formed within the planks, via beveling at 138c.

[0075] The motif and/or surface texture present at the recessed surface of the perimeter of each plank may or may not correspond to the motif/surface texture present at the main surface of a corresponding plank. Thus, a substantially continuous motif and/or surface texture may or may not be present across the surfaces of the perimeter and the interior of any individual plank. Alignment marks or markings (not shown) can be used to self-align a decorative motif on the planks. The embossed in-registration pattern may be a free form or custom design. It is to be understood that substantially any embossed-in-

registration pattern and any decorative motif may be realized. Alignment of the planks may be done visually upon joining them together. Accordingly, alignment of the planks 130 may be performed using the decorative motif and/or embossed surface texture of each of the planks.

[0076] While it has been illustrated that the planks in Figures 13A, 13B, and 14A-14C are substantially rectangular, the principles of the present invention allow the planks within the flooring system to have other shapes and sizes (e.g., geometric, freeform) or different or similar dimensions such that the flooring planks may be assembled in a "mosaic"-type arrangement or other regular, semi-repetitious, or random arrangement of panels. Further, while it is illustrated that each plank comprises an identical sub-panel layout, the principles of the present invention allow the planks within the flooring system to have other sub-panel layouts (e.g., other subpanel shapes, sizes) The individual planks within the flooring system may be cut from a board such that joints between the flooring panels of the flooring system are not visible. Further, the planks within the flooring system illustrated in Figures 13 and 14 may be joined together with or without glue. Still further, while it has been discussed that the embossed surface texture is substantially aligned with an underlying decorative motif, it is to be understood that substantially any embossed surface texture may be imparted to the planks of the present invention, regardless of the underlying decorative motif. Still further, the decorative motifs and/or the embossed surface texture of one plank may not be aligned or even be remotely similar in appearance and/or texture to decorative motifs and/or embossed surface textures of adjacent planks.

[0077] According to the principles of the present invention, any of the aforementioned decorative motifs and/or embossed surface textures that may or may not be embossed in registration with the decorative motifs (collectively referred to herein as "patterns") may be applied to any of the aforementioned planks to form a substantially continuous pattern across adjacent planks arranged along a predetermined direction by forming each of the plank patterns using at least one bulk pattern and at least one edge pattern.

[0078] Each edge pattern may be present at a perimeter portion of the plank extending along at least a portion of at least one edge of each plank. Each edge pattern may extend to a predetermined distance (e.g., about one millimeter, about one inch) into the interior of the plank, away from the perimeter of the plank. At least one bulk pattern may be arranged adjacent at least one edge pattern, wherein a pattern present at the edge of the bulk pattern adjacent the edge pattern may form a substantially continuous visual/textural pattern with a pattern present at the edge of the edge pattern adjacent the bulk pattern.

[0079] Patterns of individual planks, arranged adjacent each other along a predetermined direction within a flooring system, may complement patterns of adjacent planks (i.e., form substantially continuous patterns across adja-

cent planks) when edge patterns of the adjacent planks form a substantially continuous pattern. Where the flooring system described above comprises a plurality of adjacent planks arranged along the predetermined direction, and where the edges of each plank are arranged adjacent to edge patterns of other planks along the predetermined direction, edge patterns of adjacent planks are identical or substantially identical. The identical or substantially identical edge patterns of adjacent planks enable a continuous pattern to be formed across the adjacent planks.

[0080] For example, referring to Figure 15A, an exemplary plank pattern of plank 150 may comprise two edge patterns 152 substantially identical to each other and a bulk pattern 154. As shown in Figure 15A, the two substantially identical edge patterns 152 are present at a perimeter portion of the plank 150, extend along a portion of the opposite edges of the plank, and extend a predetermined distance into the interior of the plank 150. Still referring to Figure 15A, the pattern present at the edge of the bulk pattern 154 adjacent the edge patterns 152 forms a substantially continuous pattern with the pattern present at the edge patterns 152 adjacent the bulk pattern.

[0081] Referring now to Figure 15B, a plurality of planks 150A, 150B, 150C, such as those illustrated in Figure 15A may be arranged adjacent each other within a flooring system along a predetermined direction such that edges of each plank are arranged adjacent to the edges of other planks. along the predetermined direction (e.g., an edge of plank 150A is adjacent an edge of plank 150B, an edge of plank 150C is adjacent an edge of plank 150D). As mentioned above, a substantially continuous pattern may be formed across an individual plank 150 because the bulk pattern 154 is substantially aligned with the edge patterns 152.

[0082] In an embodiment of the invention, the predetermined direction in which the planks are arranged is based on the adjacent edge patterns 152 in the planks, such that only by arranging the planks in the predetermined direction will the pattern formed be continuous and natural-looking. In this embodiment, reversing a plank or flipping a plank over will result in a discontinuous pattern. However, it is understood that in another embodiment, the edge patterns along a portion of the perimeter may be selected such that reversing, flipping or otherwise rearranging planks does not disrupt the pattern, i.e. the pattern is continuous.

[0083] In another embodiment, the predetermined direction is based on the interlocking mechanism that joins adjacent planks, such that the planks will not fit together properly if they are arranged in a direction other than the predetermined direction. One example of such an interlocking mechanism is a glueless tongue and groove system, in which the tongue is formed along at least one edge of the plank and the groove formed along the opposite edge. In yet another embodiment, the predetermined direction is based on both the edge patterns 152

and the glueless locking mechanism.

[0084] According to the principles of the present invention, bulk patterns 154A-154F may or may not be the same. Each of the bulk patterns 154 within a flooring system may be unique. Further, according to the principles of the present invention, edge patterns of individual planks may be substantially identical. Therefore, edge patterns of adjacent planks in a flooring system, across which a substantially continuous pattern is formed along the predetermined direction, are also substantially identical. A substantially continuous pattern may be provided across plank 150A because bulk pattern 154A and edge patterns 152A are aligned with each other to produce a substantially continuous pattern. Substantially continuous patterns may be individually provided across planks 150B, 150C, because their respective bulk patterns 154B, 154C, and edge patterns 152B, 152C, are similarly aligned with each other to produce a substantially continuous pattern.

[0085] Because the edge patterns of planks 150A-150F within the flooring system illustrated in Figure 15B are identical, edge pattern 152A forms a substantially continuous pattern with edge pattern 152B, edge pattern 152C forms a substantially continuous pattern with edge pattern 152D, and so on. Accordingly, a substantially continuous pattern may be formed across planks 150A and 150B, across planks 150C and 150D, and so on. The boundary or joint between the edge pattern 152A and the edge pattern 152B is substantially not visible, or the appearance of the presence of the boundary or joint is minimized. Similarly, the boundary or joint between the edge pattern 152C and the edge pattern 152D is substantially not visible, or the appearance of the presence of the boundary or joint is minimized. The boundary or joint between the edge pattern 152E and the edge pattern 152F is substantially not visible, or the appearance of the presence of the boundary or joint is minimized.

[0086] In one embodiment of the present invention, in which the edge patterns 152 are all substantially identical, any of the planks 150A-150F may replace any other plank within the flooring system while still maintaining the presence of a substantially continuous pattern across planks arranged adjacent each other along the predetermined direction. This is because all bulk patterns of a plank are substantially aligned with their respective edge patterns to form substantially continuous patterns within a plank and because all edge patterns of planks adjacent each other within a flooring system are identical, forming form substantially continuous patterns across planks adjacent each other along the predetermined direction.

[0087] In another embodiment, planks may have adjacent right and left edge patterns 152 substantially identical, while opposite left and right edge patterns 152 are not.

[0088] For example, in Figure 15C, the unitary sub-panel 132 of plank 150 may have a pattern provided by a bulk pattern 154G, partial sub-panel 134 may have a pattern provided by bulk pattern 154I and edge pattern

152, and partial sub-panel 136 may have a pattern provided by bulk pattern 154H and edge pattern 152, wherein the bulk patterns 154G-154I may or may not be the same. As mentioned above, however, the edge pattern 152, present at the perimeter of the partial sub-panel portions 134 and 136 of the plank 150 and extending along a portion of the edges of the plank 150, are identical to each other. Accordingly, in view of Figure 13A, when, for example, planks 130A and 130B are arranged adjacent each other along a predetermined direction, edge patterns 152 of complementary partial sub-panels 134A and 136B are substantially identical to each other and a substantially continuous pattern may be formed across adjacent planks, wherein the bulk patterns of the complementary partial-sub panels become a part of a substantially continuous pattern, appearing, visually and/or texturally as a unitary sub-panel.

[0089] Furthermore, referring now to Figures 15C and 15D, flooring systems incorporating planks such as those illustrated in Figures 13A-14C may be provided with substantially continuous patterns across planks adjacent each other along predetermined directions by applying the techniques described above with reference to Figures 15A and 15B. Figure 15D shows the planks having a woodgrain pattern in the arrangement shown in Figure 15B. Because the edge pattern 152A is substantially identical to the adjacent edge pattern 152B, planks 150A and 150B have the appearance of a substantially continuous woodgrain pattern running uninterrupted across the boundary or joint between edge pattern 152A and edge pattern 152B of the adjacent plank.

[0090] In addition, because the edge patterns 152A and 152B do not run along the entire length of the boundary or joint between planks 150A and 150B, but only along the portion corresponding to the height of the partial board on the bottom half of the planks, the pattern is not continuous across that portion of the boundary between planks 150A and 150B corresponding to the height of the complete boards on the top half of the planks.

[0091] As mentioned above, within the flooring system incorporating the planks illustrated in Figures 13A-14C and 15C, the bulk patterns within the sub-panels of the planks may or may not be the same. Each of the bulk patterns within the flooring system may be unique.

[0092] Fig. 15E shows an embodiment of the invention in which the edge patterns of the planks are identical (or substantially identical) in every plank.

[0093] Specifically, Fig. 15E shows four planks, 150A, 150B, 150C, and 150D arranged such that plank 150A is adjacent the left edge of plank 150B and adjacent to a top edge of plank 150C. Plank 150D is adjacent to the right edge of plank 150C and adjacent to the bottom edge of 150B.

[0094] In this embodiment, the décor paper of each plank has a wood design.

[0095] However, it is understood that other natural looking designs other than wood are contemplated by this invention as well. The wood design in plank 150A

includes, for example, a complete board or strip 155A on a top half of the board, a short incomplete board 151A and a long incomplete board 153A. Each of the boards has a woodgrain pattern. In addition, the short and long incomplete boards 151A and 153A have an edge pattern 152 running along a portion of the perimeter of the plank corresponding to the width of the incomplete boards 151A and 153A, and may extend a small distance (such as one centimeter, for example) into the interior of the boards. The edge patterns 152 of incomplete boards 151A and 153A are identical. The edge patterns 152 may also not extend into the interior of the boards.

[0096] Similarly, planks 150B, 150C, and 150D have complete boards 155B, 155C, and 155D, respectively, running the length of the plank, and short boards 151B, 151C, and 151D which are adjacent to long boards 153B, 153C, and 153D, respectively. Each of the short and long boards may have an identical edge pattern 152 along a portion of the perimeter of the plank corresponding to the width of the short and long boards.

[0097] All short boards 151A-D, long boards 153 A-D, and complete boards 155A-D have woodgrain patterns that are different from each other or some identical to each other. Only the edge patterns 152 in the incomplete boards are identical in this particular example. Furthermore, the edge pattern and interior woodgrain pattern of each incomplete board form a continuous pattern. In other words, there is a continuous overall woodgrain pattern on each of the short boards and long boards that are all different from one another, despite the fact that the edge patterns 152 are the same.

[0098] When planks 150A and 150B are placed adjacent to one another as shown in Fig. 15E, complete boards 155A and 155B will be adjacent to each other, and long board 153A and short board 151B will be adjacent. Complete boards 155A and 155B appear as separate boards and the woodgrain pattern is discontinuous across them, because the adjacent edges of the complete boards are different. But because the edge patterns 152 in long board 153A and short board 151 B are the same, the unique woodgrain patterns of 153A and 151 B appear to form a single continuous board with a unique woodgrain pattern running across the planks 150A and 150B. Furthermore, the appearance of a complete and continuous board with a unique woodgrain pattern running in boards 153A and 151B across the planks minimizes the visibility or appearance of the joint or boundary between the planks.

[0099] Similarly, the woodgrain pattern across boards 153C and 151 D is continuous.

[0100] In a further embodiment, the planks 150A, 150B, 150C, and 150D may have a surface texture that is embossed in registration with the wood design on the décor paper. Because edge patterns 152 are part of that wood design and may be the same or substantially identical in every plank, the embossed surface texture will appear to be continuous along the incomplete boards of adjacent planks in the manner discussed above. In still

another embodiment, the embossed in registration surface texture may include bevels to imitate seams between boards, such that in plank 150A, for example, the complete board 155A would have a bevel running along its perimeter, including the boundary between board 155A and incomplete boards 151A and 153A. The incomplete boards 151A and 153A would have a bevel where they are adjacent, but the incomplete boards would not have a bevel along the portion of the perimeter of the plank 150A where the edge patterns 152 are located. In this way, a continuous wood grain pattern and corresponding embossed in registration surface texture can run continuously across planks 150A and 150B uninterrupted by a bevel. This would further reduce the appearance of the boundary between planks.

[0101] By having all edge patterns 152 to be identical, the present invention allows any planks to be fit together in the predetermined direction in which a long board 153 is adjacent a short board 151 of another plank, because the edge patterns 152 will always line up to form the appearance of a continuous wood grain pattern running across the adjacent long and short boards of the two planks. For example, if the positions of planks 150A and 150B were reversed (such that plank 150B was adjacent a top edge of plank 150C), the edge pattern 152 of long board 153B would match or be aligned with the edge pattern of short board 151A, forming a continuous wood grain pattern in the boards 153B and 151A across planks 150B and 150A.

[0102] The present invention reduces the complexity involved in installing a laminated floor, because it does not matter which planks are placed adjacent to one another in the predetermined direction. The patterns will be aligned.

[0103] In a further embodiment, the planks 150 are provided with a glueless interlocking tongue and groove system in which the tongue is formed on two adjacent perimeter edges of the plank and the groove is formed in the opposite two adjacent perimeter edges so that the planks can only be fit together in the direction that will align long boards 153 with short boards 151, for example, where edge patterns 152 meet.

[0104] Furthermore, because in this embodiment only the edge patterns are required to be identical, the interior patterns of the complete, long and short boards of the planks can be different, providing a more natural looking floor.

Claims

1. A flooring system, comprising:

at least two flooring panels (130; 130A, 130B, 130C, 130D, 130E, 130F; 150), each flooring panel comprising:

a plurality of side surfaces;

- a first upper surface (138a) adjacent at least a portion of the plurality of side surfaces; a second upper surface (138b) adjacent at least a portion of the plurality of side surfaces, wherein the first upper surface (138a) is lower than the second upper surface (138b); and **characterized in that** at least one partial sub-panel (134, 136; 134A, 136A, 134B, 136B, 134C, 136C, 134D, 136D, 134E, 136E, 134F, 136F), wherein neighboring partial sub-panels (134A, 136B; 134C, 136D; 134E, 136F) of adjacent flooring panels are complementary such that at least one of at least one decorative motif and at least one embossed surface texture is substantially continuous across at least a portion of a neighboring partial sub-panel, and wherein each flooring panel comprises at least three subpanels (132, 134, 136; 132A, 134A, 136A; 132B, 134B, 136B; 132C, 134C, 136C; 132D, 134D, 136D; 132E, 134E, 136E; 132F, 134F, 136F), wherein at least one of said sub-panels is a unitary sub-panel (132; 132A; 132B; 132C; 132D; 132E; 132F) and wherein at least two of said sub-panels are partial sub-panels (134, 136; 134A, 136A; 134B, 136B; 134C, 136C; 134D, 136D; 134E, 136E; 134F, 136F), and wherein at least two neighboring partial subpanels (134A, 136B; 134C, 136D; 134E, 136F) of respective flooring panels (130A, 130B; 130C, 130D; 130E, 130F) are complementary to each other such that they provide a substantially complete decorative motif and/or surface texture and appear as a substantially continuous, unitary sub-panel, and wherein said first upper surface (138a) is beveled.
2. A flooring system according to claim 1, wherein said second upper surface (138b) is present where neighboring partial sub-panels (134A, 136B; 134C, 136D; 134E, 136F) are complementary, so as to allow said complementary partial subpanels to appear as a part of a unitary sub-panel.
 3. A flooring system according to any of claims 1 and 2, wherein said first upper surface (138a) is present at locations where neighboring subpanels are not complementary.
 4. A flooring system according to any of the preceding claims, wherein each of said flooring panels further comprises at least one first groove (138c) dividing the second upper surface into at least two sub-surfaces.
 5. A flooring system according to claim 4, wherein said at least one first groove (138c) separates the sub-panels (132, 134, 136) in the corresponding flooring panel (130).
 6. A flooring system according to claim 4 or 5, wherein said first upper surfaces (138a) of adjacent ones of the at least two flooring panels form a second groove having a topography substantially identical to a topography of the first groove (138c).
 7. A flooring system according to claim 6, wherein said second groove further has substantially the same width as the first groove (138c).
 8. A flooring system according any of claims 4 to 7, wherein said first groove (138c) is a substantially V or U shaped groove.
 9. A flooring system according to any of the preceding claims, wherein each of said flooring panels comprises two partial sub-panels (134, 136) each provided with a bulk pattern (154H, 154I) and with an edge pattern (152), wherein the edge patterns (152) of said partial sub-panels (134, 136) are identical, and wherein said edge patterns are provided where the respective partial sub-panel is arranged to meet a complementary partial sub-panel of another flooring panel to appear as one unitary sub-panel.
 10. A flooring system according to claim 9, wherein said edge patterns (152) are provided on said second surface, and wherein said bulk patterns (154H, 154I) are preferably different.
 11. A flooring system according to any of the preceding claims, wherein said neighboring partial subpanels (134A, 136B; 134C, 136D; 134E, 136F) are complementary to each other such that they provide a substantially complete decorative motif, said decorative motif being a wood grain pattern.
 12. A flooring system according to any of the preceding claims, wherein said first surface (138a) is present along a first portion of at least one side of each flooring panel, and wherein said second surface (138b) is present along at least a second portion of said at least one side.
- Patentansprüche**
1. Fußbodensystem, das umfasst:
 - wenigstens zwei Fußbodenplatten (130; 130A, 130B, 130C, 130D, 130E, 130F; 150), wobei jede Fußbodenplatte umfasst:

- eine Vielzahl seitlicher Flächen;
 eine erste obere Fläche (138a), die an wenigstens einen Teil der Vielzahl seitlicher Flächen angrenzt;
 eine zweite obere Fläche (138b), die an wenigstens einen Teil der Vielzahl seitlicher Flächen angrenzt, wobei die erste obere Fläche (138a) tiefer liegt als die zweite obere Fläche (138b); und **gekennzeichnet durch**
 wenigstens eine abgeteilte Unterplatte (134, 136; 134A, 136A, 134B, 136B, 134C, 136C, 134D, 136D, 134E, 136E, 134F, 136F), wobei benachbarte abgeteilte Unterplatten (134A, 136B; 134C, 136D; 134E, 136F) aneinandergrenzender Fußbodenplatten so komplementär sind, dass wenigstens ein Ziermotiv oder/und wenigstens eine geprägte Oberflächenstruktur im Wesentlichen durchgehend über wenigstens einen Teil einer benachbarten abgeteilten Unterplatte vorhanden ist/sind, und wobei jede Fußbodenplatte wenigstens drei Unterplatten (132, 134, 136; 132A, 134A, 136A; 132B, 134B, 136B; 132C, 134C, 136C; 132D, 134D, 136D; 132E, 134E, 136E; 132F, 134F, 136F) umfasst, wenigstens eine der Unterplatten eine ungeteilte Unterplatte (132; 132A; 132B; 132C; 132D; 132E; 132F) ist und wenigstens zwei der Unterplatten abgeteilte Unterplatten (134, 136; 134A, 136A; 134B, 136B; 134C, 136C; 134D, 136D; 134E, 136E; 134F, 136F) sind, und wobei wenigstens zwei benachbarte abgeteilte Unterplatten (134A, 136B; 134C, 136D; 134E, 136F) jeweiliger Fußbodenplatten (130A, 130B; 130C, 130D; 130E, 130F) so komplementär zueinander sind, dass sie ein im Wesentlichen vollständiges Ziermotiv und/oder eine im Wesentlichen vollständige Oberflächenstruktur bilden und als eine im Wesentlichen durchgehende ungeteilte Unterplatte erscheinen, und wobei die erste obere Fläche (138a) abgeschrägt ist.
2. Fußbodensystem nach Anspruch 1, wobei die zweite obere Fläche (138b) dort vorhanden ist, wo benachbarte abgeteilte Unterplatten (134A, 136B; 134C, 136D; 134E, 136F) komplementär sind, so dass die komplementären abgeteilten Unterplatten als ein Teil einer ungeteilten Unterplatte erscheinen können.
 3. Fußbodensystem nach einem der Ansprüche 1 und 2, wobei die erste obere Fläche (138a) an Positionen vorhanden ist, an denen benachbarte Unterplatten nicht komplementär sind.
 4. Fußbodensystem nach einem der vorangehenden Ansprüche, wobei jede der Fußbodenplatten des Weiteren wenigstens eine erste Nut (138c) umfasst, die die zweite obere Fläche in wenigstens zwei Unterflächen teilt.
 5. Fußbodensystem nach Anspruch 4, wobei die wenigstens eine erste Nut (138c) die Unterplatten (132, 134, 136) in der entsprechenden Fußbodenplatte (130) trennt.
 6. Fußbodensystem nach Anspruch 4 oder 5, wobei die ersten oberen Flächen (138a) aneinandergrenzender der wenigstens zwei Fußbodenplatten eine zweite Nut bilden, die eine Topografie hat, die im Wesentlichen identisch mit einer Topografie der ersten Nut (138c) ist.
 7. Fußbodensystem nach Anspruch 6, wobei die zweite Nut des Weiteren im Wesentlichen die gleiche Breite hat wie die erste Nut (138c).
 8. Fußbodensystem nach einem der Ansprüche 4 bis 7, wobei die erste Nut (138c) eine im Wesentlichen V- oder U-förmige Nut ist.
 9. Fußbodensystem nach einem der vorangehenden Ansprüche, wobei jede der Fußbodenplatten zwei abgeteilte Unterplatten (134, 136) umfasst, die jeweils mit einem Hauptmuster (154H, 154I) und mit einem Randmuster (152) versehen sind, wobei die Randmuster (152) der abgeteilten Unterplatten (134, 136) identisch sind und die Randmuster dort vorhanden sind, wo die jeweilige abgeteilte Unterplatte so auf eine komplementäre abgeteilte Unterplatte einer anderen Fußbodenplatte trifft, dass sie als eine ungeteilte Unterplatte erscheinen.
 10. Fußbodensystem nach Anspruch 9, wobei die Randmuster (152) an der zweiten Fläche vorhanden sind und die Hauptmuster (154H, 154I) vorzugsweise verschieden sind.
 11. Fußbodensystem nach einem der vorangehenden Ansprüche, wobei die benachbarten abgeteilten Unterplatten (134A, 136B; 134C, 136D; 134E, 136F) so komplementär zueinander sind, dass sie ein im Wesentlichen vollständiges Ziermotiv bilden, wobei das Ziermotiv ein Holzmaserungsmuster ist.
 12. Fußbodensystem nach einem der vorangehenden Ansprüche, wobei die erste Fläche (138a) an einem ersten Teil wenigstens einer Seite jeder Fußbodenplatte vorhanden ist und die zweite Fläche (138b) an wenigstens einem zweiten Teil der wenigstens einen Seite vorhanden ist.

Revendications

1. Système de plancher comprenant :

au moins deux panneaux de plancher (130 ; 130A, 130B, 130C, 130D, 130E, 130F, 150), chacun de ces panneaux de plancher comprenant :

plusieurs surfaces latérales, une première surface supérieure (138a) adjacente à au moins une partie des surfaces latérales,

une seconde surface supérieure (138b) adjacente à au moins une partie des surfaces latérales, la première surface supérieure (138a) étant située à un niveau inférieur à celui de la seconde surface supérieure (138b),

caractérisé en ce qu'

il est prévu au moins un sous-panneau partiel (134, 136 ; 134A, 136A ; 134B, 136B ; 134C, 136C ; 134D, 136D ; 134E, 136E ; 134F, 136F), des sous-panneaux partiels voisins (134A, 136B, 134C, 136D, 134E, 136F) de panneaux de plancher adjacents étant complémentaires de sorte qu'au moins un motif décoratif et/ou au moins une texture surfacique en relief soit essentiellement continu au travers d'au moins une partie d'un sous-panneau partiel voisin, et chacun des panneaux de plancher comporte au moins trois sous-panneaux (132, 134, 136 ; 132A, 134A, 136A ; 132B, 134B, 136B ; 132C, 134C, 136C ; 132D, 134D, 136D ; 132E, 134E, 136E ; 132F, 134F, 136F), au moins l'un de ces sous-panneaux étant un sous-panneau unitaire (132, 132A, 132B, 132C, 132D, 132E, 132F) et au moins deux de ces sous-panneaux étant des sous-panneaux partiels (134, 136 ; 134A, 136A ; 134B, 136B ; 134C, 136C ; 134D, 136D ; 134E, 136E ; 134F, 136F), et au moins deux sous-panneaux partiels voisins (134A, 136B, 134C, 136D, 134E, 136F) de panneaux de plancher respectifs (130A, 130B, 130C, 130D, 130E, 130F) sont complémentaires de façon à fournir un motif décoratif et/ou une texture de surface essentiellement complet et à apparaître comme un sous-panneau unitaire essentiellement continu, et la première surface (138a) est chanfreinée.

2. Système de plancher conforme à la revendication 1, dans lequel la seconde surface supérieure (138b) est présente là où des sous-panneaux partiels voisins (134A, 136B, 134C, 136D, 134E, 136F) sont

complémentaires de façon à permettre à ces sous-panneaux partiels complémentaires d'apparaître comme une partie d'un sous-panneau unitaire.

3. Système de plancher conforme à l'une quelconque des revendications 1 et 2, dans lequel la première surface supérieure (138a) est présente dans des emplacements dans lesquels des sous-panneaux voisins ne sont pas complémentaires.

4. Système de plancher conforme à l'une quelconque des revendications précédentes, dans lequel chacun des panneaux de plancher comporte en outre au moins une première rainure (138c) subdivisant la seconde surface supérieure en au moins deux sous-surfaces.

5. Système de plancher conforme à la revendication 4, dans lequel la première rainure (138c) sépare les sous-panneaux (132, 134, 136) en les panneaux de plancher (130) correspondants.

6. Système de plancher conforme à la revendication 4 ou 5, dans lequel les premières surfaces supérieures (138a) de panneaux adjacents parmi les panneaux de plancher qui sont au moins au nombre de deux forment une seconde rainure ayant une topographie essentiellement identique à la topographie de la première rainure (138c).

7. Système de plancher conforme à la revendication 6, dans lequel la seconde rainure a en outre essentiellement la même largeur que la première rainure (138c).

8. Système de plancher conforme à l'une quelconque des revendications 4 à 7, dans lequel la première rainure (138c) est une rainure essentiellement en forme de V ou de U.

9. Système de plancher conforme à l'une quelconque des revendications précédentes, dans lequel chacun des panneaux de plancher comprend deux sous-panneaux partiels (134, 136) équipés chacun d'un décor volumique (154H, 154I) et d'un décor de bord (152), les décors de bord (152) des sous-panneaux partiels (134, 136) étant identiques, et les décors de bord étant prévus là où le sous-panneau partiel respectif est positionné pour rencontrer un sous-panneau partiel complémentaire d'un autre panneau de plancher pour apparaître comme un sous-panneau unitaire.

10. Système de plancher conforme à la revendication 9, dans lequel les panneaux de bord (152) sont prévus sur la seconde surface, et les décors volumiques (154H, 154I) sont de préférence différents.

11. Système de plancher conforme à l'une quelconque des revendications précédentes, dans lequel les sous-panneaux partiels voisins (134A, 136B, 134C, 136D, 134E, 136F) sont complémentaires de façon à ce qu'ils fournissent un motif décoratif essentiellement complet, ce motif décoratif étant un décor de grain de bois. 5
12. Système de plancher conforme à l'une quelconque des revendications précédentes, dans lequel la première surface (138a) est présente le long d'une première partie d'au moins un côté de chacun des panneaux de plancher, tandis que la seconde surface (138b) est présente le long d'au moins une seconde partie de ce premier côté. 10
15

20

25

30

35


40

45

50

55

FIG. 1
PRIOR ART






FIG. 3
PRIOR ART




FIG. 4
PRIOR ART




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




Figure 12A




Figure 12B




Figure 13A




Figure 13B




Figure 14A




Figure 14B




Figure 14C




Figure 15A




Figure 15B




Figure 15C




FIG. 15D





FIG. 15E



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 903807 A [0006]
- US 6401415 A [0006]
- US 2057135 A, Cherry [0007]
- US 2046593 A, Urbain [0007]
- US 3946529 A, Chevaux [0008]
- US 5295341 A, Kajiwara [0009]
- US 6101778 A, Martensson [0010]
- US 4131705 A [0014]
- US 2002100231 A [0015]
- US 2002014047 A [0016]