



Office de la Propriété

Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2365971 C 2008/07/08

(11)(21) **2 365 971**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 2000/04/12
(87) Date publication PCT/PCT Publication Date: 2000/10/19
(45) Date de délivrance/Issue Date: 2008/07/08
(85) Entrée phase nationale/National Entry: 2001/09/06
(86) N° demande PCT/PCT Application No.: FI 2000/000308
(87) N° publication PCT/PCT Publication No.: 2000/061907
(30) Priorité/Priority: 1999/04/13 (FI990807)

(51) Cl.Int./Int.Cl. *E21B 19/20* (2006.01),
E21B 19/14 (2006.01), *E21B 19/18* (2006.01)


(72) Inventeurs/Inventors:
HUHDANMAKI, TAPANI, FI;
HAKKINEN, LEO, FI

(73) Propriétaire/Owner:
SANDVIK MINING AND CONSTRUCTION OY, FI

(74) Agent: OGILVY RENAULT LLP/S.E.N.C.R.L.,S.R.L.

(54) Titre : AGENCEMENT DANS UN APPAREIL DE FORAGE DE ROCHES

(54) Title: ARRANGEMENT IN ROCK DRILLING APPARATUS




(57) Abrégé/Abstract:

The invention relates to an arrangement for replacing a drilling component in a rock drilling apparatus, with arrangement comprises a component magazine (12) for storing replaceable components (15) required in drilling and means for driving the drilling unit (5) to a predefined position and location relative to the component magazine. The arrangement further comprises a changing unit (16) for moving the components (15) between the component magazine (12) and the drilling unit (5).

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : E21B 19/20		A1	(11) International Publication Number: WO 00/61907
			(43) International Publication Date: 19 October 2000 (19.10.00)
(21) International Application Number:	PCT/FI00/00308	(81) Designated States:	AE, AG, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date:	12 April 2000 (12.04.00)	(30) Priority Data:	
990807	13 April 1999 (13.04.99)	FI	
(71) Applicant (for all designated States except US):	SANDVIK TAMROCK OY [FI/FI]; Pihtisulunkatu 9, FIN-33330 Tampere (FI).	(72) Inventors; and	
(75) Inventors/Applicants (for US only):	HUHDANMÄKI, Tapani [FI/FI]; Lielahdenkatu 37 C 36, FIN-33410 Tampere (FI). HÄKKINEN, Leo [FI/FI]; Jenseninkatu 27 C 14, FIN-33610 Tampere (FI).	(74) Agent:	KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).
		Published	<i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> <i>In English translation (filed in Finnish).</i>

(54) Title: ARRANGEMENT IN ROCK DRILLING APPARATUS



(57) Abstract

The invention relates to an arrangement for replacing a drilling component in a rock drilling apparatus, with arrangement comprises a component magazine (12) for storing replaceable components (15) required in drilling and means for driving the drilling unit (5) to a predefined position and location relative to the component magazine. The arrangement further comprises a changing unit (16) for moving the components (15) between the component magazine (12) and the drilling unit (5).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ARRANGEMENT IN ROCK DRILLING APPARATUS

The invention relates to an arrangement for changing a drilling component in a rock drilling apparatus comprising a carrier and a boom 5 arranged manoeuvrably to it, to which boom a drilling unit is manoeuvrably arranged, the drilling unit comprising at least a rock drill, a feeding beam and feeding means, and which arrangement further comprises at least one component magazine for storing the drilling components required in drilling and a changing unit for handling the drilling components between the 10 component magazine and the drilling unit.

Extremely heavy stress is directed to a drill bit used in rock drilling, and as a result of it, the drill bit needs occasionally to be changed due to wear and possible damage to it. For efficient rock drilling, a drill bit in good condition is required. In a known solution, the replacing apparatus of the drill bit with its 15 magazine is arranged to the drilling unit. The solution has the drawback, however, that the weight and outer dimensions of the drilling unit necessarily increase in such a solution, whereby handling the drilling unit is difficult and visibility to the object being drilled is poor. A heavy structure requires a robust boom and heavy means for moving the drilling unit, which factors naturally 20 increase the manufacturing costs of the equipment. Further, maintaining the equipment and defining its settings is difficult when the drill bit magazine and the changing unit are arranged tightly to the feeding beam. In addition removing used drill bits and bringing in new ones to the magazine is awkward. Further, it is not in all cases possible to store enough drill bits in the drilling 25 unit, since the weight and outer dimensions of the magazine limit the number of drill bits. Equipment has been developed to solve the above problems, in which equipment the drill bits are already attached to the ends of the drill rods and arranged to a magazine on a carrier. The problem with these solutions is that the rod handling apparatuses require several degrees of freedom in order 30 to be able to move the drill rod with its drill bits from the magazine to the drilling unit. The solution thus requires control of complex movements and the use of expensive and easily damaged components in demanding drilling conditions. Another problem with the solution is that because the drill bits are attached to the drill rods, handling them is awkward due to their large size and 35 weight. In addition, the magazine takes up a lot of space.

It is an object of the present invention to provide a novel arrangement for replacing the drill bit or other drilling component of a rock drill, the invention also avoiding problems occurring in prior art.

The arrangement of the invention is characterized in that the 5 component magazine is arranged to a carrier or boom, separate from the drilling unit, and that the arrangement comprises means for driving the drilling unit to a predefined position and location with respect to the component magazine for replacing the drilling component.

The essential idea of the invention is that the drilling unit with its 10 rock drill and feeding equipment is driven to a predefined location and position with respect to the component magazine for replacing the drilling component. This way, the relative location of the component magazine and the drilling unit driven to a certain replacement position is exactly known. The changing unit is 15 preferably arranged to turn with respect to the carrier or the boom, whereby it is capable of moving the drilling components being replaced between the drilling unit and the magazine. The essential idea of a preferred embodiment of the invention is that the changing unit and the component magazine are arranged to the boom, whereby the movements of the boom do not affect the relative position of the changing unit, component magazine and drilling unit 20 driven to the replacement position. The essential idea of a second preferred embodiment of the invention is that the positioning movements of the changing unit are mechanically restricted.

The invention provides the advantage that replacing the drill bit does not require complex movements of the changing unit, whereby the 25 changing unit can be made structurally simple and, at the same time, reliable. This makes the manufacturing and operational costs of the changing unit low. No complex and fault-sensitive sensor or control apparatuses or an exact control of movements are no longer necessarily needed. The motion speed of simple movements can be made quite high, thus clearly shortening the time 30 needed to replace the drill bit. The solution in question provides the further advantage that when the changing unit and the component magazine are arranged to the carrier or boom, they do not add to the weight and outer dimensions of the drilling unit, thus making handling the equipment easier, allowing a better visibility to the drilling location and in addition, making it 35 possible to design the structures and drives of the drilling unit smaller and, at the same time, less expensive. On the other hand, locating the component

magazine to the boom or carrier allows the use of a larger magazine or of several magazines, thus providing a longer uninterrupted operation time of the drilling unit.

According to a still further broad aspect of the present invention there is provided an arrangement for replacing a drilling component in a rock drilling apparatus. The arrangement comprises a carrier and a boom arranged manoeuvrably to it, and to which boom a drilling unit is manoeuvrably arranged. The drilling unit comprises at least a rock drill, a feeding beam and feeding means. The arrangement further comprises at least one component magazine for storing drilling components required in drilling and a changing unit for handling the drilling components between the component magazine and the drilling unit. The arrangement is characterized in that the component magazine is arranged to the carrier or the boom, separate from the drilling unit, and that the arrangement comprises means for driving the drilling unit to a predefined position and location with respect to the component magazine for replacing a drilling component.

The invention is described in greater detail in the attached drawings, in which Figures 1a and 1b show schematic views of rock drilling apparatuses to which the arrangement of the invention for replacing a drilling component has been applied, and

Figures 2a and 2b show schematic views of the principle of installing a drill 20 cuttings pipe used in rock drilling.

Figure 1a shows a very simplified view of a part of a rock drilling apparatus in which the application of the solution of the invention is particularly advantageous. It should be noted that in this application, a drilling component refers not only to drill bits but also, for instance, to drill cuttings pipes described later in Figures 2a and 2b 25 and the means required for their installation, as well as other possible components required in drilling and handled with the changing unit. The rock drilling apparatus shown in the figure comprises a manoeuvrable carrier 1 with its control cabin 2 and necessary auxiliary apparatuses. A boom 4 which can be lifted and lowered by means of a hydraulic cylinder 3 is arranged to the carrier 1. The boom 4 is preferably 30 forked, i.e. it comprises two beams longitudinal to the carrier 1 at a distance from each other, which can be lowered against the ground during drilling and

correspondingly lifted up at least when the rock drilling equipment is moved. For clarity's sake, the figure shows only the hindmost beam of the boom and the cross-section of a transverse beam 4a connecting the beams. An actual drilling unit 5 comprising at least a rock drill 7, a feeding beam 6 and other feeding means is 5 arranged to the boom 4, preferably close to its free end. In the figure, the drilling unit is partly marked with a dashed line. The rock drill 7 is fed by means of hydraulic cylinders, for instance, in the longitudinal direction of the feeding beam 6. The drilling unit 5 can be moved in many different ways relative to the boom 4. Firstly, the entire 10 drilling unit can be turned with a hydraulic motor, for instance, in direction A relative to a horizontal first axis 8. Further, it can be lifted and lowered in direction B by means of a lifting apparatus 9 of the drilling unit, such as a hydraulic cylinder. The drilling unit can also be tilted forward and backward relative to the boom 4 in direction C shown in the figure by means of a tilting cylinder 10 and, further, tilted in the

transverse direction D of the rock drill by means of other tilting cylinders not shown herein for clarity's sake. By means of the above moving means, the drilling unit can be directed in a desired manner, whereby it can be used to drill holes in a versatile manner to the ceiling, walls or floor of tunnels, for instance.

5 Keeping the drilling unit in position can be ensured by pressing separate supports against the surface being drilled during drilling. Further, rock bolting or charging equipment can be arranged to the feeding beam, which can be moved to the drilled hole by indexing, for instance, immediately after the drill bit with the drill rod has been moved aside. For drill rods needed in extension 10 rod drilling, a rod drill magazine 11 is preferably arranged to the drilling unit, from which the rods can be connected consecutively to each other by suitable automatic means and to which the drill rods detached from the drill rod system can correspondingly be stored in a manner known per se.

In extension rod drilling, a dulled drill bit is normally replaced when 15 a new hole is started, because then the extension rod combination must in any case be dismantled. When a drill bit is damaged during drilling, the extension rods are dismantled and the drilling unit is driven to the replacement position. After replacing the drill bit, the drilling of the unfinished hole can in most cases be continued, in which case the drilling unit is driven by means of boom control 20 automatics back to the drill hole.

The drill bit replacement is now according to the invention arranged in such a manner that a component magazine 12 is arranged to the boom for the drill bits to be replaced, which magazine can preferably be turned around its axis in direction E and to which magazine drill bits or other necessary 25 components can be stored in a simple manner. Other types of magazines, such as chain-like magazines, can naturally be used, as desired. The magazine shown in the figure can at its simplest be made up of a disciform body 13 on whose periphery pins or corresponding protrusions 14 are arranged, to which the components 15 can be arranged by means of their 30 inner holes. This way, it is easy to grip the outer periphery of the components with a gripping device of the changing unit or another similar handling apparatus. The magazine 12 is preferably arranged in the space between the forks of the boom 4, where it is safe from battering and where it, on the other hand, in no way obstructs visibility or adds to the outer dimensions of the rock 35 drilling apparatus. Because the magazine 12 is not arranged to the drilling unit, the magazine can be made larger, whereby more components than before fit

into it. Further, according to the idea of the invention, a changing unit 16 is arranged to the rock drilling apparatus, the changing unit being a kind of a manipulator capable of moving drilling components 15 between the component magazine 12 and the drilling unit 5. The drilling unit is driven to a predefined replacement position for the replacement of components. In modern rock drilling apparatuses, it is known to use automatic, for instance numeric, control means for directing and controlling the boom and the drilling unit automatically according to an exactly designed drilling program. Such a control can now also be utilised when driving the drilling unit to the replacement position. Because the relative position of the component magazine 12 and the drilling unit 5 is exactly known in the replacement position, and further, because the drilling unit is at this point in any case positioned in an advantageous position with respect to replacement, well within the reach of the changing unit, the changing unit 16 need necessarily not move other than relative to the two movement axes, i.e. a minimum of two degrees of freedom is enough. The figure therefore shows a changing unit comprising an arm 17 articulated turnably to the boom at its other end, which arm can be lengthened and shortened in direction F. At the free end of the arm 17, there is a gripping device 18 for gripping the components being handled preferably at their outer periphery. The changing unit 16 can be turned relative to a horizontal turning joint 19 in direction G by means of a hydraulic cylinder 20 or a corresponding actuator, for instance.

The drilling component is replaced in such a manner that the drill rod combination is in the usual manner dismantled automatically rod by rod into the drill rod magazine. Screw joints are usually used between the rods so that the joint can be opened by turning the rock drill. If necessary, the rock drill can be used to hammer open stuck joints. When the last of the drill rods and the drill bit at its end has been pulled out of the drilled hole, the drilling unit 5 is driven to the replacement position for replacing the drill bit, at which stage its position, that is, its location and position, is exactly known at least in relation to the magazine 12. The drilling unit is preferably driven into an upright position, in which case taking the components from the magazine and arranging them for connection to the drilling unit can take place without changing the position of the gripping device. If the gripping device 18 of the changing unit 16 is made turnable, the replacing can also be done when the drilling unit is driven horizontal in relation to the carrier or into a certain angle position. The altitude

of the drilling unit should also preferably be arranged in the replacement position in such a manner that the changing unit can replace the component advantageously with respect to the movements of the changing unit. The turning motion of the changing unit is easily restricted by mechanical means, 5 for instance, to a desired position, in which case no separate movement adjustments or sensorings are needed. The lower position of the changing unit arm 17 can also be mechanically restricted with respect to the component magazine 12, in which case the changing unit is arranged to turn along a predefined path between its mechanically restricted extreme positions. 10 Further, the change of the arm's length can be mechanically restricted in the extreme positions by means of a rod 17a, for instance, since the distance between the changing unit and the magazine 12 and also between the changing unit and the drilling unit 5 is known in advance. When the positioning movements of the changing unit are arranged as simple as possible in this 15 manner, without a need for exact adjustment of the movements, the structure and operation of the changing unit can be implemented in a very simple manner by applying conventional components which have been proven reliable. It is then not necessary to use complex adjustment and measurement equipment. In addition, the movements of the changing unit can be fast.

20 The changing unit removes the drill bit from the drill shank 28 and takes it to the component magazine, from which it at the same time takes a new drill bit and takes it to the drilling unit. The drilling component is positioned by means of the changing unit in direction H of the movement axis of the rock drill 7 feed, whereby connecting the drilling component to the drill shank can 25 be done by turning the drill to close the screw joint between the component and the shank. The drill bit is moved by means of the feeding movement of the drill to the end of the feeding beam, to which means have been arranged for keeping a drill bit brought to them in place after the drill bit is detached from the drill shank. After this, the rock drill is driven back to its starting position, 30 and an extension rod can be arranged between the drill bit and the shank. As many extension rods as are required for the current drilling are arranged between the drill bit and the rock drill. Further, it is possible to arrange the changing unit in such a manner that it can take the drill bit directly to the end of the feeding beam for hold, whereby the operation of the equipment becomes 35 faster.

In addition to the solution shown in Figure 1a, it is possible to arrange both the changing unit and the component magazine to the carrier, in which case the location of the changing unit and the magazine are known regardless of the position of the boom. The changing unit can also be 5 arranged to the carrier and the magazine to the boom, or vice versa. In the latter case, the position of the changing unit with respect to the magazine and the control data required for using the changing unit are obtained by means of suitable positioning sensors, for instance. In all cases, the drilling unit is positioned to the replacement position according to the magazine. Depending 10 on the fixing point of the changing unit and the magazine, the movement of the changing unit between the magazine and the drilling unit is controlled either by fixed restrictors or on the basis of information provided by suitable positioning sensors.

Figure 1b shows a solution in which the changing unit 16 is 15 arranged to the drilling unit 5. The changing unit 16 can then be articulated to the feeding beam 6, for instance, in which case it can take components 15 from the component magazine 12 and take them directly to the end of the feeding beam for hold. A drilling component 15 taken for hold at the end of the feeding beam is shown by a dashed line. For clarity's sake, the figure does not 20 show the actuators used in turning the changing unit 16. This kind of a solution provides the advantage that when a drilling component 15 is taken for hold, the changing unit 16 can be turned without any complex control, since the relative position of the changing unit and the hold station is exactly known and substantially unchanging. Further, because the drilling unit is according to the 25 inventive idea driven to a predefined position and location with respect to the component magazine 12 for replacing the drilling component, the position of the changing unit with respect to the component magazine in replacement position is also exactly known.

Figure 2a shows the principle of a drill cuttings pipe arranged in a 30 drill hole. The task of the drill cuttings pipe 21 is to prevent drill cuttings 22, i.e. rock chippings created during drilling, brought up by means of a drilling medium during a downward or downward slanting drilling from flowing back down the drilled hole. The drill cuttings pipe in a way forms a high collar around the drilled hole. For installing the drill cuttings pipe 21, a start hole 23 is 35 drilled with a drill bit larger than the actual hole, after which the drill cuttings pipe is partly pushed into the hole as shown in Figure 2b. The inner diameter

of the drill cuttings pipe 21 is naturally designed so that the actual drill bit 24 with its extension rods 25a to 25c can be pushed through it to drill the actual drilling hole 26. This kind of a drill cuttings pipe is typically installed manually, which is slow and awkward and thus not suitable for modern rock drilling. The 5 solution of the invention now also provides an improvement to the installation of drill cuttings pipes. A drill bit with a larger diameter for drilling the hole for the drill cuttings pipe can be stored in and replaced from the component magazine, and a suitable tool for installing the drill cuttings pipe can be arranged on the drill shank after drilling the hole for the drill cuttings pipe. After 10 this, the changing unit fetches the drill cuttings pipe to be installed and brings it to the tool connected to the drill shank, the tool being a kind of a plunger 27, and after this, the drill cuttings pipe 21 brought to the plunger for installation is pushed into the hole 23 by means of the rock drill feeding apparatus. The plunger is then taken back by the changing unit and drilling is continued as 15 usual through the drill cuttings pipe.

It is possible to have more than one magazine, for instance two: a first magazine for the tools, i.e. the drill bits and the plunger for the drill cuttings pipe, and a second magazine for the drill cuttings pipes. The magazines can be as shown in Figure 1a, for instance, and they can be 20 arranged side by side in the space between the boom forks as seen from the front of the rock drill. In such a case, there is also a vertical turning joint with the turning joint 19 of the changing unit so that the changing unit can also turn in sideward direction of the rock drilling apparatus. The sideward movement of the changing unit can also be restricted in its extreme positions. On the other 25 hand, the magazines can be arranged in such a manner that the magazine needed at each time for handling the components is driven to a certain location where the changing unit can handle the components in the magazine. This location of the magazine is also the point according to which the drilling unit is positioned in its replacement position.

30 The drawings and the description related to them are only intended to illustrate the idea of the invention. The invention may vary in detail within the scope of the claims. Thus, the boom of the rock drill or the drilling unit need not be exactly as described in the figures, but the invention can be applied to other kinds of rock drilling apparatuses. Further, differing from what 35 is shown in the figure, the changing unit can be arranged to turn horizontally only, in which case the component magazine can be arranged to the carrier

behind the control cabin, for instance. Replacing components with the changing unit then requires at its simplest only turning the changing unit to a certain angle horizontally and lengthening its arm. It should also be noted that the solution of the invention can well be applied to other situations than just to
5 replacing drill bits or the like in extension rod drilling. The arrangement of the invention thus does not necessarily at all comprise a drill rod cartridge or it may be located elsewhere than with the drilling unit.

CLAIMS

1. An arrangement for replacing a drilling component in a rock drilling apparatus comprising a carrier (1) and a boom (4) arranged manoeuvrably to it, to which boom a drilling unit (5) is manoeuvrably arranged, the drilling unit comprising at least a rock drill (7), a feeding beam (6) and feeding means, and which arrangement further comprises at least one component magazine (12) for storing drilling components required in drilling and a changing unit (16) for handling the drilling components (15) between the component magazine (12) and the drilling unit (5), characterized in that the component magazine (12) is arranged to the carrier (1) or boom (4), separate from the drilling unit (5), and that the arrangement comprises means for driving the drilling unit (5) to a predefined position and location with respect to the component magazine (12) for replacing a drilling component (15).
2. An arrangement as claimed in claim 1, characterized in that the changing unit (16) is arranged to the carrier (1) or boom (4).
3. An arrangement as claimed in claim 1 or 2, characterized in that the changing unit (16) is arranged to turn relative to its turning joint (19) between the component magazine (12) and the drilling unit (5), that the changing unit (16) comprises an arm (17) capable of being lengthened or shortened, and that the free end of the arm comprises a gripping device (18) for gripping the drilling components.
4. An arrangement as claimed in any one of claims 1 to 3, characterized in that the component magazine (12) and the changing unit (16) are arranged to the boom (4), whereby the relative position of the component magazine, changing unit and drilling unit is independent of the position of the boom.
5. An arrangement as claimed in claim 4, characterized in that the movements of the changing unit (16) are mechanically restricted according to the relative position of

the predefined replacement position of the drilling unit (5) and the component magazine (12).

6. An arrangement as claimed in claim 1, characterized in that the changing unit (16) is arranged to the drilling unit (5) and that the changing unit (16) is arranged to handle the drilling components (15) between the component magazine (12) and a hold station at the end of the feeding beam (6).
7. An arrangement as claimed in any one of claims 1 to 6, characterized in that the component magazine (12) comprises a turnable disciform body (13) on the periphery of which protrusions (14) are arranged for fastening the drilling components (15).
8. An arrangement as claimed in any one of claims 1-7, characterized in that the boom (4) comprises two beams longitudinal to the rock drilling apparatus at a distance from each other and that the component magazine (12) and the changing unit (16) are arranged between the beams of the boom.

1/3




FIG. 1a

2/3




FIG. 1b

3/3

