

JAMES B. R. HARDEMAN.

Buckles.

No. 128,037.

Patented June 18, 1872.

Fig. 1





Fig. 2



Witnesses:

Chas. Nida.
H. A. Graham.

Inventor:

J. B. R. Hardeman

PER

Munn & Co.
Attorneys.

UNITED STATES PATENT OFFICE.

JEROME B. R. HARDEMAN, OF TEHUACANA, TEXAS, ASSIGNOR TO HIMSELF
AND E. W. FOSTER, OF SAME PLACE.

IMPROVEMENT IN BUCKLES.

Specification forming part of Letters Patent No. 128,037, dated June 18, 1872.

Specification describing a new and Improved Buckle, invented by JEROME B. R. HARDEMAN, of Tehuacana, in the county of Limestone and State of Texas.

This invention relates to a new buckle, which is provided with two tongues on the same pivot, and with a guard for securing the same and the straps in position, thereby producing a simple and reliable means of connecting two straps.

In the accompanying drawing, Figure 1 represents a top view, and Fig. 2 a longitudinal section of my improved buckle.

Similar letters of reference indicate corresponding parts.

A in the drawing represents the frame of the buckle, of rectangular or other form. B is the pivot for the two tongues *a* and *b*, it being a rigid cross-bar in the frame. Another such cross-bar, *d*, is also formed in the frame, as shown. The tongue *a* is plain and short, and rests on the end of the frame. The tongue *b* is a forked wire, with a vertical prong, *e*, at the outer end, said end fitting through the

slotted end pieces *f* of the frame. *g* is a guard or cross-piece above the middle of the frame.

One strap, C, is drawn through the slotted piece *f*, laid around the cross-bar *d*, and then again drawn through the piece *f*, as in Fig. 2. The prong *e* of the tongue *b* is then let down through it and the piece *f*. The other strap, D, is buckled by the tongue *a* in the ordinary manner, and then drawn under the guard *g*, so as to rest on the tongue *b* and hold it down, preventing it from being raised out of the strap C.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

The buckle-frame A, provided with cross-pieces B *d*, slotted end piece *f*, tongues *a* *b*, and guard *g*, all arranged to operate substantially as herein shown and described.

JEROME B. R. HARDEMAN.

Witnesses:

R. H. WADE,
J. T. HAY.