



US009286138B2

(12) **United States Patent**
Busaba et al.

(10) **Patent No.:** **US 9,286,138 B2**
(45) **Date of Patent:** ***Mar. 15, 2016**

(54) **MAJOR BRANCH INSTRUCTIONS**

(71) Applicant: **INTERNATIONAL BUSINESS MACHINES CORPORATION**, Armonk, NY (US)

(72) Inventors: **Fadi Y. Busaba**, Poughkeepsie, NY (US); **Steven R. Carlough**, Wappingers Falls, NY (US); **Christopher A. Krygowski**, Lagrangeville, NY (US); **Brian R. Prasky**, Wappingers Falls, NY (US); **Chung-Lung K. Shum**, Wappingers Falls, NY (US)

(73) Assignee: **INTERNATIONAL BUSINESS MACHINES CORPORATION**, Armonk, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 210 days.
This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/678,185**

(22) Filed: **Nov. 15, 2012**

(65) **Prior Publication Data**

US 2013/0198496 A1 Aug. 1, 2013

Related U.S. Application Data

(63) Continuation of application No. 13/362,574, filed on Jan. 31, 2012.

(51) **Int. Cl.**
G06F 9/30 (2006.01)
G06F 9/40 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G06F 9/528** (2013.01); **G06F 9/3005** (2013.01); **G06F 9/30145** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC G06F 9/3842; G06F 9/3851; G06F 9/46; G06F 9/466; G06F 9/467
USPC 712/235
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,833,599 A 5/1989 Colwell et al.
5,809,294 A 9/1998 Ando

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0725334 A1 7/1996

OTHER PUBLICATIONS

Oplinger, "Enhancing Software Reliability with Speculative Threads", a Ph. D. thesis, 2004, Stanford University, pp. 1-125.*
(Continued)

Primary Examiner — Andrew Caldwell


Assistant Examiner — Yuqing Xiao

(74) *Attorney, Agent, or Firm* — Margaret McNamara, Esq.; Blanche E. Schiller, Esq.; Heslin Rothenberg Farley & Mesiti P.C.

(57) **ABSTRACT**

Major branch instructions are provided that enable execution of a computer program to branch from one segment of code to another segment of code. These instructions also create a new stream of processing at the other segment of code enabling execution of the other segment of code to be performed in parallel with the segment of code from which the branch was taken. In one example, the other stream of processing starts a transaction for processing instructions of the other stream of processing.

14 Claims, 15 Drawing Sheets



- (51) **Int. Cl.**
G06F 9/46 (2006.01)
G06F 9/52 (2006.01)
G06F 9/38 (2006.01)
G06F 9/32 (2006.01)

- (52) **U.S. Cl.**
 CPC **G06F 9/322** (2013.01); **G06F 9/3804**
 (2013.01); **G06F 9/3842** (2013.01); **G06F**
9/3851 (2013.01); **G06F 9/46** (2013.01); **G06F**
9/466 (2013.01); **G06F 9/467** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,812,811	A *	9/1998	Dubey et al.	712/216
6,691,221	B2	2/2004	Joshi et al.	
7,124,282	B2	10/2006	Zandveld et al.	
7,134,124	B2 *	11/2006	Ohsawa et al.	718/100
7,299,343	B2	11/2007	Kalluri et al.	
7,577,827	B2	8/2009	Hoogerbrugge	
7,877,585	B1	1/2011	Coon et al.	
7,930,695	B2	4/2011	Chaudhry et al.	
8,473,950	B2 *	6/2013	Flood et al.	718/101
8,949,583	B1 *	2/2015	Tene et al.	712/228
2002/0147760	A1 *	10/2002	Torii	709/107
2003/0018826	A1	1/2003	Chaudhry et al.	
2004/0103410	A1	5/2004	Sakai	
2005/0125645	A1 *	6/2005	Rudd et al.	712/239
2006/0149944	A1 *	7/2006	Eisen et al.	712/235
2007/0240158	A1	10/2007	Chaudhry et al.	
2008/0288730	A1	11/2008	Heller, Jr. et al.	
2009/0031310	A1 *	1/2009	Lev et al.	718/101
2009/0217020	A1	8/2009	Yourst	
2010/0082952	A1	4/2010	Sunayama	
2010/0162247	A1 *	6/2010	Welc et al.	718/101
2010/0205408	A1 *	8/2010	Chung et al.	712/216
2010/0269102	A1 *	10/2010	Latorre et al.	717/130
2011/0246993	A1	10/2011	Moir et al.	

OTHER PUBLICATIONS

Shen et al., "Modern Processor Design fundamentals of superscalar processors", Oct. 2002, McGraw-Hill Companies, Inc., Beta ed., pp. 457-468.*

International Search Report and Written Opinion for PCT/EP2013/051227 dated Apr. 22, 2013, pp. 1-8.
 Busaba, Fadi Y. et al., "Major Branch Instructions with Transactional Memory," U.S. Appl. No. 13/362,513, dated Jan. 31, 2012, pp. 1-70.
 Busaba, Fadi Y. et al., "Major Branch Instructions with Transactional Memory," U.S. Appl. No. 13/678,217, dated Nov. 15, 2012, pp. 1-64.
 Busaba, Fadi Y. et al., "Major Branch Instructions," U.S. Appl. No. 13/362,574, dated Jan. 31, 2012, pp. 1-69.
 Mameesh et al., "Speculative-Aware Execution: A Simple and Efficient Technique for Utilizing Multi-Cores to Improve Single-Thread Performance," PACT '10, Sep. 11-15, 2010, pp. 421-430.
 Stark, Jared Warner, IV, "Out-of-Order Fetch, Decode, and Issue," University of Michigan, 2000 (no further date information available), pp. 1-282.
 Office Action for U.S. Appl. No. 13/678,217, dated Oct. 20, 2014, 25 pages.
 Herlihy et al., "Transactional Memory: Architectural Support for Lock-Free Data Structures," May 1993, Proceedings of the 206th Annual International Symposium on Computer Architecture, pp. 289-300.
 Office Action for U.S. Appl. No. 13/362,513, dated Oct. 24, 2014, 28 pages.
 Office Action for U.S. Appl. No. 13/362,574, dated Nov. 19, 2014, 24 pages.
 Oplinger, Jeffrey, "Enhancing Software Reliability with Speculative Threads," Ph.D. Thesis, Aug. 2004, Stanford University, pp. 1-125.
 "Intel® 64 and IA-32 Architectures Software Developer's Manual vol. 1," Order No. 253665-022US, Nov. 2006, 486 pages.
 "Intel® 64 and IA-32 Architectures Software Developer's Manual vol. 2A," Order No. 253666-022US, Nov. 2006, 744 pages.
 "Intel® Itanium® Architecture Software Developer's Manual vol. 1," Jan. 2006, 250 pages.
 "Intel® Itanium® Architecture Software Developer's Manual vol. 2," Jan. 2006, 653 pages.
 "Intel® Itanium® Architecture Software Developer's Manual vol. 3," Jan. 2006, 986 pages.
 "z/Architecture® Principles of Operation," IBM® Publication No. SA22-7932-08, Ninth Edition, Aug. 2010, 1496 pages.
 Final Office Action for U.S. Appl. No. 13/678,217 dated Feb. 4, 2015, pp. 1-23.
 Final Office Action for U.S. Appl. No. 13/362,513 dated Feb. 24, 2015, pp. 1-37.
 Final Office Action for U.S. Appl. No. 13/362,574 dated Apr. 13, 2015, pp. 1-27.

* cited by examiner




FIG. 1A




FIG. 1B






FIG. 1C






FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6

COMPUTER
PROGRAM
PRODUCT
700




FIG. 7




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13

MAJOR BRANCH INSTRUCTIONS

This application is a continuation of co-pending U.S. Ser. No. 13/362,574 entitled, "MAJOR BRANCH INSTRUCTIONS," filed Jan. 31, 2012, which is hereby incorporated herein by reference in its entirety.

BACKGROUND

An aspect of the invention relates, in general, to computer programs, and in particular, to branch instructions used within computer programs.

A computer program (a.k.a., program or application) is a sequence of instructions written to perform a specific task within a computing environment. Each instruction performs a particular operation, such as add, subtract, move, shift, compare, store, and load, to name just a few examples. The instructions are fetched by a processor in sequential order, unless a particular instruction directs the processing to continue at a different location. For instance, instead of fetching the next sequential instruction, a branch instruction may direct the processor to fetch an instruction at a different location in the program. On average, a program has a branch every four to five instructions.

In some computer micro-architectures, an instruction is executed to completion before the next instruction begins. However, in other micro-architectures, pipelining is used to increase the number of instructions that can be concurrently executed. In pipelining, the processing of an instruction is split into a plurality of independent steps, such as fetch, decode, dispatch, issue, execute and complete, as well as potentially others, which are executed in a pipeline. As the first step of the instruction (e.g., fetch) completes in the pipeline, then another instruction may begin, and so forth.

Pipelining also facilitates the execution of instructions out-of-order from their position in the program. For instance, the issue step has associated therewith an issue queue, which receives instructions in-order of the program. The issue queue is responsible for holding each instruction until the data (e.g., operands) needed by the instruction is available, and then it issues the instruction for execution. If the data for one instruction is available prior to the data for another instruction, then the one instruction can be sent out for execution before the other instruction (out-of-order processing), even if the other instruction is first in the program. For example, if instructions A, B and C are to be executed, where A is the oldest and C is the youngest, if B is dependent on A, and C is not dependent on A or B, then the instructions can be issued in the order of A, C, B, thereby utilizing the pipeline at a higher rate and allowing instructions to be processed faster.

The out-of-order processing, however, is constrained by an out-of-order window/queue of a finite size in which instructions may be processed out-of-order. The issue window is typically 100 or less instructions and the reorder window, which re-orders the instructions back into its original order, is typically 200 or less instructions, where the 100 is a subset of the 200.

BRIEF SUMMARY

Shortcomings of the prior art are overcome and advantages are provided through the provision of a method of executing a machine instruction. The method includes, for instance, obtaining, by a processor, a machine instruction for execution, the machine instruction being defined for computer execution according to a computer architecture, the machine instruction including: at least one opcode field for specifying

an opcode, the opcode defining a branch operation; and at least one field for determining a target location in which to branch; and executing the machine instruction in a first stream of processing, the executing including: starting a second stream of processing, the second stream of processing having a relationship with the first stream of processing and is to execute one or more instructions starting at the target location defined using the at least one field of the machine instruction, the one or more instructions being out of sequential execution order from one or more instructions being processed by the first stream of processing, the first stream of processing continuing to process one or more instructions subsequent to the machine instruction; and wherein execution of the second stream of processing is speculative in that at least one instruction of the one or more instructions of the second stream of processing is executed even though reaching the at least one instruction of the second stream of processing by processing of the first stream is tentative, and wherein updating of architected state by one or more instructions of the second stream of processing is performed based on the first stream of processing reaching a predefined point in processing.

Computer program products and systems relating to one or more aspects of the present invention are also described and may be claimed herein. Further, services relating to one or more aspects of the present invention are also described and may be claimed herein.

Additional features and advantages are realized through the techniques of the present invention. Other embodiments and aspects of the invention are described in detail herein and are considered a part of the claimed invention.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

One or more aspects of the present invention are particularly pointed out and distinctly claimed as examples in the claims at the conclusion of the specification. The foregoing and objects, features, and advantages of one or more aspects of the invention are apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

FIG. 1A depicts one embodiment of a computing environment to incorporate and use one or more aspects of the present invention;

FIG. 1B depicts another embodiment of a computing environment to incorporate and use one or more aspects of the present invention;

FIG. 1C depicts further details of the memory of FIG. 1B, in accordance with an aspect of the present invention;

FIG. 2A depicts one example of an existing design of an instruction pipeline;

FIG. 2B depicts one example of another design of an instruction pipeline, in accordance with an aspect of the present invention;

FIG. 3 depicts an example of a portion of a program that includes one or more branches, in accordance with an aspect of the present invention;

FIG. 4A depicts one example of a format of a generic branch instruction, in accordance with an aspect of the present invention;

FIG. 4B depicts another example of a format of a generic branch instruction, in accordance with an aspect of the present invention;

FIG. 5 depicts one example of logic associated with processing major branches, in accordance with an aspect of the present invention;

FIG. 6 depicts one example of logic associated with processing major branches with transactional memory, in accordance with an aspect of the present invention;

FIG. 7 depicts one embodiment of a computer program product incorporating one or more aspects of the present invention;

FIG. 8 depicts one embodiment of a host computer system to incorporate and use one or more aspects of the present invention;

FIG. 9 depicts a further example of a computer system to incorporate and use one or more aspects of the present invention;

FIG. 10 depicts another example of a computer system comprising a computer network to incorporate and use one or more aspects of the present invention;

FIG. 11 depicts one embodiment of various elements of a computer system to incorporate and use one or more aspects of the present invention;

FIG. 12A depicts one embodiment of the execution unit of the computer system of FIG. 11 to incorporate and use one or more aspects of the present invention;

FIG. 12B depicts one embodiment of the branch unit of the computer system of FIG. 11 to incorporate and use one or more aspects of the present invention;

FIG. 12C depicts one embodiment of the load/store unit of the computer system of FIG. 11 to incorporate and use one or more aspects of the present invention; and

FIG. 13 depicts one embodiment of an emulated host computer system to incorporate and use one or more aspects of the present invention.

DETAILED DESCRIPTION

Programs are written in code (e.g., source code), which includes the individual instructions to be executed. There are segments (also referred to as portions, regions, etc.) of code which are not dependent on each other, however, the starting/entry points of these segments are separated by greater than the hardware out-of-order window. Since they are separated, as per the number of executed instructions between the two points, by greater than the out-of-order window, existing branches, referred to herein as minor branches, cannot be reached in a timely manner within the out-of-order window of the first segment to execute instructions of the second segment out-of-order with respect to the first segment. To address this, major branches are provided, in accordance with an aspect of the present invention, to branch from one segment of code to another segment of code to allow a larger out-of-order window than what can be seen by hardware alone (i.e., the amount of code that can be spanned to enter the out-of-order window/queue is larger, although the out-of-order window/queue remains the same physical size (e.g., supporting 100 instructions; the 100 instructions coming from multiple threads of instruction, as discussed below)).

In accordance with an aspect of the present invention, major branch instructions are provided that enable execution to branch from one segment of code to another segment of code. These instructions create a new stream or thread of execution at the other segment of code enabling execution of the other segment of code to be in parallel with the segment of code from which the branch was taken.

In one example, execution of the new stream is speculative in that it is not known whether processing of the first stream will actually reach the instructions of the new stream (i.e., the first stream reaching the new stream is tentative). It is possible that one or more instructions of the new stream are executed,

but processing of the first stream takes a different path and does not reach the new stream.

One embodiment of a computing environment to incorporate and use one or more aspects of the present invention is described with reference to FIG. 1A. A computing environment **100** includes, for instance, a processor **102** (e.g., a central processing unit), a memory **104** (e.g., main memory), and one or more input/output (I/O) devices and/or interfaces **106** coupled to one another via, for example, one or more buses **108** and/or other connections.

In one example, processor **102** is a z/Architecture® processor which is part of a System z® server offered by International Business Machines Corporation (IBM®), Armonk, N.Y. The System z® server implements the z/Architecture®, which specifies the logical structure and functional operation of the computer. One embodiment of the z/Architecture® is described in an IBM® publication entitled, “z/Architecture Principles of Operation,” IBM® Publication No. SA22-7832-08, Ninth Edition, August, 2010, which is hereby incorporated herein by reference in its entirety. In one example, the processor executes an operating system, such as z/OS®, also offered by International Business Machines Corporation. IBM®, z/Architecture® and z/OS® are registered trademarks of International Business Machines Corporation, Armonk, N.Y., USA. Other names used herein may be registered trademarks, trademarks, or product names of International Business Machines Corporation or other companies.

Another embodiment of a computing environment to incorporate and use one or more aspects of the present invention is described with reference to FIG. 1B. In this example, a computing environment **120** includes, for instance, a native central processing unit **122**, a memory **124**, and one or more input/output devices and/or interfaces **126** coupled to one another via, for example, one or more buses **128** and/or other connections. As examples, computing environment **120** may include a PowerPC® processor, a pSeries® server or an xSeries® server offered by International Business Machines Corporation, Armonk, N.Y.; an HP Superdome with Intel Itanium II® processors offered by Hewlett Packard Co., Palo Alto, Calif.; and/or other machines based on architectures offered by IBM®, Hewlett Packard, Intel, Sun Microsystems or others. PowerPC®, pSeries® and xSeries® are registered trademarks of International Business Machines Corporation, Armonk, N.Y., USA. Intel® and Itanium II® are registered trademarks of Intel Corporation, Santa Clara, Calif.

Native central processing unit **122** includes one or more native registers **130**, such as one or more general purpose registers and/or one or more special purpose registers used during processing within the environment. These registers include information that represents the state of the environment at any particular point in time.

Moreover, native central processing unit **122** executes instructions and code that are stored in memory **124**. In one particular example, the central processing unit executes emulator code **132** stored in memory **124**. This code enables the computing environment configured in one architecture to emulate another architecture. For instance, emulator code **132** allows machines based on architectures other than the z/Architecture®, such as PowerPC® processors, pSeries® servers, xSeries® servers, HP Superdome servers or others, to emulate the z/Architecture® and to execute software and instructions developed based on the z/Architecture®.

Further details relating to emulator code **132** are described with reference to FIG. 1C. Guest instructions **150** comprise software instructions (e.g., machine instructions) that were developed to be executed in an architecture other than that of

native CPU **122**. For example, guest instructions **150** may have been designed to execute on a z/Architecture® processor **102**, but instead are being emulated on native CPU **122** (which may be, for example, an Intel® Itanium II® processor). In one example, emulator code **132** includes an instruction fetching unit **152** to obtain one or more guest instructions **150** from memory **124**, and to optionally provide local buffering for the instructions obtained. It also includes an instruction translation routine **154** to determine the type of guest instruction that has been obtained and to translate the guest instruction into one or more corresponding native instructions **156**. This translation includes, for instance, identifying the function to be performed by the guest instruction and choosing the native instruction to perform that function.

Further, emulator **132** includes an emulation control routine **160** to cause the native instructions to be executed. Emulation control routine **160** may cause native CPU **122** to execute a routine of native instructions that emulate one or more previously obtained guest instructions and, at the conclusion of such execution, return control to the instruction fetch routine to emulate the obtaining of the next guest instruction or a group of guest instructions. Execution of the native instructions **156** may include loading data into a register from memory **124**; storing data back to memory from a register; or performing some type of arithmetic or logic operation, as determined by the translation routine.

Each routine is, for instance, implemented in software, which is stored in memory and executed by the native central processing unit **122**. In other examples, one or more of the routines or operations are implemented in firmware, hardware, software or some combination thereof. The registers of the emulated processor may be emulated using registers **130** of the native CPU or by using locations in memory **124**. In embodiments, the guest instructions **150**, native instructions **156** and emulator code **132** may reside in the same memory or may be disbursed among different memory devices.

As used herein, firmware includes, e.g., the microcode, millicode and/or macrocode of the processor. It includes, for instance, the hardware-level instructions and/or data structures used in implementation of higher level machine code. In one embodiment, it includes, for instance, proprietary code that is typically delivered as microcode that includes trusted software or microcode specific to the underlying hardware and controls operating system access to the system hardware.

In one example, a guest instruction **150** that is obtained, translated and executed is a branch instruction described herein. The instruction, which is a z/Architecture® instruction in this example, is fetched from memory, translated and represented as a sequence of native instructions **156** (e.g., PowerPC®, pSeries®, xSeries®, Intel®, etc.) which are executed.

In another embodiment, one or more of the instructions are executed in another architecture environment, including, for example, an architecture as described in the “Intel® 64 and IA-32 Architectures Software Developer’s Manual Volume 1,” Order No. 253665-022US, November 2006; “Intel® 64 and IA-32 Architecture Software Developer’s Manual Volume 2A,” Order No. 253666-022US, November 2006; the “Intel® Itanium® Architecture Software Developer’s Manual Volume 1,” Doc. No. 245317-005, January 2006; the “Intel® Itanium® Architecture Software Developer’s Manual Volume 2,” Doc. No. 245318-005, January 2006; and/or the “Intel® Itanium® Architecture Software Developer’s Manual Volume 3,” Doc. No. 245319-005, January 2006; each of which is hereby incorporated herein by reference in its entirety.

In one embodiment, a processor can be executed in simultaneous multithreading (SMT) mode or single thread mode. In simultaneous multithreading mode, the processor can simultaneously execute multiple independent threads of execution. A thread, as described in further detail below, may be used in executing one or more instructions of a computer program.

As described above, to process the instructions of a computer program, an instruction pipeline is used, examples of which are described with reference to FIGS. 2A-2B. Referring to FIG. 2A, in an existing design, the following steps of each instruction are performed in-order **200**: instruction fetch (I-Fetch), instruction decode, group (e.g., grouping of instructions for how they are to be tracked through the pipeline), and instruction dispatch. That is, if Instruction A is first in the program, followed by Instruction B, then fetch, decode, group, and dispatch of Instruction A are performed prior to those steps of Instruction B. However, the steps of Instruction B may be started prior to completion of the steps of Instruction A; e.g., a fetch of Instruction B can commence after a fetch of Instruction A is complete, but before decode of Instruction A is complete. Each of these steps may also work on more than a single instruction in parallel.

The steps of instruction issue, instruction execution and reordering, however, may be performed out-of-order **202**. For instance, Instruction B may be executed before Instruction A, but not completed. The completion of the instruction (e.g., checkpointing) is again performed in-order **204**, such that, for instance, Instruction A is to complete before Instruction B. One reason to force in-order completion is to allow precise exception detection and reporting for instructions which behave illegally with respect to the architecture.

In accordance with an aspect of the present invention, another design of the instruction pipeline is provided in which more of the processing can be performed out-of-order. For instance, as shown in FIG. 2B, the instruction fetch, decode, group, dispatch, issue, execute and reorder can be performed out-of-order **250**, while the complete step is performed in-order **252**. This design is used, for instance, in the processing of major branch instructions, as described herein. (Although various instruction steps are described herein, more, less or different steps may be used in other examples.)

One type of branch, referred to herein as a minor branch, defines the next instruction in the program to be executed. This next instruction is not the next instruction in sequential order of the program, but is still part of the processing stream (e.g., thread) currently being executed. Contrasted with minor branches is another type of branch, referred to as major branches, provided in accordance with an aspect of the present invention. A major branch defines a code point (target address) which is not next in sequential program order and will not be part of the processing stream currently being executed, but instead, will be executed as part of a new processing stream (e.g., thread). This type of branch is further described with reference to FIG. 3.

Referring to FIG. 3, one example of a computer program **300** (or a portion thereof) is depicted, which includes a plurality of instructions. The first instruction of the computer program is Instruction A **302**. Processing begins with Instruction A and proceeds to Instruction B **304**, Instruction C **306** and Instruction D **310** in sequential order. In this example, Instruction D is a major branch Open instruction to target Y **340**. The major branch Open instruction is executed causing a second stream (referred to herein as a child stream) to be started/opened (for example, a second thread on a SMT processor, referred to herein as a child thread, is activated). The first stream (referred to herein as the parent stream) continues

to process Instruction E **312**, Instruction F **314** and Instruction G **320**. Instruction G branches to Target X **322**, at which Instruction M **324** is processed, followed by Instructions N **326** and O **328**. These instructions are also processed as part of the first stream, since the branch at Instruction G is a minor branch and does not cause another stream of processing to be started/opened.

In accordance with an aspect of the present invention, the processing of the parent stream (i.e., one or more of Instructions E, F, G, M, N and O) subsequent to the major branch Open is parallel to the processing of the child stream (i.e., one or more of instructions: T **342**, U **344**, and V **346**).

Instruction O, in this example, is a major branch Close instruction, which branches to Target Y **340**. The close instruction denotes that the parent thread has caught up to the target address of the major branch OPEN. At this point, the child thread becomes the parent thread, and the thread resources assigned to what was the parent thread are now available for further processing (e.g., as another child thread).

The number of threads available depends on the architecture of the processor. For instance, for an SMT-2 processor, there are two threads available, and therefore, one child (a.k.a., assist) thread can be started. For an SMT-4 processor, there are four threads available, and therefore, three child threads can be started allowing for further out-of-order processing.

In one embodiment, the instructions of the child thread do not complete until the instructions of the parent thread have completed, since instructions are to complete in-order in the example pipeline designs described herein. At the time the instructions of the parent thread checkpoint (e.g., save its state, such as architectural state), the child thread becomes the parent thread and the instructions which were in what was defined as the child thread are now allowed to checkpoint.

In accordance with an aspect of the present invention, any existing or new branch instruction of an instruction set architecture can be defined as a major branch instruction, as well as or in lieu of a minor branch instruction. For instance, many architectures currently have a number of branch instructions that perform various branch operations. Each of these branch instructions (or a subset thereof) can be implemented as a major branch (OPEN/CLOSE) and/or a minor branch instruction. To accomplish this, the opcode or other field of the branch instruction defines the type of the branch instruction as either a major branch (e.g., major branch Open or major branch Close) or a minor branch.

For instance, a branch instruction could have one of three different opcodes: minor branch opcode, major branch Open opcode or major branch Close opcode. Although the three types of branch instructions would have different opcodes, the format of the instruction is the same, as well as the branch operation. The difference lies in how the instruction is processed. For example, its pipeline processing is different, its target address may be different, and its processing as far as being part of the initial thread or another thread depends on the type of branch instruction.

In a further example, instead of different opcodes, a field is added to the instruction (e.g., a separate field from the other fields of the instruction or an add-on to one of the existing fields, such as the opcode field or another field) that indicates the type of branch instruction. For instance, a 2-bit field may be used that has the following meaning, in one particular example:

- 00—Minor branch; instruction behaves as it has
- 01—Unused
- 10—Major branch Close
- 11—Major branch Open

Embodiments of formats of a generic branch instruction are depicted in FIGS. 4A-4B. As shown in FIG. 4A, a branch instruction **400** includes at least one opcode field **402** including an opcode indicating the particular branch instruction, as well as the type of branch instruction (major Open, major Close, minor); and a target address field **404** used to determine the location to which the branch instruction is to jump.

In a further example, a branch instruction **420** (FIG. 4B) includes at least one opcode field **422** including an opcode indicating the particular branch instruction, a format field **424** designating the type of branch instruction (e.g., major Open, major Close, minor), and a target address field **426**. Format field **424** may be a separate field or part of another field, such as the opcode.

The target address field **404**, **426** can be one or more fields used to determine the target location. As examples, it can be a register field that designates a register, the contents of which specify an address of the target location; it can be two fields, such as a base register field and a displacement field, in which the contents of the register designated in the base register field are added to the contents of the displacement field to obtain an address of the target location; or any other combination of fields, registers etc. used to designate the target location.

Further, each individual branch instruction, regardless of whether it is a major or minor branch, may include one or more fields to perform the particular branch operation. As indicated, there can be many branch instructions, examples of which are described in the above-referenced Principles of Operation. For those branch instructions in the Principles of Operation, the particular format of the branch instruction is used, but either the opcode or another field added to the format or appended to an existing field of the instruction indicates the type of branch instruction, e.g., minor, major Open, major Close, in accordance with an aspect of the present invention.

Additional details regarding the processing of major branch instructions are described with reference to FIG. 5. This processing is performed by the processor (e.g., during various pipeline stages) for each thread within an SMT processor (e.g., core).

Referring to FIG. 5, initially, an instruction is fetched and decoded, and an inquiry is made as to whether the instruction is a major branch Open instruction, INQUIRY **500**. If the opcode or other field of the instruction indicates it is not a major branch Open instruction, then processing continues to one or more other pipeline stages.

At another pipeline stage, a determination is made as to whether a major branch Close instruction is at checkpoint (i.e., complete step), INQUIRY **502**. If not, then processing continues to one or more other pipeline stages, and during such processing, a further inquiry is made as to whether an unexpected pipeline redirect (e.g., branch wrong, operating system task swap) is being experienced, INQUIRY **504**. If not, then the instruction (or instructions) is (are) processed at each pipeline stage and then advanced to the next stage, STEP **506**. Processing continues to the next instruction.

Returning to INQUIRY **500**, if it is a major branch Open instruction, then a second stream (e.g., child thread) is denoted as started/active, STEP **510**. In one example, this includes tracking (e.g., by a counter) that another thread of the pre-defined number of threads is being used. Further, a second stream (e.g., SMT thread for the child) is started at the branch's target, STEP **512**. In one example, this includes setting a pointer or other indication to use the child thread, as well as starting, in one example, instruction fetch and branch prediction for the child thread. Since this stream or thread is a child of a parent, in this example, the parent's architectural

state is referenced by the child. If the child changes an architectural state, then that updated state is associated with just the child. Processing then continues at one or more pipeline stages.

Referring to INQUIRY 502, if it is a major branch Close instruction that has reached checkpoint, then the second stream (e.g., child thread) is allowed to checkpoint one or more instructions of its stream that have completed, STEP 520. The parent stream (e.g., parent SMT thread) is deallocated, such that its resources can be used by another stream or thread, STEP 522. The child stream becomes the parent stream (e.g., by setting a pointer or other indication that it is the parent) in which processing continues where the child thread is processing. The child is considered complete, STEP 524. Processing then continues at one or more other pipeline stages.

Returning to INQUIRY 504, if the parent stream (e.g., thread) encounters a branch wrong or operating system intervention, the child stream is terminated and invalidated, STEP 528. In one example, each child stream can start another child stream via a major branch Open instruction, assuming available threads. Thus, if there are multiple child streams, then each child stream is terminated and invalidated. An indication is made that there is no active child thread, STEP 530, and processing continues at STEP 506. As such, any instructions executed or to be executed by the child stream are now to be processed by the parent stream. Furthermore, upon encountering the associated major Close instruction, it is to be ignored as the close action has already taken place. (In a further embodiment, if there are multiple child streams and one of those child streams encounters a branch wrong, then only the one or more younger child streams are terminated.)

In a further aspect of the present invention, when employing a major branch Open instruction to branch to a target address, the instructions at the target address may be treated as executing within a transaction, in which the results of the instructions are committed as one atomic unit (i.e., all committed or not). In one embodiment, the major branch Open instruction not only starts a new stream or thread, but also starts a transaction via transactional memory. Transactional memory provides the means to state that a given block of code is a transaction. A transaction allows a program to checkpoint instructions at completion; however, upon the start of a transaction, the state of the machine is recorded such that if the transaction does not complete, the machine/processor/pipeline can be restored to the point of the entry of the transaction. All stores are committed to memory at the end of the transaction. This allows the state of the entire system to be able to be restored to the point at which the transaction started. In a transaction, any changes are committed together. If a transaction is abnormally terminated, the processor reverts back to a state prior to starting the transaction. By defining the new child stream as a transaction, the child stream is allowed to perform an architecture checkpoint in parallel with the parent stream; however, the child transaction does not end (TEND) until the child becomes the parent. Should the parent stream encounter a branch wrong, the child stream, which is a transaction, is terminated and the state of the machine is reverted (as defined by the definition of transaction memory) as though no actions in the child stream took place.

In one embodiment, in order for the pipeline to determine that a transaction is to be started via transactional memory with respect to detecting a major branch Open, the architecture is modified. As examples, an opcode (e.g., 402, FIG. 4A) is provided that indicates a branch major Open with transaction; or format field 424, which may be a part of the opcode

field or another field or separate therefrom, includes a code that indicates major branch Open with transaction initiated.

In another embodiment, initiation of a transaction for a major branch Open instruction is independent of the architecture and, instead, under control of hardware pipeline. Hardware control of starting a transaction with respect to major branch Open may initiate a major branch Open as a transaction via transactional memory when such was not specified by the instruction. For example, if the hardware supports nested transactions, then upon detecting a major branch Open instruction, independent of whether the major branch Open instruction format specifies a transaction to be started, one may be started, as directed by the hardware. Furthermore, hardware may allow the processing of major branch Open, but deny the major branch Open from initiating as a transaction, even if such is specified by the architected format of the instruction. For example, if resources for processing transactions are running low in the machine, then while the major branch Open instruction format states to start a transaction, a transaction may be prevented from being started, so as to leave the remaining transactional resources available for any transactions which are already in progress. Other examples also exist.

Further, with a major branch Close instruction, the following actions take place in one embodiment: the parent stream is retired as being an active stream; the child stream becomes the parent stream; and if the major Branch Open started a transaction, what was the child stream is no longer in a transactional memory state and reverts to a classical processor processing state (transaction end). As such, checkpoint content can no longer be rewound to a prior architectural checkpoint state.

One embodiment of the processing associated with a branch instruction with transactional memory is described with reference to FIG. 6. Again, this processing is performed for each thread within an SMT processor and by the logic of the processor processing the branch instruction.

Referring to FIG. 6, a determination is made as to whether a major branch Open instruction is being decoded, INQUIRY 600. If the opcode or other field of the instruction indicates that a major branch Open instruction is not being decoded, then processing continues to one or more other pipeline stages.

At another pipe stage, a determination is made as to whether a major branch Close instruction is at checkpoint, INQUIRY 602. If the major branch Close instruction is not at checkpoint, then processing continues to one or more other pipeline stages.

A further determination is made as to whether an unexpected pipeline redirect has occurred, INQUIRY 604. If not, the instruction (or instructions) is (are) processed at each pipeline stage and then advanced to the next stage, STEP 606. Processing moves to the next instruction, STEP 600.

Returning to INQUIRY 600, if a major branch Open instruction is being decoded, then it is denoted that another stream (e.g., child thread) is being started/active, STEP 610, and the other stream (e.g., thread) is started at the branch's target, STEP 612. Further, in accordance with an aspect of the invention, a determination is made as to whether a transaction is to be started, INQUIRY 613. As one example, a field of the instruction (either an existing field or a new field) is used to indicate if a transaction is to be started. As another example, the hardware of the processor makes this determination either by overriding the instruction or in lieu of the instruction having such a field that indicates a transaction is to be started. If a transaction is to be started, then the new stream starts a transaction (TBEGIN), STEP 614. For the start of the trans-

action, a snapshot of the current state of the machine is maintained/taken such that if the transaction is abnormally terminated, the state of the machine can be restored to the point at which the transaction started. Thereafter, or if a transaction is not started, processing continues to one or more other pipeline stages.

Returning to INQUIRY 602, if the logic determines that a major branch Close instruction is at checkpoint, then a determination is made as to whether a transaction was started, INQUIRY 616. If a transaction was started, then the child stream transaction ends (TEND), STEP 618. Further, the architected state of the machine is updated to reflect the child's transactional work, STEP 620. The parent stream (e.g., SMT thread) is deallocated and is no longer active, STEP 622. The child stream is made to be the parent stream and it is noted that the child is no longer active, STEP 624. Processing then continues in the pipeline.

Referring to INQUIRY 616, if a transaction is not started, then any complete child instructions are allowed to checkpoint, STEP 621, and processing continues to STEP 622.

Returning to INQUIRY 604, if an unexpected pipeline redirect has been encountered, then a determination is made as to whether a transaction was started, INQUIRY 626. If a transaction was started, then the child stream's transaction is abnormally terminated (TABORT), STEP 630. Thereafter, or if a transaction was not started, the child stream is deallocated and invalidated, STEP 632; and it is noted that the child is no longer active, STEP 634. In one embodiment, more than one child stream can be in process. If the redirect is encountered on the parent, then all the child streams having any association with the parent are ended, including abnormally terminating the transaction. If the redirect is at a child stream, then any younger child streams are to be ended, including abnormally terminating the transaction. Further, if a child stream encounters an interrupt or exception, the child stream pauses process and resumes process upon becoming the parent stream. Processing continues to STEP 606.

The starting of the child stream(s) in transactional memory allows the child stream(s) to run further ahead. A child stream no longer has to withhold pipelining resources to prevent a hang-up in the parent thread. Further, the child stream is able to retire instructions from the out-of-order completion tables which were limited in size, typically supporting around 200 instructions maximum. In one embodiment, child streams still maintain some limits on the amount of completion that can be performed as a transaction, for resources are required to maintain all of the store data which is to be committed upon completion of the transaction. The hardware to maintain the stores until transaction completion is a lot less restrictive than those resources for the out-of-order windows with respect to, for instance, frequency, latency, capacity, and/or floor plan placement.

Described above is a branch mechanism that enables one segment of code of a program to be processed concurrent to at least one other segment of code of the same program. In one example, a branch instruction is provided that starts a parallel thread (e.g., a child thread) in the taken path, but keeps executing (e.g., parent thread) in the non-taken path. The parent thread includes instructions for either ending the thread or joining the other thread. In one embodiment, the child thread does not update architected state (i.e., state visible to other applications, threads, etc.) until the parent thread reaches a defined point in processing, such as a major branch Close instruction. Further, in one embodiment, the thread of the taken path starts a transactional memory transaction.

The use of major branches allows instructions to be decoded/dispatched out-of-order, so as to provide a larger

out-of-order window for instructions to be executed. Without a major branch OPEN/CLOSE, instructions are decoded and dispatched in-order, but may be issued out-of-order, and are completed in-order.

In one embodiment, the amount of processing of the child streams is limited to the out-of-order resources available in the processor. The child streams while using out-of-order resources are not to consume all resources as to create a hang situation such that the parent is unable to obtain resources it needs to make forward progress. This limitation, however, is avoided if the child stream uses transactional processing.

In one embodiment, if a major branch OPEN is encountered and all threads are in use for spanning off child paths, then the major branch OPEN is not executed. This is denoted and upon encountering the paired major branch CLOSE, it is also not executed. By not executing on the CLOSE, a parent to child thread switch will not take place.

In one example, a restart of the parent stream, including a restart of the I-fetch fetching stream, terminates the child stream of processing and any of its children, etc. A restart in a child stream terminates its child and any younger children, but not the parent.

The hardware (e.g., transistors) that define a processor pipeline is made up of many queues. The queues are finite in size, and such queues include, but are not limited to: cache line addresses, instructions to decode (post instruction fetch), instructions to dispatch, instructions from dispatch to architectural checkpoint, general purpose registers, branch queues, and store queues. Without transactional processing, a processor may require a subset or all of these queues to empty in an in-order fashion, even in an out-of-order processor. Those resources (e.g., queues) claimed by a child stream may not be emptied until the parent stream has completed. If the child stream occupies too many resources, then the parent may not have enough resources available to perform the operations of instructions as defined by the architecture and ordered by the software program. It is to prevent such a hang situation that the child may not use resources to the point that there are not enough resources available to the parent for the parent to make forward progress. For the child to be able to limit its resource usage it is to know how much resource is available for it to use. This amount of resource may be either hardwired in the hardware or the parent thread can communicate to the child how much resource is available to be used. Furthermore, the parent may communicate an under-amount of resources that are available for the child to use such that, while the child does not hang the parent, the child does not use so much resource as to bring the parent's rate of forward progress to a crawl.

In a further embodiment, branch prediction is allowed to proceed down a child stream in the manner it would proceed down two independent threads in, for instance, an SMT-2 environment. Branch prediction may be used to predict whether a branch is to be taken and/or the target location of that branch.

As will be appreciated by one skilled in the art, one or more aspects of the present invention may be embodied as a system, method or computer program product. Accordingly, one or more aspects of the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a "circuit," "module" or "system". Furthermore, one or more aspects of the present invention may take the form of a com-

puter program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

Any combination of one or more computer readable medium(s) may be utilized. The computer readable medium may be a computer readable storage medium. A computer readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, infrared or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer readable storage medium include the following: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a computer readable storage medium may be any tangible medium that can contain or store a program for use by or in connection with an instruction execution system, apparatus, or device.

Referring now to FIG. 7, in one example, a computer program product 700 includes, for instance, one or more non-transitory computer readable storage media 702 to store computer readable program code means or logic 704 thereon to provide and facilitate one or more aspects of the present invention.

Program code embodied on a computer readable medium may be transmitted using an appropriate medium, including but not limited to wireless, wireline, optical fiber cable, RF, etc., or any suitable combination of the foregoing.

Computer program code for carrying out operations for one or more aspects of the present invention may be written in any combination of one or more programming languages, including an object oriented programming language, such as Java, Smalltalk, C++ or the like, and conventional procedural programming languages, such as the "C" programming language, assembler or similar programming languages. The program code may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user's computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

One or more aspects of the present invention are described herein with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the invention. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

These computer program instructions may also be stored in a computer readable medium that can direct a computer, other programmable data processing apparatus, or other devices to function in a particular manner, such that the instructions stored in the computer readable medium produce an article of manufacture including instructions which implement the function/act specified in the flowchart and/or block diagram block or blocks.

The computer program instructions may also be loaded onto a computer, other programmable data processing apparatus, or other devices to cause a series of operational steps to be performed on the computer, other programmable apparatus or other devices to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide processes for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

The flowchart and block diagrams in the figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods and computer program products according to various embodiments of one or more aspects of the present invention. In this regard, each block in the flowchart or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the block may occur out of the order noted in the figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

In addition to the above, one or more aspects of the present invention may be provided, offered, deployed, managed, serviced, etc. by a service provider who offers management of customer environments. For instance, the service provider can create, maintain, support, etc. computer code and/or a computer infrastructure that performs one or more aspects of the present invention for one or more customers. In return, the service provider may receive payment from the customer under a subscription and/or fee agreement, as examples. Additionally or alternatively, the service provider may receive payment from the sale of advertising content to one or more third parties.

In one aspect of the present invention, an application may be deployed for performing one or more aspects of the present invention. As one example, the deploying of an application comprises providing computer infrastructure operable to perform one or more aspects of the present invention.

As a further aspect of the present invention, a computing infrastructure may be deployed comprising integrating computer readable code into a computing system, in which the code in combination with the computing system is capable of performing one or more aspects of the present invention.

As yet a further aspect of the present invention, a process for integrating computing infrastructure comprising integrating computer readable code into a computer system may be provided. The computer system comprises a computer readable medium, in which the computer medium comprises one or more aspects of the present invention. The code in combination with the computer system is capable of performing one or more aspects of the present invention.

Although various embodiments are described above, these are only examples. For example, other computing environments can incorporate and use one or more aspects of the present invention. For instance, a computing environment may include a central processor complex having a plurality of processors. The central processor complex may or may not be logically partitioned. Further, computing environments of other architectures can incorporate and use one or more aspects of the present invention. Additionally, while major branch Open and Close are described, they may be called by different names or additional major branch types may be provided. Many changes and/or additions may be made without departing from the spirit of the present invention.

Further, other types of computing environments can benefit from one or more aspects of the present invention. As an example, a data processing system suitable for storing and/or executing program code is usable that includes at least two processors coupled directly or indirectly to memory elements through a system bus. The memory elements include, for instance, local memory employed during actual execution of the program code, bulk storage, and cache memory which provide temporary storage of at least some program code in order to reduce the number of times code must be retrieved from bulk storage during execution.

Input/Output or I/O devices (including, but not limited to, keyboards, displays, pointing devices, DASD, tape, CDs, DVDs, thumb drives and other memory media, etc.) can be coupled to the system either directly or through intervening I/O controllers. Network adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Modems, cable modems, and Ethernet cards are just a few of the available types of network adapters.

Other examples of computing environments that may incorporate and/or use one or more aspects of the present invention are described below.

Referring to FIG. 8, representative components of a Host Computer system **5000** to implement one or more aspects of the present invention are portrayed. The representative host computer **5000** comprises one or more CPUs **5001** in communication with computer memory (i.e., central storage) **5002**, as well as I/O interfaces to storage media devices **5011** and networks **5010** for communicating with other computers or SANs and the like. The CPU **5001** is compliant with an architecture having an architected instruction set and architected functionality. The CPU **5001** may have dynamic address translation (DAT) **5003** for transforming program addresses (virtual addresses) into real addresses of memory. A DAT typically includes a translation lookaside buffer (TLB) **5007** for caching translations so that later accesses to the block of computer memory **5002** do not require the delay of address translation. Typically, a cache **5009** is employed between computer memory **5002** and the processor **5001**. The cache **5009** may be hierarchical having a large cache available to more than one CPU and smaller, faster (lower level) caches between the large cache and each CPU. In some implementations, the lower level caches are split to provide separate low level caches for instruction fetching and data accesses. In one embodiment, an instruction is fetched from memory **5002** by an instruction fetch unit **5004** via a cache **5009**. The instruction is decoded in an instruction decode unit **5006** and dispatched (with other instructions in some embodiments) to instruction execution unit or units **5008**. Typically several execution units **5008** are employed, for example an arithmetic execution unit, a floating point execution unit and a branch instruction execution unit. The instruction is executed by the

execution unit, accessing operands from instruction specified registers or memory as needed. If an operand is to be accessed (loaded or stored) from memory **5002**, a load/store unit **5005** typically handles the access under control of the instruction being executed. Instructions may be executed in hardware circuits or in internal microcode (firmware) or by a combination of both.

As noted, a computer system includes information in local (or main) storage, as well as addressing, protection, and reference and change recording. Some aspects of addressing include the format of addresses, the concept of address spaces, the various types of addresses, and the manner in which one type of address is translated to another type of address. Some of main storage includes permanently assigned storage locations. Main storage provides the system with directly addressable fast-access storage of data. Both data and programs are to be loaded into main storage (from input devices) before they can be processed.

Main storage may include one or more smaller, faster-access buffer storages, sometimes called caches. A cache is typically physically associated with a CPU or an I/O processor. The effects, except on performance, of the physical construction and use of distinct storage media are generally not observable by the program.

Separate caches may be maintained for instructions and for data operands. Information within a cache is maintained in contiguous bytes on an integral boundary called a cache block or cache line (or line, for short). A model may provide an EXTRACT CACHE ATTRIBUTE instruction which returns the size of a cache line in bytes. A model may also provide PREFETCH DATA and PREFETCH DATA RELATIVE LONG instructions which effects the prefetching of storage into the data or instruction cache or the releasing of data from the cache.

Storage is viewed as a long horizontal string of bits. For most operations, accesses to storage proceed in a left-to-right sequence. The string of bits is subdivided into units of eight bits. An eight-bit unit is called a byte, which is the basic building block of all information formats. Each byte location in storage is identified by a unique nonnegative integer, which is the address of that byte location or, simply, the byte address. Adjacent byte locations have consecutive addresses, starting with 0 on the left and proceeding in a left-to-right sequence. Addresses are unsigned binary integers and are 24, 31, or 64 bits.

Information is transmitted between storage and a CPU or a channel subsystem one byte, or a group of bytes, at a time. Unless otherwise specified, in, for instance, the *z/Architecture*®, a group of bytes in storage is addressed by the leftmost byte of the group. The number of bytes in the group is either implied or explicitly specified by the operation to be performed. When used in a CPU operation, a group of bytes is called a field. Within each group of bytes, in, for instance, the *z/Architecture*®, bits are numbered in a left-to-right sequence. In the *z/Architecture*®, the leftmost bits are sometimes referred to as the “high-order” bits and the rightmost bits as the “low-order” bits. Bit numbers are not storage addresses, however. Only bytes can be addressed. To operate on individual bits of a byte in storage, the entire byte is accessed. The bits in a byte are numbered 0 through 7, from left to right (in, e.g., the *z/Architecture*®). The bits in an address may be numbered 8-31 or 40-63 for 24-bit addresses, or 1-31 or 33-63 for 31-bit addresses; they are numbered 0-63 for 64-bit addresses. Within any other fixed-length format of multiple bytes, the bits making up the format are consecutively numbered starting from 0. For purposes of error detection, and in preferably for correction, one or more check bits may be transmitted with each byte or with a group of bytes.

Such check bits are generated automatically by the machine and cannot be directly controlled by the program. Storage capacities are expressed in number of bytes. When the length of a storage-operand field is implied by the operation code of an instruction, the field is said to have a fixed length, which can be one, two, four, eight, or sixteen bytes. Larger fields may be implied for some instructions. When the length of a storage-operand field is not implied but is stated explicitly, the field is said to have a variable length. Variable-length operands can vary in length by increments of one byte (or with some instructions, in multiples of two bytes or other multiples). When information is placed in storage, the contents of only those byte locations are replaced that are included in the designated field, even though the width of the physical path to storage may be greater than the length of the field being stored.

Certain units of information are to be on an integral boundary in storage. A boundary is called integral for a unit of information when its storage address is a multiple of the length of the unit in bytes. Special names are given to fields of 2, 4, 8, and 16 bytes on an integral boundary. A halfword is a group of two consecutive bytes on a two-byte boundary and is the basic building block of instructions. A word is a group of four consecutive bytes on a four-byte boundary. A doubleword is a group of eight consecutive bytes on an eight-byte boundary. A quadword is a group of 16 consecutive bytes on a 16-byte boundary. When storage addresses designate halfwords, words, doublewords, and quadwords, the binary representation of the address contains one, two, three, or four rightmost zero bits, respectively. Instructions are to be on two-byte integral boundaries. The storage operands of most instructions do not have boundary-alignment requirements.

On devices that implement separate caches for instructions and data operands, a significant delay may be experienced if the program stores into a cache line from which instructions are subsequently fetched, regardless of whether the store alters the instructions that are subsequently fetched.

In one embodiment, the invention may be practiced by software (sometimes referred to licensed internal code, firmware, micro-code, milli-code, pico-code and the like, any of which would be consistent with one or more aspects of the present invention). Referring to FIG. 8, software program code which embodies one or more aspects of the present invention may be accessed by processor 5001 of the host system 5000 from long-term storage media devices 5011, such as a CD-ROM drive, tape drive or hard drive. The software program code may be embodied on any of a variety of known media for use with a data processing system, such as a diskette, hard drive, or CD-ROM. The code may be distributed on such media, or may be distributed to users from computer memory 5002 or storage of one computer system over a network 5010 to other computer systems for use by users of such other systems.

The software program code includes an operating system which controls the function and interaction of the various computer components and one or more application programs. Program code is normally paged from storage media device 5011 to the relatively higher-speed computer storage 5002 where it is available for processing by processor 5001. The techniques and methods for embodying software program code in memory, on physical media, and/or distributing software code via networks are well known and will not be further discussed herein. Program code, when created and stored on a tangible medium (including but not limited to electronic memory modules (RAM), flash memory, Compact Discs (CDs), DVDs, Magnetic Tape and the like is often referred to

as a "computer program product". The computer program product medium is typically readable by a processing circuit preferably in a computer system for execution by the processing circuit.

FIG. 9 illustrates a representative workstation or server hardware system in which one or more aspects of the present invention may be practiced. The system 5020 of FIG. 9 comprises a representative base computer system 5021, such as a personal computer, a workstation or a server, including optional peripheral devices. The base computer system 5021 includes one or more processors 5026 and a bus employed to connect and enable communication between the processor(s) 5026 and the other components of the system 5021 in accordance with known techniques. The bus connects the processor 5026 to memory 5025 and long-term storage 5027 which can include a hard drive (including any of magnetic media, CD, DVD and Flash Memory for example) or a tape drive for example. The system 5021 might also include a user interface adapter, which connects the microprocessor 5026 via the bus to one or more interface devices, such as a keyboard 5024, a mouse 5023, a printer/scanner 5030 and/or other interface devices, which can be any user interface device, such as a touch sensitive screen, digitized entry pad, etc. The bus also connects a display device 5022, such as an LCD screen or monitor, to the microprocessor 5026 via a display adapter.

The system 5021 may communicate with other computers or networks of computers by way of a network adapter capable of communicating 5028 with a network 5029. Example network adapters are communications channels, token ring, Ethernet or modems. Alternatively, the system 5021 may communicate using a wireless interface, such as a CDPD (cellular digital packet data) card. The system 5021 may be associated with such other computers in a Local Area Network (LAN) or a Wide Area Network (WAN), or the system 5021 can be a client in a client/server arrangement with another computer, etc. All of these configurations, as well as the appropriate communications hardware and software, are known in the art.

FIG. 10 illustrates a data processing network 5040 in which one or more aspects of the present invention may be practiced. The data processing network 5040 may include a plurality of individual networks, such as a wireless network and a wired network, each of which may include a plurality of individual workstations 5041, 5042, 5043, 5044. Additionally, as those skilled in the art will appreciate, one or more LANs may be included, where a LAN may comprise a plurality of intelligent workstations coupled to a host processor.

Still referring to FIG. 10, the networks may also include mainframe computers or servers, such as a gateway computer (client server 5046) or application server (remote server 5048) which may access a data repository and may also be accessed directly from a workstation 5045). A gateway computer 5046 serves as a point of entry into each individual network. A gateway is needed when connecting one networking protocol to another. The gateway 5046 may be preferably coupled to another network (the Internet 5047 for example) by means of a communications link. The gateway 5046 may also be directly coupled to one or more workstations 5041, 5042, 5043, 5044 using a communications link. The gateway computer may be implemented utilizing an IBM eServer™ System z® server available from International Business Machines Corporation.

Referring concurrently to FIG. 9 and FIG. 10, software programming code which may embody one or more aspects of the present invention may be accessed by the processor 5026 of the system 5020 from long-term storage media 5027, such as a CD-ROM drive or hard drive. The software pro-

programming code may be embodied on any of a variety of known media for use with a data processing system, such as a diskette, hard drive, or CD-ROM. The code may be distributed on such media, or may be distributed to users **5050**, **5051** from the memory or storage of one computer system over a network to other computer systems for use by users of such other systems.

Alternatively, the programming code may be embodied in the memory **5025**, and accessed by the processor **5026** using the processor bus. Such programming code includes an operating system which controls the function and interaction of the various computer components and one or more application programs **5032**. Program code is normally paged from storage media **5027** to high-speed memory **5025** where it is available for processing by the processor **5026**. The techniques and methods for embodying software programming code in memory, on physical media, and/or distributing software code via networks are well known and will not be further discussed herein. Program code, when created and stored on a tangible medium (including but not limited to electronic memory modules (RAM), flash memory, Compact Discs (CDs), DVDs, Magnetic Tape and the like is often referred to as a "computer program product". The computer program product medium is typically readable by a processing circuit preferably in a computer system for execution by the processing circuit.

The cache that is most readily available to the processor (normally faster and smaller than other caches of the processor) is the lowest (L1 or level one) cache and main store (main memory) is the highest level cache (L3 if there are 3 levels). The lowest level cache is often divided into an instruction cache (I-Cache) holding machine instructions to be executed and a data cache (D-Cache) holding data operands.

Referring to FIG. 11, an exemplary processor embodiment is depicted for processor **5026**. Typically one or more levels of cache **5053** are employed to buffer memory blocks in order to improve processor performance. The cache **5053** is a high speed buffer holding cache lines of memory data that are likely to be used. Typical cache lines are 64, 128 or 256 bytes of memory data. Separate caches are often employed for caching instructions than for caching data. Cache coherence (synchronization of copies of lines in memory and the caches) is often provided by various "snoop" algorithms well known in the art. Main memory storage **5025** of a processor system is often referred to as a cache. In a processor system having 4 levels of cache **5053**, main storage **5025** is sometimes referred to as the level 5 (L5) cache since it is typically faster and only holds a portion of the non-volatile storage (DASD, tape etc) that is available to a computer system. Main storage **5025** "caches" pages of data paged in and out of the main storage **5025** by the operating system.

A program counter (instruction counter) **5061** keeps track of the address of the current instruction to be executed. A program counter in a z/Architecture® processor is 64 bits and can be truncated to 31 or 24 bits to support prior addressing limits. A program counter is typically embodied in a PSW (program status word) of a computer such that it persists during context switching. Thus, a program in progress, having a program counter value, may be interrupted by, for example, the operating system (context switch from the program environment to the operating system environment). The PSW of the program maintains the program counter value while the program is not active, and the program counter (in the PSW) of the operating system is used while the operating system is executing. Typically, the program counter is incremented by an amount equal to the number of bytes of the current instruction. RISC (Reduced Instruction Set Comput-

ing) instructions are typically fixed length while CISC (Complex Instruction Set Computing) instructions are typically variable length. Instructions of the IBM z/Architecture® are CISC instructions having a length of 2, 4 or 6 bytes. The Program counter **5061** is modified by either a context switch operation or a branch taken operation of a branch instruction for example. In a context switch operation, the current program counter value is saved in the program status word along with other state information about the program being executed (such as condition codes), and a new program counter value is loaded pointing to an instruction of a new program module to be executed. A branch taken operation is performed in order to permit the program to make decisions or loop within the program by loading the result of the branch instruction into the program counter **5061**.

Typically an instruction fetch unit **5055** is employed to fetch instructions on behalf of the processor **5026**. The fetch unit either fetches "next sequential instructions", target instructions of branch taken instructions, or first instructions of a program following a context switch. Modern Instruction fetch units often employ prefetch techniques to speculatively prefetch instructions based on the likelihood that the prefetched instructions might be used. For example, a fetch unit may fetch 16 bytes of instruction that includes the next sequential instruction and additional bytes of further sequential instructions.

The fetched instructions are then executed by the processor **5026**. In an embodiment, the fetched instruction(s) are passed to a dispatch unit **5056** of the fetch unit. The dispatch unit decodes the instruction(s) and forwards information about the decoded instruction(s) to appropriate units **5057**, **5058**, **5060**. An execution unit **5057** will typically receive information about decoded arithmetic instructions from the instruction fetch unit **5055** and will perform arithmetic operations on operands according to the opcode of the instruction. Operands are provided to the execution unit **5057** preferably either from memory **5025**, architected registers **5059** or from an immediate field of the instruction being executed. Results of the execution, when stored, are stored either in memory **5025**, registers **5059** or in other machine hardware (such as control registers, PSW registers and the like).

A processor **5026** typically has one or more units **5057**, **5058**, **5060** for executing the function of the instruction. Referring to FIG. 12A, an execution unit **5057** may communicate with architected general registers **5059**, a decode/dispatch unit **5056**, a load store unit **5060**, and other **5065** processor units by way of interfacing logic **5071**. An execution unit **5057** may employ several register circuits **5067**, **5068**, **5069** to hold information that the arithmetic logic unit (ALU) **5066** will operate on. The ALU performs arithmetic operations such as add, subtract, multiply and divide as well as logical function such as and, or and exclusive-or (XOR), rotate and shift. Preferably the ALU supports specialized operations that are design dependent. Other circuits may provide other architected facilities **5072** including condition codes and recovery support logic for example. Typically the result of an ALU operation is held in an output register circuit **5070** which can forward the result to a variety of other processing functions. There are many arrangements of processor units, the present description is only intended to provide a representative understanding of one embodiment.

An ADD instruction for example would be executed in an execution unit **5057** having arithmetic and logical functionality while a floating point instruction for example would be executed in a floating point execution having specialized floating point capability. Preferably, an execution unit operates on operands identified by an instruction by performing an

opcode defined function on the operands. For example, an ADD instruction may be executed by an execution unit **5057** on operands found in two registers **5059** identified by register fields of the instruction.

The execution unit **5057** performs the arithmetic addition on two operands and stores the result in a third operand where the third operand may be a third register or one of the two source registers. The execution unit preferably utilizes an Arithmetic Logic Unit (ALU) **5066** that is capable of performing a variety of logical functions such as Shift, Rotate, And, Or and XOR as well as a variety of algebraic functions including any of add, subtract, multiply, divide. Some ALUs **5066** are designed for scalar operations and some for floating point. Data may be Big Endian (where the least significant byte is at the highest byte address) or Little Endian (where the least significant byte is at the lowest byte address) depending on architecture. The IBM z/Architecture® is Big Endian. Signed fields may be sign and magnitude, 1's complement or 2's complement depending on architecture. A 2's complement number is advantageous in that the ALU does not need to design a subtract capability since either a negative value or a positive value in 2's complement requires only an addition within the ALU. Numbers are commonly described in shorthand, where a 12 bit field defines an address of a 4,096 byte block and is commonly described as a 4 Kbyte (Kilo-byte) block, for example.

Referring to FIG. 12B, branch instruction information for executing a branch instruction is typically sent to a branch unit **5058** which often employs a branch prediction algorithm such as a branch history table **5082** to predict the outcome of the branch before other conditional operations are complete. The target of the current branch instruction will be fetched and speculatively executed before the conditional operations are complete. When the conditional operations are completed the speculatively executed branch instructions are either completed or discarded based on the conditions of the conditional operation and the speculated outcome. A typical branch instruction may test condition codes and branch to a target address if the condition codes meet the branch requirement of the branch instruction, a target address may be calculated based on several numbers including ones found in register fields or an immediate field of the instruction for example. The branch unit **5058** may employ an ALU **5074** having a plurality of input register circuits **5075**, **5076**, **5077** and an output register circuit **5080**. The branch unit **5058** may communicate with general registers **5059**, decode dispatch unit **5056** or other circuits **5073**, for example.

The execution of a group of instructions can be interrupted for a variety of reasons including a context switch initiated by an operating system, a program exception or error causing a context switch, an I/O interruption signal causing a context switch or multi-threading activity of a plurality of programs (in a multi-threaded environment), for example. Preferably a context switch action saves state information about a currently executing program and then loads state information about another program being invoked. State information may be saved in hardware registers or in memory for example. State information preferably comprises a program counter value pointing to a next instruction to be executed, condition codes, memory translation information and architected register content. A context switch activity can be exercised by hardware circuits, application programs, operating system programs or firmware code (microcode, pico-code or licensed internal code (LIC)) alone or in combination.

A processor accesses operands according to instruction defined methods. The instruction may provide an immediate operand using the value of a portion of the instruction, may

provide one or more register fields explicitly pointing to either general purpose registers or special purpose registers (floating point registers for example). The instruction may utilize implied registers identified by an opcode field as operands. The instruction may utilize memory locations for operands. A memory location of an operand may be provided by a register, an immediate field, or a combination of registers and immediate field as exemplified by the z/Architecture® long displacement facility wherein the instruction defines a base register, an index register and an immediate field (displacement field) that are added together to provide the address of the operand in memory for example. Location herein typically implies a location in main memory (main storage) unless otherwise indicated.

Referring to FIG. 12C, a processor accesses storage using a load/store unit **5060**. The load/store unit **5060** may perform a load operation by obtaining the address of the target operand in memory **5053** and loading the operand in a register **5059** or another memory **5053** location, or may perform a store operation by obtaining the address of the target operand in memory **5053** and storing data obtained from a register **5059** or another memory **5053** location in the target operand location in memory **5053**. The load/store unit **5060** may be speculative and may access memory in a sequence that is out-of-order relative to instruction sequence, however the load/store unit **5060** is to maintain the appearance to programs that instructions were executed in order. A load/store unit **5060** may communicate with general registers **5059**, decode/dispatch unit **5056**, cache/memory interface **5053** or other elements **5083** and comprises various register circuits, ALUs **5085** and control logic **5090** to calculate storage addresses and to provide pipeline sequencing to keep operations in-order. Some operations may be out of order but the load/store unit provides functionality to make the out of order operations to appear to the program as having been performed in order, as is well known in the art.

Preferably addresses that an application program "sees" are often referred to as virtual addresses. Virtual addresses are sometimes referred to as "logical addresses" and "effective addresses". These virtual addresses are virtual in that they are redirected to physical memory location by one of a variety of dynamic address translation (DAT) technologies including, but not limited to, simply prefixing a virtual address with an offset value, translating the virtual address via one or more translation tables, the translation tables preferably comprising at least a segment table and a page table alone or in combination, preferably, the segment table having an entry pointing to the page table. In the z/Architecture®, a hierarchy of translation is provided including a region first table, a region second table, a region third table, a segment table and an optional page table. The performance of the address translation is often improved by utilizing a translation lookaside buffer (TLB) which comprises entries mapping a virtual address to an associated physical memory location. The entries are created when the DAT translates a virtual address using the translation tables. Subsequent use of the virtual address can then utilize the entry of the fast TLB rather than the slow sequential translation table accesses. TLB content may be managed by a variety of replacement algorithms including LRU (Least Recently used).

In the case where the processor is a processor of a multi-processor system, each processor has responsibility to keep shared resources, such as I/O, caches, TLBs and memory, interlocked for coherency. Typically, "snoop" technologies will be utilized in maintaining cache coherency. In a snoop environment, each cache line may be marked as being in any

one of a shared state, an exclusive state, a changed state, an invalid state and the like in order to facilitate sharing.

I/O units **5054** (FIG. 11) provide the processor with means for attaching to peripheral devices including tape, disc, printers, displays, and networks for example. I/O units are often presented to the computer program by software drivers. In mainframes, such as the System z® from IBM®, channel adapters and open system adapters are I/O units of the mainframe that provide the communications between the operating system and peripheral devices.

Further, other types of computing environments can benefit from one or more aspects of the present invention. As an example, as mentioned herein, an environment may include an emulator (e.g., software or other emulation mechanisms), in which a particular architecture (including, for instance, instruction execution, architected functions, such as address translation, and architected registers) or a subset thereof is emulated (e.g., on a native computer system having a processor and memory). In such an environment, one or more emulation functions of the emulator can implement one or more aspects of the present invention, even though a computer executing the emulator may have a different architecture than the capabilities being emulated. As one example, in emulation mode, the specific instruction or operation being emulated is decoded, and an appropriate emulation function is built to implement the individual instruction or operation.

In an emulation environment, a host computer includes, for instance, a memory to store instructions and data; an instruction fetch unit to fetch instructions from memory and to optionally, provide local buffering for the fetched instruction; an instruction decode unit to receive the fetched instructions and to determine the type of instructions that have been fetched; and an instruction execution unit to execute the instructions. Execution may include loading data into a register from memory; storing data back to memory from a register; or performing some type of arithmetic or logical operation, as determined by the decode unit. In one example, each unit is implemented in software. For instance, the operations being performed by the units are implemented as one or more subroutines within emulator software.

More particularly, in a mainframe, architected machine instructions are used by programmers, usually today “C” programmers, often by way of a compiler application. These instructions stored in the storage medium may be executed natively in a z/Architecture® IBM® Server, or alternatively in machines executing other architectures. They can be emulated in the existing and in future IBM® mainframe servers and on other machines of IBM® (e.g., Power Systems servers and System x® Servers). They can be executed in machines running Linux on a wide variety of machines using hardware manufactured by IBM®, Intel®, AMD™, and others. Besides execution on that hardware under a z/Architecture®, Linux can be used as well as machines which use emulation by Hercules, UMX, or FSI (Fundamental Software, Inc), where generally execution is in an emulation mode. In emulation mode, emulation software is executed by a native processor to emulate the architecture of an emulated processor.

The native processor typically executes emulation software comprising either firmware or a native operating system to perform emulation of the emulated processor. The emulation software is responsible for fetching and executing instructions of the emulated processor architecture. The emulation software maintains an emulated program counter to keep track of instruction boundaries. The emulation software may fetch one or more emulated machine instructions at a time and convert the one or more emulated machine instructions to a corresponding group of native machine instructions

for execution by the native processor. These converted instructions may be cached such that a faster conversion can be accomplished. Notwithstanding, the emulation software is to maintain the architecture rules of the emulated processor architecture so as to assure operating systems and applications written for the emulated processor operate correctly. Furthermore, the emulation software is to provide resources identified by the emulated processor architecture including, but not limited to, control registers, general purpose registers, floating point registers, dynamic address translation function including segment tables and page tables for example, interrupt mechanisms, context switch mechanisms, Time of Day (TOD) clocks and architected interfaces to I/O subsystems such that an operating system or an application program designed to run on the emulated processor, can be run on the native processor having the emulation software.

A specific instruction being emulated is decoded, and a subroutine is called to perform the function of the individual instruction. An emulation software function emulating a function of an emulated processor is implemented, for example, in a “C” subroutine or driver, or some other method of providing a driver for the specific hardware as will be within the skill of those in the art after understanding the description of the preferred embodiment. Various software and hardware emulation patents including, but not limited to U.S. Pat. No. 5,551,013, entitled “Multiprocessor for Hardware Emulation”, by Beausoleil et al.; and U.S. Pat. No. 6,009,261, entitled “Preprocessing of Stored Target Routines for Emulating Incompatible Instructions on a Target Processor”, by Scalzi et al; and U.S. Pat. No. 5,574,873, entitled “Decoding Guest Instruction to Directly Access Emulation Routines that Emulate the Guest Instructions”, by Davidian et al; and U.S. Pat. No. 6,308,255, entitled “Symmetrical Multiprocessing Bus and Chipset Used for Coprocessor Support Allowing Non-Native Code to Run in a System”, by Gorishek et al; and U.S. Pat. No. 6,463,582, entitled “Dynamic Optimizing Object Code Translator for Architecture Emulation and Dynamic Optimizing Object Code Translation Method”, by Lethin et al; and U.S. Pat. No. 5,790,825, entitled “Method for Emulating Guest Instructions on a Host Computer Through Dynamic Recompilation of Host Instructions”, by Eric Traut, each of which is hereby incorporated herein by reference in its entirety; and many others, illustrate a variety of known ways to achieve emulation of an instruction format architected for a different machine for a target machine available to those skilled in the art.

In FIG. 13, an example of an emulated host computer system **5092** is provided that emulates a host computer system **5000'** of a host architecture. In the emulated host computer system **5092**, the host processor (CPU) **5091** is an emulated host processor (or virtual host processor) and comprises an emulation processor **5093** having a different native instruction set architecture than that of the processor **5091** of the host computer **5000'**. The emulated host computer system **5092** has memory **5094** accessible to the emulation processor **5093**. In the example embodiment, the memory **5094** is partitioned into a host computer memory **5096** portion and an emulation routines **5097** portion. The host computer memory **5096** is available to programs of the emulated host computer **5092** according to host computer architecture. The emulation processor **5093** executes native instructions of an architected instruction set of an architecture other than that of the emulated processor **5091**, the native instructions obtained from emulation routines memory **5097**, and may access a host instruction for execution from a program in host computer memory **5096** by employing one or more instruction(s) obtained in a sequence & access/decode routine which may

decode the host instruction(s) accessed to determine a native instruction execution routine for emulating the function of the host instruction accessed. Other facilities that are defined for the host computer system 5000' architecture may be emulated by architected facilities routines, including such facilities as 5
general purpose registers, control registers, dynamic address translation and I/O subsystem support and processor cache, for example. The emulation routines may also take advantage of functions available in the emulation processor 5093 (such as general registers and dynamic translation of virtual 10
addresses) to improve performance of the emulation routines. Special hardware and off-load engines may also be provided to assist the processor 5093 in emulating the function of the host computer 5000'.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising", when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components and/or groups thereof. 20

The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below, if any, are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of one or more aspects of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the invention. The embodiment was chosen and described in order to best explain the principles of the invention and the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiment with various modifications as are suited to the particular use contemplated. 30
40

What is claimed is:

1. A method of executing a machine instruction, the method comprising:

obtaining, by a processor, a machine instruction for execution, the machine instruction being defined for computer execution according to a computer architecture, the machine instruction comprising:

at least one opcode field for specifying an opcode, the opcode defining a branch operation; 50

a type indication to specify a type of the branch operation, wherein the type indication specifies how the branch operation is to be processed in this execution of the machine instruction, wherein in another execution of the same branch operation it is processed differently, and wherein the type indication is configured to specify the following types of execution: a minor branch in which the machine instruction is executed in a first stream of processing and the branch operation does not cause a second stream of processing to be started, a major branch open in which the machine instruction is executed in the first stream of processing and the branch operation causes the second stream of processing to be started, and a major branch close in which processing of the first stream of processing meets up with processing of the second stream of processing; and 60
65

at least one field for determining a target location in which to branch; and

executing the machine instruction, the executing being based on the type indication specifying the major branch open, the machine instruction being executed in the first stream of processing, the executing comprising:

starting the second stream of processing, the second stream of processing having a relationship with the first stream of processing in that the second stream of processing references architected state of the first stream of processing, and the second stream of processing is to execute one or more instructions starting at the target location defined using the at least one field of the machine instruction, the one or more instructions being out of sequential execution order from one or more instructions being processed by the first stream of processing, the first stream of processing continuing to process one or more instructions subsequent to the machine instruction;

wherein execution of the second stream of processing is speculative in that at least one instruction of the one or more instructions of the second stream of processing is executed even though reaching the at least one instruction of the second stream of processing by processing of the first stream of processing is tentative, and wherein updating of architected state by one or more instructions of the second stream of processing is performed based on the first stream of processing reaching a predefined point in processing; and obtaining by the processor another machine instruction, the other machine instruction specifying a branch operation and having the type indication, the type indication of the other machine instruction specifying the major branch close indicating processing of the first stream of processing has caught up with the target of the major branch open, and wherein execution of the major branch close comprises updating the architected state by the one or more instructions of the second stream of processing based on the first stream of processing reaching the predefined point in processing. 20
30
40

2. The method of claim 1, wherein at least one instruction of the one or more instructions executed in the second stream of processing is processed, at least in part, in parallel to one or more instructions processed in the first stream of processing.

3. The method of claim 1, wherein the first stream of processing is deallocated subsequent to the first stream of processing reaching an instruction having a target location of an instruction of the second stream of processing.

4. The method of claim 3, wherein the instruction reached by the first stream of processing comprises the major branch close instruction.

5. The method of claim 4, further comprising: based on processing the major branch close instruction, checkpointing one or more completed instructions of the second stream of processing, based on there being one or more completed instructions; and making the second stream of processing a new first stream of processing.

6. The method of claim 1, wherein the second stream of processing comprises a child thread in a simultaneous multithreading processor, and the first stream of processing comprises a parent thread in the simultaneous multithreading processor.

7. The method of claim 1, wherein the type indication is included in one of the following: the opcode, a part of the opcode, and a field separate from the opcode.

27

8. The method of claim 1, wherein the at least one instruction of the one or more instructions of the second stream of processing is decoded and dispatched out-of-order with respect to at least one instruction of the first stream of processing.

9. The method of claim 8, wherein the at least one instruction is also executed out-of-order, but is completed in-order.

10. The method of claim 1, further comprising starting by the second stream of processing a third stream of processing, based on execution of a major branch open instruction in the second stream of processing.

11. The method of claim 1, further comprising restarting the first stream of processing, wherein the restarting terminates the second stream of processing.

12. The method of claim 1, further comprising controlling use of resources by the second stream of processing to prevent the second stream of processing from hindering forward progress of the first stream of processing.

13. A method of executing a machine instruction, the method comprising:

obtaining, by a processor, a machine instruction for execution, the machine instruction being defined for computer execution according to a computer architecture, the machine instruction comprising:

at least one opcode field for specifying an opcode, the opcode defining a branch operation;

a type indication to specify a type of the branch operation, wherein the same branch operation is executable in a plurality of different ways depending on the type indication, wherein the type indication specifies how the branch operation is to be processed in this execution of the machine instruction, and wherein the type indication is configured to specify the following types of execution: a minor branch in which the machine instruction is executed in a first stream of processing and the branch operation does not cause a second stream of processing to be started, a major branch open in which the machine instruction is executed in the first stream of processing and the branch operation causes the second stream of processing to be started, and a major branch close in which processing of the first stream of processing meets up with processing of the second stream of processing; and

at least one field for determining a target location in which to branch; and

executing the machine instruction, the executing being based on the type indication specifying the major branch open, the machine instruction being executed in the first stream of processing, the executing comprising:

starting the second stream of processing, the second stream of processing having a relationship with the first stream of processing in that the second stream of processing references architected state of the first stream of processing, and the second stream of processing is to execute one or more instructions starting at the target location defined using the at least one field of the machine instruction, the one or more instructions being out of sequential execution order from one or more instructions being processed by the first stream of processing, the first stream of processing continuing to process one or more instructions subsequent to the machine instruction; and

wherein execution of the second stream of processing is speculative in that at least one instruction of the one or more instructions of the second stream of processing is executed even though reaching the at least one instruction of the second stream of processing by

28

processing of the first stream of processing is tentative, and wherein updating of architected state by one or more instructions of the second stream of processing is performed based on the first stream of processing reaching a predefined point in processing.

14. A computer system for executing a machine instruction, the computer system comprising:
a memory; and

a processor in communications with the memory, wherein the computer system is configured to perform a method, said method comprising:

obtaining a machine instruction for execution, the machine instruction being defined for computer execution according to a computer architecture, the machine instruction comprising:

at least one opcode field for specifying an opcode, the opcode defining a branch operation;

a type indication to specify a type of the branch operation, wherein the same branch operation is executable in a plurality of different ways depending on the type indication, wherein the type indication specifies how the branch operation is to be processed in this execution of the machine instruction, and wherein the type indication is configured to specify the following types of execution: a minor branch in which the machine instruction is executed in a first stream of processing and the branch operation does not cause a second stream of processing to be started, a major branch open in which the machine instruction is executed in the first stream of processing and the branch operation causes the second stream of processing to be started, and a major branch close in which processing of the first stream of processing meets up with processing of the second stream of processing; and
at least one field for determining a target location in which to branch; and

executing the machine instruction, the executing being based on the type indication specifying the major branch open, the machine instruction being executed in the first stream of processing, the executing comprising:

starting the second stream of processing, the second stream of processing having a relationship with the first stream of processing in that the second stream of processing references architected state of the first stream of processing, and the second stream of processing is to execute one or more instructions starting at the target location defined using the at least one field of the machine instruction, the one or more instructions being out of sequential execution order from one or more instructions being processed by the first stream of processing, the first stream of processing continuing to process one or more instructions subsequent to the machine instruction; and

wherein execution of the second stream of processing is speculative in that at least one instruction of the one or more instructions of the second stream of processing is executed even though reaching the at least one instruction of the second stream of processing by processing of the first stream of processing is tentative, and wherein updating of architected state by one or more instructions of the

second stream of processing is performed based on the first stream of processing reaching a predefined point in processing.

* * * * *