



US 20200258343A1

(19) **United States**

(12) **Patent Application Publication**
Forutanpour et al.

(10) **Pub. No.: US 2020/0258343 A1**

(43) **Pub. Date: Aug. 13, 2020**

(54) **KIOSK FOR EVALUATING AND
PURCHASING USED ELECTRONIC
DEVICES**

H04N 5/225 (2006.01)

G06T 7/00 (2006.01)

(52) **U.S. Cl.**

CPC G07F 17/0014 (2013.01); **G06Q 30/0278**
(2013.01); **G06T 2207/30108** (2013.01); **G06T**
7/0004 (2013.01); **H04N 5/2253** (2013.01)

(71) Applicant: **ecoATM, LLC**, San Diego, CA (US)

(72) Inventors: **Babak Forutanpour**, San Diego, CA
(US); **Jeffrey Ploetner**, San Diego, CA
(US); **Robert O'Neil**, San Diego, CA
(US); **Neil Vesco**, San Diego, CA (US)

(21) Appl. No.: **16/788,169**

(22) Filed: **Feb. 11, 2020**

Related U.S. Application Data

(60) Provisional application No. 62/807,153, filed on Feb.
18, 2019, provisional application No. 62/804,714,
filed on Feb. 12, 2019.

Publication Classification

(51) **Int. Cl.**


G07F 17/00 (2006.01)

G06Q 30/02 (2006.01)

(57)

ABSTRACT

Consumer operated kiosks for recycling electronic devices are disclosed herein. In some embodiments, the kiosk includes a rotatable inspection plate configured to receive an electronic device when the inspection plate is in a first position. The kiosk can include a camera having a field of view including at least a portion of the inspection plate. The kiosk can include a wired and/or wireless connectivity device configured to connect to the electronic device and one or more processors configured to: receive characteristic information about the electronic device via the wired and/or wireless connectivity device; cause the inspection plate to rotate to a second position; receive one or more images of the electronic device via the camera when the inspection plate is in the second position; and facilitate determination of an offer price for the electronic device based at least in part on the characteristic information and the one or more images.






Fig. 1






Fig. 2






Fig. 5




Fig. 6




Fig. 7A




Fig. 7B




Fig. 7C




Fig. 7D




Fig. 7E




Fig. 7F




Fig. 7G




Fig. 8




Fig. 9




Fig. 10A




Fig. 10B




Fig. 11A




Fig. 11B




Fig. 11C




Fig. 11D




Fig. 12A



Fig. 12B




Fig. 13




Fig. 14A




Fig. 14B




Fig. 15A




Fig. 15B

Fig. 16A





Fig. 16B






Fig. 17




Fig. 18A





Fig. 18B






Fig. 19B




Fig. 20




Fig. 21




Fig. 22A




Fig. 22B




Fig. 23

KIOSK FOR EVALUATING AND PURCHASING USED ELECTRONIC DEVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to and the benefit of U.S. Provisional Application No. 62/807,153, titled KIOSK FOR EVALUATING AND PURCHASING USED ELECTRONIC DEVICES, which was filed on Feb. 18, 2019, and to U.S. Provisional Application No. 62/804,714, titled CONNECTOR CARRIER FOR ELECTRONIC DEVICE KIOSK, which was filed on Feb. 12, 2019, each of which is incorporated herein by reference in its entirety and made part of the present disclosure.

TECHNICAL FIELD

[0002] The present disclosure is generally related to consumer operated kiosks for buying mobile phones and other electronic devices from users.

BACKGROUND

[0003] There are more mobile phones in use now than there are people on the planet. The rapid growth of mobile phones is due in part on the rapid pace at which these devices evolve. Because of the rapid pace of development, a relatively high percentage of mobile phones are replaced every year as consumers continually upgrade to obtain the latest features or a better operating plan. According to the U.S. Environmental Protection Agency, the U.S. alone disposes of over 370 million mobile phones, PDAs, tablets, and other electronic devices every year. Millions of other outdated or broken mobile phones are simply tossed into junk drawers or otherwise kept until a suitable disposal solution arises.

[0004] Although many mobile phone retailers and cell carrier stores now offer mobile phone trade-in or buyback programs, many old phones still end up in landfills or are improperly disassembled and disposed of in developing countries. Unfortunately, however, mobile phones and similar devices typically contain substances that can be harmful to the environment, such as arsenic, lithium, cadmium, copper, lead, mercury and zinc. If not properly disposed of, these toxic substances can seep into groundwater from decomposing landfills and contaminate the soil with potential harmful consequences for humans and the environment.

[0005] As an alternative to retailer trade-in or buyback programs, consumers can recycle and/or sell their used mobile phones using self-service kiosks located in malls, retail stores, or other publicly accessible areas. Such kiosks are operated by ecoATM, LLC, the assignee of the present application, and aspects of these kiosks are described in, for example: U.S. Pat. Nos. 7,881,965, 8,195,511, 8,200,533, 8,239,262, 8,423,404 and 8,463,646; U.S. Provisional Patent Application Nos. 62/169,072, 62/202,330, 62/332,736 62/782,302 and 62/782,947; and U.S. patent application Ser. Nos. 14/498,763, 14/500,739, 14/506,449, 14/568,051, 14/598,469, 14/660,768, 14/663,331, 14/873,145, 14/873,158, 14/925,357, 14/925,375, 14/934,134, 14/964,963, 14/967,183, 14/966,346, 15/057,707, 15/130,851, 15/176,975 and 16/719,699, each of which is incorporated herein by reference in its entirety.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 is front, top, right isometric view of an electronic device recycling kiosk configured in accordance with embodiments of the present technology.

[0007] FIG. 2 is a front, top, left isometric view of the kiosk of FIG. 1.

[0008] FIG. 3 is a back, top, left isometric view of the kiosk of FIG. 1.

[0009] FIG. 4 is a bottom, front, right isometric view of the kiosk of FIG. 1.

[0010] FIG. 5 is a front, top, right isometric view of the kiosk of FIG. 1 with a front door and associated hardware omitted for purposes of better illustrating internal components and systems of the kiosk.

[0011] FIG. 6 is a front schematic view of an electronic device recycling kiosk configured in accordance with embodiments of the present technology.

[0012] FIG. 7A is a front, top, right isometric view of an electronic device evaluation system (DES) of the electronic device recycling kiosk of FIGS. 1-5 configured in accordance with embodiments of the present technology.

[0013] FIG. 7B is a front view of the DES of FIG. 7A.

[0014] FIG. 7C is a right side view of the DES of FIG. 7A.

[0015] FIG. 7D is a back view of the DES of FIG. 7A.

[0016] FIG. 7E is a left side view of the DES of FIG. 7A.

[0017] FIG. 7F is a top plan view of the DES of FIG. 7A.

[0018] FIG. 7G is a bottom plan view of the DES of FIG. 7A.

[0019] FIG. 8 is a back, top, right isometric view of the DES of FIG. 7A with portions of the lower housing removed for purposes of illustration.

[0020] FIG. 9 is a front, top, right isometric view of the DES of FIG. 7A with the upper and lower housings removed for purposes of illustration.

[0021] FIG. 10A is a cross-sectional side view of the DES of FIG. 7A taken along cut-plane A-A of FIG. 7B, in which a tilting assembly is in a home position and an access door is opened.

[0022] FIG. 10B is an enlarged cross-sectional side view of the tilting assembly of FIG. 7A taken along cut-plane A-A of FIG. 7B, in which the tilting assembly is in the home position and the access door is opened.

[0023] FIG. 11A is a cross-sectional side view of the DES of FIG. 7A taken along cut-plane A-A of FIG. 7B, in which the tilting assembly is in the home position and the access door is closed.

[0024] FIG. 11B is a cross-sectional side view of the DES of FIG. 7A taken along cut-plane A-A of FIG. 7B, in which the tilting assembly is in a grading position and the access door is closed.

[0025] FIG. 11C is a cross-sectional side view of the DES of FIG. 7A taken along cut-plane A-A of FIG. 7B, in which the tilting assembly is in a binning position and the access door is closed.

[0026] FIG. 11D is a back, top, right isometric view of the DES of FIG. 7A with the upper and lower housings removed for purposes of illustration.

[0027] FIG. 12A is an enlarged cross-sectional side view of a chute of the DES of FIG. 7A taken along the cut-plane A-A of FIG. 7B.

[0028] FIG. 12B is a schematic side view of a storage bin.

[0029] FIG. 13 is a cross-sectional side view of the DES of FIG. 7A taken along cut-plane A-A of FIG. 7B, in which the DES is in a repair or maintenance configuration.

[0030] FIG. 14A is an isometric view of an electronic device recycling kiosk configured in accordance with other embodiments of the present technology.

[0031] FIG. 14B is a front view of the kiosk of FIG. 14A.

[0032] FIG. 15A is a front, top, right isometric view of an electronic device evaluation system (DES) of the electronic device recycling kiosk of FIGS. 14A and 14B configured in accordance with embodiments of the present technology.

[0033] FIG. 15B is a front side elevation view of the DES of FIG. 15A.

[0034] FIG. 16A is an enlarged front, top, right isometric view of an inspection area of the DES of FIG. 15A.

[0035] FIG. 16B is an enlarged front, top, right isometric view of the inspection area of the DES of FIG. 15A, with the upper DES housing removed for purposes of illustration.

[0036] FIG. 17 is a view of connector assemblies of the DES of FIG. 15A along an axis of rotation of the primary connector assembly.

[0037] FIG. 18A is a front isometric view of a secondary connector assembly of the DES of FIG. 15A.

[0038] FIG. 18B is a rear isometric view of the secondary connector assembly of FIG. 18A.

[0039] FIG. 19A is a rear exploded view of the secondary connector assembly of FIG. 18A.

[0040] FIG. 19B is a front exploded view of the secondary connector assembly of FIG. 18A.

[0041] FIG. 20 is a cross-sectional top view of the secondary connector assembly of FIG. 18A taken along the cut-plane B-B of FIG. 17.

[0042] FIG. 21 is a schematic diagram illustrating various components associated with the kiosks of FIGS. 1-6 and 14A-14B.

[0043] FIGS. 22A and 22B illustrate a flow routing for evaluating and purchasing an electronic device from a user in accordance with embodiments of the present technology.

[0044] FIG. 23 is a schematic diagram of a suitable distributed computing environment for implementing various aspects of the present technology.

DETAILED DESCRIPTION

[0045] The following disclosure describes various embodiments of consumer operated kiosks for recycling mobile phones and other electronic devices. In some embodiments, the kiosks are sized and shaped to fit relatively small installation sites (e.g., urban retailers, airports, transportation stations, or other space-sensitive settings). The kiosks can include a housing configured to accommodate one or more displays, user interfaces, testing apparatuses, bins, device evaluation systems (DESs), and/or other kiosk components. In some embodiments, DESs configured in accordance with the present technology can include moveable and/or tiltable testing equipment configured to transition between two or more positions. For example, the DES can include a test platform, a connector assembly, and one or more upper and/or lower cameras and light assemblies, all or some of which can be configured to transition between a home position (e.g., a position in which the user interacts with the kiosk), a grading position (e.g., a position in which the kiosk/DES is configured to evaluate the condition of the phone or other electronic device to be purchased), and a binning position (e.g., a position in which the electronic device is transitioned into a bin or other holding unit after completion of the transaction with the user) by tilting one or more components of the DES about an axis of

rotation. These features can allow for a reduction in the volume of the kiosk necessary to evaluate the electronic device to be purchased and/or recycled. In some embodiments, upper and/or lower domes of the testing equipment are gray in color, in contrast to conventional domes that are white. The gray coloring of the dome(s) can reduce glare on the tested electronic device and can allow for improved device identification and/or damage detection. In certain applications, the domes can include black (or otherwise dark-colored) portions on the interior surfaces thereof to absorb excess light and further reduce glare. As a result of these and/or other features and improvements, kiosks configured according to the present technology are able to evaluate electronic devices while occupying a relatively small footprint in a retail or other setting.

[0046] Certain details are set forth in the following description and in FIGS. 1-23 to provide a thorough understanding of various embodiments of the present technology. In other instances, well-known structures, materials, operations and/or systems often associated with mobile electronic devices, mobile device recycling kiosks, etc. are not shown or described in detail in the following disclosure to avoid unnecessarily obscuring the description of the various embodiments of the technology. Those of ordinary skill in the art will recognize, however, that the present technology can be practiced without one or more of the details set forth herein, or with other structures, methods, components, and so forth.

[0047] The terminology used below is to be interpreted in its broadest reasonable manner, even though it is being used in conjunction with a detailed description of certain examples of embodiments of the technology. Indeed, certain terms may even be emphasized below; however, any terminology intended to be interpreted in any restricted manner will be overtly and specifically defined as such in this Detailed Description section.

[0048] The accompanying Figures depict embodiments of the present technology and are not intended to be limiting of its scope. The sizes of various depicted elements are not necessarily drawn to scale, and these various elements may be arbitrarily enlarged to improve legibility. Component details may be abstracted in the Figures to exclude details such as position of components and certain precise connections between such components when such details are unnecessary for a complete understanding of how to make and use the invention. Many of the details, dimensions, angles and other features shown in the Figures are merely illustrative of particular embodiments of the disclosure. Accordingly, other embodiments can have other details, dimensions, angles and features without departing from the spirit or scope of the present invention. In addition, those of ordinary skill in the art will appreciate that further embodiments of the invention can be practiced without several of the details described below. In the Figures, identical reference numbers identify identical, or at least generally similar, elements.

[0049] FIGS. 1 and 2 are front isometric views of a kiosk 10 configured in accordance with embodiments of the present technology for purchasing electronic devices (e.g., mobile phones, tablets, etc.) from a user. FIG. 3 is a rear isometric view of the kiosk 10, and FIG. 4 is a bottom isometric view of the kiosk 10. Referring to FIGS. 1-4 collectively, the kiosk 10 can include a housing 12 and one or more user interface devices 14a-d configured to facilitate

use of the kiosk 10. The user interface devices 14a-d can include a keypad 14a, an ID card reader 14b, a payment dispenser 14c, a receipt dispenser 14d, and/or other user interface devices (e.g., a thumbprint scanner) to facilitate the electronic device purchase process. As illustrated, the kiosk 10 can also include one or more displays 16a-b. The one or more displays 16a-b can include touch-screen capability for receiving user inputs in response to displayed prompts, etc. The kiosk 10 can also include an access door 18 which can retract to permit the user to submit their electronic device (not shown) for evaluation. The access door 18 can cover an aperture in a front door 20 of the kiosk 10. One or more of the user inputs 14a-d can be positioned on or in the front door 20 of the kiosk 10. In some embodiments, one or more of the user interfaces 14a-d can be positioned on or in a side wall 22 of the kiosk housing 12.

[0050] Referring to FIG. 1, the housing 12 can have a height H, a width W, and a depth D. In some embodiments, the height H is between 24-90 inches, between 30-90 inches, between 36-72 inches, and/or between 48-84 inches. In some embodiments, the width W is between 10-54 inches, between 12-48 inches, between 24-36 inches, and/or between 20-30 inches. In some embodiments, the depth D is between 15-30 inches and/or between 18-24 inches.

[0051] As illustrated in FIG. 4, the kiosk 10 can include one or more feet 24 and/or one or more casters 26. The feet 24 can be configured to adjust in height to allow for levelling of the kiosk 10 at non-level installation locations. In some embodiments, the feet 24 can be retracted upward and above the casters 26 to allow the kiosk 10 to be easily moved on the casters. In some embodiments, the casters 26 are adjustable and capable of moving downward to contact a floor or other surface upon which the kiosk 10 is installed.

[0052] FIG. 5 is an isometric view of the kiosk 10 with the front door 20 (FIG. 1) removed to illustrate internal components of the kiosk 10. The front door 20 can be configured such that it pivots (e.g., about one or more hinges) between opened and closed positions while one or both of the displays 16a-b remain stationary. Maintaining one or more of the displays 16a-b in the position illustrated in FIGS. 1-2 can allow a technician or other operator to perform maintenance and/or repair to internal components of the kiosk 10 while observing instructions on one or more of the displays 16. In some embodiments, one of the displays 16 (e.g., the upper display 16b) is connected to and moves with the front door 20 while the other display (e.g., the lower display 16a) remains in place.

[0053] The kiosk 10 can include one or more compartments 30a-b configured to accommodate the displays 16a-b. These display compartment(s) 30a-b can be positioned at or near an upper end of the kiosk 10. One or more dispensers 32a-b (e.g., receipt printers/dispensers, label printers/dispensers, cash/voucher or other remuneration dispensers, etc.) can be positioned in appropriate locations and compartments within the kiosk 10 to dispense associated receipts, labels, cash, etc. to users as needed to perform the methods described herein. CPUs and other computer hardware 35 can be positioned in a lower portion of the kiosk 10 and can be operably connected, via cables (e.g., extendable cables) and/or via wireless connectors to other components within and/or outside of the kiosk 10. In some embodiments, the kiosk 10 includes one or more power cables configured to plug into a wall outlet or other facility power source. In some embodiments, one or more energy storage units (e.g.,

batteries) can be positioned in the kiosk 10 to power the components described above. The DES 34 can be positioned at or near a lower portion of the kiosk 10 above a bin slot 36 configured to accommodate a bin or other storage receptacle for receiving purchased and/or recycled electronic device.

[0054] In some embodiments, the DES 34 can be positioned at or near the center of the kiosk 10. In other embodiments, the DES 34 can be positioned in other portions of the kiosk 10, for example. FIG. 6 illustrates a front schematic view of a kiosk 10' wherein a DES 34' can be positioned at or near one of the sidewalls of a housing 12' of the kiosk 10'. Remaining hardware 35' and user interfaces 32' can be positioned in the space above, below, and/or to the side of the DES 34'. In some configurations, positioning the DES 34' toward one side of the kiosk 10' can further reduce the overall dimensions of the kiosk 10', as the user interfaces 32' and other hardware components 35' can be positioned in a compact, localized arrangement. In some embodiments, the kiosk 10' includes a single display 16'. The single display can include touch screen capabilities and/or can display advertisements/instructions. In some embodiments, the kiosk 10' includes two displays 16a', 16b' similar in function and/or structure to the displays 16a, 16b, respectively, described above.

[0055] FIG. 7A is an enlarged front isometric view of the DES 34 removed from the kiosk 10 to better illustrate the components of the DES 34. As illustrated, the DES 34 can include an upper housing 40 and a lower housing 42. In some embodiments, the upper and lower housings 40, 42 are integrally formed with each other. In other embodiments, the upper and lower housings 40, 42 are separate parts. In some embodiments, the kiosk includes an access door assembly 44. The access door assembly 44 can be connected to the upper DES housing 40. In some embodiments, the access door assembly 44 includes a lower frame 46 mounted to the upper DES housing 40. The access door frame 46 can include an opening 48 configured to provide access to an inspection area 50 of the kiosk 10. As described in more detail below, the access door assembly 44 can include an access door 18 configured to move (e.g., slide) between a closed position and an open position (as shown in FIG. 7A) along a movement direction 53. In the closed position, the access door 18 blocks access to the electronic device inspection area 50 of the DES 34. In the open positioned, the access door 18 is moved away from the inspection area 50 as shown in FIG. 7A to allow for insertion and/or removal of an electronic device 54 into/from the inspection area 50.

[0056] FIG. 7B is a front view of the DES 34 and FIG. 7C is a right side view thereof. As illustrated in FIG. 7B, the inspection area 50 can have a width W2 (e.g., as measured parallel to the floor on which the kiosk 10 is installed) sufficient to receive a mobile phone or other electronic device 54. For example, the width W2 of the inspection area can be at least 4 inches, at least 6 inches, at least 8 inches, and/or at least 12 inches. In some embodiments, the width W2 of the inspection area 50 is between 4-10 inches, between 6-12 inches, between 8-20 inches, and/or between 10-14 inches. Preferably, the width W2 of the inspection area 50 is approximately 18 inches. As shown in FIG. 7C, the upper housing 40 can have a dome-shape, a partial dome shape, or an otherwise bulbous shape. The shape of the upper housing 40 can facilitate use of the upper housing 40 as an upper dome for visual inspection of the electronic device 54, as described in more detail below. The upper DES

housing 40 can include one or more inwardly-directed light assemblies mounted therein or thereon. For example, an upper side light assembly 56 can be mounted through a sidewall of the upper housing 40 and an upper rear light assembly 58 can be mounted through a rear wall of the upper housing 40 and directed into the upper DES housing 40. In the illustrated embodiment, each of the light assemblies 56, 58 includes the same number of lights (e.g., three lights). In some embodiments, the side light assembly 56 can include a different number of lights than the rear light assembly 58. For example, due to the shape of most electronic devices being longer than they are wide, the side light assembly 56 may include more lights than the rear light assembly 58 to better illuminate the full length of the electronic device. In some embodiments, an upper camera 60 (FIG. 7C) is mounted on or in an upper portion of the upper DES housing 40 (e.g., at or near an upper end of the upper DES housing 40).

[0057] FIG. 7D is a rear elevation view of the DES 34. As illustrated, the lower DES housing 42 can include a chute 62 or other structure through which the electronic device, as described in detail below, can be configured to fall after inspection of the device and acceptance of a purchase offer by the user. In some embodiments, a drive assembly 64, configured to facilitate tilting of the inspection area 50 and other components, as described in more detail below, is mounted on a side of the lower DES housing 42. The access door assembly 44 can include a locking mechanism 137 configured to selectively engage with one or more lock interfaces 139 on the access door 18 (e.g., on a back surface of the access door 18). For example, the lock interfaces 139 can be indentations on the back surface of the access door configured to receive a movable protrusion or other portion of the locking mechanism 137. Engaging the lock interfaces 139 with the locking mechanism 137 can inhibit or prevent the access door from moving between the opened and closed configurations without selective disengagement of the movable protrusion of the locking mechanism 137 from the lock interfaces 139.

[0058] FIGS. 7E, 7F, and 7G are a left side view, a top view, and a bottom view, respectively, of the DES 34. As illustrated in FIG. 7F, the access door 18 can include one or more guides 64 configured to engage (e.g., slidably engage) a rail 66 on a track 68. In some embodiments, the track 68 and/or rail 66 (e.g., a round rail) are mounted or otherwise attached to the access door frame 46. Engagement between the guides 64 and the rail 66 can facilitate movement of the access door 18 along the movement path 53 in two parallel and opposite directions (e.g., parallel to the length of the rail 68) while limiting movement of the access door 18 in other directions.

[0059] FIG. 8 is a rear isometric view of the DES 34 with the upper DES housing 40 and right and rear sidewalls of the lower DES housing 42 removed for purposes of illustration. The DES 34 can include an access door motor 74 (e.g., a step motor) configured to move the access door 18 between the opened position (FIG. 7A) and the closed position (FIG. 11A). For example, the access door motor 74 can be configured to rotate a sprocket 76 having teeth sized and shaped to interface with a toothed track 78 on the back side of the access door 18. Rotation of the sprocket moves 76 the access door 18 between the opened and closed positions. In some embodiments, the access door motor 74, the guides 66, and/or the track 70 include a dampening mechanism to

inhibit or prevent damaging impacts between the access door 18 and other components of the kiosk if power is cutoff from the kiosk and the access door 18 moves toward the closed position.

[0060] As illustrated in FIG. 8, The DES 34 can include a moveable evaluation subassembly (“MES”) 80. The MES 80 can include the drive assembly 64 configured to tilt/rotate one or more components of the DES 34 about a horizontal axis of rotation between two or more positions. The MES 80 can include a base plate 84 that is operably coupled to the drive assembly 64. The base plate 84 can be hingedly (e.g., rotatably) connected to the lower DES housing 42, to the upper DES housing 40, or to some other portion of the kiosk 10. Additional components can be mounted to the base plate 84, as explained in more detail below. For example, a connector carrier 85 (e.g., a primary connector carrier and/or rotatable connector carrier) can be rotatably mounted to the base plate 84 and configured to move with the base plate 84. As described in greater detail below, the connector carrier 85 can include multiple individual electrical connectors circumferentially distributed on a rotatable hub (e.g., a carousel). In some embodiments, a lower dome assembly 87 is mounted to the base plate 84 and/or otherwise configured to move with the base plate 84.

[0061] FIG. 9 is an isometric view of the MES 80 with the upper DES housing 40 and lower DES housing 42 removed for purposes of illustration. The MES 80 can further include a mirror assembly 86 that is mounted to the base plate 84. For example, the mirror assembly 86 may include one or more hinges 88 pivotably coupled to the base plate 84 to allow for rotation and/or deflection of the mirror assembly 86 with respect to the base plate 84.

[0062] As illustrated in FIGS. 8 and 9, the drive assembly 64 can include a tilt motor 90 (e.g., a stepper motor) operably coupled to a first pulley 92. The drive assembly 64 can include a drive belt 94 (e.g., a toothed belt) connected to the first pulley 92 and to a second pulley 96. The first pulley 92 and second pulley 96 can be mounted to the lower housing 42 of the DES 34 or to some other fixed structure. The tilt motor 90 can be configured to rotate the first pulley 92 to rotate the second pulley 96 via the drive belt 94. In some embodiments, the tilting assembly can include a meshed gear arrangement between the tilt motor 90 and the base plate 84 to facilitate rotation of the base plate 84. The MES 80 can include a bracket 97 rotationally locked to the second tilt pulley 96 and configured to rotate about a tilt axis 99. The bracket 97 can be mounted to the base plate 84 such that rotation of the second pulley 96 rotates the base plate 84.

[0063] Referring to FIG. 9, the MES 80 can include an inspection plate 100. The inspection plate 100 can be, for example, a transparent plate used during inspection of the phone or other electronic device 54. The inspection plate 100 can be constructed from glass, polymer, or some other suitable material (e.g., a transparent or translucent material). For example, the inspection plate 100 can be constructed from an oleophobic material or coated with an oleophobic material. Use of an oleophobic material or other smudge-resistant material can improve the performance of the kiosk 10 and reduce the need for frequent servicing to clean the inspection plate 100. In some embodiments, the inspection plate 100 and the base plate 84 are formed together as a single piece of transparent material. In some embodiments, the inspection plate 100 is mounted to the base plate 84. For example, the base plate 84 can have an aperture sized and

shaped to receive the inspection plate 100. Preferably, the upper camera 60 has a field of vision that includes all or most of the inspection plate 100.

[0064] As further illustrated in FIG. 9, the mirror assembly 86 can include a mirror plate 102 that generally surrounds the inspection area 50 on at least two sides. In some embodiments, the mirror assembly 86 includes one or more mirrors mounted to a mirror frame 104 that extends around the inspection area 50 on at least two sides. The mirror frame 104 can be formed as part of, or otherwise connected to the mirror plate 102. The mirror plate 102 and/or the mirror frame 104 can be hingedly (e.g., rotatably) connected to the base plate 84 or some other structure of the kiosk 10. In the illustrated embodiment, the mirror assembly 86 includes a first side mirror 106a positioned on a first side of the inspection area 50 and a second side mirror 106b on a second side of the inspection area 50 opposite the first side mirror 106a. In some embodiments, the mirror assembly 86 further includes a top side mirror 106c extending at least partially between the first and second side mirrors 106a, 106b. One or more of the mirrors 106a, 106b, 106c can be arranged at an angle with respect to the mirror plate 102. The angle(s) of the mirrors 106a-c with respect to the mirror plate 102 can be, for example, between 10°-85°, between 20°-80°, between 25°-55°, between 30°-60°, between 45°-65°, and/or between 40°-50°. Angling the mirrors with respect to the mirror plate 102 can enable cameras in the inspection area 50 to obtain reflected views of the sides of the phone or other electronic device 54 during inspection from a direction perpendicular or substantially perpendicular to the inspection plate 100.

[0065] In some embodiments, a lower side of the mirror frame 104 can include a shelf member 110 having one or more ridges 112, ribs, or protrusions. These ridges 112 can be configured to provide a gap G between the bottom end of the electronic device 54 and the shelf member 110. Spacing the bottom end of the phone or other electronic device 54 away from the shelf member 110 can allow light to show through the gap G so that the bottom edge of the electronic device 54 can be observed by the cameras or other imaging equipment of the kiosk 10. Viewing the bottom edge of the electronic device 54 can facilitate easier and/or more accurate evaluation of the overall size of the electronic device 54, as well as easier detection of damage to the bottom edge of the electronic device 54. In some embodiments, the ridges 112 or some other portion of the shelf member 110 include one or more lips or protrusions configured to reduce the likelihood that the electronic device 54 tips over and away from the inspection plate 100 as the inspection plate 100 moves between its various positions (see discussion of FIGS. 11A-11C below). The shelf member 110 can also include a connector slot or connector aperture through which a connector 114 from the connector carrier 85 can be inserted to connect to the phone. Further details describing structure and operation of the connector carrier 85 are described in U.S. Provisional Patent App. No. 62/804,714, titled CONNECTOR CARRIER FOR ELECTRONIC DEVICE KIOSK and filed Feb. 12, 2019, and also in Attorney Reference number 111220-8053.US01, titled CONNECTOR CARRIER FOR ELECTRONIC DEVICE KIOSK and filed Feb. 11, 2020, the entire disclosures of which are incorporated by reference herein.

[0066] FIG. 10A is a cross-sectional side view of the DES 34 that shows the DES 34 in an initial or “home” position the

MES 80 is arranged at an angle with respect to horizontal. For example, the angle A1 between the base plate 84 and horizontal can be less than 90° and greater than 0°. In some embodiments, the angle between the base plate 84 and horizontal is between 40°-80°, between 55°-75°, between 10°-85°, between 45°-70°, and/or between 30°-65° when the DES 34 is in the home position. In some embodiments, the angle between the base plate 84 and horizontal is approximately 60°. Orienting the base plate 84 at an angle less than 90° with respect to horizontal when in the home position can reduce the risk of the phone 54 inadvertently falling out of the inspection area 50. Orienting the base plate 84 an angle greater than 0° with respect to horizontal when in the home position can reduce the required depth of the kiosk 10 to accommodate the access door assembly 44 and/or other components of the kiosk 10, thereby reducing the overall size and/or footprint of the kiosk 10. In some embodiments, as illustrated in FIGS. 8 and 11D, the MES 80 can include one or more locking mechanisms 141 configured to selectively engage portions of the kiosk 10 (e.g., portions of the lower housing 42 of the DES 34) to inhibit or prevent inadvertent transition of the MES 80 between tilting positions.

[0067] As illustrated in FIG. 10A, the lower dome assembly 87 can include a lower dome 120 having a curved dome/bulbous shape. The lower dome 120 can be mounted to the base plate 84 such that the lower dome assembly 87 moves with the base plate 84 as the MES 80 drives the base plate 84 between various positions. In some embodiments, the lower dome assembly 87 includes one or more cameras and/or lighting assemblies used to inspect the phone or other electronic device. For example, the lower dome assembly 87 can include a lower camera 122 mounted to the lower dome 120. The lower camera 122 can have a field of vision that includes all or most of the inspection plate 100. In some embodiments, the lower dome assembly 87 includes first and second lighting assemblies 126, 124. Returning to FIG. 9, the mirror frame 104 can include one or more calibration structures configured to facilitate calibration of the cameras 60, 122 (e.g., after installation, repair, replacement, and/or refurbishment of one of the cameras). For example, the mirror frame 104 can include one or more visual indicators 91 (e.g., dots, protrusions, indentations, etc.) located at known positions on the mirror frame 104 and observable by one or both of the cameras 60, 122. The visual indicators 91 can be used to recalibrate evaluation of and/or scale images captured by the cameras 60, 122. One or more of the lighting assemblies (e.g., the lower rear lighting assembly 124) can be mounted on a back side of the lower dome 120. In some embodiments, another lighting assembly (e.g., the lower side lighting assembly 126) is positioned on a side of the lower dome 120.

[0068] FIG. 10B illustrates an enlarged side view of the MES 80 and other components of the kiosk 10. The upper DES housing 40 can include one or more rims or edges 128 at the boundaries of the inspection area 50. When the MES 80 is in the home position as shown, the rims 128 of the upper DES housing 40 can overlap the mirror frame 104 such that access to the interior of the upper and lower DES housings 40, 42 is closed to outside access. Access to the connector carrier 85 is also blocked by the interface between the upper DES housing 40 and the mirror frame 104.

[0069] FIGS. 11A-11C are left side cross-sectional views illustrating the DES 34 in the home position, an inspection

position, and a binning position, respectively. More specifically, FIG. 11A illustrates the access door **18** and the MES **80** in their respective default positions (e.g., the positions in which they are positioned in the absence of interaction with a user or maintenance staff). In the default position, the access door **18** is closed, thereby blocking access to the inspection area **50** of the DES **34**. A user may instruct the kiosk **10** (e.g., via a touch screen portion of one of the displays **16a-b**, and/or via one of the user interface devices **14a-d**) to open the access door **18** (e.g., as illustrated in FIG. 10B) to allow for placement of a phone or other electronic device **54** into the inspection area **50**. For example, the user may tap or press one or more buttons or icons on the displays **16a-b** or on the keypad **14a** associated with a request to begin a transaction. The user may specify, via one or more of the user interface devices **14a-d** (FIG. 1) and/or via a touch screen portion of one of the displays **16a-b**, the make and/or model of the user's electronic device **54**. The connector carrier **85** can rotate and/or move toward the inspection area **50** and present the relevant connector **114** (FIG. 9) to the inspection area **50**. After the user inputs the electronic device **54** into the inspection area **50** and connects a connector **114** (FIG. 9) thereto, the user may instruct the kiosk **10** (e.g., via a touch screen portion of one of the displays **16a-b**, and/or via one or more of the user interface devices **14a-d**) to evaluate the electronic device **54** for trade-in and/or purchase value. In some embodiments, before closing the access door **18** and/or prior to placement of the electronic device **54** into the inspection area **50**, the kiosk **10** may use the lower camera **122** to take a picture of the user through the inspection plate **100** (e.g., for adherence to second-hand dealer laws and/or for other security purposes). As illustrated in FIGS. 10B and 11A, the kiosk **10** can include one more door stops **136** configured to limit downward movement of the access door **18** and/or to define the closed position of the access door **18**.

[0070] As illustrated in FIG. 11B, the MES **80** can rotate from the home position to an evaluation (e.g., grading, inspection, etc.) position. In some embodiments, the base plate **84** and/or inspection plate **100** are positioned substantially horizontal when in the evaluation position. The kiosk **10** can be configured to evaluate the electronic device **54** when the MES **80** is in the evaluation position. Evaluation of the electronic device **54** can include visual evaluation (e.g., via the cameras **60**, **122**) and/or electrical evaluation (e.g., via the connector **114** and/or via a software application or wireless connection) to determine various information about the device that can affect the monetary value of the device. Such information can include, for example, the make, model, sub-model of the device, the device features (e.g., memory size, cell service carrier, etc.), device operability, device charge and/or rechargeability, physical condition (e.g., presence or absence of cracks, display function and condition, etc.).

[0071] Electrical evaluation, visual evaluation, grading, detection of cracks and/or of screen covers, and/or other evaluation and analysis of the electronic device **54** can be performed as described in U.S. Pat. Nos. 10,496,963; 10,475,002; 10,445,708; 10,438,174; 10,417,615; 10,401,411; 10,269,110; 10,157,427; 10,127,647; 10,055,798; 10,032,140; 9,911,102; 9,904,911; 9,885,672; 9,881,284; 9,818,160; 8,463,646; 8,423,404; 8,239,262; 8,200,533; 8,195,511; and 7,881,965; U.S. patent application Ser. Nos. 12/573,089; 12/727,624; 13/113,497; 12/785,465; 13/017,

560; 13/438,924; 13/753,539; 13/658,825; 13/733,984; 13/705,252; 13/487,299; 13/492,835; 13/562,292; 13/658,828; 13/693,032; 13/792,030; 13/794,814; 13/794,816; 13/862,395; 13/913,408; 14/498,763; 14/500,739; 14/873,158; 14/506,449; 14/925,357; 14/925,375; 14/934,134; 14/964,963; 14/568,051; 14/966,346; 14/598,469; 14/660,768; 14/663,331; 15/057,707; 15/091,487; 15/214,791; 15/630,460; 15/641,145; 15/672,157; 15/855,320; 15/901,526; 15/977,729; 16/195,785; 16/357,041; 16/534,741; 16/556,018; 16/556,104; 16/575,003; 16/575,090; and Ser. No. 16/601,492, and 16/719,699; U.S. Provisional Application No. 62/169,072, titled "METHODS AND SYSTEMS FOR VISUALLY EVALUATING ELECTRONIC DEVICES," filed by the applicant on Jun. 1, 2015; U.S. Provisional Application No. 62/202,330, titled "METHODS AND SYSTEMS FOR INSPECTING MOBILE DEVICES AND OTHER CONSUMER ELECTRONIC DEVICES WITH ROBOTIC ACTUATION," filed by the applicant on Aug. 7, 2015; U.S. Provisional Application No. 62/332,736, titled "METHODS AND SYSTEMS FOR DETECTING DAMAGE IN EDGE REGIONS OF MOBILE ELECTRONIC DEVICES," filed by the applicant on May 6, 2016; U.S. Provisional Application No. 62/804,714, titled "CONNECTOR CARRIER FOR ELECTRONIC DEVICE KIOSK," filed by the applicant on Feb. 12, 2019; U.S. Provisional Application No. 62/807,153, titled "KIOSK FOR EVALUATING AND PURCHASING USED ELECTRONIC DEVICES," filed by the applicant on Feb. 18, 2019, and U.S. Provisional Application No. 62/807,165, titled "NEURAL NETWORK BASED PHYSICAL CONDITION EVALUATION OF ELECTRONIC DEVICES, AND ASSOCIATED SYSTEMS AND METHODS," filed by the applicant on Feb. 18, 2019, and U.S. Provisional Application No. 62/950,075, titled "SYSTEMS AND METHODS FOR VENDING AND/OR PURCHASING MOBILE PHONES AND OTHER ELECTRONIC DEVICES," filed by the applicant on Dec. 18, 2019. All the patents and patent applications listed in the preceding sentence and any other patents or patent applications identified herein are incorporated herein by reference in their entireties.

[0072] In some embodiments, evaluation (e.g., electrical and/or visual inspection) of the electronic device **54** include obtaining characteristic information about the electronic device **54**, which can include device identification, make, model, and/or configuration. In other embodiments, the characteristic information can further include device functionality including hardware/software configuration, charging capability, memory capacity, etc. Information necessary to identify and/or evaluate a mobile device can include, for example, a unique identifier (e.g., an IMEI number or an MEID or equivalent number of a mobile phone, a hardware media access control address (MAC address) of a networkable device, or a model number and serial number of the electronic device); information describing the device manufacturer (e.g., a manufacturer name or ID code), model, characteristics and capabilities (e.g., CPU type and speed, storage capacity (SRAM, DRAM, disk, etc.), wireless carrier, radio bands (frequency ranges and encodings such as CDMA, GSM, LTE, etc.), and/or color, condition; and so on. In some embodiments, the electrical analysis can include evaluating the condition and/or functionality of the charging circuit of the electronic device. In particular, the testing electronics can measure the amount of charge current that

the charging circuit draws on the power lines, and the testing electronics can use the corresponding current measurement signal to determine whether the charging circuit is functional or damaged. In some embodiments, the kiosk 10 can perform the electrical analysis using one or more of the methods and/or systems described in detail in the commonly owned patents and patent applications identified herein and incorporated by reference in their entireties.

[0073] In some embodiments, the inner surface (or at least a majority thereof) of one or both of the upper dome 40 and the lower dome 120 is gray in color. Using gray upper and/or lower domes 40, 120 can enhance the vividness of shadows of the electronic device 54 cast onto the upper and lower domes 40, 120. For example, the gray color of the domes 40, 120 can absorb a portion of the light cast by the light assemblies, thereby reducing glare and increasing the vividness/crispness of the shadows. In some embodiments, one or both of the upper and lower domes 40, 120 can include a darkened (e.g., black, charcoal, or some other dark color) portion or band. For example, one or both of the domes can include a black band 132 on their respective inner surfaces. The black or darkened portions or bands 132 can absorb light and reduce glare within the domes 40, 120. Additionally or alternatively, in some embodiments, the upper and/or lower domes 40, 120 include one or more apertures there-through to allow light to escape, thereby reducing glare within the inspection area 50 and on the inner surface of the domes 40, 120. The darkened portions and/or apertures can reduce unwanted reflections of light from the phone or electronic device 54 (e.g., reflections from curved/beveled corners and/or edges) to allow for increased accuracy and reliability in the evaluation/grading process.

[0074] After the kiosk 10 evaluates the electronic device 54 as described above, the user is presented with a purchase offer via, for example, one of the displays 16a-b. The purchase price can be offered/paid in the form of, for example, cash, a voucher redeemable for cash, merchandise, services, etc., electronic value (e.g., bitcoin, e-certificates, credit to electronic payment account, etc.), credit (e.g., a prepaid credit card, debit card, gift card, etc.), coupons, loyalty points, and/or other forms of value. If the user rejects the offer (e.g., via a touch screen portion of one of the displays 16a-b, and/or via one of the user interface devices 14a-d), the MES 80 returns to the home position (FIG. 11A), the access door 18 opens, and the connector 114, if still connected to the electronic device 54, disconnects from the electronic device 54. In some transactions, the electronic device 54 may be displaced on the inspection plate 100 from its original home position. For example, the electronic device 54 may tilt in a direction parallel to the face of the inspection plate 100. In some such situations, the electronic device 54 may become jammed between, for example, the access door frame 46 and the inspection plate 100. The kiosk 10 can be configured to detect such a jam and retract the MES 80 a small distance toward the evaluation position. The MES 80 may be locked in this intermediate position while the access door 18 opens to allow the user to retrieve their electronic device 54. Use of this intermediate position (e.g., a locked intermediate position) between the evaluation position and the home position can reduce the likelihood of damage to the electronic device 54 and/or to the kiosk 10 during operation.

[0075] If the user accepts the offer from the kiosk 10 and inputs that decision into the kiosk 10 (e.g., via a touch screen

portion of one of the displays 16a-b, and/or via one of the user interface devices 14a-d), the MES 80 rotates further downwardly about the pivot axis 99, as illustrated in FIG. 11C. In some embodiments, the offer price (e.g., cash, voucher, or some other type of remuneration) is dispensed to the user after acceptance (e.g., via the payment dispenser 14c and/or electronically into an account of the user). In some embodiments, the DES 34 includes a mirror stop 136 configured to engage the mirror frame 104 and prevent it from tilting down beyond a predetermined position (e.g., beyond the grading position). For example, the mirror stop 136 can contact a portion of the mirror frame 104 and/or the mirror plate 102 to prevent movement of the mirror assembly 86 downwardly past the mirror stop 136. As illustrated in FIG. 11D, the base plate 84 can include one or more notches 140 configured to allow the base plate 84 to move past the one or more mirror stops 136 as the MES 80 rotates between the grading position and the binning position. As illustrated in FIG. 11C, the mirror frame 104 can tilt upward relative to the hinges 88 (due, e.g., to the interference by the mirror stop 136) while the remainder of the MES 80 tilts downward. Separating the mirror frame 104 from the inspection plate 100 in this manner enables the electronic device 54 to slide off the inspection plate 100 in a direction 142 toward the chute 62 without hitting or otherwise contacting the mirror frame 104.

[0076] FIG. 12A is an enlarged elevation view of the chute 62 and associated components. The chute 62 can include a moveable flap or panel 144. The panel 144 can be configured to rotate about a hinge 146. When the phone or other electronic device 54 contacts the panel 144, the panel 144 can rotate about the hinge 146 to dampen the momentum of the electronic device 54 and reduce the risk of damage to the electronic device 54 during the binning process. A counterbalance 150 can be connected to the panel 144 on a side of the hinge 146 opposite the panel 144. The counterbalance 150 can be sufficiently heavy to bias the panel 144 to the closed position illustrated in FIG. 12A, but light enough to permit a phone or electronic device 54 to deflect the panel 144 as the electronic device 54 passes through the chute 62. After sliding down the panel 144, the device 54 contacts a lower plate 148 configured to direct the electronic device 54 into a waiting bin 170. In some embodiments, the chute 62 includes a sensor 152 (e.g., a Hall-effect sensor or other sensor) configured to detect when the panel 144 is in a deflected position. Should the sensor 152 detect that the panel 144 remains in the deflected position for longer than a predetermined period of time (e.g., less than 2 seconds, less than 5 seconds, less than 10 seconds, and/or less than 30 seconds), the kiosk 10 can be configured to cease operation and/or alert repair personnel that the chute 62 is malfunctioning. Such malfunctions can include a full or overfull bin, an electronic device stuck in the chute 62, and/or other malfunction.

[0077] In some embodiments, as illustrated in FIG. 12B, the bin 170 includes a protrusion 172 (e.g., a conical, pyramidal, cylindrical, and/or some other shape) extending from a lower surface of the bin. The protrusion 172 can be sized and shaped such that electronic devices contact the protrusion 172 before settling in the bottom of the bin 170. The protrusion 172 can act a diverter to randomize the distribution of electronic devices within the bin 170 to reduce the likelihood of overfilling only a portion of the bin 170 while other portions of the bin remain unfilled. In some

embodiments, the protrusion 172 provides a softer landing for the device 54 than the bottom of the bin 170 (e.g., the protrusion 172 breaks the fall of the electronic device 54 between the tilt plate and the bottom of the bin 170). In some embodiments, one or more of the cameras of the kiosk can be configured to monitor the transition of the electronic device 54 through the chute 62 to confirm exit of the electronic device 54 from the DES 34. In some embodiments, the bin 170 can be prelabelled, addressed, and/or otherwise ready for shipment once the bin 170 is sealed. In some embodiments, the kiosk 10 is configured to determine the amount of filler and/or air pouches recommended for inclusion in the bin 170 to reduce the likelihood of damage to the electronic devices in transit. Such determinations can be made, for example, based on automatic volume estimates based on the number and types of the electronic devices purchased by the kiosk 10 and introduced to the bin 170. The bin 170 can have a size and shape to encourage and/or ensure that the electronic devices are oriented in an orderly (e.g., co-aligned and/or stacked) configuration within the bin 170 to reduce wasted space in the bin 170. In some embodiments, maintenance of the kiosk and/or retrieval of the bins 170 is crowd-sourced. In some embodiments, independent vendors are notified of the types and quantities of electronic devices gathered in the bin 170 and given the opportunity to bid for or purchase the bin 170 and retrieve the bin 170 directly from the kiosk 10.

[0078] As those of ordinary skill in the art will appreciate, the foregoing routines are but some examples of ways in which the kiosk 10 can be used to recycle or otherwise process consumer electronic devices such as mobile phones. Although the foregoing examples are described in the context of mobile phones, it should be understood that kiosk 10 and various embodiments thereof can also be used in a similar manner for recycling virtually any consumer electronic device, such as MP3 players, tablet computers, PDAs, and other portable devices, as well as other relatively non-portable electronic devices such as desktop computers, printers, devices for playing games, entertainment or other digital media on CDs, DVDs, Blu-ray, etc. Moreover, although the foregoing examples are described in the context of use by a consumer, the kiosk 10 in various embodiments thereof can similarly be used by others, such as store clerk, to assist consumers in recycling, selling, exchanging, etc. their electronic devices.

[0079] FIG. 13 illustrates the DES 34 in a repair or maintenance position. In the repair position, the access door 18 is in the opened position and the MES 80 is in the grading (e.g., horizontal) position. In such a configuration, the repair personnel have access to the mirror assembly 86, lower dome assembly 87, connector carrier 85, and/or to other components in the interior of the DES 34 via an access aperture 150 in the upper dome 40.

[0080] FIG. 14A is a front isometric view of a kiosk 1010 configured in accordance with other embodiments of the present technology for purchasing electronic devices (e.g., mobile phones, tablets, etc.) from a user. Certain features of the kiosk 1010 (and of the DES 1034, described below) are similar in structure and/or function to, or the same as, features of the kiosk 10 described above. Such features of the kiosk 1010 are identified by reference numbers identical to those used with respect to the kiosk 10, but with the addition of 1000. For example, the kiosk 1010 includes first and second displays 1016a-b that are similar to or the same

as the first and second displays 16a-b described above with respect to the kiosk 10. The kiosk 1010 can include a housing 1012 with a height H2, a depth D2, and a width W3 similar to or the same as the height H, the depth D, and the width W, respectively of the kiosk 10.

[0081] FIG. 14B is a front view of the kiosk 1010 and illustrates an arrangement of user interface devices 1014a-d that is different from the arrangement of user interface devices 14a-d of the kiosk 10. For example, an ID card reader 1014b and a payment dispenser 1014c are positioned to one side of the electronic device inspection area 1050. A keypad 1014a and/or a receipt dispenser 1014d can also be positioned to the side and/or below the inspection area 1050. In some embodiments, one or more of the user interface devices 1014a-d are positioned above the inspection area 1050. The inspection area 1050 is positioned closer to a side of the kiosk 1010 (i.e., farther from the center of the kiosk 1010) than the area 50 of the kiosk 10. The inspection area 1050 can have a width W4 that is greater than the width W2 of the inspection area 50 described above. As explained below, the width W4 of the inspection area 1050 can be at least partially attributed to the presence of one or more connectors in addition to the connector carrier 85.

[0082] FIGS. 15A and 15B are enlarged front isometric and front views, respectively, of the DES 1034 removed from the kiosk 1010 to better illustrate the components of the DES 1034. The DES 1034 includes an access door 1018 configured to slide along the track 1068 in a manner similar to the same as described above with respect to the door 18 and track 68 of the DES 34. Movement of the access door 1018 along the track 1068 can prohibit and allow access to the inspection area 1050. The track 1068 can be mounted to the upper DES housing 1040. In some embodiments, the track 1068 is mounted to the access door frame 1046.

[0083] In use, a mobile phone or other electronic device 1054 can be placed into or removed from the inspection area 1050 when the access door 1018 is in a raised position (i.e., the position illustrated in FIGS. 15A-15B). The DES 1034 can include an inspection plate 1100 similar to or the same as the inspection plate 100 described above. The inspection plate 100 can be connected to other mechanisms of the DES 1034 configured to tilt or otherwise move the inspection plate 1100 in a manner similar to or the same as the movement tilting of the inspection plate 100 described above. For conciseness, features of the DES 1034 which are functionally and/or structurally equivalent to the features of the DES 34 described above will not be re-described.

[0084] FIG. 16A is an isometric view of the inspection area 1050 of the DES 1034. The kiosk 1010 can include one or more secondary connectors 1115a-b in addition to the connector 114 (i.e., the connectors 114, collectively, of the primary connector carrier 85). For example, the kiosk 1010 can include a first secondary connector 1115a positioned to one side of the connector 114 and a second secondary connector 1115b positioned on an opposite side of the connector 114. The first and second secondary connectors 1115a-b (as well as the connector 114) can be selected so that all, or at least most, of the commercially available mobile phones and other mobile electronic devices can be connected to the primary connector carrier 85 and/or to the first and second secondary connectors 1115a-b. For example, in some embodiments the connectors 114, 1115a-b can include Mini-USB, Micro-USB, USB-C and/or Lightning connectors. Positioning the first and second secondary

connectors **1115a-b** on opposite sides of the primary connector carrier **85** can allow the primary connector carrier **85**, and its several different connectors **114**, to be used for non-foldable phones and other electronic devices while the secondary connectors **1115a-b** are used to connect to foldable phones and other electronic devices with offset connection port. In some embodiments, both the first secondary connector **1115a** and the second secondary connector **1115b** are the same type of connector (e.g., Mini-USB, Micro-USB, USB-C, Lightning, etc.), and in other embodiments the first and second secondary connectors **1115a-b** are different from each other.

[0085] As described above, the secondary connectors **1115a-b** can be positioned to accommodate foldable phones or other electronic devices having data and/or electrical connectors in non-central positions. In some embodiments, the secondary connectors **1115a-b** are configured to accommodate electronic devices having nonstandard connector types. The secondary connectors **1115a-b** can be configured to remain retracted with the kiosk **1010** unless and until a user designates that they wish the kiosk **1010** to evaluate a foldable phone. The kiosk **1010** can be configured to extend one or both of the secondary connectors **1115a-b** if a user indicates (e.g., via a touch screen on the displays **1016a-b**) that the electronic device to be evaluated is a device with an offset electrical connector (e.g., a foldable phone).

[0086] FIG. 16B is an isometric view of the inspection area **1050** of the DES **1034** with the shelf **1110** and upper DES housing **1040** removed for clarity. The secondary connectors **1115a-b** are connected to secondary connector assemblies **1089a-b**. The secondary connector assemblies **1089a-b** can be separate from the primary connector carrier **85**. In some embodiments, the secondary connector assemblies **1089a-b** are electrically connected to the primary connector carrier **85** (e.g., via connection to one or more sockets in the primary connector carrier **85**). The secondary connector assemblies **1089a-b** can be mounted to the base plate **1084** or to some other structure of the kiosk **1010**, as discussed in detail with respect to FIG. 20.

[0087] FIG. 17 is a front view of the primary connector carrier **85** and the secondary connector assemblies **1089a-b**, as observed parallel to an axis of rotation of the connector carrier **85**. The first secondary connector assembly **1089a** is illustrated in a lowered or retracted position, while the second secondary connector assembly **1089b** is illustrated in a raised or extended position. Retraction and extension of the secondary connector assemblies **1089a-b** can be controlled in response to user input (e.g., via a touch screen portion of one of the displays **1016a-b**, and/or via one of the user interface devices **1014a-d**) identifying a foldable phone to be evaluated. The secondary connectors **1115a-b** may be necessary for foldable phones, as the data/charging ports on many foldable phones are positioned at or near the center of one segment of the phone (e.g., on one half or one third of the foldable phone). Such port positioning puts the port at an off-center portion of the foldable phone when the foldable phone is unfolded. In some embodiments, retraction and extension of the secondary connector assemblies **1089a-b** is controlled in response to visual inspection and identification of a foldable phone within the kiosk (e.g., via one or more of the cameras within the kiosk). For example, visual inspection of an electronic device may reveal connection ports in offset positions, folding features, and/or other indicators that the electronic device is a foldable phone.

[0088] FIGS. 18A-18B are isometric views of the secondary connector assembly **1089a**, while FIGS. 19A-19B are exploded views thereof. As illustrated, the secondary connector assembly **1089a** includes a connector **1115a**, a connector holder **1360**, an electrical cable **1362**, and a base connector **1366** (e.g., a universal cable connector, such as a USB connector). The electrical cable **1362** the first end portion electrically connected to the connector **1115a** and a second portion electrically connected to the base connector **1366**. To hold (e.g., fixedly hold) the phone connector **1115a** in its proper position relative to the shelf member **1110**, the connector **1115a** is received in a corresponding connector holder **1360**, which in turn is held in a corresponding retaining bracket **1364**. The connector holder **1360** can include asymmetric protrusions on either side thereof and/or other dimensional features to ensure that the holder **1360** is positioned in the corresponding retaining brackets **1364** in the correct orientation (e.g., with the tip of the connector **1115a** pointing upward). The base connector **1366** is operably received in a corresponding connector socket within the kiosk **1010**.

[0089] The secondary connector assembly **1089a** can have a drive assembly including a motor **1400** (e.g., an electric motor), a motor frame **1402**, a cam drive **1404**, and a driven bracket **1408**. The motor **1400** can be mounted within the kiosk **1010** via the motor frame **1402**. For example, the motor frame **1402** can be fastened or otherwise connected to the base plate **1084** or some other component of the kiosk **1010**. The motor **1400** can be configured to drive rotation of the cam drive **1404**. The cam drive **1404**, in turn, can be configured to drive movement of the driven bracket **1408** up and down. For example, the cam drive **1404** can include a cam coupling **1410** (FIG. 19A) configured to receive a driveshaft **1412** of the motor **1400**. The cam drive **1404** can be configured to translate rotation of the driveshaft **1412** (FIG. 19B) into linear motion of the driven bracket **1408**. More specifically, the cam drive **1404** can include the cam tab **1416** (FIG. 19B) configured to engage with a cam receiver **1418** (FIG. 19A) of the driven bracket **1408**. The cam receiver **1418** can be, for example, a slot configured to receive the cam tab **1416**.

[0090] The driven bracket **1408** can be coupled to the retaining bracket **1364** either directly or indirectly. Preferably, the retaining bracket **1364** and driven bracket **1408** are rotationally and translationally affixed to each other when assembled. For example, one or more fasteners, adhesives, or other coupling methods and structures can be used to couple the driven bracket **1408** the retaining bracket **1364**. One or both of the driven bracket **1408** and the retaining bracket **1364** can include alignment features configured to maintain desired alignment between the driven bracket **1408** and retaining bracket **1364**. Maintaining alignment between the driven bracket **1408** and the retaining bracket **1364** can reduce the likelihood of motion of the driven bracket **1408** in directions other than the desired extension and retraction directions. The alignment features can include one or more protrusions or indentations on one or both of the retaining bracket **1364** and the driven bracket **1408**. For example, the retaining bracket **1364** can include one, two, or more protrusions **1420** (FIG. 19A) configured to engage one, two or more indentations **1422** (FIG. 19B) in the driven bracket **1408**.

[0091] Returning to FIG. 18A, the connector holder **1360** can be coupled to the retaining bracket **1364** via one or more

retaining mechanisms **1424**. The retaining mechanism **1424** can be, for example, a clip or other structure configured to releasably engage with one or both of the connector holder **1360** and the retaining bracket **1564**. The retaining mechanism **1424** can include a retaining tab **1430** configured to engage with the retaining slot **1432** in the connector holder **1360**. The retaining mechanism **1424** can include a release mechanism **1434** configured to allow the user to quickly and easily release the retaining mechanism **1424** from the connector holder **1360**. For example, the release mechanism **1434** can be a flange or other protrusion configured to be pulled or otherwise manipulated to release the retaining tab **1430** from the retaining slot **1432**.

[0092] FIG. 20 is a cross-sectional view of the secondary connector assembly **1089a** is taken along the cut plane **20-20** in FIG. 17. As discussed above, the secondary connector assembly **1089a** can be mounted to the base plate **1084**. More specifically, the retaining bracket **1364** and driven bracket **1408** can clamp onto or otherwise capture a portion of the base plate **1084**. Connection between the retaining bracket **1364** and the driven bracket **1408** can be tight enough to reduce the risk of vibration between the connector assembly **1089a** and the base plate **1084** while being loose enough to allow translational motion of the connector assembly **1089a** with respect to the base plate **1084**. For example, one or both of the driven bracket **1408** and the retaining bracket **1064** can include a spacing portion **1430** (e.g., a protrusion, or other structure extending between the driven bracket **1408** and the retaining bracket **1064**) which spaces the driven bracket **1408** from the retaining bracket **1064**. This spacing can form one or more channels **1433** or tracks in which retained portions **1435** of the base plate **1084** can be captured. The spacing portion **1430** can inhibit or prevent over tightening of the driven bracket **1408** and retaining bracket **1064** onto the retained portions **1435** of the base plate **1084**. In some embodiments, one or more fasteners **1436** extend at least partially through the spacing portion **1430** to connect the driven bracket **1408** the retaining bracket **1064**. The channels **1433** and retained portions **1435** can be configured to permit linear motion of the secondary connector assembly **1089a** in the retraction and extension directions while preventing translation or rotation of the secondary connector assembly **1089a** in other directions. While FIGS. 18A-20 illustrate and describe the components and features of the first secondary connector assembly **1089a**, it should be noted that the second secondary connector assembly **1089b** can be identical to or substantially identical to the first secondary connector assembly **1089a** in both structure and function.

[0093] FIG. 21 provides a schematic representation of an architecture of the kiosk **10**, **1010** configured in accordance with embodiments of the present technology. In the illustrated embodiment, the kiosk **10**, **1010** includes a suitable processor or central processing unit (CPU) **2100** that controls operation of the kiosk **10**, **1010** in accordance with computer-readable instructions stored on system memory **2106**. The CPU **2100** may be any logic processing unit, such as one or more CPUs, digital signal processors (DSPs), application-specific integrated circuits (ASICs), etc. The CPU **2100** may be a single processing unit or multiple processing units in a device or distributed across multiple devices. The CPU **2100** is connected to the memory **2106** and may be coupled to other hardware devices, for example, with the use of a bus (e.g., a PCI Express or Serial ATA bus).

The CPU **2100** can include, by way of example, a standard personal computer (PC) (e.g., a DELL OPTIPLEX 7010 PC) or other type of embedded computer running any suitable operating system, such as Windows, Linux, Android, iOS, or an embedded real-time operating system. In some embodiments, the CPU **2100** can be a small form factor PC with integrated hard disk drive (HDD) or solid-state drive (SSD) and universal serial bus (USB) or other ports to communicate with the other components of the kiosk **10**, **1010**. In other embodiments, the CPU **2100** can include a microprocessor with a standalone motherboard that interfaces with a separate HDD. The memory **2106** can include read-only memory (ROM) and random access memory (RAM) or other storage devices, such as disk drives or SSDs, that store the executable applications, test software, databases and other software required to, for example, control kiosk components, process electronic device information and data (to, e.g., evaluate device make, model, condition, pricing, etc.), communicate and exchange data and information with remote computers and other devices, etc.

[0094] The CPU **2100** can provide information and instructions to kiosk users via the display screen **16**, **1016** and/or an audio system (e.g., a speaker) **2104**. The CPU **2100** can also receive user inputs via, e.g., a touch screen **2108** associated with the display screen **16**, **1016**, a keypad with physical keys, and/or a microphone **2110**. Additionally, the CPU **2100** can receive personal identification and/or biometric information associated with users via the ID reader **14b**, **1014b**, one or more external cameras **2116**, and/or a fingerprint reader **2114**. In some embodiments, the CPU **2100** can also receive information (such as user identification and/or account information) via a card reader **2112** (e.g., a debit, credit, or loyalty card reader having, e.g., a suitable magnetic stripe reader, optical reader, etc.). The CPU **2100** can also control operation of the label dispenser **110** and systems for providing remuneration to users, such as the payment dispenser **14c**, **1014c** and/or a receipt or voucher printer **32a-b** and an associated dispenser **14d**, **1014d**.

[0095] As noted above, the kiosk **10**, **1010** additionally includes a number of electronic, optical and electromechanical devices for electrically, visually and/or physically analyzing electronic devices placed therein for recycling. Such systems can include one more internal cameras **60**, **122** for visually inspecting electronic devices for, e.g., determining external dimensions and condition, and one or more of the electrical connectors **114**, **1115** (e.g., USB connectors) for, e.g., powering up electronic devices and performing electronic analyses. As noted above, the cameras **60**, **122** can be operably coupled to the upper and lower chambers **40**, **1040** and **120**, and one or more of the connectors **114**, **1115** can be movably and interchangeably carried by the connector assemblies **85**, **1089**. The kiosk **10**, **1010** further includes a plurality of mechanical components that are electronically actuated for carrying out the various functions of the kiosk **10**, **1010** during operation. The mechanical components **2118** can include, for example, the inspection area access door **18**, **1018** and one or more of the movable components (e.g. the inspection plate **100**, **1100**, the upper and lower chambers **40**, **1040** and **120**, etc.) operably associated with the inspection area **50**, **1050**. The kiosk **10**, **1010** further includes power **2102**, which can include battery power and/or facility power for operation of the various electrical components associated with kiosk operation.

[0096] In the illustrated embodiment, the kiosk **10**, **1010** further includes a network connection **2122** (e.g., a wired connection, such as an Ethernet port, cable modem, FireWire cable, Lightning connector, USB port, etc.) suitable for communication with, e.g., all manner of remote processing devices via a communication link **2150**, and a wireless transceiver **2124** (e.g., including a Wi-Fi access point, Bluetooth transceiver, near-field communication (NFC) device, and/or a wireless modem or cellular radio utilizing GSM, CDMA, 3G, 4G and/or 5G technologies, each of which may include an associated antenna or antennas) for data communications suitable for communication with, e.g., all manner of remote processing devices via the communication link **2150** and/or directly via, e.g., a wireless peer-to-peer connection. For example, the wireless transceiver **2124** can facilitate wireless communication with handheld devices, such as a mobile device **54**, **1054**, **2130** (e.g., a smartphone) either in the proximity of the kiosk **10**, **1010** or remote therefrom. By way of example only, in the illustrated embodiment the mobile device **54**, **1054**, **2130** can include one or more features, applications and/or other elements commonly found in smartphones and other known mobile devices. For example, the mobile device **54**, **1054**, **2130** can include a CPU and/or a graphics processing unit (GPU) **2134** for executing computer readable instructions stored on memory **2136**. In addition, the mobile device **54**, **1054** can include an internal power source or battery **2132**, a dock connector **2146**, a USB port or other connection port **2148**, a camera **2140**, and/or well-known input devices, including, for example, a touch screen **2142**, a keypad, etc. In many embodiments, the mobile device **54**, **1054** can also include a speaker **2144** for two-way communication and audio playback. In addition to the foregoing features, the mobile device **54**, **1054** can include a mobile operating system (OS) **2131** and/or a device wireless transceiver that may include one or more antennas **2138** for wirelessly communicating with, for example, other mobile devices, websites, and the kiosk **10**, **1010**. Such communication can be performed via, e.g., the communication link **2150** (which can include the Internet, a public or private intranet, a local or extended Wi-Fi network, cell towers, the plain old telephone system (POTS), etc.), direct wireless communication, etc.

[0097] Unless described otherwise, the construction and operation of the various components shown in FIG. **21** are of conventional design. As a result, such components need not be described in further detail herein, as they will be readily understood by those skilled in the relevant art. In other embodiments, the kiosk **10**, **1010** and/or the mobile device **54**, **1054** can include other features that may be different from those described above. In still further embodiments, the kiosk **10**, **1010** and/or the mobile device **54**, **1054** can include more or fewer features similar to those described above.

[0098] FIGS. **22A** and **22B** are flow diagrams of a routine **2200** for operating the kiosk **10**, **1010** in accordance with embodiments of the present technology. In some embodiments, all or portions of the routine **2200** can be performed by the processor **2100** described above with reference to FIG. **21**, in accordance with computer-readable instructions stored on the memory **2106**. Referring first to FIG. **22A**, the routine begins when the user approaches the kiosk **10**, **1010**. The routine **2200** then proceeds to block **2202** wherein the user to initiate the transaction with the kiosk **10**, **1010**. For

example, the user may approach the kiosk **10**, **1010** and indicate (via, e.g., interactions with the display **16**, **1016**) that the user wishes to sell an electronic device that the user currently owns (e.g., a mobile phone).

[0099] After the transaction is initiated, the routine **2200** proceeds to block **2204** wherein the user may identify the type of electronic device they wish to be evaluated (e.g., via a touch screen portion of one of the displays **16a-b**, **1016a-b** and/or via one of the user interface devices **14a-d**, **1014a-d**). In decision block **2206**, the routine **2200** determines whether the electronic device is wirelessly connected to the kiosk **10**, **1010**. For example, confirming wireless connection can include receiving user input to the kiosk via the electronic device, wirelessly sending a confirmation code to the electronic device from the kiosk for entry by the user on one of the displays **16a-b**, **1016a-b** or user inputs **14a-b**, **1014a-b**, and/or some other confirmation method known in the art. If so, the routine proceeds to block **2210** wherein the access door the kiosk is opened to provide access to the inspection area of the kiosk. If no wireless connection exists between the electronic device and the kiosk **10**, **1010**, the routine proceeds to block **2208** wherein an appropriate electrical connector (e.g., a connector configured to connect to a docking port, data port, charging port, and/or some other port of the electronic device) is presented. Determining the appropriate electrical connector can be accomplished by receiving user input (e.g., via a touch screen portion of one of the displays **16a-b**, **1016a-d**, and/or via one of the user interface devices **14a-d**, **1014a-d**) identifying the make/model of the electronic device. In some embodiments, the user may be asked (e.g., via one of the displays **16a-d**, **1016a-d**) to select the type of electrical connector appropriate for the electronic device. In some embodiments, the electrical connector is presented after the access door is opened. In some embodiments, even in the presence of a wireless connection between the electronic device and the kiosk **10**, **1010**, the kiosk presents a wired electrical connector to the user. Presentation of the connector can include, for example, rotation of the primary connector carrier **85** and/or extension of one of the secondary connectors **1115**.

[0100] In some embodiments, after the access door is opened, the user will be instructed (e.g., via one of the displays **16a-b**, **1016a-b**) to connect the electronic device to the kiosk, if such a connection is not already established. Once the electronic device is connected to the kiosk, the routine **2200** can proceed to block **2214** wherein the access door is closed. The access doors also locked to prevent the user or other persons from accessing the electronic device during inspection and from accessing the interior of the kiosk **10**, **1010**.

[0101] As illustrated in FIG. **22B**, the routine **2200** can proceed to block **2216**, wherein the evaluation assembly of the kiosk is rotated from the home position (FIG. **11A**) to an evaluation position (FIG. **11B**). In some embodiments, the electrical connector is disconnected from the electronic device before or when the evaluation assembly is in the evaluation position. The routine **2000** can proceed to block **2221** evaluation assembly is in the evaluation position. At block **2220**, the electronic device is evaluated. Evaluation of the device includes evaluation of the physical condition of the device (e.g., detecting damage or other wear), confirmation of the type of device (e.g., make and model), and/or evaluation of the functional condition of the device (e.g., battery charge, wireless capability, screen functionality,

etc.). These evaluations can be accomplished via visual inspection and/or electrical inspection of the device within the kiosk **10**, **1010**. In some embodiments, a visual inspection is performed by remote personnel observing the electronic device via the one or more cameras of the kiosk. In some embodiments, visual inspection is performed, at least in part, via a neural network applying machine learning, as described in U.S. Provisional Patent Application No. 62/807,165, entitled NEURAL NETWORK BASED PHYSICAL CONDITION EVALUATION OF ELECTRONIC DEVICES, AND ASSOCIATED SYSTEMS AND METHODS and filed Feb. 18, 2019 (attorney reference number 111220-8054.US00), the entire disclosure of which is incorporated by reference herein and made part of the present disclosure. Device evaluation can also include determining a purchase offer for the electronic device. In some instances, purchase offer is a cash offer or equivalent. In other instances, the purchase offer may be for trade-in credit, retail credit, or some other non-cash compensation. Depending on the condition of the device, the offer may be for recycling-only, without financial remuneration.

[**10102**] After evaluation and valuation of the electronic device, the routine **2200** can proceed to block **2222** wherein the offer is presented to the user. The routine then proceeds to decision block **2224** wherein the user either accepts the offer or rejects the offer. Should the user reject the offer, the routine **2200** proceeds to block **2226** wherein the evaluation assembly is returned to the home position. In block **2228** the access door is opened. Finally, a block **2230**, the electronic device is returned to the user via the access door.

[**10103**] If, however, the user accepts the offer, the routine proceeds to block **2234** to disconnect the electrical connector from the electronic device (if such disconnection did not already occur). The routine **2200** then proceeds to block **2236** wherein the evaluation assembly is further rotated to a binning position (FIG. **11C**). In the binning position, the inspection plate and/or other components of the evaluation assembly are oriented to cause the electronic device to move from the evaluation assembly to a bin (block **2238**) or other receptacle. The bin can be positioned within the kiosk **10**, **1010** or adjacent the kiosk **10**, **1010**. Preferably, the bin is secured via one or more locks or other mechanisms configured to inhibit or prevent access to the electronic device is within the bin by unauthorized persons. The access door of the kiosk **10**, **1010** can remain closed and locked during one or more of blocks **2234-2240**.

[**10104**] In some embodiments, the routine include block **2240**, in which remuneration determined in block **2222** is provided to the user. Remuneration can be dispensed by the kiosk payment dispenser **14c**, **1014c**, directly deposited into a user's account, or otherwise provided to the user. In some embodiments, remuneration is delayed until receipt and inspection of the electronic device at a remote evaluation facility.

[**10105**] FIG. **23** is a schematic diagram of a suitable network environment for implementing various aspects of an electronic device recycling system **2300** configured in accordance with embodiments of the present technology. In the illustrated embodiment, a plurality of the kiosks **10**, **1010** (identified individually as kiosks **100a**, **1010a-10n**, **1010n**) can exchange information with one or more remote computers (e.g., one or more server computers **2304**) via the communication link **2150**. Although the communication link **2150** can include a publicly available network (e.g., the

Internet with a web interface), a private communication link, such as an intranet or other network can also be used. Moreover, in various embodiments the individual kiosks **10**, **1010** can be connected to a host computer (not shown) that facilitates the exchange of information between the kiosks **10**, **1010** and remote computers, other kiosks, mobile devices, etc.

[**10106**] The server computer **2304** can perform many or all of the functions for receiving, routing and storing of electronic messages, such as webpages, audio signals and electronic images necessary to implement the various electronic transactions described herein. For example, the server computer **2304** can retrieve and exchange web pages and other content with an associated database or databases **2306**. In some embodiments, the database **2306** can include information related to mobile phones and/or other consumer electronic devices. Such information can include, for example, make, model, serial number, International Mobile Equipment Identity (IMEI) number, carrier plan information, pricing information, owner information, etc. In various embodiments the server computer **2304** can also include a server engine **2308**, a web page management component **2310**, a content management component **2312**, and a database management component **2314**. The server engine **2308** can perform the basic processing and operating system level tasks associated with the various technologies described herein. The webpage management component **2310** can handle creation and/or display and/or routing of web or other display pages. The content management component **2312** can handle many of the functions associated with the routines described herein. The database management component **2314** can perform various storage, retrieval and query tasks associated with the database **2306**, and can store various information and data such as animation, graphics, visual and audio signals, etc.

[**10107**] In the illustrated embodiment, the kiosks **10**, **1010** can also be operably connected to a plurality of other remote devices and systems via the communication link **2150**. For example, the kiosks **10**, **1010** can be operably connected to a plurality of user devices **2318** (e.g., personal computers, laptops, handheld devices, etc.) having associated browsers **2320**. Similarly, as described above the kiosks **10**, **1010** can each include wireless communication facilities for exchanging digital information with wireless-enabled electronic devices, such as the electronic device **730**. The kiosks **10**, **1010** and/or the server computer **2304** are also operably connectable to a series of remote computers for obtaining data and/or exchanging information with necessary service providers, financial institutions, device manufactures, authorities, government agencies, etc. For example, the kiosks **10**, **1010** and the server computer **2304** can be operably connected to one or more cell carriers **2322**, one or more device manufacturers **2324** (e.g., mobile phone manufacturers), one or more electronic payment or financial institutions **2328**, one or more databases (e.g., the GSMA IMEI Database, etc.), and one or more computers and/or other remotely located or shared resources associated with cloud computing **2326**. The financial institutions **2328** can include all manner of entity associated with conducting financial transactions, including banks, credit/debit card facilities, online commerce facilities, online payment systems, virtual cash systems, money transfer systems, etc.

[**10108**] In addition to the foregoing, the kiosks **10**, **1010** and the server computer **2304** can also be operably con-

nected to a resale marketplace **2330** and a kiosk operator **2332**. The resale marketplace **2330** represents a system of remote computers and/or services providers associated with the reselling of consumer electronic devices through both electronic and brick and mortar channels. Such entities and facilities can be associated with, for example, online auctions for reselling used electronic devices as well as for establishing market prices for such devices. The kiosk operator **2332** can be a central computer or system of computers for controlling all manner of operation of the network of kiosks **10, 1010**. Such operations can include, for example, remote monitoring and facilitating of kiosk maintenance (e.g., remote testing of kiosk functionality, downloading operational software and updates, etc.), servicing (e.g., periodic replenishing of cash and other consumables), performance, etc. In addition, the kiosk operator **2332** can further include one or more display screens operably connected to cameras located at each of the kiosks **10, 1010** (e.g., one or more of the cameras **60, 122** described above). This remote viewing capability enables operator personnel to verify user identification and/or make other visual observations in real-time during transactions.

[0109] The foregoing description of the electronic device recycling system **2300** illustrates but one possible network system suitable for implementing the various technologies described herein. Accordingly, those of ordinary skill in the art will appreciate that other systems consistent with the present technology can omit one or more of the facilities described in reference to FIG. **23**, or can include one or more additional facilities not described in detail in FIG. **23**.

[0110] The kiosks **10, 1010**, mobile devices **2330, 54**, and **1054**, server computers **2304**, user computers or devices **2318**, etc. can include one or more central processing units or other logic-processing circuitry, memory, input devices (e.g., keyboards and pointing devices), output devices (e.g., display devices and printers), and storage devices (e.g., magnetic, solid state, fixed and floppy disk drives, optical disk drives, etc.). Such computers can include other program modules such as an operating system, one or more application programs (e.g., word processing or spreadsheet applications), and the like. The computers can include wireless computers, such as mobile phones, personal digital assistants (PDAs), palm-top computers, tablet computers, notebook and laptop computers, desktop computers, e-readers, music players, GPS devices, wearable computers such as smartwatches and Google® Glass™, etc., that communicate with the Internet via a wireless link. The computers may be general-purpose devices that can be programmed to run various types of applications, or they may be single-purpose devices optimized or limited to a particular function or class of functions. Aspects of the invention may be practiced in a variety of other computing environments.

[0111] While the Internet is shown, a private network, such as an intranet can likewise be used herein. The network can have a client-server architecture, in which a computer is dedicated to serving other client computers, or it can have other architectures such as peer-to-peer, in which one or more computers serve simultaneously as servers and clients. A database or databases, coupled to the server computer(s), stores much of the web pages and content exchanged between the user computers. The server computer(s), including the database(s), can employ security measures to inhibit malicious attacks on the system, and to preserve integrity of the messages and data stored therein (e.g., firewall systems,

message encryption and/or authentication (e.g., using transport layer security (TLS) or secure sockets layer (SSL)), password protection schemes, encryption of stored data (e.g., using trusted computing hardware), and the like).

[0112] One skilled in the relevant art will appreciate that the concepts of the invention can be used in various environments other than location based or the Internet. In general, a display description can be in HTML, XML or WAP format, email format or any other format suitable for displaying information (including character/code-based formats, algorithm-based formats (e.g., vector generated), and bitmapped formats). Also, various communication channels, such as local area networks, wide area networks, or point-to-point dial-up connections, can be used instead of the Internet. The system can be conducted within a single computer environment, rather than a client/server environment. Also, the user computers can comprise any combination of hardware or software that interacts with the server computer, such as television-based systems and various other consumer products through which commercial or noncommercial transactions can be conducted. The various aspects of the invention described herein can be implemented in or for any e-mail environment.

[0113] Although not required, aspects of the invention are described in the general context of computer-executable instructions, such as routines executed by a data processing device, e.g., a server computer, wireless device or personal computer. Those skilled in the relevant art will appreciate that aspects of the invention can be practiced with other communications, data processing, or computer system configurations, including: Internet appliances, hand-held devices (including personal digital assistants (PDAs)), wearable computers, all manner of cellular or mobile phones (including Voice over IP (VoIP) phones), dumb terminals, media players, gaming devices, multi-processor systems, microprocessor-based or programmable consumer electronics, set-top boxes, network PCs, mini-computers, mainframe computers, and the like. Indeed, the terms “computer,” “server,” “host,” “host system,” and the like are generally used interchangeably herein, and refer to any of the above devices and systems, as well as any data processor.

[0114] Aspects of the inventions can be embodied in a special purpose computer or data processor that is specifically programmed, configured, or constructed to perform one or more of the computer-executable instructions described in detail herein. While aspects of the invention, such as certain functions, are described as being performed exclusively on a single device, the invention can also be practiced in distributed environments where functions or modules are shared among disparate processing devices, which are linked through a communications network, such as a Local Area Network (LAN), Wide Area Network (WAN), or the Internet. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

[0115] Those of ordinary skill in the art will appreciate that the routines and other functions and methods described herein can be implemented as an application specific integrated circuit (ASIC), by a digital signal processing (DSP) integrated circuit, through conventional programmed logic arrays and/or circuit elements. While many of the embodiments are shown and described as being implemented in hardware (e.g., one or more integrated circuits designed specifically for a task), such embodiments could equally be

implemented in software and be performed by one or more processors. Such software can be stored on any suitable computer-readable medium, such as microcode stored in a semiconductor chip, on a computer-readable disk, or downloaded from a server and stored locally at a client.

[0116] Aspects of the invention may be stored or distributed on tangible computer-readable media, including magnetically or optically readable computer discs, hard-wired or preprogrammed chips (e.g., EEPROM semiconductor chips), nanotechnology memory, biological memory, or other data storage media. Alternatively, computer implemented instructions, data structures, screen displays, and other data under aspects of the invention may be distributed over the Internet or over other networks (including wireless networks), on a propagated signal on a propagation medium (e.g., an electromagnetic wave(s), a sound wave, etc.) over a period of time, or they may be provided on any analog or digital network (packet switched, circuit switched, or other scheme). Although specific circuitry is described above, those of ordinary skill in the art will recognize that a microprocessor-based system could also be used where any logical decisions are configured in software.

[0117] References throughout the foregoing description to features, advantages, or similar language do not imply that all of the features and advantages that may be realized with the present technology should be or are in any single embodiment of the invention. Rather, language referring to the features and advantages is understood to mean that a specific feature, advantage, or characteristic described in connection with an embodiment is included in at least one embodiment of the present technology. Thus, discussion of the features and advantages, and similar language, throughout this specification may, but do not necessarily, refer to the same embodiment.

[0118] Furthermore, the described features, advantages, and characteristics of the present technology may be combined in any suitable manner in one or more embodiments. One skilled in the relevant art will recognize that the present technology can be practiced without one or more of the specific features or advantages of a particular embodiment. In other instances, additional features and advantages may be recognized in certain embodiments that may not be present in all embodiments of the present technology.

[0119] Any patents and applications and other references noted above, including any that may be listed in accompanying filing papers, are incorporated herein by reference in the entirety, except for any subject matter disclaimers or disavowals, and except to the extent that the incorporated material is inconsistent with the express disclosure herein, in which case the language in this disclosure controls. Aspects of the invention can be modified, if necessary, to employ the systems, functions, and concepts of the various references described above to provide yet further implementations of the invention.

[0120] Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Addition-

ally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, refer to this application as a whole and not to any particular portions of this application. Where the context permits, words in the above Detailed Description using the singular or plural number may also include the plural or singular number respectively. The word “or,” in reference to a list of two or more items, covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list.

[0121] While the above description describes various embodiments of the invention and the best mode contemplated, regardless how detailed the above text, the invention can be practiced in many ways. Details of the system may vary considerably in its specific implementation, while still being encompassed by the present disclosure. As noted above, particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the following claims should not be construed to limit the invention to the specific examples disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed examples, but also all equivalent ways of practicing or implementing the invention under the claims.

[0122] From the foregoing, it will be appreciated that specific embodiments of the invention have been described herein for purposes of illustration, but that various modifications may be made without deviating from the spirit and scope of the various embodiments of the invention. Further, while various advantages associated with certain embodiments of the invention have been described above in the context of those embodiments, other embodiments may also exhibit such advantages, and not all embodiments need necessarily exhibit such advantages to fall within the scope of the invention. Accordingly, the invention is not limited, except as by the appended claims.

[0123] Although certain aspects of the invention are presented below in certain claim forms, the applicant contemplates the various aspects of the invention in any number of claim forms. Accordingly, the applicant reserves the right to pursue additional claims after filing this application to pursue such additional claim forms, in either this application or in a continuing application.

We claim:

1. A consumer operated kiosk configured to evaluate an electronic device received from a user, the kiosk comprising:
 - a housing;
 - an inspection plate rotatable relative to the housing between a first position and a second position, wherein the inspection plate is configured to receive the electronic device when the inspection plate is in the first position;
 - a camera having a field of view including at least a portion of the inspection plate;
 - a wired and/or wireless connectivity device configured to connect to the electronic device; and
 - one or more processors operably connected to the wired and/or wireless connectivity device, the camera, and the inspection plate, wherein the one or more processors are configured to:

receive characteristic information about the electronic device via the wired and/or wireless connectivity device;

cause the inspection plate to rotate from the first position to the second position with the electronic device thereon;

receive one or more images of the electronic device via the camera when the inspection plate is in the second position; and

facilitate determination of an offer price for the electronic device based at least in part on the characteristic information and the one or more images.

2. The kiosk of claim 1 wherein the inspection plate is configured to rotate from the second position to a third position to move the electronic device from the inspection plate to a storage receptacle.

3. The kiosk of claim 1, further comprising one or more mirrors positioned proximate the inspection plate when the inspection plate is in the second position, the one or more mirrors configured to provide the camera with one or more reflected views of the electronic device positioned on the inspection plate.

4. The kiosk of claim 3 wherein the one or more mirrors are mounted to a mirror frame configured to rotate relative to the inspection plate.

5. The kiosk of claim 1 wherein the camera is a first camera, and wherein the kiosk further comprises a second camera having a field of view including at least a portion of the inspection plate.

6. The kiosk of claim 5, wherein the first camera is positioned above the inspection plate when the inspection plate is in the second position, and wherein the second camera is positioned below the inspection plate when the inspection plate is in the second position.

7. The kiosk of claim 1 wherein the wired and/or wireless connectivity device includes an electrical connector mounted to a rotatable hub.

8. The kiosk of claim 7 wherein the electrical connector is a first electrical connector, wherein the kiosk further comprises a second electrical connector spaced apart from the rotatable hub, wherein the second electrical connector is configured to translate between a retracted position and an extended position, and wherein the second electrical connector is configured to electrically connect to the electronic device when in the extended position.

9. The kiosk of claim 8, further comprising a third electrical connector spaced apart from the rotatable hub, wherein the second electrical connector is positioned to a first side of the rotatable hub, and the third electrical connector is positioned to a second side of the rotatable hub opposite the first side of the rotatable hub, wherein the third electrical connector is configured to translate between a retracted position and an extended position, and wherein the third electrical connector is configured to electrically connect to the electronic device when in the extended position.

10. The kiosk of claim 1, wherein the electronic device is a mobile phone.

11. The kiosk of claim 1, wherein the inspection plate is transparent.

12. A consumer operated kiosk for evaluating electronic devices, the kiosk comprising:

- a housing;
- an inspection plate rotatable relative to the housing between a first position and a second position, wherein the inspection plate is configured to receive an electronic device in the first position and support the electronic device in the first position and the second position; and
- a camera with a field of view of at least a portion of the inspection plate and configured to capture images of the electronic device when the inspection plate is in the second position.

13. The kiosk of claim 12 wherein at least a portion of an inner surface of the housing is gray and configured to absorb light emitted within the housing.

14. The kiosk of claim 12 wherein an inner surface of the housing includes a black band configured to reduce glare within the housing.

15. The kiosk of claim 12 wherein the one or more processors are configured to rotate the inspection plate from the second position to a third position if the user accepts an offer from the kiosk to purchase the electronic device, and wherein the second position is between the first position and the third position.

16. The kiosk of claim 15 wherein inspection plate is horizontal when the evaluation subassembly is in the second position.

17. The kiosk of claim 12, wherein the camera is mounted to an upper portion of the housing.

18. A method of evaluating an electronic device using a consumer operated kiosk, the method comprising:

- positioning an inspection plate of the kiosk in a first position;
- receiving the electronic device on the inspection plate in the first position;
- rotating the inspection plate away from a first position to a second position;
- visually evaluating the electronic device using a camera when the inspection plate is in the second position; and
- providing the user with an offer to purchase the electronic device, wherein the offer is based at least in part on the visual evaluation of the electronic device.

19. The method of claim 18, further comprising rotating the inspection plate away from the second position to a third position to deposit the electronic device in a storage receptacle in response to an acceptance of the offer by the user.

20. The method of claim 18, further comprising presenting the user with an electrical connector to be connected to the electronic device when the inspection plate is in the first position.

21. The method of claim 20, further comprising electrically evaluating the electronic device via the electrical connector.

22. The method of claim 21, further comprising automatically disconnecting the electrical connector from the electronic device after electrically evaluating the electronic device.

* * * * *