




(22) Date de dépôt/Filing Date: 2010/05/14 (41) Mise à la disp. pub./Open to Public Insp.: 2010/11/18 (45) Date de délivrance/Issue Date: 2018/05/22 (62) Demande originale/Original Application: 2 762 092 (30) Priorité/Priority: 2009/05/15 (US61/178,757)	(51) Cl.Int./Int.Cl. <i>H04W 24/00</i> (2009.01), <i>H04W 84/18</i> (2009.01) (72) Inventeurs/Inventors: CITRANO, JOSEPH, III, US; TOEPKE, TODD M., US; DEWEY, ALAN R., US; RUSSELL, ALDEN C., III, US; ROTVOLD, ERIC D., US (73) Propriétaire/Owner: FISHER-ROSEMOUNT SYSTEMS, INC., US (74) Agent: MARKS & CLERK
--	--

(54) Titre : DETECTION ET LOCALISATION AMELIOREES DE DISPOSITIFS SUR SITE SANS FIL
(54) Title: IMPROVED DETECTION AND LOCATION OF WIRELESS FIELD DEVICES



(57) **Abrégé/Abstract:**
A method (60) of evaluating a potential location (30) to add a wireless field device (32) to an existing network of a plurality of existing field devices (10) is provided. The method (60) includes placing (62) a handheld field maintenance tool (52) in the potential location (30) and causing the handheld field maintenance tool (52) to identify wireless field devices (10) within communicative range of the potential location (30). Information related to wireless communication at a potential location (30) is viewed. Methods (70, 250) are also provided for identifying a selected field device in a process installation using a handheld field maintenance tool (52).

ABSTRACT

A method (60) of evaluating a potential location (30) to add a wireless field device (32) to an existing network of a plurality of existing field devices (10) is provided. The method (60) includes placing (62) a handheld field maintenance tool (52) in the potential location (30) and causing the handheld field maintenance tool (52) to identify wireless field devices (10) within communicative range of the potential location (30). Information related to wireless communication at a potential location (30) is viewed. Methods (70, 250) are also provided for identifying a selected field device in a process installation using a handheld field maintenance tool (52).

IMPROVED DETECTION AND LOCATION OF WIRELESS FIELD DEVICES

This is a divisional application of Canadian Patent Application Serial No. 2,762,092 filed on May 14, 2010. It should be understood that the expression “the invention” and the like used herein may refer to subject matter claimed in either the parent or the divisional applications.

BACKGROUND

[0001] In industrial settings, control systems are used to monitor and control industrial and chemical processes, and the like. Typically, the process control system performs these functions using field devices distributed at key locations in the industrial process and coupled to the control circuitry in the control room by a process control loop. Field devices generally perform a function, such as sensing a parameter or operating upon the process, in a distributed control or process monitoring system.

[0002] Some field devices include a transducer. A transducer is understood to mean either a device that generates an output signal based on a physical input or that generates a physical output based on an input signal. Typically, a transducer transforms an input into an output having a different form. Types of transducers include various analytical equipment, pressure sensors, thermistors, thermocouples, strain gauges, flow transmitters, positioners, actuators, solenoids, indicator lights, and others.

[0003] Some process installations may involve highly volatile, or even explosive, environments. Accordingly, it is often beneficial, or even required, for field devices and the handheld field maintenance tools used with such field devices to comply with intrinsic safety requirements. These requirements help ensure that compliant electrical devices will not generate a source of ignition even under fault conditions. One example of Intrinsic Safety requirements is set forth in: APPROVAL STANDARD INTRINSICALLY SAFE APPARATUS AND ASSOCIATED APPARATUS FOR USE IN CLASS I, II and III, DIVISION NUMBER 1 HAZARDOUS (CLASSIFIED) LOCATIONS, CLASS NUMBER 3610, promulgated by Factory Mutual Research October, 1998. Examples of handheld field maintenance tools that comply with intrinsic

- 2 -

safety requirements include those sold under trade designations Model 375 Field Communicator and Model 475 Field Communicator, available from Emerson Process Management of Austin, Texas.

[0004] Typically, each field device also includes communication circuitry that is used for communicating with a process control room, or other circuitry, over a process control loop. Traditionally, analog field devices have been connected to the control room by two-wire process control current loops. In some installations, wireless technologies have begun to be used to communicate with field devices. Wireless operation simplifies field device wiring and set-up.

[0005] One wireless process communication technology standard is known as the WirelessHART standard. The WirelessHART standard was published by the HART Communication Foundation in September 2007. Relevant portions of the Wireless HART® Specification include: HCF_Spec 13, revision 7.0; HART Specification 65 - Wireless Physical Layer Specification; HART Specification 75 - TDMA Data Link Layer Specification (TDMA refers to Time Division Multiple Access); HART Specification 85 - Network Management Specification; HART Specification 155 - Wireless Command Specification; and HART Specification 290 - Wireless Devices Specification.

[0006] Another wireless network communication technology is set forth in ISA100.1 Ia. This technology proposes wireless communication at the 2.4 GHz frequency using radio circuitry in accordance with IEEE 802.15.4-2006. The ISA100.11 standard is maintained by the International Society of Automation (ISA).

[0007] While these wireless communication technologies provide important advantages to the art of process control and communication, traditional techniques for maintaining and configuring wireless field devices that employ such communication is sometimes rendered inefficient.

SUMMARY

[0008] A method of evaluating a potential location to add a wireless field device to an existing network of a plurality of existing wireless field devices is provided. The method includes placing a handheld field maintenance tool in the potential location and causing the handheld field maintenance tool to identify wireless field devices within communicative range of the potential location. Information related to wireless communication at the potential location is viewed. Methods are also provided for

identifying a selected field device in a process installation using a handheld field maintenance tool.

According to an aspect of the present invention there is provided a method of evaluating a potential location within a process environment for addition of a wireless field device to an existing network of a plurality of existing wireless field devices, the method comprising:

- placing a handheld field maintenance tool in the potential location;
- causing the handheld field maintenance tool to identify wireless field devices within communicative range of the potential location;
- viewing information, on a display of the handheld field maintenance tool, related to wireless communication at the potential location, wherein information related to wireless communication at the potential location comprises a device identifier and a signal strength for each identified wireless field device;
- providing a recommendation of which wireless sensor network the wireless field device should join; and
- wherein the handheld field maintenance tool is intrinsically safe.

According to another aspect of the present invention there is provided a method of studying a wireless sensor network including a plurality of wireless field devices, the method comprising:

- monitoring signal strength of each network field device over a selected duration;
- and
- providing the monitored signal strength correlated with physical position of each network field device.

Aspects of the present invention are provided by the following clauses:

Clauses

- I. A method of locating a selected field device in a process installation with a handheld field maintenance tool, the method comprising:
 - obtaining an indication of a physical location of the selected field device;
 - obtaining an indication of a current position of the handheld field maintenance tool; and
 - generating an indication to a user of the handheld field maintenance tool that

- 3a -

directs the user from the current position to the physical location of the selected field device.

2. The method of clause 1, wherein obtaining an indication of the physical location of the selected field device is obtained via a wireless communication module of the handheld field maintenance tool.

3. The method of clause 2, wherein the indication of the physical location of the selected field device is provided by the selected field device.

4. The method of clause 1, wherein generating an indication to the user includes presenting the user with a map indicating the current position and the physical location of the selected field device.

5. The method of clause 1, and further comprising automatically generating a local annunciation at the selected field device.

6. The method of clause 5, wherein the local annunciation is automatically generated when the current position is within a threshold proximity of the physical location of the selected field device.

7. The method of clause 1, wherein the handheld field maintenance tool complies with at least one intrinsic safety specification.

8. The method of clause 1, wherein the indication includes a heading.

9. The method of clause 1, wherein the indication includes an elevation angle.

10. A method of locating a selected field device in a process installation with a handheld field maintenance tool, the method comprising:

communicating with the selected field device using a handheld field maintenance tool to cause the wireless field device to generate a local annunciation.

- 3b -

11. The method of clause 10, wherein wireless communication between the handheld field maintenance tool and the selected field device is in accordance with a process industry standard communication protocol.
12. The method of clause 10, wherein the annunciation is an audible annunciation.
13. The method of clause 10, wherein the annunciation is a visual annunciation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Fig. 1 is a diagrammatic view of a wireless process control environment in which embodiments of the present invention are particularly useful.

[0010] Fig. 2 is a diagrammatic view of a wireless process control environment in which a new wireless field device is being added.

[0011] Fig. 3 is a diagrammatic view of a wireless process control environment in which a new wireless field device is being added in accordance with an embodiment of the present invention.

[0012] Fig. 4 is a flow diagram of a method of evaluating a potential location for a new wireless field device in accordance with an embodiment of the present invention.

[0013] Fig. 5 is a diagrammatic system block diagram of a handheld field maintenance tool in accordance with the embodiment of the present invention.

[0014] Fig. 6 is a diagrammatic view of a method of locating a selected field device using a handheld field maintenance tool in accordance with an embodiment of the present invention.

[0015] Fig. 7 is a flow diagram of a method of locating a selected field device using a handheld field maintenance tool in accordance with an embodiment of the present invention.

[0016] Fig. 8 is a diagrammatic view of a method of locating a selected field device in accordance with another embodiment of the present invention.

[0017] Fig. 9 is a flow diagram of a method of locating a selected field device in accordance with another embodiment of the present invention.

DETAILED DESCRIPTION

[0018] Fig. 1 is a diagrammatic view of a wireless process control environment in which embodiments of the present invention are particularly useful. As illustrated in Fig. 1, a plurality of wireless field devices 10 are communicatively coupled either directly or indirectly via wireless communication to wireless gateway 20. Wireless field devices 10 are generally illustrated as wireless process variable transmitters, such as those sold under the trade designation Model 3051S wireless pressure transmitter, from Emerson Process Management, of Chanhassen, Minnesota. However, those skilled in the art will recognize that wireless field devices 10 can include other types of wireless process variable transmitters, as well as wireless actuators, valve positioners, et cetera. Wireless gateway 20 is configured to communicate with wireless field devices 10 using known wireless process communication protocols, such as the WirelessHART protocol described above. One example of a wireless gateway is sold under the trade designation Model 1420 by Emerson Process Management, of Chanhassen, Minnesota. Wireless gateway 20 includes one or more wired ports that are configured to couple to a local area network, such as an Ethernet local area network as illustrated at reference numeral 22. By virtue of its wired connection, wireless gateway 20 can provide information to and receive information from any device coupled to local network 22 such as workstations 24 and 26.

[0019] The wireless field device network illustrated in Fig. 1 can be considered a mesh network in that some of the field devices communicate with other field devices to pass their communication ultimately on to wireless gateway 20. Thus, a field device that is located too far away from wireless gateway 20 to otherwise communicate directly, can still provide wireless process communication by virtue of communication through one or more other wireless field devices.

[0020] Fig. 2 is a diagrammatic view of a wireless process control environment in which a new wireless field device is being added. When installation of a new wireless field device is required, the process is currently quite cumbersome. For wireless field devices, the physical position of the field device is often very important. This is because the physical position of the device will affect its proximity to other devices in the mesh network as well as proximity to a gateway. Further, sources of electromagnetic interference or physical obstructions may affect a field device more significantly at one position versus another. Thus, when a user is planning to install a new wireless field device into an existing network of wireless field devices, the user will generally perform a number of tasks and evaluations relative to the physical location of the new device.

[0021] The user will typically evaluate physical distances between the proposed installation location illustrated at reference numeral 30 in Fig. 2 and other connections points 10 (which in a self-organizing network could be any member of the network) and decide if the distances are within the expected effective communication range of the new wireless field device.

[0022] In order to study location 30 in detail, the user will often walk into the field to location 30 and place a wireless test device at location 30. Then, the user will return to one of workstations 24, 26 and access wireless gateway 20 and wait for the wireless test device to join the wireless network. The wireless test device can require up to 10 minutes to join the network. Once the test device does join the network, the user views communication characteristic information relative to the test device through a user interface provided by the wireless gateway. If proposed location 30 is satisfactory, the user then returns to location 30 and replaces the test device with the new wireless field device. However, if position 30 is not satisfactory, the entire process is repeated for an alternate location. If the user is exploring even a few potential locations, the process can quickly consume significant time.

[0023] Fig. 3 is a diagrammatic view of a wireless process control environment in which a new wireless field device is being added in accordance with an embodiment of the present invention. The embodiment illustrated with respect to Fig. 3 leverages a new ability of a handheld field maintenance tool to improve the process of adding new wireless field devices to existing wireless networks. Instead of deploying a test field device to proposed location 30, handheld field maintenance tool 52 is used. Tool 52 has a wireless process communication module (Shown in Fig. 5) that allows tool 52 to listen to and communicate directly with field devices 10. Accordingly, when tool 52 is located at position 30, a user can select a function supplied by tool 52 to cause tool 52 to identify all wireless field devices 10 within communication range of position 30. Tool 52 then displays the wireless field devices 10 within range of position 30. This display may simply include the number of field devices with which tool 52 can communicate at position 30. However, the display can be more sophisticated including a listing of device tags or MAC addresses, and the signal strength at position 30. Additionally, tool 52 can also measure and report other connectivity issues, such as the presence of electromagnetic interference, other process communication networks, communication errors, or any other suitable parameter of interest to a technician deploying a new wireless field device. The embodiment described with respect to Fig. 3 is believed to be particularly applicable to WirelessHART, but any other suitable wireless process communication protocol can be used. Moreover, while the embodiment described with respect to Fig. 3, is illustrated relative to handheld field maintenance tool 52, any device that can communicate on the wireless sensor network and provide useful information to a technician or user may be employed. Thus, tool 52 could simply be a module or device that plugs into a laptop computer or other suitable mobile device. However, since the device is located, at least some of the time, in the field, it is preferred that tool 52 comply with at least one intrinsic safety specification, such as that listed above.

-7-

[0024] Additionally, or alternatively, the signal quality at position 30 can be evaluated over time. Thus, if position 30 is susceptible to periodic electromagnetic interference, such a study would detect such interference thereby addressing a potentially intermittent communication difficulty. The study of position 30 can be done using a software application resident in one or more field devices 10, gateway 20, or preferably tool 52 to continually or periodically monitor signal strength of each network member over time. Preferably, the monitored signal strength information is stored and combined with geographic information (such as a map of the network) to provide a user with a graphical, intuitive depiction of signal quality as a function of position in the wireless process network. This map is termed a network heat map and can be used to graphically depict past history of signal strength to 1, 2, 3, 4 ... et cetera devices in the area of position 30. Further, the application, in some embodiments, illustrates the lowest signal strength to 1, 2, 3 ... et cetera wireless field devices. Further still, in some embodiments, the software application can recommend which wireless sensor network the new field device should join as well as provides an indication of anticipated communication reliability for the new wireless field device.

[0025] Fig. 4 is a flow diagram of a method of evaluating a potential location for a new wireless field device in accordance with an embodiment of the present invention. Method 60 begins at block 62 where a handheld field maintenance tool is placed at a proposed location of a new wireless field device. Next, at block 64, the handheld field maintenance tool identifies at least some wireless field devices within range of the handheld field maintenance tool. Preferably, the handheld field maintenance tool identifies all wireless field devices within range during block 64. At block 66, the handheld field maintenance tool provides information related to the wireless communication to a user via a display of the handheld field maintenance tool. This information may be the number of field devices found; the device tags of the field devices; the signal strength relative to each field device, et cetera.

[0026] Fig. 5 is a diagrammatic system block diagram of a handheld field maintenance tool in accordance with the embodiment of the present invention. It is preferred that tool 52 comply with at least one intrinsic safety specification, such as that listed above, in order to help ensure safety in potentially explosive environments.

[0027] Handheld field maintenance tool 52 includes at least one wireless process communication module 120. Suitable examples for wireless process communication module 120 include a module that generates and/or receives proper signals in accordance with a known wireless communication protocol, such as the WirelessHART protocol described above. Another suitable wireless process communication protocol is that set forth in ISA100.11a described above. While Fig. 5 shows a single wireless process communication module 120, it is expressly contemplated that any suitable number of wireless process communication modules can be used to communicate in accordance with various wireless process communication protocols now in existence or later developed.

[0028] Handheld field maintenance tool 52 also includes at least one secondary wireless communication protocol module 122. Wireless communication protocol module 122 can communicate in accordance with one or more of the options shown in phantom in Fig. 5. Specifically, wireless communication protocol module 122 may communicate in accordance with a Bluetooth specification 124; a Wi-Fi specification 126; a known RFID specification 128; cellular communication techniques 130; and/or satellite communication 132. These communication techniques and methodologies allow handheld field maintenance tool 52 to communicate directly with wireless gateway 20 either via direct wireless communication, or using the Internet to which a wireless gateway is generally coupled. While one wireless communication protocol module 122 is shown in Fig. 5, any suitable number may be used. Each of the wireless process communication protocol module 120 and wireless communication protocol module 122 is coupled to controller 130.

which is also coupled to the wired process communication module 138. Controller 130 is preferably a microprocessor that executes a sequence of instructions to perform handheld field maintenance tasks. Wired process communication module 138 allows the handheld field maintenance tool to be physically coupled via a wired connection at terminals 142, 144 to a field device. Examples of suitable wired process communication include the highway addressable remote transducer (HART®) protocol, the FOUNDATION™ Fieldbus protocol, and others.

[0029] Handheld field maintenance tool 52 can include a number of optional items that facilitate additional embodiments of the present invention. Specifically, tool 52 can include a position detection module, such as GPS module 150. GPS module 150 can be configured to additionally use the Wide Area Augmentation System (WAAS) for improved accuracy and/or can be configured to operate using differential GPS techniques as appropriate. Module 150 is coupled to controller 130 to provide controller 130 with an indication of the geographic position of tool 52. Additionally, tool 52 also preferably comprises compass module 152 coupled to controller 130 such that tool 52 can indicate the direction in which it is pointing. Finally, tool 52 can also include tilt module 154 coupled to controller 130 to provide an indication to controller 130 relative to an angle of inclination of tool 52 relative to gravity. However, additional axes of sensing are also contemplated.

[0030] The optional components of tool 52 are particularly useful in embodiments of the present invention where a handheld field maintenance tool helps a technician or engineer find the physical location of a wireless field device in the field. An oil refinery is often a very large process installation with many field devices positioned at various locations, some of which may not be readily visible. When a technician or engineer needs to physically locate a field device to perform engineering, setup and maintenance tasks, the technician or engineer would previously need to perform one of the following tasks. The technician or engineer would be forced to search for the field device based on

memory or word-of-mouth directions. Alternatively, the technician or engineer would look up the field device in engineering drawings, which often do not contain detailed information about the physical location of the device. Then, based on that often limited information, the technician or engineer would attempt to physically find the device in the plant or process installation.

[0031] Fig. 6 is a diagrammatic view of a process of finding a wireless field device using a handheld field maintenance tool to locate a selected field device in accordance with an embodiment of the present invention. Handheld field maintenance tool 100 can be identical to tool 52 described above with respect to Fig. 5. However, a different reference numeral is used because it need not be the same. Tool 100 includes a user interface (in the form of a keypad, navigation buttons, and a display) that allows a technician or engineer to select a specific field device to locate. Such selection will generally be in the form of selecting a device tag or identifier, but may take any suitable form. In the example shown in Fig. 6, the technician has selected wireless field device 206 among devices 200, 202, 204, and 206. While four field devices are illustrated, in reality, the field devices could number in the hundreds with field devices dispersed throughout the factory or process installation. Preferably, handheld field maintenance tool 100 contains a map of the process installation that is either pre-loaded into the handheld field maintenance tool, or communicated wirelessly to tool 100 through any suitable means. Additionally, in the event that handheld field maintenance tool 100 has previously interacted with the selected field device (such as during installation of the field device) handheld field maintenance tool 100 may have acquired information that relates the position (as indicated by the GPS module at the time of the previous interaction) to the device. This position information can be written to the field device, stored in handheld field maintenance tool 100 or both. It is also contemplated that handheld field maintenance tool 100 or a different handheld field maintenance tool can access the wireless field device using any suitable wireless communication and receive from the wireless field device location information indicative of a position of the

wireless field device. Once the device tag is identified, the handheld field maintenance tool obtains position information, preferably from GPS module 150 relative to the position of tool 100. Once tool 100 knows its own position, it generates an indication, vector, route, or other suitable directions to help the technician or engineer travel to the physical location of field device 206. Preferably, the map includes an indication of tool 100 on the map so the user can gauge progress to the destination (field device 206). Additionally, since the technician is usually walking, and GPS heading information is based on movement, tool 100 may use its optional compass to provide the user with a directional indication 208 that points or leads the technician or engineer to the selected field device 206 even when the technician or engineer is standing still. Finally, since at least some process installations such as refineries may have field devices positioned tens or hundreds of feet above the ground, tool 100 can use tilt module 154 to cause the technician or engineer to incline tool 100 at an angle that causes the tool to be essentially aimed at field device 206. Thus, if a user reaches a position where field device 206 is supposed to be, but field device 206 is actually located far overhead, tool 100 would indicate an angle of incline that would direct the user's attention to the proper elevation to locate the field device.

[0032] Fig. 7 is a flow diagram of a method of locating a selected field device using a handheld field maintenance tool in accordance with an embodiment of the present invention. Method 70 begins at block 72 where an indication of a physical location of a selected field device is obtained by a handheld field maintenance tool. This may be done by accessing an internal pre-loaded database within the handheld field maintenance tool that correlates all device tags in the process installation to physical positions. Alternatively, the handheld field maintenance tool can generate a query based on the selected device identification to a suitable server or computing device in an asset management system to receive position information relative to the selected device. As set forth above, since the handheld field maintenance tool has ample

wireless communication abilities, this query may be submitted while the user is in the field. Next, at block 74, the handheld field maintenance tool determines its current position. This can be done in any suitable manner, but preferably includes accessing an internal GPS module, such as module 150. Then, the controller of the handheld field maintenance tool processes the physical location of the selected field device and the current position of the handheld field maintenance tool to provide an indication to the user to direct the user toward the physical location of the selected wireless field device.

[0033] Another aid for the technician or engineer's search for the wireless field device is illustrated with respect to Fig. 8. Specifically, once the user has selected a field device to locate, the handheld field maintenance tool 100 can communicate on the wireless sensor network in which the field device is located to cause the field device to generate a local annunciation to help capture the user's attention. This local annunciation 210 can be in the form of an audible alert or siren, a flashing light or indicator, or both. Thus, as the technician or engineer is walking near the field device, the field device's sounds and lights will help the technician or engineer focus on the desired field device.

[0034] Fig. 9 is a flow diagram of a method of locating a selected field device in accordance with another embodiment of the present invention. Method 250 begins at block 252 where a user selects a wireless field device with a handheld field maintenance tool. Next, at block 254, the handheld field maintenance tool generates suitable wireless communication, preferably wireless process communication, to cause the selected field device to generate a local annunciation.

[0035] While each of the embodiments described with respect to Figs. 6 and 8 can be practiced separately, combinations of the embodiments are also useful. For example, the user can obtain and follow a map to arrive in the general area of the selected field device. Then, once handheld field maintenance tool senses proximity above a certain threshold to the field device, the handheld field maintenance tool can automatically interact with the field device through the

-13-

wireless sensor network to cause the field device to generate the local annunciation and confirm the location of the field device. Further still, if the user reaches the location of the selected field device and cannot find it, the user may also obtain additional location assistance information using the handheld field maintenance tool. For example, the user may download an image of the field device located in its position. The user can then view the image and compare it to the user's physical reality to find the field device.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A method of evaluating a potential location within a process environment for addition of a wireless field device to an existing network of a plurality of existing wireless field devices, the method comprising:
 - placing a handheld field maintenance tool in the potential location;
 - causing the handheld field maintenance tool to identify wireless field devices within communicative range of the potential location;
 - viewing information, on a display of the handheld field maintenance tool, related to wireless communication at the potential location, wherein information related to wireless communication at the potential location comprises a device identifier and a signal strength for each identified wireless field device;
 - providing a recommendation of which wireless sensor network the wireless field device should join; and
 - wherein the handheld field maintenance tool is intrinsically safe.
2. The method of claim 1, wherein the handheld field maintenance tool communicates with each wireless field device in accordance with a process industry standard protocol.
3. The method of claim 2, wherein the process industry standard protocol is a WirelessHART protocol.
4. The method of any one of claims 1 to 3, wherein the information related to wireless communication at the potential location includes an indication of electromagnetic interference.
5. The method of any one of claims 1 to 4, and further comprising:
 - providing an indication of anticipated communication reliability for the wireless field device at the potential location.

6. The method of any one of claims 1 to 5, and further comprising:
providing a graphic representation of detected signal strength as a function of a
detected position of each identified wireless field device.

1/9




FIG. 1

2/9




FIG. 2

3/9




Fig. 3

4/9




FIG. 4

5/9




FIG. 5

6/9




FIG. 6

7/9




FIG. 7

8/9




FIG. 8

9/9




FIG. 9

