



US010613499B2

(12) **United States Patent**  
**Zimmerman et al.**

(10) **Patent No.:** **US 10,613,499 B2**

(45) **Date of Patent:** **Apr. 7, 2020**

(54) **SYSTEM AND METHOD FOR VIRTUAL INTERNET OF THINGS (IOT) DEVICES AND HUBS**

(71) Applicant: **Afero, Inc.**, Los Altos, CA (US)

(72) Inventors: **Scott Zimmerman**, Mountain View, CA (US); **Joe Britt**, Los Altos, CA (US)

(73) Assignee: **Afero, Inc.**, Los Altos, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 43 days.

(21) Appl. No.: **15/960,358**

(22) Filed: **Apr. 23, 2018**

(65) **Prior Publication Data**

US 2018/0246484 A1 Aug. 30, 2018

**Related U.S. Application Data**

(63) Continuation of application No. 14/791,361, filed on Jul. 3, 2015, now Pat. No. 9,977,415.

(51) **Int. Cl.**

**G05B 19/042** (2006.01)  
**H04L 29/08** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **G05B 19/042** (2013.01); **G05B 15/02** (2013.01); **H04L 12/2807** (2013.01);  
(Continued)

(58) **Field of Classification Search**

CPC ..... **G05B 19/042**; **H04L 67/12**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2013/0173621 A1 7/2013 Kapoor et al.  
2014/0241354 A1 8/2014 Shuman et al.  
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/US2016/040808 dated Nov. 21, 2016, 15 pages.

(Continued)


*Primary Examiner* — Mark A Connolly

(74) *Attorney, Agent, or Firm* — Nicholson De Vos Webster & Elliott LLP

(57) **ABSTRACT**

A system and method are described for virtualizing Internet of Things (IoT) devices and hubs. For example, one embodiment of a system comprises: a primary Internet of Things (IoT) cloud service to register IoT devices owned by users who have subscribed with the primary IoT cloud service; IoT device management logic on the primary IoT cloud service to provide access to data generated by the primary IoT devices and to control the IoT devices responsive to user input; the IoT device management logic to establish a communication channel with an external IoT cloud service providing to a user registering one or more external IoT devices controlled by the external IoT cloud service; and wherein upon the external IoT cloud service providing the IoT device management logic with access to the one or more external IoT devices, the IoT device management logic to generate virtual representations of the one or more external IoT devices to allow user access to information generated by the external IoT devices and to allow the user to control the external IoT devices through the virtual representations.

**17 Claims, 35 Drawing Sheets**



- (51) **Int. Cl.**  
*H04L 12/28* (2006.01)  
*G05B 15/02* (2006.01)

- (52) **U.S. Cl.**  
CPC ..... *H04L 67/10* (2013.01); *H04L 67/12*  
(2013.01); *G05B 2219/2642* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2014/0330959	A1	11/2014	Zhang	
2015/0019553	A1	1/2015	Shaashua et al.	
2015/0134761	A1	5/2015	Sharma et al.	
2016/0274611	A1*	9/2016	Amer	G05F 1/66
2017/0257129	A1*	9/2017	Egner	H04B 1/385
2018/0152894	A1*	5/2018	Lin	H04L 29/08

OTHER PUBLICATIONS

International Preliminary Report on Patentability for Application No. PCT/US2016/040808 dated Jan. 18, 2018, 11 pages.  
Requirement for Restriction/Election for U.S. Appl. No. 14/791,361 dated Aug. 11, 2017, 6 pages.  
Notice of Allowance for U.S. Appl. No. 14/791,361 dated Jan. 26, 2018, 11 pages.

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9A



**FIG. 9B**





FIG. 10



**FIG. 11**




FIG. 12A







FIG. 12B



**Fig. 13**



**Fig. 14**



**Fig. 15**




Fig. 16A




Fig. 16B




Fig. 17

4 bytes	N bytes	6 bytes
Counter 1800	Encrypted Data 1801	Tag 1802

**Fig. 18**




Fig. 19




Fig. 20





Fig. 21



**Fig. 22**




Fig. 23A





Fig. 23B



**Fig. 23C**





FIG. 24



**FIG. 25**






FIG. 26



**Fig. 27**



**Fig. 28**

1

## SYSTEM AND METHOD FOR VIRTUAL INTERNET OF THINGS (IOT) DEVICES AND HUBS

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of co-pending U.S. patent application Ser. No. 14/791,361, filed Jul. 3, 2015, all of which is hereby incorporated by reference.

### BACKGROUND

#### Field of the Invention

This invention relates generally to the field of computer systems. More particularly, the invention relates to a system and method for virtual IoT devices and hubs.

#### Description of the Related Art

The "Internet of Things" refers to the interconnection of uniquely-identifiable embedded devices within the Internet infrastructure. Ultimately, IoT is expected to result in new, wide-ranging types of applications in which virtually any type of physical thing may provide information about itself or its surroundings and/or may be controlled remotely via client devices over the Internet.

IoT development and adoption has been slow due to issues related to connectivity, power, and a lack of standardization. For example, one obstacle to IoT development and adoption is that no standard platform exists to allow developers to design and offer new IoT devices and services. In order enter into the IoT market, a developer must design the entire IoT platform from the ground up, including the network protocols and infrastructure, hardware, software and services required to support the desired IoT implementation. As a result, each provider of IoT devices uses proprietary techniques for designing and connecting the IoT devices, making the adoption of multiple types of IoT devices burdensome for end users. Another obstacle to IoT adoption is the difficulty associated with connecting and powering IoT devices. Connecting appliances such as refrigerators, garage door openers, environmental sensors, home security sensors/controllers, etc, for example, requires an electrical source to power each connected IoT device, and such an electrical source is often not conveniently located (e.g., an AC outlet is generally not found within a refrigerator).

### BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the present invention can be obtained from the following detailed description in conjunction with the following drawings, in which:

FIGS. 1A-B illustrates different embodiments of an IoT system architecture;

FIG. 2 illustrates an IoT device in accordance with one embodiment of the invention;

FIG. 3 illustrates an IoT hub in accordance with one embodiment of the invention;

FIG. 4A-B illustrate embodiments of the invention for controlling and collecting data from IoT devices, and generating notifications;

FIG. 5 illustrates embodiments of the invention for collecting data from IoT devices and generating notifications from an IoT hub and/or IoT service;

2

FIG. 6 illustrates one embodiment of a system in which an intermediary mobile device collects data from a stationary IoT device and provides the data to an IoT hub;

FIG. 7 illustrates intermediary connection logic implemented in one embodiment of the invention;

FIG. 8 illustrates a method in accordance with one embodiment of the invention;

FIG. 9A illustrates an embodiment in which program code and data updates are provided to the IoT device;

FIG. 9B illustrates an embodiment of a method in which program code and data updates are provided to the IoT device;

FIG. 10 illustrates a high level view of one embodiment of a security architecture;

FIG. 11 illustrates one embodiment of an architecture in which a subscriber identity module (SIM) is used to store keys on IoT devices;

FIG. 12A illustrates one embodiment in which IoT devices are registered using barcodes or QR codes;

FIG. 12B illustrates one embodiment in which pairing is performed using barcodes or QR codes;

FIG. 13 illustrates one embodiment of a method for programming a SIM using an IoT hub;

FIG. 14 illustrates one embodiment of a method for registering an IoT device with an IoT hub and IoT service; and

FIG. 15 illustrates one embodiment of a method for encrypting data to be transmitted to an IoT device;

FIGS. 16A-B illustrate different embodiments of the invention for encrypting data between an IoT service and an IoT device;

FIG. 17 illustrates embodiments of the invention for performing a secure key exchange, generating a common secret, and using the secret to generate a key stream;

FIG. 18 illustrates a packet structure in accordance with one embodiment of the invention;

FIG. 19 illustrates techniques employed in one embodiment for writing and reading data to/from an IoT device without formally pairing with the IoT device;

FIG. 20 illustrates an exemplary set of command packets employed in one embodiment of the invention;

FIG. 21 illustrates an exemplary sequence of transactions using command packets;

FIG. 22 illustrates a method in accordance with one embodiment of the invention; and

FIGS. 23A-C illustrates a method for secure pairing in accordance with one embodiment of the invention;

FIG. 24 illustrates one embodiment of an architecture for virtual IoT devices;

FIG. 25 illustrates an exemplary graphical user interface displayed on a user device containing graphical representations of real and virtual IoT devices;

FIG. 26 illustrates one embodiment of an architecture for implementing a virtual IoT hub;

FIG. 27 illustrates a method in accordance with one embodiment of the invention;

FIG. 28 illustrates a method for virtual device pairing in accordance with one embodiment of the invention.

### DETAILED DESCRIPTION

In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the embodiments of the invention described below. It will be apparent, however, to one skilled in the art that the embodiments of the invention may be practiced without some of these specific details. In

other instances, well-known structures and devices are shown in block diagram form to avoid obscuring the underlying principles of the embodiments of the invention.

One embodiment of the invention comprises an Internet of Things (IoT) platform which may be utilized by developers to design and build new IoT devices and applications. In particular, one embodiment includes a base hardware/software platform for IoT devices including a predefined networking protocol stack and an IoT hub through which the IoT devices are coupled to the Internet. In addition, one embodiment includes an IoT service through which the IoT hubs and connected IoT devices may be accessed and managed as described below. In addition, one embodiment of the IoT platform includes an IoT app or Web application (e.g., executed on a client device) to access and configured the IoT service, hub and connected devices. Existing online retailers and other Website operators may leverage the IoT platform described herein to readily provide unique IoT functionality to existing user bases.

FIG. 1A illustrates an overview of an architectural platform on which embodiments of the invention may be implemented. In particular, the illustrated embodiment includes a plurality of IoT devices **101-105** communicatively coupled over local communication channels **130** to a central IoT hub **110** which is itself communicatively coupled to an IoT service **120** over the Internet **220**. Each of the IoT devices **101-105** may initially be paired to the IoT hub **110** (e.g., using the pairing techniques described below) in order to enable each of the local communication channels **130**. In one embodiment, the IoT service **120** includes an end user database **122** for maintaining user account information and data collected from each user's IoT devices. For example, if the IoT devices include sensors (e.g., temperature sensors, accelerometers, heat sensors, motion detectors, etc), the database **122** may be continually updated to store the data collected by the IoT devices **101-105**. The data stored in the database **122** may then be made accessible to the end user via the IoT app or browser installed on the user's device **135** (or via a desktop or other client computer system) and to web clients (e.g., such as websites **130** subscribing to the IoT service **120**).

The IoT devices **101-105** may be equipped with various types of sensors to collect information about themselves and their surroundings and provide the collected information to the IoT service **120**, user devices **135** and/or external Websites **130** via the IoT hub **110**. Some of the IoT devices **101-105** may perform a specified function in response to control commands sent through the IoT hub **110**. Various specific examples of information collected by the IoT devices **101-105** and control commands are provided below. In one embodiment described below, the IoT device **101** is a user input device designed to record user selections and send the user selections to the IoT service **120** and/or Website.

In one embodiment, the IoT hub **110** includes a cellular radio to establish a connection to the Internet **220** via a cellular service **115** such as a 4G (e.g., Mobile WiMAX, LTE) or 5G cellular data service. Alternatively, or in addition, the IoT hub **110** may include a WiFi radio to establish a WiFi connection through a WiFi access point or router **116** which couples the IoT hub **110** to the Internet (e.g., via an Internet Service Provider providing Internet service to the end user). Of course, it should be noted that the underlying principles of the invention are not limited to any particular type of communication channel or protocol.

In one embodiment, the IoT devices **101-105** are ultra low-power devices capable of operating for extended peri-

ods of time on battery power (e.g., years). To conserve power, the local communication channels **130** may be implemented using a low-power wireless communication technology such as Bluetooth Low Energy (LE). In this embodiment, each of the IoT devices **101-105** and the IoT hub **110** are equipped with Bluetooth LE radios and protocol stacks.

As mentioned, in one embodiment, the IoT platform includes an IoT app or Web application executed on user devices **135** to allow users to access and configure the connected IoT devices **101-105**, IoT hub **110**, and/or IoT service **120**. In one embodiment, the app or web application may be designed by the operator of a Website **130** to provide IoT functionality to its user base. As illustrated, the Website may maintain a user database **131** containing account records related to each user.

FIG. 1B illustrates additional connection options for a plurality of IoT hubs **110-111**, **190**. In this embodiment a single user may have multiple hubs **110-111** installed onsite at a single user premises **180** (e.g., the user's home or business). This may be done, for example, to extend the wireless range needed to connect all of the IoT devices **101-105**. As indicated, if a user has multiple hubs **110**, **111** they may be connected via a local communication channel (e.g., Wifi, Ethernet, Power Line Networking, etc). In one embodiment, each of the hubs **110-111** may establish a direct connection to the IoT service **120** through a cellular **115** or WiFi **116** connection (not explicitly shown in FIG. 1B). Alternatively, or in addition, one of the IoT hubs such as IoT hub **110** may act as a "master" hub which provides connectivity and/or local services to all of the other IoT hubs on the user premises **180**, such as IoT hub **111** (as indicated by the dotted line connecting IoT hub **110** and IoT hub **111**). For example, the master IoT hub **110** may be the only IoT hub to establish a direct connection to the IoT service **120**. In one embodiment, only the "master" IoT hub **110** is equipped with a cellular communication interface to establish the connection to the IoT service **120**. As such, all communication between the IoT service **120** and the other IoT hubs **111** will flow through the master IoT hub **110**. In this role, the master IoT hub **110** may be provided with additional program code to perform filtering operations on the data exchanged between the other IoT hubs **111** and IoT service **120** (e.g., servicing some data requests locally when possible).

Regardless of how the IoT hubs **110-111** are connected, in one embodiment, the IoT service **120** will logically associate the hubs with the user and combine all of the attached IoT devices **101-105** under a single comprehensive user interface, accessible via a user device with the installed app **135** (and/or a browser-based interface).

In this embodiment, the master IoT hub **110** and one or more slave IoT hubs **111** may connect over a local network which may be a WiFi network **116**, an Ethernet network, and/or a using power-line communications (PLC) networking (e.g., where all or portions of the network are run through the user's power lines). In addition, to the IoT hubs **110-111**, each of the IoT devices **101-105** may be interconnected with the IoT hubs **110-111** using any type of local network channel such as WiFi, Ethernet, PLC, or Bluetooth LE, to name a few.

FIG. 1B also shows an IoT hub **190** installed at a second user premises **181**. A virtually unlimited number of such IoT hubs **190** may be installed and configured to collect data from IoT devices **191-192** at user premises around the world. In one embodiment, the two user premises **180-181** may be configured for the same user. For example, one user premises **180** may be the user's primary home and the other

user premises **181** may be the user's vacation home. In such a case, the IoT service **120** will logically associate the IoT hubs **110-111**, **190** with the user and combine all of the attached IoT devices **101-105**, **191-192** under a single comprehensive user interface, accessible via a user device with the installed app **135** (and/or a browser-based interface).

As illustrated in FIG. 2, an exemplary embodiment of an IoT device **101** includes a memory **210** for storing program code and data **201-203** and a low power microcontroller **200** for executing the program code and processing the data. The memory **210** may be a volatile memory such as dynamic random access memory (DRAM) or may be a non-volatile memory such as Flash memory. In one embodiment, a non-volatile memory may be used for persistent storage and a volatile memory may be used for execution of the program code and data at runtime. Moreover, the memory **210** may be integrated within the low power microcontroller **200** or may be coupled to the low power microcontroller **200** via a bus or communication fabric. The underlying principles of the invention are not limited to any particular implementation of the memory **210**.

As illustrated, the program code may include application program code **203** defining an application-specific set of functions to be performed by the IoT device **201** and library code **202** comprising a set of predefined building blocks which may be utilized by the application developer of the IoT device **101**. In one embodiment, the library code **202** comprises a set of basic functions required to implement an IoT device such as a communication protocol stack **201** for enabling communication between each IoT device **101** and the IoT hub **110**. As mentioned, in one embodiment, the communication protocol stack **201** comprises a Bluetooth LE protocol stack. In this embodiment, Bluetooth LE radio and antenna **207** may be integrated within the low power microcontroller **200**. However, the underlying principles of the invention are not limited to any particular communication protocol.

The particular embodiment shown in FIG. 2 also includes a plurality of input devices or sensors **210** to receive user input and provide the user input to the low power microcontroller, which processes the user input in accordance with the application code **203** and library code **202**. In one embodiment, each of the input devices include an LED **209** to provide feedback to the end user.

In addition, the illustrated embodiment includes a battery **208** for supplying power to the low power microcontroller. In one embodiment, a non-chargeable coin cell battery is used. However, in an alternate embodiment, an integrated rechargeable battery may be used (e.g., rechargeable by connecting the IoT device to an AC power supply (not shown)).

A speaker **205** is also provided for generating audio. In one embodiment, the low power microcontroller **299** includes audio decoding logic for decoding a compressed audio stream (e.g., such as an MPEG-4/Advanced Audio Coding (AAC) stream) to generate audio on the speaker **205**. Alternatively, the low power microcontroller **200** and/or the application code/data **203** may include digitally sampled snippets of audio to provide verbal feedback to the end user as the user enters selections via the input devices **210**.

In one embodiment, one or more other/alternate I/O devices or sensors **250** may be included on the IoT device **101** based on the particular application for which the IoT device **101** is designed. For example, an environmental sensor may be included to measure temperature, pressure, humidity, etc. A security sensor and/or door lock opener may be included if the IoT device is used as a security device. Of

course, these examples are provided merely for the purposes of illustration. The underlying principles of the invention are not limited to any particular type of IoT device. In fact, given the highly programmable nature of the low power microcontroller **200** equipped with the library code **202**, an application developer may readily develop new application code **203** and new I/O devices **250** to interface with the low power microcontroller for virtually any type of IoT application.

In one embodiment, the low power microcontroller **200** also includes a secure key store for storing encryption keys for encrypting communications and/or generating signatures. Alternatively, the keys may be secured in a subscriber identify module (SIM).

A wakeup receiver **207** is included in one embodiment to wake the IoT device from an ultra low power state in which it is consuming virtually no power. In one embodiment, the wakeup receiver **207** is configured to cause the IoT device **101** to exit this low power state in response to a wakeup signal received from a wakeup transmitter **307** configured on the IoT hub **110** as shown in FIG. 3. In particular, in one embodiment, the transmitter **307** and receiver **207** together form an electrical resonant transformer circuit such as a Tesla coil. In operation, energy is transmitted via radio frequency signals from the transmitter **307** to the receiver **207** when the hub **110** needs to wake the IoT device **101** from a very low power state. Because of the energy transfer, the IoT device **101** may be configured to consume virtually no power when it is in its low power state because it does not need to continually "listen" for a signal from the hub (as is the case with network protocols which allow devices to be awakened via a network signal). Rather, the microcontroller **200** of the IoT device **101** may be configured to wake up after being effectively powered down by using the energy electrically transmitted from the transmitter **307** to the receiver **207**.

As illustrated in FIG. 3, the IoT hub **110** also includes a memory **317** for storing program code and data **305** and hardware logic **301** such as a microcontroller for executing the program code and processing the data. A wide area network (WAN) interface **302** and antenna **310** couple the IoT hub **110** to the cellular service **115**. Alternatively, as mentioned above, the IoT hub **110** may also include a local network interface (not shown) such as a WiFi interface (and WiFi antenna) or Ethernet interface for establishing a local area network communication channel. In one embodiment, the hardware logic **301** also includes a secure key store for storing encryption keys for encrypting communications and generating/verifying signatures. Alternatively, the keys may be secured in a subscriber identify module (SIM).

A local communication interface **303** and antenna **311** establishes local communication channels with each of the IoT devices **101-105**. As mentioned above, in one embodiment, the local communication interface **303**/antenna **311** implements the Bluetooth LE standard. However, the underlying principles of the invention are not limited to any particular protocols for establishing the local communication channels with the IoT devices **101-105**. Although illustrated as separate units in FIG. 3, the WAN interface **302** and/or local communication interface **303** may be embedded within the same chip as the hardware logic **301**.

In one embodiment, the program code and data includes a communication protocol stack **308** which may include separate stacks for communicating over the local communication interface **303** and the WAN interface **302**. In addition, device pairing program code and data **306** may be stored in the memory to allow the IoT hub to pair with new

IoT devices. In one embodiment, each new IoT device **101-105** is assigned a unique code which is communicated to the IoT hub **110** during the pairing process. For example, the unique code may be embedded in a barcode on the IoT device and may be read by the barcode reader **106** or may be communicated over the local communication channel **130**. In an alternate embodiment, the unique ID code is embedded magnetically on the IoT device and the IoT hub has a magnetic sensor such as a radio frequency ID (RFID) or near field communication (NFC) sensor to detect the code when the IoT device **101** is moved within a few inches of the IoT hub **110**.

In one embodiment, once the unique ID has been communicated, the IoT hub **110** may verify the unique ID by querying a local database (not shown), performing a hash to verify that the code is acceptable, and/or communicating with the IoT service **120**, user device **135** and/or Website **130** to validate the ID code. Once validated, in one embodiment, the IoT hub **110** pairs the IoT device **101** and stores the pairing data in memory **317** (which, as mentioned, may include non-volatile memory). Once pairing is complete, the IoT hub **110** may connect with the IoT device **101** to perform the various IoT functions described herein.

In one embodiment, the organization running the IoT service **120** may provide the IoT hub **110** and a basic hardware/software platform to allow developers to easily design new IoT services. In particular, in addition to the IoT hub **110**, developers may be provided with a software development kit (SDK) to update the program code and data **305** executed within the hub **110**. In addition, for IoT devices **101**, the SDK may include an extensive set of library code **202** designed for the base IoT hardware (e.g., the low power microcontroller **200** and other components shown in FIG. 2) to facilitate the design of various different types of applications **101**. In one embodiment, the SDK includes a graphical design interface in which the developer needs only to specify input and outputs for the IoT device. All of the networking code, including the communication stack **201** that allows the IoT device **101** to connect to the hub **110** and the service **120**, is already in place for the developer. In addition, in one embodiment, the SDK also includes a library code base to facilitate the design of apps for mobile devices (e.g., iPhone and Android devices).

In one embodiment, the IoT hub **110** manages a continuous bi-directional stream of data between the IoT devices **101-105** and the IoT service **120**. In circumstances where updates to/from the IoT devices **101-105** are required in real time (e.g., where a user needs to view the current status of security devices or environmental readings), the IoT hub may maintain an open TCP socket to provide regular updates to the user device **135** and/or external Websites **130**. The specific networking protocol used to provide updates may be tweaked based on the needs of the underlying application. For example, in some cases, where may not make sense to have a continuous bi-directional stream, a simple request/response protocol may be used to gather information when needed.

In one embodiment, both the IoT hub **110** and the IoT devices **101-105** are automatically upgradeable over the network. In particular, when a new update is available for the IoT hub **110** it may automatically download and install the update from the IoT service **120**. It may first copy the updated code into a local memory, run and verify the update before swapping out the older program code. Similarly, when updates are available for each of the IoT devices **101-105**, they may initially be downloaded by the IoT hub **110** and pushed out to each of the IoT devices **101-105**. Each

IoT device **101-105** may then apply the update in a similar manner as described above for the IoT hub and report back the results of the update to the IoT hub **110**. If the update is successful, then the IoT hub **110** may delete the update from its memory and record the latest version of code installed on each IoT device (e.g., so that it may continue to check for new updates for each IoT device).

In one embodiment, the IoT hub **110** is powered via A/C power. In particular, the IoT hub **110** may include a power unit **390** with a transformer for transforming A/C voltage supplied via an A/C power cord to a lower DC voltage.

FIG. 4A illustrates one embodiment of the invention for performing universal remote control operations using the IoT system. In particular, in this embodiment, a set of IoT devices **101-103** are equipped with infrared (IR) and/or radio frequency (RF) blasters **401-403**, respectively, for transmitting remote control codes to control various different types of electronics equipment including air conditioners/heaters **430**, lighting systems **431**, and audiovisual equipment **432** (to name just a few). In the embodiment shown in FIG. 4A, the IoT devices **101-103** are also equipped with sensors **404-406**, respectively, for detecting the operation of the devices which they control, as described below.

For example, sensor **404** in IoT device **101** may be a temperature and/or humidity sensor for sensing the current temperature/humidity and responsively controlling the air conditioner/heater **430** based on a current desired temperature. In this embodiment, the air conditioner/heater **430** is one which is designed to be controlled via a remote control device (typically a remote control which itself has a temperature sensor embedded therein). In one embodiment, the user provides the desired temperature to the IoT hub **110** via an app or browser installed on a user device **135**. Control logic **412** executed on the IoT hub **110** receives the current temperature/humidity data from the sensor **404** and responsively transmits commands to the IoT device **101** to control the IR/RF blaster **401** in accordance with the desired temperature/humidity. For example, if the temperature is below the desired temperature, then the control logic **412** may transmit a command to the air conditioner/heater via the IR/RF blaster **401** to increase the temperature (e.g., either by turning off the air conditioner or turning on the heater). The command may include the necessary remote control code stored in a database **413** on the IoT hub **110**. Alternatively, or in addition, the IoT service **421** may implement control logic **421** to control the electronics equipment **430-432** based on specified user preferences and stored control codes **422**.

IoT device **102** in the illustrated example is used to control lighting **431**. In particular, sensor **405** in IoT device **102** may photosensor or photodetector configured to detect the current brightness of the light being produced by a light fixture **431** (or other lighting apparatus). The user may specify a desired lighting level (including an indication of ON or OFF) to the IoT hub **110** via the user device **135**. In response, the control logic **412** will transmit commands to the IR/RF blaster **402** to control the current brightness level of the lights **431** (e.g., increasing the lighting if the current brightness is too low or decreasing the lighting if the current brightness is too high; or simply turning the lights ON or OFF).

IoT device **103** in the illustrated example is configured to control audiovisual equipment **432** (e.g., a television, A/V receiver, cable/satellite receiver, AppleTV™, etc). Sensor **406** in IoT device **103** may be an audio sensor (e.g., a microphone and associated logic) for detecting a current

ambient volume level and/or a photosensor to detect whether a television is on or off based on the light generated by the television (e.g., by measuring the light within a specified spectrum). Alternatively, sensor **406** may include a temperature sensor connected to the audiovisual equipment to detect whether the audio equipment is on or off based on the detected temperature. Once again, in response to user input via the user device **135**, the control logic **412** may transmit commands to the audiovisual equipment via the IR blaster **403** of the IoT device **103**.

It should be noted that the foregoing are merely illustrative examples of one embodiment of the invention. The underlying principles of the invention are not limited to any particular type of sensors or equipment to be controlled by IoT devices.

In an embodiment in which the IoT devices **101-103** are coupled to the IoT hub **110** via a Bluetooth LE connection, the sensor data and commands are sent over the Bluetooth LE channel. However, the underlying principles of the invention are not limited to Bluetooth LE or any other communication standard.

In one embodiment, the control codes required to control each of the pieces of electronics equipment are stored in a database **413** on the IoT hub **110** and/or a database **422** on the IoT service **120**. As illustrated in FIG. 4B, the control codes may be provided to the IoT hub **110** from a master database of control codes **422** for different pieces of equipment maintained on the IoT service **120**. The end user may specify the types of electronic (or other) equipment to be controlled via the app or browser executed on the user device **135** and, in response, a remote control code learning module **491** on the IoT hub may retrieve the required IR/RF codes from the remote control code database **492** on the IoT service **120** (e.g., identifying each piece of electronic equipment with a unique ID).

In addition, in one embodiment, the IoT hub **110** is equipped with an IR/RF interface **490** to allow the remote control code learning module **491** to “learn” new remote control codes directly from the original remote control **495** provided with the electronic equipment. For example, if control codes for the original remote control provided with the air conditioner **430** is not included in the remote control database, the user may interact with the IoT hub **110** via the app/browser on the user device **135** to teach the IoT hub **110** the various control codes generated by the original remote control (e.g., increase temperature, decrease temperature, etc). Once the remote control codes are learned they may be stored in the control code database **413** on the IoT hub **110** and/or sent back to the IoT service **120** to be included in the central remote control code database **492** (and subsequently used by other users with the same air conditioner unit **430**).

In one embodiment, each of the IoT devices **101-103** have an extremely small form factor and may be affixed on or near their respective electronics equipment **430-432** using double-sided tape, a small nail, a magnetic attachment, etc. For control of a piece of equipment such as the air conditioner **430**, it would be desirable to place the IoT device **101** sufficiently far away so that the sensor **404** can accurately measure the ambient temperature in the home (e.g., placing the IoT device directly on the air conditioner would result in a temperature measurement which would be too low when the air conditioner was running or too high when the heater was running). In contrast, the IoT device **102** used for controlling lighting may be placed on or near the lighting fixture **431** for the sensor **405** to detect the current lighting level.

In addition to providing general control functions as described, one embodiment of the IoT hub **110** and/or IoT service **120** transmits notifications to the end user related to the current status of each piece of electronics equipment.

The notifications, which may be text messages and/or app-specific notifications, may then be displayed on the display of the user’s mobile device **135**. For example, if the user’s air conditioner has been on for an extended period of time but the temperature has not changed, the IoT hub **110** and/or IoT service **120** may send the user a notification that the air conditioner is not functioning properly. If the user is not home (which may be detected via motion sensors or based on the user’s current detected location), and the sensors **406** indicate that audiovisual equipment **430** is on or sensors **405** indicate that the lights are on, then a notification may be sent to the user, asking if the user would like to turn off the audiovisual equipment **432** and/or lights **431**. The same type of notification may be sent for any equipment type.

Once the user receives a notification, he/she may remotely control the electronics equipment **430-432** via the app or browser on the user device **135**. In one embodiment, the user device **135** is a touchscreen device and the app or browser displays an image of a remote control with user-selectable buttons for controlling the equipment **430-432**. Upon receiving a notification, the user may open the graphical remote control and turn off or adjust the various different pieces of equipment. If connected via the IoT service **120**, the user’s selections may be forwarded from the IoT service **120** to the IoT hub **110** which will then control the equipment via the control logic **412**. Alternatively, the user input may be sent directly to the IoT hub **110** from the user device **135**.

In one embodiment, the user may program the control logic **412** on the IoT hub **110** to perform various automatic control functions with respect to the electronics equipment **430-432**. In addition to maintaining a desired temperature, brightness level, and volume level as described above, the control logic **412** may automatically turn off the electronics equipment if certain conditions are detected. For example, if the control logic **412** detects that the user is not home and that the air conditioner is not functioning, it may automatically turn off the air conditioner. Similarly, if the user is not home, and the sensors **406** indicate that audiovisual equipment **430** is on or sensors **405** indicate that the lights are on, then the control logic **412** may automatically transmit commands via the IR/RF blasters **403** and **402**, to turn off the audiovisual equipment and lights, respectively.

FIG. 5 illustrates additional embodiments of IoT devices **104-105** equipped with sensors **503-504** for monitoring electronic equipment **530-531**. In particular, the IoT device **104** of this embodiment includes a temperature sensor **503** which may be placed on or near a stove **530** to detect when the stove has been left on. In one embodiment, the IoT device **104** transmits the current temperature measured by the temperature sensor **503** to the IoT hub **110** and/or the IoT service **120**. If the stove is detected to be on for more than a threshold time period (e.g., based on the measured temperature), then control logic **512** may transmit a notification to the end user’s device **135** informing the user that the stove **530** is on. In addition, in one embodiment, the IoT device **104** may include a control module **501** to turn off the stove, either in response to receiving an instruction from the user or automatically (if the control logic **512** is programmed to do so by the user). In one embodiment, the control logic **501** comprises a switch to cut off electricity or gas to the stove **530**. However, in other embodiments, the control logic **501** may be integrated within the stove itself.

FIG. 5 also illustrates an IoT device 105 with a motion sensor 504 for detecting the motion of certain types of electronics equipment such as a washer and/or dryer. Another sensor that may be used is an audio sensor (e.g., microphone and logic) for detecting an ambient volume level. As with the other embodiments described above, this embodiment may transmit notifications to the end user if certain specified conditions are met (e.g., if motion is detected for an extended period of time, indicating that the washer/dryer are not turning off). Although not shown in FIG. 5, IoT device 105 may also be equipped with a control module to turn off the washer/dryer 531 (e.g., by switching off electric/gas), automatically, and/or in response to user input.

In one embodiment, a first IoT device with control logic and a switch may be configured to turn off all power in the user's home and a second IoT device with control logic and a switch may be configured to turn off all gas in the user's home. IoT devices with sensors may then be positioned on or near electronic or gas-powered equipment in the user's home. If the user is notified that a particular piece of equipment has been left on (e.g., the stove 530), the user may then send a command to turn off all electricity or gas in the home to prevent damage. Alternatively, the control logic 512 in the IoT hub 110 and/or the IoT service 120 may be configured to automatically turn off electricity or gas in such situations.

In one embodiment, the IoT hub 110 and IoT service 120 communicate at periodic intervals. If the IoT service 120 detects that the connection to the IoT hub 110 has been lost (e.g., by failing to receive a request or response from the IoT hub for a specified duration), it will communicate this information to the end user's device 135 (e.g., by sending a text message or app-specific notification).

#### Apparatus and Method for Communicating Data Through an Intermediary Device

As mentioned above, because the wireless technologies used to interconnect IoT devices such as Bluetooth LE are generally short range technologies, if the hub for an IoT implementation is outside the range of an IoT device, the IoT device will not be able to transmit data to the IoT hub (and vice versa).

To address this deficiency, one embodiment of the invention provides a mechanism for an IoT device which is outside of the wireless range of the IoT hub to periodically connect with one or more mobile devices when the mobile devices are within range. Once connected, the IoT device can transmit any data which needs to be provided to the IoT hub to the mobile device which then forwards the data to the IoT hub.

As illustrated in FIG. 6 one embodiment includes an IoT hub 110, an IoT device 601 which is out of range of the IoT hub 110 and a mobile device 611. The out of range IoT device 601 may include any form of IoT device capable of collecting and communicating data. For example, the IoT device 601 may comprise a data collection device configured within a refrigerator to monitor the food items available in the refrigerator, the users who consume the food items, and the current temperature. Of course, the underlying principles of the invention are not limited to any particular type of IoT device. The techniques described herein may be implemented using any type of IoT device including those used to collect and transmit data for smart meters, stoves, washers, dryers, lighting systems, HVAC systems, and audiovisual equipment, to name just a few.

Moreover, the mobile device In operation, the IoT device 611 illustrated in FIG. 6 may be any form of mobile device capable of communicating and storing data. For example, in one embodiment, the mobile device 611 is a smartphone with an app installed thereon to facilitate the techniques described herein. In another embodiment, the mobile device 611 comprises a wearable device such as a communication token affixed to a neckless or bracelet, a smartwatch or a fitness device. The wearable token may be particularly useful for elderly users or other users who do not own a smartphone device.

In operation, the out of range IoT device 601 may periodically or continually check for connectivity with a mobile device 611. Upon establishing a connection (e.g., as the result of the user moving within the vicinity of the refrigerator) any collected data 605 on the IoT device 601 is automatically transmitted to a temporary data repository 615 on the mobile device 611. In one embodiment, the IoT device 601 and mobile device 611 establish a local wireless communication channel using a low power wireless standard such as BTLE. In such a case, the mobile device 611 may initially be paired with the IoT device 601 using known pairing techniques.

Once the data has been transferred to the temporary data repository, the mobile device 611 will transmit the data once communication is established with the IoT hub 110 (e.g., when the user walks within the range of the IoT hub 110). The IoT hub may then store the data in a central data repository 413 and/or send the data over the Internet to one or more services and/or other user devices. In one embodiment, the mobile device 611 may use a different type of communication channel to provide the data to the IoT hub 110 (potentially a higher power communication channel such as WiFi).

The out of range IoT device 601, the mobile device 611, and the IoT hub may all be configured with program code and/or logic to implement the techniques described herein. As illustrated in FIG. 7, for example, the IoT device 601 may be configured with intermediary connection logic and/or application, the mobile device 611 may be configured with an intermediary connection logic/application, and the IoT hub 110 may be configured with an intermediary connection logic/application 721 to perform the operations described herein. The intermediary connection logic/application on each device may be implemented in hardware, software, or any combination thereof. In one embodiment, the intermediary connection logic/application 701 of the IoT device 601 searches and establishes a connection with the intermediary connection logic/application 711 on the mobile device (which may be implemented as a device app) to transfer the data to the temporary data repository 615. The intermediary connection logic/application 701 on the mobile device 611 then forwards the data to the intermediary connection logic/application on the IoT hub, which stores the data in the central data repository 413.

As illustrated in FIG. 7, the intermediary connection logic/applications 701, 711, 721, on each device may be configured based on the application at hand. For example, for a refrigerator, the connection logic/application 701 may only need to transmit a few packets on a periodic basis. For other applications (e.g., temperature sensors), the connection logic/application 701 may need to transmit more frequent updates.

Rather than a mobile device 611, in one embodiment, the IoT device 601 may be configured to establish a wireless connection with one or more intermediary IoT devices, which are located within range of the IoT hub 110. In this

embodiment, any IoT devices **601** out of range of the IoT hub may be linked to the hub by forming a “chain” using other IoT devices.

In addition, while only a single mobile device **611** is illustrated in FIGS. **6-7** for simplicity, in one embodiment, multiple such mobile devices of different users may be configured to communicate with the IoT device **601**. Moreover, the same techniques may be implemented for multiple other IoT devices, thereby forming an intermediary device data collection system across the entire home.

Moreover, in one embodiment, the techniques described herein may be used to collect various different types of pertinent data. For example, in one embodiment, each time the mobile device **611** connects with the IoT device **601**, the identity of the user may be included with the collected data **605**. In this manner, the IoT system may be used to track the behavior of different users within the home. For example, if used within a refrigerator, the collected data **605** may then include the identify of each user who passes by fridge, each user who opens the fridge, and the specific food items consumed by each user. Different types of data may be collected from other types of IoT devices. Using this data the system is able to determine, for example, which user washes clothes, which user watches TV on a given day, the times at which each user goes to sleep and wakes up, etc. All of this crowd-sourced data may then be compiled within the data repository **413** of the IoT hub and/or forwarded to an external service or user.

Another beneficial application of the techniques described herein is for monitoring elderly users who may need assistance. For this application, the mobile device **611** may be a very small token worn by the elderly user to collect the information in different rooms of the user’s home. Each time the user opens the refrigerator, for example, this data will be included with the collected data **605** and transferred to the IoT hub **110** via the token. The IoT hub may then provide the data to one or more external users (e.g., the children or other individuals who care for the elderly user). If data has not been collected for a specified period of time (e.g., 12 hours), then this means that the elderly user has not been moving around the home and/or has not been opening the refrigerator. The IoT hub **110** or an external service connected to the IoT hub may then transmit an alert notification to these other individuals, informing them that they should check on the elderly user. In addition, the collected data **605** may include other pertinent information such as the food being consumed by the user and whether a trip to the grocery store is needed, whether and how frequently the elderly user is watching TV, the frequency with which the elderly user washes clothes, etc.

In another implementation, the if there is a problem with an electronic device such as a washer, refrigerator, HVAC system, etc, the collected data may include an indication of a part that needs to be replaced. In such a case, a notification may be sent to a technician with a request to fix the problem. The technician may then arrive at the home with the needed replacement part.

A method in accordance with one embodiment of the invention is illustrated in FIG. **8**. The method may be implemented within the context of the architectures described above, but is not limited to any particular architecture.

At **801**, an IoT device which is out of range of the IoT hub periodically collects data (e.g., opening of the refrigerator door, food items used, etc). At **802** the IoT device periodically or continually checks for connectivity with a mobile device (e.g., using standard local wireless techniques for

establishing a connection such as those specified by the BTLE standard). If the connection to the mobile device is established, determined at **802**, then at **803**, the collected data is transferred to the mobile device at **803**. At **804**, the mobile device transfers the data to the IoT hub, an external service and/or a user. As mentioned, the mobile device may transmit the data immediately if it is already connected (e.g., via a WiFi link).

In addition to collecting data from IoT devices, in one embodiment, the techniques described herein may be used to update or otherwise provide data to IoT devices. One example is shown in FIG. **9A**, which shows an IoT hub **110** with program code updates **901** that need to be installed on an IoT device **601** (or a group of such IoT devices). The program code updates may include system updates, patches, configuration data and any other data needed for the IoT device to operate as desired by the user. In one embodiment, the user may specify configuration options for the IoT device **601** via a mobile device or computer which are then stored on the IoT hub **110** and provided to the IoT device using the techniques described herein. Specifically, in one embodiment, the intermediary connection logic/application **721** on the IoT hub **110** communicates with the intermediary connection logic/application **711** on the mobile device **611** to store the program code updates within a temporary storage **615**. When the mobile device **611** enters the range of the IoT device **601**, the intermediary connection logic/application **711** on the mobile device **611** connects with the intermediary/connection logic/application **701** on the IoT device **601** to provide the program code updates to the device. In one embodiment, the IoT device **601** may then enter into an automated update process to install the new program code updates and/or data.

A method for updating an IoT device is shown in FIG. **9B**. The method may be implemented within the context of the system architectures described above, but is not limited to any particular system architectures.

At **900** new program code or data updates are made available on the IoT hub and/or an external service (e.g., coupled to the mobile device over the Internet). At **901**, the mobile device receives and stores the program code or data updates on behalf of the IoT device. The IoT device and/or mobile device periodically check to determine whether a connection has been established at **902**. If a connection is established, determined at **903**, then at **904** the updates are transferred to the IoT device and installed.

#### Embodiments for Improved Security

In one embodiment, the low power microcontroller **200** of each IoT device **101** and the low power logic/microcontroller **301** of the IoT hub **110** include a secure key store for storing encryption keys used by the embodiments described below (see, e.g., FIGS. **10-15** and associated text). Alternatively, the keys may be secured in a subscriber identify module (SIM) as discussed below.

FIG. **10** illustrates a high level architecture which uses public key infrastructure (PKI) techniques and/or symmetric key exchange/encryption techniques to encrypt communications between the IoT Service **120**, the IoT hub **110** and the IoT devices **101-102**.

Embodiments which use public/private key pairs will first be described, followed by embodiments which use symmetric key exchange/encryption techniques. In particular, in an embodiment which uses PKI, a unique public/private key pair is associated with each IoT device **101-102**, each IoT hub **110** and the IoT service **120**. In one embodiment, when

a new IoT hub **110** is set up, its public key is provided to the IoT service **120** and when a new IoT device **101** is set up, its public key is provided to both the IoT hub **110** and the IoT service **120**. Various techniques for securely exchanging the public keys between devices are described below. In one embodiment, all public keys are signed by a master key known to all of the receiving devices (i.e., a form of certificate) so that any receiving device can verify the validity of the public keys by validating the signatures. Thus, these certificates would be exchanged rather than merely exchanging the raw public keys.

As illustrated, in one embodiment, each IoT device **101**, **102** includes a secure key storage **1001**, **1003**, respectively, for security storing each device's private key. Security logic **1002**, **1304** then utilizes the securely stored private keys to perform the encryption/decryption operations described herein. Similarly, the IoT hub **110** includes a secure storage **1011** for storing the IoT hub private key and the public keys of the IoT devices **101-102** and the IoT service **120**; as well as security logic **1012** for using the keys to perform encryption/decryption operations. Finally, the IoT service **120** may include a secure storage **1021** for security storing its own private key, the public keys of various IoT devices and IoT hubs, and a security logic **1013** for using the keys to encrypt/decrypt communication with IoT hubs and devices. In one embodiment, when the IoT hub **110** receives a public key certificate from an IoT device it can verify it (e.g., by validating the signature using the master key as described above), and then extract the public key from within it and store that public key in its secure key store **1011**.

By way of example, in one embodiment, when the IoT service **120** needs to transmit a command or data to an IoT device **101** (e.g., a command to unlock a door, a request to read a sensor, data to be processed/displayed by the IoT device, etc) the security logic **1013** encrypts the data/command using the public key of the IoT device **101** to generate an encrypted IoT device packet. In one embodiment, it then encrypts the IoT device packet using the public key of the IoT hub **110** to generate an IoT hub packet and transmits the IoT hub packet to the IoT hub **110**. In one embodiment, the service **120** signs the encrypted message with its private key or the master key mentioned above so that the device **101** can verify it is receiving an unaltered message from a trusted source. The device **101** may then validate the signature using the public key corresponding to the private key and/or the master key. As mentioned above, symmetric key exchange/encryption techniques may be used instead of public/private key encryption. In these embodiments, rather than privately storing one key and providing a corresponding public key to other devices, the devices may each be provided with a copy of the same symmetric key to be used for encryption and to validate signatures. One example of a symmetric key algorithm is the Advanced Encryption Standard (AES), although the underlying principles of the invention are not limited to any type of specific symmetric keys.

Using a symmetric key implementation, each device **101** enters into a secure key exchange protocol to exchange a symmetric key with the IoT hub **110**. A secure key provisioning protocol such as the Dynamic Symmetric Key Provisioning Protocol (DSKPP) may be used to exchange the keys over a secure communication channel (see, e.g., Request for Comments (RFC) 6063). However, the underlying principles of the invention are not limited to any particular key provisioning protocol.

Once the symmetric keys have been exchanged, they may be used by each device **101** and the IoT hub **110** to encrypt

communications. Similarly, the IoT hub **110** and IoT service **120** may perform a secure symmetric key exchange and then use the exchanged symmetric keys to encrypt communications. In one embodiment a new symmetric key is exchanged periodically between the devices **101** and the hub **110** and between the hub **110** and the IoT service **120**. In one embodiment, a new symmetric key is exchanged with each new communication session between the devices **101**, the hub **110**, and the service **120** (e.g., a new key is generated and securely exchanged for each communication session). In one embodiment, if the security module **1012** in the IoT hub is trusted, the service **120** could negotiate a session key with the hub security module **1312** and then the security module **1012** would negotiate a session key with each device **120**. Messages from the service **120** would then be decrypted and verified in the hub security module **1012** before being re-encrypted for transmission to the device **101**.

In one embodiment, to prevent a compromise on the hub security module **1012** a one-time (permanent) installation key may be negotiated between the device **101** and service **120** at installation time. When sending a message to a device **101** the service **120** could first encrypt/MAC with this device installation key, then encrypt/MAC that with the hub's session key. The hub **110** would then verify and extract the encrypted device blob and send that to the device.

In one embodiment of the invention, a counter mechanism is implemented to prevent replay attacks. For example, each successive communication from the device **101** to the hub **110** (or vice versa) may be assigned a continually increasing counter value. Both the hub **110** and device **101** will track this value and verify that the value is correct in each successive communication between the devices. The same techniques may be implemented between the hub **110** and the service **120**. Using a counter in this manner would make it more difficult to spoof the communication between each of the devices (because the counter value would be incorrect). However, even without this a shared installation key between the service and device would prevent network (hub) wide attacks to all devices.

In one embodiment, when using public/private key encryption, the IoT hub **110** uses its private key to decrypt the IoT hub packet and generate the encrypted IoT device packet, which it transmits to the associated IoT device **101**. The IoT device **101** then uses its private key to decrypt the IoT device packet to generate the command/data originated from the IoT service **120**. It may then process the data and/or execute the command. Using symmetric encryption, each device would encrypt and decrypt with the shared symmetric key. If either case, each transmitting device may also sign the message with its private key so that the receiving device can verify its authenticity.

A different set of keys may be used to encrypt communication from the IoT device **101** to the IoT hub **110** and to the IoT service **120**. For example, using a public/private key arrangement, in one embodiment, the security logic **1002** on the IoT device **101** uses the public key of the IoT hub **110** to encrypt data packets sent to the IoT hub **110**. The security logic **1012** on the IoT hub **110** may then decrypt the data packets using the IoT hub's private key. Similarly, the security logic **1002** on the IoT device **101** and/or the security logic **1012** on the IoT hub **110** may encrypt data packets sent to the IoT service **120** using the public key of the IoT service **120** (which may then be decrypted by the security logic **1013** on the IoT service **120** using the service's private key). Using symmetric keys, the device **101** and hub **110** may share a symmetric key while the hub and service **120** may share a different symmetric key.

While certain specific details are set forth above in the description above, it should be noted that the underlying principles of the invention may be implemented using various different encryption techniques. For example, while some embodiments discussed above use asymmetric public/private key pairs, an alternate embodiment may use symmetric keys securely exchanged between the various IoT devices **101-102**, IoT hubs **110**, and the IoT service **120**. Moreover, in some embodiments, the data/command itself is not encrypted, but a key is used to generate a signature over the data/command (or other data structure). The recipient may then use its key to validate the signature.

As illustrated in FIG. **11**, in one embodiment, the secure key storage on each IoT device **101** is implemented using a programmable subscriber identity module (SIM) **1101**. In this embodiment, the IoT device **101** may initially be provided to the end user with an un-programmed SIM card **1101** seated within a SIM interface **1100** on the IoT device **101**. In order to program the SIM with a set of one or more encryption keys, the user takes the programmable SIM card **1101** out of the SIM interface **500** and inserts it into a SIM programming interface **1102** on the IoT hub **110**. Programming logic **1125** on the IoT hub then securely programs the SIM card **1101** to register/pair the IoT device **101** with the IoT hub **110** and IoT service **120**. In one embodiment, a public/private key pair may be randomly generated by the programming logic **1125** and the public key of the pair may then be stored in the IoT hub's secure storage device **411** while the private key may be stored within the programmable SIM **1101**. In addition, the programming logic **525** may store the public keys of the IoT hub **110**, the IoT service **120**, and/or any other IoT devices **101** on the SIM card **1401** (to be used by the security logic **1302** on the IoT device **101** to encrypt outgoing data). Once the SIM **1101** is programmed, the new IoT device **101** may be provisioned with the IoT Service **120** using the SIM as a secure identifier (e.g., using existing techniques for registering a device using a SIM). Following provisioning, both the IoT hub **110** and the IoT service **120** will securely store a copy of the IoT device's public key to be used when encrypting communication with the IoT device **101**.

The techniques described above with respect to FIG. **11** provide enormous flexibility when providing new IoT devices to end users. Rather than requiring a user to directly register each SIM with a particular service provider upon sale/purchase (as is currently done), the SIM may be programmed directly by the end user via the IoT hub **110** and the results of the programming may be securely communicated to the IoT service **120**. Consequently, new IoT devices **101** may be sold to end users from online or local retailers and later securely provisioned with the IoT service **120**.

While the registration and encryption techniques are described above within the specific context of a SIM (Subscriber Identity Module), the underlying principles of the invention are not limited to a "SIM" device. Rather, the underlying principles of the invention may be implemented using any type of device having secure storage for storing a set of encryption keys. Moreover, while the embodiments above include a removable SIM device, in one embodiment, the SIM device is not removable but the IoT device itself may be inserted within the programming interface **1102** of the IoT hub **110**.

In one embodiment, rather than requiring the user to program the SIM (or other device), the SIM is pre-programmed into the IoT device **101**, prior to distribution to the end user. In this embodiment, when the user sets up the IoT device **101**, various techniques described herein may be

used to securely exchange encryption keys between the IoT hub **110**/IoT service **120** and the new IoT device **101**.

For example, as illustrated in FIG. **12A** each IoT device **101** or SIM **401** may be packaged with a barcode or QR code **1501** uniquely identifying the IoT device **101** and/or SIM **1001**. In one embodiment, the barcode or QR code **1201** comprises an encoded representation of the public key for the IoT device **101** or SIM **1001**. Alternatively, the barcode or QR code **1201** may be used by the IoT hub **110** and/or IoT service **120** to identify or generate the public key (e.g., used as a pointer to the public key which is already stored in secure storage). The barcode or QR code **601** may be printed on a separate card (as shown in FIG. **12A**) or may be printed directly on the IoT device itself. Regardless of where the barcode is printed, in one embodiment, the IoT hub **110** is equipped with a barcode reader **206** for reading the barcode and providing the resulting data to the security logic **1012** on the IoT hub **110** and/or the security logic **1013** on the IoT service **120**. The security logic **1012** on the IoT hub **110** may then store the public key for the IoT device within its secure key storage **1011** and the security logic **1013** on the IoT service **120** may store the public key within its secure storage **1021** (to be used for subsequent encrypted communication).

In one embodiment, the data contained in the barcode or QR code **1201** may also be captured via a user device **135** (e.g., such as an iPhone or Android device) with an installed IoT app or browser-based applet designed by the IoT service provider. Once captured, the barcode data may be securely communicated to the IoT service **120** over a secure connection (e.g., such as a secure sockets layer (SSL) connection). The barcode data may also be provided from the client device **135** to the IoT hub **110** over a secure local connection (e.g., over a local WiFi or Bluetooth LE connection).

The security logic **1002** on the IoT device **101** and the security logic **1012** on the IoT hub **110** may be implemented using hardware, software, firmware or any combination thereof. For example, in one embodiment, the security logic **1002**, **1012** is implemented within the chips used for establishing the local communication channel **130** between the IoT device **101** and the IoT hub **110** (e.g., the Bluetooth LE chip if the local channel **130** is Bluetooth LE). Regardless of the specific location of the security logic **1002**, **1012**, in one embodiment, the security logic **1002**, **1012** is designed to establish a secure execution environment for executing certain types of program code. This may be implemented, for example, by using TrustZone technology (available on some ARM processors) and/or Trusted Execution Technology (designed by Intel). Of course, the underlying principles of the invention are not limited to any particular type of secure execution technology.

In one embodiment, the barcode or QR code **1501** may be used to pair each IoT device **101** with the IoT hub **110**. For example, rather than using the standard wireless pairing process currently used to pair Bluetooth LE devices, a pairing code embedded within the barcode or QR code **1501** may be provided to the IoT hub **110** to pair the IoT hub with the corresponding IoT device.

FIG. **12B** illustrates one embodiment in which the barcode reader **206** on the IoT hub **110** captures the barcode/QR code **1201** associated with the IoT device **101**. As mentioned, the barcode/QR code **1201** may be printed directly on the IoT device **101** or may be printed on a separate card provided with the IoT device **101**. In either case, the barcode reader **206** reads the pairing code from the barcode/QR code **1201** and provides the pairing code to the local communication module **1280**. In one embodiment, the local commu-

nication module **1280** is a Bluetooth LE chip and associated software, although the underlying principles of the invention are not limited to any particular protocol standard. Once the pairing code is received, it is stored in a secure storage containing pairing data **1285** and the IoT device **101** and IoT hub **110** are automatically paired. Each time the IoT hub is paired with a new IoT device in this manner, the pairing data for that pairing is stored within the secure storage **685**. In one embodiment, once the local communication module **1280** of the IoT hub **110** receives the pairing code, it may use the code as a key to encrypt communications over the local wireless channel with the IoT device **101**.

Similarly, on the IoT device **101** side, the local communication module **1590** stores pairing data within a local secure storage device **1595** indicating the pairing with the IoT hub. The pairing data **1295** may include the pre-programmed pairing code identified in the barcode/QR code **1201**. The pairing data **1295** may also include pairing data received from the local communication module **1280** on the IoT hub **110** required for establishing a secure local communication channel (e.g., an additional key to encrypt communication with the IoT hub **110**).

Thus, the barcode/QR code **1201** may be used to perform local pairing in a far more secure manner than current wireless pairing protocols because the pairing code is not transmitted over the air. In addition, in one embodiment, the same barcode/QR code **1201** used for pairing may be used to identify encryption keys to build a secure connection from the IoT device **101** to the IoT hub **110** and from the IoT hub **110** to the IoT service **120**.

A method for programming a SIM card in accordance with one embodiment of the invention is illustrated in FIG. **13**. The method may be implemented within the system architecture described above, but is not limited to any particular system architecture.

At **1301**, a user receives a new IoT device with a blank SIM card and, at **1602**, the user inserts the blank SIM card into an IoT hub. At **1303**, the user programs the blank SIM card with a set of one or more encryption keys. For example, as mentioned above, in one embodiment, the IoT hub may randomly generate a public/private key pair and store the private key on the SIM card and the public key in its local secure storage. In addition, at **1304**, at least the public key is transmitted to the IoT service so that it may be used to identify the IoT device and establish encrypted communication with the IoT device. As mentioned above, in one embodiment, a programmable device other than a "SIM" card may be used to perform the same functions as the SIM card in the method shown in FIG. **13**.

A method for integrating a new IoT device into a network is illustrated in FIG. **14**. The method may be implemented within the system architecture described above, but is not limited to any particular system architecture.

At **1401**, a user receives a new IoT device to which an encryption key has been pre-assigned. At **1402**, the key is securely provided to the IoT hub. As mentioned above, in one embodiment, this involves reading a barcode associated with the IoT device to identify the public key of a public/private key pair assigned to the device. The barcode may be read directly by the IoT hub or captured via a mobile device via an app or browser. In an alternate embodiment, a secure communication channel such as a Bluetooth LE channel, a near field communication (NFC) channel or a secure WiFi channel may be established between the IoT device and the IoT hub to exchange the key. Regardless of how the key is transmitted, once received, it is stored in the secure keystore of the IoT hub device. As mentioned above, various secure

execution technologies may be used on the IoT hub to store and protect the key such as Secure Enclaves, Trusted Execution Technology (TXT), and/or Trustzone. In addition, at **803**, the key is securely transmitted to the IoT service which stores the key in its own secure keystore. It may then use the key to encrypt communication with the IoT device. One again, the exchange may be implemented using a certificate/signed key. Within the hub **110** it is particularly important to prevent modification/addition/removal of the stored keys.

A method for securely communicating commands/data to an IoT device using public/private keys is illustrated in FIG. **15**. The method may be implemented within the system architecture described above, but is not limited to any particular system architecture.

At **1501**, the IoT service encrypts the data/commands using the IoT device public key to create an IoT device packet. It then encrypts the IoT device packet using IoT hub's public key to create the IoT hub packet (e.g., creating an IoT hub wrapper around the IoT device packet). At **1502**, the IoT service transmits the IoT hub packet to the IoT hub. At **1503**, the IoT hub decrypts the IoT hub packet using the IoT hub's private key to generate the IoT device packet. At **1504** it then transmits the IoT device packet to the IoT device which, at **1505**, decrypts the IoT device packet using the IoT device private key to generate the data/commands. At **1506**, the IoT device processes the data/commands.

In an embodiment which uses symmetric keys, a symmetric key exchange may be negotiated between each of the devices (e.g., each device and the hub and between the hub and the service). Once the key exchange is complete, each transmitting device encrypts and/or signs each transmission using the symmetric key before transmitting data to the receiving device.

### Apparatus and Method for Establishing Secure Communication Channels in an Internet of Things (IoT) System

In one embodiment of the invention, encryption and decryption of data is performed between the IoT service **120** and each IoT device **101**, regardless of the intermediate devices used to support the communication channel (e.g., such as the user's mobile device **611** and/or the IoT hub **110**). One embodiment which communicates via an IoT hub **110** is illustrated in FIG. **16A** and another embodiment which does not require an IoT hub is illustrated in FIG. **16B**.

Turning first to FIG. **16A**, the IoT service **120** includes an encryption engine **1660** which manages a set of "service session keys" **1650** and each IoT device **101** includes an encryption engine **1661** which manages a set of "device session keys" **1651** for encrypting/decrypting communication between the IoT device **101** and IoT service **120**. The encryption engines may rely on different hardware modules when performing the security/encryption techniques described herein including a hardware security module **1630-1631** for (among other things) generating a session public/private key pair and preventing access to the private session key of the pair and a key stream generation module **1640-1641** for generating a key stream using a derived secret. In one embodiment, the service session keys **1650** and the device session keys **1651** comprise related public/private key pairs. For example, in one embodiment, the device session keys **1651** on the IoT device **101** include a public key of the IoT service **120** and a private key of the IoT device **101**. As discussed in detail below, in one embodiment, to establish a secure communication session, the public/private session key pairs, **1650** and **1651**, are used by

21

each encryption engine, **1660** and **1661**, respectively, to generate the same secret which is then used by the SKGMs **1640-1641** to generate a key stream to encrypt and decrypt communication between the IoT service **120** and the IoT device **101**. Additional details associated with generation and use of the secret in accordance with one embodiment of the invention are provided below.

In FIG. **16A**, once the secret has been generated using the keys **1650-1651**, the client will always send messages to the IoT device **101** through the IoT service **120**, as indicated by Clear transaction **1611**. “Clear” as used herein is meant to indicate that the underlying message is not encrypted using the encryption techniques described herein. However, as illustrated, in one embodiment, a secure sockets layer (SSL) channel or other secure channel (e.g., an Internet Protocol Security (IPSEC) channel) is established between the client device **611** and IoT service **120** to protect the communication. The encryption engine **1660** on the IoT service **120** then encrypts the message using the generated secret and transmits the encrypted message to the IoT hub **110** at **1602**. Rather than using the secret to encrypt the message directly, in one embodiment, the secret and a counter value are used to generate a key stream, which is used to encrypt each message packet. Details of this embodiment are described below with respect to FIG. **17**.

As illustrated, an SSL connection or other secure channel may be established between the IoT service **120** and the IoT hub **110**. The IoT hub **110** (which does not have the ability to decrypt the message in one embodiment) transmits the encrypted message to the IoT device at **1603** (e.g., over a Bluetooth Low Energy (BTLE) communication channel). The encryption engine **1661** on the IoT device **101** may then decrypt the message using the secret and process the message contents. In an embodiment which uses the secret to generate a key stream, the encryption engine **1661** may generate the key stream using the secret and a counter value and then use the key stream for decryption of the message packet.

The message itself may comprise any form of communication between the IoT service **120** and IoT device **101**. For example, the message may comprise a command packet instructing the IoT device **101** to perform a particular function such as taking a measurement and reporting the result back to the client device **611** or may include configuration data to configure the operation of the IoT device **101**.

If a response is required, the encryption engine **1661** on the IoT device **101** uses the secret or a derived key stream to encrypt the response and transmits the encrypted response to the IoT hub **110** at **1604**, which forwards the response to the IoT service **120** at **1605**. The encryption engine **1660** on the IoT service **120** then decrypts the response using the secret or a derived key stream and transmits the decrypted response to the client device **611** at **1606** (e.g., over the SSL or other secure communication channel).

FIG. **16B** illustrates an embodiment which does not require an IoT hub. Rather, in this embodiment, communication between the IoT device **101** and IoT service **120** occurs through the client device **611** (e.g., as in the embodiments described above with respect to FIGS. **6-9B**). In this embodiment, to transmit a message to the IoT device **101** the client device **611** transmits an unencrypted version of the message to the IoT service **120** at **1611**. The encryption engine **1660** encrypts the message using the secret or the derived key stream and transmits the encrypted message back to the client device **611** at **1612**. The client device **611** then forwards the encrypted message to the IoT device **101** at **1613**, and the encryption engine **1661** decrypts the mes-

22

sage using the secret or the derived key stream. The IoT device **101** may then process the message as described herein. If a response is required, the encryption engine **1661** encrypts the response using the secret and transmits the encrypted response to the client device **611** at **1614**, which forwards the encrypted response to the IoT service **120** at **1615**. The encryption engine **1660** then decrypts the response and transmits the decrypted response to the client device **611** at **1616**.

FIG. **17** illustrates a key exchange and key stream generation which may initially be performed between the IoT service **120** and the IoT device **101**. In one embodiment, this key exchange may be performed each time the IoT service **120** and IoT device **101** establish a new communication session. Alternatively, the key exchange may be performed and the exchanged session keys may be used for a specified period of time (e.g., a day, a week, etc). While no intermediate devices are shown in FIG. **17** for simplicity, communication may occur through the IoT hub **110** and/or the client device **611**.

In one embodiment, the encryption engine **1660** of the IoT service **120** sends a command to the HSM **1630** (e.g., which may be such as a CloudHSM offered by Amazon®) to generate a session public/private key pair. The HSM **1630** may subsequently prevent access to the private session key of the pair. Similarly, the encryption engine on the IoT device **101** may transmit a command to the HSM **1631** (e.g., such as an Atecc508 HSM from Atmel Corporation®) which generates a session public/private key pair and prevents access to the session private key of the pair. Of course, the underlying principles of the invention are not limited to any specific type of encryption engine or manufacturer.

In one embodiment, the IoT service **120** transmits its session public key generated using the HSM **1630** to the IoT device **101** at **1701**. The IoT device uses its HSM **1631** to generate its own session public/private key pair and, at **1702**, transmits its public key of the pair to the IoT service **120**. In one embodiment, the encryption engines **1660-1661** use an Elliptic curve Diffie-Hellman (ECDH) protocol, which is an anonymous key agreement that allows two parties with an elliptic curve public-private key pair, to establish a shared secret. In one embodiment, using these techniques, at **1703**, the encryption engine **1660** of the IoT service **120** generates the secret using the IoT device session public key and its own session private key. Similarly, at **1704**, the encryption engine **1661** of the IoT device **101** independently generates the same secret using the IoT service **120** session public key and its own session private key. More specifically, in one embodiment, the encryption engine **1660** on the IoT service **120** generates the secret according to the formula  $\text{secret} = \text{IoT device session pub key} * \text{IoT service session private key}$ , where “\*” means that the IoT device session public key is point-multiplied by the IoT service session private key. The encryption engine **1661** on the IoT device **101** generates the secret according to the formula  $\text{secret} = \text{IoT service session pub key} * \text{IoT device session private key}$ , where the IoT service session public key is point multiplied by the IoT device session private key. In the end, the IoT service **120** and IoT device **101** have both generated the same secret to be used to encrypt communication as described below. In one embodiment, the encryption engines **1660-1661** rely on a hardware module such as the KSGMs **1640-1641** respectively to perform the above operations for generating the secret.

Once the secret has been determined, it may be used by the encryption engines **1660** and **1661** to encrypt and decrypt data directly. Alternatively, in one embodiment, the

encryption engines **1660-1661** send commands to the KSGMs **1640-1641** to generate a new key stream using the secret to encrypt/decrypt each data packet (i.e., a new key stream data structure is generated for each packet). In particular, one embodiment of the key stream generation module **1640-1641** implements a Galois/Counter Mode (GCM) in which a counter value is incremented for each data packet and is used in combination with the secret to generate the key stream. Thus, to transmit a data packet to the IoT service **120**, the encryption engine **1661** of the IoT device **101** uses the secret and the current counter value to cause the KSGMs **1640-1641** to generate a new key stream and increment the counter value for generating the next key stream. The newly-generated key stream is then used to encrypt the data packet prior to transmission to the IoT service **120**. In one embodiment, the key stream is XORed with the data to generate the encrypted data packet. In one embodiment, the IoT device **101** transmits the counter value with the encrypted data packet to the IoT service **120**. The encryption engine **1660** on the IoT service then communicates with the KSGM **1640** which uses the received counter value and the secret to generate the key stream (which should be the same key stream because the same secret and counter value are used) and uses the generated key stream to decrypt the data packet.

In one embodiment, data packets transmitted from the IoT service **120** to the IoT device **101** are encrypted in the same manner. Specifically, a counter is incremented for each data packet and used along with the secret to generate a new key stream. The key stream is then used to encrypt the data (e.g., performing an XOR of the data and the key stream) and the encrypted data packet is transmitted with the counter value to the IoT device **101**. The encryption engine **1661** on the IoT device **101** then communicates with the KSGM **1641** which uses the counter value and the secret to generate the same key stream which is used to decrypt the data packet. Thus, in this embodiment, the encryption engines **1660-1661** use their own counter values to generate a key stream to encrypt data and use the counter values received with the encrypted data packets to generate a key stream to decrypt the data.

In one embodiment, each encryption engine **1660-1661** keeps track of the last counter value it received from the other and includes sequencing logic to detect whether a counter value is received out of sequence or if the same counter value is received more than once. If a counter value is received out of sequence, or if the same counter value is received more than once, this may indicate that a replay attack is being attempted. In response, the encryption engines **1660-1661** may disconnect from the communication channel and/or may generate a security alert.

FIG. **18** illustrates an exemplary encrypted data packet employed in one embodiment of the invention comprising a 4-byte counter value **1800**, a variable-sized encrypted data field **1801**, and a 6-byte tag **1802**. In one embodiment, the tag **1802** comprises a checksum value to validate the decrypted data (once it has been decrypted).

As mentioned, in one embodiment, the session public/private key pairs **1650-1651** exchanged between the IoT service **120** and IoT device **101** may be generated periodically and/or in response to the initiation of each new communication session.

One embodiment of the invention implements additional techniques for authenticating sessions between the IoT service **120** and IoT device **101**. In particular, in one embodiment, hierarchy of public/private key pairs is used including a master key pair, a set of factory key pairs, and a set of IoT

service key pairs, and a set of IoT device key pairs. In one embodiment, the master key pair comprises a root of trust for all of the other key pairs and is maintained in a single, highly secure location (e.g., under the control of the organization implementing the IoT systems described herein). The master private key may be used to generate signatures over (and thereby authenticate) various other key pairs such as the factory key pairs. The signatures may then be verified using the master public key. In one embodiment, each factory which manufactures IoT devices is assigned its own factory key pair which may then be used to authenticate IoT service keys and IoT device keys. For example, in one embodiment, a factory private key is used to generate a signature over IoT service public keys and IoT device public keys. These signature may then be verified using the corresponding factory public key. Note that these IoT service/device public keys are not the same as the “session” public/private keys described above with respect to FIGS. **16A-B**. The session public/private keys described above are temporary (i.e., generated for a service/device session) while the IoT service/device key pairs are permanent (i.e., generated at the factory).

With the foregoing relationships between master keys, factory keys, service/device keys in mind, one embodiment of the invention performs the following operations to provide additional layers of authentication and security between the IoT service **120** and IoT device **101**:

A. In one embodiment, the IoT service **120** initially generates a message containing the following:

1. The IoT service’s unique ID:  
The IoT service’s serial number;  
a Timestamp;  
The ID of the factory key used to sign this unique ID;  
A Class of the unique ID (i.e., a service);  
IoT service’s public key  
The signature over the unique ID.
2. The Factory Certificate including:  
A timestamp  
The ID of the master key used to sign the certificate  
The factory public key  
The signature of the Factory Certificate
3. IoT service session public key (as described above with respect to FIGS. **16A-B**)
4. IoT service session public key signature (e.g., signed with the IoT service’s private key)

B. In one embodiment, the message is sent to the IoT device on the negotiation channel (described below). The IoT device parses the message and:

1. Verifies the signature of the factory certificate (only if present in the message payload)
2. Verifies the signature of the unique ID using the key identified by the unique ID
3. Verifies the IoT service session public key signature using the IoT service’s public key from the unique ID
4. Saves the IoT service’s public key as well as the IoT service’s session public key
5. Generates the IoT device session key pair

C. The IoT device then generates a message containing the following:

1. IoT device’s unique ID  
IoT device serial number  
Timestamp  
ID of factory key used to sign this unique ID  
Class of unique ID (i.e., IoT device)  
IoT device’s public key  
Signature of unique ID
2. IoT device’s session public key

3. Signature of (IoT device session public key+IoT service session public key) signed with IoT device's key  
 D. This message is sent back to the IoT service. The IoT service parses the message and:

1. Verifies the signature of the unique ID using the factory public key
  2. Verifies the signature of the session public keys using the IoT device's public key
  3. Saves the IoT device's session public key
- E. The IoT service then generates a message containing a signature of (IoT device session public key+IoT service session public key) signed with the IoT service's key.

F. The IoT device parses the message and:

1. Verifies the signature of the session public keys using the IoT service's public key
2. Generates the key stream from the IoT device session private key and the IoT service's session public key
3. The IoT device then sends a "messaging available" message.

G. The IoT service then does the following:

1. Generates the key stream from the IoT service session private key and the IoT device's session public key
2. Creates a new message on the messaging channel which contains the following:

Generates and stores a random 2 byte value  
 Set attribute message with the boomerang attribute Id (discussed below) and the random value

H. The IoT device receives the message and:

1. Attempts to decrypt the message
2. Emits an Update with the same value on the indicated attribute Id

I. The IoT service recognizes the message payload contains a boomerang attribute update and:

1. Sets its paired state to true
2. Sends a pairing complete message on the negotiator channel

J. IoT device receives the message and sets his paired state to true

While the above techniques are described with respect to an "IoT service" and an "IoT device," the underlying principles of the invention may be implemented to establish a secure communication channel between any two devices including user client devices, servers, and Internet services.

The above techniques are highly secure because the private keys are never shared over the air (in contrast to current Bluetooth pairing techniques in which a secret is transmitted from one party to the other). An attacker listening to the entire conversation will only have the public keys, which are insufficient to generate the shared secret. These techniques also prevent a man-in-the-middle attack by exchanging signed public keys. In addition, because GCM and separate counters are used on each device, any kind of "replay attack" (where a man in the middle captures the data and sends it again) is prevented. Some embodiments also prevent replay attacks by using asymmetrical counters.

#### Techniques for Exchanging Data and Commands without Formally Pairing Devices

GATT is an acronym for the Generic Attribute Profile, and it defines the way that two Bluetooth Low Energy (BTLE) devices transfer data back and forth. It makes use of a generic data protocol called the Attribute Protocol (ATT), which is used to store Services, Characteristics and related data in a simple lookup table using 16-bit Characteristic IDs for each entry in the table. Note that while the "characteristics" are sometimes referred to as "attributes."

On Bluetooth devices, the most commonly used characteristic is the devices "name" (having characteristic ID 10752 (0x2A00)). For example, a Bluetooth device may identify other Bluetooth devices within its vicinity by reading the "Name" characteristic published by those other Bluetooth devices using GATT. Thus, Bluetooth device have the inherent ability to exchange data without formally pairing/bonding the devices (note that "paring" and "bonding" are sometimes used interchangeably; the remainder of this discussion will use the term "pairing").

One embodiment of the invention takes advantage of this capability to communicate with BTLE-enabled IoT devices without formally pairing with these devices. Pairing with each individual IoT device would extremely inefficient because of the amount of time required to pair with each device and because only one paired connection may be established at a time.

FIG. 19 illustrates one particular embodiment in which a Bluetooth (BT) device 1910 establishes a network socket abstraction with a BT communication module 1901 of an IoT device 101 without formally establishing a paired BT connection. The BT device 1910 may be included in an IoT hub 110 and/or a client device 611 such as shown in FIG. 16A. As illustrated, the BT communication module 1901 maintains a data structure containing a list of characteristic IDs, names associated with those characteristic IDs and values for those characteristic IDs. The value for each characteristic may be stored within a 20-byte buffer identified by the characteristic ID in accordance with the current BT standard. However, the underlying principles of the invention are not limited to any particular buffer size.

In the example in FIG. 19, the "Name" characteristic is a BT-defined characteristic which is assigned a specific value of "IoT Device 14." One embodiment of the invention specifies a first set of additional characteristics to be used for negotiating a secure communication channel with the BT device 1910 and a second set of additional characteristics to be used for encrypted communication with the BT device 1910. In particular, a "negotiation write" characteristic, identified by characteristic ID <65532> in the illustrated example, may be used to transmit outgoing negotiation messages and the "negotiation read" characteristic, identified by characteristic ID <65533> may be used to receive incoming negotiation messages. The "negotiation messages" may include messages used by the BT device 1910 and the BT communication module 1901 to establish a secure communication channel as described herein. By way of example, in FIG. 17, the IoT device 101 may receive the IoT service session public key 1701 via the "negotiation read" characteristic <65533>. The key 1701 may be transmitted from the IoT service 120 to a BTLE-enabled IoT hub 110 or client device 611 which may then use GATT to write the key 1701 to the negotiation read value buffer identified by characteristic ID <65533>. IoT device application logic 1902 may then read the key 1701 from the value buffer identified by characteristic ID <65533> and process it as described above (e.g., using it to generate a secret and using the secret to generate a key stream, etc).

If the key 1701 is greater than 20 bytes (the maximum buffer size in some current implementations), then it may be written in 20-byte portions. For example, the first 20 bytes may be written by the BT communication module 1903 to characteristic ID <65533> and read by the IoT device application logic 1902, which may then write an acknowledgement message to the negotiation write value buffer identified by characteristic ID <65532>. Using GATT, the BT communication module 1903 may read this acknowl-

edgement from characteristic ID <65532> and responsively write the next 20 bytes of the key **1701** to the negotiation read value buffer identified by characteristic ID <65533>. In this manner, a network socket abstraction defined by characteristic IDs <65532> and <65533> is established for exchanging negotiation messages used to establish a secure communication channel.

In one embodiment, once the secure communication channel is established, a second network socket abstraction is established using characteristic ID <65534> (for transmitting encrypted data packets from IoT device **101**) and characteristic ID <65533> (for receiving encrypted data packets by IoT device). That is, when BT communication module **1903** has an encrypted data packet to transmit (e.g., such as encrypted message **1603** in FIG. **16A**), it starts writing the encrypted data packet, 20 bytes at a time, using the message read value buffer identified by characteristic ID <65533>. The IoT device application logic **1902** will then read the encrypted data packet, 20 bytes at a time, from the read value buffer, sending acknowledgement messages to the BT communication module **1903** as needed via the write value buffer identified by characteristic ID <65532>.

In one embodiment, the commands of GET, SET, and UPDATE described below are used to exchange data and commands between the two BT communication modules **1901** and **1903**. For example, the BT communication module **1903** may send a packet identifying characteristic ID <65533> and containing the SET command to write into the value field/buffer identified by characteristic ID <65533> which may then be read by the IoT device application logic **1902**. To retrieve data from the IoT device **101**, the BT communication module **1903** may transmit a GET command directed to the value field/buffer identified by characteristic ID <65534>. In response to the GET command, the BT communication module **1901** may transmit an UPDATE packet to the BT communication module **1903** containing the data from the value field/buffer identified by characteristic ID <65534>. In addition, UPDATE packets may be transmitted automatically, in response to changes in a particular attribute on the IoT device **101**. For example, if the IoT device is associated with a lighting system and the user turns on the lights, then an UPDATE packet may be sent to reflect the change to the on/off attribute associated with the lighting application.

FIG. **20** illustrates exemplary packet formats used for GET, SET, and UPDATE in accordance with one embodiment of the invention. In one embodiment, these packets are transmitted over the message write <65534> and message read <65533> channels following negotiation. In the GET packet **2001**, a first 1-byte field includes a value (0X10) which identifies the packet as a GET packet. A second 1-byte field includes a request ID, which uniquely identifies the current GET command (i.e., identifies the current transaction with which the GET command is associated). For example, each instance of a GET command transmitted from a service or device may be assigned a different request ID. This may be done, for example, by incrementing a counter and using the counter value as the request ID. However, the underlying principles of the invention are not limited to any particular manner for setting the request ID.

A 2-byte attribute ID identifies the application-specific attribute to which the packet is directed. For example, if the GET command is being sent to IoT device **101** illustrated in FIG. **19**, the attribute ID may be used to identify the particular application-specific value being requested. Returning to the above example, the GET command may be directed to an application-specific attribute ID such as power

status of a lighting system, which comprises a value identifying whether the lights are powered on or off (e.g., 1=on, 0=off). If the IoT device **101** is a security apparatus associated with a door, then the value field may identify the current status of the door (e.g., 1=opened, 0=closed). In response to the GET command, a response may be transmitting containing the current value identified by the attribute ID.

The SET packet **2002** and UPDATE packet **2003** illustrated in FIG. **20** also include a first 1-byte field identifying the type of packet (i.e., SET and UPDATE), a second 1-byte field containing a request ID, and a 2-byte attribute ID field identifying an application-defined attribute. In addition, the SET packet includes a 2-byte length value identifying the length of data contained in an n-byte value data field. The value data field may include a command to be executed on the IoT device and/or configuration data to configure the operation of the IoT device in some manner (e.g., to set a desired parameter, to power down the IoT device, etc). For example, if the IoT device **101** controls the speed of a fan, the value field may reflect the current fan speed.

The UPDATE packet **2003** may be transmitted to provide an update of the results of the SET command. The UPDATE packet **2003** includes a 2-byte length value field to identify the length of the n-byte value data field which may include data related to the results of the SET command. In addition, a 1-byte update state field may identify the current state of the variable being updated. For example, if the SET command attempted to turn off a light controlled by the IoT device, the update state field may indicate whether the light was successfully turned off.

FIG. **21** illustrates an exemplary sequence of transactions between the IoT service **120** and an IoT device **101** involving the SET and UPDATE commands. Intermediary devices such as the IoT hub and the user's mobile device are not shown to avoid obscuring the underlying principles of the invention. At **2101**, the SET command **2101** is transmitted from the IoT service to the IoT device **101** and received by the BT communication module **1901** which responsively updates the GATT value buffer identified by the characteristic ID at **2102**. The SET command is read from the value buffer by the low power microcontroller (MCU) **200** at **2103** (or by program code being executed on the low power MCU such as IoT device application logic **1902** shown in FIG. **19**). At **2104**, the MCU **200** or program code performs an operation in response to the SET command. For example, the SET command may include an attribute ID specifying a new configuration parameter such as a new temperature or may include a state value such as on/off (to cause the IoT device to enter into an "on" or a low power state). Thus, at **2104**, the new value is set in the IoT device and an UPDATE command is returned at **2105** and the actual value is updated in a GATT value field at **2106**. In some cases, the actual value will be equal to the desired value. In other cases, the updated value may be different (i.e., because it may take time for the IoT device **101** to update certain types of values). Finally, at **2107**, the UPDATE command is transmitted back to the IoT service **120** containing the actual value from the GATT value field.

FIG. **22** illustrates a method for implementing a secure communication channel between an IoT service and an IoT device in accordance with one embodiment of the invention. The method may be implemented within the context of the network architectures described above but is not limited to any specific architecture.

At **2201**, the IoT service creates an encrypted channel to communicate with the IoT hub using elliptic curve digital

signature algorithm (ECDSA) certificates. At **2202**, the IoT service encrypts data/commands in IoT device packets using the a session secret to create an encrypted device packet. As mentioned above, the session secret may be independently generated by the IoT device and the IoT service. At **2203**, the IoT service transmits the encrypted device packet to the IoT hub over the encrypted channel. At **2204**, without decrypting, the IoT hub passes the encrypted device packet to the IoT device. At **22-5**, the IoT device uses the session secret to decrypt the encrypted device packet. As mentioned, in one embodiment this may be accomplished by using the secret and a counter value (provided with the encrypted device packet) to generate a key stream and then using the key stream to decrypt the packet. At **2206**, the IoT device then extracts and processes the data and/or commands contained within the device packet.

Thus, using the above techniques, bi-directional, secure network socket abstractions may be established between two BT-enabled devices without formally pairing the BT devices using standard pairing techniques. While these techniques are described above with respect to an IoT device **101** communicating with an IoT service **120**, the underlying principles of the invention may be implemented to negotiate and establish a secure communication channel between any two BT-enabled devices.

FIGS. **23A-C** illustrate a detailed method for pairing devices in accordance with one embodiment of the invention. The method may be implemented within the context of the system architectures described above, but is not limited to any specific system architectures.

At **2301**, the IoT Service creates a packet containing serial number and public key of the IoT Service. At **2302**, the IoT Service signs the packet using the factory private key. At **2303**, the IoT Service sends the packet over an encrypted channel to the IoT hub and at **2304** the IoT hub forwards the packet to IoT device over an unencrypted channel. At **2305**, the IoT device verifies the signature of packet and, at **2306**, the IoT device generates a packet containing the serial number and public key of the IoT Device. At **2307**, the IoT device signs the packet using the factory private key and at **2308**, the IoT device sends the packet over the unencrypted channel to the IoT hub.

At **2309**, the IoT hub forwards the packet to the IoT service over an encrypted channel and at **2310**, the IoT Service verifies the signature of the packet. At **2311**, the IoT Service generates a session key pair, and at **2312** the IoT Service generates a packet containing the session public key. The IoT Service then signs the packet with IoT Service private key at **2313** and, at **2314**, the IoT Service sends the packet to the IoT hub over the encrypted channel.

Turning to FIG. **23B**, the IoT hub forwards the packet to the IoT device over the unencrypted channel at **2315** and, at **2316**, the IoT device verifies the signature of packet. At **2317** the IoT device generates session key pair (e.g., using the techniques described above), and, at **2318**, an IoT device packet is generated containing the IoT device session public key. At **2319**, the IoT device signs the IoT device packet with IoT device private key. At **2320**, the IoT device sends the packet to the IoT hub over the unencrypted channel and, at **2321**, the IoT hub forwards the packet to the IoT service over an encrypted channel.

At **2322**, the IoT service verifies the signature of the packet (e.g., using the IoT device public key) and, at **2323**, the IoT service uses the IoT service private key and the IoT device public key to generate the session secret (as described in detail above). At **2324**, the IoT device uses the IoT device private key and IoT service public key to generate the

session secret (again, as described above) and, at **2325**, the IoT device generates a random number and encrypts it using the session secret. At **2326**, the IoT service sends the encrypted packet to IoT hub over the encrypted channel. At **2327**, the IoT hub forwards the encrypted packet to the IoT device over the unencrypted channel. At **2328**, the IoT device decrypts the packet using the session secret.

Turning to FIG. **23C**, the IoT device re-encrypts the packet using the session secret at **2329** and, at **2330**, the IoT device sends the encrypted packet to the IoT hub over the unencrypted channel. At **2331**, the IoT hub forwards the encrypted packet to the IoT service over the encrypted channel. The IoT service decrypts the packet using the session secret at **2332**. At **2333** the IoT service verifies that the random number matches the random number it sent. The IoT service then sends a packet indicating that pairing is complete at **2334** and all subsequent messages are encrypted using the session secret at **2335**.

### System and Method for Virtual Internet of Things (IoT) Devices and Hubs

In one embodiment, the IoT system supports the virtualization of IoT devices of different IoT services and integrates information related to these “external” IoT devices to provide the end user with a single location from which the access all IoT device information. By way of example, the user may have a previously installed smart thermostat such as a Nest® thermostat, which is designed to communicate with a different IoT system, potentially using a different set of protocols. In one embodiment of the invention, the IoT service provides the user with access to both the IoT devices designed to communicate with the IoT service (e.g., via the IoT hub as described above) and with IoT devices designed to communicate with other IoT services. This may be accomplished by accessing an application programming interface (API) exposed by the external cloud services to both control the external IoT devices and collect data generated by the IoT devices. In addition, one embodiment virtualizes the external IoT devices so that they appear within a single, integrated graphical user interface on the user’s mobile device or computer (e.g., via a single mobile app in which all devices, virtual and non-virtual, are arranged together). Users may then control and retrieve data from the IoT devices in the same manner as they control and retrieve data from non-virtual IoT devices.

In addition, one embodiment of the invention provides the user with the ability to configure an IoT system without the use of an IoT hub—or using a “virtual” IoT hub as described herein. This is accomplished in one embodiment by providing IoT device access to the IoT service via the user’s mobile device or other computing device. For example, the user’s mobile device may establish a connection with the IoT service via a cellular or WiFi connection as previously described, and may also establish a Bluetooth or WiFi connection with each of the IoT devices. In one embodiment, the IoT devices may periodically connect with the user’s mobile device and/or may only connect when they have data to transmit. In this embodiment, an IoT device may establish a connection, receive commands from the user’s mobile device, transmit data to the user’s mobile device, and then disconnect. The user’s mobile device thus acts as a temporary repository for commands and data transmitted between the IoT service and the IoT device.

As illustrated in FIG. **24**, an architecture on which the embodiments of the invention may be implemented may include an IoT hub **2405** communicatively coupled to a

plurality of IoT devices **101-103** and also communicatively coupled to an IoT cloud service **2420** via the Internet **2422** (e.g., in a similar manner as described above). A user may control and access information from the IoT devices **101-103** via a user device **2410** on which an IoT app or application is installed (e.g., an app/application designed by the IoT cloud service **2420**). In one embodiment, access to the IoT devices **101-103** is provided via the IoT cloud service **2420**. For example, to retrieve information or control one of the IoT devices, the user opens the app on the IoT device **2410**, which connects the user to the IoT cloud service **2420**. If the user successfully authenticates with the IoT cloud service **2420** (e.g., via a user name or password), the IoT cloud service **2420** establishes a connection with one or more of the IoT devices **101-103** via the IoT hub **2405**. Various different security techniques such as described above (e.g., using digital signatures, encryption, etc) may be employed to protect the communication between the IoT devices **101-103**, the IoT cloud service **2420** and the user device **2410**.

In one embodiment, IoT device management logic **2415** on the IoT service **2420** collects data from the IoT devices **101-103** and compiles the data within an IoT device database **2430**. For example, the IoT device management logic **2415** may periodically query each of the IoT devices **101-103** to confirm that each of the IoT devices is operational and retrieve any data which has been generated by the IoT devices **101-103**. For example, if IoT device **101** is a smart thermostat, the IoT device management logic **2415** may collect the latest temperature readings and any other pertinent data (e.g., motion sensor data, humidity data, etc). In addition, some IoT devices **101-103** may actively push data to the IoT device management logic **2415** (e.g., when a threshold is reached, when a security alarm is triggered, etc) which then stores the data within the IoT device database **2430**.

In addition, the IoT device management logic **2415** may transmit commands to each of the IoT devices **101-103**, either automatically or in response to input from the user via the IoT app on the mobile device **2410**. For example, if IoT device **101** is a thermostat, the user may control the temperature via the IoT app on the user device **2410** which will transmit the new temperature reading to the IoT service **2420**. The IoT device management logic **2415** on the IoT service **2420** will then transmit a command to change the temperature to the IoT device **101** and may also update the IoT device database **2430** to reflect the new temperature. In this manner, the IoT device database **2430** may contain the current status of the various IoT devices **101-103** which may be readily provided to the user's mobile device **2410** upon request. Of course, the above examples are provided merely for the purpose of explanation. The underlying principles of the invention are not limited to any particular types of IoT devices.

In one embodiment, in addition to collecting data and sending commands to IoT devices **101-103** provided by the IoT service **2420** (or partners of the IoT service **2420**), the IoT device management logic **2415** establishes a connection with one or more external IoT cloud services **2440**. This may be accomplished, for example, by accessing a public or private application programming interface (API) **2445** exposed by the IoT cloud service **2440**. In one embodiment, the API **2445** comprises logic for authenticating connections established over the Internet **2422** from remote hosts such as the IoT device management logic **2415**. Once authenticated, the API **2445** provides access to a set or functions for transmitting commands to one or more external IoT devices

**2401-2402** which are managed as "virtual" IoT devices by the IoT device management logic **2415**. In one embodiment, the API **2445** provides access via IoT device management logic **2450** executed by the external IoT cloud service **2440** which may manage its own set of IoT devices **2401-2402** using its own set of commands and data structures and storing data related to its IoT devices **2401-2402** within its own IoT device database **2455**. In one embodiment, the API **2445** includes logic for translating between the commands and data formats used by the IoT device management logic **2450** on the external IoT cloud service **2440** and the IoT device management logic **2415** on the IoT cloud service. Of course, translation is not required if the commands and data formats used by the IoT device management logic **2415** on the IoT cloud service **2420** are the same as those used by the IoT device management logic **2450** on the external IoT cloud service.

Regardless of how the API is implemented, in one embodiment, the IoT device management logic **2415** utilizes the API **2445** to retrieve information provided from the external IoT devices **2401-2402** and to send commands to control the external IoT devices **2401-2402**. In one embodiment, the IoT device management logic **2415** creates and manages records in the IoT device database **2430** for each of the external IoT devices **2401-2402** (e.g., containing information received from or related to the external IoT devices **2401-2402**). In this manner, the IoT device management logic **2415** "virtualizes" the external IoT devices **2401-2402**, so that they may be accessed by the same app or application installed on the user's mobile device **2410**.

FIG. **25** illustrates an exemplary GUI in which a virtual IoT device graphic **2502** is displayed along with other non-virtual IoT device graphics **2501**, **2503-2504**. The virtual IoT device graphic **2502**, for example, may represent one of the external IoT devices **2401-2402** while the non-virtual IoT device graphics **2501**, **2503-2504** may represent IoT devices **101-103** in FIG. **24**. As illustrated, the same set of device status information, data, and/or control functions may be made available for the virtual IoT device **2502** as for the non-virtual IoT devices **2501**, **2503-2504** (or a subset of functions depending on the functions provided via the API **2445**). This status information, data, and/or control functions may be read from records in the IoT device database **2430**.

In one embodiment, the user device **2410** establishes a connection with the IoT cloud service **2420** and the IoT device management logic **2415** establishes a connection with the external IoT cloud service via the API **2445**. The user may initially provide the IoT device management logic **2415** with the credentials needed to establish the connection with the API **2445** (e.g., a user name and password). Once the connection has been established, the user may control or retrieve information from any of the IoT devices **2401-2402** managed directly by the external IoT cloud service **2440**.

In one embodiment of the invention, the end user is provided with the ability to capture a picture of barcodes or QR codes associated with the external IoT devices **2401-2402** with the user device **2410** to virtualize the external IoT devices **2401-2402** in the system (e.g., as described above with respect to the primary IoT devices **101-103**). The barcodes may be printed either on the devices themselves or on paperwork or a container provided with the devices. In one embodiment, upon capturing the barcode/QR code, the user device **2410** transmits the barcode/QR code data to the IoT cloud service **2420** and the IoT device management registers the IoT devices **2401-2402** in the IoT device database **2430** and communicates with the API **2445** to

establish a connection with the IoT devices **2401-2402** as described above. In this manner, the user can easily integrate IoT devices **2401-2402** into the system, including those from external IoT cloud services **2440**. Once registered in this manner, the virtual IoT devices will appear within the GUI of the user device **2410** as described above (see, e.g., FIG. **25** and associate text).

FIG. **26** illustrates an embodiment of the invention which operates with a “virtual” IoT hub. For example, the user may not have a physical IoT hub but the techniques described herein may be implemented to reproduce the functionality of the IoT hub by “virtualizing” the IoT hub **2600** in the IoT cloud service **2420**. In this example the user’s mobile device **2410** communicates directly to the IoT devices **101-103** over, for example, Bluetooth (e.g., BTLE), Wifi, or other local wireless connection. In one embodiment, new IoT devices **101-103** may be added to the system using the same techniques described above (e.g., scanning a barcode or QR code to register the devices with the system). In this case, the user device **2410** receives the QR code or barcode data from a new IoT device **101** and passes the data to the IoT cloud service **2420**. The IoT cloud service **2420** then generates encrypted messages using the QR code data (as described above) and sends the encrypted messages back to the user’s device **2410**, which forwards the encrypted messages to the IoT device **101**. All of the same types of messages described above may be passed between the IoT cloud service **2420** and the IoT devices **101-103** (e.g., security, OTA support, diagnostics, device telemetry, etc.) using the user device **2410** as an intermediary. Consequently, as long as a user is at home or in the office (or in any location where the IoT devices **101-103** reside), the user may still control the IoT devices **101-103** and setup, security, and device updates still work the same manner.

In one embodiment, the user device **2410** does not maintain a continuous connection with each of the IoT devices **101-103**. Rather, it may periodically connect, exchange data, and then disconnect from each IoT device **101-103**. In this manner, the user device **2410** may act as a central hub for all communication between the IoT cloud service **2420** and a variety of different IoT devices. In addition, it allows for multiple different user devices **2410** to access each of the IoT devices **101-103**. For example, if there are two or more individuals with devices in the user’s home, each of these devices may access the IoT devices **101-103** at different times to provide communication with the IoT service **2420**. Note that this is distinguishable from the standard Bluetooth pairing model where the phone keeps the connection open and prevents other devices from being able to connect.

A method in accordance with one embodiment of the invention is illustrated in FIG. **27**. The method may be implemented within the context of the system architectures described above but is not limited to any particular system architecture.

At **2701**, the user initiates registration of a new external IoT device. By way of example, the user may have purchased an IoT device from a service other than the user’s normal IoT service (e.g., such as Nest® smart thermostat). As mentioned above, the app on the user’s mobile device may instruct the user to snap a picture of the barcode/QR code associated with the new device which the user’s device transmits to the IoT service. In response, at **2702**, the IoT service authenticates and/or establishes a communication channel with the external IoT cloud service. As mentioned above, the communication may be accomplished via an API exposed by the external IoT cloud service. Once the external IoT device has been registered, at **2703**, it may be displayed

within the GUI of the user app and a record for the new IoT device may be stored within an IoT device database on the IoT cloud service.

At **2704**, the user may generate commands to control the external IoT device via the user app. The commands are passed to the external IoT cloud service API via the IoT cloud service. As mentioned, in some embodiments, the API may translate the commands into native commands directly interpretable by the external IoT device. In addition, at **2705**, any information generated by the IoT device may be sent from the external IoT cloud service to the IoT cloud service via the API. Once again, the API may translate the information as needed for use by the IoT cloud service. The IoT cloud service then transmits the information to the app where it may be displayed on the user device.

FIG. **28** illustrates another method for virtual device pairing in accordance with one embodiment of the invention. The method may be implemented within the context of the system architectures described above, but is not limited to any particular system architecture.

At **2801**, the user captures the new QR code or barcode associated with a new IoT device. In one embodiment, the new IoT device is one designed by the operator of the external IoT cloud service **2440**. At **2802**, the user is prompted for credentials for the virtual device account (e.g., a user name and password for the external IoT cloud service **2440**). At **2803**, the IoT cloud service **2420** authenticates with the virtual device account using the provided credentials. Finally, at **2804**, the IoT cloud service **2440** creates a virtual device representation that appears within the user’s GUI (e.g., as shown in FIG. **25**).

Embodiments of the invention may include various steps, which have been described above. The steps may be embodied in machine-executable instructions which may be used to cause a general-purpose or special-purpose processor to perform the steps. Alternatively, these steps may be performed by specific hardware components that contain hardwired logic for performing the steps, or by any combination of programmed computer components and custom hardware components.

As described herein, instructions may refer to specific configurations of hardware such as application specific integrated circuits (ASICs) configured to perform certain operations or having a predetermined functionality or software instructions stored in memory embodied in a non-transitory computer readable medium. Thus, the techniques shown in the figures can be implemented using code and data stored and executed on one or more electronic devices (e.g., an end station, a network element, etc.). Such electronic devices store and communicate (internally and/or with other electronic devices over a network) code and data using computer machine-readable media, such as non-transitory computer machine-readable storage media (e.g., magnetic disks; optical disks; random access memory; read only memory; flash memory devices; phase-change memory) and transitory computer machine-readable communication media (e.g., electrical, optical, acoustical or other form of propagated signals—such as carrier waves, infrared signals, digital signals, etc.). In addition, such electronic devices typically include a set of one or more processors coupled to one or more other components, such as one or more storage devices (non-transitory machine-readable storage media), user input/output devices (e.g., a keyboard, a touchscreen, and/or a display), and network connections. The coupling of the set of processors and other components is typically through one or more busses and bridges (also termed as bus controllers). The storage device and signals carrying the

35

network traffic respectively represent one or more machine-readable storage media and machine-readable communication media. Thus, the storage device of a given electronic device typically stores code and/or data for execution on the set of one or more processors of that electronic device. Of course, one or more parts of an embodiment of the invention may be implemented using different combinations of software, firmware, and/or hardware.

Throughout this detailed description, for the purposes of explanation, numerous specific details were set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the invention may be practiced without some of these specific details. In certain instances, well known structures and functions were not described in elaborate detail in order to avoid obscuring the subject matter of the present invention. Accordingly, the scope and spirit of the invention should be judged in terms of the claims which follow.

What is claimed is:

1. A system for virtualizing an IoT hub comprising:
  - a plurality of IoT devices to receive commands and data from an IoT service and to provide data to the IoT service in accordance with functions performed by each of the IoT devices;
  - at least one wireless user device to establish a communication channel with the IoT service and to establish periodic local wireless connections with each of the IoT devices to emulate a connection with an IoT hub, wherein upon establishing the wireless connection between each IoT device and the wireless user device, the wireless user device provides connectivity to the IoT service on behalf of each IoT device, providing data and commands generated from the IoT service to the IoT device, and providing data generated by the IoT device to the IoT service, wherein the at least one wireless user device is configured to automatically establish a first temporary wireless connection to a first IoT device exchange data/commands with the first IoT device, disconnect the first temporary wireless connection, and then establish a second temporary wireless connection to a second IoT device, exchange data/commands with the second IoT device, and then disconnect the second temporary wireless connection.
2. The system as in claim 1 wherein the wireless user device is configured to automatically connect, exchange data/commands and disconnect from N different IoT devices.
3. The system as in claim 2 wherein the wireless user device is configured to connect with each of the IoT devices using a Bluetooth protocol.
4. The system as in claim 3 wherein the wireless user device is configured to open the communication channel with the IoT service using a WiFi or cellular data protocol.
5. The system as in claim 1 wherein to register a new IoT device with the IoT service, the wireless user device captures a barcode or QR code associated with the new IoT device, transmits QR code or barcode data to the IoT service.
6. The system as in claim 5 wherein the IoT service uses the QR code or barcode data to register the new IoT device and subsequently uses the QR code or barcode data to encrypt or sign messages passed to the new IoT device via the wireless user device.
7. A method for virtualizing an IoT hub comprising:
  - receiving, by a plurality of IoT devices, commands and data from an IoT service;
  - providing data to the IoT service in accordance with functions performed by each of the IoT devices;

36

- establishing, by at least one wireless user device, a communication channel with the IoT service;
  - establishing periodic local wireless connections with each of the IoT devices to emulate a connection with an IoT hub, wherein upon establishing the wireless connection between each IoT device and the wireless user device, the wireless user device provides connectivity to the IoT service on behalf of each IoT device, providing data and commands generated from the IoT service to the IoT device, and providing data generated by the IoT device to the IoT service;
  - automatically establishing a first temporary wireless connection to a first IoT device exchange data/commands with the first IoT device;
  - disconnecting the first temporary wireless connection;
  - establishing a second temporary wireless connection to a second IoT device, exchange data/commands with the second IoT device; and
  - disconnecting the second temporary wireless connection.
8. The method as in claim 7 wherein the wireless user device is configured to automatically connect, exchange data/commands and disconnect from N different IoT devices.
  9. The method as in claim 8 wherein the wireless user device is configured to connect with each of the IoT devices using a Bluetooth protocol.
  10. The method as in claim 9 wherein the wireless user device is configured to open the communication channel with the IoT service using a WiFi or cellular data protocol.
  11. The method as in claim 7, further comprising:
    - capturing a barcode or QR code associated with the new IoT device to register a new IoT device with the IoT service; and
    - transmitting QR code or barcode data to the IoT service.
  12. The system as in claim 11 wherein the IoT service uses the QR code or barcode data to register the new IoT device and subsequently uses the QR code or barcode data to encrypt or sign messages passed to the new IoT device via the wireless user device.
  13. A non-transitory computer readable storage medium including instructions stored thereon for virtualizing an IoT hub which, when executed by one or more processors, cause the one or more processors to:
    - receive, by a plurality of IoT devices, commands and data from an IoT service;
    - provide data to the IoT service in accordance with functions performed by each of the IoT devices;
    - establish, by at least one wireless user device, a communication channel with the IoT service;
    - establish periodic local wireless connections with each of the IoT devices to emulate a connection with an IoT hub, wherein upon establishing the wireless connection between each IoT device and the wireless user device, the wireless user device provides connectivity to the IoT service on behalf of each IoT device, providing data and commands generated from the IoT service to the IoT device, and providing data generated by the IoT device to the IoT service;
    - automatically establish a first temporary wireless connection to a first IoT device exchange data/commands with the first IoT device;
    - disconnect the first temporary wireless connection;
    - establish a second temporary wireless connection to a second IoT device, exchange data/commands with the second IoT device; and
    - disconnect the second temporary wireless connection.

14. The non-transitory computer readable storage medium as in claim 13 wherein the wireless user device is configured to automatically connect, exchange data/commands and disconnect from N different IoT devices.

15. The non-transitory computer readable storage medium as in claim 14 wherein the wireless user device is configured to connect with each of the IoT devices using a Bluetooth protocol.

16. The non-transitory computer readable storage medium as in claim 15 wherein the wireless user device is configured to open the communication channel with the IoT service using a WiFi or cellular data protocol.

17. The non-transitory computer readable storage medium as in claim 13, wherein the instructions, when executed, further cause the one or more processors to:  
capture a barcode or QR code associated with the new IoT device to register a new IoT device with the IoT service; and  
transmit QR code or barcode data to the IoT service, wherein the IoT service uses the QR code or barcode data to register the new IoT device and subsequently uses the QR code or barcode data to encrypt or sign messages passed to the new IoT device via the wireless user device.

\* \* \* \* \*