



US006354694B1

(12) **United States Patent**  
**Weber et al.**

(10) **Patent No.:** **US 6,354,694 B1**  
(45) **Date of Patent:** **\*Mar. 12, 2002**

(54) **METHOD AND APPARATUS FOR  
IMPROVED INK-DROP DISTRIBUTION IN  
INK-JET PRINTING**

(75) Inventors: **Timothy L. Weber**, Corvallis; **John P. Harmon**, Albany, both of OR (US); **S. Dana Seccombe**, Foster City, CA (US); **Colin C. Davis**, Corvallis, OR (US); **Paul J. McClellan**, Salem, OR (US); **David J. Waller**, Corvallis, OR (US)

(73) Assignee: **Hewlett-Packard Company**, Palo Alto, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/252,737**

(22) Filed: **Feb. 19, 1999**

**Related U.S. Application Data**

(63) Continuation of application No. 08/812,385, filed on Mar. 5, 1997.

(51) Int. Cl.<sup>7</sup> ..... **B41J 2/14; B41J 2/16**

(52) U.S. Cl. .... **347/48; 347/47**

(58) Field of Search ..... **347/48, 40, 47**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,396,924 A	8/1983	Rosenstock .....	347/40
4,468,679 A	8/1984	Suga et al. ....	347/10
4,550,326 A	10/1985	Allen et al. ....	347/44
4,621,273 A	11/1986	Anderson .....	347/40
4,631,548 A	12/1986	Milbrandt .....	347/43
4,914,451 A	4/1990	Morris et al. ....	347/105
4,967,203 A	10/1990	Doan et al. ....	347/41
4,967,208 A	10/1990	Childers .....	347/41

4,999,646 A	3/1991	Trask .....	347/41
5,196,056 A	3/1993	Prasad .....	106/15.05
5,258,774 A	11/1993	Rogers .....	347/40
5,422,666 A	6/1995	Koyama .....	347/41
5,485,180 A	1/1996	Askeland et al. ....	347/15
5,583,550 A	12/1996	Hickman et al. ....	347/41
5,731,827 A	3/1998	Mantell et al. ....	347/40
5,764,256 A	6/1998	Zhang .....	347/71

**FOREIGN PATENT DOCUMENTS**

EP	0517519 A2	12/1992	
EP	0627314 A2	12/1994	
EP	0730961 A1	9/1996	
EP	0767061	4/1997	..... B41J/2/14

**OTHER PUBLICATIONS**

“Bubble Ink-Jet Technology With Improved Performance”, Enrico Manini, Olivetti, Ivea, Italy Article, Chapter 4, Thermal Ink Jet, pp. 177–178.

Output Hardcopy Devices, Chapter 13, by W. J. Lloyd and H. T. Taub, (Ed. R.C. Dubeck and S. Sherr, Academic Press, San Diego, 1988).

J. Borch, “Plain Paper Choices for Ink Jet Printing”, Ink and Substrates, Chapter 5, pp 288–292.


Primary Examiner—Thinh Nguyen


(57) **ABSTRACT**

A method and apparatus for improving ink-jet print quality uses a print head having an array using a plurality of nozzles in sets in each drop generator mechanism. Where a conventional ink-jet pen fires a single droplet of ink at a pixel per firing cycle, the present invention fires a plurality of droplets at different subdivisions of pixels. The particular array design may vary from ink-to-ink or pen-to-pen. Each drop generator of a print head array includes a plurality of nozzles wherein each of the nozzles has an exit orifice with an areal dimension, and produces an ink droplet that produces a dot on adjacent print media wherein the dot has an areal dimension, less than the areal dimension of a pixel to be printed. Dots are printed in a pattern for each pixel wherein print quality is achieved that approximates a higher resolution print made by conventional ink-jet methodologies.

**25 Claims, 11 Drawing Sheets**

**(1 of 11 Drawing Sheet(s) Filed in Color)**








Fig. 2




Fig. 2A

**FIG. 4B**




FIG. 5




Fig. 6a




Fig. 6b




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B





FIG. 9C



10x magnification






FIG.11A




FIG.11B




FIG.12A




FIG.12B




FIG.12C




FIG.12D




FIG.12E




FIG.13

1

## METHOD AND APPARATUS FOR IMPROVED INK-DROP DISTRIBUTION IN INK-JET PRINTING

### CROSS REFERENCE TO RELATED APPLICATION

This is a continuation of copending application Ser. No. 08/812,385 filed on Mar. 5, 1997.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates generally to methods and apparatus for reproducing images and alphanumeric characters, more particularly to ink-jet hard copy apparatus and, more specifically to a thermal ink-jet, multi-orifice drop generator, print head construct and its method of operation.

#### 2. Description of Related Art

The art of ink-jet hard copy technology is relatively well developed. Commercial products such as computer printers, graphics plotters, copiers, and facsimile machines employ ink-jet technology for producing hard copy. The basics of this technology are disclosed, for example, in various articles in the *Hewlett-Packard Journal*, Vol. 36, No. 5 (May 1985), Vol. 39, No. 4 (August 1988), Vol. 39, No. 5 (October 1988), Vol. 43, No. 4 (August 1992), Vol. 43, No. 6 (December 1992) and, Vol. 45, No. 1 (February 1994) editions. Ink-jet devices are also described by W. J. Lloyd and H. T. Taub in *Output Hardcopy Devices*, chapter 13 (Ed. R. C. Durbeck and S. Sherr, Academic Press, San Diego, 1988).

It has been estimated that the human visual system can distinguish ten million colors. Printing systems use a small subset of colors, yet can create acceptable reproductions of original images. Generally speaking, this is achieved by mixing the primary colors (red, blue green-additive; or cyan, magenta, yellow-subtractive) in sufficiently small quanta and exploiting tristimulus response idiosyncrasies of the human visual system. Effective use of these small quanta can be achieved in dot matrix color printing by varying the density or area fill, or both, to recreate each color or a reasonable semblance thereof in the image.

The quality of a printed image has many aspects. When the printed matter is an image that is a reproduction of an original image (that is to say, a photograph or graphic design rather than merely text printing), the goal of an imaging system is to accurately reproduce the appearance of the original. To achieve this goal, the system must accurately reproduce both the perceived colors (hues) and the perceived relative luminance ratios (tones) of the original. Human visual perception quickly adjusts to wide variations in luminance levels, from dark shadows to bright highlights. Between these extremes, perception tends toward an expectation of smooth transitions in luminance. However, imaging systems have yet to achieve complete faithful reproduction of the full dynamic range and perception continuity of the human visual system. While the goal is to achieve true photographic image quality reproduction, imaging systems' dynamic range printing capabilities are limited by the sensitivity and saturation level limitations inherent to the recording mechanism. The effective dynamic range can be extended somewhat by utilizing a non-linear conversion that allows some shadow and highlight detail to remain.

In ink-jet technology, which uses dot matrix manipulation to form both images and alphanumeric characters, the colors and tone of a printed image are modulated by the presence or absence of drops of ink deposited on the print medium at

2

each target picture element (known as "pixels") of a superimposed rectangular grid overlay of the image. The luminance continuity—tonal transitions within the recorded image—is especially affected by the inherent quantization effects of using ink droplets and dot matrix imaging. These effects can appear as contouring in printed images where the original image had smooth transitions. Moreover the imaging system can introduce random or systematic luminance fluctuations (graininess—the visual recognition of individual dots with the naked eye).

Perceived quantization effects which detract from print quality can be reduced by decreasing the physical quantization levels in the imaging system and by utilizing techniques that exploit the psycho-physical characteristics of the human visual system to minimize the human perception of the quantization effects. It has been estimated that the unaided human visual system will perceive individual dots until they have been reduced to less than or equal to approximately twenty to twenty-five microns in diameter in the printed image. Therefore, undesirable quantization effects of the dot matrix printing method are reduced in the current state of the art by decreasing the size of each drop and printing at a high resolution; that is, a 1200 dots per inch ("dpi") printed image looks better to the eye than a 600 dpi image which in turn improves upon 300 dpi, etc. Additionally, undesired quantization effect can be reduced by utilizing more pen colors with varying densities of color (e.g., two cyan ink print cartridges, each containing a different dye load (the ratio of dye to solvent in the chemical composition of the ink) or containing different types of chemical colorants, dye-based or pigment-based).

To reduce quantization effects, print quality also can be enhanced by methods of saturating each pixel with large volumes of dye by using large drops, a high dye-load ink formula, or by firing multiple drops of the same color or color formulation at each pixel. Such methods are discussed in U.S. Pat. No. 4,967,203 (Doan) for an Interlace Printing Process, U.S. Pat. No. 4,999,646 (Trask) for a Method for Enhancing the Uniformity and Consistency of Dot Formation Produced by Color Ink Jet Printing, and U.S. Pat. No. 5,583,550 (Hickman) for Ink Drop Placement for Improved Imaging (each assigned to the common assignee of the present invention). However, large drops create large dots, or larger groups of dots known as "superpixels," which are quite visible in transition zones. Moreover, each of these methods consume ink at a rapid rate and are thus more expensive to operate. Drop volume control and multi-drop methods of inking are taught respectively by Childers in U.S. Pat. No. 4,967,208 for an Offset Nozzle Droplet Formation and U.S. Pat. No. 5,485,180 (Askeland et al.) for Inking for Color-Inkjet Printers, Using Non-Integral Drop Averages, Media Varying Inking, or More Than Two Drops Per Pixel (each assigned to the common assignee of the present invention). In a multi-drop mode, the resulting dot will vary in size or in color depending on the number of drops fired at an individual pixel or superpixel and the constitution of the ink with respect to its spreading characteristics after impact on the particular medium being printed (plain paper, glossy paper, transparency, etc.). The luminance and color of the printed image is modulated by manipulating the size and densities of drops of each color at each target pixel. The quantization effects of this mode can be physically reduced in the same ways as for the single-drop per pixel mode. The quantization levels can also be reduced at the same printing resolution by increasing the number of drops that can be fired at one time from each nozzle in a print head array and either adjusting the density

of the ink or the size of each drop fired so as to achieve full dot density. However, simultaneously decreasing drop size and increasing the printing resolution, or increasing the number of pens and varieties of inks employed in a hard copy apparatus is very expensive, so ink-jet hard copy apparatus designed specifically for imaging art reproduction generally use multi-drop modes to improve color saturation.

When the size of the printed dots is modulated the image quality is very dependent on dot placement accuracy and resolution. Misplaced dots leave unmarked pixels which appear as white dots or even bands of white lines within or between print swaths (known as "banding"). Mechanical tolerances are critical in the construction as the print head geometries of the nozzles are reduced in order to achieve a resolution of 600 dpi or greater. Therefore, the cost of manufacture increases with the increase of the resolution design specification. Furthermore, as the number of drops fired at one time by multiplexing nozzles increases, the minimum nozzle drop volume decreases, dot placement precision requirements increase, and thermal efficiency of the print head becomes more difficult to control. High temperatures not only bum out print head elements faster but also have to be taken into account when formulating the inks to be used.

When the density of the printed dots is modulated, the low dye load inks require that more ink be placed on the print media, resulting in less efficient ink usage and higher risk of ink coalescence and smearing. Ink usage efficiency decreases and risk of coalescence and smearing increases with the number of drops fired at one time from each nozzle of the print head array.

Another methodology for controlling print quality is to focus on the properties of the ink itself. When an ink drop contacts the print media, lateral diffusion ("spreading") begins, eventually ceasing as the colorant vehicle (water or some other solvent) of the ink is sufficiently spread and evaporates. For example, in U.S. Pat. No. 4,914,451 (Morris et al., assigned to the common assignee of the present invention), Post-Pointing Image Development of Ink-Jet Generated Transparencies, lateral spreading of each droplet is controlled with media coatings that control latent lateral diffusion of the printed ink dots. However, this increases the cost of the print media. Lateral spreading also causes adjacent droplets to bleed into each other. The ink composition itself can be constituted to reduce bleed, such as taught by Prasad in U.S. Pat. No. 5,196,056 for an Ink Jet Composition with Reduced Bleed. However, this may result in a formulation not suitable for the spectrum of available print media that end users may find desirous.

One apparatus for improving print quality is discussed in a very short article, Bubble Ink-Jet Technology with Improved Performance, by Enrico Manini, Olivetti, presented at IS&T's Tenth International Congress on Advances in Non-Impact Printing Technologies, Oct. 30–Nov. 4, 1994, New Orleans, La. Manini shows a concept for, "better distributing the ink on the paper, by using more, smaller droplets . . . utiliz(ing) several nozzles for each pressure chamber, so that a fine shower of ink is deposited on the paper." Sketches are provided by Manini showing two-nozzle pressure chambers, three-nozzle chambers, and four-nozzle chambers. Manini shows the deposition of multiple drops of ink within a pixel areal dimension such that individual drops are in adjacent contact or overlapping. Manini alleges the devices abilities: to make a square elementary dot to thereby provide a 15% ink savings and faster drying time; to create better linearity in gray scaling; and to allow the use of smaller nozzles which allow higher

capillary refill (meaning a faster throughput capability—generally measured in printed pages per minute, "ppm"). No working embodiment is disclosed and Manini himself admits, "The hydraulic tuning between the entrance duct and the outlet nozzles is however rather complex and requires a lot of experimentation."

Manini, however, only followed along the path of prior U.S. Pat. No. 4,621,273, filed on Dec. 16, 1982, teaching a Print Head for Printing or Vector Plotting with a Multiplicity of Line Widths (Anderson; assigned to the common assignee herein). Anderson shows a multi-nozzle arrangement (a "primitive") for an 80–100 dpi raster/vector plotter with ink jet nozzles at selected points of a two-dimensional grid. However, while Anderson teaches a variety of useful primitive patterns (see e.g., FIGS. 1A–2B therein), the dot pattern is specifically limited to having only one nozzle on any given column in the grid by having only one nozzle in any given row or column. Selective firing is then directed depending on the plot to be created. A heavy interlacing of dots is required as demonstrated in FIGS. 4 and 5 therein.

Another problem with thermal ink-jet print heads is the phenomenon known as "puddling." An ink drop exiting an orifice will tend to leave behind minute amounts of ink on the nozzle plate surface about each orifice. As these puddles grow, surface tension between the puddle and an exiting ink drop will tend to attract the tail of the drop and change its trajectory. A change in trajectory means the drop will not hit its targeted pixel center, introducing, printing errors on the media. Tuning of nozzle plates is proposed by Allen et al. in U.S. Pat. No. 4,550,326 for Fluidic Tuning of Impulse Jet Devices Using Passive Orifices (assigned to the common assignee herein).

Another problem in ink-jet printing occurs at higher resolutions, for example, in multi-pass and bidirectional 300 dpi printing. Misaligned drops cause adverse consequences such as graininess, hue shift, white spaces, and the like. Normally, binary drops are deposited on the grid of square pixels such that drops overlap to a degree necessary to ensure no visible white spaces occur at the four corners of the target pixel (as taught by Trask, Doan, and Hickman, supra). As mentioned, ink usage is dramatically increased by these techniques. Moreover, print media line feed error is significant compared to drop size and, without multiple-drop or overlap between pixels, white banding between swaths occurs. Thus, each of these prior art inventions are using more ink than would be required if perfectly accurate trajectories of perfectly sized ink drops could be achieved.

Therefore, until a technological breakthrough to achieve such perfection is attained, there is still a need for improvement in thermal ink-jet print heads and methods of distribution of ink drops to achieve superior print quality, decreasing quantization effects and ink usage. The goal is to reduce the required luminance and color quantization levels of an ink-jet printing system for high fidelity without requiring higher dot placement printing resolution while also increasing data throughput.

#### SUMMARY OF THE INVENTION

In its basic aspects, the present invention provides a print head device for use in printing a pixel dot matrix on a print medium. The print head device includes: an array of drop generators, each of the drop generators having a plurality of nozzles and the plurality of nozzles is configured such that each drop generator includes a set of nozzles in a predetermined layout providing a set of nozzles in each of the drop generators wherein as a drop generator traverses print

5

medium target pixels as the print head is scanned across the medium, the nozzles in each set provide a distribution of ink droplets forming dots on the medium such that at least one of the dots formed on the medium from each set is substantially outside the target pixel.

Another basic aspect of the present invention is an ink-jet pen. The pen includes: a housing; at least one on-board ink reservoir within the housing, the reservoir containing at least one supply of ink of a predetermined chemical formulation; a print head fluidically coupled to the reservoir to receive a flow of ink therefrom; electrical contacts for connecting the print head to a hard copy apparatus print controller; the print head having a plurality of drop generators oriented in an array; each drop generator of the array having a plurality of nozzles arrayed about a geometric center point of the drop generator; each of the drop generators having at least one heating element connected to the electrical contacts; each of the nozzles having an ink entrance port proximate the heating element, the entrance port having an entrance port areal dimension; each of the nozzles having an exit orifice distal from the heating element for emitting ink drops onto an adjacently positioned print medium, the exit orifice having a predetermined exit orifice areal dimension less than an areal dimension of a pixel to be printed using the cartridge and less than the entrance orifice areal dimension and wherein the sum of the areal dimensions of the exit orifices in an array of nozzles is less than the areal dimension of a pixel.

In another basic aspect of the invention there is taught a method of distributing ink drops onto an adjacent print medium in order to form a dot matrix print on a grid of pixels wherein the dot matrix is manipulated selectively to form graphic art, images, and alphanumeric characters. The method includes the steps of:

scanning a print medium with at least one ink-jet pen in a first axial direction, X;

during the step of scanning,

simultaneously generating a plurality of ink drops in each drop generator of a drop generator array of an ink-jet print head of the ink-jet pen,

simultaneously firing sets of the simultaneously generated ink drops selectively at the grid of pixels such that each of the sets of ink drops form dots on the media, each of the dots having a size less than the size of a pixel, and each of the sets of ink drops being distributed in a pattern on or about a target pixel of the grid such that each of the drops of a set produces a dot having an area less than or equal to 1 divided by number-of-drops-per-set multiplied by the area of the target pixel  $area_{dot} \leq (1/n) * P_a$  where "n" is the number of orifices per drop generator and "P<sub>a</sub>" is the area of a pixel to be printed)

In yet another basic aspect the present invention provides for an ink-jet hard copy apparatus, having a housing, a scanning carriage, at least one pen mounted in the carriage, and a platen where swath printing operation is performed. The apparatus further provides for the pen having a housing; at least one on-board ink reservoir within the housing, the reservoir containing at least one supply of ink of a predetermined chemical formulation; a print head fluidically coupled to the reservoir to receive a flow of ink therefrom; electrical contacts for connecting the print head to a hard copy apparatus print controller; the print head having a plurality of drop generators oriented in an array; each drop generator of the array having a plurality of nozzles arrayed about a geometric center point of the drop generator; each of the drop generators having at least one heating element

6

connected to the electrical contacts; and each of the nozzles having an ink entrance port proximate the heating element, the entrance port having an entrance port areal dimension, each of the nozzles having an exit orifice distal from the heating element for emitting ink drops onto an adjacently positioned print medium, the exit orifice having a predetermined exit orifice areal dimension less than the areal dimension of a pixel to be printed using the cartridge and less than the entrance orifice areal dimension and wherein the sum of the areal dimensions of the exit orifices in an array of nozzles is less than the areal dimension of a pixel, and each of the nozzles of each of the drop generators are oriented in a position rotated about a geometric center point of the drop generator with respect to an intersection of axes in a plane of a scan axis and a plane of a media motion axis such that dots are printed from each of the nozzles in adjoining pixels to a pixel which a drop generator is traversing, and each exit orifice has an exit orifice areal dimension sized to eject a droplet that will create a dot on a target media with an areal dimension less than or equal to an area calculated in accordance with a formula: 1 divided by the number of orifices per drop generator times the areal dimension of a pixel ( $A_{eo} = (1/n) * P_a$ , where "A<sub>eo</sub>" is the exit orifice area, "n" is the number of orifice per drop generator, and "P<sub>a</sub>" is the area of a pixel to be printed)

It is an advantage of the present invention that it provides a method for lowering edge transition sharpness.

It is a further advantage of the present invention that it improves the imaging of luminance transition zones.

It is an advantage of the present invention that it achieves lower print graininess and smoother color transitions in the printing of mid-tone regions than is achieved using single orifice drop generators implementing the same dot placement resolution, without requiring increased printing resolution or number of multi-drop mode print levels.

It is an advantage of the present invention that it substantially eliminates the need for overlapping of printed dots to reduce quantization errors, decreasing the amount of ink needed to print an image.

It is an advantage of the present invention that it improves ink-jet print quality perception without increasing ink quantity per print.

It is an advantage of the present invention that it decreases graininess of an ink-jet print without reducing dye load in the ink.

It is another advantage of the present invention that it reduces the amount of water or other dye solvent deposited on the print media, thereby reducing both drying time and print media cockle effects.

It is another advantage of the present invention that nozzle dimensions are reduced, decreasing refill time (refill time is proportional to the capillarity force which is inversely proportional to exit orifice diameter) and increasing hard copy throughput proportionally.

It is another advantage of the present invention that reduced nozzle dimensions forming smaller ink drops requires less firing energy per drop from the heating element of the drop generator, improving thermal characteristics and print head life expectancy.

It is yet another advantage of the present invention that it increases life of the print head as heating element resistors are not required to fire as many times per pixel as in commercial multi-drop mode hard copy apparatus.

It is another advantage of the present invention that it improves print quality through reducing sensitivity to drop misalignment, decreasing sensitivity to trajectory errors caused by formation of puddles of ink around a nozzle's exit orifice.

It is yet another advantage of the present invention that print quality is improved while using less ink by distributing a given drop volume, e.g., of a 600 dpi drop, over the area of a larger region, e.g., four quadrants of a 300 dpi pixel area, approximately one-quarter the saturation of the full dye load, lowering the density of the page by spreading less ink more evenly over the pixels.

It is still another advantage of the present invention that a multi-nozzle drop generator can be adapted to a variety of layout configurations such that resulting dots on the print media form more diffuse pixel fill, require less ink to print, and conceal drop misalignment errors, sheet feed errors, and trajectory errors.

It is still another advantage of the present invention that graphics and images require only single inks of primary colors to produce a range of hues formerly requiring multiple inks of primary colors using different dye loads or colorant formulations.

It is a further advantage of the present invention that it increases throughput by being adaptable to employing bidirectional scan printing.

It is a further advantage of the present invention that it is adaptable to a combination of orientations of each multi-nozzle drop generator such that printing errors, such as those caused by clogged nozzles or mis-firing drop generator nozzles, are masked in the print.

It is yet another advantage of the present invention that it eases the manufacturing tolerance requirement for nozzle-to-heating element alignment.

It is yet another advantage of the present invention that it can be retrofit to existing commercial ink-jet hard copy apparatus.

Other objects, features and advantages of the present invention will become apparent upon consideration of the following explanation and the accompanying drawings, in which like reference designations represent like features throughout the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The file of this patent contains at least one drawing executed in color. Copies of this patent with color drawing (s) will be provided by the Patent and Trademark Office upon request and payment of the necessary fee.

FIG. 1 is a schematic drawing in perspective view (partial cut-away) of an ink-jet apparatus (cover panel facia removed) in which the present invention is incorporated.

FIG. 2 is a schematic drawing in a perspective view of an ink-jet print cartridge component of FIG. 1.

FIG. 2A is a schematic drawing of detail of a print head component of the print cartridge of FIG. 2.

FIGS. 3A, 3B and 3C are schematic drawings (top view) of three different nozzle placement configurations relative to a central heating element of an ink-jet print head drop generator construct in accordance with the present invention.

FIG. 4A is a schematic drawing in accordance with the present invention of a cross-section of an ink drop generator, taken in cross-section A—A of FIG. 3B.

FIG. 4B is a schematic drawing (top view) in accordance with the present invention of a fourth nozzle placement configuration relative to a central heating element of a drop generator as shown in FIGS. 3A—3C.

FIG. 5 is a schematic drawing (top view) of a set of three, four nozzle, one heating element, ink-jet drop generators (a portion of a full array) in accordance with a preferred embodiment of the present invention.

FIGS. 6A and 6B are schematic drawings (top view) of the embodiment of the present invention as shown in FIG. 5 shown in reduction in FIG. 6A and with FIG. 6B showing in comparison to FIG. 6A, a counter rotational orientation of the nozzle sets.

FIG. 7 is schematic drawing (top view) of a set of three, four nozzle, four heating element, ink-jet drop generators (a portion of a full array) in accordance with an alternative embodiment of the present invention as shown in FIG. 5.

FIG. 8 is a schematic drawing (top view) of the embodiment of the present invention as shown in FIG. 7 with a counter rotational orientation of the nozzles.

FIGS. 9A, 9B, and 9C demonstrate a method of sequential scanning passes for printing a dot matrix formed in accordance with the present invention using a single multi-nozzle drop generator as shown in FIG. 5.

FIGS. 10A, 10B, 10C and 10D are color comparison sample prints demonstrating print quality improvement in accordance with the use of a multi-nozzle print head constructed in accordance with the present invention.

FIGS. 11A and 11B depict two exemplary print head nozzle orientation strategies for the methodology as shown in FIGS. 9A—9C.

FIGS. 12A, 12B, 12C, 12D, and 12E demonstrate a more complex exemplary print head nozzle orientation strategy in comparison to FIGS. 11A—11B.

FIG. 13 is an alternative embodiment of an ink drop generator in cross-section of the present invention as shown in FIG. 4A.

The drawings referred to in this specification should be understood as not being drawn to scale except if specifically noted.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference is made now in detail to a specific embodiment of the present invention, which illustrates the best mode presently contemplated by the inventors for practicing the invention. Alternative embodiments are also briefly described as applicable.

An exemplary ink-jet hard copy apparatus, a computer printer 101, is shown in rudimentary form in FIG. 1. A printer housing 103 contains a platen 105 to which input print media 107 is transported by mechanisms as would be known in the state of the art. A carriage 109 holds a set 111 of individual print cartridges, one having cyan ink, one having magenta ink, one having yellow ink, and one having black ink. (Alternatively, ink-jet “pens” comprise semi-permanent print head mechanisms having at least one small volume, on-board, ink chamber that is sporadically replenished from fluidically-coupled, off-axis, ink reservoirs; the present invention is applicable to both ink-jet cartridges and pens.) The carriage 109 is mounted on a slider 113, allowing the carriage 109 to be scanned back and forth across the print media 107. The scan axis, “X,” is indicated by arrow 115. As the carriage 109 scans, ink drops can be fired from the set 111 of print cartridges onto the media 107 in predetermined print swath patterns, forming images or alphanumeric characters using dot matrix manipulation. Generally, the dot matrix manipulation is determined by a computer (not shown) and instructions are transmitted to an on-board, microprocessor-based, electronic controller (not shown) within the printer 101. The ink drop trajectory axis, “Z,” is indicated by arrow 117. When a swath of print has been completed, the media 107 is moved an appropriate distance



along the print media axis, "Y," indicated by arrow 119 and the next swath can be printed.

An exemplary thermal ink-jet cartridge 210 is shown in FIGS. 2 and 2A. A cartridge housing, or shell, 212 contains an internal reservoir of ink (not shown). The cartridge 210 is provided with a print head 214, which may be manufactured in the manner of a flex circuit 218, having electrical contacts 220. The print head 214 includes an orifice plate 216, having a plurality of miniature nozzles 217 constructed in combination with subjacent structures leading to respective heating elements (generally electrical resistors) that are connected to the contacts 220; together these elements form a print head array of "drop generators" (not shown; but see FIG. 4 below, and e.g., above-referenced U.S. Pat. Nos. 4,967,208 and 5,278,584; see also, U.S. Pat. Nos. 5,291,226, 5,305,015, and 5,305,018 (Schantz et al., assigned to the common assignee of the present invention and incorporated herein by reference) which teach methodologies for the manufacture of laser ablated print head components). FIG. 2A depicts a simplified commercial design having an array of nozzles 217 comprising a layout of a plurality of single nozzle drop generators arranged in two parallel columns. Thermal excitation of ink via the heating elements is used to eject ink drops through the nozzles onto an adjacent print medium (see FIG. 1, element 107). In a commercial product such as the Hewlett-Packard™ DeskJet™ printer, one hundred and ninety-two (192), single nozzle, drop generators are employed to allow 300 dpi print resolution.

Nozzle configurations, a primary aspect of the present invention, are design factors that control droplet size, velocity and trajectory of the droplets of ink in the Z axis. The standard drop generator configuration has one orifice and is fired in either a single-drop per pixel or multi-drop per pixel print mode. (In the single-drop mode (known as "binary"), one ink drop is selectively fired from each nozzle 217 from each print cartridge 210 toward a respective target pixel on the print media 107 (that is, a target pixel might get one drop of yellow from a nozzle and two drops of cyan from another nozzle to achieve a specific hue); in the multi-drop mode to improve saturation and resolution two drops of yellow and four of cyan might be used for that particular hue. (For the purpose of this description and the claims of the present invention, a target pixel shall mean a pixel which a drop generator is traversing as an ink-jet print head is scanned across an adjacent print medium, taking into consideration the physics of firing, flight time, trajectory, nozzle configuration, and the like as would be known to a person skilled in the art; that is, in a conventional print head it is the pixel at which a particular drop generator is aiming; as will be recognized based on the following detailed description, with respect to the present invention, the target pixel may differ in location from a pixel on which the drop generator of the present invention forms dots; that is, dots may be formed in pixels other than the currently traversed pixel, i.e., other than the traditional target pixel.)) The resulting dot on the print media is approximately the same size and color as the dots from the same and other nozzles on the same print cartridge.

Comparing FIGS. 3A–C and 4A–B to FIGS. 2 and 2A, it will be recognized that in multi-nozzle drop generator design, the orifice plate can have a variety of layout configurations for each drop generator. In a commercial embodiment, each multi-nozzle drop generator now includes an array of sets of nozzles; for example to do 300 dpi printing, 192 sets of four-nozzle drop generators (768 nozzles in sets of four) is employed. Note that since the number of heating elements has not been changed from the

construct depicted in FIGS. 1–2A to achieve the configurations in FIGS. 3A–3C and FIG. 4B, a retrofit using the same controller is possible.

In cross-section as generally depicted in FIG. 4A, taken in section A–A of FIG. 4B, a drop generator 401 is formed using, for example, known laser ablation construction (see Background section and Schantz et al. U.S. Patents, supra), having a heating element, resistor, 403, located in an ink firing chamber 405. In a top-firing (versus side-firing) embodiment, nozzles 407, 409, 411, 413, are cut through a manifold 415. Each nozzle 407, 409, 411, 413 is tapered from an ink entrance diameter, "D," 417, superjacent the heating element 403 to a distal, narrower, ink drop exit diameter, "d," 419. (In order to clearly distinguish the nozzle elements, the entrance proximate the heating element 403 is referred to as an ink "entrance port" and the distal ink exit from the nozzle from which ink droplets are expelled toward the print media is referred to as an "exit orifice".) A comparison of FIGS. 3A, 3B, 3C and 4B exemplifies that a variety of design relative configurations are possible (the examples are not intended to limit the scope of the invention to only the shown layouts as others, including both even and odd number of nozzle/orifice set arrays and combinatorial nozzle/orifice sets will be apparent to those skilled in the art). It should be kept in mind that a specific optimal layout may be dependent upon many apparatus design factors, including scan velocity, ink composition, ink droplet flight time, flight distance between the orifice plate and the media, and the like as would be known to a person skilled in the art. Moreover, in the preferred embodiment of the present invention, it is specifically intended that the droplets simultaneously fired do not merge in flight. If expedient to another design criteria, the nozzles can be oriented such that drops will merge or actually diverge in flight. Such an alternative embodiment is shown in FIG. 13.

Moreover, note that the mix of nozzles per drop generator need not be a constant throughout the array. That is, a first set for one ink may have three nozzles and another set of the array for another ink may have six nozzles per drop generator.

Each exit orifice has an exit orifice areal dimension less than: the integer 1 divided by the number of orifices per drop generator times the areal dimension of a pixel ( $1/n * P_a$ , where "n" is the number of orifices per drop generator and "P<sub>a</sub>" is the area of a pixel to be printed). For example, if three nozzles are in a particular drop generator, each exit orifice has an area less than  $1/3$  times the area of a pixel,  $1/3 * (1/300)^2$  sq. in.; if four nozzles per drop generator, each exit orifice has an area less than  $1/4 * (1/300)^2$  sq. in., etc. The sum of the areas of each nozzle array in a drop generator is therefore less than the area of a pixel. In other words, the intent is to generate ink droplets that will form dots having a diameter less than or equal to approximately twenty to twenty-five microns in a distribution pattern where the dots occupy contiguous regions of the pixels and any spaces remaining between the dots are substantially less than twenty to twenty-five microns and are therefore invisible to the naked eye.

A first preferred embodiment of a partial orifice plate array 501 of four nozzle ink drop generators is shown in FIG. 5 (three sets of a total array), referred to hereinafter as a "right rotated quad architecture." Note that in the preceding exemplary embodiments (as in the Manini prior art), the nozzles 407, 409, 411, 413 are all oriented in quadrants orthogonally set about a geometric center point of the resistor 403 (viz., the geometric center point of the drop generator and relative to the scan axis, X, and the print axis,

Y). As shown in FIG. 5, it has been found that rotating away from this orthogonal orientation of the layout has distinct advantages. Moreover, note that the array also has each column of drop generators offset with respect to the Y-axis, arrow 119. (The purpose and methodology of such offsets is taught by Chan et al. in U.S. Pat. No. 4,812,859 for a Multi-Chamber Ink Jet Recording Head for Color Use, assigned to the assignee of the present invention and incorporated herein by reference.) A primary advantage is that such a configuration will allow bi-directional X-axis printing, doubling the effective throughput.

While FIGS. 5 and 6A show a right rotated quad architecture of the nozzles around the central heating element, FIG. 6B, demonstrates a left rotation of the nozzles 407-413" about the centrally located heating elements 403-403". As will be demonstrated hereinafter, it has been found that combinations of rotations and the use of different rotations affects print quality.

FIG. 7 depicts an alternative embodiment where ink drop generators similar to FIG. 5 are employed with each nozzle 407-413" having a separate heating element 403'<sub>1</sub>-403'<sub>4</sub> through 403'<sub>4</sub>. With this arrangement and using dot matrix manipulation, individual heating element electrical connections, and addressing algorithm techniques, it is possible to fire less than all nozzles at the same time. This would allow fine tuning of the image resolution.

While FIG. 7 shows a right rotation about a geometric center point of the drop generator indicative of the intersection of planes parallel to the X and Y axes, FIG. 8, demonstrates a left rotation of the nozzles 407-413" and the individual heating elements 403'<sub>1</sub>-403'<sub>3</sub>.

Printing operation in accordance with the present invention is depicted in FIGS. 9A-9C, showing a contiguous set of nine arbitrary pixels, 901-909, from a full grid overlay of an image to be printed (greatly magnified; in commercial designs each pixel generally will be  $\frac{1}{300}''^2$  by  $\frac{1}{300}''^2$  or smaller). For convenience of explanation, the firing of a single set of four nozzles as shown in FIG. 5 will be described in order to achieve a dot fill of more than one pixel 905; the process then continues sequentially. It should be understood that in a commercial embodiment, the firing will be algorithmically controlled and that some or all of the selected sets of nozzles in the array will fire four ink droplets of an appropriate color during each scan in the X-axis (arrow 115), creating a print head array wide swath equal to the length of the array in the Y-axis (arrow 119) in accordance with the firing signals generated by the print controller; for example, this could be a one inch or smaller pen swath up to a page length swath.

Assume a central pixel 905 of this grid subsection, having square dimensions of one three-hundredth of an inch ( $\frac{1}{300}''$ )<sup>2</sup>, is to be covered with yellow ink. As shown in FIG. 9A, in the first scan pass, for example, left to right along the X-axis, "pass<sub>1</sub>," four ink droplets 911 are fired in the Z-axis deposited about pixel 901 in accordance with instructions from the controller from one set of nozzles (e.g. nozzles 407", 409", 411", 413" as shown in FIG. 5). Note that at this firing, due to the rotated quad architecture, ink droplets 911 are deposited in pixels 902 and 906 and in two pixels outside the exemplary grid area 901-909. Upon movement of the print head  $\frac{1}{300}''$  in the X axis 115 so that the nozzle set is traversing appropriately in a relative position with respect to pixel 902, four droplets 912 are deposited, including a first ink droplets in the upper left quadrant of the exemplary yellow pixel 905 and droplets in pixels 901 and 903. Upon moving the print head  $\frac{1}{300}''$  so that the nozzle set is over

pixel 903, four droplets 913 are deposited, including droplets in pixels 902 and 904. (in this example, only a single pixel row is being printed per pass; it will be recognized by a person skilled in the art that the complexity of the firing algorithm during pass<sub>1</sub> is dependent upon the image being produced and the full construction of the print head implementation with many pixels in a nozzle array wide swath are being inked simultaneously, including drop-on-drop mixing of primary color inks to produce all of the hues and luminance ratios of the image that are required to reproduce the image faithfully.) At the end of pass<sub>1</sub>, with a media shift in the Y axis 119, a second swath can be printed during a next scan pass across the print medium.

FIG. 9B depicts a second pass, from right to left, pass<sub>2</sub>, that first deposits four ink droplets 914 about pixel 904, including an ink droplet in the upper right quadrant of the target pixel and drops in pixels 903 and 909. Upon movement of the print head  $\frac{1}{300}''$  so that the nozzle set is over the exemplary pixel 905, four droplets 915 are deposited, including droplets in the pixels 902, 904, 906 and 908. Upon moving the print head another  $\frac{1}{300}''$  so that the nozzle set is over pixel 906, four droplets 916 are deposited, including a third ink droplet in the lower left quadrant of the exemplary pixel 905, and droplets in pixels 901 and 907.

Similarly, FIG. 9C depicts a third pass, from left to right, pass<sub>3</sub>. Four ink droplets 917 are deposited about pixel 907, including dotting pixels 906 and 908 when the drop generator set is above pixel 907 in the Z axis (FIG. 1, arrow 117). Upon moving the print head  $\frac{1}{300}''$  so that the nozzle set is over pixel 908, four droplets 918 are deposited, including a fourth ink droplet in the lower right quadrant of the exemplary pixel 905 and drops in pixels 907 and 909. Note that at this point in the pass<sub>3</sub>, the region around exemplary pixel 905 is filled via this bidirectional scanning method. The process continues with drops 919 being deposited about pixel 909.

Also note that by pass<sub>3</sub>, droplets of ink are being placed in locations such that some interlacing due to spreading may occur. This effect will depend upon the rotation layouts used in any specific design implementation.

It has been further discovered, that print quality is improved when a combination of different nozzle rotations orientation is used which also may be important for meeting mechanical tolerances during manufacture of the print head. For example, assume a CMYK ink-jet hard copy apparatus employs one tricolor print cartridge for CMY inks with subsets of the array of nozzles each coupled to specific color ink reservoir and a separate black ink print cartridge (e.g., a standard, single nozzle configuration). When the nozzle set array for cyan ink is left-rotated such as shown in FIG. 6B and the nozzle set arrays for magenta and yellow inks are respectively right rotated as shown in FIGS. 5 and 6B, an improvement in print quality is achieved.

To demonstrate the achievement of improved print quality in accordance with the present invention, color samples of a facial image, eye region, are provided as FIGS. 10A-10D. These FIGURES are a plain paper copy of a subsection prints and at a ten times magnification. The eye and a band of yellow makeup shown was each created from an original image by using four different computer generated virtual printing methodologies and the comparison prints made using a Hewlett-Packard™ DeskJet™ printer, model 850. FIG. 10A is a rendering of such a sample print as can be made with a conventional single nozzle print head, 300 dpi printer; FIG. 10B from a print made on a conventional single nozzle print head, 600 dpi printer; FIG. 10C from a print

produced by experimental computer modeling using a print head in accordance with the present to invention using a nozzle layout configuration for CMYK inks in a right rotated quad architecture ("CMYK R-RotQuad") as shown in FIG. 5; and, FIG. 10D from a print head in accordance with the present invention using nozzle array layout configuration for cyan ink in a left rotated orientation ("CL-") as shown in FIG. 6B and magenta and yellow inks nozzle array layout configurations in a right rotated architecture ("MYK-R-RotQuad") as shown in FIG. 5.

FIG. 10A shows a noticeable grain; that is, even in the highest resolution area of the iris, individual dots are very apparent to the unaided eye. Only in center of the pupil where black saturation is achieved do the individual dots disappear. Luminance transition regions, e.g., above the eye ball and to the viewer's right side where yellow dots are dominant, are discontinuous rather than smooth (compare FIG. 10B).

FIG. 10B shows a high resolution, 600 dpi, print with rich color saturation, smooth tonal transition, and markedly reduced granularity, with the reduced size individual dots showing quantization effects mostly in transition zones toning and the whites of the eyes.

Comparing FIG. 10C to FIGS. 10A and 10B, it can immediately be recognized that the overall print quality appears to be closer to the high resolution 600 dpi print of FIGURE B than it does to FIG. 10A. A marked reduction in overall graininess obvious. Richer hues are perceived and luminance ratios are improved.

Comparing FIG. 10D to FIGS. 10A and 10B, the same observations can be made as were made with respect to FIG. 10C. While FIGS. 10C and 10D are very close to each other in overall print quality, FIG. 10D has an overall sharpness that appears to be closer to FIG. 10B; in other words, the resolution appears to be slightly closer to the 600 dpi sample print.

The counter rotation of some color ink designated drop generators provides the advantage of more quantization effect print error reduction. As an example, note that FIG. 10D has less noticeable diagonal banding in the "white flash region" of the iris than does FIG. 10C. This technique also is effective at masking moire patterns (an undesirable pattern that occurs when a halftone is made from a previously printed halftone which causes a conflict between the dot arrangements).

An example of a specific advantageous printing scheme is shown in FIG. 11A. A combination of nozzle rotations in a print head is shown in order to direct four yellow ink droplets toward a target pixel 1101 with other; droplets, represented by capital Y's in the drawing, falling in accordance with a right rotated cyan nozzle cluster represented by capital C's, a left rotated magenta nozzle cluster represented by capital M's, and black placed at the outermost comers fired from a separate, conventional print head, i.e., a single nozzle design. This arrangement is desirable because it reduces granularity in the printed image.

FIG. 11B indicates a rotation printing scheme which will enhance the printing of black dots, particularly in a printer that will also be used for near-laser quality alphanumeric text printing.

FIGS. 12A through 12E demonstrate an example of the more complex implementation scheme which can be devised in accordance with the present invention. FIGS. 12A through 12D show that as scanned, an appropriately constructed print head can lay down super pixels in patterns such that as consecutive rows are printed, the super pixels are layered, C,

Y, M, K to produce a pattern as shown in FIG. 12E. Actual nozzle firing and dot deposition will of course be based on the image being duplicated.

The present invention speeds throughput significantly due to the decreased nozzle size since refill time is proportional to the capillarity force which is inversely proportional to the radius of the bore of the nozzle. In the state of the art, a 300 dpi ink-jet printer operates at about five kHz, a 600 dpi printer operates at about twelve kHz. The deposition of the smaller droplets in accordance with the apparatus and method of the present invention (for example, having individual drop volumes equivalent to a 1200 dpi hard copy printer) is estimated to allow operating at approximately 30 kHz at 300 dpi but without the need for high data rates that multi-drop mode, high resolution printing requires.

The present invention also decreases print head operating temperature problems. Each heating element will fire more ink drops per cycle. The print head will tend to get hotter in conventional multi-drop modes in accordance with the formula:

$$T_e = E_{drop} / M_{drop} * C_p$$

where  $T_e$  represents the characteristic temperature change of the ink firing,  $E$  is the drop energy,  $M$  is the drop mass, and  $C_p$  is specific heat. It has been found that in high resolution printing, e.g., 1200 dpi, as the ink drops decrease in mass the energy requirement is not decreasing proportionally, leading to temperature excursions over 70° C. which is unacceptable for, reproducible print.

In accordance with the foregoing description, the present invention provides a print head design and ink drop deposition methodology using that design which provides superior print quality while employing techniques generally associated with low resolution ink-jet printing. Print head mechanical and electrical operational requirements are also facilitated.

The foregoing description of the preferred embodiment of the present invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Obviously, many modifications and variations will be apparent to practitioners skilled in this art.

Clearly, a set of nozzles per each drop generator is not limited to two, three or four. For example, where an ink composition is designed for lateral spreading, where the intent is to cover a region uniformly with as little ink as possible, a hexagonal array reduces the total ink deposited by approximately thirty percent. Thus, a combination of using some hexagonal sets of nozzles used for a black filled area with other configurations for other color inks can be designed into specific print heads.

Moreover, the present invention has been described in terms of a typical, commercial, scanning ink-jet apparatus. However, page width and page length print heads are also feasible in the state of the art and the invention is adaptable to those implementations.

Similarly, any process steps described might be interchangeable with other steps in order to achieve the same result. The embodiment was chosen and described in order to best explain the principles of the invention and its best mode practical application to thereby enable others skilled in the art to understand the invention for various embodiments and with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims appended hereto and their equivalents.

15

What is claimed is:

1. A printhead device for use in printing a pixel dot matrix on a print medium, comprising:

an array of drop generators, at least one of said drop generators having a plurality of nozzles;

at least one heating element located within said at least one drop generator;

said plurality of nozzles configured in a predetermined layout such that as said at least one drop generator traverses a print medium target pixel as said print head is scanned across the print medium, said plurality of nozzles ejects ink droplets to deposit a distribution of ink dots on the print medium upon an activation of said at least one heating element; and

at least one nozzle of said plurality of nozzles formed to direct an ink droplet of said ink droplets to deposit an ink dot of said distribution of ink dots on the print medium substantially outside said print medium target pixel upon said activation of said at least one heating element.

2. The device as set forth in claim 1, wherein said array of drop generators further comprises:

said predetermined layout of said plurality of nozzles of said at least one drop generator arranged such that all of said plurality of nozzles provides a distribution of ink droplets forming dots on the medium such that all the dots generated are outside a respective target pixel in a respective row of pixels during each firing of said at least one drop generator.

3. The device as set forth in claim 1 wherein said plurality of nozzles further comprises:

each of said plurality of nozzles having an exit orifice wherein each exit orifice has an exit orifice dimensional area sized for ejecting a droplet of ink creating a dot on a target media with an areal dimension less than said print medium target pixel dimensional area and for said set of nozzles a sum of resultant droplets dimensional area being less than or equal to said target pixel dimensional area.

4. The device as set forth in claim 1, wherein said at least one of said drop generators further comprises:

a set of four nozzles, each nozzle of said set of nozzles having an exit orifice diameter; and

said exit orifice diameter of each of the four nozzles being less than or equal to one-half the larger of a length or width of said target pixel dimension.

5. The device as set forth in claim 4, wherein each of said nozzles further comprises:

the exit orifice of each nozzle of said set of four nozzles having an areal dimension that produces an ink droplet producing a dot on the print medium having a diameter less than or equal to one-half the larger of a length or width dimension of said target pixel.

6. The device as set forth in claim 1 wherein said each of said nozzles further comprises:

an exit orifice having diameter producing an ink droplet forming a dot having a diameter approximately less than or equal to a diameter in a range of approximately twenty to twenty-five microns.

7. The device as set forth in claim 1 wherein the print head further comprises:

each of the nozzles of said at least one drop generator being oriented in a position about a center point of the drop generator with respect to an intersection of axes in a plane of a scan axis and a plane of a media motion axis.

16

8. The device as set forth in claim 7 wherein the print head further comprises:

each of the nozzles being oriented in a position rotated about the center point such that dots are printed from each of said nozzles at least partially in adjoining pixels to said target pixel which said at least one drop generator is traversing.

9. The device as set forth in claim 7 wherein the print head further comprises:

in the array of drop generators, said plurality of nozzles for said at least one drop generator being associated with a first color of ink and oriented in said position about the center point and a set of nozzles for a second drop generator of said array of drop generators being associated with a second color of ink and positioned in a rotated orientation about the center point.

10. The device as set forth in claim 7 wherein the print head further comprises:

the nozzles are positioned in a non-symmetrical distribution about the center point.

11. The device as set forth in claim 7 wherein said print head further comprises:

said array of drop generators having fewer than all of the drop generators having their respective nozzles positioned in an identical symmetry about respective center points of each of the drop generators.

12. The device as set forth in claim 1, further comprising:

each of said plurality of nozzles having an entrance port proximate the heating element, each entrance port having a predetermined entrance port diameter, and

each of said plurality of nozzles having an exit orifice distal the heating element, each exit orifice having a predetermined exit orifice diameter wherein the exit orifice diameter is less than the entrance diameter.

13. The device as set forth in claim 1 wherein the print head further comprises:

each drop generator in said array of drop generators having one or more coordinated heating elements.

14. The device as set forth in claim 1 wherein the print head further comprises:

each of said plurality of nozzles having an exit orifice from which ink is expelled and an entrance port, each of said plurality of nozzles having a separate coordinated heating element positioned subjacent the entrance port.

15. The device as set forth in claim 1 wherein said plurality of nozzles further comprises:

each of said plurality of nozzles having an exit orifice dimension for ejecting a droplet of ink to create a dot on the print medium with an areal dimension less than a print medium single pixel dimensional area and, for said plurality of nozzles, a sum of dot areal dimensions being less than or equal to said target pixel dimensional area.

16. The device as set forth in claim 1, wherein each of said drop generators further comprises:

a set of four nozzles; and

each nozzle of said set of nozzles having an exit orifice dimension to produce a resultant dot on the print medium with a diameter less than one-half the larger of a length or width of said target pixel.

17. A method of printing a pixel dot matrix on a print medium, comprising the steps of:

disposing an array of drop generators in a printhead device and associating a plurality of nozzles and a

17

heating element with a first drop generator of said array of drop generators;

scanning said printhead device across the print medium such that said first drop generator traverses a print medium target pixel;

activating said heating element when said first drop generator traverses said print medium target pixel as said printhead device is scanned across the print medium to eject ink droplets from each of said plurality of nozzles and deposit a distribution of ink dots on the print medium; and

forming at least one nozzle of said plurality of nozzles to direct an ink droplet of said ejected ink droplets to deposit an ink dot of said distribution of ink dots on the print medium substantially outside said print medium target pixel upon said activation of said heating element.

18. The method in accordance with the method of claim 17, further comprising the step of forming each of said plurality of nozzles to deposit each ink dot of said distribution of ink dots on the print medium outside said target pixel upon activation of said heating element.

19. The method in accordance with the method of claim 17 wherein said step of activating said heating element further comprises the step of depositing said distribution of ink dots on the print medium with a sum of dimensional areas of all said ink dots of said distribution being less than or equal to said target pixel dimensional area.

20. The method in accordance with the method of claim 17 further comprising the step of sizing an exit orifice of each nozzle of said plurality of nozzles to eject a droplet of ink for deposit of an ink dot on the print medium with an dimensional area less than said print medium target pixel dimensional area and with a sum of dimensional areas of all ink dots deposited upon said activation of said heating element being less than or equal to said target pixel dimensional area.

21. The method in accordance with the method of claim 17, further comprising the step of forming four nozzles

18

having an exit orifice diameter of each of said formed four nozzles less than or equal to one-half the larger of a length or width dimension of said target pixel.

22. The method in accordance with the method of claim 21 wherein said step of forming four nozzles further comprises the step of forming said exit orifice of each of the four nozzles with an areal dimension that produces an ink droplet forming an ink dot on the print medium having a diameter less than or equal to one-half the larger of said length or width dimension of said target pixel.

23. The method in accordance with the method of claim 17 further comprising the step of orienting each nozzle of said plurality of nozzles into a position about a center point of said first drop generator with respect to an intersection of axes in a plane of an axis of printhead scanning and a plane of a media motion axis.

24. The method in accordance with the method of claim 23 wherein the step of orienting each nozzle of said plurality of nozzles further comprises the step of rotating each of said oriented nozzles about said center point such that dots are deposited from each of said rotated nozzles at least partially in adjoining pixels to said target pixel which said first drop generator is traversing.

25. The method in accordance with the method of claim 23 further comprising the steps of:

positioning said plurality of nozzles associated with said first drop generator in a related orientation about said center point;

associating a plurality of nozzles and a heating element with a second drop generator; and

positioning said plurality of nozzles associated with said second drop generator in an orientation about said center point rotated from said related orientation of said plurality of nozzles associated with said first drop generator.

\* \* \* \* \*