




(86) Date de dépôt PCT/PCT Filing Date: 2005/04/26
(87) Date publication PCT/PCT Publication Date: 2005/11/17
(85) Entrée phase nationale/National Entry: 2006/10/16
(86) N° demande PCT/PCT Application No.: NL 2005/000311
(87) N° publication PCT/PCT Publication No.: 2005/107481
(30) Priorité/Priority: 2004/05/11 (NL1026171)

(51) Cl.Int./Int.Cl. **A22C 7/00** (2006.01)
(71) Demandeur/Applicant:
STORK TITAN B.V., NL
(72) Inventeurs/Inventors:
MESKENDAHL, DIRK, DE;
VAN DER EERDEN, HENDRICUS FRANCISCUS
JACOBUS M, NL
(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : **MOULAGE**
(54) Title: **MOULDING**



(57) **Abrégé/Abstract:**

A system for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises: - a production device having: - a frame, - a mould member provided with at least one mould cavity, the frame supporting the mould member, - mass feed means for feeding the mass to the one or more mould cavities of the mould member, the system furthermore comprising at least one cleaning device for cleaning one or more parts of the production device which come into contact with the mass. The mould member is preferably removable from the frame. Furthermore, the system preferably comprises a storage device for storing a plurality of mould members. It is preferable for each removable mould member to be provided with an identification, the system comprising recognition means for recognizing the identification of a mould member. Furthermore, the system preferably comprises a memory for storing at least one history of a mould member.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 November 2005 (17.11.2005)

PCT

(10) International Publication Number
WO 2005/107481 A2

(51) International Patent Classification⁷: **A22C 7/00**

(21) International Application Number:
PCT/NL2005/000311

(22) International Filing Date: 26 April 2005 (26.04.2005)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1026171 11 May 2004 (11.05.2004) NL

(71) Applicant (for all designated States except US): **STORK TITAN B.V.** [NL/NL]; 3, Handelstraat, NL-5831 AV Boxmeer (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MESKENDAHL, Dirk** [DE/DE]; 8, Hagenweg, 47559 Kranenburg (DE). **VAN DER EERDEN, Hendricus, Franciscus, Jacobus, Maria** [NL/NL]; 120, Vondellaan, NL-5421 PS Gemert (NL).

(74) Agent: **BROOKHUIS, H., J., A.**; Exter Polak & Char-
louis B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **MOULDING**



(57) **Abstract:** A system for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises: - a production device having: - a frame, - a mould member provided with at least one mould cavity, the frame supporting the mould member, - mass feed means for feeding the mass to the one or more mould cavities of the mould member, the system furthermore comprising at least one cleaning device for cleaning one or more parts of the production device which come into contact with the mass. The mould member is preferably removable from the frame. Furthermore, the system preferably comprises a storage device for storing a plurality of mould members. It is preferable for each removable mould member to be provided with an identification, the system comprising recognition means for recognizing the identification of a mould member. Furthermore, the system preferably comprises a memory for storing at least one history of a mould member.

WO 2005/107481 A2

MOULDING

- 5 The first aspect of the present invention relates to a system for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption.
- 10 The invention is deemed suitable in particular for the moulding of products from a meat mass, such as for hamburgers and the like, but other edible masses, for example of fish, potato, dough, etc. are also conceivable.
- 15 WO 00/30458 and WO 2004/002229 have disclosed systems having a production device provided with a frame, a mould member designed as a mould drum and provided with at least one mould cavity, the frame supporting the mould member, and furthermore provided with mass feed means for feeding the mass to the one or more mould
- 20 cavities of the mould member. US 4,975,039, for example, has disclosed a system having a mould member designed as a mould plate which can move to and fro.

It is an object of the first aspect of the invention to propose
25 measures which enhance the expedient use of systems of this type.

Moreover, it is an object of the first aspect of the invention to propose improvements in the area of the cleaning of systems
30 of this type.

A first aspect of the invention relates to a system for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption in
35 accordance with claim 1, as well as a mould drum designed and intended for a system for moulding three-dimensional products from a mass of one or more food starting materials suitable for consumption in accordance with claim 5. Further advantageous embodiments are described in the dependent claims 2-4 and 6-11.

The second aspect of the invention provides a system according to claim 12. Further advantageous embodiments are described in the dependent claims 13-58.

5

A third aspect of the invention relates to a system according to claim 59, the system furthermore comprising a storage device for storing a plurality of mould members. The storage device and if appropriate the further system is preferably designed as will be explained on the basis of the first aspect of the invention.

10

A fourth aspect of the invention relates to a system according to claim 60, in which each removable mould member is provided with an identification, and in which the system comprises recognition means for recognizing the identification of a mould member. Furthermore, the system is preferably designed as will be explained on the basis of the first aspect of the invention.

15

A fifth aspect of the invention relates to a system according to claim 61, in which the mould member can be removeable from the frame and in which the system furthermore comprises a memory for storing at least one history of a mould member. Furthermore the system is preferably designed as will be explained on the basis of the first aspect of the invention.

20

25

The various aspects of the invention also relate to a method for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, in which use is made of a system of this type.

30

It will be clear that the various aspects of the invention can be realized separately and/or in all possible combinations.

The various aspects of the invention will be explained in more detail below with reference to the drawing, in which:

35

Fig. 1 diagrammatically depicts an exemplary embodiment of a system according to the invention having a production device,

mould drum cleaning device, cleaning device for the production device,

Fig. 2 diagrammatically depicts a part of the production device with mould drum, and conveyor means for the mould drum from

5 Figure 1,

Fig. 3 diagrammatically depicts the positioning of the mould drum in the mould drum cleaning device from Figure 1,

Fig. 4a shows a mould drum according to the invention,

10 Fig. 4b shows a cross section through part of the mould drum from Figure 4a,

Fig. 5 diagrammatically depicts part of the mould drum cleaning device from Figure 3,

Fig. 6 diagrammatically depicts the production device and an associated cleaning device from Figure 1,

15 Fig. 7 shows the production device and the cleaning device which has been positioned against part of it,

Fig. 8 diagrammatically depicts a variant of Figure 7,

Fig. 9 diagrammatically depicts a second exemplary embodiment of a system according to the invention,

20 Fig. 10 shows the cleaning device which has been moved towards the production device and has its housing in the open position,

Fig. 11 shows the illustration from Figure 10 with the housing in the closed position,

25 Fig. 12 diagrammatically depicts a third exemplary embodiment of a system according to the invention, and

Fig. 13 diagrammatically depicts a fourth exemplary embodiment of a system according to the invention.

30 In the figures, reference numeral 1 denotes a production device which is designed to mould three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, in particular a meat-containing mass.

35 The production device 1 is described in detail in WO 2004/002229, the contents of which are hereby deemed to be incorporated in the present application.

The production device 1 has a mould drum 20, as will be

explained in more detail below. The production device 1 is only an example aimed at explaining the invention. The invention can also be realized using production devices of different designs, for example as shown in WO 00/30458.

5

By way of example, the invention can be used on production devices in which the mould member comprises a mould plate which is movable, for example can slide to and fro, which mould plate is provided with one or more mould cavities, which mould cavities each have an opening in at least one plate surface, the mass feed means comprising one or more mass feed members arranged along a plate surface. A production device of this type is often also used for the moulding of meat products, such as for example hamburgers. A device of this type is shown, for example, in US 4,975,039.

10

The production device 1 has a mould drum part 10 with a frame, in this case a frame which can be moved over the floor and supports a mould member designed as a mould drum 20. The mould drum 20 has a drum surface at the outer circumference which is provided with a plurality of mould cavities 21.

20

The frame 10 is provided with a horizontal mould drum fitting spindle 11, so that the mould drum 20 is rotatable with respect to the frame 10 about the spindle 11.

25

In an embodiment which is not shown, the frame may have a plurality of mould drum fitting spindles, or the frame comprises other support means for supporting the mould drum rotatably with respect to the frame.

30

At one end, the fitting spindle 11 is fixed to the frame 10, so that the mould drum 20 can be pushed onto the fitting spindle 11 and removed from the free end.

35

Furthermore, the frame 10 is provided with mould drum drive means 14 for rotating the mould drum 20. In the embodiment shown, a statically disposed distributor 14a, suitable for supplying or sucking out a liquid or gaseous forcing agent, such

as air, compressed air, water or steam or the like, is arranged in the vicinity of the mould drum drive means 14. A distributor which is known per se is provided with a pump and slots through which the forcing agent can flow. On account of the distributor
5 14a being disposed in a static position, the rotating mould drum alternately moves past forcing agent feed slots and forcing agent discharge slots.

Furthermore, the production device 1 has a mass feed part 15,
10 which is likewise designed such that it can be moved over the floor and is provided with a storage container 16 for mass, in this example a (kneaded) meat mass, pump means 17 (illustrated highly diagrammatically) for pumping the mass, and a mass feed member 18 connected to the pump means 17. At a mass feed
15 position, the mass feed member 18 bears against the outer circumference of the mould drum 20, so that (meat) mass can be fed to the passing mould cavities 21 of the rotating mould drum 20 under a filling pressure.

20 In this example, the mass feed member 18 is supported pivotably by means of a support spindle 18a on the frame 10.

Here, the frame 10 is also provided with a discharge member 25 for discharging the moulded products, in this case in the form
25 of a (mesh) belt conveyor 25 which extends as far as beneath the mould drum 2, so that products which have been ejected from the mould cavities 21 in the region of the underside of the belt pass onto the said belt conveyor 25.

30 The system comprises further product conveyor means, in this case two sets of belt conveyors 30, 31 and 32, 33, for discharging moulded products, if appropriate to further product treatment devices.

35 As has been stated, the mould drum 20 is removable. For this purpose, in Figures 1-3 a mould drum conveyor 40 is provided. This conveyor 40, shown by way of example, has a movable frame 41, a mould drum gripper 42 and lifting means 43 for moving the gripper 42 up and down.

It can be seen from Figure 2 that after the mass feed member 18 has been moved away from the mould drum 20, the conveyor 40 can be moved towards the frame 10, so that the gripper 42 can handle
5 the mould drum 20. Then, the gripper 42 is moved to the correct height, so that it bears the weight of the mould drum 20 and the mould drum 20 is slid off the spindle 11. Then, the mould drum 20 can be displaced to a mould drum cleaning device 50, which is disposed at a distance from the production device 1. It should
10 be noted that there is no need to provide a fixed arrangement, but rather, as can be seen, the device 50 is likewise of movable design. However, it is preferable for the cleaning work to be carried out at a different location from the production of foodstuffs.

15 The design of the cleaning device 50 and the cleaning of the mould drum 20 will now be explained in more detail with reference to Figures 3-5; in this context, it should be noted that this is an example of the invention.

20 As is diagrammatically depicted in Figure 3 by the arrow, the mould drum 20 is placed in the cleaning device 50 with the aid of conveyor 40. The cleaning device 50 is in this case designed to carry out a plurality of possible cleaning processes
25 substantially automatically, for example a primary cleaning process (which could be of relatively short duration) and an intensive cleaning process (for example in order to realize complete disinfection).

30 It can be seen from Figures 4a, b that the mould drum 20 is provided with mould cavities 21 each having a mould cavity wall, which is formed at least in part by a wall part with a porous structure.

35 In the preferred embodiment of the mould drum 20 shown, there is an outer drum 22, which is made at least in part (and in this example completely) from material with a porous structure, in such a manner that a mould cavity 21 has a mould cavity wall which is at least partially porous.

Inside the outer drum 22 there is positioned an inner member 23 which fits into the outer drum 22, the inner member 23, together with the adjoining surface of the outer drum 22, forming a number of passages 24 which extend from one head end 20a of the mould drum 20, so that a medium can be forced through the porous walls of the mould cavities 21 and/or suction can take place via a passage 24 of this type. The said medium, for example compressed air, can be used, for example, to release the moulded product from a mould cavity 21. The suction can be used to extract air during the filling operation and/or, for example, to suck a film or the like into the mould cavity.

In a variant which is not shown, the passages 24, if appropriate branching into passages of smaller diameter, continue as far as the mould cavity, in which case the porous wall, for example made from sintered metal, is then absent.

It can be seen from Figure 4b that the outer surface of the inner member 23 is provided with grooves which extend substantially in the axial direction and form the passages 24.

The outer drum 22 could, for example, be assembled from one or more rings of porous material, for example porous metal, in which case the one or more mould cavities 21 are formed by a material-removing machining operation, for example an electro-erosive machining operation.

If appropriate, the mould drum may comprise rings, optionally provided with mould cavities, which are releasably coupled to one another, so that a set of rings is obtained as seen in the axial direction of the mould drum. This can serve to influence the capacity of the moulding device, for example by combining rings with and without mould cavities and/or rings with different numbers and/or shapes of the mould cavities. It should be noted that when the mould member is designed as a mould plate, it is also possible to make use of an assembly of parts which forms the final mould plate.

If the outer drum 22 is made from metal, the porous structure can be sealed in the outermost part 22c of the surface of the outer drum by a lubricating action during the machining of the metal porous drum 20 in a lathe. Obviously, the sealing of the
5 said outermost part 22c could also be realized in other ways, for example by the application of a coating layer (which if appropriate partially penetrates into the porous material).

In an embodiment which is not shown, the mould drum only
10 comprises an "outer" wall, for example such as the component 22 shown in Fig. 4b. The frame may then, for example, comprise passages via which a medium (air) can be displaced to or from the mould cavities in the mould drum. By way of example, it is possible to provide for the fitting spindle to be provided with
15 passages, such as for example the passages 24. In a variant, the frame comprises the inner member 23 (optionally releasable), and the mould drum is formed by component 22, which can be removed from the inner member 23. As will subsequently be demonstrated, it would then be possible, for example, for only the "outer
20 drum" 22 to be placed in the cleaning device 50, and for a storage device for outer drums 22 to be provided.

It would also be possible to provide for the mould drum to be supported by supporting features at both head-ends of the mould
25 drum.

The cleaning device 50 is designed to force at least one cleaning liquid through the wall parts with the porous structure into the mould cavities 21. As can be seen in Figure 4a, the
30 passages 24 leading to each mould cavity 21 each have a feed opening 24a in an end face 20a of the mould drum 20.

The cleaning device 50 has a distributor 51 which comes to bear against the head-end face 20a, for the purpose of feeding
35 cleaning liquid to one or more of the passages 24. In this way, any possible contamination which has stuck to or in the porous wall part of a mould cavity 21 is forced out and discharged.

The cleaning device 50 is provided with supporting means 52 for

rotatably supporting the mould drum 20 that is to be cleaned, in this case rollers 52 which bear against the outer circumference of the drum and, via a motor (not shown), serve as drive means for driving the mould drum 20 to be cleaned in rotation. In an
5 embodiment which is not shown, the mould drum to be cleaned can be driven by a central shaft.

The cleaning device 50 has a collection trough 53 for cleaning liquid and a cover 54, so that the cleaning of the mould drum 20
10 can take place in a closed chamber.

The cleaning device 50 is designed to collect and at least partially recirculate cleaning liquid, for which purpose a pump 57 is provided. The cleaning device 50 is provided with a filter
15 for filtering the cleaning liquid, for example a coarse filter 55 and a fine filter 56.

It is preferable to provide heating means for heating the cleaning liquid. Furthermore, there are means for mixing one or
20 more chemicals with a cleaning liquid, for example a disinfectant, stored, for example, in containers 58.

Spraying means 59 are provided here for an initial coarse cleaning.
25

In one possible cleaning process, first of all the outer side of the drum is rinsed by the sprayers 59, followed by rinsing with cold water (together with a suitable cleaning agent) via the passages 24, followed by disinfection with water provided with
30 suitable chemicals and a final rinse via the passages and on the outside with cold water. As an alternative, one or more steps could also be carried out using hot water (40-90 degrees Celsius).

35 The cleaning could also comprise descaling of the mould member, for example using a suitable acid, which may be of relevance in particular to mould cavities with a porous wall structure.

In an embodiment which is not shown, the cleaning device

comprises inspection means. These inspection means, for example having a digital (infrared) camera with associated image-processing means, can monitor the cleaning and also the state of the mould drum. By way of example, it is possible to detect
5 damage and/or wear to the drum. These inspection results can be stored in a memory and if appropriate interpreted in combination with the use/cleaning history, for example in order to determine the expected service life.

10 Furthermore, the system comprises a second cleaning device 60, which is designed to clean that part of the production device 1 which bears the mould drum 20, in particular after the said mould drum 20 has been removed. That part of the device 10, after all, also becomes soiled during production.

15 As can be seen from Figures 1 and 6, in this example the cleaning device 60 is of movable design, in such a manner that the cleaning device 60 can be placed against that part of the production device 1 which is to be cleaned.

20 The cleaning device 60 comprises a housing 61, which can form a closed chamber around that part of the production device that is to be cleaned, in order for a cleaning process to be carried out in the said closed chamber.

25 In this example, the said housing 61 - when it is bearing against a corresponding part of component 10 (cf. Figure 7) - surrounds the fitting spindle 11 for the drum and the discharge belt 25 as well as the support spindle 18a. In this case, the
30 underside of the housing 61 forms a collection trough 62 for cleaning liquid (that is to be recirculated). One or more sprayers or other similar devices which spray out optionally heated cleaning liquid may be provided in the cleaning device 60. The device 60 may likewise be provided with one or more
35 filters, additions of chemicals, etc. It is preferable for the cleaning device also to be able to carry out a number of possible cleaning processes as desired. It is preferable for this cleaning device likewise to comprise inspection means (not shown) for inspecting the production device, so that the

cleaning and the state of the device can be monitored.

Figure 8 shows a variant of the cleaning device 60, which device 60' is arranged in a fixed position, so that that part 10 of the production device 1 which is to be cleaned is moved to the
5 cleaning device 60'. In this case too, a housing 61' forms a protected chamber around the components to be cleaned.

Figure 9 shows a system in which there is a storage device 80
10 for storing a plurality of mould members, in this example mould drums 20. The storage device 80 forms a storage chamber which is substantially closed off with respect to the outside for storing the mould members, for example the mould drums 20. The storage device 80 comprises associated conveyor means for displacing the
15 mould members 20 between a receiving and/or release position and one or more storage positions.

In this example, the storage device 80 is combined with a mould drum cleaning device 100.

20

The storage device 80 is located at a distance from the production device 1, and there are conveyor means 110 for conveying the mould drums 20 between the storage device 80 and the production device 1.

25

These conveyor means 110 in this case comprise an overhead conveyor 111, along which the gripper 42 for a mould drum 20 can be displaced. A drive motor 112 is provided for this purpose. The gripper 42 can remove a mould drum 20 from the device 1 and
30 move it towards the storage device 80, where the mould drum 20 is transferred by internal conveyor means associated with the storage device. In this example, the storage device 80 is provided with an endless suspended track 81 with carriers 82 which can be displaced along the said track 81 and can each
35 carry a drum 20. The cleaning device 100 is located along the track 81, for example at the location where the mould drums 20 first reach the storage device 80 after use.

It can be seen from Figure 9 that the cleaning device 60'' for

the production device 1 likewise has associated conveyor means, which in this case are designed as an extension of the overhead conveyor 111. This conveyor 111 can move the cleaning device 60'' between an inactive position at a distance from the production device 1 (cf. Figure 9) and an active position at the production device (cf. Figures 10 and 11).

The cleaning device 60'' has two housing parts 61a'' and 61b'', which can move with respect to one another between an open position (Figure 10) and a closed position (Figure 11). In the open position, the cleaning device 60'' can be fitted to that part 10 of the production device 1 which is to be cleaned, and then the parts to be cleaned (spindle 11, conveyor belt 25) can be enclosed and a cleaning treatment carried out.

In this example, the housing parts 61a'' and 61b'' can be displaced along a guide 114 which is located at the top side of the housing parts. The guide 114 can in turn be displaced along the conveyor 111.

Figure 12 shows a system which largely corresponds to the system shown in Figures 9-11. In Figure 12, there is a mould drum storage device 80' where mould drums 20 lie in racks or the like. A conveyor means (not shown) of the storage device is responsible for putting in and removing mould drums 20. Furthermore, there is a cleaning device 100' combined with the storage device 80''. As can be seen, the gripper 42 first releases the mould drum 20 at this cleaning device 100'.

Figure 13 shows a system which largely corresponds to the systems shown in Figures 9-12. The storage device 80'' has a paternoster for the mould drums 20.

For expedient production of three-dimensional food products by means of a system which uses exchangeable mould members, such as the mould drums which have been explained with reference to the drawing, it is preferable to provide for each removable mould member, in the examples mould drum 20, to be provided with an identification.

By way of example, each mould drum 20 is provided with an optically readable code (such as a barcode), an electronic transponder (which can be read and if appropriate written
5 remotely), or other identification characteristic. The said characteristic is preferably unique to each mould member.

The system is in this case provided with suitable recognition or reading means for recognizing the identification of a mould
10 member. If appropriate, it is also possible to provide writing means for adapting the identification characteristic, for example when using a writable transponder.

Figure 1 indicates that the part 10 of the production device 1
15 is provided with recognition means for, preferably automatically, recognizing the identification of a mould drum 20, for example a reader 120 for a transponder which is arranged at a suitable location, for example at an head-end face, on the mould drum 20.

20 This reader 120 is connected to a control device 130 of the system, which in this case has an associated computer 131. A history of the use of the mould drum 20 is stored for each mould drum 20 in the memory of the computer 131. Partially on this
25 basis, it is possible to determine the instant at which a mould drum 20 has to be cleaned, and if appropriate by what cleaning process. For example, the cleaning process can be matched to the type of mould drum, and the way in which each mould drum is cleaned can be determined separately.

30 The history can define the use of the mould drum 20, for example in conjunction with the identification provided to the products ultimately produced, which is useful, for example, in the context of product safety (for example if products need to be
35 recalled).

In one variant, the mould member cleaning device is (also) provided with recognition means for recognizing the identification of a mould member, such as reader 121 in

Figure 9.

In Figure 9, a further reader 122 serves as a recognition means for the mould drums 20 for correct operation of the storage
5 device 80.

It is preferable, therefore, to provide storage for the history of a mould member, in which context the cleaning of the mould member is also stored. It is preferable for at least the times
10 and the associated designation of the cleaning processes carried out to be stored.

The identification of mould members 20 allows optimum efficiency of the system to be achieved, in which context the correct
15 cleaning of the mould members 20 can be ensured and documented. Furthermore, the cleaning of component 10 using cleaning device 60 can also be stored, so that a complete picture of the cleaning of the parts of the system which may become contaminated is obtained.

20

The use of, preferably automated, storage and conveyor means for the mould members allows their quality to be ensured and a high production rate to be achieved. Moreover, a change of mould members, for example when switching to a different shape of
25 product, can be carried out quickly and with little operator intervention.

CLAIMS

1. System for moulding three-dimensional products from a mass
5 of one or more food starting materials which are suitable for
consumption, in particular human consumption, which system
comprises:
- a production device having:
 - a frame,
10 - a mould member provided with at least one mould
cavity, the frame supporting the mould member,
 - mass feed means for feeding the mass to the one or
more mould cavities of the mould member,
the mould member comprising a mould drum which is rotatable with
15 respect to the frame about an associated axis of rotation, which
mould drum is provided with one or more mould cavities, which
mould cavities each have an opening in at least one drum
surface, the mass feed means comprising one or more mass feed
members disposed along a drum surface,
20 and the mould drum comprising an outer drum which is made at
least partially from material with a porous structure, in such a
manner that a mould cavity has a mould cavity wall which is at
least partially porous,
and an inner member also being provided, which inner member fits
25 into the outer drum, the inner member, preferably together with
the adjoining surface of the outer drum, forming one or more
passages which extend from one head-end of the mould drum, so
that a medium can be forced through the porous mould cavity wall
and/or suction can take place via a passage of this type.
30
2. System according to claim 1, in which the outer surface of
the inner member is provided with grooves which extend, for
example, substantially in the axial direction and form the
passages.
- 35
3. System according to claim 1 or 2, in which the outer drum
is composed of one or more rings of porous material, for example
porous metal, with the one or more mould cavities being formed
by a material-removing machining operation, for example an

electro-erosive machining operation.

4. System according to claim 3, in which the porous structure is sealed in the outermost surface of the outer drum, for example by a lubricating action during the machining of a metal porous ring in a lathe.

5. Mould drum designed and intended for a system for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises:

- a production device having:
 - a frame,
 - a mould member provided with at least one mould cavity, the frame supporting the mould member,
 - mass feed means for feeding the mass to the one or more mould cavities of the mould member,
- the mould member comprising a mould drum which is rotatable with respect to the frame about an associated axis of rotation, which mould drum is provided with one or more mould cavities, which mould cavities each have an opening in at least one drum surface, the mass feed means comprising one or more mass feed members disposed along a drum surface,
- and the mould drum comprising an outer drum which is made at least partially from material with a porous structure, in such a manner that a mould cavity has a mould cavity wall which is at least partially porous,
- and an inner member also being provided, which inner member fits into the outer drum, the inner member, preferably together with the adjoining surface of the outer drum, forming one or more passages which extend from one head-end of the mould drum, so that a medium can be forced through the porous mould cavity wall and/or suction can take place via a passage of this type.

6. Mould drum according to claim 5, in which the outer surface of the inner member is provided with grooves which extend, for example, substantially in the axial direction and form the passages.

7. Mould drum according to claim 5 or 6, in which the outer drum is composed of one or more rings of porous material, for example porous metal, with the one or more mould cavities being formed by a material-removing machining operation, for example
5 an electro-erosive machining operation.

8. Mould drum according to claim 7, in which the porous structure is sealed in the outermost surface of the outer drum, for example by a lubricating action during the machining of a
10 metal porous ring in a lathe.

9. Mould member cleaning device designed and intended for a system according to one or more of the preceding claims.

15 10. Production device cleaning device designed and intended for a system according to one or more of the preceding claims.

11. Method for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for
20 consumption, in particular human consumption, in particular a mass of meat, in which use is made of a system according to one or more of the preceding claims.

12. System for moulding three-dimensional products from a mass
25 of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises:

- a production device having:

30 - a frame,
- a mould member provided with at least one mould cavity, the frame supporting the mould member,
- mass feed means for feeding the mass to the one or more mould cavities of the mould member,
the system furthermore comprising at least one cleaning device
35 for cleaning one or more parts of the production device which come into contact with the mass.

13. System according to claim 12, in which the mould member is removable from the frame.

14. System according to claim 12 or 13, in which the mould member is moveable with respect to the frame, the production device being provided with drive means for the mould member.

5

15. System according to claim 14, in which the mould member comprises a mould drum which is rotatable with respect to the frame about an associated axis of rotation, which mould drum is provided with one or more mould cavities, which mould cavities
10 each have an opening in at least one drum surface, the mass feed means comprising one or more mass feed members arranged along a drum surface.

16. System according to claim 15, in which the frame defines a
15 substantially horizontal axis of rotation for the mould drum.

17. System according to claim 16, in which the frame comprises a fitting spindle which at one end is fixed to the frame, so that the mould drum can be slid onto the fitting spindle.

20

18. System according to claim 14, in which the mould member comprises a moveable mould plate which can, for example, be slid to and fro, which mould plate is provided with one or more mould cavities, which mould cavities each have an opening in at least
25 one plate surface, the mass feed means comprising one or more mass feed members arranged along a plate surface.

19. System according to one or more of the preceding claims 12-18, in which a mould member cleaning device is designed to clean
30 the mould member.

20. System according to claims 13 and 19, in which the mould member cleaning device is arranged at a distance from the production device.

35

21. System according to claim 20, in which the system furthermore comprises conveyor means for conveying the mould member between the production device and the mould member cleaning device.

22. System according to one or more of the preceding claims 12-21, in which the system comprises a production device cleaning device for cleaning one or more parts of the production device.

5

23. System according to claims 13 and 22, in which the production device cleaning device is designed to clean one or more parts of the production device after removal of the mould member.

10

24. System according to claim 23, in which the production device cleaning device has associated conveyor means for moving the said production device cleaning device between an inactive position at a distance from the production device and an active

15 position at the production device.

25. System according to one or more of claims 22-24, in which the production device cleaning device comprises a housing which can form a closed chamber around that part of the production device that is to be cleaned, for the purpose of carrying out a cleaning process in the said closed chamber.

20

26. System at least according to claim 13, in which the system furthermore comprises a storage device for storing a plurality of mould members.

25

27. System according to claim 26, in which the storage device is combined with the mould member cleaning device.

28. System according to claim 26 or 27, in which the storage device is arranged at a distance from the production device, and in which conveyor means are provided for conveying the mould members between the storage device and the production device.

30

29. System at least according to claim 1, in which each removable mould member is provided with an identification, and in which the system comprises recognition means for recognizing the identification of a mould member.

35

30. System according to claim 29, in which the production device is provided with recognition means for recognizing the identification of a mould member.

5 31. System according to claim 29 or 30, in which the mould member cleaning device is provided with recognition means for recognizing the identification of a mould member.

10 32. System according to one or more of claims 29-31, in which the system furthermore comprises a memory for storing at least one history of a mould member.

15 33. System according to claim 32, in which the history comprises the use of the mould member.

34. System according to claim 32 or 33, in which the history comprises the cleaning of the mould member.

20 35. System according to one or more of claims 32-34, in which the system comprises a computer with a memory which is designed to store the history of one or more mould members.

25 36. System according to one or more of claims 29-35, in which the system comprises a plurality of mould members and each mould member is provided with a unique identification.

30 37. System according to one or more of the preceding claims 12-36, in which a cleaning device is designed to carry out at least one cleaning process substantially automatically.

38. System according to claim 37, in which a cleaning device is designed to carry out one of several possible cleaning processes as desired.

35 39. System according to claims 32, 34 and 38, in which the history of a mould member includes at least the times and the associated designation of the cleaning processes carried out.

40. System according to claim 38 or 39, in which the cleaning

device is designed to carry out at least a primary cleaning process and an intensive cleaning process.

41. System according to one or more of the preceding claims 12-
5 40, in which a cleaning device is designed to treat the one or more parts that are to be cleaned with at least one cleaning liquid.

42. System according to claim 41, in which the cleaning device
10 is designed to collect and at least partially recirculate the cleaning liquid.

43. System according to claim 42, in which the cleaning device
is provided with a filter for filtering the cleaning liquid, for
15 example a coarse filter and a fine filter.

44. System according to one or more of claims 41-43, in which
the cleaning device is provided with heating means for heating
cleaning liquid.

20

45. System according to one or more of claims 41-44, in which
the cleaning device is provided with means for mixing one or
more chemicals with a cleaning liquid, for example a
disinfectant.

25

46. System according to one or more of the preceding claims 41-
45, in which the mould member is provided with one or more
passages which are in communication with each mould cavity of
the mould member, and in which the cleaning device can be
30 coupled to the said one or more passages, in such a manner that
cleaning liquid can flow through the said passages to the mould
cavity.

47. System according to one or more of the preceding claims 12-
35 46, in which the mould member is provided with one or more mould
cavities each with a mould cavity wall, which is formed at least
in part by a wall part with a porous structure.

48. System according to claims 46 and 47, in which the cleaning

device is designed to force cleaning liquid through the wall part with the porous structure into the mould cavity.

49. System according to claim 47 or 48, in which the passages
5 leading to each mould cavity each have a feed opening in a surface of the mould member, for example in an end face of the mould drum, and in which the cleaning device has a distributor for feeding cleaning liquid to one or more of the passages.

10 50. System at least according to claim 15, in which the mould member cleaning device is provided with support means for rotatably supporting the mould drum that is to be cleaned, and in which there are also drive means for driving the mould drum to be cleaned in rotation.

15 51. System according to claim 21 and/or 24 and/or 28, in which the conveyor means comprise a conveyor track, preferably an overhead conveyor track for the mould members.

20 52. System according to claim 21 and/or 24 and/or 28, in which the conveyor means comprise a frame which can be moved over the floor.

25 53. System according to claim 51 or 52, in which the conveyor means comprise a gripper member for gripping a mould member, as well as associated orientation means, for example lifting means for moving the gripper member up and down.

30 54. System according to claim 26, in which the storage device is designed to store a plurality of mould members, and in which the storage device comprises associated conveyor means for displacing the mould members between a receiving and/or release position and one or more storage positions.

35 55. System according to claim 54, in which the storage device comprises a conveyor with an endless conveyor track, for example a suspended conveyor track or a paternoster, provided with carriers which are each designed to receive a mould member.

56. System according to claim 54, in which the storage device forms at least one storage chamber which is substantially closed with respect to the outside for storing the mould members, for example the mould drums.

5

57. System according to claim 25, in which the production device cleaning device comprises a housing assembled from a plurality of parts which is moveable with respect to one another between a closed position and an open position, so that in the open position the housing can be fitted to the production device, after which the closed position is adopted and the cleaning can take place.

58. System according to claim 25, in which the production device comprises discharge means for discharging moulded products, for example a belt conveyor, and in which the production device cleaning device is designed at least to clean the discharge means.

59. System for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises:

- a production device having:

25

- a frame,

- a mould member provided with at least one mould cavity, the frame supporting the mould member,

- mass feed means for feeding the mass to the one or more mould cavities of the mould member,


30 - in which the mould member is removable from the frame, and
- in which the system furthermore comprises a storage device for storing a plurality of mould members.


60. System for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises:


- a production device having:


- a frame,

- a mould member provided with at least one mould cavity, the frame supporting the mould member,
 - mass feed means for feeding the mass to the one or more mould cavities of the mould member,
 - 5 - in which the mould member is removable from the frame, and
 - in which each removable mould member is provided with an identification, and in which the system comprises recognition means for recognizing the identification of a mould member.
- 10 61. System for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for consumption, in particular human consumption, which system comprises:
- a production device having:
 - 15 - a frame,
 - a mould member provided with at least one mould cavity, the frame supporting the mould member,
 - mass feed means for feeding the mass to the one or more mould cavities of the mould member,
 - 20 - in which the mould member is removable from the frame, and
 - in which the system furthermore comprises a memory for storing at least one history of a mould member.
62. Mould drum designed and intended for a system according to
- 25 one or more of the preceding claims.
63. Mould member cleaning device designed and intended for a system according to one or more of the preceding claims.
- 30 64. Production device cleaning device designed and intended for a system according to one or more of the preceding claims.
65. Method for moulding three-dimensional products from a mass of one or more food starting materials which are suitable for
- 35 consumption, in particular human consumption, in particular a meat mass, in which use is made of a system according to one or more of the preceding claims.















FIG. 5










FIG. 9






FIG. 11








FIG. 13

