



US008820020B2

(12) **United States Patent**  
**Koch et al.**

(10) **Patent No.:** **US 8,820,020 B2**  
(45) **Date of Patent:** **Sep. 2, 2014**

(54) **HIP, RIDGE OR RAKE SHINGLES AND STACKS OF HIP, RIDGE OR RAKE SHINGLES**

USPC ..... **52/518**; 552/520; 552/543; 552/276; 552/527; 552/557

(71) Applicants: **Stephen A. Koch**, Collegeville, PA (US); **Husnu M. Kalkanoglu**, Swarthmore, PA (US); **Robert L. Jenkins**, HoneyBrook, PA (US); **Gregory F. Jacobs**, Oreland, PA (US)

(58) **Field of Classification Search**  
USPC ..... 52/518, 520, 543, 276, DIG. 16, 57, 52/557, 527  
See application file for complete search history.

(72) Inventors: **Stephen A. Koch**, Collegeville, PA (US); **Husnu M. Kalkanoglu**, Swarthmore, PA (US); **Robert L. Jenkins**, HoneyBrook, PA (US); **Gregory F. Jacobs**, Oreland, PA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

|              |      |         |                 |       |         |
|--------------|------|---------|-----------------|-------|---------|
| 4,404,783    | A *  | 9/1983  | Freiborg        | ..... | 52/518  |
| 2004/0258883 | A1 * | 12/2004 | Weaver          | ..... | 428/143 |
| 2005/0274090 | A1 * | 12/2005 | Johnson et al.  | ..... | 53/442  |
| 2007/0144077 | A1 * | 6/2007  | Quaranta et al. | ..... | 52/43   |

\* cited by examiner

*Primary Examiner* — Mark Wendell

(73) Assignee: **CertainTeed Corporation**, Valley Forge, PA (US)

(74) *Attorney, Agent, or Firm* — Paul & Paul

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(57) **ABSTRACT**

(21) Appl. No.: **13/628,163**

A plurality of hip, ridge or rake shingles, and the shingles produced thereby and stacks and packages of such shingles are provided.

(22) Filed: **Sep. 27, 2012**

An adhesive impregnated mat is moved longitudinally, and granules are provided onto adhesive, in predetermined bands. An overlay band of adhesive, continuous or discontinuous is provided, with granules thereon, increasing the thickness of the shingle material being made, in predetermined bands, relative to the remainder of the shingle material. The shingle material is slit longitudinally, and one portion can be laminated to another portion, preferably creating a multiple-ply laminated shingle material with thickened overlay portions and optionally with shadow line portions. The material is then slit longitudinally, and cut transversely into a plurality of hip, ridge or rake shingles, which may be individually separated from each other, or which may comprise a plurality of connected together shingles. The shingles are then stacked and wrapped.

(65) **Prior Publication Data**

US 2013/0020381 A1 Jan. 24, 2013


**Related U.S. Application Data**

(62) Division of application No. 12/364,842, filed on Feb. 3, 2009, now Pat. No. 8,323,440.

(51) **Int. Cl.**  
**E04D 1/00** (2006.01)  
**E04D 1/30** (2006.01)  
**E04D 1/20** (2006.01)

(52) **U.S. Cl.**  
CPC .. **E04D 1/20** (2013.01); **E04D 1/30** (2013.01);  
**E04D 2001/005** (2013.01); **E04D 2001/302**  
(2013.01); **E04D 2001/305** (2013.01)

**8 Claims, 10 Drawing Sheets**






Fig. 1




Fig. 2






Fig. 3




Fig. 4




Fig. 4A




Fig. 5










Fig. 5A










Fig. 13




Fig. 14




Fig. 15

1

# HIP, RIDGE OR RAKE SHINGLES AND STACKS OF HIP, RIDGE OR RAKE SHINGLES

## CROSS-REFERENCE TO RELATED APPLICATION

This is a divisional of U.S. application Ser. No. 12/364,842, filed Feb. 3, 2009

## BACKGROUND OF THE INVENTION

In the shingle art, it is known to cover hips, ridges, and rakes of a roof with shingles.

In the past, when a roof was being shingled with multiple-tab shingles, it was common to cut or tear a single tab of a multiple-tab shingle, severing the same from the rest of the shingle, and to then use that cut-away tab as a hip, ridge, or rake shingle.

However, as demand for different aesthetic effects became popular, wherein laminated shingles having different aesthetic effects became more popular, it became desirable to have the hip, ridge, or rake shingles be consistent with the same aesthetics as the shingles covering the rest of the roof. Such laminated shingles of the hip, ridge or rake type are shown for example in U.S. Pat. Nos. Des.366,336; 4,835,929 and 6,494,010.

## SUMMARY OF THE INVENTION

The present invention is directed to a process for efficiently producing a plurality of hip, ridge or rake shingles wherein the shingles have a thickened portion along an edge and which is exposed in the installed condition of the shingles on a roof, and to provide shingles and packages of shingles made in accordance with the process.

Accordingly, it is an object of this invention to provide a novel process for producing laminated hip, ridge or rake shingles.

It is a further object of this invention to achieve the above object, wherein an overlay strip is provided on an upper, exposed surface of the shingle, with the overlay being comprised of an overlay adhesive with overlay granules adhered thereto.

It is a further object of this invention to provide an indefinite length of fibrous sheet having different portions that comprise an anterior layer of shingle material and other portions comprising a posterior layer of shingle material, and wherein the layers of shingle material are laminated and then transversely cut to produce at least a pair of laminated shingles, substantially simultaneously, side-by-side as the laminated layers of shingle material are advanced longitudinally.

It is a further object of this invention to accomplish the above object, wherein a plurality of overlay strips of adhesive and granules are provided on the anterior layer of shingle material, as the length of fibrous sheet moves in a longitudinal direction.

It is a further object of this invention to accomplish the above objects, wherein each posterior portion of the sheet of shingle material has a width that is of greater transverse width than the transverse width of the anterior portion of the sheet of shingle material, whereby the shingles produced thereby have a portion of the posterior layer along an edge of the anterior layer that is uncovered by the anterior layer.

It is another object of this invention to produce shingles in accordance with the objects above, wherein at least one

2

shadow line is provided, for ornamental or aesthetic effect near an edge of the anterior shingle layer.

It is yet another object of this invention to produce laminated hip, ridge, or rake shingles, that are adhered together in such a way that, as the laminated shingles are bent into the approximate shape of an inverted V, the shingle layers can have some relative movement, to facilitate a smooth bending operation.

It is another object of this invention to produce laminated hip, ridge, or rake shingles whereby a plurality of shingles remain connected together, but have perforation means facilitating their ready separation for installation on a roof.

It is a further object of this invention to provide stacks of shingles in accordance with the objects set forth above.

Other objects and advantages of the present invention will be readily understood upon a reading of the following brief descriptions of the drawing figures, the detailed descriptions of the preferred embodiments, and the appended claims.

## BRIEF DESCRIPTION OF THE DRAWING FIGURES

FIG. 1 is a schematic top plan view of a portion of the shingle process in accordance with this invention.

FIG. 1A is a schematic top plan view of a continuation of the shingle process illustrated in FIG. 1.

FIG. 2 is a schematic front elevational view of the portion of the shingle process illustrated in FIG. 1, taken along the line II-II of FIG. 1.

FIG. 2A is a schematic front elevational view of the portion of the shingle process illustrated in FIG. 1A, taken generally along the line IIA-IIA of FIG. 1A.

FIG. 3 is a perspective view of a pair of opposed rollers having transverse cutters thereon, for transversely cutting layers of shingle material.

FIG. 4 is an illustration similar to that of FIG. 3, but wherein one of the rollers has spaced-apart cutters, for incompletely severing some of the shingle material being cut thereby.

FIG. 4A is an illustration somewhat similar to those of FIGS. 3 and 4, but wherein the upper roller includes sets of blades of different depth, whereby, along the length of the upper roller, some blades can cut through a shingle, such as a laminated shingle, through a plurality of layers, and other blades are of a shallower depth to only cut through a single layer of the laminated layers, and wherein the opposing roller is of the anvil type.

FIG. 5 is an end view of each of the pairs of rollers of FIGS. 3 and 4, illustrating the manner in which such cutters engage laminated shingle material (shown in phantom) therebetween.

FIG. 5A is an illustration similar to that of FIG. 5, but wherein the lower roller is an anvil roller.

FIG. 6 is a top perspective view of a bent hip, ridge, or rake shingle, in accordance with this invention.

FIG. 7 is a sectional view, taken through the shingle of FIG. 6, generally along the line VII-VII of FIG. 6.

FIG. 8 is a top perspective view of an array of hip, ridge, or rake shingles in accordance with this invention, as they would appear in the installed condition on a roof.

FIG. 9 is an enlarged detail view of a portion of FIG. 8, showing the details thereof in greater clarity.

FIG. 10 is a top plan view of three connected-together laminated shingles, in accordance with this invention, prior to their final separation, and wherein a continuous overlay comprised of adhesive and granules imbedded therein is shown across the three shingles of FIG. 10, with a shadow band

therebeneath, all adjacent an upper edge of the group of three shingles of FIG. 10, with each of the shingles having a portion of laminating adhesive shown in phantom, connecting the laminated layers together.

FIG. 11 is an illustration like that of FIG. 10, but wherein the overlay strip is discontinuous, in the form of longitudinally spaced-apart overlays.

FIG. 12 is an illustration of the shingles of FIG. 10, after their separation.

FIG. 13 is a stack of shingles of the type of FIG. 10, shown with wrapping material being applied thereto, in phantom, for wrapping the stack of shingles into a package.

FIG. 14 is an illustration similar to that of FIG. 13, but for the separated shingles of FIG. 12.

FIG. 15 is a side elevational view of shingles of the type illustrated in FIGS. 13 and 14, packaged together, but wherein adjacent shingles are packaged back-to-back, showing adhesive strips on the back of each laminated shingle, covered by a release strip of a next-adjacent shingle, and wherein the packaging for the shingles of FIG. 15 is illustrated in phantom.

#### DETAILED DESCRIPTIONS OF THE PREFERRED EMBODIMENTS

Referring now to the drawings in detail, reference is first made to FIGS. 1 and 2. A sheet 20 comprising an indefinite length of fibrous material, such as organic or inorganic mat, is provided, which may or may not be provided in the form of a roll 21, and which is impregnated or will become impregnated with a preferably bituminous material such as asphalt. The mat 20, as it travels in its longitudinal path 22, may pass over a roller 23, to pass beneath another transverse roller 24 to impregnate at least the lower surface of the fibrous sheet 20 with an adhesive 25, that also will preferably be a bituminous material such as asphalt, from a transverse tank 26, with the fibrous sheet 20 then passing over another transverse roller 27, to be delivered beneath another roller 28, disposed in a particle application trough 30, or the like, for adherence of tiny granule particles such as sand, mica, or the like to the undersurface 31 of the fibrous sheet 20.

It will be understood that other techniques for applying an adhesive to the fibrous sheet 20 may be employed, such as by running the sheet 20 through a bath of adhesive, that, again, will preferably be of a bituminous material such as asphalt. Similarly, other techniques for applying tiny granules such as sand, mica or the like to the undersurface 31 of the fibrous sheet 20 may likewise be employed, as alternatives. As a further alternative, the tiny granules could be applied at a different time, for example, at a later time.

The fibrous sheet 20 may then pass over and under another series of rollers 32, 33, to a location where an adhesive such as asphalt or other bituminous material is applied to the top surface 34 of the sheet 20.

In the embodiment of FIGS. 1 and 2, such adhesive is applied from a transverse adhesive trough 35 by applying the adhesive 36 to a roller 37 arranged in the trough 35, which, in turn, applies the adhesive to another, larger roller 38, which applies the adhesive as the upper surface 34 as the fibrous sheet 20 passes through the nip 40 between the large roller 38 and another roller 41.

The thus impregnated sheet 20 then passes around another transverse roller 42 before traveling beneath a granule applicator 43, for deposit of granules 44 on an upper surface 45 of the sheet 20.

The granule applicator 43 is divided into six application zones 47, 48, 50, 51, 52 and 53, separated by walls 54, 55, 56, 57, 58, 60 and 61.

Granules from zone 47 are preferably post-industrial granules or lower cost or scrap granules or recycled granules and are shown as dark granules and are deposited in a wide longitudinal band 62, shown at the lower right of FIG. 1, from between walls 54 and 55 of granule applicator 43. The band 62 of darker granules will thus be on the front surface of the posterior shingle layer after longitudinal cutting and lamination of the anterior and posterior shingle layers together, as will be discussed hereinafter.

Granules from zone 48, between walls 55 and 56, are shown as lighter colored granules, but, because they will be covered in the installed condition, could be granules like those from zone 47. The granules from zone 48 are deposited in a longitudinal band 63, on a portion of the sheet 20 that will form a component of an anterior shingle layer.

Preferably dark granules will be deposited from zone 50 between walls 56 and 57, to form a longitudinal shadow band 64.

Preferably lighter granules are deposited from zone 51 of the granule applicator 43, from between walls 57 and 58, to form a longitudinal band 62' of such lighter granules or granules of a different shade or color than those forming the band 63 on a portion of the sheet 20 that will also comprise the upper surface of an anterior shingle layer.

Another longitudinal shadow line band 66 of dark granules is formed on the upper surface of the sheet 20, from the zone 52 of the granule applicator 43 that is between walls 58 and 60, to provide another shadow band of darker granules.

Another longitudinal band of granules 67 is formed by dropping granules from the zone 53 of the granule applicator 43, between walls 60 and 61, with the longitudinal band 67 being similar to the longitudinal band 63. The granules from band 67, because they will be covered in the installed condition, could likewise be granules like those from zone 47.

After the above-discussed granules are dropped onto the upper surface of the fibrous sheet 20 as described above, from granule applicator 43, the sheet 20 passes beneath a roller 68, to be delivered to nips 70 beneath adhesive applicator rollers 71 and 72 that receive adhesive via rollers 73 and 74 carried on shaft 75. The rollers 73 and 74 are, in turn, engaged with adhesives 76 in adhesive troughs 77, 78, to apply two continuous or discontinuous parallel bands of adhesive to the upper surface of the portion of the sheet 20 that will comprise the anterior shingle layers.

The sheet 20 with the two narrow bands of adhesive applied via rollers 71 and 72, then passes beneath roller 80, as the sheet 20 moves longitudinally rightward as shown in the direction of the arrow 81 in FIG. 2.

It will be noted that the roller 80 has two necked-down portions of reduced diameter, 82 and 83, where the longitudinal strips of adhesive have been applied via rollers 71 and 72, to keep adhesive from being smeared by the surface of the roller 80, as the thin adhesive bands pass beneath the roller 80.

The sheet 20 is thus delivered beneath overlay granule applicators 84 and 85, which deposit overlay granules, preferably dark in shading, onto the thin longitudinal bands of adhesive that has been applied via adhesive applicator rollers 71 and 72, as shown at 86 at the right end of FIG. 2.

Alternatively, the sheet 20 could be routed in a different way, so that an adhesive such as that 76 is applied as contact with a roller occurs, prior to the granule application as shown at 86.

Continuing on to FIGS. 1A and 2A, the sheet 20 then continues in the longitudinal direction 87 shown in FIG. 1A,

5

such that its portion **62**, shown as darker in FIGS. **1** and **1A** for visual differentiation between the layers, passes beneath an adhesive applicator **88**, by means of which transversely spaced-apart adhesive zones **90, 91** are applied as the sheet **20** passes therebeneath. The adhesive zones **90, 91** are not only

transversely spaced-apart, but are longitudinally spaced-apart, as shown. The sheet **20** then passes between a pair of slitter rollers **92, 93**, carried by shafts **89, 89'**, where the sheet **20** is longitudinally slit, with the slit continuing at **94**, and with the sheet then continuing, to pass over roller **99**, with the posterior sheet P being brought beneath the anterior sheet A (shown as the lighter sheet in FIG. **1A**) and the two sheets P, A are laminated together by means of the adhesive zones **90, 91**, pressed together by passing through the nip **95** between upper and lower rollers **96, 97**. The thus laminated sheet **100** is brought together, as shown at the right end of FIG. **1**. Sheet P follows the path of arrow X while sheet A follows the path of arrow Y as the sheets P, A are laminated together. The roller **93** can optionally be an anvil roller, which the blade of the roller **92** can cut against.

The laminated sheet **100** then passes beneath another pair of opposed slitter rollers **101, 102**, whereby the laminated sheet is slit into two, along slit line **103**, yielding transversely adjacent laminated sheets **104** and **105**, as viewed at the right end of FIG. **1A**. One of the rollers, such as the roller **102**, for example, could be an anvil roller, against which a blade of a slitter roller **101** operates, if desired.

Alternatively, the slitter rollers **101, 102** could be carried by the shaft **89, 89'**, or by some other shaft (not shown) to slit the sheet **20** longitudinally upstream of the lamination step, into two parallel anterior layers and two parallel posterior layers, which would then be laminated together.

As a further alternative, the sheet **20** could be used to produce only an anterior sheet A. Such may be used if it were desired to have anterior layers only, with overlays thereon, with or without shadow bands thereon, to produce a single thickness layer of hip, ridge or rake shingle, which would still have a greater apparent thickness, due to the overlay thereon.

As a further alternative in accordance with this invention, the sheet **20** could be slit longitudinally into more than two distinct layers by means of multiple opposed slitter rollers such as those **92, 93**, to yield more than two parallel layers, such that when those parallel layers are brought together and laminated, the lamination would comprise more than two laminated layers, at least one of which would have the band or bands of overlay comprised of adhesive and granules thereon.

The adjacent laminated sheets **104** and **105** then pass beneath a pair of transverse cutter rollers **106** and **107**, each shown as having three transverse cutters **108, 110** disposed preferably  $120^\circ$  apart around rollers **106, 107**, with the rollers **106, 107** being sized to cut the laminated sheets **104, 105** transversely into predetermined sizes, whenever cutters **108, 110** meet each other, to cut the laminated sheets **104, 105** into either separate longitudinally adjacent shingles **111** of desired size, or into connected-together longitudinally adjacent shingles of desired size, still connected by means of incompletely severed shingles. Alternative cutting arrangements will be discussed hereinafter.

It will be apparent throughout FIGS. **1** and **2** and throughout FIGS. **1A** and **2A**, that the various rollers are all shaft-mounted, and that in many cases, the rollers will be positively driven via motors or the like. However, it will likewise be understood that in many cases some of the rollers that are not actually used to longitudinally move the sheet forward in the direction of the arrow **22**, for example, can be idler rollers, rather than motor-driven rollers.

6

Further, while the rollers are shown for cutting processes, other cutting means may be employed, such as, for example, stamping blades, water jets, laser cutters, and other cutting means known in the art.

While the illustrations of FIGS. **1, 1A, 2** and **2A** illustrate an apparatus for producing a pair of laminated sheets **104** and **105**, it will be understood that such depends on the width of the machine. For example, a wider machine could produce three or four or more such sheets similar to sheets **104, 105**, as alternatives.

In any event, the lines of partial or complete severance will be shown at **112, 113**, and will be addressed hereinafter.

With reference now to FIG. **3**, it will be seen that the rollers **106, 107** are shown together, such that their cutters **108, 110**, are transversely continuous, to completely sever through both anterior and posterior shingle layers, as the continuous laminated shingle sheet portions **104, 105** pass therebetween.

With reference to FIG. **4**, the upper and lower rollers **107', 106'** likewise have transversely continuous cutters **108', 110'**, but for the roller **106**, at two of the locations around the roller that are approximately  $120^\circ$  spaced-apart, there are provided a plurality of discontinuous transverse cutter teeth **109**. The cutter teeth **109**, when engaging the posterior layer of shingle material, will incompletely sever the posterior layer of shingle material, whereas the cutters **108'** and **110'** will completely sever the anterior and posterior layers of shingle material where they engage the shingle material, such that every third laminated shingle will be completely separated, to yield groups of three laminated shingles that are still connected together by portions of material in the posterior shingle layer that are not severed, because of the cutter-free spaces **115** between spaced-apart cutter teeth **109**.

With reference now to FIG. **4A**, it will be seen that the lower roller **106''** is an anvil roller, not having cutters thereon. The upper roller **107''** provides the cutting. In this arrangement, some of the cutting teeth **109''** are larger, for cutting either completely through, or at least deeper through the shingle material passing between the rollers **106'', 107''**, with intervening teeth **109''** not protruding as much from the surface of the roller **107''** as the teeth **109''**, such that the teeth **109''** make an incomplete cut depthwise through the material passing between the rollers **106'', 107''**. Thus, if the material passing between the rollers **106'', 107''** is, for example, a two layer laminate, the teeth **109''** may cut completely through both layers of the laminate, with the shallower teeth **109''** cutting through only one layer of the laminate, and with every third cutting area around the roller **107''** having a cutting tooth **110''** of sufficient depth to cut completely through both layers of, for example, a two-layer laminate, for completely severing through every third hip, ridge or rake shingle, so that multiple shingles can remain together, only partially severed, for packaging and/or transport purposes.

Alternatively, shallow teeth **109'''** and full cut teeth **109'''** could be connected to one another rather than separated as is depicted in FIG. **4A**.

It will be understood that the present invention is not limited to having only three connected-together shingles, between complete separations of shingles, but rather two or four, or even a greater number of shingles could be connected together, between locations of complete transverse cuts, depending upon the number of shingles that one may desire to have connected together. Thus, the present invention allows for considerable variation in the number of shingles that can remain connected together, depending upon the sizes of packages of shingles that one might desire.

With reference now to FIG. **5**, it will be seen that a sheet, for example that **111'** of laminated shingle material shown in

phantom, is passing between the rollers 106, 107, as the sheet 111' moves in the longitudinal direction 116 shown, with the rollers 106, 107 being oppositely rotated as shown by the arrows 117, 118.

With reference now to FIG. 5A, there is provided an end view of the rollers 106", 107" illustrated in FIG. 4A, turning in the directions of arrows 117', 118' as sheet 111" moves in the direction of arrow 116' after passing through the rollers 106", 107" and with the various cutting teeth 109' and 110" operating to cut against the surface of the roller 106", but wherein the intervening shallower teeth 109" are not shown in FIG. 5A, in that they are hidden from view in the illustration of FIG. 5A.

With reference now to FIGS. 6 and 7, a laminated hip, ridge, or rake shingle 120 is shown, as comprising a posterior shingle layer 121 and an anterior shingle layer 122. The shingle layers 121 and 122 are adhered together by means of generally one zone 90 or 91 of adhesive material (not shown in FIG. 6 or 7), in order to allow for sliding of adjacent surfaces of the posterior and anterior shingle layers 121, 122 relative to each other as the shingle 120 is bent into an inverted V shaped configuration, as shown in FIG. 6.

The anterior shingle layer 120 is shown with lighter granules 129 on its upper surface. Near the end 123 of the shingle that will not be exposed in the installed condition of the shingle 120 when laid up on a roof, it will be seen that a protruding portion 124 of the posterior shingle layer 121 extends beyond the end 125 of the anterior shingle layer 122. Also, proximate the end 123 of the shingle 120 and remote from its opposite end 123' an overlay 126 comprised of granules 127 over an adhesive 128 is shown, extending the thickness T of the shingle, as shown, to yield a thicker-appearing shingle as viewed in the installed condition (FIG. 8). It will be noted that the adhesive 128 is that applied in a thin band, via a roller 71 or 72 as described above, and that the granules 127 are those applied via a granule applicator such as the applicators 84 or 85, as described above.

The posterior and anterior shingle layers 121, 122, are constructed as described above, each having a mat layer 130 impregnated above and below with adhesive layers 131, 132, with granules 133 on the adhesive layer 131 and with smaller particles 134 such as sand, mica or the like beneath the adhesive layer 132. Except perhaps for the color or shading of granules, each of the anterior and posterior shingle layers 122, 121, are similarly constructed.

A shadow line or band 135, of darker granules is provided, just to the left of the overlay 126, as shown in FIG. 7. The overlay 126, while preferably being comprised of somewhat darker granules than the major upper surface of the anterior shingle layer 122, is spaced from the protruding portion 124 of the posterior shingle layer 121, by a portion 136 of the upper surface of the anterior shingle layer, as shown at the upper end of FIG. 6. Alternatively, the overlay 126 could extend farther to the right than is shown in FIG. 7, for example, to the edge 125 of the anterior layer 122. However, in some embodiments, the "stepping" effect of the layer "feathering out" that would be achieved as shown in the illustration of FIG. 7 such that the height of overlapping shingles as shown in FIG. 8 would be more gradual, would allow the overlapped shingles as shown in FIG. 8 to conform more smoothly to the roof.

Referring now to FIGS. 8 and 9, it will be seen that a plurality of three shingles 120, 120' and 120" of the type illustrated in FIG. 6 are shown, in overlapping relation to each other as they would appear on a roof. With specific reference to the zone 140 where adjacent shingles 120 and 120' overlap, and specifically with reference to the enlargement 141 thereof

shown in FIG. 9, what one sees in FIG. 9, is the upper surface 120' of the anterior shingle layer, with a shadow line 135 disposed thereon, and then one would see the edge of the thickened overlay 126 contributing to the overall thickness T for the shingle 120', that is discussed for FIG. 7. Also, for successive overlapped shingles, such as those 120 and 120' shown in FIG. 8, it will be seen that the protruding portion 124 of the posterior shingle layer 121 will allow an overlying portion of a next adjacent shingle, for example that 120, to more gradually overlie the end 123 of a next-underlying shingle 120', providing a more feathered overlap, rather than an abrupt overlap for an overlying portion of the shingle 120 relative to the underlying shingle 120', contributing to the aesthetic effect, and also with the protruding portion 124 of the posterior layer of the underlying shingle providing some underlying support that can be beneficial in resisting shingle breakage, as for example, if one were to step on an overlying hip, ridge or rake shingle near an edge of that shingle where it overlies a next underlying shingle.

With reference to FIG. 10, a strip 150 is presented of three connected laminated hip, ridge or rake shingles 151, 152 and 153, with their anterior shingle layers being completely severed at 154 and 155, and with their posterior shingle layers being incompletely severed as discussed above with reference to the transverse severance mechanism discussed relating to FIG. 4 above, with zones 156 of adhesive being shown in phantom connecting the anterior and posterior layers of shingle material together. Shadow lines 135, overlays 126, narrow anterior portions 136, and protruding portions 124 of the posterior shingle layers, all as have been discussed above with respect to FIGS. 6 and 7 also appear on the connected together shingles of FIG. 10. It will be understood that, if desired, it could, as an alternative, be the posterior shingle layer that is completely severed by means of a mechanism such as that of FIG. 4, or both posterior and anterior shingle layers could be incompletely severed, as may be desired. Also, it will be apparent that only two adjacent shingles could be connected together, if desired, rather than the three shown in FIG. 10, or that four or more could be connected together, as may be desired.

FIG. 11 is an illustration like that of FIG. 10, differing therefrom only in that the overlay strips 126 shown in FIG. 10 could, if desired, be comprised of a plurality of discontinuous zones 126' of overlay, each being made up of a zone of adhesive with the layer of granules applied thereto, as may be desired. Such provides a discontinuous, or staggered thickness effect having a different aesthetic than that shown for the illustration of FIG. 10. Such may also provide a greater ease of bendability of the shingle for installation, folded over a hip, ridge or rake, as well as providing a mechanical flexibility along the fold direction.

In some embodiments, a portion of the discontinuity between discontinuous zones 126' could be at the mid-line of the shingle, such as where the bend occurs in FIG. 8, which may facilitate bending of the shingles in the approximate shapes shown in FIG. 8, at the desired location where bendability is best facilitated; namely, at the apex of the bend which would be between some spaced-apart overlays.

FIG. 12 shows three adjacent and virtually identical hip, ridge or rake shingles 160, completely severed, as for example, may be made by passing between a pair of rollers 106, 107, each with continuous cutters 108 or 110 thereon, or a single continuous cutter 108 on one roller, operating against an anvil roller, for completely severing through the shingles. Otherwise, the shingles of FIG. 12 appear the same as those of FIG. 10, although, if desired, they could appear to be the same as those of FIG. 11, if spaced-apart overlay zones are desired.

It will be understood that the process as described for FIGS. 1, 1A, 2 and 2A to produce either completely separated shingles as shown in FIG. 12, or to produce incompletely severed shingles as illustrated in FIG. 10, separated completely every few shingles, and/or to produce discontinuous overlay zones 126' as shown in FIG. 11 could all be synchronized, such that the cutting that is effected by any of the rollers illustrated in FIGS. 3, 4, 4A, 5 and 5A, or that is effected by controlling adhesive applications or by controlling granule drops, can all be controlled in a synchronized manner, if desired, for example, in accordance with one or more of U.S. patent publication 2006/0260731 and U.S. Pat. No. 6,467,235, the complete disclosures of which are herein incorporated by reference.

Alternatively, adhesive bands with release strips could be disposed on tops or bottoms of shingles in a stack such that the configuration of a stack of shingles would be to have the adhesive bands and release strips in alignment, rather than staggered as shown in FIG. 15.

As an alternative to the partial or fully separated shingles discussed above with reference to FIGS. 10-12, the cutting between adjacent shingles could be complete in those portions of the shingles that would be exposed in the installed condition, and the remainder of the adjacent shingles could still be connected, such as by being partially perforated in the headlap portion of those shingles that would not be visible in the installed condition. Thus, for packaging purposes, the shingles could still be connected, but such an arrangement would yield a cleaner cut in those parts of the shingles that would be visible in the installed condition on a roof, and the efficiency of connected-together shingles would still exist for purposes of transport and handling.

With reference now to FIG. 13, it will be seen that a plurality of strips 150 of three connected-together shingles, in flattened form, may be packaged together, by wrapping the same by means of any conventional paper, plastic, or cardboard wrapper 170, for ease of handling and/or shipment. It will be noted that in the illustration of FIG. 13, the shingles in the stack are alternated, some facing downwardly and others facing upwardly, as may be desired, so that the overlays of the various shingles are not all vertically aligned in the stack, as shown. However, there are many possible variations as to how the shingles in a given stack may be arranged, with the illustration of FIG. 13 being by way of example, only.

With reference now to FIG. 14, it will be seen that a plurality of shingles 160, of the type illustrated in FIG. 12, are shown stacked alternately, face up or face down, with a wrapping 180, shown in phantom, for wrapping about the stack shown in FIG. 14, for ease of handling and/or shipment, as may be desired.

Referring now to FIG. 15, another package of shingles 190 is provided, in which a plurality of laminated shingle 191 are provided in a stack, with a wrapping 192 being shown in phantom applied thereover.

It will be understood that in the end view as shown in FIG. 15, the shingles could be any of those shown in either FIG. 13 or 14, as may be desired.

In the arrangement of illustration of FIG. 15, each of the shingles 191 is shown packaged back-to-back with adjacent shingles, with each comprising an anterior shingle layer 192, a posterior shingle layer 193, laminated together by means of a suitable adhesive (not shown), and with an overlay 194 of granules adhered to an upper surface of the anterior shingle layer 192, and secured thereto by means of an overlay adhesive (not shown). The overlay 194 may be comprised of granules as has been discussed above with respect to the various embodiments.

A strip of adhesive 195 is shown on the bottom surface 196 of the posterior shingle layer 193, near an end 197 of the shingle 191 that would be the weather-exposed end of the shingle 191, in the installed condition on a roof. A layer of release material 198, is shown, carried by a next-underlying shingle in the stack illustrated in FIG. 15, but located so that it is disposed against the adhesive 195 of the next-overlying shingle in a stack, when the shingles are arranged in the stack in a back-to-back manner as illustrated in FIG. 15. It will be understood that such an arrangement prevents shingles having an adhesive strip 195 thereon from becoming stuck to a next-adjacent shingle, so that when the shingles are separated from the stack illustrated in FIG. 15, they will not be stuck together. Alternatively, the adhesive strips and release material could be disposed on tops or bottoms of the shingles in alignment in the stack, if desired.

It will thus be seen that the present invention provides a thick-appearing hip, ridge and/or rake shingle that is efficient in its use of material, allowing for the making of shingles on a single manufacturing line, whereby a single sheet of impregnated shingle material can simultaneously make both posterior and anterior shingle layers, and that after the shingle layers are brought together and laminated, a pair of adjacent laminated shingles can be made simultaneously, by cutting transversely, and, as the laminated shingle material is moved longitudinally, the shingles can be cut to pairs of laminated shingles with overlays thereon, either completely cut through, or incompletely cut through, for handling and packaging purposes, as may be desired.

The addition of a shadow line to the upper surface of the shingle that is weather-exposed in the installed condition, gives the appearance of even greater thickness, and provides a custom look, as may be desired. During the installation, the amount of shadow line or overlay that is exposed from an underlying shingle, relative to a portion of a next-overlying shingle, can be selected by the installer for desired aesthetic effect.

In some embodiments, the granules in the zone or band 62' are selected to match or be complementary to the granules that are on the field shingles with which the hip, ridge or rake shingles to be applied. For example, the granules in the zone or band 62' could be selected to provide a transition zone in color or appearance, or to provide a variegated effect relative to the granules of the field shingles. Such variations could be applied in a transverse direction or a longitudinal direction, or both, as may be desired.

Instead of various ones of the process features in accordance with this invention discussed above, either by way of variations in application of adhesive, or variations in the depositing of granules, it will be understood that various features known in the art may be used instead of some of the detailed features discussed above with respect to this invention. For example, such features as are disclosed in U.S. Pat. No. 4,352,837 to Kopenhaver, or U.S. Pat. No. 6,355,132 to Beck et al or U.S. Pat. No. 6,044,608 to Stahl et al, may be used, as alternatives, and the complete disclosures of these patents are herein incorporated by reference.

It will be understood that variations can be made in the manner of construction, as well as in the amount of overlay and/or shadow line, and that variations can be made in the coloration and/or darkness of the various granules applied to different portions of the shingle, all within the spirit and scope of the invention as defined in the appended claims

What is claimed is:

1. A laminated hip, ridge or rake shingle having upper, lower and right and left edges and being adapted to be folded into an inverted V-shape along a fold line substantially paral-

11

lel to said right and left edges and substantially perpendicular to said top and bottom edges comprising a posterior shingle layer and an anterior shingle layer, with the posterior shingle layer being adapted to be unexposed to weather in the installed condition on a roof and with the anterior shingle layer being adapted to be substantially exposed to weather in the installed condition on a roof, each layer having top and bottom surfaces, with an adhesive adhering said layers together; each said layer being comprised of an adhesive impregnated mat with upper and lower surfaces; with granules on the upper surfaces; with granules on a surfaces of the posterior shingle layer being substantially sandwiched between the posterior layer and anterior layer; and including an overlay of granule covered adhesive comprising a narrow band along the top surface of the anterior layer between right and left edges of the shingle, substantially parallel to and adjacent the top edges of the shingle, creating a thicker band along the shingle than the rest of the shingle.

2. The shingle of claim 1, wherein the overlay is substantially proximate an unexposed edge of the shingle in the installed condition of the shingle when it is in installed on a roof.

3. The shingle of claim 1, wherein a portion of the posterior layer along an edge of the anterior layer is uncovered by the

12

anterior layer and is unexposed to weather in the installed condition when installed on a roof.

4. The shingle of claim 3, wherein the overlay is substantially proximate an unexposed edge of the shingle in the installed condition of the shingle when it is installed on a roof.

5. The shingle of claim 1, wherein some granules on the upper surface of the anterior layer are darker than the other granules on the upper surface of the anterior layer and comprise a shadow line band disposed generally parallel to said narrow overlay band.

6. A stack of shingles according to claim 1, with means wrapping the shingles together in the stack.

7. A strip comprising a plurality of connected laminated hip, ridge or rake shingles according to claim 1, wherein at least one of the shingle layers has at least one line of perforations between adjacent connected shingles, comprising means facilitating ready separation of connected shingles along the at least one line of perforations, prior to installation of the shingles on a roof.

8. A stack of strips of connected laminated shingles according to claim 7, with means wrapping the shingles together in the stack.

\* \* \* \* \*