

(19) **DANMARK**

(10) **DK/EP 2314654 T3**



Patent- og
Varemærkestyrelsen

(12) **Oversættelse af
europæisk patentskrift**

-
- (51) Int.Cl.: **C 09 K 5/04 (2006.01)**
- (45) Oversættelsen bekendtgjort den: **2016-11-28**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2016-08-03**
- (86) Europæisk ansøgning nr.: **10011167.3**
- (86) Europæisk indleveringsdag: **2003-10-27**
- (87) Den europæiske ansøgnings publiceringsdag: **2011-04-27**
- (30) Prioritet: **2002-10-25 US 421435 P** **2002-10-25 US 421263 P**
- (62) Stamansøgningsnr: **03777896.6**
- (84) Designerede stater: **AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR**
- (73) Patenthaver: **Honeywell International Inc., 115 Tabor Road, Morris Plains, NJ 07950, USA**
- (72) Opfinder: **Pham, Hang T., c/o Honeywell International Inc., 101 Columbia Road, PO box 2245, Morristown NJ 07962-2245, USA**
Singh, Rajiv R., c/o Honeywell International Inc., 101 Columbia Road, PO Box 2245, Morristown NJ 07962-2245, USA
- (74) Fuldmægtig i Danmark: **RWS Group, Europa House, Chiltern Park, Chiltern Hill, Chalfont St Peter, Bucks SL9 9FG, Storbritannien**
- (54) Benævnelse: **SAMMENSÆTNINGER, DER INDEHOLDER FLUORSUBSTITUERED E OLEFINER**
- (56) Fremdragne publikationer:
US-A- 3 723 318
US-A- 5 001 287
US-A- 5 714 083
US-A- 6 111 150
US-B1- 6 258 292
DATABASE WPI Week 199221 Thomson Scientific, London, GB; AN 1992-172539 XP2343594, -& JP H04 110388 A (DAIKIN KOGYO KK) 10 April 1992 (1992-04-10)
TAPSCOTT R E ET AL: "Tropodegradable fluorocarbon replacements for ozone-depleting and global-warming chemicals", JOURNAL OF FLUORINE CHEMISTRY, ELSEVIER, NL, vol. 101, no. 2, 1 February 2000 (2000-02-01), pages 209-213, XP004244520, ISSN: 0022-1139, DOI: 10.1016/S0022-1139(99)00161-X
UNEP 2002 REPORT OF THE REFRIGERATION, AIR CONDITIONING AND HEAT PUMPS TECHNICAL OPTIONS COMMITTEE"; COVER PAGE, PAGES III-IV; PAGES 1-36
2006 - STANDARD FOR SPECIFICATIONS FOR FLUOROCARBON REFRIGERANTS, ARI STANDARD 700-2006
JONES ET AL: 'NEARLY AZEOTROPIC MIXTURES TO REPLACE REFRIGERANT 12'" NASA TECH BRIEF VOL. 16, NO. 8, ITEM #122 FROM JPL NEW TECHNOLOGY REPORT MPO 1803//528, PAGES 1-39, AUGUST 1992.
KOPKO: 'Beyond CFCs: Extending the Search for New Refrigerants, 1998, pages 39-46.'

Fortsættes ...

DESCRIPTION

FIELD OF THE INVENTION

[0001] This invention relates to compositions having utility in numerous applications, including particularly refrigeration systems, and to methods and systems which utilize such compositions.

BACKGROUND OF THE INVENTION

[0002] Fluorocarbon based fluids have found widespread use in many commercial and industrial applications. For example, fluorocarbon based fluids are frequently used as a working fluid in systems such as air conditioning, heat pump and refrigeration applications. The vapor compression cycle is one of the most commonly used type methods to accomplish cooling or heating in a refrigeration system. The vapor compression cycle usually involves the phase change of the refrigerant from the liquid to the vapor phase through heat absorption at a relatively low pressure and then from the vapor to the liquid phase through heat removal at a relatively low pressure and temperature, compressing the vapor to a relatively elevated pressure, condensing the vapor to the liquid phase through heat removal at this relatively elevated pressure and temperature, and then reducing the pressure to start the cycle over again.

[0003] While the primary purpose of refrigeration is to remove heat from an object or other fluid at a relatively low temperature, the primary purpose of a heat pump is to add heat at a higher temperature relative to the environment.

[0004] Certain fluorocarbons have been a preferred component in many heat exchange fluids, such as refrigerants, for many years in many applications. For, example, fluoroalkanes, such as chlorofluoromethane and chlorofluoroethane derivatives, have gained widespread use as refrigerants in applications including air conditioning and heat pump applications owing to their unique combination of chemical and physical properties. Many of the refrigerants commonly utilized in vapor compression systems are either single components fluids or azeotropic mixtures.

[0005] Concern has increased in recent years about potential damage to the earth's atmosphere and climate, and certain chlorine-based compounds have been identified as particularly problematic in this regard. The use of chlorine-containing compositions (such as chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCF's) and the like) as refrigerants in air-conditioning and refrigeration systems has become disfavored because of the ozone-depleting properties associated with many of such compounds. There has thus been an increasing need for new fluorocarbon and hydrofluorocarbon compounds and compositions that offer alternatives for refrigeration and heat pump applications. For example, it has become desirable to retrofit chlorine-containing refrigeration systems by replacing chlorine-containing refrigerants with non-chlorine-containing refrigerant compounds that will not deplete the ozone layer, such as hydrofluorocarbons (HFC's).

[0006] It is generally considered important, however, that any potential substitute refrigerant must also possess those properties present in many of the most widely used fluids, such as excellent heat transfer properties, chemical stability, low- or no-toxicity, non-flammability and lubricant compatibility, among others.

[0007] Applicants have come to appreciate that lubricant compatibility is of particular importance in many of applications. More particularly, it is highly desirable for refrigeration fluids to be compatible with the lubricant utilized in the compressor unit, used in most refrigeration systems. Unfortunately, many non-chlorine-containing refrigeration fluids, including HFC's, are relatively insoluble and/or immiscible in the types of lubricants used traditionally with CFC's and HFC's, including, for example, mineral oils, alkylbenzenes or poly(alpha-olefins). In order for a refrigeration fluid-lubricant combination to work at a desirable level of efficiency within a compression refrigeration, air-conditioning and/or heat pump system, the lubricant should be sufficiently soluble in the refrigeration liquid over a wide range of operating temperatures. Such solubility lowers the viscosity of the lubricant and allows it to flow more easily throughout the system. In the absence of such solubility, lubricants tend to become lodged in the coils of the evaporator of the refrigeration, air-conditioning or heat pump system, as well as other parts of the system, and thus reduce the system efficiency.

[0008] With regard to efficiency in use, it is important to note that a loss in refrigerant thermodynamic performance or energy efficiency may have secondary environmental impacts through increased fossil fuel usage arising from an increased demand for electrical energy.

[0009] Furthermore, it is generally considered desirably for CFC refrigerant substitutes to be effective without major engineering changes to conventional vapor compression technology currently used with CFC refrigerants.

[0010] Flammability is another important property for many applications. That is, it is considered either important or essential in many applications, including particularly in heat transfer applications, to use compositions which are non-flammable. Thus, it is frequently beneficial to use in such compositions compounds which are nonflammable. As used herein, the term "nonflammable" refers to compounds or compositions which are determined to be nonflammable as determined in accordance with ASTM standard E-681, dated 2002, which is incorporated herein by reference. Unfortunately, many HFC's which might otherwise be desirable for used in refrigerant compositions are not nonflammable. For example, the fluoroalkane difluoroethane (HFC-152a) and the fluoroalkene 1,1,1-trifluorpropene (HFO-1243zf) are each flammable and therefore not viable for use in many applications.

[0011] Higher fluoroalkenes, that is fluorine-substituted alkenes having at least five carbon atoms, have been suggested for use as refrigerants. U.S. Patent No. 4,788,352 - Smutny is directed to production of fluorinated C₅ to C₈ compounds having at least some degree of unsaturation. The Smutny patent identifies such higher olefins as being known to have utility as refrigerants, pesticides, dielectric fluids, heat transfer fluids, solvents, and intermediates in various chemical reactions. (See column 1, lines 11 22).

[0012] While the fluorinated olefins described in Smutny may have some level of effectiveness in heat transfer applications, it is believed that such compounds may also have certain disadvantages. For example, some of these compounds may tend to attack substrates, particularly general-purpose plastics such as acrylic resins and ABS resins. Furthermore, the higher olefinic compounds described in Smutny may also be undesirable in certain applications because of the potential level of toxicity of such compounds which may arise as a result of pesticide activity noted in Smutny." Also, such compounds may have a boiling point which is too high to make them useful as a refrigerant in certain applications.

[0013] Bromofluoromethane and bromochlorofluoromethane derivatives, particularly bromotrifluoromethane (Halon 1301) and bromochlorodifluoromethane (Halon 1211) have gained widespread use as fire extinguishing agents in enclosed areas such as airplane cabins and computer rooms. However, the use of various halons is being phased out due to their high ozone depletion. Moreover, as halons are frequently used in areas where humans are present, suitable replacements must also be safe to humans at concentrations necessary to suppress or extinguish fire.

[0014] JP-A-H04 110388 discloses a heat transfer medium for heat pumps and heat engines, which comprises an organic compound represented by the molecular formula C₃H_mF_n, where m is from 1 to 5, n is from 1 to 5 and m+n = 6, and which has one double bond.


[0015] US 5 714 083 discloses a refrigerant fluid containing hexafluoropropene (FC-1216) and hydrocarbons as a replacement for CFC-12.

[0016] Applicants have thus come to appreciate a need for heat transfer compositions that are potentially useful in numerous applications, including vapor compression heating and cooling systems and methods, while avoiding one or more of the disadvantages noted above.

SUMMARY

[0017] Applicants have found that the above-noted need, and other needs, can be satisfied by a refrigerant composition comprising:

1. A) at least 50% by weight of a compound of Formula II below:



where each R is independently Cl, F, Br, I or H

R' is (CR₂)_nY,

Y is CF₃

n is 0 and wherein at least one R on the unsaturated terminal carbon is H, and at least one of the remaining Rs is F; and

2. B) a lubricant which is a polyalkylene glycol, wherein said composition has a Global Warming Potential (GWP) of no greater than 50.

[0018] Applicants believe that a relatively low toxicity level is associated with compounds of Formula II, preferably wherein Y is CF₃, wherein at least one R on the unsaturated terminal carbon is H, and at least one of the remaining Rs is F. Applicants believe also that all structural, geometric and stereoisomers of such compounds are effective and of beneficially low toxicity.

[0019] Thus, in certain preferred embodiments the compositions of the present invention comprise one or more compounds selected from the group consisting of tetrafluoropropenes (HFO-1234), pentafluoropropenes (HFO-1225) and combinations of these.

[0020] It is even more preferred that the compounds of the present invention are the tetrafluoropropene and pentafluoropropene compounds in which the unsaturated terminal carbon has not more than one F substituent, specifically: 1, 3, 3, 3-tetrafluoropropene (HFO-1234ze); 2, 3, 3, 3-tetrafluoropropene (HFO-1234y); and 1,2,3,3,3-pentafluoropropene (HFO-1225ye), and any and all stereoisomers of each of these. Applicant has discovered that such compounds have a very low acute toxicity level, as measured by inhalation exposure to mice and rats. On the other hand, applicants have found that a relatively high degree of toxicity may be associated with certain compounds adaptable for use with the present compositions, namely, those compounds which have more than one F on the terminal unsaturated carbon, or which do not have at least one H on the terminal unsaturated carbon. For example, applicants have discovered that 1,1,3,3,3-pentafluoropropene (HFO-1225zc) exhibits an unacceptably high degree of toxicity, as measured by inhalation exposure to mice and rats.

[0021] The preferred compounds of the present invention, namely, HFO-1225 and HFO-1234 are known materials and are listed in Chemical Abstracts databases. HFO-1225 is commercially available, for example from Syntex Chemical Co. Furthermore, methods are described generally in the patent literature for producing fluoroalkenes. For example, the production of fluoropropenes such as CF₃CH=CH₂ by catalytic vapor phase fluorination of various saturated and unsaturated halogen-containing C₃ compounds is described in U.S. Patent Nos. 2,889,379; 4,798,818 and 4,465,786. each of which is incorporated herein by reference. U.S. Patent No. 5,532,419, which is also incorporated herein by reference, discloses a vapor phase catalytic process for the preparation of fluoroalkene using a chloro- or bromo-halofluorocarbon and HF. EP 974,571. also incorporated herein by reference, discloses the preparation of 1,1,1,3-tetrafluoropropene by contacting 1,1,1,3,3-pentafluoropropane (HFC-245fa) in the vapor phase with a chromium-based catalyst at elevated temperature, or in the liquid phase with an alcoholic solution of KOH, NaOH, Ca(OH)₂ or Mg(OH)₂. In addition, methods for producing compounds in accordance with the present invention are described generally in connection with concurrently filed United States Patent Application entitled "Process for Producing Fluoropropenes" bearing attorney docket number (H0003789 (26267)), which is also incorporated herein by reference.

[0022] The present compositions are believed to possess properties that are advantageous for a number of important reasons. For example, applicants believe, based at least in part on mathematical modeling, that the fluoroolefins of the present invention will not have a substantial negative affect on atmospheric chemistry, being negligible contributors to ozone depletion in comparison to some other halogenated species. The preferred compositions of the present invention thus have the advantage of not contributing substantially to ozone depletion. The preferred compositions also do not contribute substantially to global warming compared to many of the hydrofluoroalkanes presently in use.

[0023] The compositions of the present invention have a Global Warming Potential (GWP) of not greater than 150, more preferably not greater than 100 and even more preferably not greater than 75. As used herein, "GWP" is measured relative to that of carbon dioxide and over a 100 year time horizon, as defined in The Scientific Assessment of Ozone Depletion, 2002, a report of the World Meteorological Association's Global Ozone Research and Monitoring Project," which is incorporated herein by reference.

[0024] The present compositions also preferably have an Ozone Depletion Potential (ODP) of not greater than 0.05, more preferably not greater than 0.02 and even more preferably about zero. As used herein, "ODP" is as defined in "The Scientific Assessment of Ozone Depletion, 2002, A report of the World Meteorological Association's Global Ozone Research and Monitoring Project," which is incorporated herein by reference.

[0025] The refrigerant compositions of the present invention comprise compound(s) in accordance with Formula II, in an amount

that is at least 50% by weight, and even more preferably at least 70 % by weight, of the composition.

[0026] The compositions of the present invention may include other components for the purpose of enhancing or providing certain functionality to the composition, or in some cases to reduce the cost of the composition. The refrigerant compositions according to the present invention, especially those used in vapor compression systems, include a lubricant, generally in amounts of from 30 to 50 percent by weight of the composition. Furthermore, the present compositions may also include a compatibilizer, such as propane, for the purpose of aiding compatibility and/or solubility of the lubricant. Such compatibilizers, including propane, butanes and pentanes, are preferably present in amounts of from 0.5 to 5 percent by weight of the composition. Combinations of surfactants and solubilizing agents may also be added to the present compositions to aid oil solubility, as disclosed by U.S. Patent No. 6,516,837, the disclosure of which is incorporated by reference. Commonly used refrigeration lubricants such as Poly Alkylene Glycols (PAGs) that are used in refrigeration machinery with hydrofluorocarbon (HFC) refrigerants may be used with the refrigerant compositions of the present invention.

METHODS AND SYSTEMS

[0027] The compositions of the present invention are useful in connection with numerous methods and systems, including as refrigerants used in refrigeration, air conditioning and heat pump systems.

[0028] The preferred heat transfer methods generally comprise providing a composition of the present invention and causing heat to be transferred to or from the composition changing the phase of the composition. For example, the present methods provide cooling by absorbing heat from a fluid or article, preferably by evaporating the present refrigerant composition in the vicinity of the body or fluid to be cooled to produce vapor comprising the present composition. Preferably the methods include the further step of compressing the refrigerant vapor, usually with a compressor or similar equipment to produce vapor of the present composition at a relatively elevated pressure. Generally, the step of compressing the vapor results in the addition of heat to the vapor, thus causing an increase in the temperature of the relatively high pressure vapor. Preferably, the present methods include removing from this relatively high temperature, high pressure vapor at least a portion of the heat added by the evaporation and compression steps. The heat removal step preferably includes condensing the high temperature, high pressure vapor while the vapor is in a relatively high pressure condition to produce a relatively high pressure liquid comprising a composition of the present invention. This relatively high pressure liquid preferably then undergoes a nominally isenthalpic reduction in pressure to produce a relatively low temperature, low pressure liquid. In such embodiments, it is this reduced temperature refrigerant liquid which is then vaporized by heat transferred from the body or fluid to be cooled.

[0029] In another process embodiment of the invention, the compositions of the invention may be used in a method for producing heating which comprises condensing a refrigerant comprising the compositions in the vicinity of a liquid or body to be heated. Such methods, as mentioned hereinbefore, frequently are reverse cycles to the refrigeration cycle described above.

EXAMPLES

[0030] The following examples are provided for the purpose of illustrating the present invention but without limiting the scope thereof.

REFERENCE EXAMPLE 1

[0031] The coefficient of performance (COP) is a universally accepted measure of refrigerant performance, especially useful in representing the relative thermodynamic efficiency of a refrigerant in a specific heating or cooling cycle involving evaporation or condensation of the refrigerant. In refrigeration engineering, this term expresses the ratio of useful refrigeration to the energy applied by the compressor in compressing the vapor. The capacity of a refrigerant represents the amount of cooling or heating it provides and provides some measure of the capability of a compressor to pump quantities of heat for a given volumetric flow rate of refrigerant. In other words, given a specific compressor, a refrigerant with a higher capacity will deliver more cooling or heating power. One means for estimating COP of a refrigerant at specific operating conditions is from the thermodynamic properties of the refrigerant using standard refrigeration cycle analysis techniques (see for example, R.C. Downing, FLUOROCARBON REFRIGERANTS HANDBOOK, Chapter 3, Prentice-Hall, 1988).

[0032] A refrigeration /air conditioning cycle system is provided where the condenser temperature is about 66°C (150°F) and the

evaporator temperature is about -37°C (-35°F) under nominally isentropic compression with a compressor inlet temperature of about 10°C (50°F). COP is determined for several compositions of the present invention over a range of condenser and evaporator temperatures and reported in Table I below, based upon HFC-134a having a COP value of 1.00, a capacity value of 1.00 and a discharge temperature of 79°C (175 °F).

TABLE I

REFRIGERANT COMPOSITION	Relative COP	Relative CAPACITY	DISCHARGE TEMPERATURE °C(°F)
HFO 1225ve	1.02	0.76	70 (158)
HFO trans-1234ze	1.04	0.70	74 (165)
HFO cis-1234ze	1.13	0.36	68 (155)
HFO 1234yf	0.98	1.10	76 (168)

[0033] This example shows that certain of the preferred compounds for use with the present compositions each have a better energy efficiency than HFC-134a (1.02, 1.04 and 1.13 compared to 1.00) and the compressor using the present refrigerant compositions will produce discharge temperatures (70°C (158°F), 74°C (165°F) and 68°C (155°F) compared to 79°C (175°F)), which is advantageous since such result will likely leading to reduced maintenance problems.

EXAMPLE 2

[0034] The miscibility of HFO-1225ye and HFO-1234ze with various refrigeration lubricants is tested. The lubricants tested are mineral oil (C3), alkyl benzene (Zerol 150), ester oil (Mobil EAL 22 cc and Solest 120), polyalkylene glycol (PAG) oil (Goodwrench Refrigeration Oil for 134a systems), and a poly(alpha-olefirt) oil (CP-6005-100). For each refrigerant/oil combination, three compositions are tested, namely 5, 20 and 50 weight percent of lubricant, with the balance of each being the compound of the present invention being tested

[0035] The lubricant compositions are placed in heavy-walled glass tubes. The tubes are evacuated, the refrigerant compound in accordance with the present invention is added, and the tubes are then sealed. The tubes are then put into an air bath environmental chamber, the temperature of which is varied from about -50°C to 70°C. At roughly 10°C intervals, visual observations of the tube contents are made for the existence of one or more liquid phases. In a case where more than one liquid phase is observed, the mixture is reported to be immiscible. In a case where there is only one liquid phase observed, the mixture is reported to be miscible. In those cases where two liquid phases were observed, but with one of the liquid phases occupying only a very small volume, the mixture is reported to be partiality miscible.

[0036] The polyalkylene glycol and ester oil lubricants were judged to be miscible in all tested proportions over the entire temperature range, except that for the HFO-1225ye mixtures with polyalkylene glycol, the refrigerant mixture was found to be immiscible over the temperature range of -54°C to -30°C and to be partially miscible over from -20 to 50°C. At 50 weight percent concentration of the PAG in refrigerant and at 60°, the refrigerant/PAG mixture was miscible. At 70°C, it was miscible from 5 weight percent lubricant in refrigerant to 50 weight percent lubricant in refrigerant.

EXAMPLE 3

[0037] The compatibility of the refrigerant compounds and compositions of the present invention with PAG lubricating oils while in contact with metals used in refrigeration and air conditioning systems is tested at 350° C, representing conditions much more severe than are found in many refrigeration and air conditioning applications.

[0038] Aluminium, copper and steel coupons are added to heavy walled glass tubes. Two grams of oil are added to the tubes. The tubes are then evacuated and one gram of refrigerant is added. The tubes are put into an oven at 350°F for one week and visual observations are made. At the end of the exposure period, the tubes are removed.

[0039] This procedure was done for the following combinations of oil and the compound of the present invention:

1. a) HFC-1234ze and GM Goodwrench PAG oil
2. b) HFC1243 zf and GM Goodwrench oil PAG oil
3. c) HFC-1234ze and MOLAR-56 PAG oil

4. d) HFC-1243 zf and MOPAR-56 PAG oil
5. e) HFC-1225 ye and MOPAR-56 PAG oil.

[0040] In all cases, there is minimal change in the appearance of the contents of the tube. This indicates that the refrigerant compounds and compositions of the present invention are stable in contact with aluminum, steel and copper found in refrigeration and air conditioning systems, and the types of lubricating oils that are likely to be included in such compositions or used with such compositions in these types of systems.

COMPARATIVE EXAMPLE

[0041] Aluminum, copper and steel coupons are added to a heavy walled glass tube with mineral oil and CFC-12 and heated for one week at 350°C, as in Example 3. At the end of the exposure period, the tube is removed and visual observations are made. The liquid contents are observed to turn black, indicating there is severe decomposition of the contents of the tube.

[0042] CFC-12 and mineral oil have heretofore been the combination of choice in many refrigerant systems and methods. Thus, the refrigerant compounds and compositions of the present invention possess significantly better stability with many commonly used lubricating oils than the widely-used prior art refrigerant-lubricating oil combination.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- [US4788352A \[0011\]](#)
- [JPH04110388A \[0014\]](#)
- [US5714083A \[0015\]](#)
- [US2869379A \[0021\]](#)
- [US4798818A \[0021\]](#)
- [US4465786A \[0021\]](#)
- [US5532419A \[0021\]](#)
- [EP974671A \[0021\]](#)
- [US6516837B \[0026\]](#)


Non-patent literature cited in the description

- **R.C. DOWNING** FLUOROCARBON REFRIGERANTS HANDBOOK 19880000 [\[0031\]](#)

Patentkrav

1. Kølemiddelsammensætning, der omfatter:

A) mindst 50 vægt-% af en fluoralken med formel II:



hvor hver R uafhængigt er Cl, F, Br, I eller H; R' er $(CR_2)_nY$; Y er CF_3 , n er 0, mindst én R på den umættede terminale carbon er H, og mindst én af de resterende R'er er F; og

10 B) et smøremiddel, som er en polyalkylenglycol, hvilken kølemiddelsammensætning har et potentiale for global opvarmning (GWP) på højst 150.

2. Sammensætning ifølge krav 1, hvor fluoralken er en tetrafluorpropen (HFO-1234).

15

3. Sammensætning ifølge krav 1, hvor smøremidlet er til stede i en mængde på 30 til 50 vægt-% af sammensætningen.

20 4. Sammensætning ifølge krav 1, der omfatter mindst 70 vægt-% af fluoralken.

5. Anvendelse af en sammensætning ifølge krav 1 i et luftkonditionerings-, køle- eller varmepumpesystem.