





(22) Date de dépôt/Filing Date: 2003/08/08
(41) Mise à la disp. pub./Open to Public Insp.: 2004/02/19
(45) Date de délivrance/Issue Date: 2012/05/01
(62) Demande originale/Original Application: 2 494 185
(30) Priorités/Priorities: 2002/08/09 (US60/402,164);
2003/05/20 (US10/442,307)

(51) Cl.Int./Int.Cl. *A46B 9/04* (2006.01),
A46B 7/06 (2006.01)
(72) Inventeurs/Inventors:
MOSKOVICH, ROBERT, US;
STORZ, JOACHIM, AT;
LANGGNER, TANJA, GB;
KUCHLER, THOMAS, AT
(73) Propriétaire/Owner:
COLGATE-PALMOLIVE COMPANY, US
(74) Agent: SMART & BIGGAR

(54) Titre : BROSSE A DENTS COMPORTANT DES ELEMENTS DE NETTOYAGE MOBILES ET FIXES
(54) Title: TOOTHBRUSH WITH FIXED AND MOVABLE CLEANING ELEMENTS



(57) Abrégé/Abstract:

A toothbrush comprises a handle and a head. The head includes a first section having cleaning elements extending outwardly from its outer surface. A ball joint is mounted to the head adjacent to the first section. The ball joint also includes cleaning elements extending outwardly from the outer surface. The head includes resilient material urging the ball joint to be in its initial position after the pivotal movement of the ball joint cleaning elements.



ABSTRACT

A toothbrush comprises a handle and a head. The head includes a first section having cleaning elements extending outwardly from its outer surface. A ball joint is mounted to the head adjacent to the first section. The ball joint also includes cleaning elements extending outwardly from the outer surface. The head includes resilient material urging the ball joint to be in its initial position after the pivotal movement of the ball joint cleaning elements.

62301-2467D

TOOTHBRUSH WITH FIXED AND MOVABLE CLEANING ELEMENTS

This is a divisional of Application Serial No. 2,494,185
filed August 8, 2003.

5

Background of the Invention

10 The present invention is directed primarily to a manually held toothbrush which would include a handle and a head. With conventional manual toothbrushes, cleaning elements, such as tufts of bristles, are mounted to the head. When toothpaste is applied to the cleaning elements the user inserts the head into the mouth and brushes the teeth in a known manner.

15 Conventionally, a toothbrush head is of one piece construction which is elongated and symmetrical in shape on each side of the longitudinal center line. Generally, the head includes fixed bristles extending outwardly from one surface of the head. Attempts have been made to provide additional flexibility to the bristles by permitting some movement of the bristles during use of the toothbrush. A number of patents, for example, disclose utilizing a pivotal or ball joint mounted on the toothbrush head to permit such movement. U.S. Patent No. 5,491,866, for example, discloses an articulate toothbrush wherein a pivot joint connects the handle and head. All of the bristles are mounted to the pivotable head. U.S. Patent No. 20 3,398,421 discloses a toothbrush wherein the head includes a pair of carriers each of which is retained by a ball member; alternatively, a single ball member is used for all of the carriers. No other bristles are included in the head. A similar approach is disclosed in patent abstracts of Japan publication no. 06327517.

25 Another approach is to have a plurality of individually mounted groups of bristles secured to a respective ball, such as disclosed in U.S. Patent No. 2,263,802 and Russian patent SU 1752336. The head includes no fixed bristles. A similar approach is utilized in a hairbrush disclosed in U.S. Patent No. 4,114,222.

30

U.S. Patent No. 4,654,922 discloses a toothbrush with a universal joint for two segments located outwardly of the head with the joints being disposed in a longitudinal direction. Accordingly, the head actually includes the two separate sections which extend outwardly from the head. The head itself may also be attached to the handle by a ratchet ball.

62301-2467D

U.S. Patent No. 6,088,870 discloses a toothbrush having a flexibly mounted bristles wherein the bristles are mounted on a resilient lattice network.

Summary of the Invention

5 An object of some embodiments of this invention is to provide a toothbrush wherein the toothbrush head includes cleaning elements, such as bristles, mounted on a ball joint to provide an extra degree of motion, in addition to fixed cleaning elements.

10 In accordance with an embodiment of this invention an elongated head is attached to the end of a handle. The head has an outer surface from which a plurality of cleaning elements extend. In addition, the head includes a further set of cleaning elements mounted to a ball joint located
15 generally perpendicular to the outer surface so that these cleaning elements may move in various directions, including along the longitudinal axis of the head.

 In one embodiment of this invention the ball joint is located below the outer surface of the head. The ball
20 joint includes an outwardly extending stem which in its initial position is perpendicular to the outer surface of the head. A carrier for the cleaning elements is mounted to the stem. The stem is surrounded by elastomer material to urge the stem back to its initial position.

25 The ball joint could be mounted to the head as a separate component which is snapped into place or could be joined into the cavity of the head by a flexible, resilient elastomer. The ball joint might be assembled via insert molding process.

62301-2467D

An aspect of the invention provides a toothbrush comprising: a handle; an elongated head mounted to said handle, said head having an outer surface, a longitudinal axis, a first section, and a second section; fixed cleaning
5 elements mounted to said first section and extending outwardly from said outer surface; a ball joint mounted to said second section, said ball joint including a carrier; cleaning elements mounted to said carrier and extending in a direction outwardly from said outer surface; resilient
10 material disposed against the ball joint; wherein said ball joint has an initial position generally perpendicular to said longitudinal axis and is movable away from said initial position in response to said ball joint cleaning elements contacting the teeth of the user whereby said carrier and
15 said ball joint cleaning elements are also movable.

There is also provided a toothbrush comprising a handle, an elongated head mounted to said handle, said head having an outer surface, a socket in said head disposed at said outer surface, a ball joint movably mounted in said
20 socket located inwardly of said outer surface, a recess in said outer surface communicating with said socket, a stem extending from said ball joint through said recess and to at least said outer surface, said ball joint and said stem having an initial position wherein said stem is generally
25 perpendicular to said outer surface, a carrier mounted to said stem, cleaning elements mounted to said carrier extending outwardly from said outer surface, said ball joint and said stem being movable away from said initial position in response to said cleaning elements contacting the teeth
30 of a user, and a biasing structure in said recess disposed against said stem to urge said stem to said initial position.

62301-2467D

According to one particular aspect of the invention, there is provided a toothbrush head comprising: a first outer surface, a second outer surface opposite the first outer surface and an opening defined therebetween; a plurality of first cleaning elements extending from the first outer surface; and a carrier including a restricted end and a second cleaning element opposite the restricted end, the carrier movably mounted within the opening, the second cleaning element movable relative to the first outer surface; wherein the opening comprises a constriction that represents the smallest cross-section of the opening and that retains the carrier in the opening or prevents the carrier from passing through the second outer surface; wherein the restricted end of the carrier is positioned between said constriction and a plane defined along said second outer surface; and wherein the carrier enables movement of the second cleaning element from a first position perpendicular to the first outer surface, to a second position angled relative to the first outer surface.

There is also provided a power toothbrush comprising: a power source; and a first outer surface, a second outer surface opposite the first outer surface and an opening defined therebetween; a plurality of first cleaning elements extending from the first outer surface; and a carrier including a restricted end and a second cleaning element opposite the restricted end, the carrier movably mounted within the opening, the second cleaning element movable relative to the first outer surface; wherein the opening comprises a constriction that represents the smallest cross-section of the opening and that retains the carrier in the opening or prevents the carrier from passing through the second outer surface; wherein the restricted end of the carrier is positioned between said constriction and a

62301-2467D

plane defined along said second outer surface; and wherein the carrier enables movement of the second cleaning element from a first position perpendicular to the first outer surface, to a second position angled relative to the first
5 outer surface.

Another aspect of the invention provides a toothbrush comprising: a handle, an elongated head mounted to said handle, said head having an outer surface, fixed cleaning elements mounted to said head and extending
10 outwardly from said outer surface, and movable cleaning elements mounted to said head by at least one movable carrier and extending outwardly from said outer surface, the carrier being connected by a stem to a pivotable joint that is pivotally received in a socket located in an underside of
15 the head that is opposite to the outer surface of the head, wherein said movable cleaning elements can be pivoted away from an initial position generally perpendicular to a longitudinal axis of the head in response to said movable cleaning elements contacting the teeth of the user causing
20 pivotal movement of the pivotable joint in the socket.

62301-2467D

The Drawings:

- Figure 1 is a perspective view of a toothbrush in accordance with this invention;
- 5 ▪ Figure 2 is a side elevational view of the toothbrush shown in Figure 1;
- Figure 3 is a front elevational view of the toothbrush shown in Figures 1-2;
- Figure 4 is a cross-sectional view taken through Figure 3 along the line 4-4;
- Figure 5 is a view similar to Figure 4 in a different phase of operation;
- Figure 6 is a view similar to Figures 4-5 of an alternative form of this invention;
- 10 ▪ Figure 7 is a plan view of the alternative shown in Figure 6; and
- Figure 8 is a front elevational view of a further toothbrush in accordance with this invention.

Detailed Description

15

The present invention is directed to toothbrushes which are inserted in the mouth during use. Although the drawings illustrate a toothbrush which is manually operated, it is to be understood that the teachings of this invention could be incorporated in power operated or electric toothbrushes wherein a portion of the toothbrush head is, for example, oscillated such

20 as by means of the type of drive illustrated in U.S. Patent No. 5,625,916. Such a toothbrush would include at least one oscillating or rotating section and would also include at least one section wherein the cleaning elements are mounted on a ball joint as later described.

25

Figures 1-3 show a toothbrush 10 in accordance with this invention. As shown therein toothbrush 10 includes a handle 12 and a head 14. Head 14 includes a fixed section 16 having an outer surface 18 from which various cleaning elements 19,20 extend. Head 14 also includes a section located near handle 12 which includes a ball joint 22 having cleaning elements 24. The utilization of the ball joint 22 introduces an extra degree of motion other

30 than flexing the bristle strands where bristles are used as the cleaning elements.

The ball joint 22 could be mounted to head 14 in any suitable manner. Figure 4, for example, illustrates a socket 26 located in a recess 28 on the underside of head 14, that is the side

62301-2467D

opposite outer surface 18. The ball joint 22 includes a neck or stem 30 connected to a carrier 32 with the cleaning elements 24 mounted to carrier 32. Stem 30 could be surrounded by elastomeric material 34 to fill the opening in head 14 necessary to accommodate the ball joint while still permitting universal type movement of ball joint 22.

5

As shown in Figure 4 the bottom of carrier 32 is concave to complement the convex outer surface of elastomer 34 and head 14 to facilitate the pivoting of carrier 32. As also shown, ball joint 22, stem 30 and carrier 32 are integral.

10 Figure 5 illustrates ball joint 22 in its condition during use where the ball joint 22 has pivoted in a direction toward handle 12.

An advantage of incorporating elastomeric material such as elastomeric material 34 or the resilient pad 38 (Figure 6) around the stem 30 of the ball joint 22 is that the elastomer 34 or
15 38 provides extra motion in returning the ball joint 22 to its initial rest position where the stem 30 is generally perpendicular to the longitudinal axis or outer surface of head 14.

Figures 6-7 illustrate an alternative manner of mounting the ball joint 22. As shown therein a socket 36 which is generally spherical in shape is formed in head 14. A resilient pad formed
20 of elastomeric 38 is mounted over socket 36. Carrier 32 has depending ribs 40 which press against pad 38. During assembly, ball joint 22 is snapped into place through a central hole in the pad 38. When ball joint 22 is in socket 36, ribs 40 contact pad 38. Instead of forming the ball joint structure as a separate component, the ball joint could be incorporated in the head 14 via insert molding process.

25

In both of the embodiments of Figures 1-5 and Figures 6-7, the ball joint 22 is located recessed below the outer surface of head 14. The cleaning element carrier 32 is disposed above the outer surface and mounted for pivotal movement by its connection to stem 30. Stem 30 is surrounded by elastomeric material 34 or elastomeric pad 38 to bias stem 30 to its
30 initial position perpendicular to the outer surface of head 14.

62301-2467D

Although Figures 1-3 illustrate the ball joint 22 and its cleaning elements 24 to be located between the fixed section 16 and the handle 12, other arrangements are possible such as by having a further fixed section on the opposite side of ball joint 22 or by having the ball joint
5 located at the remote or distal end and the fixed section located between the ball joint and the handle. Similarly, while Figures 1-3 illustrate only a single ball joint the invention could be practiced with multiple ball joints.

As best illustrated in Figure 3 the cleaning elements 20 are located along the periphery of
10 fixed section 16 in a generally U-shaped pattern. Cleaning elements 19 are located within the U-shape. Cleaning elements 19 may be shorter than cleaning elements 20 to create a cup-like outer surface of the ends of the cleaning elements 19,20 to help retain toothpaste on the cleaning elements. Cleaning elements 19 might be bristle bundles, while cleaning elements 20 might be in-molded technology bristles.

15

If desired, as shown in Figure 2, the outer surface 18 of head 14 could include a concave depression 46 to accommodate a complementary shaped surface 44 of the ball joint structure. Alternatively, the outer surface 18 may have a convex protrusion which would accommodate a complementary shape concave portion of the ball joint structure, as shown in Figure 4.

20 These complementary surfaces facilitate the smooth movement of the ball joint carrier 32.

As shown in Figures 4-5 the outer surface of head 14 includes a recess 29 through which the stem 30 extends. The shape and dimension of recess 29 controls or limits the degree of pivoting that the cleaning elements 24 can make. In that regard, where the head 14 is
25 generally formed from conventional hard plastic material the edges of the recess would function as a stop to limit the degree of pivoting action of the ball joint structure. Figure 5, for example, shows the ball joint structure pivoted almost to the limit that would result where upon continued movement stem 30 contacts the edge of recess 29.

30 As shown in Figure 6 head 14 includes a recess 43 into which the pad 38 would be mounted. The degree of pivoting permitted for the ball joint structure would be controlled by the size and dimension of the various components. Thus, the outer surface of head 14 would prevent further pivoting action of ball joint 22 when the carrier 32 contacts the outer surface 18.

62301-2467D

As illustrated in Figures 4-5 the elastomer material 34 completely fills the open area in recess 29, thus, effectively functioning as biasing structure to urge the ball joint 22 back to its initial position where it is generally perpendicular to the longitudinal axis of head 14.

5

Although Figure 3 illustrates the cleaning elements 20 to be a single row of tufts of bristles it is to be understood that the cleaning elements could be arranged in a plurality of rows. What is desired in the illustrated embodiment is that there should be an open area to accommodate cleaning elements 19.

10

Any suitable form of cleaning elements may be used as the cleaning elements 19, 20 and 24. The term "cleaning elements" is intended to be used in a generic sense which could include conventional fiber bristles or massage elements or other forms of cleaning elements such as elastomeric fingers or walls arranged in a circular cross-sectional shape or any type of desired shape including straight portions or sinusoidal portions. Where bristles are used, the bristles could be mounted to tuft blocks or sections by extending through suitable openings in the tuft blocks so that the base of the bristles is mounted within or below the tuft block.

15

It is to be understood that the specific illustration of the cleaning elements is merely for exemplary purposes. The invention can be practiced with various combinations of the same or different cleaning element configurations (such as stapled or in-molded technology bristles, etc.) and/or with the same bristle or cleaning element materials (such as nylon bristles, spiral bristles, rubber bristles, etc.) Similarly, while Figure 2 illustrates the cleaning elements to be generally perpendicular to the outer surface 18 of head 14 some or all of the cleaning elements may be angled at various angles with respect to the outer surface of head 14. It is thereby possible to select the combination of cleaning element configurations, materials and orientations to achieve specific intended results to deliver additional oral health benefits, like enhanced cleaning tooth polishing, tooth whitening and/or massaging of the gums.

20

25

30

Although Figures 1-7 illustrate a manually operated toothbrush, the invention may also be practiced where the head includes one or more power or electrically operated movable sections carrying cleaning elements. Such movable section may oscillate in a rotational

62301-2467D

manner or may oscillate linearly in a longitudinal direction with respect to the longitudinal axis of the head or may oscillate linearly in a lateral or transverse direction with respect to the longitudinal axis of the head. The movable section may oscillate in and out in a direction toward and away from the outer surface of the head. The movable section may rock back and forth with respect to the outer surface of the head. The movable section may rotate continuously in the same direction, rather than oscillate. Any suitable drive mechanism may be used for imparting the desired motion to the movable section. Where plural movable sections are used, all of the movable sections may have the same type and direction of movement, or combinations of different movements may be used.

10

Figure 8 illustrates a toothbrush 10A which includes a power driven movable disc or section 50 having cleaning elements. The movable section 50 could be oscillated rotationally such as by using the type of drive mechanism shown in U.S. Patent No. 5,625,916, or could move in and out using the type of drive mechanism shown in U.S. Patent No. Re35,941.

15

Alternatively, the other types of drives referred to above could move section 50 in other manners and directions. Although Figure 8 shows movable section 50 to be at the distal end of the head, the movable section(s) could be located at any desired location on the head.

20


As should be apparent the toothbrush 10 or 10A provides a head wherein there is an extra degree of motion to the cleaning elements. This extra degree of motion is accomplished by providing cleaning elements on a ball joint structure in such a manner that the cleaning elements may freely move in virtually any direction from its initial non-use position.

62301-2467D

CLAIMS:

1. A toothbrush comprising a handle, an elongated head mounted to said handle, said head having an outer surface, a socket in said head disposed at said outer surface, a ball joint movably mounted in said socket located inwardly of said outer surface, a recess in said outer surface communicating with said socket, a stem extending from said ball joint through said recess and to at least said outer surface, said ball joint and said stem having an initial position wherein said stem is generally perpendicular to said outer surface, a carrier mounted to said stem, cleaning elements mounted to said carrier extending outwardly from said outer surface, said ball joint and said stem being movable away from said initial position in response to said cleaning elements contacting the teeth of a user, and a biasing structure in said recess disposed against said stem to urge said stem to said initial position.
2. The toothbrush of claim 1 wherein said biasing structure is resilient material surrounding said stem.
3. The toothbrush of claim 2 wherein said resilient material is elastomeric material.
4. The toothbrush of claim 3 wherein said carrier and said resilient material have arcuate contacting surfaces.
5. The toothbrush of claim 2 wherein said resilient material is a resilient pad.
6. The toothbrush of claim 1 wherein said cleaning elements are bristles.

FIG. 1



SUBSTITUTE SHEET (RULE 26)

2 / 5

FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 7






FIG. 6



SUBSTITUTE SHEET (RULE 26)

FIG. 8



SUBSTITUTE SHEET (RULE 26)

