

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 November 2007 (22.11.2007)

PCT

(10) International Publication Number
WO 2007/131555 A1

(51) International Patent Classification:
H04L 29/06 (2006.01) *H04L 12/28* (2006.01)

(74) Agent: HAGSTRÖM, Lena; Box 7086, SE-103 87 Stockholm (SE).

(21) International Application Number:
PCT/EP2006/067942

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date: 30 October 2006 (30.10.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/435,023 16 May 2006 (16.05.2006) US

(71) Applicant (*for all designated States except US*): SONY ERICSSON MOBILE COMMUNICATIONS AB [SE/SE]; SE-221 88 Lund (SE).


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): DE LEON, David [SE/SE]; Arkivgatan 24 A, SE-223 59 Lund (SE). SPARRE, Erik [SE/SE]; Vallgatan 7A, SE-234 32 Lomma (SE). GRANSTRÖM, Martin [SE/SE]; Repslagaregatan, SE-211 21 Malmö (SE).

[Continued on next page]

(54) Title: MOBILE WIRELESS COMMUNICATION TERMINALS, SYSTEMS, METHODS, AND COMPUTER PROGRAM PRODUCTS FOR MANAGING PLAYBACK OF SONG FILES



(57) Abstract: A mobile wireless communication terminal includes a wireless communication module that is configured to communicate with other communication terminals over a wireless interface, and a controller. The controller is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, to receive from the at least one participant wireless communication terminal an identification of a compliant song file stored on the at least one participant wireless communication terminal and having a metadata tag associated therewith indicating that the compliant song file is classified in a prescribed song file category, and to execute playback of the compliant song file.

WO 2007/131555 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**MOBILE WIRELESS COMMUNICATION TERMINALS, SYSTEMS, METHODS,
AND COMPUTER PROGRAM PRODUCTS FOR
MANAGING PLAYBACK OF SONG FILES**

FIELD OF THE INVENTION

[001] The present invention relates to electronic devices and, more particularly, to electronic devices, methods and computer program products for playing song files.

BACKGROUND OF THE INVENTION

[002] Mobile electronic devices, such as wireless communication terminals (*e.g.*, cellular telephones), are widely used to store and playback song files. A user may wish to play a song file on another device such as a media center (*e.g.*, a PC or laptop, a television, an audio receiver, etc.) or another wireless communication terminal. This may be accomplished by connecting the electronic device to the other device via a cable or a wireless link (*e.g.*, a Bluetooth connection) if the other device is equipped with a suitable communication module, which may be an integrated module or an auxiliary (*e.g.*, plug-in) module. Song files may be sent, one by one, from one or more mobile electronic devices to the playback device(s).

SUMMARY OF THE INVENTION

[003] According to some embodiments of the present invention, a mobile wireless communication terminal includes a wireless communication module that is configured to communicate with other communication terminals over a wireless interface, and a controller. The controller is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, to receive from the at least one participant wireless communication terminal an identification of a compliant song file stored on the at least one participant wireless communication terminal and having a metadata tag associated therewith indicating that the compliant song file is classified in a prescribed song file category, and to execute playback of the compliant song file.

[004] The controller may be configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to receive identifications of compliant songs from at least two of the plurality of participant wireless communication terminals.

[005] According to some embodiments, the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to execute playback of the compliant song file simultaneously on the plurality of participant wireless communication terminals.

[006] The controller may be configured to retrieve the compliant song file from the at least one participant wireless communication terminal for playback.

[007] According to some embodiments of the present invention, the wireless communication module is configured to communicate with other communication terminals over a direct point-to-point wireless interface, and the controller is configured to establish the connection with the at least one participant wireless communication terminal via the wireless communication module via the direct point-to-point wireless interface, and to receive the identification of a compliant song file from the at least one participant wireless communication terminal via the direct point-to-point wireless interface. The wireless communication module may comprise a Bluetooth transmitter. The wireless communication terminal may include a cellular telephone.

[008] According to further embodiments of the present invention, a mobile wireless communication terminal includes a wireless communication module that is configured to communicate with other communication terminals over a wireless interface, and a controller. The controller is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, to maintain a list of nominated song files, to receive at least one vote message from the at least one participant wireless communication terminal, to determine an elected song file from the list of nominated song files based on the at least one vote message, and to execute playback of the elected song file.

[009] According to some embodiments, the controller is configured to receive an identification of a nominated song file from the at least one participant wireless communication terminal, and to add the identification of the nominated song file to the list of nominated song files.

[010] According to some embodiments, the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to receive vote messages from at least two of the plurality of participant wireless communication terminals.

[011] The controller may be configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to execute playback of the elected song file simultaneously on the plurality of participant wireless communication terminals.

[012] The controller may be configured to retrieve the elected song file from the at least one participant wireless communication terminal for playback.

[013] According to some embodiments of the present invention, the wireless communication module is configured to communicate with other communication terminals over a direct point-to-point wireless interface, and the controller is configured to establish the connection with the at least one participant wireless communication terminal via the wireless communication module via the direct point-to-point wireless interface, and to receive the at least one vote message from the at least one participant wireless communication terminal via the direct point-to-point wireless interface. The wireless communication module may comprise a Bluetooth transmitter. The wireless communication terminal may include a cellular telephone.

[014] According to further embodiments of the present invention, a mobile wireless communication terminal includes a wireless communication module that is configured to communicate with other communication terminals over a wireless interface, and a controller. The controller is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, and to send at least one light effect signal to the at least one participant wireless communication terminal instructing the at least one participant wireless communication terminal to control at least one lighting device of the at least one participant wireless communication terminal in correspondence with playback of a song file.

[015] According to some embodiments, the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to send light effect signals to each of the plurality of participant wireless communication terminals instructing each of the plurality of

participant wireless communication terminals to control a lighting device thereof in correspondence with playback of the song file.

[016] According to some embodiments, the controller may be configured to send light effect signals to each of the plurality of participant wireless communication terminals instructing the plurality of participant wireless communication terminals to control the lighting devices thereof differently from one another.

[017] The controller may be configured to send light effect signals to each of the plurality of participant wireless communication terminals so as to cause the plurality of participant wireless communication terminals to display on respective displays thereof an image that moves over time from the display of a first of the plurality of participant wireless communication terminals to the display of a second of the plurality of participant wireless communication terminals.

[018] According to some embodiments, the controller is configured to send light effect signals to each of the plurality of participant wireless communication terminals so as to cause a lighting device of a first of the plurality of participant wireless communication terminals to respond to audio signals in a first audio frequency range and to cause a lighting device of a second of the plurality of participant wireless communication terminals to respond to audio signals in a second audio frequency range different from the first audio frequency range.

[019] The controller may be configured to execute playback of the song file simultaneously on the plurality of participant wireless communication terminals.

[020] According to some embodiments, the wireless communication module is configured to communicate with other communication terminals over a direct point-to-point wireless interface, and the controller is configured to establish the connection with the at least one participant wireless communication terminal via the wireless communication module via the direct point-to-point wireless interface, and to send the at least one light effect signal to the at least one participant wireless communication terminal via the direct point-to-point wireless interface. The wireless communication module may comprise a Bluetooth transmitter. The wireless communication terminal may include a cellular telephone.

[021] Further features, advantages and details of the present invention will be appreciated by those of ordinary skill in the art from a reading of the figures and the

detailed description of the preferred embodiments that follow, such description being merely illustrative of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[022] **Figure 1** is a schematic diagram of a mobile wireless communication terminal according to some embodiments of the present invention and an exemplary base station transceiver.

[023] **Figure 2** is a flowchart illustrating methods in accordance with some embodiments of the present invention.

[024] **Figure 3** is a schematic diagram of a song file playback system according to some embodiments of the present invention including the mobile wireless communication terminal of **Figure 1**.

[025] **Figure 4** is a schematic diagram of a song file playback system according to further embodiments of the present invention including the mobile wireless communication terminal of **Figure 1**.

[026] **Figure 5** is a schematic diagram of a song file playback system according to further embodiments of the present invention including the mobile wireless communication terminal of **Figure 1**.

[027] **Figure 6** is a schematic diagram illustrating a display of the mobile wireless communication terminal of **Figure 1** in accordance with some embodiments of the present invention.

[028] **Figure 7** is a flow chart illustrating methods in accordance with further embodiments of the present invention.

[029] **Figure 8** is a flow chart illustrating methods in accordance with further embodiments of the present invention.

[030] **Figure 9** is a schematic diagram of a song file playback system according to further embodiments of the present invention.

[031] **Figures 10A-C** are schematic diagrams of a system according to embodiments of the present invention illustrating an animation sequence displayed on three mobile wireless communication terminals of the system.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[032] The present invention now will be described more fully with reference to the accompanying drawings, in which embodiments of the invention are shown. However, this invention should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

[033] As used herein, the term "comprising" or "comprises" is open-ended, and includes one or more stated features, integers, elements, steps, components or functions but does not preclude the presence or addition of one or more other features, integers, elements, steps, components, functions or groups thereof.

[034] As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

[035] As used herein, the common abbreviation "*e.g.*", which derives from the Latin phrase "*exempli gratia*," may be used to introduce or specify a general example or examples of a previously mentioned item, and is not intended to be limiting of such item. If used herein, the common abbreviation "*i.e.*", which derives from the Latin phrase "*id est*," may be used to specify a particular item from a more general recitation.

[036] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise.

[037] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[038] It will be understood that when an element is referred to as being "coupled" or "connected" to another element, it can be directly coupled or connected to the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly coupled" or "directly connected" to another element, there

are no intervening elements present. Furthermore, "coupled" or "connected" as used herein may include wirelessly coupled or connected.

[039] Well-known functions or constructions may not be described in detail for brevity and/or clarity.

[040] The present invention may be embodied as methods, electronic devices, and/or computer program products. Accordingly, the present invention may be embodied in hardware and/or in software (including firmware, resident software, micro-code, *etc.*), which may be generally referred to herein as a "circuit" or "module". Furthermore, the present invention may take the form of a computer program product on a computer-usable or computer-readable storage medium having computer-usable or computer-readable program code embodied in the medium for use by or in connection with an instruction execution system. In the context of this document, a computer-usable or computer-readable medium may be any medium that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

[041] Embodiments according to the present invention are described with reference to block diagrams and/or operational illustrations of methods and communication terminals. In this regard, each block may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It is to be understood that each block of the block diagrams and/or operational illustrations, and combinations of blocks in the block diagrams and/or operational illustrations, can be implemented by radio frequency, analog and/or digital hardware, and/or program instructions. These program instructions may be provided to a controller, which may include one or more general purpose processors, special purpose processors, ASICs, and/or other programmable data processing apparatus, such that the instructions, which execute via the controller and/or other programmable data processing apparatus, create means for implementing the functions/acts specified in the block diagrams and/or operational block or blocks. In some alternate implementations, the functions/acts noted in the blocks may occur out of the order noted in the operational illustrations. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

[042] These computer program instructions may also be stored in a computer-usable or computer-readable memory that may direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer usable or computer-readable memory produce an article of manufacture including instructions that implement the function specified in the flowchart and/or block diagram block or blocks.

[043] The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific examples (a nonexhaustive list) of the computer-readable medium include the following: hard disks, optical storage devices, a transmission media such as those supporting the Internet or an intranet, magnetic storage devices, an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, and a compact disc read-only memory (CD-ROM).

[044] Computer program code for carrying out operations of the present invention may be written in an object oriented programming language such as Java®, Smalltalk or C++. However, the computer program code for carrying out operations of the present invention may also be written in conventional procedural programming languages, such as the "C" programming language and/or a lower level assembler language. It will be further appreciated that the functionality of any or all of the program modules may also be implemented using discrete hardware components, one or more application specific integrated circuits (ASICs), or a programmed digital signal processor or microcontroller.

[045] As used herein, "electronic component" means an active device as contrasted with a passive electrical connector or the like. An electronic component may include a processor.

[046] As used herein, "streamed" or "streaming" means that a file, such as an audio or song file, is continuously sent via a digital signal to a receiving device where the audio or song file is concurrently played via a suitable receiving application. The digital signal is typically buffered.

[047] As used herein, a "communication terminal" includes, but is not limited to, a terminal that is configured to receive/transmit communication signals via a wireline connection, such as via a public-switched telephone network (PSTN), digital subscriber

line (DSL), digital cable, or another data connection/network, and/or via a wireless interface with, for example, a cellular network, a satellite network, a wireless local area network (WLAN), and/or another communication terminal.

[048] When the communication terminal is configured to communicate over a wireless interface, it is referred to herein as a "wireless communication terminal" or a "wireless terminal." Examples of wireless terminals include, but are not limited to, a cellular telephone, personal data assistant (PDA), pager, and/or a computer that is configured to communicate data over a wireless communication interface that can include a cellular telephone interface, a Bluetooth interface, a wireless local area network interface (e.g., 802.11), another RF communication interface, and/or an optical/infra-red communication interface.

[049] As used herein, "mobile terminals" may be portable, transportable, installed in a vehicle (aeronautical, maritime, or land-based), or situated and/or configured to operate locally and/or in a distributed fashion at any other location(s) on earth and/or in space.

[050] Referring now to **Figure 1**, an exemplary mobile wireless communication terminal **10A** in accordance with some embodiments of the present invention is illustrated. The wireless terminal **10A** is configured to communicate data with one or more other wireless terminals over a direct wireless communication interface therebetween, over another wireless communication interface through one or more cellular base stations, and/or over another wireless communication interface through a wireless local area network (WLAN) router.

[051] The wireless terminal **10A** may be a mobile radiotelephone forming a part of a radiotelephone communication system **2** as illustrated in **Figure 1**. The system **2** includes the mobile wireless communication terminal **10A** and a base station transceiver, which is part of a wireless communications network **5**. In some embodiments of the present invention, the network **5** includes a base station transceiver that includes the radio transceiver(s) that define an individual cell in a cellular network and communicates with the mobile terminal **10A** (via an interface **7**) and other mobile terminals in the cell using a radio-link protocol. It will be understood that, in some embodiments of the present invention, many base station transceivers may be connected through, for example, a mobile switching center and other devices to define the wireless communications network **5**.

[052] The mobile terminal **10A** in the illustrated embodiments includes a portable housing assembly **12**, a display **20**, a user interface **22** (*i.e.*, a man machine interface (MMI)) including a speaker **24** (*i.e.*, a sound transducer), an audio player **26**, a controller **30**, a communication module **32**, a memory **34**, and a lighting device **50**. The foregoing components of the mobile terminal **10A** may be included in many conventional mobile terminals and their functionality is generally known to those skilled in the art. The mobile terminal **10A** further includes a song management module **40** and a light effects management module **44**, which may be stored in the memory **34**. The mobile terminal **10A** is capable of processing and playing song files (*e.g.*, MP3 files).

[053] The display **20** may be any suitable display screen assembly. For example, the display screen **28** may be a liquid crystal display (LCD) with or without auxiliary lighting (*e.g.*, a lighting panel).

[054] The user interface **22** may include any suitable input device(s) including, for example, a touch activated or touch sensitive device (*e.g.*, a touch screen), a joystick, a keyboard/keypad, a dial, a directional key or keys, and/or a pointing device (such as a mouse, trackball, touch pad, etc.). The speaker **24** generates sound responsive to an input audio signal. The user interface **22** can also include a microphone coupled to an audio processor that is configured to generate an audio data stream responsive to sound incident on the microphone.

[055] The controller **30** may support various functions of the mobile terminal **10A**. The controller **30** can be any commercially available or custom microprocessor, for example. In use, the controller **30** of the mobile terminal **10A** generates a display image on the display **20**. The controller **30** may control the audio player **26** and various other components of the mobile terminal **10A**.

[056] The memory **34** is configured to store digital information signals and data such as a digital audio signal and/or digital audio files.

[057] The communication module **32** is configured to communicate data over one or more wireless interfaces (*e.g.*, wireless interfaces **7**, **112**, **114**, **116**, **122**, and **134** as discussed herein (**Figures 1 and 3**)) to another remote wireless terminal as discussed herein. The communication module **32** can include a cellular communication module, a direct point-to-point connection module, and/or a WLAN module.

[058] With a cellular communication module, the wireless terminal **10A** can communicate via the base station(s) of the network **5** using one or more cellular

communication protocols such as, for example, Advanced Mobile Phone Service (AMPS), ANSI-136, Global Standard for Mobile (GSM) communication, General Packet Radio Service (GPRS), enhanced data rates for GSM evolution (EDGE), code division multiple access (CDMA), wideband-CDMA, CDMA2000, and Universal Mobile Telecommunications System (UMTS). The cellular base stations may be connected to a Mobile Telephone Switching Office (MTSO) wireless network, which, in turn, can be connected to a PSTN and/or another network.

[059] A direct point-to-point connection module may include a direct RF communication module or a direct IR communication module. The direct RF communication module may include a Bluetooth module. With a Bluetooth module, the wireless terminal **10A** can communicate via an ad-hoc network through a direct point-to-point interface.

[060] With a WLAN module, the wireless terminal **10A** can communicate through a WLAN (*e.g.*, a router **120** (**Figure 3**)) using a communication protocol that may include, but is not limited to, 802.11a, 802.11b, 802.11e, 802.11g, and/or 802.11i.

[061] The communication module **32** can include a transceiver typically having a transmitter circuit and a receiver circuit, which respectively transmit outgoing radio frequency signals (*e.g.*, to the network **5**, a router or directly to another terminal) and receive incoming radio frequency signals (*e.g.*, from the network **5**, a router or directly to another terminal), such as voice and data signals, via an antenna. The communication module **32** may include a short range transmitter and receiver, such as a Bluetooth transmitter and receiver. The antenna may be an embedded antenna, a retractable antenna or any antenna known to those having skill in the art without departing from the scope of the present invention. The radio frequency signals transmitted between the mobile terminal **10A** and the network **5**, router or other terminal may include both traffic and control signals (*e.g.*, paging signals/messages for incoming calls), which are used to establish and maintain communication with another party or destination. The radio frequency signals may also include packet data information, such as, for example, cellular digital packet data (CDPD) information. In addition, the transceiver may include an infrared (IR) transceiver configured to transmit/receive infrared signals to/from other electronic devices via an IR port.

[062] The mobile terminal **10A** may also be configured to electrically couple with another terminal via a wireline or cable for the transmission of digital communication

signals therebetween. The mobile terminal **10A** may include further components such as a camera device configured to generate a still image and/or video data stream based on incident light.

[063] According to some embodiments, the mobile terminal **10A** is a handheld mobile terminal. By "handheld mobile terminal," it is meant that the outer dimensions of the mobile terminal are adapted or configured and suitable for use by a typical operator using one hand. According to some embodiments, the total volume of the handheld mobile terminal **10A** is less than about 200 cc. According to some embodiments, the total volume of the handheld terminal **10A** is less than about 100 cc. According to some embodiments, the total volume of the handheld mobile terminal **10A** is between about 50 and 100 cc. According to some embodiments, no dimension of the handheld mobile terminal **10A** exceeds about 200 mm.

[064] A method for selecting and playing back a song file using mobile wireless communication terminals (*e.g.*, mobile terminals **10A-E**) according to embodiments of the present invention will now be described in reference to the flowchart of **Figure 2**. The method includes establishing a wireless connection between a host wireless communication terminal and at least one participant wireless communication terminal (**Block 280**). The host terminal maintains a list of nominated song files (**Block 282**). The host terminal receives at least one vote message from the at least one participant terminal (**Block 284**). The host terminal determines an elected song file from the list of nominated song files based on the at least one vote message (**Block 286**). The host terminal executes playback of the elected song file (**Block 288**). According to some embodiments, the host terminal also receives a song nomination from the at least one participant terminal and adds the song nomination to the list of nominated song files. The various method steps and operations as described herein for selecting and playing back nominated song files may be enabled and executed by the suitably configured controller **30** and song management module **40** of the implementing mobile terminal(s).

[065] According to some embodiments, connections are established between the host wireless communication terminal and a plurality of participant wireless communication terminals, and the host wireless communication terminal receives a plurality of vote messages from the plurality of participant wireless communication terminals and determines the elected song based on the plurality of vote messages.

[066] According to some embodiments, communication between the host wireless communication terminal and the participant wireless communication terminal is accomplished via a direct point-to-point interface, such as a Bluetooth wireless RF connection. According to some embodiments, communication between the host wireless communication terminal and the participant wireless communication terminal is accomplished via an indirect interface, such as through a WLAN or cellular-based system. Further aspects and embodiments of the present invention will be apparent from the following descriptions of further embodiments.

[067] With reference to **Figure 3**, an exemplary song file playback system **100A** according to embodiments of the present invention is shown therein. The system **100A** includes the mobile wireless communication terminal **10A** (also referred to herein as the "host wireless communication terminal" or "host terminal"), a plurality of additional participant wireless communication terminals **10B**, **10C**, **10D**, and **10E** (also referred to herein as the "participant wireless communication terminals" or "participant terminals"), and a media center **130**. The media center **130** includes apparatus adapted or configured to convert an audio signal (*e.g.*, a digital audio signal) to corresponding sound. The media center **130** may include, for example, a PC or laptop, a television, an audio receiver, stereo equipment, etc. The illustrated media center **130** includes a wireless communication module **132** and sound transducers (speakers) **136**. The wireless communication module **132** may be integrated with the media center **130** or may be an auxiliary or plug-in wireless communication module such as the Bluetooth Media Viewer MMV-100 module or Bluetooth Media Viewer MMV-200 module, each available from Sony Ericsson of Sweden. The terminals **10B-E** may be configured as described above with regard to the terminal **10A**. The terminals **10B-E** each include a wireless communication module **32** and a song management module **40**. However, the respective song management modules **40** may be differently configured for each terminal **10A-E** depending on the intended functionality of the device. According to some embodiments, all or some of the terminals **10B-E** are mobile wireless communication terminals. According to some embodiments, all or some of the terminals **10A-E** are handheld mobile wireless communication terminals.

[068] Referring now to **Figure 4**, a further exemplary system **100B** according to embodiments of the present invention is shown therein including the host terminal **10A** and the participant terminals **10B-E**. The system **100B** differs from the system **100A**

(**Figure 3**) in that the media center **130** is omitted and playback of the song files from the song play list **156** is conducted via the speaker **24** of the host terminal **10A**.

[069] Referring now to **Figure 5**, a further exemplary system **100C** according to embodiments of the present invention is shown therein including the host terminal **10A** and the participant terminals **10B-E**. The system **100C** differs from the system **100B** (**Figure 5**) in that playback of the song files from the song play list **156** is conducted via the speaker **24** of the host terminal **10A** and, additionally, through the respective speakers of the participant terminals **10B-E** and/or through one or more headsets (*e.g.*, in-ear stereo headsets) operatively connected to the terminals **10A-E**. More particularly, the controller **30** of the host terminal **10A** plays each song file thereon and also sends the song file to the participant terminals **10B-E** for simultaneous playback. According to some embodiments, the playback is synchronized between the mobile terminals **10A-E**.

[070] Various combinations and aspects of the exemplary systems **100A**, **100B**, **100C** may be employed and the host terminal **10A** may be configured to allow the user to selectively choose the device or combination of devices for playback from the various options discussed above. For example, the host terminal **10A** may be configured to execute playback via only the speaker **24** of the host terminal **10A**, via the speakers of the participant terminals **10B-E** but not the host terminal **10A**, via the speakers of the participant terminals **10B-E** and the media center **130**, etc. It will be appreciated that, when the song files are played back via the speakers of the terminals **10A-E**, the user of a given one of the participant terminals may disable the speaker thereof and/or may relay the song file for playback on another device (*e.g.*, an associated further media center or the like).

[071] Mobile terminals, methods and systems in accordance with embodiments of the present invention will now be described using an illustrative example of use. The host terminal **10A** is chosen to be the master or host terminal and the participant terminals **10B-E** are each designated as slave or participant terminals. The controller **30** of the host terminal **10A** establishes a wireless connection (*i.e.*, communicatively couples) with each of the participant terminals **10B-E**. According to some embodiments, the wireless connection is a direct wireless communication interface connection, according to some embodiments, a direct RF connection and, according to some embodiments, a Bluetooth connection. The connections may be established in known manner. For example, in the case of Bluetooth connections, the participant (slave) terminals **10B-E** may be set to a

searchable/discoverable state and the host (master) terminal **10A** emits an inquiry to identify the available participant (slave) terminals **10B-E** to form a piconet or personal area network.

[072] As illustrated, in the system **100A** (**Figure 3**) the host terminal **10A** communicates with the participant terminals **10B**, **10C** and **10D** via direct point-to-point wireless interfaces or links **112**, **114** and **116**, respectively, and with the participant terminal **10E** via wireless interfaces or links **118**, **122** through a WLAN router **120**. In the systems **100B** (**Figure 4**) and **100C** (**Figure 5**), the host terminal **10A** communicates with the participant terminals **10B-E** via direct point-to-point links **112**, **114**, **116**, **119**. In the case of the system **100A**, the host terminal **10A** is also communicatively coupled to the media center **130** to provide wireless song data signals via a wireless interface or link **134** to the communication module **132**. Alternatively, the host terminal **10A** can be connected to the media center **130** using a wireline or signal cable. It will be appreciated that, according to some embodiments, the interfaces may be various combinations of wireless interfaces that are direct (*e.g.*, Bluetooth) or indirect (*e.g.*, via a WLAN router or a cellular network **5**). According to some contemplated embodiments, all of the signals provided between the host terminal **10A** and the participant terminals **10B-E** to execute the song sharing procedure are provided via direct point-to-point wireless interfaces. According to some contemplated embodiments, all of the signals provided between the host terminal **10A** and the participant terminals to execute the song sharing procedure are provided via direct wireless radio frequency (RF) interfaces such as Bluetooth interfaces.

[073] Before or after establishing the connections, the host terminal **10A** may identify and designate valid participant terminals by any suitable method. According to some embodiments, the host terminal **10A** will poll or send an invitation to all or a selected group of potential participant terminals (*e.g.*, those within operational range of the host terminal's Bluetooth signal). The potential participant terminals may then opt in by replying with an acceptance of the invitation. Alternatively or additionally, the host terminal **10A** may accept unsolicited requests from participant terminals to participate. The host terminal **10A** may be used to define specific groups such as a listing of the potential participant terminals that will be permitted to participate (*e.g.*, to contribute song nominations and/or votes).

[074] Each song management module **40** provides a display **150** on the associated terminal **10A-E** as shown in **Figure 4**. The display provided on the host terminal **10A**

may differ from the display provided on the participant terminals **10B-E**. For example, the portions of the display **150** related to management functionality may be omitted from the participant terminal displays. Alternatively, the song management module **40** may provide no display on the participant terminals **10B-E**.

[075] Once the connections are established between the host terminal **10A** and the participant terminals **10B-E**, the host terminal **10A** may send a request to the participant terminals **10B-E** for song file nominations. For example, the host may actuate a "NOMINATIONS" button (**Figure 6**) on the display **150**. Each participant may use his or her respective participant terminal to send a nominee song identification to the host terminal **10A**. The nominee song identification designates a song file the participant wishes to add to the nominated song list. The nominee song identification may designate a song file stored on the participant's terminal **10B-E**. The song management module **40** of the sending participant terminal **10B-E** may provide a user interface to facilitate the selection and sending of the nominee song identification(s). For example, the module **40** may generate a list of the available stored songs and check boxes for selecting the song(s) to send to the host terminal **10A**. Additionally or alternatively, the nominated song list may comprise song identifications designating song files stored on the host terminal **10A**. According to some embodiments, only the host terminal **10A** may nominate song files. According to some embodiments, the host terminal **10A** and/or the participant terminals **10B-E** can nominate song files stored on mobile terminals other than themselves. The nominated song files constitute the nominated song list.

[076] The host terminal **10A** receives the nominee song identifications from the participant terminals **10B-E**. The song management module **40** of the host terminal **10A** creates and maintains a host nominated song list of these song identifications. The host nominated song list represents song files that are candidates to be played.

[077] According to some embodiments, the host terminal **10A** compiles the nominated song list and sends the nominated song list to the participant terminals **10B-E** for display thereon. According to some embodiments, each of the participant terminals **10B-E** receives nominations from other participant terminals (and, if applicable, the host terminal **10A**) and itself compiles and displays the nominated song list.

[078] In the illustrated embodiment, the display **150** includes a play list field **152** and control buttons **154** (e.g., soft keys). The control buttons **154** will typically only be displayed on the host terminal display. The nominated song list **156** is displayed in the

play list field **152**. The nominated song list **156** includes a row-by-row series of song identifications **156A**, each corresponding to a respective song file. As illustrated, each song identification includes a song artist, a song name, and a song play time corresponding to the associated song file, as well as an identification of the participant that has submitted the song identification as a nominee. It will be appreciated that more, less and/or different information may be provided as well. A vote counter field **156B** may also be provided for each nominated song identification **156A**.

[079] The host may initiate an election by actuating an "ELECTION" button (**Figure 6**) on the display **150**, for example. The election may be initiated for a single selected song, for a slate of songs less the full nominated song list, or for a slate including all of the nominated songs. The participants can vote on the nominated song(s) using their mobile terminals **10B-E**. The votes are sent as vote messages by the participant terminals **10B-E** to the host terminal **10A**. The host may also be enabled to vote using his or her mobile terminal **10A**. The host terminal **10A** counts or tallies the vote messages and determines the "winning" or "elected" song file or files (*i.e.*, the nominated song file or files receiving the most votes).

[080] In some cases, only a single song file is elected for playback. In other cases, a plurality of nominated song files may be elected and placed in a play list in vote rank order for playback. According to some embodiments, the host terminal **10A** may originally configure a play list that is thereafter reordered by voting of the participant terminals **10B-E** (and, optionally, the host terminal **10A**).

[081] The host may selectively manage play of the songs represented by the song list **156** using the control buttons **154**, for example. For example, the "PLAY" and "STOP" buttons may be used to start and stop transmission of the song files to the media center **130** and/or the audio players of the mobile terminals **10A-E**. The "MOVE" button may be used to prioritize or change the order of the song identifications **156A** in the play list **156** (*i.e.*, to change the order in which the associated song files will be played). The "DELETE" button may be used to delete a song identification **156A** from the play list **156**. The "DETAILS" button may be used to delete a song identification **156A** from the play list **156** so that the associated song file will not be played. The "RANDOM MIX" button may be used to cause the host terminal **10A** to execute playback of the song files (*i.e.*, send the song files to the media center **130**) in a random or other non-sequential order.

Typically, the host terminal **10A** will execute playback of the song files in the listed sequence unless the random or other non-sequential mode is in effect.

[082] When the host terminal **10A** is in play mode, the controller **30** of the host terminal **10A** will identify the elected song identification **156A** that is to be played. The host terminal **10A** will then execute playback of the elected song file. The host terminal **10A** may execute playback by any suitable method.

[083] According to some embodiments, the host terminal **10A** will execute playback of the elected song by sending a song file request to the participant terminal **10B-E** that nominated the song identification to retrieve the song file corresponding to the song identification. The corresponding participant terminal will then send a copy of the identified song file (which is stored on the participant terminal) to the host terminal **10A**. According to some embodiments, the participant terminal sends the song file to the host terminal **10A** as a copy of the song file that is then temporarily stored on the host terminal **10A** (e.g., in the memory **34**). According to other embodiments, the participant terminal sends the song file to the host terminal **10A** as a streaming song file. According to some embodiments, the request and song file signals between the host terminal and the participant terminal are sent wirelessly and, according to some embodiments, via a direct wireless RF connection such as Bluetooth.

[084] The controller **30** of the host terminal **10A** then executes playback of the retrieved song file by sending the song file to the media center **130** and/or the mobile terminals **10B-E**. The song file may be stored on the media center **130** and/or the mobile terminals **10B-E** for playback. Alternatively, the song file may be streamed to the media center **130** and/or the mobile terminals **10B-E**, for example, as the song file is streamed from the originating participant terminal to the host terminal **10A**. It may be preferable or necessary to stream the song file from the participant terminal to the host terminal and/or from the host terminal to the media center **130** and/or the mobile terminals **10B-E** if the allocated memory space on the host terminal **10A** is insufficient and/or storage of the song file on the host terminal **10A** is prevented or illegal. According to some embodiments, the song file, whether streamed or stored in whole, will be automatically erased (*i.e.*, without user intervention) from the host terminal **10A** during or after playback.

[085] Additionally or alternatively, the host terminal **10A** may execute playback of the song file by instructing the participant terminal on which the selected song file is

stored to play the selected song file and/or distribute the selected song file to other devices (*e.g.*, the other mobile terminals **10A-E** and/or the media center **130**) for playback.

[086] The controller **30** of the host terminal **10A** may execute the foregoing steps for each song identification **156A** in turn and automatically (*i.e.*, without user intervention). As the host terminal **10A** runs through the song list **156** in this fashion, the host may modify the play list **156** as desired. Also, according to some embodiments, the participant terminals **10B-E** can add new nominated song identifications to the song list **156** and vote on the nominated songs as the controller **30** of the host terminal **10A** runs through the play list **156**. According to some embodiments, new participant terminals can join the group and submit nominee song identifications and votes as the host terminal **10A** runs through the play list **156**.

[087] According to some embodiments, the host terminal may request nominations and/or only add to the nominated song list nominations of song files in a prescribed song file category or categories (*i.e.*, song files having associated therewith appropriate metadata tags as described herein). For example, the host terminal may request and limit the nominated song list to song files bearing a "disco" metadata tag.

[088] Various further modifications to the methods and apparatus may be made in accordance with embodiments of the present invention. According to some embodiments, some participant terminals can vote on nominated song files but cannot nominate song files. According to some embodiments, some participant terminals can nominate song files, but cannot vote on the nominated song files. According to some embodiments, some participant terminals can nominate and/or vote, but cannot play back the elected song files (*i.e.*, do not receive the song file from the host terminal or the originating participant terminal). According to some embodiments, some participant terminals can play back the elected song files, but cannot nominate or vote.

[089] Other functionality could also be provided. For example, the host terminal **10A** may allow the user to change the order of the song identifications **156A** according to one or more selected attributes (*e.g.*, contributing participant, song length, etc.). The host terminal **10A** may be configured to designate which of the participant terminals **10B-E** are permitted to add song identifications to the play list **156**. The participant terminals **10B-E** may be enabled to edit or modify the song list **156** in addition to adding song identifications. In this case, the host terminal **10A** may be configured to allow the host to select which of the participant terminals **10B-E** are and are not authorized to modify the

song play list **156** (*i.e.*, enable and disable the play list edit capability of the participant terminals).

[090] The mobile terminals, systems, and methods as described herein can provide a convenient and enjoyable mechanism for enabling a group of people to select and play back songs. The mobile terminals, systems, and methods can provide playback execution functionality and also allow the host terminal (and, in some cases, the participant terminals) to create, coordinate, control and/or manage a song play list. In practice, for example, partygoers can add songs from their own participant terminals to a nominated song list maintained on a host terminal (*e.g.*, the party host's own mobile terminal). If their song is elected, when their song's turn arrives in the playback sequence, a copy of the song file will automatically be sent to the host terminal and played. Thus, the partygoer need not take any further action. When, in accordance with some embodiments, the request and song transfer signals are communicated between the host terminal and the participant terminal via a direct wireless connection (*e.g.*, an RF interface such as a Bluetooth connection), the partygoer may simply place his or her participant terminal in a pocket or handbag. Participants may be added and removed as the procedure is executed. For example, when a participant leaves the Bluetooth range, his or her songs may be deleted from or moved down the play list.

[091] With reference to **Figure 7**, according to further embodiments of the present invention, mobile wireless communications terminals, methods, systems and computer program products are provided that enable selection and playback of files according to prescribed classifications or categories. Such mobile wireless communication terminals, methods, systems and computer program products may be employed with voting functionality and/or light effects functionality as described herein or independently thereof. The mobile terminal, etc., may be configured as otherwise discussed above with reference to the mobile terminals **10A-E** with suitable modifications to the song management module(s) **40** of the mobile terminals **10A-E** to enable the mobile terminals **10A-E** to function as described herein.

[092] A method for selecting and playing back a song file using mobile wireless communications terminals (*e.g.*, the mobile terminals **10A-E**) according to some embodiments of the present invention will now be described with reference to **Figure 7**. The method includes establishing a wireless connection between a host wireless communication terminal and at least one participant wireless communication terminal

(**Block 310**). The host terminal receives from the at least one participant terminal an identification of a song file that is stored on the at least one participant terminal and also has a metadata tag associated therewith that indicates the song file (with may be referred to a "compliant song file") is classified in a prescribed song file category (**Block 312**). The host terminal thereafter executes playback of the compliant song file (**Block 314**).

[093] The various method steps and operations as described herein for selecting and playing back compliant song files may be enabled and executed by the suitably configured controller **30** and song management module **40** of the implementing mobile terminal(s) **10A-E**.

[094] According to some embodiments, the host terminal establishes a wireless connection with a plurality of participant wireless communication terminals, requests identification of compliant songs from the plurality of participant terminals, and executes playback of one or more of the compliant songs on the plurality of participant terminals.

[095] According to some embodiments, the wireless connections is/are direct wireless communication interface connections, according to some embodiments, direct RF connections and, according to some embodiments, Bluetooth connections, as described herein. According to some embodiments, all of the signals provided between the host terminal and the participant terminal(s) to execute the compliant song identification procedure are provided via direct wireless RF interfaces such as Bluetooth interfaces. Similarly, according to some embodiments, the execution of playback of the compliant song files is accomplished by transferring the song files via direct wireless RF connections such as Bluetooth. More particularly, the communications between the terminals and song file transfers may be executed using the various apparatus methods and techniques described above with regard to the playlist management and playback function.

[096] According to more particular embodiments, a host terminal **10A** is designated and the controller **30** of the host terminal **10A** establishes wireless connections with one or more participant terminals such as the participant terminals **10B-E** as described above. At least some of the participant terminals **10B-E** have song files stored thereon. At least some of the participant song files include metadata tags assigned thereto. The metadata tag or tags correspond to some aspect of the associated song file by which the song file may be classified or categorized. Examples of aspects of song files and metadata tags are provided below.

[0097] The host terminal **10A** selects or designates a song file category for playback. The designated category corresponds with a metadata tag or tags. The host terminal **10A** sends a message to the participant terminals **10B-E** requesting an identification of the song files on the participant terminals **10B-E** that have the designated metadata tag associated therewith (*i.e.*, the compliant song files).

[0098] The participant terminals **10B-E** send response messages to the host terminal **10A** each including a respective listing of song files stored on the respective responding participant terminal having the prescribed metadata tag. According to some embodiments, the participant can modify the reply list to include only a compliant song file or files that the participant wishes to offer.

[0099] The host terminal **10A** selects or is used by the host to select a compliant song file from the compliant song file identifications received from the participant terminals **10B-E**. The host terminal **10A** may select the song file manually or according to further criteria (*e.g.*, using the voting functionality described hereinbelow), for example. The selected song file may be added to a play list on the host terminal **10A** if one is maintained.

[0100] The host terminal **10A** then executes playback of the selected compliant song. The host terminal **10A** may execute playback by any suitable method as those disclosed herein above with regard to the voting function. According to some embodiments, the host terminal **10A** retrieves and plays the selected song file on its own speaker **24** and/or the host terminal **10A** retrieves and distributes the selected compliant song file for playback on one or more of the participant terminals **10B-E** and/or the media center **130**, for example. According to some embodiments, the host terminal **10A** distributes the compliant song file for simultaneous (and, optionally, synchronized) playback on a plurality of the participant terminals **10B-E**. Additionally or alternatively, the host terminal **10A** may instruct the participant terminal on which the selected song file is stored to play the selected song file and/or distribute the selected song file to another device (*e.g.*, the other mobile terminals and/or the media center) for playback.

[0101] The host terminal **10A** may request and/or accept song catalog listings from one or more participant terminals as discussed above. According to some embodiments, the song catalog listings include metadata tag data. The song file catalogs may include compliant and non-compliant song files. According to some embodiments, the host terminal controller **30** searches the received song catalogs to identify and list the compliant

song files. The host terminal **10A** may thereafter select a compliant song file for playback as described herein.

[0102] The metadata tag may take any suitable form and may be associated with the song files in any suitable manner. For example, the metadata tags can be embedded in, attached to or assigned to the song files by the originator of the song file (*e.g.*, a party or entity such as a music media vendor which constructed or configured the song file prior to distribution of the song file to the participant terminal). The metadata tag may be assigned to the song file by the participant (*e.g.*, using the participant terminal or otherwise).

[0103] As discussed above, the metadata tag indicates that the compliant song file is classified in a prescribed song file category. The prescribed song file category may be any suitable category. According to some embodiments, the metadata tag indicates that the song file includes a song of a particular genre (*e.g.*, rock, techno, country/western, alternative country, disco, R&B, Hip Hop, World, Religious, Punk, Classical, Acoustic, Folk, etc.). According to some embodiments, the metadata tag indicates that the song file includes a song of a particular type (*e.g.*, mood, meditation, light music, background music, etc.). According to some embodiments, the metadata tag indicates that the song file includes a song for a particular occasion or event (*e.g.*, dance party, dinner party, birthday, wedding, graduation, etc.). According to some embodiments, the metadata tag indicates that the song file includes a song by a specified musician or artist (*e.g.*, the compliant songs are all songs by The Beatles). According to some embodiments, the metadata tag indicates that the song file includes a song having a tempo in a particular range (*e.g.*, slow, medium, fast). According to some embodiments, the metadata tag indicates that the song file includes a song that has received or is assigned a particular certification or rating (*e.g.*, a "parental advisory" rating or, alternatively, a non-parental advisory rating). The metadata tag may indicate an operational or usage status of the song file. The operational or usage status may be determined by the actual use of the song file. By way of example and in accordance with some embodiments, the metadata tag may indicate that a song file has previously won votes (as discussed herein, for example), has been played at least a prescribed number of times previously, or has been played less than a prescribed number of times (*e.g.*, never been played back within a prescribed timeframe such as the current session). Thus, for example, a play list could be constructed of popular songs or songs that have never been played.

[0104] The search and selection criteria employed to identify and select compliant songs for playback may be suitably modified or augmented. Multiple search or request parameters can be set. For example, the host may request via the host terminal **10A** an identification of all song files having both a "dance party" metadata tag and also a "non-parental advisory" metadata tag. By way of further example, the host may request via the host terminal **10A** an identification of all song files having, in combination for each song file, a metadata tag indicating the song has not been played back in the current session, a "disco" metadata tag, and a metadata tag indicating the song file has received votes. The search or request parameters may indicate negative criteria, such as a request for all songs not having a "parental advisory rating" metadata tag.

[0105] With reference to **Figure 8** according to further embodiments of the present invention, mobile wireless communications terminals, methods, systems and computer program products are provided that provide light effects corresponding to playback of a song file. In particular, the mobile terminals, methods, systems and computer program products may provide distributed light effects. Such mobile wireless communication terminals, methods, systems, and computer program products may be employed with the play list, metadata tag, voting or other functionality as described herein or independently thereof. The mobile terminal, etc., may be configured as otherwise described above with respect to the mobile terminals **10A-E** with suitable modifications to enable the mobile terminals **10A-E** to function as described herein.

[0106] A method for providing light effects on at least one participant wireless communication terminal and in correspondence with playback of a song file according to some embodiments of the present invention will now be described with reference to **Figure 8**. The method includes establishing a wireless connection between a host wireless communication terminal and at least one participant wireless communication terminal (**Block 410**). The host wireless communication terminal sends at least one light effect signal to the at least one participant wireless communication terminal instructing the at least one participant wireless communication terminal to control at least one lighting device of the at least on participant wireless communication terminal in correspondence with playback of a song file (**Block 412**). The various method steps and operations as described herein for providing light effects may be enabled and executed by the suitably configured controller **30** and the light effects management module **44** (**Figure 1**) of the implementing mobile terminals.

[0107] According to some embodiments, the host terminal establishes a wireless connection with a plurality of participant wireless communication terminals, and sends light effect signals to each of the plurality of participant terminals.

[0108] According to some embodiments, the wireless connection is/are direct wireless communication interface connections, according to some embodiments, direct RF connections and, according to some embodiments, Bluetooth connections, as described herein. According to some embodiments, all of the signals provided between the host terminal and the participant terminal(s) to execute the light effects thereon are provided via direct wireless RF interfaces such as Bluetooth interfaces. Similarly, according to some embodiments, the execution of playback of the song files is accomplished by transferring the song files via direct wireless RF connections such as Bluetooth. More particularly, the communications between the terminals and song file transfers may be executed using the various apparatus methods and techniques described above with regard to the playlist management and playback function.

[0109] According to more particular embodiments and with reference to **Figure 9**, there may be provided a system **400** including a host wireless communication terminal such as the mobile terminal **10A** and one or more participant wireless communications terminals such as the mobile terminals **10B-E** each having a respective lighting device or devices **50**. According to some embodiments, multiple participant wireless communication terminals **10B-E** are employed each having lighting devices **50**. The host wireless communication terminal **10A** may likewise include a lighting device **50**. With reference to **Figure 1**, each such lighting device **50** includes light source **52** and a light control **54** and is configured to selectively provide two different, mutually distinguishable light states. The light source **52** may include a suitable light source such as a light emitting diode (LED), a liquid crystal display (LCD), an incandescent lamp, or a phosphorescent material. For example, according to some embodiments, the light sources **52** include keypad LEDs and/or LCD displays of the mobile terminals **10A-E**. The light control **54** is adapted to selectively control the lighting device **50**. The light control **54** may itself be controlled by the controller **30** or the like of the associated terminal. The light control **54** may be an electrical switch or circuit capable of selectively actuating and deactuating the light source **52**, or a moveable element such as a shutter or a lens. The at least two light states may include different light intensities (including on/off or varying (continuous or step wise) degrees of intensity) and/or different colors.

[0110] In use during playback of a song file from or via the host terminal **10A**, the host terminal **10A** sends light effect orders or signals **422**, **424**, **426**, and **428** to each of the participant terminals **10B-E**, respectively. The light effect signals embody or represent light control orders or instructions from the host terminal **10A**. The light effect signals are dependent on, based on or correspond with the playback of the song file.

[0111] The participant terminals **10B-E** receive the light effect signals **422**, **424**, **426**, and **428** and the respective light controls **54** of the participant terminals **10B-E** operate the associated light sources **52** in accordance therewith. Accordingly, the host terminal **10A** governs the light effects displayed on the participant terminals **10B-E**. For example, the light effect signals **422**, **424**, **426**, and **428** from the host terminal **10A** may cause the light sources **52** to turn on and off. According to some embodiments, the participant terminals **10B-E** receiving the light effect signals **422**, **424**, **426**, and **428** and displaying the light effects also simultaneously playback the audio of the song file. According to some embodiments, the accompanying audio signals trigger the light effects so that the light effects are synchronized and dependent on the audio signals.

[0112] The host terminal may dynamically control the light effects on a given participant terminal or may order or instruct the participant terminal to enter an appropriate mode after which the participant terminal's own controller **30** executes a corresponding light effects program. For example, the host terminal may send a series of light effect signals that directly order or cause the participant terminal to blink a light source **52** on and off. Alternatively, the host terminal may instruct the participant terminal to enter a mode wherein the participant terminal's light effect management module **44** causes its light source **52** to blink or the like in synchrony with the audio signal.

[0113] The light effects may be any suitable light actuation, modulation, display, etc. According to some embodiments, the light effects include blinking or pulsing of one more light sources **52** and, according to some embodiments, blinking or pulsing of one or more LEDs. According to some embodiments, the light effects include video or animation. In particular, the light effects may include video or animation displayed on the participant terminal's display **20** (e.g., an LCD). The video or animation may be generated from a video file pre-stored on the participant mobile terminal or a video file transmitted (e.g., streamed) from the host terminal **10A**.

[0114] The host terminal **10A** may also govern the distribution of light effects across the participant terminals **10B-E**. According to some embodiments, the host

terminal **10A** sends different light effect signals to different participant terminals. Thus, over the course of playback of a given song file the light source **52** of the participant terminal **10B** may turn on and off at different times than the light source **52** of the participant terminal **10C**, for example. The host terminal **10A** may thereby cause the participant terminals **10B-E** to simultaneously display synchronized light effects in dynamic patterns that differ from one another. For example, the distributed light effects on the multiple mobile terminals may provide a disco light effect.

[0115] According to some embodiments, the host terminal sends light effect signals to one or more participant terminals that cause their lighting devices to actuate (*e.g.*, pulse on and off) in response to audio frequencies of the song file in a first range (*e.g.*, a high frequency range) and sends light effect signals to one or more other participant terminals that cause their lighting devices **50** to actuate (*e.g.*, pulse on and off) in response to audio frequencies of the song file in a second range (*e.g.*, low audio frequency range) different from the first range.

[0116] According to some embodiments, the host terminal causes the participant terminals to playback the song file in multi-channel audio with different audio channels being played on different participant terminals. For example, a first set of participant terminals (*e.g.*, the participant terminals **10B** and **10C**) receive from the host terminal **10A** and play back a first audio channel (*e.g.*, a left stereo channel) of the song file, and a second set of the participant terminals (*e.g.*, the participant terminals **10D** and **10E**) receive from the host terminal **10A** and play back a second, different audio channel (*e.g.*, a right stereo channel) of the song file. According to some embodiments, the light effect signals sent to the first set of participant terminals are paired with or correspond to the first audio channel and the light effect signals sent to the second set of participant terminals are paired with or correspond to the second audio channel. For example, the lighting devices **50** of the first set of participant terminals may blink in tempo or cadence with the first audio channel while the lighting devices **50** of the second set of participant terminals may blink in tempo or cadence with the second audio channel.

[0117] According to further embodiments, the multi-channel audio song file includes more than two audio channels and more than two separate channels are simultaneously respectively played back on different participant terminals. For example, the song file may be played back in a surround sound mode with three or more participant

terminals playing different channels and displaying different corresponding light effects from one another.

[0118] According to some embodiments, the relative positions or locations of the host terminal and/or the participant terminals are determined and the host terminal assigns the light effects to the participant terminals in accordance with their relative locations. Any suitable techniques can be used to distribute audio channels and determine the relative spatial locations of the terminals. According to some embodiments, the multi-channel audio playback distribution is accomplished as described in Applicant's European Patent Application No. 04103212.9, filed July 7, 2004, published as EP 1615464A1 on January 11, 2006, the disclosure of which is incorporated herein by reference. Moreover, the relative positions of the host terminal and the participant terminals may be determined and utilized as described in European Patent Application No. 0403312.9. Additionally, calibration may be accomplished as described in European Patent Application No. 04033129 or using any other suitable techniques to compensate for radio link delays.

[0119] According to some embodiments, the light effects coordinated or governed by the host terminal **10A** include a dynamic pattern that travels from mobile terminal to mobile terminal. For example, a light source (*e.g.*, an LED or an LCD display) may be pulsed on each mobile terminal **10A-E** in series so that the light pulse appears to travel along (*e.g.*, up and down) a row of the mobile terminals **10A-E**. To facilitate such operations, the relative spatial locations of the mobile terminals **10A-E** may be determined as discussed above and the light effects assigned to the several mobile terminals **10A-E** in accordance with their determined positions.

[0120] According to further embodiments, the dynamic patterned light effects include video or animation displayed on multiple mobile terminals **10A-E** such that it appears to travel from display screen **20** (*e.g.*, LCD) to display screen **20** of the mobile terminals **10A-E**. For example, in **Figure 10A**, three participant terminals **10B-D** are shown having respective display screens **20** at a first point in time to provide a collective or combined image **448A**. The displays **20** are controlled such that, at a later time, the respective images **442A**, **444A**, **446A** are replaced with new images **442B**, **444B**, **446B** as shown in **Figure 10B** to provide a new combined image **448B**, and, at a still later time, the images **442B**, **444B**, **446B** are replaced with new images **442C**, **444C**, **446C** to provide a new combined image **448C** (**Figure 10C**) giving the appearance that the objects in the combined images **448A**, **448B**, **448C** have traveled over time along the displays **20**.

between the mobile terminals **10B-D**. Thus, in the embodiment of **Figures 10A-C**, the light effects are distributed across the several mobile terminals **10B-D** in a dynamic pattern that gives the impression of an animated person walking from display screen **20** to display screen **20** of the mobile terminals **10B-D**. This operation may be paired with and facilitated by determining the relative spatial positions of the mobile terminals as discussed above.

[0121] The light effects as controlled by the host terminal may also include use of the screens or displays of multiple mobile terminals without screen-to-screen traveling animation. For example, the screens **20** may be used as a collective screen to display a still image.

[0122] Various of the invention embodiments disclosed herein can be used with or independently of other invention embodiments as disclosed herein. For example, a song file or song files may be selected for playback using the metadata tag procedure or voting procedure described herein, with the song files being played back one at a time without creation of a song file play list. According to some embodiments, the host terminal may only coordinate selection of song files for playback and instruct selected participant terminals to send song files (*e.g.*, via streaming or as a complete file) to one or more playback device(s) (*e.g.*, other participant terminals, the host terminal, or the media player) or to play the song file on the originating participant terminal only. According to some embodiments, the "host" status may shift among the mobile terminals **10A-E**.

[0123] The application programs described herein, including the song management module **40** and the light effects management module **44**, are illustrative of programs that implement various features according to embodiments of the present invention. It will be appreciated that other and/or additional application programs may be employed in accordance with embodiments of the present invention.

[0124] Although **Figure 1** illustrates an exemplary hardware/software architecture that may be used in mobile terminals and/or other electronic devices for management and playback of song files, it will be understood that the present invention is not limited to such a configuration but is intended to encompass any configuration capable of carrying out operations described herein. For example, although the memory **34** is illustrated as separate from the controller **30**, the memory **34** or portions thereof may be considered as a part of the controller **30**. More generally, while particular functionalities are shown in particular blocks by way of illustration, functionalities of different blocks and/or portions

thereof may be combined, divided, and/or eliminated. Moreover, the functionality of the hardware/software architecture of **Figure 1** may be implemented as a single processor system or a multi-processor system in accordance with various embodiments of the present invention.

[0125] Many alterations and modifications may be made by those having ordinary skill in the art, given the benefit of present disclosure, without departing from the spirit and scope of the invention. Therefore, it must be understood that the illustrated embodiments have been set forth only for the purposes of example, and that it should not be taken as limiting the invention as defined by the following claims. The following claims, therefore, are to be read to include not only the combination of elements which are literally set forth but all equivalent elements for performing substantially the same function in substantially the same way to obtain substantially the same result. The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, and also what incorporates the essential idea of the invention.

CLAIMS

1. A mobile wireless communication terminal comprising:
a wireless communication module that is configured to communicate with other communication terminals over a wireless interface; and
a controller that is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, to receive from the at least one participant wireless communication terminal an identification of a compliant song file stored on the at least one participant wireless communication terminal and having a metadata tag associated therewith indicating that the compliant song file is classified in a prescribed song file category, and to execute playback of the compliant song file.
2. The wireless communication terminal according to claim 1, wherein the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to receive identifications of compliant songs from at least two of the plurality of participant wireless communication terminals.
3. The wireless communication terminal according to any of the claims 1-2, wherein the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to execute playback of the compliant song file simultaneously on the plurality of participant wireless communication terminals.
4. The wireless communication terminal according to any of the claims 1-3, wherein the controller is configured to retrieve the compliant song file from the at least one participant wireless communication terminal for playback.
5. The wireless communication terminal according to any of the claims 1-4, wherein:
the wireless communication module is configured to communicate with other communication terminals over a direct point-to-point wireless interface; and

the controller is configured to establish the connection with the at least one participant wireless communication terminal via the wireless communication module via the direct point-to-point wireless interface, and to receive the identification of a compliant song file from the at least one participant wireless communication terminal via the direct point-to-point wireless interface.

6. The wireless communication terminal according to any of the claims 1-5, wherein the wireless communication module comprises a Bluetooth transmitter.

7. The wireless communication terminal according to any of the claims 1-6, wherein the wireless communication terminal includes a cellular telephone.

8. A mobile wireless communication terminal comprising:
a wireless communication module that is configured to communicate with other communication terminals over a wireless interface; and
a controller that is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, to maintain a list of nominated song files, to receive at least one vote message from the at least one participant wireless communication terminal, to determine an elected song file from the list of nominated song files based on the at least one vote message, and to execute playback of the elected song file.

9. The wireless communication terminal according claim 8, wherein the controller is configured to receive an identification of a nominated song file from the at least one participant wireless communication terminal, and to add the identification of the nominated song file to the list of nominated song files.

10. The wireless communication terminal according to any of the claims 8-9, wherein the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to receive vote messages from at least two of the plurality of participant wireless communication terminals.

11. The wireless communication terminal according to any of the claims 8-10, wherein the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to execute playback of the elected song file simultaneously on the plurality of participant wireless communication terminals.

12. The wireless communication terminal according to any of the claims 8-11, wherein the controller is configured to retrieve the elected song file from the at least one participant wireless communication terminal for playback.

13. The wireless communication terminal according to any of the claims 8-12, wherein:

the wireless communication module is configured to communicate with other communication terminals over a direct point-to-point wireless interface; and

the controller is configured to establish the connection with the at least one participant wireless communication terminal via the wireless communication module via the direct point-to-point wireless interface, and to receive the at least one vote message from the at least one participant wireless communication terminal via the direct point-to-point wireless interface.

14. The wireless communication terminal according to any of the claims 8-13, wherein the wireless communication module comprises a Bluetooth transmitter.

15. The wireless communication terminal according to any of the claims 8-14, wherein the wireless communication terminal includes a cellular telephone.

16. A mobile wireless communication terminal comprising:
a wireless communication module that is configured to communicate with other communication terminals over a wireless interface; and
a controller that is configured to establish a connection with at least one participant wireless communication terminal via the wireless communication module, and to send at least one light effect signal to the at least one participant wireless communication terminal instructing the at least one participant wireless communication terminal to control at least

one lighting device of the at least one participant wireless communication terminal in correspondence with playback of a song file.

17. The wireless communication terminal according to claim 16, wherein the controller is configured to establish a connection with a plurality of participant wireless communication terminals via the wireless communication module, and to send light effect signals to each of the plurality of participant wireless communication terminals instructing each of the plurality of participant wireless communication terminals to control a lighting device thereof in correspondence with playback of the song file.

18. The wireless communication terminal according to claim 17, wherein the controller is configured to send light effect signals to each of the plurality of participant wireless communication terminals instructing the plurality of participant wireless communication terminals to control the lighting devices thereof differently from one another.

19. The wireless communication terminal according to claim 18, wherein the controller is configured to send light effect signals to each of the plurality of participant wireless communication terminals so as to cause the plurality of participant wireless communication terminals to display on respective displays thereof an image that moves over time from the display of a first of the plurality of participant wireless communication terminals to the display of a second of the plurality of participant wireless communication terminals.

20. The wireless communication terminal according to any of the claims 18-19, wherein the controller is configured to send light effect signals to each of the plurality of participant wireless communication terminals so as to cause a lighting device of a first of the plurality of participant wireless communication terminals to respond to audio signals in a first audio frequency range and to cause a lighting device of a second of the plurality of participant wireless communication terminals to respond to audio signals in a second audio frequency range different from the first audio frequency range.

21. The wireless communication terminal according to any of the claims 17-20, wherein the controller is configured to execute playback of the song file simultaneously on the plurality of participant wireless communication terminals.

22. The wireless communication terminal according to any of the claims 16-21, wherein:

the wireless communication module is configured to communicate with other communication terminals over a direct point-to-point wireless interface; and

the controller is configured to establish the connection with the at least one participant wireless communication terminal via the wireless communication module via the direct point-to-point wireless interface, and to send the at least one light effect signal to the at least one participant wireless communication terminal via the direct point-to-point wireless interface.

23. The wireless communication terminal according to any of the claims 16-22, wherein the wireless communication module comprises a Bluetooth transmitter.

24. The wireless communication terminal according to any of the claims 16-23, wherein the wireless communication terminal includes a cellular telephone.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2006/067942

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04L29/06 H04L12/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2004/075169 A2 (KONINKL PHILIPS ELECTRONICS NV [NL]; PHILIPS CORP [US]; VAN DE SLUIS B) 2 September 2004 (2004-09-02) abstract page 1, line 14 - line 30	1, 2, 4-7
Y	page 11, line 21 - line 27 page 16, line 13 - line 26 page 21, line 8 - page 22, line 11	3
Y	US 2002/168938 A1 (CHANG CHIN-CHI [TW]) 14 November 2002 (2002-11-14) abstract page 1, paragraphs 9, 10 page 2, paragraph 24 ----- -/-	3, 11

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* & * document member of the same patent family

Date of the actual completion of the international search

20 April 2007

Date of mailing of the international search report

26/04/2007

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

BLANCO CARDONA, P

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2006/067942

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/032419 A1 (SHIBASAKI HIROAKI [JP] ET AL) 13 February 2003 (2003-02-13) abstract page 9, paragraphs 138,139 page 10, paragraphs 145,149 page 11, paragraphs 158,159 -----	1
X	US 2003/037157 A1 (PESTONI FLORIAN [US] ET AL) 20 February 2003 (2003-02-20) abstract	8-10, 12-15
Y	page 1, paragraphs 3,4,11 page 2, paragraphs 21,35,36 page 4, paragraphs 51,59 page 5, paragraphs 67,68 page 6, paragraphs 78,80,85,87 -----	11
X	US 2005/160270 A1 (GOLDBERG DAVID [US] ET AL) 21 July 2005 (2005-07-21) abstract	16-18, 20-24
A	page 2, paragraph 18 page 3, paragraph 33 page 12, paragraph 172 page 29, paragraph 330-333 page 30, paragraph 340 page 34, paragraphs 377,378 -----	19

INTERNATIONAL SEARCH REPORT

International application No.
PCT/EP2006/067942

Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest.

☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-7

Mobile terminal executing playback of a song file
simultaneously on a plurality of wireless terminals

2. claims: 8-15

Mobile terminal receiving vote messages for nominated song
files

3. claims: 16-24

Mobile terminal sending a signal to other wireless terminals
instructing to control a lighting device in correspondence
with the playback of a song file

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2006/067942

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2004075169 A2	02-09-2004	EP 1597895 A2 JP 2006518507 T KR 20050104382 A	23-11-2005 10-08-2006 02-11-2005
US 2002168938 A1	14-11-2002	US 2004248601 A1	09-12-2004
US 2003032419 A1	13-02-2003	EP 1303077 A2 JP 2003050589 A	16-04-2003 21-02-2003
US 2003037157 A1	20-02-2003	NONE	
US 2005160270 A1	21-07-2005	NONE	