




(86) Date de dépôt PCT/PCT Filing Date: 2018/05/29
 (87) Date publication PCT/PCT Publication Date: 2018/12/06
 (45) Date de délivrance/Issue Date: 2024/06/25
 (85) Entrée phase nationale/National Entry: 2019/11/20
 (86) N° demande PCT/PCT Application No.: IB 2018/053802
 (87) N° publication PCT/PCT Publication No.: 2018/220522
 (30) Priorités/Priorities: 2017/05/31 (PL P.421765);
 2017/05/31 (PL P.421766)

(51) Cl.Int./Int.Cl. *E05B 47/00* (2006.01)
 (72) Inventeur/Inventor:
 LITWINSKI, ARTUR, PL
 (73) Propriétaire/Owner:
 TEDEE IP SPOLKA Z OGRANICZONA
 ODPOWIEDZIALNOSCIA, PL
 (74) Agent: GOWLING WLG (CANADA) LLP

(54) Titre : DISPOSITIF D'ENTRAINEMENT POUR DEVERROUILLER ET VERROUILLER UN VERROU
 (54) Title: DRIVING DEVICE FOR UNLOCKING AND LOCKING A LOCK



(57) **Abrégé/Abstract:**

Driving device (1) for unlocking and locking a lock (1') enabling access to protected areas, within its housing (5) comprises a gear assembly (6), at least one electric energy source (9) and a driving motor (10) transmitting drive to a control element (3) for the lock (1') mechanism by means of the gear assembly (6). The lock (1') has a body (4), in which the control element (3) is seated rotatably. The driving device (1) is characterised in that an individual electric energy source (9) is so shaped that with its shape, in cross-section through the driving motor (10) and the electric energy source (9), it at least partially surrounds the driving motor (10), which means that in the area of cross-section through the electric energy source (9) there are at least two points such that a line segment joining these points passes through the area of cross-section of the driving motor (10).

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
06 December 2018 (06.12.2018)(10) International Publication Number
WO 2018/220522 A1

- (51) International Patent Classification:
E05B 47/00 (2006.01)
- (21) International Application Number:
PCT/IB2018/053802
- (22) International Filing Date:
29 May 2018 (29.05.2018)
- (25) Filing Language:
Polish
- (26) Publication Language:
English
- (30) Priority Data:
P.421765 31 May 2017 (31.05.2017) PL
P.421766 31 May 2017 (31.05.2017) PL
- (72) Inventor; and
(71) Applicant: LITWIŃSKI, Artur [PL/PL]; ul. Miączyńska 49, 02-632 Warszawa (PL).
- (74) Agent: BUDZIŃSKI, Sławomir; JWP Rzecznicy Patentowi Dorota Rzążewska Sp.K., Sienna Center, ul. Żelazna 28/30, 00-833 Warszawa (PL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,

(54) Title: DRIVING DEVICE FOR UNLOCKING AND LOCKING A LOCK




Fig. 1

(57) Abstract: Driving device (1) for unlocking and locking a lock (1') enabling access to protected areas, within its housing (5) comprises: a gear assembly (6), at least one electric energy source (9) and a driving motor (10) transmitting drive to a control element (3) for the lock (1') mechanism by means of the gear assembly (6). The lock (1') has a body (4), in which the control element (3) is seated rotatably. The driving device (1) is characterised in that an individual electric energy source (9) is so shaped that with its shape, in cross-section through the driving motor (10) and the electric energy source (9), it at least partially surrounds the driving motor (10), which means that in the area of cross-section through the electric energy source (9) there are at least two points such that a line segment joining these points passes through the area of cross-section of the driving motor (10).

[Continued on next page]

WO 2018/220522 A1 

UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

DRIVING DEVICE FOR UNLOCKING AND LOCKING A LOCK

The subject matter of the invention is a driving device for unlocking and locking a lock enabling access to protected areas, and in particular the device relates to the so called “intelligent locks”, the unlocking or locking of which may be effected without an authorised person directly contacting the lock.

A known driving device for unlocking and locking a lock enabling access to protected areas has a driving assembly to drive the lock, arranged within a housing which is in the form of a bush. The bush is secured from the outside from one side with a cover and from the other side with a base to which assembly components are fixed to or seated. The driving assembly comprises a current generator, electric motor and gear assembly.

The current generator are four cylindrical primary cells (batteries) positioned next to the motor and parallel to the motor's axis.

The electric motor is battery-driven.

The drive from the electric motor is transmitted via the gear assembly, consisting of toothed wheels, to a component used to control the lock.

The base has an opening through which passes a control element of the lock, with the second end of this element connected with the lock mechanism.

The bush, being the housing of the driving device, has teeth from the inside, the teeth cooperating with one of the toothed wheels of the gear assembly of the driving assembly. The driving device is fitted with an electronic control unit which controls the driving assembly. The electronic control unit is positioned between the cover and the motor. The electronic control unit is powered from the batteries placed in the housing. The electronic control unit may be controlled wirelessly by means of computer software, preferably a mobile device application, via a wireless connection. The device does not require external power supply and can be controlled by means of a smartphone application.

The driving device is installed from the inside of an apartment, in all door types with a profile insert. The so-designed driving device for unlocking a lock is quite large in size

because of the size of the power batteries and the size of the other components of the driving mechanism, which must be held within the housing of the device.

From Polish application P.336314 a driving device for a lock is known. The driving device, fixed on the door as a plate fitting, for the motor-driven and manual actuation of a locking cylinder, has a drive shaft for transmitting rotation to the locking cylinder, a turning knob for manually turning the drive shaft and a gear motor, arranged in the turning knob, for the motor-driven rotation of the drive shaft. A driving toothed wheel is seated on the drive shaft in a non-rotating manner and is connected with the turning knob such that it transmits torque. The gear motor is coupled to the plate fitting in a non-rotating manner and it becomes coupled to the driving toothed wheel by means of a coupling when current is applied.

From German patent application DE102014009826A1 a device for unlocking and locking entrances to access-protected areas is known. The device has a cylindrical housing. The housing holds a base plate, a miniature motor, preferably a direct current motor, an electric battery, a blocking assembly and a control unit. The blocking element of the blocking assembly is a rod with a ring, moved by the electric motor via a torsion spring arranged to transmit motion from the motor to the rod. The electric battery is to provide power supply to the control system irrespective of power supply for the device via an external power supply line. The control unit is controlled via a wireless connection.

The objective of the invention is to develop a new driving device for unlocking and locking a lock, the driving device being of simple design and with low overall dimensions, and to provide a new solution type.

According to the invention the driving device for unlocking and locking a lock enabling access to protected areas, within its housing comprises: a gear assembly, at least one electric energy source in a protective housing and an electric driving motor transmitting drive to a rotary control element for the lock mechanism by means of the gear assembly. The lock has a body, in which the control element is seated rotatably. The device is characterised in that an individual electric energy source is so shaped that with its shape, in the cross-section through the driving motor and the electric energy source, it at least partially surrounds the driving motor, which means that in the area of the cross-section through the electric energy source there are at least two points such that a line segment joining these points passes through the area of the cross-section of the driving motor.

Such shaped electric energy source so arranged around the driving motor makes it possible to considerably reduce the overall dimensions of the device by significant elimination of cavities within the housing.

It is preferred that the driving device is fitted with a base, fixed with respect to the lock, with the gear assembly, the at least one electric energy source and the driving motor being seated fixedly with respect to the base.

It is additionally preferred that the control element for the lock mechanism is seated on a toothed wheel, the toothed wheel being one of the wheels of the gear assembly, and the housing is in a form of a bush seated in a bearing in the base and it has, from the inner side, teeth engaging with the toothed wheel of the gear assembly, on which the control element for the lock mechanism is seated.

It is further preferred that the housing is seated in a bearing rotatably with respect to the body of the lock and is connected fixedly with the rotary control element for the lock, and the gear assembly, the at least one electric energy source and the driving motor are seated fixedly with respect to the housing and they rotate together with the housing, with the driving device being fitted with a ring with teeth, the ring cooperating with the toothed wheel, the toothed wheel being one of the wheels of the gear assembly and seated in a bearing in the housing, with the ring being positioned coaxially with the rotary housing and fixedly with respect to the body of the lock.

It is also preferred that the teeth of the ring are inner or outer teeth.

It is further preferred that the ring is arranged between the gear assembly and the lock.

It is preferred that the housing is connected with the control element by means of a shaped releasable connection.

It is additionally preferred that the housing is fitted with an electric socket, preferably a micro USB type socket, intended to charge the electric energy source.

It is also preferred that the protective housing of the electric energy source has a through hole, in which the driving motor is arranged.

It is at the same time preferred that the protective housing of the electric energy source is cross-sectionally wheel-shaped, with the hole positioned coaxially.

It is preferred that the protective housing of the electric energy source is cross-sectionally wheel-shaped, with the opening positioned eccentrically.

It is additionally preferred that the protective housing of the electric energy source has a cavity, in which the driving motor is arranged.

It is further preferred that the shape of the cavity in cross-section is a segment of a wheel.

It is also preferred that the protective housing of the electric energy source is a segment of a ring, the axis of which is parallel to the axis of the driving motor.

It is at the same time preferred that the electric energy source is either a primary electric cell or a secondary electric cell.

It is additionally preferred that the electric energy source is fitted with an anode, cathode and separator, all spirally wound in the form of a band around the through hole.

It is also preferred that the electric energy is fitted with an anode, cathode and separator, all arranged in layers, the plane of which is perpendicular to the axis of the driving motor.

It is also preferred that the electric energy source is fitted with an anode, cathode and separator, all arranged in layers being sectors of cylindrical surfaces of an axis parallel to the axis of the driving motor.

It is at the same time preferred that the gear assembly comprises a coupling.

It is preferred that the driving device is fitted with an electronic control unit to control the driving motor and preferably fitted with a first sensor cooperating with a manual control button, arranged on the frontal part of the driving device.

It is additionally preferred that the electronic control unit is fitted with a second sensor which determines the angular position of the rotary control element for the lock mechanism, the second sensor preferably being an accelerometer (gravitational field sensor).

It is also preferred that the electronic control unit is controlled wirelessly, preferably by means of computer software, preferably a mobile device application, via a wireless connection.

BRIEF DESCRIPTION OF DRAWINGS

The subject matter of the invention is shown by means of embodiments in the drawing, wherein:

Fig. 1 shows a longitudinal section of a driving device for unlocking and locking a lock, having a housing in the form of a bush, in which a ring with teeth is seated.

Fig. 1a shows the driving device for unlocking and locking a lock, having the housing in the form of a bush having teeth from the inner side.

Fig. 2 shows an exploded perspective view of the driving device of Fig. 1.

Fig. 3 shows an A-A cross section of Fig. 1.

Fig. 3a shows a preferred construction of the electric cell being the electric energy source.

Fig. 4 shows a longitudinal section of a driving device for unlocking and locking a lock, in a third embodiment of the invention.

Fig. 4a shows an A-A cross section of Fig. 4.

Fig. 5 shows an exploded perspective view of the driving device of Fig. 4.

Fig. 6 shows a longitudinal section of a driving device in a fourth embodiment of the invention,

Fig. 6a shows a B-B cross section of Fig. 6.

Fig. 7 shows an exploded perspective view of the driving device of Fig. 6.

Fig. 8 shows a longitudinal section of the driving device in a fifth embodiment of the invention.

Fig. 8a shows a C-C cross-section of Fig. 8.

Fig. 9 shows an exploded perspective view of the driving device of Fig. 7.

Fig. 10 shows a longitudinal section of the driving device in a sixth embodiment of the invention.

Fig. 11a shows a driving device where the electric energy source is in a shape of a cylinder with a centrally-positioned opening, as viewed from the front after removing the cover from the housing.

Fig. 11b shows a longitudinal section of two layered flat electric energy sources in a shape of rings surrounding the motor.

Fig. 12a shows a layered flat electric energy source in a shape of a cylinder with the eccentrically positioned opening, in which the motor is held, in a front view.

Fig. 12b shows a longitudinal section of two layered flat electric energy sources in a shape of a cylinder and with the eccentrically positioned opening, the electric energy sources surrounding the motor.

Fig. 13a shows a layered flat electric energy source having a cavity, in which the motor is placed, in a front view.

Fig. 13b shows a longitudinal section of two layered flat electric energy sources having a cavity, in which the motor is placed.

Fig. 14a shows two layered electric energy sources of a shape similar to that of a half-ring, surrounding the driving motor, with layers in a form of sectors of cylindrical surfaces, in a front view.

Fig. 14b shows a longitudinal section of two layered electric energy sources of a shape similar to that of a half-ring, surrounding the driving motor, with layers in a form of sectors of cylindrical surfaces.

Fig. 15a shows a layered, wound electric energy source in a shape of an open ring, surrounding the driving motor, in a front view.

Fig. 15b shows a longitudinal section of a layered, wound electric energy source in a shape of an open ring, surrounding the driving motor.

Fig. 15c shows a transversal cross section of a layered, wound electric energy source in a shape of an open ring, with a method for winding layers being shown.

Fig. 16a shows two layered wound electric energy sources of a shape similar to that of a half-ring, surrounding the driving motor, in a front view.

Fig. 16b shows a longitudinal cross section of two layered wound electric energy sources of a shape similar to that of a half-ring, surrounding a driving motor.

Fig. 16c shows a cross-section of two layered wound electric energy sources of a shape similar to that of a half-ring, with a method for winding layers being shown.

Fig. 17a shows a driving device when an electric energy source is in a shape of a cylinder with a centrally-positioned opening, in a front view after removing the frontal part from the housing.

Fig. 17b shows a longitudinal section of an electric energy source in a form of a ring, whose layers are wound spirally in the form of a web around the central opening where the driving motor is placed.

Fig. 18a shows two layered electric energy sources in a shape of an open ring, surrounding a motor, whose layers are in a form of sectors of cylindrical surfaces, in a front view.

Fig. 18b shows a longitudinal section of two layered electric energy sources in a shape of an open ring, surrounding a motor, with layers in a form of sectors of cylindrical surfaces.

Fig. 19a shows four layered electric energy sources in a shape of a ring segment, surrounding a driving motor, with layers in a form of sectors of cylindrical surfaces, in a front view.

Fig. 19b shows a longitudinal cross section of four layered electric energy sources in a shape of a ring segment, surrounding a driving motor, with layers in a form of sectors of cylindrical surfaces.

DETAILED DESCRIPTION

As shown in the embodiments of the invention in Fig. 1, Fig. 2 and Fig. 1a, a driving device 1 for unlocking and locking a lock 1' enabling access to protected areas has a cylindrical housing 5. The housing is made in a form of a bush covered at the front with a cover 19. The driving device 1 comprises a single electric energy source 9, having a form of a cylinder with a coaxially positioned opening 11. The electric energy source 9 is fitted with an anode, cathode and separator, all spirally wound in the form of a web around the through hole 11. The outer surface of the electric energy source 9 is the protective housing 12. In the opening 11 a driving motor 10 is arranged for transmitting drive to a rotary control element 3 for the lock 1' mechanism by means of a gear assembly 6. The lock 1' has a body 4, in which the control element 3 is seated rotatably. In the area of the cross-section through the single electric energy source 9 there are at least two points such that a line segment joining these points passes through the area of the cross-section of the driving motor 10, which is evident, *inter alia*, in Fig. 3. A preferred construction of the electric energy source, where anode, cathode and separator are all spirally wound around the through hole is shown in Fig. 3a.

As shown in the embodiments of the invention in Fig. 1, Fig. 2 and Fig. 1a, the driving device 1 is fitted with a base 2 fixed with respect to the lock 1', with the gear assembly 6, electric energy source 9 and driving motor 10 being seated fixedly with respect to the base.

In the embodiments of the invention shown in Fig. 1 and Fig. 1a, the driving device 1 is fitted with a support plate 7 that divides the space inside the housing 5 into a first chamber 22, where the driving motor 10 and the electric energy source 9 are held, and a second chamber 23, where the gear assembly 6 is held.

In the embodiment of the invention shown in Fig. 1a, the control element 3 for the lock 1' mechanism is seated on a toothed wheel 16 being one of the wheels of the gear assembly 6, and the housing 5 is in a form of a rotary bush seated in a bearing in the base 2 and the housing, from the inner side, has teeth 15 engaging with the toothed wheel 16 of the gear assembly 6, on which the control element 3 for the lock 1' mechanism is seated.

In the embodiment of the invention shown in Fig. 1, the control element 3 for the lock 1' mechanism is seated on the toothed wheel 16 being one of the wheels of the gear assembly 6, and the housing 5 is in a form of a rotary bush, in which a ring 17 with teeth 18 is seated, the teeth engaging with the toothed wheel 16 of the gear assembly 6, on which the control element 3 for the lock 1' mechanism is seated.

In the embodiments of the invention shown in Fig. 1 and Fig. 1a, the gear assembly 6 of the driving device 1 comprises a coupling 13, which makes it possible to uncouple the gear 6 connecting the control element 3 to the driving motor 10, with the driving motor 10 being an electric motor. The coupling 13 makes it possible to manually control the lock more easily by rotation of the housing 5, with no resistance from the driving motor 10. The driving device 1 is fitted with an electronic control unit 8, which controls the driving motor 10. The electronic control unit 8 is controlled wirelessly by means of computer software, preferably a mobile device application, via a wireless connection. The electronic control unit 8 may also be controlled wirelessly via a Bluetooth wireless connection.

As shown in the embodiments of the invention in Fig. 4, Fig. 4a, Fig. 5, Fig. 6, Fig. 6a, Fig. 7, Fig. 8 and Fig. 8a, a driving device 1 for unlocking and locking a lock 1' enabling access to protected areas has a housing 5 in a form of a can covered at the front with the frontal part 2. Inside the housing 5 there are two electric energy sources 9, a driving motor 10 and a gear assembly 6. The driving device 1 is fitted with a support plate 7 dividing the space inside the housing 5 into a first chamber 19, where the driving motor 10 and two electric energy

sources 9 are held, and a second chamber 20, where the gear assembly 6 is held. The driving motor 10 is an electric motor. In the bottom of the housing 5 there is an opening, in which one of toothed wheels 16 of a gear assembly 6 is seated by means of a bearing 13. The lock 1' has the body 4, in which a control element 3 is seated rotatably for moving a dog 21 of the lock 1'. The driving motor 10 transmits drive to the control element 3 for the lock 1' mechanism by means of the gear assembly 6 and a ring 17 with teeth 18. Rotation of the driving motor causes rotation of the housing 5 and control element 3 by the toothed wheel 16 rolling along the ring 17 with the teeth 18. The electric energy sources 9 are shaped such that they at least partially surround the driving motor 10. The outer surface of the electric energy source 9 is the protective housing 12. In the area of the cross-section through the single electric energy source 9 there are at least two points such that a line segment joining these points passes through the area of the cross-section of the driving motor 10, which is evident, *inter alia*, in Fig. 4a.

In the embodiments of the invention shown in Fig. 4, Fig. 4a, Fig. 5, Fig. 6, Fig. 6a, Fig. 7, Fig. 8 and Fig. 8a, electric energy sources 9 of layered structure were used, where anode, cathode and separator are all arranged in layers, the plane of which is perpendicular to the axis of the driving motor 10. In the embodiment of the invention shown in Fig. 4, Fig. 4a, Fig. 5 and Fig. 10, the protective housing 12 of the electric energy source 9 has a through hole 11, in which the driving motor 10 is arranged. In

cross-section, the protective housing 12 of the electric energy source 9 is wheel-shaped, and the opening 11 is positioned coaxially. In the embodiment of the invention shown in Fig. 6, Fig. 6a and Fig. 7, the opening 11 is positioned eccentrically. In the embodiment of the invention shown in Fig. 8, Fig. 8a, Fig. 9, the protective housing 12 of the electric energy source 9 has a cavity 14, in which the driving motor 10 is arranged. The shape of the cavity 14 is cross-sectionally a segment of a wheel.

As shown in the embodiments of the invention in Fig. 4, Fig. 6, Fig. 8 and Fig. 10, the housing 5 is seated in a bearing rotatably with respect to the body 4 of the lock 1' and is connected fixedly with the control element 3 for the lock 1'. The driving device 1 is fitted with the ring 17 with teeth 18 cooperating with the toothed wheel 16, being one of the wheels of the gear assembly 6 and seated in a bearing in the housing 5. The ring 17 is positioned coaxially with the rotary housing 5 and fixedly with respect to the body 4 of the lock 1'. The ring 17 is arranged between the gear assembly 6 and the lock 1'. In the embodiments of the invention shown in Fig. 4, Fig. 6, Fig. 8 and Fig. 10, the ring 17 is affixed to the lock 1' by means of a screw 15, but it is clear that in other embodiments of the invention the fixed connection of the

ring 17 and the lock 1' may be realised with the use of other known methods, for example by means of gluing, riveting or shaping.

As shown in the embodiments of the invention in Fig. 4, Fig. 6 and Fig. 8, the teeth 18 of the ring 17 are inner teeth, whereas in the embodiment of the invention shown in Fig. 10, the teeth 18 of the ring 17 are outer teeth.

As shown in the embodiments of the invention in Fig. 4, Fig. 6, Fig. 8 and Fig. 10, the driving device 1 is fitted with an electronic control unit 8 which controls the driving motor 10. The electronic control unit 8 is held between the driving motor 10 and the frontal part 2 of the housing 5. The electronic control unit 8 is fitted with a first sensor 26 cooperating with a manual control button 25 arranged on the frontal part 2 of the driving device 1. The electronic control unit 8 is fitted with a second sensor 27 which establishes angular position of the rotary housing 5. The second sensor 27 is an accelerometer (a sensor establishing angular position of the rotary housing 5 with respect to the gravity field of the Earth). The electronic control unit 8 is controlled wirelessly by means of computer software, preferably a mobile device application, via a wireless connection.

The electronic control unit 8 may also be controlled wirelessly via a Bluetooth wireless connection.

As shown in the embodiments of the invention in Fig. 4, Fig. 6, Fig. 8 and Fig. 10, the housing 5 is connected to the control element 3 by means of a shaped releasable connection 22. The housing 5 is fitted with an electric socket 23 accessible after disconnection of the shaped releasable connection 22 and invisible in the connected position. The electric socket 23 is a micro USB type socket intended to deliver supply voltage, charge the electric energy source 9 and transfer data. The shaped releasable connection of the housing 5 and the control element 3 may of course be realised by other known methods.

In all embodiments of the invention shown in Fig. 1, Fig. 1a, Fig. 2, Fig. 3, fig 3a, Fig. 4, Fig. 4a, Fig. 5, Fig. 6, Fig. 6a, Fig. 7, Fig. 8, Fig. 8a, Fig. 9, Fig. 10, Fig. 11a, Fig. 11b, Fig. 12a, Fig. 12b, Fig. 13a, Fig. 13b, Fig. 14a, Fig. 14b, Fig. 15a, Fig. 15b, Fig. 15c, Fig. 16a, Fig. 16b and Fig. 16c, 17a, Fig. 17b, Fig. 18a, Fig. 18b, Fig. 19a, Fig. 19b, the electric energy source 9 is so shaped that it at least partially surrounds the driving motor 10, and in the area of cross-section through an individual electric energy source 9 there are at least two points such that a line segment joining these points passes through the area of cross-section of the driving motor 10.

In the embodiments of the invention shown in Fig. 1, Fig. 1a, Fig. 2 and Fig. 3, fig 3a, Fig. 4, Fig. 4a, Fig. 5, Fig. 11a and Fig. 11b, Fig. 17a, Fig. 17b, the electric energy source 9 is in the shape of a cylinder with a wheel-shaped opening 11, positioned coaxially, and in the embodiment of the invention shown in Fig. 6, Fig. 6a and Fig. 7, Fig. 12a, Fig. 12b, the opening 11 is positioned eccentrically. Inside the opening 11 there is the driving motor 10.

In the embodiments of the invention shown in Fig. 8, Fig. 8a, Fig. 9, Fig. 13a, Fig. 13b, Fig. 14a, Fig. 14b, Fig. 15a, Fig. 15b, Fig. 15c, Fig. 16a, Fig. 16b, Fig. 16c, Fig. 18a, Fig. 18b, Fig. 19a, Fig. 19b, the electric energy source 9 has a cavity 14, in which the driving motor 10 is arranged. The shape of the cavity 14 in cross-section is a segment of a wheel. In the embodiments of the invention shown in Fig. 14a, Fig. 14b, Fig. 15a, Fig. 15b, Fig. 16a, Fig. 16b, Fig. 18a, Fig. 18b, Fig. 19a, Fig. 19b, the protective housing 12 of the electric energy source 9 is a segment of a ring, the axis of whose is parallel to the axis of the driving motor 10.

In the embodiments of the invention shown in Fig. 14a, Fig. 14b, Fig. 16a, Fig. 16b, Fig. 16c, Fig. 18a and Fig. 18b, there are two electric energy sources 9 in a shape being a segment of a ring, and in the embodiment shown in Fig. 19a and Fig. 19b, there are four such electric energy sources 9.

As shown in Fig. 3a, Fig. 17a, Fig. 17b, the electric energy source 9 is fitted with an anode 9a, cathode 9c and separator 9b, all spirally wound in a form of a web around the through hole 11.

In the embodiments of the invention shown in Fig. 14a, Fig. 14b, Fig. 18a, Fig. 18b, Fig. 19a and Fig. 19b, the electric energy source 9 is fitted with the anode 9a, cathode 9c and separator 9b, all arranged in layers being sectors of cylindrical surfaces of an axis parallel to the axis of the driving motor 10. And in the embodiments of the invention shown in Fig. 15a, Fig. 15b, Fig. 15c, Fig. 16a, Fig. 16b, Fig.16c, the electric energy source 9 is fitted with an anode, cathode and separator all spirally wound and shaped in the form of an open ring, as in Fig. 15a, Fig. 15b, Fig.15c or ring segments, as in Fig. 16a, Fig. 16b, Fig. 16c,

It is clear that the electric energy source 9 may also have other forms not shown in the picture, the forms fulfilling the requirements that the electric energy source 9 is so shaped that it at least partially surrounds the driving motor 10. The energy source 9 being so shaped and arranged with respect to the driving motor 10 enables essential reduction of the overall dimensions of the driving device 1.

The electric energy source 9 is a primary or secondary electric cell.

The driving device 1 is arranged at the inner side (not shown) of an entrance to access-protected areas and on the opposite side to the key-controlled part of the lock 1'.

Claims

1. Driving device (1) for unlocking and locking a lock (1') enabling access to protected areas, within its housing (5) comprising: a gear assembly (6), at least one electric energy source (9) in a protective housing (12) and an electric driving motor (10), transmitting drive to a rotary control element (3) for the lock (1') mechanism by means of a gear assembly (6), wherein the lock (1') has a body (4), where the control element (3) is seated rotatably, **characterized in that** an individual electric energy source (9) is so shaped that with its shape, in cross-section through the driving motor (10) and the electric energy source (9), it at least partially surrounds the driving motor (10), which means that in the area of cross-section through the electric energy source (9) there are at least two points such that a line segment joining these points passes through the area of cross-section of the driving motor (10).

2. The driving device of claim 1, **characterized in that** it is fitted with a base (2), fixed with respect to the lock (1'), with the gear assembly (6), the at least one electric energy source (9) and driving motor (10) being seated fixedly with respect to the base.

3. The driving device of claim 1, **characterized in that** the control element (3) for the lock (1') mechanism is seated on a toothed wheel (16), being one of the wheels of the gear assembly (6); and the housing (5) is in a form of a bush seated in a bearing in the base (2) and from the inner side it has teeth (15) engaging the toothed wheel (16) of the gear assembly (6), on which the control element (3) for the lock 1' mechanism is seated.

4. The driving device of claim 1, **characterized in that** the housing (5) is seated in a bearing rotatably with respect to the body (4) of the lock (1) and is connected fixedly with the control element (3) for the lock (1'); and the gear assembly (6), the at least one electric energy source (9) and the driving motor (10) are seated fixedly with respect to the housing (12) and they rotate together with the housing, with the driving device (1) being fitted with a ring (17) with teeth (18) cooperating with the toothed wheel (16) being one of the wheels of the gear assembly (6) and seated in a bearing in the housing (5), with the ring (17) being positioned coaxially with the rotary housing (5) and fixedly with respect to the body (4) of the lock (1').

5. The driving device of claim 4, **characterized in that** the ring (17) is arranged between the gear assembly (6) and the lock (1').

6. The driving device of claim 4, **characterized in that** the teeth (18) of the ring (17) are inner or outer teeth.

7. The driving device of claim 1, **characterized in that** the housing (5) is connected to the control element (3) by means of a shaped releasable connection (22).

8. The driving device of claim 1, **characterized in that** the housing (5) is fitted with an electric socket (23), preferably a micro USB type socket, intended to charge the electric energy source (9).

9. The driving device of claim 1, **characterized in that** the protective housing (12) of the electric energy source (9) has a through hole (11), in which the driving motor (10) is arranged.

10. The driving device of claim 9, **characterized in that** the protective housing (12) of the electric energy source (9) is cross-sectionally wheel-shaped, with the opening (11) positioned coaxially.

11. The driving device of claim 10, **characterized in that** the protective housing (12) of the electric energy source (9) is cross-sectionally wheel-shaped, with the opening (11) positioned eccentrically.

12. The driving device of claim 1, **characterized in that** the protective housing (12) of the electric energy source (9) has a cavity (14), in which the driving motor (10) is arranged.

13. The driving device of claim 12, **characterized in that** the shape of the cavity (14) cross-section is a segment of a wheel.

14. The driving device of claim 1, **characterized in that** the protective housing (12) of the electric energy source (9) is a segment of a ring, the axis of whose is parallel to the axis of the driving motor (10).

15. The driving device of claim 1, **characterized in that** the electric energy source (9) is either a primary electric cell or a secondary electric cell.

16. The driving device of claim 4, **characterized in that** the electric energy source (9) is fitted with an anode, cathode and separator, all spirally wound in the form of a web around the through hole (11).

17. The driving device of claim 4, **characterized in that** the electric energy source (9) is fitted with an anode, cathode and separator, all arranged in layers, the plane of whose is perpendicular to the axis of the driving motor (10).

18. The driving device of claim 4, **characterized in that** the electric energy source (9) is fitted with an anode, cathode and separator, all arranged in layers being sectors of cylindrical surfaces of an axis parallel to the axis of the driving motor (10).

19. The driving device of claim 1, **characterized in that** the gear assembly (6) comprises a coupling (13).

20. The driving device of claim 1, **characterized in that** it is fitted with an electronic control unit (8) for controlling the driving motor (10) and preferably fitted with a first sensor (26) cooperating with a manual control button (25), arranged on the frontal part (2) of the driving device (1).

21. The driving device of claim 20, **characterized in that** the electronic control unit (8) is fitted with a second sensor (27) which establishes angular position of the rotary housing (5), the second sensor preferably being an accelerometer or gravitational field sensor.

22. The driving device of claim 21, **characterized in that** the electronic control unit (8) is controlled wirelessly, preferably by means of computer software, preferably a mobile device application, via a wireless connection.




Fig. 1




Fig. 1a




Fig. 2




Fig. 3




Fig. 3a




Fig. 4




Fig. 4a




Fig. 5




Fig. 6




Fig. 6a




Fig. 7




Fig. 8




Fig. 8a




Fig. 9




Fig. 10

16/18




Fig. 11a




Fig. 11b




Fig. 12a




Fig. 12b




Fig. 13a




Fig. 13b




Fig. 14a




Fig. 14b




Fig. 15a




Fig. 15b




Fig. 15c




Fig. 16a




Fig. 16b




Fig. 16c




Fig. 17a




Fig. 17b




Fig. 18a




Fig. 18b




Fig. 19a




Fig. 19b

