



(51) International Patent Classification:

F24F 13/068 (2006.01) *F24F 13/08* (2006.01)
F24F 13/075 (2006.01)

(21) International Application Number:

PCT/US2017/051571

(22) International Filing Date:

14 September 2017 (14.09.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/395,035 15 September 2016 (15.09.2016) US

(71) Applicant: **ARMSTRONG WORLD INDUSTRIES, INC.** [US/US]; 2500 Columbia Avenue, P.O. Box 3001, Lancaster, Pennsylvania 17604-3001 (US).

(72) Inventor: **FRANTZ, William H.**; 20 Woodview Drive, Elizabethtown, Pennsylvania 17022 (US).

(74) Agent: **STERNER, Craig M.**; Armstrong World Industries, INC., 2500 Columbia Avenue, P.O. Box 3001, Lancaster, Pennsylvania 17604-3001 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(54) Title: CEILING SYSTEM WITH AIR MOVEMENT




FIG. 1

(57) Abstract: A ceiling system is provided that has a ceiling structure suspended within a space of a building thereby dividing the space into an occupied space below the ceiling structure and a plenum space above the ceiling structure; a panel structure supported by the ceiling structure and having an opening; a pressurized air passageway aligned with the opening, the pressurized air passageway having an outlet; and an inductive air passageway adjacent the pressurized air passageway, the inductive air passageway having an inlet and an outlet. Wherein the pressurized air passageway and the inductive air passageway are configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

CEILING SYSTEM WITH AIR MOVEMENT

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a PCT International Application that claims the benefit of U.S. Provisional Application No. 62/395,035, filed on September 15, 2016. The disclosure of the above application is incorporated herein by reference.

FIELD

[0002] The present invention relates to building ceiling systems. Particular embodiments of the invention relate to an air moving system used with a suspended acoustical ceiling system.

BACKGROUND

[0003] Many types of ceiling systems include panels, such as, for example, acoustical panels that are suspended from a building structure and separate a building space into an occupied space below the ceiling system and a plenum space above the ceiling system.

[0004] Such suspended ceiling systems can present challenges and with regard to heating, ventilation, and air conditioning of the occupied space. Some suspended ceiling systems include grills, registers and diffusers or other openings that allow conditioned air from an HVAC (heating, ventilating, and air conditioning) system to enter the occupied space.

[0005] Various systems and methods for improving thermal comfort in an occupied space exist.

[0006] These include using a passive thermal mass such as stone, concrete, brick, or water to passively store and released thermal energy to the thermal benefit of the occupants of the occupied space.

[0007] Another way to improve thermal comfort is to use fans to produce the desired airflow across occupants of the occupied space (“adaptive comfort”). Thermally comfortable conditions can be achieved in even very hot environments when air flow is introduced over people’s bodies. A significant energy saving benefit can be recognized when an adaptive comfort strategy is used to create desired thermal conditions in the building. With an adaptive comfort strategy, air temperatures can be allowed to increase well above “normal” set point temperatures. For example, set point temperatures may be increased from 75° F up

to 82° F. Typically, this would create a very uncomfortable thermal environment in a building. However, when local air flow is introduced these conditions are perceived as quite pleasant by many occupants. Another very significant benefit to this adaptive comfort strategy is that for each 1° F increase in set point temperature that is permitted in a building, a resulting energy savings of from 3% to 5% can be realized. Allowing the set point temperature to increase 7° F (from 75° F to 82° F) can produce an energy savings of between 21% and 35%.

[0008] Yet another way to improve thermal comfort is the use of radiant heating and cooling systems. Modern, ceiling-based radiant heating and cooling panels offer significant energy savings to the user but are essentially capacity-limited by the rate of radiant heat transfer between the panel and the occupants of the space.

SUMMARY

[0009] Certain problems exist with each of the three methods for improving thermal comfort described above.

[0010] Fans can be added to passive thermal mass systems. However, the acoustical issues with the hard surfaces typically used for these systems would remain. Embodiments of the invention introduce acoustic absorption while simultaneously increasing the thermal performance of the thermally massive material.

[0011] Bladed fans, bladeless fans, or “punkah” style fans can be used to create air motion in adaptive comfort strategies. However, these fans are typically very intrusive and very noticeable in the space. In some cases, such as a classroom for children, moving blades might be undesirable as they can be distracting. Embodiments of the invention have no moving parts in the occupied space. The air mover is integrated in the design of the ceiling panel and is essentially hidden from view. Embodiments of the invention use an induction style venturi to induce air motion. This is a very energy efficient way of moving large volumes of air. Embodiments of the invention can also introduce varying flow or oscillating flow rates to simulate a more natural breeze as experienced outdoors in nature.

[0012] Fans can be used as separate elements to existing radiant panels. However, adding such fans to an existing system would be inelegant. Embodiments of the invention integrate the air mover fully within the design of a ceiling panel. The ceiling panel is located up in the ceiling void in close proximity to the existing radiant panel system.

[0013] Particular embodiments of the invention provide a ceiling system that includes a ceiling structure suspended within a space of a building thereby dividing the space into an occupied space below the ceiling structure and a plenum space above the ceiling structure; a panel structure supported by the ceiling structure and having an opening; a pressurized air passageway aligned with the opening, the pressurized air passageway having an outlet; and an inductive air passageway adjacent the pressurized air passageway, the inductive air passageway having an inlet and an outlet. The pressurized air passageway and the inductive air passageway are configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.

[0014] Some embodiments include the induced air flow being air from the plenum that flows through the inductive air passageway.

[0015] Some embodiments include the panel structure being an acoustical panel structure.

[0016] Some embodiments include the panel structure being a canopy-type panel structure that is configured such that the panel structure is spaced away from a wall of the occupied space.

[0017] Some embodiments include the outlet of the inductive air passageway directing the induced airflow toward the occupied space.

[0018] Some embodiments include the pressurized air and the induced air flow mixing together at the outlet of the pressurized air passageway.

[0019] Some embodiments include the pressurized air passageway being fluidly connected to an air supply space other than the plenum space and drawing the pressurized air from the air supply space.

[0020] Some embodiments include the pressurized air passageway being tubular.

[0021] Some embodiments include the pressurized air passageway including a venturi.

[0022] Some embodiments include the outlet of the pressurized air passageway being a slot.

[0023] Some embodiments include the inductive air passageway being formed by an air diverter located near an outside surface of the pressurized air passageway.

[0024] Some embodiments include the inductive air passageway comprising two inductive air passageways, each of the inductive air passageways being formed by an air diverter located near an outside surface of the pressurized air passageway.

[0025] Some embodiments include the pressurized air passageway being located between the air diverters.

[0026] Some embodiments include an air moving device that supplies pressurized air to the pressurized air passageway.

[0027] Some embodiments include the pressurized air passageway being ring shaped, and the outlet being a slot in the lower side of the ring shape.

[0028] Some embodiments include the pressurized air passageway and the inductive air passageway being located within a field area of the panel structure, the field area of the panel structure being an area away from all edges of the panel structure.

[0029] Some embodiments include the pressurized air passageway and the inductive air passageway being attached to an edge of the panel structure.

[0030] Some embodiments include a plurality of panel structures, wherein the pressurized air passageway and the inductive air passageway are attached to an edge of one of the plurality of panel structures, and the pressurized air passageway and the inductive air passageway are located between two adjacent ones of the plurality of panel structures.

[0031] Some embodiments include a phase change material attached to, or integral with, the panel structure.

[0032] Some embodiments include a water evaporation device, the water evaporation device being configured to present water to the pressurized air or the inductive air flow.

[0033] Particular embodiments of the invention provide a method of moving air in an occupied space in a building. The method includes dividing with a ceiling structure the space in the building into an occupied space below the ceiling structure and a plenum space above the ceiling structure; providing an opening in a panel structure supported by the ceiling structure; and inducing an induced airflow out of an outlet of an inductive air passageway by passing pressurized air through an outlet of a pressurized air passageway, the inductive air passageway being adjacent the pressurized air passageway, and the pressurized air passageway being aligned with the opening in the panel structure. The pressurized air passageway and the inductive air passageway are configured such that pressurized air passing

through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.

[0034] Some methods of the invention include the induced air flow being air from the plenum that flows through the inductive air passageway.

[0035] Some methods of the invention include the panel structure being an acoustical panel structure.

[0036] Some methods of the invention include the panel structure being a canopy-type panel structure that is configured such that the panel structure is spaced away from a wall of the occupied space.

[0037] Some methods of the invention include the induced airflow being directed toward the occupied space by the outlet of the inductive air passageway.

[0038] Some methods of the invention include the pressurized air and the induced air flow being mixed together at the outlet of the pressurized air passageway.

[0039] Some methods of the invention include the pressurized air passageway being fluidly connected to an air supply space other than the plenum space and the pressurized air being drawn from the air supply space.

[0040] Some methods of the invention include the pressurized air passageway being tubular.

[0041] Some methods of the invention include the feature of the pressurized air passageway including a venturi.

[0042] Some methods of the invention include the outlet of the pressurized air passageway being a slot.

[0043] Some methods of the invention include the inductive air passageway being formed by an air diverter located near an outside surface of the pressurized air passageway.

[0044] Some methods of the invention include the inductive air passageway comprising two inductive air passageways, each of the inductive air passageways being formed by an air diverter located near an outside surface of the pressurized air passageway.

[0045] Some methods of the invention include the pressurized air passageway being located between the air diverters.

[0046] Some methods of the invention include supplying pressurized air to the pressurized air passageway with an air moving device.

[0047] Some methods of the invention include the pressurized air passageway being ring shaped, and the outlet being a slot in the lower side of the ring shape.

[0048] Some methods of the invention include the pressurized air passageway and the inductive air passageway being located within a field area of the panel structure, the field area of the panel structure being an area away from all edges of the panel structure.

[0049] Some methods of the invention include the pressurized air passageway and the inductive air passageway being attached to an edge of the panel structure.

[0050] Some methods of the invention include locating the pressurized air passageway and the inductive air passageway between two adjacent ones of a plurality of panel structures, wherein the pressurized air passageway and the inductive air passageway are attached to an edge of one of the plurality of panel structures.

[0051] Some methods of the invention include a phase change material attached to, or integral with, the panel structure.

[0052] Some methods of the invention include presenting water to the pressurized air or the inductive air flow with a water evaporation device.

[0053] Particular embodiments of the invention provide a ceiling system including a ceiling structure suspended within a space of a building thereby dividing the space into an occupied space below the ceiling structure and a plenum space above the ceiling structure; a first panel structure supported by the ceiling structure and having an edge; a pressurized air passageway attached to the edge of the first panel structure, the pressurized air passageway having an outlet; and an inductive air passageway adjacent the pressurized air passageway, the inductive air passageway being attached to the edge of the first panel structure and having an inlet and an outlet. The pressurized air passageway and the inductive air passageway are configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.

[0054] Some embodiments include the first panel structure being oriented in a baffle-style arrangement such that the edge of the first panel structure is a lowest edge of the first panel structure, and the inductive air passageway is located below the edge of the first panel structure.

[0055] Some embodiments include a second panel structure supported by the ceiling structure.

[0056] Some embodiments include the second panel structure having a lower edge, the first panel structure and the second panel structure being oriented in a baffle-style arrangement, and the first panel structure and the second panel structure being attached to each other such that the inductive air passageway is attached to and is located below the lower edge of the first panel structure and the lower edge of the second panel structure.

[0057] Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0058] The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0059] FIG. 1 is a sectional view of an occupied space, ceiling system, and plenum space;

[0060] FIG. 2 is a perspective view of a ceiling system having an air mover hanging below a suspended ceiling;

[0061] FIG. 3 is a perspective view of an example of a ceiling panel in accordance with the embodiment shown in Fig. 2;

[0062] FIG. 4 is a partial sectional view of an example of a ceiling panel in accordance with the embodiment shown in Fig. 2;

[0063] FIG. 5 is a partial sectional view of an annular induction air mover;

[0064] FIG. 6 is a partial sectional view of the annular induction air mover of Fig. 5;

[0065] FIG. 7 is a perspective view of a ceiling system having a rectangular air mover;

[0066] FIG. 8 is a perspective view of a canopy ceiling system in which an air mover is an integral part of the ceiling system;

[0067] FIG. 9 is a partial sectional view of the canopy ceiling system of Fig. 8;

[0068] FIG. 10 is a perspective view of a baffle type ceiling system in which an air mover is an integral part of the ceiling system;

[0069] FIG. 11 is a perspective view of an angled canopy ceiling system in which an air mover is an integral part of the ceiling system;

[0070] FIG. 12 is an enlarged view of the ceiling system of Fig. 11;

[0071] FIG. 13 is a sectional view of the ceiling system of Figs. 11 and 12;

[0072] FIG. 14 is a partial sectional view of a baffle type ceiling system in which an air mover is an integral part of the ceiling system;

[0073] FIG. 15 is a perspective view of an oscillating induction air mover mounted to a ceiling panel;

[0074] FIG. 16 is a perspective view of the ceiling panel of Fig. 15;

[0075] FIG. 17 is a perspective view of an induction air mover positioned above a ceiling panel that includes a thermal mass;

[0076] FIG. 18 is a perspective view of an induction air mover attached to a ceiling panel that includes a thermal mass; and

[0077] FIG. 19 is a side view of ceiling system having an air mover that moves air across a radiant surface.

[0078] All drawings are schematic and not necessarily to scale. Parts given a reference numerical designation in one figure may be considered to be the same parts where they appear in other figures without a numerical designation for brevity unless specifically labeled with a different part number and described herein.

DETAILED DESCRIPTION

[0079] The following description of the preferred embodiments is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

[0080] In the description of embodiments disclosed herein, any reference to direction or orientation is merely intended for convenience of description and is not intended in any way to limit the scope of the present invention. Relative terms such as "lower," "upper," "horizontal," "vertical," "above," "below," "up," "down," "top" and "bottom" as well as derivative thereof (e.g., "horizontally," "downwardly," "upwardly," etc.) should be construed to refer to the orientation as then described or as shown in the drawing under discussion. These relative terms are for convenience of description only and do not require that the

apparatus be constructed or operated in a particular orientation. Terms such as “attached,” “connected,” “coupled,” “interconnected,” and similar refer to a relationship wherein structures are secured or attached to one another either directly or indirectly through intervening structures, as well as both movable or rigid attachments or relationships, unless expressly described otherwise. The term “fixed” refers to two structures that cannot be separated without damaging one of the structures. The term “filled” refers to a state that includes completely filled or partially filled.

[0081] As used throughout, ranges are used as shorthand for describing each and every value that is within the range. Any value within the range can be selected as the terminus of the range. In addition, all references cited herein are hereby incorporated by reference in their entireties. In the event of a conflict in a definition in the present disclosure and that of a cited reference, the present disclosure controls.

[0082] The term “opening” as used in this application can refer to any passageway through which air can travel.

[0083] As explained above, occupant comfort and operating efficiency can be improved by implementing systems and methods according to embodiments of the invention. Particular embodiments use inductive airflow incorporated into a ceiling panel to achieve these benefits.

[0084] Many types of ceiling systems and methods for mounting ceiling panels have been used. One type of system uses a suspended metal support grid including an array of orthogonally intersecting grid support members. An array of grid openings are formed between the grid support members. These openings are filled by the ceiling panels. Ceiling panels are mounted to and supported by the support grid using numerous approaches. Other types of ceiling systems can use ceiling panels, such as plank ceiling systems, canopy type ceiling systems and baffle type ceiling systems.

[0085] A building panel can be part of a building system such as a ceiling or wall. In particular embodiments, the building panel is part of a ceiling system which separates an occupied space from a plenum space. The occupied space is space below the ceiling system such as office space or the like. The plenum space is space above the ceiling system in which mechanical, electrical and other building systems and equipment can be housed. In some situations, the plenum space is simply an open space above the ceiling system and below the upper structure of the building space.

[0086] Fig. 1 shows an example of one type of suspended ceiling system. In this example, an occupied space 10 such as, for example, office space is shown below a ceiling system 20 that extends to and contacts all four walls of the office space. Above ceiling system 20 and below structural slab 60 is a plenum space 30 that can house building systems such as ductwork, wiring, water piping and fire sprinkler piping. Ceiling system 20 includes a plurality of panels 40 supported by a suspended grid structure 50. Other types of suspended ceiling systems will be described below.

[0087] Fig. 2 shows an example of a ceiling system 100 that separates a building space into an occupied space 10 and a plenum space 30. Plenum space 30 is above ceiling system 100 and below structural slab 60. Ceiling system 100 has a plurality of ceiling panels 200 that, in this example, are acoustic ceiling panels. An air moving system 300 is shown in this example as integrated into a group of four ceiling panels 200. In other examples, such as the example shown in Figs. 3 and 4, air moving system 300 is integrated into a single ceiling panel 200. While the example shown in Fig. 2 is a round air moving system, other shapes can also be used. For example, Fig. 7 shows an example of a square air moving system 500. In Fig. 7, air moving system 500 is shown as integrated into a group of four ceiling panels 200. In other examples, air moving system 500 is integrated into a single ceiling panel 200.

[0088] As shown in Figs. 3 and 4, air moving system 300 has a body 310 that defines a pressurized air passageway 320. Pressurized air exits pressurized air passageway 320 through an opening 322 along the bottom of body 310. In Fig. 3, body 310 is mounted directly to ceiling panel 200, whereas in Fig. 4, body 310 is mounted to ceiling panel 200 by way of one or more supports 330. Supports 330 can be hollow to provide a conduit for the pressurized air from an air source above ceiling panel 200 to pressurized air passageway 320. The air source can be a fan located in plenum space 30 or a remotely located fan that pushes air through ductwork that is located in plenum space 30.

[0089] Figs. 5 and 6 show an example of an embodiment of the invention that induces airflow by the use of a venturi. In such embodiments, pressurized air is fed into a venturi to increase the air flow velocity and then exhausted adjacent to one or more inductive air passageways such that the exhausted pressurized air induces air flow through the inductive air passageways. An air moving system 400 has a pressurized air passageway 420 inside a body 410. Pressurized air passageway 420 is fed pressurized air from a remote fan or other air mover that can be located in the plenum space, or located outside of the plenum space and pushes air through ductwork that is located in the plenum space. In this example, the

pressurized air can be routed through one or more supports 445. In this example, two air diverters 430 are positioned adjacent to body 410 to create inductive air passageways 440. Other examples can have one or more than two inductive air passageways. As the pressurized air flows out of an outlet 470 of pressurized air passageway 420 (represented by arrow B), low pressure regions are created at outlets 450 of inductive air passageways 440. These low pressure regions result in air being drawn (represented by arrows A) into inductive air passageways 440 and expelled from outlet 460. The pressurized air flowing from outlet 470 and the induced airflow from outlets 450 mixes and is distributed into the occupied space. Such an induced airflow system can provide increased airflow economically and less obtrusively than a conventional fan. In addition, when the induced airflow is drawn from the occupied space, as in this example, increased circulation is achieved with a reduced fan requirement. This increased circulation provides additional efficiency by mixing the pressurized air, which may be heated or cooled, with the air that is in the occupied space.

[0090] Other examples of the invention draw the induced airflow from an area outside of the occupied space, such as, for example, the plenum space. Figs. 8 and 9 show such an example. In Fig. 8, a canopy type ceiling system 100 is shown. In such a canopy type ceiling system, one or more ceiling panels 210 are suspended in a building space to divide the building space into an occupied space 10 and a plenum space 30. Plenum space 30 is located between ceiling system 100 and structural slab 60. Canopy type ceiling systems usually do not extend all the way to the walls of the occupied space, but instead are positioned away from the walls so as to create gaps. Similarly, ceiling panels 210 in a canopy type ceiling system are usually spaced apart such that they do not contact each other. However, in some canopy type ceiling systems, multiple panels can contact each other to form one or more canopies.

[0091] Evaporative cooling can be included in any of the embodiments of the invention. An example of such evaporative cooling includes introducing water into the pressurized air passageway or the inductive air passageway. This can be done by, for example, wetting a surface (such as a porous surface or a wick) in one of the passageways or spraying water into one of the air streams.

[0092] In the system shown in Figs. 8 and 9, an air moving system 600 is located in an opening 211 in ceiling panel 210. Similar to the system shown in Figs. 5 and 6, air moving system 600 has a pressurized air passageway inside a body 610. The pressurized air passageway is fed pressurized air from a remote fan or other air mover that can be located in

plenum space 30, or located outside of plenum space 30 and pushes air through ductwork that is located in plenum space 30. In this example, the pressurized air can be routed through one or more supports (not shown). In this example, two air diverters 630 are positioned adjacent to body 610 to create an inductive air passageway on either side of body 610. Other examples can have one or more than two inductive air passageways. As the pressurized air flows out of the outlet at the bottom of the pressurized air passageway, low pressure regions are created at the outlets of the inductive air passageways. These low pressure regions result in air being drawn into the inductive air passageways and expelled from outlet of body 610. The pressurized air flowing from the outlet of body 610 and the induced airflow from the outlets of the inductive air passageways mixes and is distributed into the occupied space. In this example, the induced airflow is drawn from plenum space 30. This arrangement draws the air that can stagnate above a canopy type (or other type) ceiling and circulates it into the occupied space.

[0093] In some embodiments of the invention, the ceiling panel is an acoustic panel. The acoustic panel can be made from a range of fibers, porous materials including mineral fiber, wood wool, fiberglass, rock wool, sintered metals, foamed polymeric materials, and perforated metals, for example.

[0094] While the air diverters in the examples shown above are curved, linear air diverters can also be used (as seen in the example shown in Figs. 11-13). The air diverters and the body of the air moving system can be made, for example, from metal or polymeric materials.

[0095] As stated above, the fan or other air mover can be mounted on the ceiling panel or can be remotely located. Locating the fan and motor remotely from the occupied space and/or the plenum space has the advantages of removing a source of heat and noise from the occupied space. Also, a single (or multiple) remotely located fan can provide pressurized air to multiple air moving systems.

[0096] Another form of suspended ceiling that can be improved by embodiments of the invention is the baffle type ceiling. Fig. 10 shows a baffle type ceiling system 300 having a plurality of vertically oriented baffles 220 that separate a building space into an occupied space 10 and a plenum space 30. Plenum space 30 is located between baffles 220 and a structural slab 60. An air moving system 700 is incorporated into particular ones of baffles 220 to create an unobtrusive and efficient air moving system. Air moving system 700 can be similar to air moving system 600 shown in Fig. 9, but split into two semi-circles that are

attached to either side of one of the baffles 220. While a semi-circular shape is shown in the figures, other shapes such as, for example, diamond, square, rectangular, triangle, oval, compound curve, or other shape can also be used. The pressurized air can be fed to air moving system 700 by way of a conduit that runs inside baffle 220 and is therefore hidden from view, or it can be fed by way of a conduit that is a separate support for air moving system 700. The fan or air mover that supplies the pressurized air to air moving system 700 can be located inside baffle 220, on top of baffle 220, in the plenum space, or remotely from the building space.

[0097] Figs. 11-13 show an example of another type of ceiling system that can be improved by embodiments of the invention. Fig. 11 shows a canopy type ceiling system that has panels 230 extending in the shape of wings from a central spine. Panels 230 separate a building space into an occupied space 10 and a plenum space 30. Plenum space 30 is located between panels 230 and a structural slab 60. This system has an air moving system 800 that acts as the spine to which panels 230 are attached. Some embodiments have only one panel 230 extending from each side of the spine, whereas other embodiments have multiple panels 232 extending from each side.

[0098] Figs. 12 and 13 show air moving system 800 in more detail. Similarly to the other examples discussed, air moving system 800 has a pressurized air passageway 820 inside a body 810. Pressurized air passageway 820 is fed pressurized air from a remote fan or other air mover that can be located in the plenum space, or located outside of the plenum space and pushes air through ductwork that is located in the plenum space. In this example, the pressurized air can be routed through one or more supports (not shown). In this example, two air diverters 830 are positioned adjacent to body 810 to create inductive air passageways 840. Other examples can have one or more than two inductive air passageways. As the pressurized air flows out of outlets 870 of pressurized air passageway 820 (represented by arrows B), low pressure regions are created at outlets of inductive air passageways 840. These low pressure regions result in air being drawn (represented by arrows A) into inductive air passageways 840 and expelled from outlets 860. The pressurized air flowing from outlets 870 and the induced airflow from the inductive air passageway outlets mixes and is distributed into the occupied space. Such an induced airflow system can provide increased airflow economically and less obtrusively than a conventional fan. In addition, when the induced airflow is drawn from the occupied space, as in this example, increased circulation is achieved with a reduced fan requirement. This increased circulation provides additional

efficiency by mixing the pressurized air, which may be heated or cooled, with the air that is in the occupied space.

[0099] In this example, air moving system 800 acts as the structural support for panels 232. As shown in Fig. 13, body 810 includes brackets 812 to which panels 232 are attached. Other connection methods and shapes can also be used.

[00100] Fig. 14 shows an example of another type of ceiling system that can be improved by embodiments of the invention. Fig. 14 shows a baffle type ceiling system (similar to that shown in Fig. 10) that has a plurality of panels 240 extending vertically. Panels 240 separate a building space into an occupied space and a plenum space 30. Plenum space 30 is located between panels 240 and a structural slab 60. In this example, an air moving system 900 is attached to a bottom edge of one or more panels 240. Similarly to the other examples discussed, air moving system 900 has a pressurized air passageway inside a body. The pressurized air passageway is fed pressurized air from a remote fan or other air mover that can be located in the plenum space, or located outside of the plenum space and pushes air through ductwork that is located in the plenum space. In this example, the pressurized air can be routed through one or more supports (not shown). In this example, two air diverters are positioned adjacent to the body to create inductive air passageways. Other examples can have one or more than two inductive air passageways. As the pressurized air flows out of outlets of the pressurized air passageway, low pressure regions are created at outlets of the inductive air passageways. These low pressure regions result in air being drawn into the inductive air passageways and expelled from outlets of the inductive air passageways. The pressurized air flowing from the outlet of the pressurized air passageway and the induced airflow from the inductive air passageway outlets mixes and is distributed into the occupied space. Such an induced airflow system can provide increased airflow economically and less obtrusively than a conventional fan.

[00101] In this example, the induced airflow will tend to be drawn from the space between baffles 240. Although, some air induced air flow may be drawn from the occupied space. The composition of the induced airflow depends on the relative temperatures of the occupied space and the plenum space, the velocity of the air exiting air moving system 900, and the shape and size of the air diverters. The pressurized air can be fed to the pressurized air passageway by way of a conduit running in a baffle 240 or a conduit running between two baffles 240 that are attached to each other (as shown in Fig. 14). The number of air moving systems 900 used in a particular occupied space can be one or more. An air moving system

900 can be attached to every baffle, or can be attached to only certain baffles. Air moving system 900 can extend completely below the baffle, as shown in Fig. 14, or the baffle to which air moving system 900 is attached can be shortened so that the bottom of air moving system 900 is even with the bottoms of the baffles that do not have an air moving system. The position of air moving system 900 relative to the bottom of adjacent baffles will also influence from where the induced airflow will be drawn. All other things being equal, the more elevated the bottom of air moving system 900 is relative to the bottom of adjacent baffles, the more the induced air will be drawn from the plenum space.

[00102] Figs. 15 and 16 show an example of an air moving system 1200 that has an optionally oscillating induction fan 1240 mounted to a ceiling panel. Induction fan 1240 has a motor 1242 and is attached to the ceiling panel by way of a mount 1244. In particular embodiments, mount 1244 and/or motor 1242 cause induction fan 1240 to oscillate so that the air moved by air moving system 1200 passes through opening 1220 in the ceiling panel at different angles and therefore creates a simulation of a natural breeze on the occupants below. This arrangement draws an inductive airflow from the space above the ceiling panel (the plenum space) and mixes it with pressurized air. The pressurized air can be drawn from the plenum space or from a space outside of the plenum space. The pressurized air can be heated or cooled. The benefits discussed above from using induced airflow also apply to this embodiment.

[00103] Figs. 17 and 18 show an example of an air moving system 110 that has a fan that moves air over a phase change material to induce more thermal transfer to and/or from the phase change material. In this example, an induction fan 1140 has a motor 1142, and an outlet 1146 at its lower edge. A phase change material 1120 is attached to the upper side of a ceiling panel. Fan 1140 moves air over phase change material 1120 to promote increased thermal transfer. The ceiling panel can be any type of ceiling panel such as, for example, a canopy type, a cloud type, a drop in panel in a grid system, or other type of ceiling panel.

[00104] Fig. 17 shows an example where fan 1140 is separate from the ceiling panel whereas Fig. 18 shows an example where fan 1140 is attached to the ceiling panel by a mount 1144. In both examples, a space exists between outlet 1146 of fan 1140 and phase change material 1120.

[00105] Phase change material 1120 can be a material that changes from a solid to a liquid as it absorbs heat or a material that changes from a liquid to a gas as it absorbs heat.

An example of an appropriate phase change material is a salt hydrate phase change material composed of water mixed with calcium chloride and a nucleating agent. Any appropriate phase change material can be used.

[00106] Fig. 19 shows an example of an air moving system 1300 that is used with a radiant surface to promote thermal transfer to/from the radiant surface. In this example, radiant surface 70 has a plurality of conduits 74 that are embedded in the structure behind radiant surface 70. Conduits 74 can carry a liquid or a gas through the structure to heat or cool radiant surface 70. As stated above, a problem with radiant surfaces is that air flow is needed to transfer heat to/from the radiant surface. The embodiment shown in Fig. 19 provides air moving system 1300 to move air across radiant surface 70. Air moving system 1300 includes an air mover 1320 that is mounted in a ceiling panel 1310 (in this example, a canopy type panel). Air moving system 1300 draws air from plenum space 30 over radiant surface 70 and projects it down into occupied space 10 (represented by arrows C). In this example, air mover 1320 is an inductive air mover. Examples such as this provide increased thermal transfer to/from the radiant surface in an unobtrusive system that has no visible moving parts.

[00107] While the foregoing description and drawings represent exemplary embodiments of the present disclosure, it will be understood that various additions, modifications and substitutions may be made therein without departing from the spirit and scope and range of equivalents of the accompanying claims. In particular, it will be clear to those skilled in the art that the present invention may be embodied in other forms, structures, arrangements, proportions, sizes, and with other elements, materials, and components, without departing from the spirit or essential characteristics thereof. In addition, numerous variations in the methods/processes described herein may be made within the scope of the present disclosure. One skilled in the art will further appreciate that the embodiments may be used with many modifications of structure, arrangement, proportions, sizes, materials, and components and otherwise, used in the practice of the disclosure, which are particularly adapted to specific environments and operative requirements without departing from the principles described herein. The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive. The appended claims should be construed broadly, to include other variants and embodiments of the disclosure, which may be made by those skilled in the art without departing from the scope and range of equivalents.

In addition, all combinations of any and all of the features described in the disclosure, in any combination, are part of the invention.

CLAIMS

What is claimed is:

1. A ceiling system comprising:
 - a ceiling structure suspended within a space of a building thereby dividing the space into an occupied space below the ceiling structure and a plenum space above the ceiling structure;
 - a panel structure supported by the ceiling structure and having an opening;
 - a pressurized air passageway aligned with the opening, the pressurized air passageway having an outlet; and
 - an inductive air passageway adjacent the pressurized air passageway, the inductive air passageway having an inlet and an outlet,wherein the pressurized air passageway and the inductive air passageway are configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.
2. The ceiling system of claim 1, wherein the induced air flow is air from the plenum that flows through the inductive air passageway.
3. The ceiling system of any of the preceding claims, wherein the panel structure is an acoustical panel structure.
4. The ceiling system of any of the preceding claims, wherein the panel structure is a canopy-type panel structure that is configured such that the panel structure is spaced away from a wall of the occupied space.
5. The ceiling system of any of the preceding claims, wherein the outlet of the inductive air passageway directs the induced airflow toward the occupied space.
6. The ceiling system of any of the preceding claims, wherein the pressurized air and the induced air flow mix together at the outlet of the pressurized air passageway.

7. The ceiling system of any of the preceding claims, wherein the pressurized air passageway is fluidly connected to an air supply space other than the plenum space and draws the pressurized air from the air supply space.
8. The ceiling system of any of the preceding claims, wherein the pressurized air passageway is tubular.
9. The ceiling system of any of the preceding claims, wherein the pressurized air passageway includes a venturi.
10. The ceiling system of any of the preceding claims, wherein the outlet of the pressurized air passageway is a slot.
11. The ceiling system of any of the preceding claims, wherein the inductive air passageway is formed by an air diverter located near an outside surface of the pressurized air passageway.
12. The ceiling system of any of claims 1-10, wherein the inductive air passageway comprises two inductive air passageways, each of the inductive air passageways is formed by an air diverter located near an outside surface of the pressurized air passageway.
13. The ceiling system of claim 12, wherein the pressurized air passageway is located between the air diverters.
14. The ceiling system of any of the preceding claims, further comprising an air moving device that supplies pressurized air to the pressurized air passageway.
15. The ceiling system of any of the preceding claims, wherein the pressurized air passageway is ring shaped, and the outlet is a slot in the lower side of the ring shape.
16. The ceiling system of any of the preceding claims, wherein the pressurized air passageway and the inductive air passageway are located within a field area of the panel structure, the field area of the panel structure being an area away from all edges of the panel structure.

17. The ceiling system of any of the preceding claims, wherein the pressurized air passageway and the inductive air passageway are attached to an edge of the panel structure.
18. The ceiling system of any of the preceding claims, further comprising:
a plurality of the panel structure;
wherein the pressurized air passageway and the inductive air passageway are attached to an edge of one of the plurality of panel structures; and
the pressurized air passageway and the inductive air passageway are located between two adjacent ones of the plurality of panel structures.
19. The ceiling system of any of the preceding claims, further comprising a phase change material attached to, or integral with, the panel structure.
20. The ceiling system of any of the preceding claims, further comprising a water evaporation device, the water evaporation device being configured to present water to the pressurized air or the inductive air flow.
21. A method of moving air in an occupied space in a building, the method comprising:
dividing with a ceiling structure the space in the building into an occupied space below the ceiling structure and a plenum space above the ceiling structure;
providing an opening in a panel structure supported by the ceiling structure;
inducing an induced airflow out of an outlet of an inductive air passageway by passing pressurized air through an outlet of a pressurized air passageway, the inductive air passageway being adjacent the pressurized air passageway, and the pressurized air passageway being aligned with the opening in the panel structure; and
wherein the pressurized air passageway and the inductive air passageway are configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.
22. The method of claim 21, wherein the induced air flow is air from the plenum that flows through the inductive air passageway.
23. The method of any of claims 21-22, wherein the panel structure is an acoustical panel structure.

24. The method of any of claims 21-23, wherein the panel structure is a canopy-type panel structure that is configured such that the panel structure is spaced away from a wall of the occupied space.
25. The method of any of claims 21-24, wherein the induced airflow is directed toward the occupied space by the outlet of the inductive air passageway.
26. The method of any of claims 21-25, wherein the pressurized air and the induced air flow are mixed together at the outlet of the pressurized air passageway.
27. The method of any of claims 21-26, wherein the pressurized air passageway is fluidly connected to an air supply space other than the plenum space and the pressurized air is drawn from the air supply space.
28. The method of any of claims 21-27, wherein the pressurized air passageway is tubular.
29. The method of any of claims 21-28, wherein the pressurized air passageway includes a venturi.
30. The method of any of claims 21-29, wherein the outlet of the pressurized air passageway is a slot.
31. The method of any of claims 21-30, wherein the inductive air passageway is formed by an air diverter located near an outside surface of the pressurized air passageway.
32. The method of any of claims 21-31, wherein the inductive air passageway comprises two inductive air passageways, each of the inductive air passageways is formed by an air diverter located near an outside surface of the pressurized air passageway.
33. The method of claim 32, wherein the pressurized air passageway is located between the air diverters.

34. The method of any of claims 21-33, further comprising supplying pressurized air to the pressurized air passageway with an air moving device.

35. The method of any of claims 21-34, wherein the pressurized air passageway is ring shaped, and the outlet is a slot in the lower side of the ring shape.

36. The method of any of claims 21-35, wherein the pressurized air passageway and the inductive air passageway are located within a field area of the panel structure, the field area of the panel structure being an area away from all edges of the panel structure.

37. The method of any of claims 21-36, wherein the pressurized air passageway and the inductive air passageway are attached to an edge of the panel structure.

38. The method of any of claims 21-37, further comprising locating the pressurized air passageway and the inductive air passageway between two adjacent ones of a plurality of panel structures, and:

wherein the pressurized air passageway and the inductive air passageway are attached to an edge of one of the plurality of panel structures.

39. The method of any of claims 21-38, further comprising a phase change material attached to, or integral with, the panel structure.

40. The method of any of claims 21-39, further comprising presenting water to the pressurized air or the inductive air flow with a water evaporation device.

41. A ceiling system comprising:

a ceiling structure suspended within a space of a building thereby dividing the space into an occupied space below the ceiling structure and a plenum space above the ceiling structure;

a first panel structure supported by the ceiling structure and having an edge;

a pressurized air passageway attached to the edge of the first panel structure, the pressurized air passageway having an outlet;

an inductive air passageway adjacent the pressurized air passageway, the inductive air passageway being attached to the edge of the first panel structure and having an inlet and an outlet; and

wherein the pressurized air passageway and the inductive air passageway are configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow out of the outlet of the inductive air passageway.

42. The ceiling system of claim 41, wherein the induced air flow is air from the plenum that flows through the inductive air passageway.

43. The ceiling system of any of claims 41-42 any of the preceding claims, wherein the panel structure is an acoustical panel structure.

44. The ceiling system of any of claim 41-43, wherein the first panel structure is oriented in a baffle-style arrangement such that the edge of the first panel structure is a lowest edge of the first panel structure, and the inductive air passageway is located below the edge of the first panel structure.

45. The ceiling system of any of claims 41-44, further comprising a second panel structure supported by the ceiling structure.

46. The ceiling system of claim 45 further comprising:
wherein the second panel structure has a lower edge;
the first panel structure and the second panel structure are oriented in a baffle-style arrangement; and

the first panel structure and the second panel structure are attached to each other such that the inductive air passageway is attached to and is located below the lower edge of the first panel structure and the lower edge of the second panel structure.

47. The ceiling system of any of claims 41-46, further comprising a phase change material attached to, or integral with, the first panel structure.

48. The ceiling system of any of claims 41-47, further comprising a water evaporation device, the water evaporation device being configured to present water to the pressurized air or the inductive air flow.

49. A ceiling system comprising:

a ceiling structure suspended within a space of a building thereby dividing the space into an occupied space below the ceiling structure and a plenum space above the ceiling structure;

a panel structure supported by the ceiling structure and having an opening; and

a pressurized air passageway aligned with the opening, the pressurized air passageway having a venturi and an outlet;

wherein the pressurized air passageway is configured such that pressurized air passing through the outlet of the pressurized air passageway induces an induced air flow.

50. The ceiling system of claim 49, further comprising an inductive air passageway adjacent the pressurized air passageway, the inductive air passageway having an inlet and an outlet,

wherein the pressurized air passageway and the inductive air passageway are configured such that the pressurized air passing through the outlet of the pressurized air passageway induces the induced air flow out of the outlet of the inductive air passageway.

51. The ceiling system of any of claims 49-50, wherein the induced air flow is air from the plenum that flows through the inductive air passageway.

52. The ceiling system of any of claims 49-51, wherein the panel structure is an acoustical panel structure.

53. The ceiling system of any of claims 49-52, wherein the panel structure is a canopy-type panel structure that is configured such that the panel structure is spaced away from a wall of the occupied space.

54. The ceiling system of any of claims 49-53, wherein the outlet of the inductive air passageway directs the induced airflow toward the occupied space.

55. The ceiling system of any of claims 49-54, wherein the pressurized air and the induced air flow mix together at the outlet of the pressurized air passageway.

56. The ceiling system of any of claims 49-55, wherein the pressurized air passageway is fluidly connected to an air supply space other than the plenum space and draws the pressurized air from the air supply space.

57. The ceiling system of any of claims 49-56, wherein the pressurized air passageway is tubular.

58. The ceiling system of any of claims 49-57, wherein the outlet of the pressurized air passageway is a slot.

59. The ceiling system of any of claims 49-58, wherein the inductive air passageway is formed by an air diverter located near an outside surface of the pressurized air passageway.

60. The ceiling system of any of claims 50-58, wherein the inductive air passageway comprises two inductive air passageways, each of the inductive air passageways is formed by an air diverter located near an outside surface of the pressurized air passageway.

61. The ceiling system of claim 60, wherein the pressurized air passageway is located between the air diverters.

62. The ceiling system of any of claims 49-61, further comprising an air moving device that supplies pressurized air to the pressurized air passageway.

63. The ceiling system of any of claims 49-62, wherein the pressurized air passageway is ring shaped, and the outlet is a slot in the lower side of the ring shape.

64. The ceiling system of any of claims 49-63, wherein the pressurized air passageway and the inductive air passageway are located within a field area of the panel structure, the field area of the panel structure being an area away from all edges of the panel structure.

65. The ceiling system of any of claims 49-64, wherein the pressurized air passageway and the inductive air passageway are attached to an edge of the panel structure.

1/15




FIG. 1

2/15




FIG. 2

3/15




FIG. 3




FIG. 4

4/15




FIG. 5




FIG. 6

5/15




FIG. 7




FIG. 8




FIG. 9

8/15




FIG. 10

9/15




FIG. 11




FIG. 12

11/15




FIG. 13

12/15




FIG. 14

13/15




FIG. 15




FIG. 16

14/15




FIG. 17




FIG. 18

15/15




FIG. 19

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2017/051571**A. CLASSIFICATION OF SUBJECT MATTER****F24F 13/068(2006.01)i, F24F 13/075(2006.01)i, F24F 13/08(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

F24F 13/068; F24F 1/00; F24F 7/007; F28F 27/02; A61L 9/20; F24F 13/00; F24F 1/02; F24F 13/06; F24F 13/08; F24F 13/075

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords: building, ceiling system, HVAC, air diverter, air passageway, panel, flow velocity, induced air, vane and chilled beam

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2014-0318733 A1 (OY HALTON GROUP LTD.) 30 October 2014 See paragraphs [0030]–[0031], [0066] and figures 1, 9A–9C.	1–3, 21–23, 41–43 , 49–51
Y	JP 3554180 B2 (DAIKIN IND., LTD.) 18 August 2004 See paragraphs [0034]–[0038] and figures 1–4.	1–3, 21–23, 41–43 , 49–51
A	US 2013-0291735 A1 (LIVCHAK et al.) 07 November 2013 See paragraphs [0092]–[0094] and figures 12A–12B.	1–3, 21–23, 41–43 , 49–51
A	US 2015-0176851 A1 (AIRIUS IP HOLDINGS, L.L.C.) 25 June 2015 See paragraphs [0044]–[0048] and figures 1–5, 9–10.	1–3, 21–23, 41–43 , 49–51
A	KR 10-0772216 B1 (LG ELECTRONICS INC.) 01 November 2007 See paragraphs [0025]–[0043] and figures 1–5.	1–3, 21–23, 41–43 , 49–51



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

20 December 2017 (20.12.2017)

Date of mailing of the international search report

20 December 2017 (20.12.2017)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea

Facsimile No. +82-42-481-8578

Authorized officer

LEE, Dal Kyong

Telephone No. +82-42-481-8440



INTERNATIONAL SEARCH REPORTInternational application No.
PCT/US2017/051571**Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)**

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 13, 33, 46, 61
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
Claims 13, 33, 46 and 61 are regarded unclear since they refer to multiple dependent claims which do not comply with PCT Rule 6.4(a). Hence, claims 13, 33, 46 and 61 do not meet the requirements of PCT Article 6.
3. ☒ Claims Nos.: 4-12, 14-20, 24-32, 34-40, 44-45, 47-48, 52-60, 62-65
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of any additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/051571

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2014-0318733 A1	30/10/2014	AU 2011-207455 A1 AU 2016-201936 A1 CA 2787151 A1 CN 102792118 A CN 102792118 B EP 2526362 A1 EP 2526362 B1 EP 3196578 A1 HK 1175231 A1 JP 2013-518235 A JP 5863671 B2 MX 2012008519 A RU 2012135066 A RU 2583771 C2 SG 10201500549 A SG 182507 A1 US 2012-0295532 A1 US 9726442 B2 WO 2011-091380 A1	30/08/2012 21/04/2016 28/07/2011 21/11/2012 25/11/2015 28/11/2012 12/04/2017 26/07/2017 06/01/2017 20/05/2013 17/02/2016 31/08/2012 27/02/2014 10/05/2016 30/03/2015 30/08/2012 22/11/2012 08/08/2017 28/07/2011
JP 3554180 B2	18/08/2004	CN 1243934 C CN 1296561 A EP 1069381 A1 JP 11-281108 A JP 2000-130807 A JP 2000-130808 A JP 3680643 B2 KR 10-0392302 B1 KR 10-0423116 B1 US 6551185 B1 WO 99-050603 A1	01/03/2006 23/05/2001 17/01/2001 15/10/1999 12/05/2000 12/05/2000 10/08/2005 22/07/2003 18/03/2004 22/04/2003 07/10/1999
US 2013-0291735 A1	07/11/2013	CA 2818444 A1 CA 2818444 C CN 103347544 A CN 103347544 B EP 2640428 A1 EP 2640428 B1 MX 2013005526 A US 2016-0303271 A1 US 9393338 B2 WO 2012-068569 A1	24/05/2012 17/05/2016 09/10/2013 13/01/2016 25/09/2013 11/01/2017 17/07/2013 20/10/2016 19/07/2016 24/05/2012
US 2015-0176851 A1	25/06/2015	CA 2875347 A1 US 9702576 B2	19/06/2015 11/07/2017
KR 10-0772216 B1	01/11/2007	KR 10-2007-0050563 A	16/05/2007